

# ltluatex.dtx

## (LuaT<sub>E</sub>X-specific support)

David Carlisle and Joseph Wright\*

2023/08/03

## Contents

<b>1 Overview</b>	<b>2</b>
<b>2 Core T<sub>E</sub>X functionality</b>	<b>2</b>
<b>3 Plain T<sub>E</sub>X interface</b>	<b>3</b>
<b>4 Lua functionality</b>	<b>3</b>
4.1 Allocators in Lua . . . . .	3
4.2 Lua access to T <sub>E</sub> X register numbers . . . . .	4
4.3 Module utilities . . . . .	5
4.4 Callback management . . . . .	5
<b>5 Implementation</b>	<b>6</b>
5.1 Minimum LuaT <sub>E</sub> X version . . . . .	6
5.2 Older L <sup>A</sup> T <sub>E</sub> X/Plain T <sub>E</sub> X setup . . . . .	7
5.3 Attributes . . . . .	9
5.4 Category code tables . . . . .	9
5.5 Named Lua functions . . . . .	11
5.6 Custom whatsits . . . . .	11
5.7 Lua bytecode registers . . . . .	11
5.8 Lua chunk registers . . . . .	12
5.9 Lua loader . . . . .	12
5.10 Lua module preliminaries . . . . .	14
5.11 Lua module utilities . . . . .	14
5.12 Accessing register numbers from Lua . . . . .	16
5.13 Attribute allocation . . . . .	17
5.14 Custom whatsit allocation . . . . .	17
5.15 Bytecode register allocation . . . . .	18
5.16 Lua chunk name allocation . . . . .	18
5.17 Lua function allocation . . . . .	18
5.18 Lua callback management . . . . .	19

---

\*Significant portions of the code here are adapted/simplified from the packages `luatex` and `luatexbase` written by Heiko Oberdiek, Élie Roux, Manuel Pégourié-Gonnar and Philipp Gesang.

## 1 Overview

LuaTeX adds a number of engine-specific functions to TeX. Several of these require set up that is best done in the kernel or need related support functions. This file provides *basic* support for LuaTeX at the  $\text{\LaTeX} 2\epsilon$  kernel level plus as a loadable file which can be used with plain TeX and  $\text{\LaTeX}$ .

This file contains code for both TeX (to be stored as part of the format) and Lua (to be loaded at the start of each job). In the Lua code, the kernel uses the namespace `luatexbase`.

The following \count registers are used here for register allocation:

```
\e@alloc@attribute@count Attributes (default 258)
\e@alloc@ccodetable@count Category code tables (default 259)
\e@alloc@luafunction@count Lua functions (default 260)
  \e@alloc@whatsit@count User whatsits (default 261)
  \e@alloc@bytecode@count Lua bytecodes (default 262)
  \e@alloc@luachunk@count Lua chunks (default 263)
```

(\count 256 is used for \newmarks allocation and \count 257 is used for \newXeTeXintercharclass with XeTeX, with code defined in `ltfinal.dtx`). With any  $\text{\LaTeX} 2\epsilon$  kernel from 2015 onward these registers are part of the block in the extended area reserved by the kernel (prior to 2015 the  $\text{\LaTeX} 2\epsilon$  kernel did not provide any functionality for the extended allocation area).

## 2 Core TeX functionality

The commands defined here are defined for possible inclusion in a future  $\text{\LaTeX}$  format, however also extracted to the file `ltluatex.tex` which may be used with older  $\text{\LaTeX}$  formats, and with plain TeX.

```
\newattribute \newattribute{\langle attribute\rangle}
  Defines a named \attribute, indexed from 1 (i.e. \attribute0 is never defined).
  Attributes initially have the marker value -"7FFFFFFF ('unset') set by the engine.

\newcatcodetable \newcatcodetable{\langle catcodetable\rangle}
  Defines a named \catcodetable, indexed from 1 (\catcodetable0 is never assigned).
  A new catcode table will be populated with exactly those values assigned
  by IniTeX (as described in the LuaTeX manual).

\newluafunction \newluafunction{\langle function\rangle}
  Defines a named \luafunction, indexed from 1. (Lua indexes tables from 1 so
  \luafunction0 is not available).

\newluacmd \newluadef{\langle function\rangle}
  Like \newluafunction, but defines the command using \luadef instead of just
  assigning an integer.

\newprotectedluacmd \newluadef{\langle function\rangle}
  Like \newluacmd, but the defined command is not expandable.

\newwhatsit \newwhatsit{\langle whatsit\rangle}
  Defines a custom \whatsit, indexed from 1.

\newluabytecode \newluabytecode{\langle bytecode\rangle}
```

Allocates a number for Lua bytecode register, indexed from 1.

```
\newluachunkname newluachunkname{\langle chunkname\rangle}
```

Allocates a number for Lua chunk register, indexed from 1. Also enters the name of the register (without backslash) into the `lua.name` table to be used in stack traces.

```
\catcodetable@initex Predefined category code tables with the obvious assignments. Note that the \catcodetable@string latex and atletter tables set the full Unicode range to the codes predefined by \catcodetable@latex the kernel.
```

```
\catcodetable@atletter \setattribute{\langle attribute\rangle}{\langle value\rangle}
```

```
\setattribute \unsetattribute{\langle attribute\rangle}
```

```
\unsetattribute Set and unset attributes in a manner analogous to \setlength. Note that attributes take a marker value when unset so this operation is distinct from setting the value to zero.
```

### 3 Plain $\text{\TeX}$ interface

The `ltluatex` interface may be used with plain  $\text{\TeX}$  using `\input{ltluatex}`. This inputs `ltluatex.tex` which inputs `etex.src` (or `etex.sty` if used with  $\text{\LaTeX}$ ) if it is not already input, and then defines some internal commands to allow the `ltluatex` interface to be defined.

The `luatexbase` package interface may also be used in plain  $\text{\TeX}$ , as before, by inputting the package `\input luatexbase.sty`. The new version of `luatexbase` is based on this `ltluatex` code but implements a compatibility layer providing the interface of the original package.

## 4 Lua functionality

### 4.1 Allocators in Lua

```
new_attribute luatexbase.new_attribute(\langle attribute\rangle)
```

Returns an allocation number for the `\langle attribute\rangle`, indexed from 1. The attribute will be initialised with the marker value `-"7FFFFFFF` ('unset'). The attribute allocation sequence is shared with the  $\text{\TeX}$  code but this function does *not* define a token using `\attributedef`. The attribute name is recorded in the `attributes` table. A metatable is provided so that the table syntax can be used consistently for attributes declared in  $\text{\TeX}$  or Lua.

```
new_whatsit luatexbase.new_whatsit(\langle whatsit\rangle)
```

Returns an allocation number for the custom `\langle whatsit\rangle`, indexed from 1.

```
new_bytecode luatexbase.new_bytecode(\langle bytecode\rangle)
```

Returns an allocation number for a bytecode register, indexed from 1. The optional `\langle name\rangle` argument is just used for logging.

```
new_chunkname luatexbase.new_chunkname(\langle chunkname\rangle)
```

Returns an allocation number for a Lua chunk name for use with `\directlua` and `\latelua`, indexed from 1. The number is returned and also `\langle name\rangle` argument is added to the `lua.name` array at that index.

```
new_luafunction luatexbase.new_luafunction(\langle functionname\rangle)
```

Returns an allocation number for a lua function for use with `\luafunction`, `\lateluafunction`, and `\luadef`, indexed from 1. The optional `\langle functionname\rangle` argument is just used for logging.

These functions all require access to a named  $\text{\TeX}$  count register to manage their allocations. The standard names are those defined above for access from  $\text{\TeX}$ , e.g. “e@alloc@attribute@count, but these can be adjusted by defining the variable  $\langle type \rangle\_count\_name$  before loading `ltluatex.lua`, for example

```
local attribute_count_name = "attributetracker"
require("ltluatex")
```

would use a  $\text{\TeX}$  `\count` (`\countdef`'d token) called `attributetracker` in place of “e@alloc@attribute@count.

## 4.2 Lua access to $\text{\TeX}$ register numbers

`registernumber luatexbase.registernumer(<name>)`

Sometimes (notably in the case of Lua attributes) it is necessary to access a register *by number* that has been allocated by  $\text{\TeX}$ . This package provides a function to look up the relevant number using  $\text{Lua}\text{\TeX}$ 's internal tables. After for example `\newattribute\myattrib`, `\myattrib` would be defined by (say) `\myattrib=\attribute15`. `luatexbase.registernumer("myattrib")` would then return the register number, 15 in this case. If the string passed as argument does not correspond to a token defined by `\attributedef`, `\countdef` or similar commands, the Lua value `false` is returned.

As an example, consider the input:

```
\newcommand\test[1]{%
\typeout{#1: \expandafter\meaning\csname#1\endcsname^^J
\space\space\space\space
\directlua{tex.write(luatexbase.registernumer("#1") or "bad input")}%
}

\test{undefinedrubbish}

\test{space}

\test{hbox}

\test{@MM}

\test{@tempdima}
\test{@tempdimb}

\test{strutbox}

\test{sixt@0n}

\attributedef\myattr=12
\myattr=200
\test{myattr}
```

If the demonstration code is processed with  $\text{Lua}\text{\TeX}$  then the following would be produced in the log and terminal output.

```
undefinedrubbish: \relax
```

```

    bad input
space: macro:->
    bad input
hbox: \hbox
    bad input
@MM: \mathchar"4E20
20000
@tempdima: \dimen14
14
@tempdimb: \dimen15
15
strutbox: \char"B
11
sixt@n: \char"10
16
myattr: \attribute12
12

```

Notice how undefined commands, or commands unrelated to registers do not produce an error, just return `false` and so print `bad input` here. Note also that commands defined by `\newbox` work and return the number of the box register even though the actual command holding this number is a `\chardef` defined token (there is no `\boxdef`).

### 4.3 Module utilities

`provides_module luatexbase.provides_module(<info>)`

This function is used by modules to identify themselves; the `info` should be a table containing information about the module. The required field `name` must contain the name of the module. It is recommended to provide a field `date` in the usual L<sup>A</sup>T<sub>E</sub>X format `yyyy/mm/dd`. Optional fields `version` (a string) and `description` may be used if present. This information will be recorded in the log. Other fields are ignored.

```

module_info luatexbase.module_info(<module>, <text>)
module_warning luatexbase.module_warning(<module>, <text>)
module_error luatexbase.module_error(<module>, <text>)

```

These functions are similar to L<sup>A</sup>T<sub>E</sub>X's `\PackageError`, `\PackageWarning` and `\PackageInfo` in the way they format the output. No automatic line breaking is done, you may still use `\n` as usual for that, and the name of the package will be prepended to each output line.

Note that `luatexbase.module_error` raises an actual Lua error with `error()`, which currently means a call stack will be dumped. While this may not look pretty, at least it provides useful information for tracking the error down.

### 4.4 Callback management

`add_to_callback luatexbase.add_to_callback(<callback>, <function>, <description>)` Registers the `<function>` into the `<callback>` with a textual `<description>` of the function. Functions are inserted into the callback in the order loaded.

`remove_from_callback luatexbase.remove_from_callback(<callback>, <description>)` Removes the callback function with `<description>` from the `<callback>`. The removed function and its description are returned as the results of this function.

`in_callback luatexbase.in_callback(<callback>, <description>)` Checks if the `<description>` matches one of the functions added to the list for the `<callback>`, returning a boolean value.

`disable_callback luatexbase.disable_callback(<callback>)` Sets the `<callback>` to `false` as described in the LuaTeX manual for the underlying `callback.register` built-in. Callbacks will only be set to false (and thus be skipped entirely) if there are no functions registered using the callback.

`callback_descriptions` A list of the descriptions of functions registered to the specified callback is returned. `{}` is returned if there are no functions registered.

`create_callback luatexbase.create_callback(<name>,<type>,<default>)` Defines a user defined callback. The last argument is a default function or `false`.

`call_callback luatexbase.call_callback(<name>,...)` Calls a user defined callback with the supplied arguments.

`declare_callback_rule luatexbase.declare_callback_rule(<name>, <first>, <relation>, <second>)` Adds an ordering constraint between two callback functions for callback `<name>`.

The kind of constraint added depends on `<relation>`:

**before** The callback function with description `<first>` will be executed before the function with description `<second>`.

**after** The callback function with description `<first>` will be executed after the function with description `<second>`.

**incompatible-warning** When both a callback function with description `<first>` and with description `<second>` is registered, then a warning is printed when the callback is executed.

**incompatible-error** When both a callback function with description `<first>` and with description `<second>` is registered, then an error is printed when the callback is executed.

**unrelated** Any previously declared callback rule between `<first>` and `<second>` gets disabled.

Every call to `declare_callback_rule` with a specific callback `<name>` and descriptions `<first>` and `<second>` overwrites all previous calls with same callback and descriptions.

The callback functions do not have to be registered yet when the functions is called. Only the constraints for which both callback descriptions refer to callbacks registered at the time the callback is called will have an effect.

## 5 Implementation

```
1 {*2ekernel | tex | latexrelease}
2 {2ekernel | latexrelease}\ifx\directlua\@undefined\else
```

### 5.1 Minimum LuaTeX version

LuaTeX has changed a lot over time. In the kernel support for ancient versions is not provided: trying to build a format with a very old binary therefore gives some information in the log and loading stops. The cut-off selected here relates to the

tree-searching behaviour of `require()`: from version 0.60, LuaTeX will correctly find Lua files in the `texmf` tree without ‘help’.

```

3 <latexrelease> \IncludeInRelease{2015/10/01}
4 <latexrelease>           {\newluafunction}{LuaTeX}%
5 \ifnum\lualatexversion<60 %
6   \wlog{*****}
7   \wlog{* LuaTeX version too old for ltluatex support *}
8   \wlog{*****}
9   \expandafter\endinput
10 \fi

```

Two simple L<sup>A</sup>T<sub>E</sub>X macros from `ltdefns.dtx` have to be defined here because `ltdefns.dtx` is not loaded yet when `ltluatex.dtx` is executed.

```

11 \long\def\@gobble#1{}
12 \long\def\@firstofone#1{#1}

```

## 5.2 Older L<sup>A</sup>T<sub>E</sub>X/Plain T<sub>E</sub>X setup

```
13 <*tex>
```

Older L<sup>A</sup>T<sub>E</sub>X formats don’t have the primitives with ‘native’ names: sort that out. If they already exist this will still be safe.

```

14 \directlua{tex.enableprimitives("",tex.extraprimitives("luatex"))}
15 \ifx\et@alloc\@undefined
    In pre-2014 LATEX, or plain TEX, load etex.{sty,src}.
16   \ifx\documentclass\@undefined
17     \ifx\loccount\@undefined
18       \input{etex.src}%
19     \fi
20     \catcode`\@=11 %
21     \outer\expandafter\def\csname newfam\endcsname
22                           {\alloc@8\fam\chardef\et@xmaxfam}
23   \else
24     \RequirePackage{etex}
25     \expandafter\def\csname newfam\endcsname
26                           {\alloc@8\fam\chardef\et@xmaxfam}
27     \expandafter\let\expandafter\new@mathgroup\csname newfam\endcsname
28   \fi

```

### 5.2.1 Fixes to `etex.src/etex.sty`

These could and probably should be made directly in an update to `etex.src` which already has some LuaTeX-specific code, but does not define the correct range for LuaTeX.

2015-07-13 higher range in luatex.

```

29 \edef \et@xmaxregs {\ifx\directlua\@undefined 32768\else 65536\fi}
luatex/xetex also allow more math fam.
30 \edef \et@xmaxfam {\ifx\Umathcode\@undefined\sixt@@n\else\@ccclvi\fi}
31 \count 270=\et@xmaxregs % locally allocates \count registers
32 \count 271=\et@xmaxregs % ditto for \dimen registers
33 \count 272=\et@xmaxregs % ditto for \skip registers
34 \count 273=\et@xmaxregs % ditto for \muskip registers
35 \count 274=\et@xmaxregs % ditto for \box registers

```

```

36 \count 275=\et@xmaxregs % ditto for \toks registers
37 \count 276=\et@xmaxregs % ditto for \marks classes
    and 256 or 16 fam. (Done above due to plain/LATEX differences in lluatex.)
38 % \outer\def\newfam{\alloc@8\fam\chardef\et@xmaxfam}
    End of proposed changes to etex.src

```

### 5.2.2 luatex specific settings

Switch to global cf luatex.sty to leave room for inserts not really needed for luatex but possibly most compatible with existing use.

```

39 \expandafter\let\csname newcount\expandafter\expandafter\endcsname
40           \csname globcount\endcsname
41 \expandafter\let\csname newdimen\expandafter\expandafter\endcsname
42           \csname globdimen\endcsname
43 \expandafter\let\csname newskip\expandafter\expandafter\endcsname
44           \csname globskip\endcsname
45 \expandafter\let\csname newbox\expandafter\expandafter\endcsname
46           \csname globbox\endcsname

```

Define \e@alloc as in latex (the existing macros in etex.src hard to extend to further register types as they assume specific 26x and 27x count range. For compatibility the existing register allocation is not changed.

```

47 \chardef\@alloc@top=65535
48 \let\@alloc\chardef\chardef
49 \def\@alloc#1#2#3#4#5#6{%
50   \global\advance#3\@ne
51   \e@ch@ck{#3}{#4}{#5}{#1%
52   \allocationnumber#3\relax
53   \global#2#6\allocationnumber
54   \wlog{\string#6=\string#1\the\allocationnumber}}%
55 \gdef\@ch@ck#1#2#3#4{%
56   \ifnum#1<#2\else
57     \ifnum#1=#2\relax
58       #1@cclvi
59       \ifx\count#4\advance#1 10 \fi
60     \fi
61     \ifnum#1<#3\relax
62     \else
63       \errmessage{No room for a new \string#4}%
64     \fi
65   \fi}%

```

Fix up allocations not to clash with etex.src.

```

66 \expandafter\csname newcount\endcsname\@alloc@attribute@count
67 \expandafter\csname newcount\endcsname\@alloc@ccodetable@count
68 \expandafter\csname newcount\endcsname\@alloc@luafunction@count
69 \expandafter\csname newcount\endcsname\@alloc@whatsit@count
70 \expandafter\csname newcount\endcsname\@alloc@bytecode@count
71 \expandafter\csname newcount\endcsname\@alloc@luachunk@count

```

End of conditional setup for plain T<sub>E</sub>X / old L<sup>A</sup>T<sub>E</sub>X.

```

72 \fi
73 
```

### 5.3 Attributes

`\newattribute` As is generally the case for the LuaTeX registers we start here from 1. Notably, some code assumes that `\attribute0` is never used so this is important in this case.

```
74 \ifx\@alloc@attribute@count\@undefined
75   \countdef\@alloc@attribute@count=258
76   \e@alloc@attribute@count=\z@
77 \fi
78 \def\newattribute#1{%
79   \e@alloc\attribute\attributedef
80   \e@alloc@attribute@count\m@ne\@alloc@top#1%
81 }
```

`\setattribute` Handy utilities.

```
82 \def\setattribute#1{\#1=\numexpr#2\relax}
83 \def\unsetattribute#1{\#1=-"7FFFFFFF\relax}
```

### 5.4 Category code tables

`\newcatcodetable` Category code tables are allocated with a limit half of that used by LuaTeX for everything else. At the end of allocation there needs to be an initialization step. Table 0 is already taken (it's the global one for current use) so the allocation starts at 1.

```
84 \ifx\@alloc@ccodetable@count\@undefined
85   \countdef\@alloc@ccodetable@count=259
86   \e@alloc@ccodetable@count=\z@
87 \fi
88 \def\newcatcodetable#1{%
89   \e@alloc\catcodetable\chardef
90   \e@alloc@ccodetable@count\m@ne{"8000}#1%
91   \initcatcodetable\allocationnumber
92 }
```

`\catcodetable@initex` Save a small set of standard tables. The Unicode data is read here in using a parser `\catcodetable@string` simplified from that in `load-unicode-data`: only the nature of letters needs to `\catcodetable@latec` be detected.

```
93 \newcatcodetable\catcodetable@initex
94 \newcatcodetable\catcodetable@string
95 \begingroup
96 \def\setstrangeccode#1#2#3{%
97   \ifnum#1>#2 %
98     \expandafter\@gobble
99   \else
100     \expandafter\@firstofone
101   \fi
102   {%
103     \catcode#1=#3 %
104     \expandafter\setstrangeccode\expandafter
105     {\number\numexpr#1 + 1\relax}{#2}{#3}
106   }%
107 }
108 \@firstofone{%
```

```

109   \catcodetable\catcodetable@initex
110     \catcode0=12 %
111     \catcode13=12 %
112     \catcode37=12 %
113     \setrangingcatcode{65}{90}{12}%
114     \setrangingcatcode{97}{122}{12}%
115     \catcode92=12 %
116     \catcode127=12 %
117     \savecatcodetable\catcodetable@string
118   \endgroup
119 }
120 \newcatcodetable\catcodetable@latex
121 \newcatcodetable\catcodetable@atletter
122 \begingroup
123   \def\parseunicodedataI#1;#2;#3;#4\relax{%
124     \parseunicodedataII#1;#3;#2 First>\relax
125   }%
126   \def\parseunicodedataII#1;#2;#3 First>#4\relax{%
127     \ifx\relax#4\relax
128       \expandafter\parseunicodedataIII
129     \else
130       \expandafter\parseunicodedataIV
131     \fi
132     {#1}#2\relax%
133   }%
134   \def\parseunicodedataIII#1#2#3\relax{%
135     \ifnum 0%
136       \if L#21\fi
137       \if M#21\fi
138       >0 %
139       \catcode"#1=11 %
140     \fi
141   }%
142   \def\parseunicodedataIV#1#2#3\relax{%
143     \readunicoderead to \unicodedataline
144     \if L#2%
145       \count0="#1 %
146       \expandafter\parseunicodedataV\unicodedataline\relax
147     \fi
148   }%
149   \def\parseunicodedataV#1;#2\relax{%
150     \loop
151       \unless\ifnum\count0>"#1 %
152         \catcode\count0=11 %
153         \advance\count0 by 1 %
154       \repeat
155   }%
156   \def\storedpar{\par}%
157   \chardef\unicoderead=\numexpr\count16 + 1\relax
158   \openin\unicoderead=UnicodeData.txt %
159   \loop\unless\ifeof\unicoderead %
160     \read\unicoderead to \unicodedataline
161     \unless\ifx\unicodedataline\storedpar
162       \expandafter\parseunicodedataI\unicodedataline\relax

```

```

163     \fi
164     \repeat
165     \closein\unicoderead
166     \@firstofone{%
167         \catcode64=12 %
168         \savecatcodetable\catcodetable@lateX
169         \catcode64=11 %
170         \savecatcodetable\catcodetable@atletter
171     }
172 \endgroup

```

## 5.5 Named Lua functions

`\newluafunction` Much the same story for allocating LuaTeX functions except here they are just numbers so they are allocated in the same way as boxes. Lua indexes from 1 so once again slot 0 is skipped.

```

173 \ifx\@alloc@luafunction@count\@undefined
174   \countdef\@alloc@luafunction@count=260
175   \@alloc@luafunction@count=\z@
176 \fi
177 \def\newluafunction{%
178   \@alloc@luafunction\@alloc@chardef
179   \@alloc@luafunction@count\m@ne\@alloc@top
180 }

```

`\newluacmd` Additionally two variants are provided to make the passed control sequence call `\newprotectedluacmd` the function directly.

```

181 \def\newluacmd{%
182   \@alloc@luafunction\luadef
183   \@alloc@luafunction@count\m@ne\@alloc@top
184 }
185 \def\newprotectedluacmd{%
186   \@alloc@luafunction{\protected\luadef}
187   \@alloc@luafunction@count\m@ne\@alloc@top
188 }

```

## 5.6 Custom whatsits

`\newwhatsit` These are only settable from Lua but for consistency are definable here.

```

189 \ifx\@alloc@whatsit@count\@undefined
190   \countdef\@alloc@whatsit@count=261
191   \@alloc@whatsit@count=\z@
192 \fi
193 \def\newwhatsit#1{%
194   \@alloc@whatsit\@alloc@chardef
195   \@alloc@whatsit@count\m@ne\@alloc@top#1%
196 }

```

## 5.7 Lua bytecode registers

`\newluabytocode` These are only settable from Lua but for consistency are definable here.

```

197 \ifx\@alloc@bytocode@count\@undefined

```

```

198 \countdef{e@alloc@bytecode@count=262
199   e@alloc@bytecode@count=\z@
200 \fi
201 \def\newluabytecode#1{%
202   e@alloc@luabytecode{e@alloc@chardef
203     e@alloc@bytecode@count\m@ne{e@alloc@top#1}%
204 }

```

## 5.8 Lua chunk registers

`\newluachunkname` As for bytecode registers, but in addition we need to add a string to the `lua.name` table to use in stack tracing. We use the name of the command passed to the allocator, with no backslash.

```

205 \ifx{e@alloc@luachunk@count}\undefined
206   \countdef{e@alloc@luachunk@count=263
207   e@alloc@luachunk@count=\z@
208 \fi
209 \def\newluachunkname#1{%
210   e@alloc@luachunk{e@alloc@chardef
211     e@alloc@luachunk@count\m@ne{e@alloc@top#1}%
212     {\escapechar\m@ne
213     \directlua{lua.name[\the\allocationnumber]="\string#1"}%}
214 }

```

## 5.9 Lua loader

Lua code loaded in the format often has to be loaded again at the beginning of every job, so we define a helper which allows us to avoid duplicated code:

```

215 \def\now@and@everyjob#1{%
216   \everyjob\expandafter{\the\everyjob
217     #1%
218   }%
219   #1%
220 }

```

Load the Lua code at the start of every job. For the conversion of `TEX` into numbers at the Lua side we need some known registers: for convenience we use a set of systematic names, which means using a group around the Lua loader.

```

221 <2ekernel> \now@and@everyjob{%
222   \begingroup
223     \attributedef{attributezero=0 %
224     \chardef\charzero=0 %

```

Note name change required on older luatex, for hash table access.

```

225     \countdef\CountZero=0 %
226     \dimendef\dimenzero=0 %
227     \mathchardef\mathcharzero=0 %
228     \muskipdef\muskipzero=0 %
229     \skipdef\skipzero=0 %
230     \toksdef\tokszero=0 %
231     \directlua{require("ltluatex")}
232   \endgroup
233 <2ekernel>
234 <latexrelease> \EndIncludeInRelease

```

```

235 <|latexrelease> \IncludeInRelease{0000/00/00}
236 <|latexrelease>                                {\newluafunction}{LuaTeX}%
237 <|latexrelease> \let\@alloc@attribute@count\@undefined
238 <|latexrelease> \let\newattribute\@undefined
239 <|latexrelease> \let\setattribute\@undefined
240 <|latexrelease> \let\unsetattribute\@undefined
241 <|latexrelease> \let\@alloc@ccodetable@count\@undefined
242 <|latexrelease> \let\newcatcodetable\@undefined
243 <|latexrelease> \let\catcodetable@initex\@undefined
244 <|latexrelease> \let\catcodetable@string\@undefined
245 <|latexrelease> \let\catcodetable@latex\@undefined
246 <|latexrelease> \let\catcodetable@atletter\@undefined
247 <|latexrelease> \let\@alloc@luafunction@count\@undefined
248 <|latexrelease> \let\newluafunction\@undefined
249 <|latexrelease> \let\@alloc@luafunction@count\@undefined
250 <|latexrelease> \let\newwhatsit\@undefined
251 <|latexrelease> \let\@alloc@whatsit@count\@undefined
252 <|latexrelease> \let\newluabytecode\@undefined
253 <|latexrelease> \let\@alloc@bytecode@count\@undefined
254 <|latexrelease> \let\newluachunkname\@undefined
255 <|latexrelease> \let\@alloc@luachunk@count\@undefined
256 <|latexrelease> \directlua{\luatexbase.uninstall()}
257 <|latexrelease> \EndIncludeInRelease

    In \everyjob, if luatfload is available, load it and switch to TU.

258 <|latexrelease> \IncludeInRelease{2017/01/01}%
259 <|latexrelease>                                {\fontencoding}{TU in everyjob}%
260 <|latexrelease> \fontencoding{TU}\let\encodingdefault\f@encoding
261 <|latexrelease> \ifx\directlua\@undefined\else
262 <|2ekernel> \everyjob\expandafter{%
263 <|2ekernel>   \the\everyjob
264 <|*2ekernel, latexrelease>
265   \directlua{%
266     if xpcall(function ()%
267       require('luatfload-main')%
268       end, texio.write_nl) then %
269     local _void = luatfload.main ()%
270   else %
271     texio.write_nl('Error in luatfload: reverting to OT1')%
272     tex.print('\string\\def\string\\\encodingdefault{OT1}')%
273   end %
274   }%
275   \let\f@encoding\encodingdefault
276   \expandafter\let\csname ver@luatfload.sty\endcsname\fmtversion
277 <|/2ekernel, latexrelease>
278 <|latexrelease> \fi
279 <|2ekernel> }
280 <|latexrelease> \EndIncludeInRelease
281 <|latexrelease> \IncludeInRelease{0000/00/00}%
282 <|latexrelease>                                {\fontencoding}{TU in everyjob}%
283 <|latexrelease> \fontencoding{OT1}\let\encodingdefault\f@encoding
284 <|latexrelease> \EndIncludeInRelease

285 <|2ekernel | latexrelease> \fi
286 <|/2ekernel | tex | latexrelease>

```

## 5.10 Lua module preliminaries

```
287 /*lua>
```

Some set up for the Lua module which is needed for all of the Lua functionality added here.

**luatexbase** Set up the table for the returned functions. This is used to expose all of the public functions.

```
288 luatexbase      = luatexbase or { }
289 local luatexbase = luatexbase
```

Some Lua best practice: use local versions of functions where possible.

```
290 local string_gsub      = string.gsub
291 local tex_count         = tex.count
292 local tex_setcount      = tex.setcount
293 local texio_write_nl    = texio.write_nl
294 local flush_list        = node.flush_list

295 local luatexbase_warning
296 local luatexbase_error
```

## 5.11 Lua module utilities

### 5.11.1 Module tracking

**modules** To allow tracking of module usage, a structure is provided to store information and to return it.

```
297 local modules = modules or { }
```

**provides\_module** Local function to write to the log.

```
298 local function luatexbase_log(text)
299   texio_write_nl("log", text)
300 end
```

Modelled on \ProvidesPackage, we store much the same information but with a little more structure.

```
301 local function provides_module(info)
302   if not (info and info.name) then
303     luatexbase_error("Missing module name for provides_module")
304   end
305   local function spaced(text)
306     return text and (" " .. text) or ""
307   end
308   luatexbase_log(
309     "Lua module: " .. info.name
310     .. spaced(info.date)
311     .. spaced(info.version)
312     .. spaced(info.description)
313   )
314   modules[info.name] = info
315 end
316 luatexbase.provides_module = provides_module
```

### 5.11.2 Module messages

There are various warnings and errors that need to be given. For warnings we can get exactly the same formatting as from TeX. For errors we have to make some changes. Here we give the text of the error in the L<sup>A</sup>T<sub>E</sub>X format then force an error from Lua to halt the run. Splitting the message text is done using \n which takes the place of \MessageBreak.

First an auxiliary for the formatting: this measures up the message leader so we always get the correct indent.

```

317 local function msg_format(mod, msg_type, text)
318   local leader = ""
319   local cont
320   local first_head
321   if mod == "LaTeX" then
322     cont = string.gsub(leader, ".", " ")
323     first_head = leader .. "LaTeX: "
324   else
325     first_head = leader .. "Module " .. msg_type
326     cont = "(" .. mod .. ")"
327     .. string.gsub(first_head, ".", " ")
328     first_head = leader .. "Module " .. mod .. " " .. msg_type .. ":" ..
329   end
330   if msg_type == "Error" then
331     first_head = "\n" .. first_head
332   end
333   if string.sub(text,-1) ~= "\n" then
334     text = text .. " "
335   end
336   return first_head .. " "
337   .. string.gsub(
338     text
339     .. "on input line "
340     .. tex.inputlineno, "\n", "\n" .. cont .. " "
341   )
342   .. "\n"
343 end

module_info Write messages.
module_warning 344 local function module_info(mod, text)
module_error 345   texio_write_nl("log", msg_format(mod, "Info", text))
346 end
347 luatexbase.module_info = module_info
348 local function module_warning(mod, text)
349   texio_write_nl("term and log",msg_format(mod, "Warning", text))
350 end
351 luatexbase.module_warning = module_warning
352 local function module_error(mod, text)
353   error(msg_format(mod, "Error", text))
354 end
355 luatexbase.module_error = module_error

Dedicated versions for the rest of the code here.
356 function luatexbase_warning(text)

```

```

357   module_warning("luatexbase", text)
358 end
359 function luatexbase_error(text)
360   module_error("luatexbase", text)
361 end

```

## 5.12 Accessing register numbers from Lua

Collect up the data from the  $\text{\TeX}$  level into a Lua table: from version 0.80,  $\text{\LaTeX}$  makes that easy.

```

362 local luaregisterbasetable = { }
363 local registermap = {
364   attributezero = "assign_attr"      ,
365   charzero     = "char_given"       ,
366   CountZero    = "assign_int"       ,
367   dimenzero    = "assign_dimen"     ,
368   mathcharzero = "math_given"       ,
369   muskipzero   = "assign_mu_skip"  ,
370   skipzero     = "assign_skip"     ,
371   tokszero    = "assign_toks"      ,
372 }
373 local createtoken
374 if tex.luatexversion > 81 then
375   createtoken = token.create
376 elseif tex.luatexversion > 79 then
377   createtoken = newtoken.create
378 end
379 local hashtokens = tex.hashtokens()
380 local luatexversion = tex.luatexversion
381 for i,j in pairs (registermap) do
382   if luatexversion < 80 then
383     luaregisterbasetable[hashtokens[i][1]] =
384       hashtokens[i][2]
385   else
386     luaregisterbasetable[j] = createtoken(i).mode
387   end
388 end

```

`registernumber` Working out the correct return value can be done in two ways. For older  $\text{\LaTeX}$  releases it has to be extracted from the `hashtokens`. On the other hand, newer  $\text{\LaTeX}$ 's have `newtoken`, and whilst `.mode` isn't currently documented, Hans Hagen pointed to this approach so we should be OK.

```

389 local registernumber
390 if luatexversion < 80 then
391   function registernumber(name)
392     local nt = hashtokens[name]
393     if(nt and luaregisterbasetable[nt[1]]) then
394       return nt[2] - luaregisterbasetable[nt[1]]
395     else
396       return false
397     end
398   end
399 else

```

```

400     function registernumber(name)
401       local nt = createtoken(name)
402       if(luaregisterbasetable[nt.cmdname]) then
403         return nt.mode - luaregisterbasetable[nt.cmdname]
404       else
405         return false
406       end
407     end
408   end
409 luatexbase.registernumber = registernumber

```

### 5.13 Attribute allocation

`new_attribute` As attributes are used for Lua manipulations its useful to be able to assign from this end.

```

410 local attributes=setmetatable(
411 {}, {
412   __index = function(t,key)
413     return registernumber(key) or nil
414   end
415   )
416   luatexbase.attributes = attributes
417 local attribute_count_name =
418   attribute_count_name or "e@alloc@attribute@count"
419 local function new_attribute(name)
420   tex_setcount("global", attribute_count_name,
421               tex_count[attribute_count_name] + 1)
422   if tex_count[attribute_count_name] > 65534 then
423     luatexbase_error("No room for a new \\attribute")
424   end
425   attributes[name]= tex_count[attribute_count_name]
426   luatexbase_log("Lua-only attribute " .. name .. " = " ..
427                 tex_count[attribute_count_name])
428   return tex_count[attribute_count_name]
429 end
430 luatexbase.new_attribute = new_attribute

```

### 5.14 Custom whatsit allocation

`new_whatsit` Much the same as for attribute allocation in Lua.

```

432 local whatsit_count_name = whatsit_count_name or "e@alloc@whatsit@count"
433 local function new_whatsit(name)
434   tex_setcount("global", whatsit_count_name,
435               tex_count[whatsit_count_name] + 1)
436   if tex_count[whatsit_count_name] > 65534 then
437     luatexbase_error("No room for a new custom whatsit")
438   end
439   luatexbase_log("Custom whatsit " .. (name or "") .. " = " ..
440                 tex_count[whatsit_count_name])
441   return tex_count[whatsit_count_name]
442 end
443 luatexbase.new_whatsit = new_whatsit

```

## 5.15 Bytecode register allocation

`new_bytecode` Much the same as for attribute allocation in Lua. The optional `(name)` argument is used in the log if given.

```
444 local bytecode_count_name =
445           bytecode_count_name or "e@alloc@bytecode@count"
446 local function new_bytecode(name)
447   tex_setcount("global", bytecode_count_name,
448               tex_count[bytecode_count_name] + 1)
449   if tex_count[bytecode_count_name] > 65534 then
450     luatexbase_error("No room for a new bytecode register")
451   end
452   luatexbase_log("Lua bytecode " .. (name or "") .. " = " ..
453                   tex_count[bytecode_count_name])
454   return tex_count[bytecode_count_name]
455 end
456 luatexbase.new_bytecode = new_bytecode
```

## 5.16 Lua chunk name allocation

`new_chunkname` As for bytecode registers but also store the name in the `lua.name` table.

```
457 local chunkname_count_name =
458           chunkname_count_name or "e@alloc@luachunk@count"
459 local function new_chunkname(name)
460   tex_setcount("global", chunkname_count_name,
461               tex_count[chunkname_count_name] + 1)
462   local chunkname_count = tex_count[chunkname_count_name]
463   chunkname_count = chunkname_count + 1
464   if chunkname_count > 65534 then
465     luatexbase_error("No room for a new chunkname")
466   end
467   lua.name[chunkname_count]=name
468   luatexbase_log("Lua chunkname " .. (name or "") .. " = " ..
469                   chunkname_count .. "\n")
470   return chunkname_count
471 end
472 luatexbase.new_chunkname = new_chunkname
```

## 5.17 Lua function allocation

`new_luafunction` Much the same as for attribute allocation in Lua. The optional `(name)` argument is used in the log if given.

```
473 local luafunction_count_name =
474           luafunction_count_name or "e@alloc@luafunction@count"
475 local function new_luafunction(name)
476   tex_setcount("global", luafunction_count_name,
477               math.max(
478                 #(lua.get_functions_table()),
479                 tex_count[luafunction_count_name])
480               + 1)
481   lua.get_functions_table()[tex_count[luafunction_count_name]] = false
482   if tex_count[luafunction_count_name] > 65534 then
483     luatexbase_error("No room for a new luafunction register")
```

```

484     end
485     luatexbase_log("Lua function " .. (name or "") .. " = " ..
486                     tex_count[luafunction_count_name])
487     return tex_count[luafunction_count_name]
488 end
489 luatexbase.new_luafunction = new_luafunction

```

## 5.18 Lua callback management

The native mechanism for callbacks in LuaTeX allows only one per function. That is extremely restrictive and so a mechanism is needed to add and remove callbacks from the appropriate hooks.

### 5.18.1 Housekeeping

The main table: keys are callback names, and values are the associated lists of functions. More precisely, the entries in the list are tables holding the actual function as `func` and the identifying description as `description`. Only callbacks with a non-empty list of functions have an entry in this list.

Actually there are two tables: `realcallbacklist` directly contains the entries as described above while `callbacklist` only directly contains the already sorted entries. Other entries can be queried through `callbacklist` too which triggers a resort.

Additionally `callbackrules` describes the ordering constraints: It contains two element tables with the descriptions of the constrained callback implementations. It can additionally contain a `type` entry indicating the kind of rule. A missing value indicates a normal ordering constraint.

```

490 local realcallbacklist = {}
491 local callbackrules = {}
492 local callbacklist = setmetatable({}, {
493     __index = function(t, name)
494         local list = realcallbacklist[name]
495         local rules = callbackrules[name]
496         if list and rules then
497             local meta = {}
498             for i, entry in ipairs(list) do
499                 local t = {value = entry, count = 0, pos = i}
500                 meta[entry.description], list[i] = t, t
501             end
502             local count = #list
503             local pos = count
504             for i, rule in ipairs(rules) do
505                 local rule = rules[i]
506                 local pre, post = meta[rule[1]], meta[rule[2]]
507                 if pre and post then
508                     if rule.type then
509                         if not rule.hidden then
510                             assert(rule.type == 'incompatible-warning' and luatexbase_warning
511                                 or rule.type == 'incompatible-error' and luatexbase_error)(
512                                 "Incompatible functions \".. rule[1] .. \" and \".. rule[2]
513                                 .. \" specified for callback \".. name .. \".\"")
514                         rule.hidden = true

```

```

515         end
516     else
517         local post_count = post.count
518         post.count = post_count+1
519         if post_count == 0 then
520             local post_pos = post.pos
521             if post_pos ~= pos then
522                 local new_post_pos = list[pos]
523                 new_post_pos.pos = post_pos
524                 list[post_pos] = new_post_pos
525             end
526             list[pos] = nil
527             pos = pos - 1
528         end
529         pre[#pre+1] = post
530     end
531 end
532
533 for i=1, count do -- The actual sort begins
534     local current = list[i]
535     if current then
536         meta[current.value.description] = nil
537         for j, cur in ipairs(current) do
538             local count = cur.count
539             if count == 1 then
540                 pos = pos + 1
541                 list[pos] = cur
542             else
543                 cur.count = count - 1
544             end
545         end
546         list[i] = current.value
547     else
548         -- Cycle occurred. TODO: Show cycle for debugging
549         -- list[i] = ...
550         local remaining = {}
551         for name, entry in next, meta do
552             local value = entry.value
553             list[#list + 1] = entry.value
554             remaining[#remaining + 1] = name
555         end
556         table.sort(remaining)
557         local first_name = remaining[1]
558         for j, name in ipairs(remaining) do
559             local entry = meta[name]
560             list[i + j - 1] = entry.value
561             for _, post_entry in ipairs(entry) do
562                 local post_name = post_entry.value.description
563                 if not remaining[post_name] then
564                     remaining[post_name] = name
565                 end
566             end
567         end
568         local cycle = {first_name}

```

```

569     local index = 1
570     local last_name = first_name
571     repeat
572         cycle[last_name] = index
573         last_name = remaining[last_name]
574         index = index + 1
575         cycle[index] = last_name
576     until cycle[last_name]
577     local length = index - cycle[last_name] + 1
578     table.move(cycle, cycle[last_name], index, 1)
579     for i=2, length//2 do
580         cycle[i], cycle[length + 1 - i] = cycle[length + 1 - i], cycle[i]
581     end
582     error('Cycle occurred at ' .. table.concat(cycle, ' -> ', 1, length))
583     end
584     end
585   end
586   realcallbacklist[name] = list
587   t[name] = list
588   return list
589 end
590 })

```

Numerical codes for callback types, and name-to-value association (the table keys are strings, the values are numbers).

```

591 local list, data, exclusive, simple, reverselist = 1, 2, 3, 4, 5
592 local types  = {
593   list      = list,
594   data      = data,
595   exclusive = exclusive,
596   simple    = simple,
597   reverselist = reverselist,
598 }

```

Now, list all predefined callbacks with their current type, based on the *LuaTeX* manual version 1.01. A full list of the currently-available callbacks can be obtained using

```

\directlua{
  for i,_ in pairs(callback.list()) do
    texio.write_nl("- " .. i)
  end
}
\bye

```

in plain *LuaTeX*. (Some undocumented callbacks are omitted as they are to be removed.)

```
599 local callbacktypes = callbacktypes or {
```

Section 8.2: file discovery callbacks.

```

600   find_read_file    = exclusive,
601   find_write_file   = exclusive,
602   find_font_file    = data,
603   find_output_file  = data,

```

```

604  find_format_file    = data,
605  find_vf_file        = data,
606  find_map_file       = data,
607  find_enc_file       = data,
608  find_pk_file        = data,
609  find_data_file      = data,
610  find_opentype_file  = data,
611  find_truetype_file  = data,
612  find_type1_file     = data,
613  find_image_file     = data,

614  open_read_file      = exclusive,
615  read_font_file      = exclusive,
616  read_vf_file         = exclusive,
617  read_map_file        = exclusive,
618  read_enc_file        = exclusive,
619  read_pk_file         = exclusive,
620  read_data_file       = exclusive,
621  read_truetype_file   = exclusive,
622  read_type1_file      = exclusive,
623  read_opentype_file   = exclusive,

```

Not currently used by luatex but included for completeness. may be used by a font handler.

```

624  find_cidmap_file   = data,
625  read_cidmap_file   = exclusive,

```

Section 8.3: data processing callbacks.

```

626  process_input_buffer = data,
627  process_output_buffer = data,
628  process_jobname      = data,

```

Section 8.4: node list processing callbacks.

```

629  contribute_filter    = simple,
630  buildpage_filter     = simple,
631  build_page_insert    = exclusive,
632  pre_linebreak_filter = list,
633  linebreak_filter     = exclusive,
634  append_to_vlist_filter= exclusive,
635  post_linebreak_filter= reverselist,
636  hpack_filter          = list,
637  vpack_filter          = list,
638  hpack_quality         = exclusive,
639  vpack_quality         = exclusive,
640  pre_output_filter     = list,
641  process_rule          = exclusive,
642  hyphenate              = simple,
643  ligaturing             = simple,
644  kerning                = simple,
645  insert_local_par      = simple,
646 % mlist_to_hlist       = exclusive,
647  new_graf                = exclusive,

```

Section 8.5: information reporting callbacks.

```

648  pre_dump              = simple,
649  start_run              = simple,

```

```

650 stop_run           = simple,
651 start_page_number = simple,
652 stop_page_number   = simple,
653 show_error_hook    = simple,
654 show_warning_message= simple,
655 show_error_message  = simple,
656 show_lua_error_hook = simple,
657 start_file          = simple,
658 stop_file           = simple,
659 call_edit            = simple,
660 finish_synctex      = simple,
661 wrapup_run          = simple,

```

Section 8.6: PDF-related callbacks.

```

662 finish_pdffile      = data,
663 finish_pdfpage       = data,
664 page_objnum_provider = data,
665 page_order_index     = data,
666 process_pdf_image_content = data,

```

Section 8.7: font-related callbacks.

```

667 define_font           = exclusive,
668 glyph_info             = exclusive,
669 glyph_not_found        = exclusive,
670 glyph_stream_provider  = exclusive,
671 make_extensible         = exclusive,
672 font_descriptor_objnum_provider = exclusive,
673 input_level_string      = exclusive,
674 provide_charproc_data  = exclusive,
675 }
676 luatexbase.callbacktypes=callbacktypes

```

Sometimes multiple callbacks correspond to a single underlying engine level callback. Then the engine level callback should be registered as long as at least one of these callbacks is in use. This is implemented though a shared table which counts how many of the involved callbacks are currently in use. The engine level callback is registered iff this count is not 0.

We add `mlist_to_hlist` directly to the list to demonstrate this, but the handler gets added later when it is actually defined.

All callbacks in this list are treated as user defined callbacks.

```

677 local shared_callbacks = {
678   mlist_to_hlist = {
679     callback = "mlist_to_hlist",
680     count = 0,
681     handler = nil,
682   },
683 }
684 shared_callbacks.pre_mlist_to_hlist_filter = shared_callbacks.mlist_to_hlist
685 shared_callbacks.post_mlist_to_hlist_filter = shared_callbacks.mlist_to_hlist

```

`callback.register` Save the original function for registering callbacks and prevent the original being used. The original is saved in a place that remains available so other more sophisticated code can override the approach taken by the kernel if desired.

```
686 local callback_register = callback_register or callback.register
```

```

687 function callback.register()
688   luatexbase_error("Attempt to use callback.register() directly\n")
689 end

```

### 5.18.2 Handlers

The handler function is registered into the callback when the first function is added to this callback's list. Then, when the callback is called, the handler takes care of running all functions in the list. When the last function is removed from the callback's list, the handler is unregistered.

More precisely, the functions below are used to generate a specialized function (closure) for a given callback, which is the actual handler.

The way the functions are combined together depends on the type of the callback. There are currently 4 types of callback, depending on the calling convention of the functions the callback can hold:

**simple** is for functions that don't return anything: they are called in order, all with the same argument;

**data** is for functions receiving a piece of data of any type except node list head (and possibly other arguments) and returning it (possibly modified): the functions are called in order, and each is passed the return value of the previous (and the other arguments untouched, if any). The return value is that of the last function;

**list** is a specialized variant of *data* for functions filtering node lists. Such functions may return either the head of a modified node list, or the boolean values **true** or **false**. The functions are chained the same way as for *data* except that for the following. If one function returns **false**, then **false** is immediately returned and the following functions are *not* called. If one function returns **true**, then the same head is passed to the next function. If all functions return **true**, then **true** is returned, otherwise the return value of the last function not returning **true** is used.

**reverselist** is a specialized variant of *list* which executes functions in inverse order.

**exclusive** is for functions with more complex signatures; functions in this type of callback are *not* combined: An error is raised if a second callback is registered.

Handler for **data** callbacks.

```

690 local function data_handler(name)
691   return function(data, ...)
692     for _,i in ipairs(callbacklist[name]) do
693       data = i.func(data,...)
694     end
695   return data
696 end
697 end

```

Default for user-defined **data** callbacks without explicit default.

```
698 local function data_handler_default(value)
```

```
699     return value
700 end
```

Handler for **exclusive** callbacks. We can assume `callbacklist[name]` is not empty: otherwise, the function wouldn't be registered in the callback any more.

```
701 local function exclusive_handler(name)
702     return function(...)
703         return callbacklist[name][1].func(...)
704     end
705 end
```

Handler for **list** callbacks.

```
706 local function list_handler(name)
707     return function(head, ...)
708         local ret
709         for _,i in ipairs(callbacklist[name]) do
710             ret = i.func(head, ...)
711             if ret == false then
712                 luatebase_warning(
713                     "Function '" .. i.description .. "' returned false\n"
714                     .. "in callback '" .. name .. "'"
715                 )
716             return false
717         end
718         if ret ~= true then
719             head = ret
720         end
721     end
722     return head
723 end
724 end
```

Default for user-defined **list** and **reverselist** callbacks without explicit default.

```
725 local function list_handler_default(head)
726     return head
727 end
```

Handler for **reverselist** callbacks.

```
728 local function reverselist_handler(name)
729     return function(head, ...)
730         local ret
731         local callbacks = callbacklist[name]
732         for i = #callbacks, 1, -1 do
733             local cb = callbacks[i]
734             ret = cb.func(head, ...)
735             if ret == false then
736                 luatebase_warning(
737                     "Function '" .. cb.description .. "' returned false\n"
738                     .. "in callback '" .. name .. "'"
739                 )
740             return false
741         end
742         if ret ~= true then
743             head = ret
744         end
745     end
746 end
```

```

746     return head
747   end
748 end

Handler for simple callbacks.

749 local function simple_handler(name)
750   return function(...)
751     for _,i in ipairs(callbacklist[name]) do
752       i.func(...)
753     end
754   end
755 end

Default for user-defined simple callbacks without explicit default.

756 local function simple_handler_default()
757 end

Keep a handlers table for indexed access and a table with the corresponding
default functions.

758 local handlers = {
759   [data]      = data_handler,
760   [exclusive] = exclusive_handler,
761   [list]      = list_handler,
762   [reverselist] = reverselist_handler,
763   [simple]    = simple_handler,
764 }
765 local defaults = {
766   [data]      = data_handler_default,
767   [exclusive] = nil,
768   [list]      = list_handler_default,
769   [reverselist] = list_handler_default,
770   [simple]    = simple_handler_default,
771 }

```

### 5.18.3 Public functions for callback management

Defining user callbacks perhaps should be in package code, but impacts on `add_to_callback`. If a default function is not required, it may be declared as `false`. First we need a list of user callbacks.

```
772 local user_callbacks_defaults = {}
```

`create_callback` The allocator itself.

```

773 local function create_callback(name, ctype, default)
774   local ctype_id = types[ctype]
775   if not name or name == ""
776   or not ctype_id
777   then
778     luatexbase_error("Unable to create callback:\n" ..
779                      "valid callback name and type required")
780   end
781   if callbacktypes[name] then
782     luatexbase_error("Unable to create callback '" .. name ..
783                      "' :\ncallback is already defined")
784   end
785   default = default or defaults[ctype_id]
```

```

786     if not default then
787         luatexbase_error("Unable to create callback '" .. name ..
788                         .. "':\ndefault is required for '" .. ctype ..
789                         .. "' callbacks")
790     elseif type (default) ~= "function" then
791         luatexbase_error("Unable to create callback '" .. name ..
792                         .. "':\ndefault is not a function")
793     end
794     user_callbacks_defaults[name] = default
795     callbacktypes[name] = ctype_id
796 end
797 luatexbase.create_callback = create_callback

```

`call_callback` Call a user defined callback. First check arguments.

```

798 local function call_callback(name,...)
799     if not name or name == "" then
800         luatexbase_error("Unable to create callback:\n" ..
801                         .. "valid callback name required")
802     end
803     if user_callbacks_defaults[name] == nil then
804         luatexbase_error("Unable to call callback '" .. name ..
805                         .. "':\nunknown or empty")
806     end
807     local l = callbacklist[name]
808     local f
809     if not l then
810         f = user_callbacks_defaults[name]
811     else
812         f = handlers[callbacktypes[name]](name)
813     end
814     return f(...)
815 end
816 luatexbase.call_callback=call_callback

```

`add_to_callback` Add a function to a callback. First check arguments.

```

817 local function add_to_callback(name, func, description)
818     if not name or name == "" then
819         luatexbase_error("Unable to register callback:\n" ..
820                         .. "valid callback name required")
821     end
822     if not callbacktypes[name] or
823         type(func) ~= "function" or
824         not description or
825         description == "" then
826         luatexbase_error(
827             "Unable to register callback.\n\n"
828             .. "Correct usage:\n"
829             .. "add_to_callback(<callback>, <function>, <description>)"
830         )
831     end

```

Then test if this callback is already in use. If not, initialise its list and register the proper handler.

```
832     local l = realcallbacklist[name]
```

```

833     if l == nil then
834         l = { }
835         realcallbacklist[name] = l
Handle count for shared engine callbacks.

836     local shared = shared_callbacks[name]
837     if shared then
838         shared.count = shared.count + 1
839         if shared.count == 1 then
840             callback_register(shared.callback, shared.handler)
841         end

```

If it is not a user defined callback use the primitive callback register.

```

842     elseif user_callbacks_defaults[name] == nil then
843         callback_register(name, handlers[callbacktypes[name]](name))
844     end
845 end

```

Actually register the function and give an error if more than one `exclusive` one is registered.

```

846     local f = {
847         func      = func,
848         description = description,
849     }
850     if callbacktypes[name] == exclusive then
851         if #l == 1 then
852             luatexbase_error(
853                 "Cannot add second callback to exclusive function\n" ..
854                 name .. ",")
855         end
856     end
857     table.insert(l, f)
858     callbacklist[name] = nil

```

Keep user informed.

```

859     luatexbase_log(
860         "Inserting '" .. description .. "' in '" .. name .. "'."
861     )
862 end
863 luatexbase.add_to_callback = add_to_callback

```

`declare_callback_rule` Add an ordering constraint between two callback implementations

```

864 local function declare_callback_rule(name, desc1, relation, desc2)
865     if not callbacktypes[name] or
866         not desc1 or not desc2 or
867         desc1 == "" or desc2 == "" then
868         luatexbase_error(
869             "Unable to create ordering constraint. "
870             .. "Correct usage:\n"
871             .. "declare_callback_rule(<callback>, <description_a>, <description_b>)"
872         )
873     end
874     if relation == 'before' then
875         relation = nil
876     elseif relation == 'after' then

```

```

877     desc2, desc1 = desc1, desc2
878     relation = nil
879     elseif relation == 'incompatible-warning' or relation == 'incompatible-error' then
880     elseif relation == 'unrelated' then
881     else
882       luatexbase_error(
883         "Unknown relation type in declare_callback_rule"
884       )
885     end
886     callbacklist[name] = nil
887     local rules = callbackrules[name]
888     if rules then
889       for i, rule in ipairs(rules) do
890         if rule[1] == desc1 and rule[2] == desc2 or rule[1] == desc2 and rule[2] == desc1 then
891           if relation == 'unrelated' then
892             table.remove(rules, i)
893           else
894             rule[1], rule[2], rule.type = desc1, desc2, relation
895           end
896         return
897       end
898     end
899     if relation ~= 'unrelated' then
900       rules[#rules + 1] = {desc1, desc2, type = relation}
901     end
902   elseif relation ~= 'unrelated' then
903     callbackrules[name] = {{desc1, desc2, type = relation}}
904   end
905 end
906 luatexbase.declare_callback_rule = declare_callback_rule

```

`remove_from_callback` Remove a function from a callback. First check arguments.

```

907 local function remove_from_callback(name, description)
908   if not name or name == "" then
909     luatexbase_error("Unable to remove function from callback:\n" ..
910                      "valid callback name required")
911   end
912   if not callbacktypes[name] or
913     not description or
914     description == "" then
915     luatexbase_error(
916       "Unable to remove function from callback.\n\n"
917       .. "Correct usage:\n"
918       .. "remove_from_callback(<callback>, <description>)"
919     )
920   end
921   local l = realcallbacklist[name]
922   if not l then
923     luatexbase_error(
924       "No callback list for '" .. name .. "'\n")
925   end

```

Loop over the callback's function list until we find a matching entry. Remove it and check if the list is empty: if so, unregister the callback handler.

```

926 local index = false
927 for i,j in ipairs(l) do
928   if j.description == description then
929     index = i
930     break
931   end
932 end
933 if not index then
934   luatexbase_error(
935     "No callback '" .. description .. "' registered for '" ..
936     name .. "'\n")
937 end
938 local cb = l[index]
939 table.remove(l, index)
940 luatexbase_log(
941   "Removing '" .. description .. "' from '" .. name .. "'."
942 )
943 if #l == 0 then
944   realcallbacklist[name] = nil
945   callbacklist[name] = nil
946   local shared = shared_callbacks[name]
947   if shared then
948     shared.count = shared.count - 1
949     if shared.count == 0 then
950       callback_register(shared.callback, nil)
951     end
952   elseif user_callbacks_defaults[name] == nil then
953     callback_register(name, nil)
954   end
955 end
956 return cb.func,cb.description
957 end
958 luatexbase.remove_from_callback = remove_from_callback

```

`in_callback` Look for a function description in a callback.

```

959 local function in_callback(name, description)
960   if not name
961     or name == ""
962     or not realcallbacklist[name]
963     or not callbacktypes[name]
964     or not description then
965       return false
966   end
967   for _, i in pairs(realcallbacklist[name]) do
968     if i.description == description then
969       return true
970     end
971   end
972   return false
973 end
974 luatexbase.in_callback = in_callback

```

`disable_callback` As we subvert the engine interface we need to provide a way to access this functionality.

```

975 local function disable_callback(name)
976   if(realcallbacklist[name] == nil) then
977     callback_register(name, false)
978   else
979     luatexbase_error("Callback list for " .. name .. " not empty")
980   end
981 end
982 luatexbase.disable_callback = disable_callback

```

**callback\_descriptions** List the descriptions of functions registered for the given callback. This will sort the list if necessary.

```

983 local function callback_descriptions (name)
984   local d = {}
985   if not name
986     or name == ""
987     or not realcallbacklist[name]
988     or not callbacktypes[name]
989   then
990     return d
991   else
992     for k, i in pairs(callbacklist[name]) do
993       d[k]= i.description
994     end
995   end
996   return d
997 end
998 luatexbase.callback_descriptions =callback_descriptions

```

**uninstall** Unlike at the T<sub>E</sub>X level, we have to provide a back-out mechanism here at the same time as the rest of the code. This is not meant for use by anything other than `latexrelease`: as such this is *deliberately* not documented for users!

```

999 local function uninstall()
1000   module_info(
1001     "luatexbase",
1002     "Uninstalling kernel luatexbase code"
1003   )
1004   callback.register = callback_register
1005   luatexbase = nil
1006 end
1007 luatexbase.uninstall = uninstall

```

**mlist\_to\_hlist** To emulate these callbacks, the “real” `mlist_to_hlist` is replaced by a wrapper calling the wrappers before and after.

```

1008 create_callback('pre_mlist_to_hlist_filter', 'list')
1009 create_callback('mlist_to_hlist', 'exclusive', node.mlist_to_hlist)
1010 create_callback('post_mlist_to_hlist_filter', 'reverselist')
1011 function shared_callbacks.mlist_to_hlist.handler(head, display_type, need_penalties)
1012   local current = call_callback("pre_mlist_to_hlist_filter", head, display_type, need_penalties)
1013   if current == false then
1014     flush_list(head)
1015     return nil
1016   end
1017   current = call_callback("mlist_to_hlist", current, display_type, need_penalties)

```

```
1018 local post = call_callback("post_mlist_to_hlist_filter", current, display_type, need_penal
1019 if post == false then
1020   flush_list(current)
1021   return nil
1022 end
1023 return post
1024 end

1025 ⟨/lua⟩

Reset the catcode of @.
1026 ⟨tex⟩\catcode‘@=\et atcatcode\relax
```