

The `eolgrab` package

Heiko Oberdiek*

2016/05/16 v1.1

Abstract

This package implements a generic argument grabber to catch an argument that is delimited by the line end.

Contents

1 Documentation	1
1.1 Examples	2
1.1.1 Small L ^A T _E X document as example	3
1.1.2 L ^A T _E X document with environments	4
1.2 Limitations	4
2 Implementation	4
2.1 Reload check and package identification	4
2.2 Catcodes	6
2.3 Resources	6
2.4 Macro <code>\eolgrab</code>	7
3 Installation	8
3.1 Download	8
3.2 Bundle installation	8
3.3 Package installation	8
3.4 Refresh file name databases	9
3.5 Some details for the interested	9
4 References	9
5 History	9
[2011/01/12 v1.0]	9
[2016/05/16 v1.1]	9
6 Index	10

1 Documentation

The starting point for this package was a feature request of Arno Trautmann in the mailing list `texhax`¹ [1]. A macro `\eolsection` should behave like `\section`, but the argument should be delimited by the line end instead of given in curly braces:

```
\eolsection My Title
```

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

¹Info page for mailing list `texhax`: <https://tug.org/mailman/listinfo/texhax>

Phil Taylor answered this with an implementation for `\eolsection`. Because this feature could be useful for other macros as well, I answered with an implementation of `\eolgrab` as general solution [3].

Both formats plain \TeX and \LaTeX are supported by the package, see the example for `\eolsection` below.

```
\eolgrab {\langle code\rangle} {\langle argument\rangle} {\langle EOL\rangle}
```

Macro `\eolgrab` takes two arguments. The first argument is `\langle code\rangle`, a classical undelimited \TeX macro argument. The second argument is delimited by the line end `\langle EOL\rangle`. The macro calls `\langle code\rangle` with `\langle argument\rangle` as argument in curly braces. Because the catcode of the line end is changed, `\eolgrab` will not work in the argument of other macros. Macro `\eolgrab` is made robust if either ε - \TeX 's `\protected` or \LaTeX 's `\DeclareRobustCommand` is available.

```
\eolgrabopt {\langle code\rangle} {\langle argument\rangle} {\langle EOL\rangle}
```

Macro `\eolgrabopt` passes `\langle argument\rangle` as optional argument to `\langle code\rangle` if `\langle argument\rangle` is not empty.

```
\eolgrabopt\item foo
```

becomes to

```
\item[{\foo}]
```

The curly argument braces are added to support square brackets inside `\langle argument\rangle`. If the `\langle argument\rangle` is empty:

```
\eolgrabopt\item
```

then

```
\item
```

is called without optional argument.

1.1 Examples

- The line

```
\eolgrab\section My Title
```

is equivalent to

```
\section{My Title}
```

- The next example uses the star form of `\section`. Then the command to be called consists of two tokens. Therefore the first argument of `\eolgrab` needs curly braces:

```
\eolgrab{\section*}My Title
```

becomes

```
\section*{My Title}
```

- Now \LaTeX 's `\PackageError` is used. This macro has three arguments, the package or class name, the message text and the help text. A standard help text of \LaTeX is used as given in macro `\@ehc`. The second argument, the message text is used as argument, delimited by line end:

```
\eolgrab{\PackageError{foobar}}%
Some error message text\MessageBreak%
with several lines
\@ehc
```

In the first two lines of the example, the line end is suppressed by the comment character (percent), thus the argument is delimited by the line end of the third line. The result is:

```
\PackageError{foobar}{Some error message text\MessageBreak%
with several lines}\@ehc
```

- The original request for macro `\eolsection`, see above, can be implemented easily with the help of `\eolgrab`. Example for L^AT_EX:

```
\usepackage{eolgrab}
\newcommand*{\eolsection}{\eolgrab\section}
```

Example for plain T_EX:

```
\input eolgrab.sty\relax
\def\eolsection{\eolgrab\section}
```

And a sophisticated variant for L^AT_EX that also supports the star syntax and the optional argument:

```

1  <*example-sec>
2  \documentclass{article}
3  \usepackage{eolgrab}
4  \makeatletter
5  \newcommand*{\eolsection}{%
6      \@ifstar{%
7          \eolgrab{\section*}{%
8              \@ifnextchar[{%
9                  \eoloptsection
10                 }{%
11                     \eolgrab\section
12                     }%
13                 }%
14             }%
15         }%
16     \newcommand*{\eoloptsection}[1][]{%
17         \eolgrab{\section[#1]}{%
18     }%
19     \makeatother
20     \begin{document}
21     \tableofcontents
22     \eolsection Section without star and optional argument
23     \eolsection*Section with star
24     \eolsection[Short section title]Long section title
25     \end{document}
26     </example-sec>
```

1.1.1 Small L^AT_EX document as example

```

27 <*example-ltx>
28 \RequirePackage{eolgrab}
29 \eolgrab\documentclass article
30 \eolgrab\begin document
31 \eolgrab\section Hello World
32 \eolgrab\emph Some text
33 \eolgrab\end document
34 </example-ltx>
```

1.1.2 L^AT_EX document with environments

```
35 <*example-env>
36 \documentclass{article}
37 \usepackage{eolgrab}
38 \newcommand*{\Begin}{\eolgrab \begin}
39 \newcommand*{\End }{\eolgrab \end }
40 \newcommand*{\Item }{\eolgrabopt\item }
41 \Begin document
42 \Begin itemize
43 \Item
44   first item
45 \Item
46   second item
47 \End itemize
48 \Begin description
49 \Item foo
50   is the first syllable of foobar.
51 \Item bar
52   is the second syllable of foobar.
53 \End description
54 \End document
55 </example-env>
```

1.2 Limitations

Macro `\eolgrab` needs to catch the line end. If T_EX reads a line, then it throws away the line end characters (carriage return, line feed) and removes spaces at the end of the line. Then it adds the character with the character code that is given by `\endlinechar` at the end of the line. The category code of the inserted character is given by the current value of its `\catcode`. If `\endlinechar` is not a valid character code (especially if it is negative), then no character is added.

In plain T_EX and L^AT_EX the standard settings of the inserted endline character is the character with code 13 (or `^M` in T_EX notation) with catcode 5 (end of line). That means the inserted end of line character behaves like a space token. For example, it is removed after macro names. Therefore `\eolgrab` changes the catcode.

Therefore `\eolgrab` has some limitations:

- Like other verbatim stuff, the macro `\eolgrab` cannot be used in the argument of other macros. `\eolgrab` want to change the catcode of the end of line character. If this character is read before, because it is processed as argument of another macro, the catcode is already set and is not reassigned later if `\eolgrab` changes the category code for this character code.
- The argument must not contain the end of line character. Otherwise the first end of line character is already taken as delimiter, leaving the rest of the line outside the argument.
- Because `\eolgrab` is probably mostly used in the line with the delimited argument. Therefore changes of `\endlinechar` will not affect the current line.

2 Implementation

```
56 <*package>
```

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```
57 \begingroup\catcode61\catcode48\catcode32=10\relax%
58 \catcode13=5 % ^M
```

```

59  \endlinechar=13 %
60  \catcode35=6 % #
61  \catcode39=12 %
62  \catcode44=12 %
63  \catcode45=12 %
64  \catcode46=12 %
65  \catcode58=12 %
66  \catcode64=11 % @
67  \catcode123=1 % {
68  \catcode125=2 % }
69  \expandafter\let\expandafter\x\csname ver@eolgrab.sty\endcsname
70  \ifx\x\relax % plain-TeX, first loading
71  \else
72    \def\empty{}%
73    \ifx\x\empty % LaTeX, first loading,
74      % variable is initialized, but \ProvidesPackage not yet seen
75    \else
76      \expandafter\ifx\csname PackageInfo\endcsname\relax
77        \def\x#1#2{%
78          \immediate\write-1{Package #1 Info: #2.}%
79        }%
80    \else
81      \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
82    \fi
83    \x{eolgrab}{The package is already loaded}%
84    \aftergroup\endinput
85  \fi
86 \fi
87 \endgroup%

```

Package identification:

```

88 \begingroup\catcode61\catcode48\catcode32=10\relax%
89   \catcode13=5 % ^M
90   \endlinechar=13 %
91   \catcode35=6 % #
92   \catcode39=12 %
93   \catcode40=12 %
94   \catcode41=12 %
95   \catcode44=12 %
96   \catcode45=12 %
97   \catcode46=12 %
98   \catcode47=12 %
99   \catcode58=12 %
100  \catcode64=11 % @
101  \catcode91=12 %
102  \catcode93=12 %
103  \catcode123=1 %
104  \catcode125=2 %
105 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
106   \def\x#1#2#3[#4]{\endgroup
107     \immediate\write-1{Package: #3 #4}%
108     \xdef#1[#4]%
109   }%
110 \else
111   \def\x#1#2[#3]{\endgroup
112     #2[#3]%
113     \ifx#1\undefined
114       \xdef#1[#3]%
115     \fi
116     \ifx#1\relax
117       \xdef#1[#3]%
118     \fi
119   }%

```

```

120  \fi
121 \expandafter\x\csname ver@eolgrab.sty\endcsname
122 \ProvidesPackage{eolgrab}%
123 [2016/05/16 v1.1 Catch arguments delimited by end of line (HO)]%

```

2.2 Catcodes

```

124 \begingroup\catcode61\catcode48\catcode32=10\relax%
125  \catcode13=5 % ^M
126  \endlinechar=13 %
127  \catcode123=1 %
128  \catcode125=2 %
129  \catcode64=11 %
130  \def\x{\endgroup
131    \expandafter\edef\csname eolgrab@AtEnd\endcsname{%
132      \endlinechar=\the\endlinechar\relax
133      \catcode13=\the\catcode13\relax
134      \catcode32=\the\catcode32\relax
135      \catcode35=\the\catcode35\relax
136      \catcode61=\the\catcode61\relax
137      \catcode64=\the\catcode64\relax
138      \catcode123=\the\catcode123\relax
139      \catcode125=\the\catcode125\relax
140    }%
141  }%
142 \x\catcode61\catcode48\catcode32=10\relax%
143 \catcode13=5 % ^M
144 \endlinechar=13 %
145 \catcode35=6 %
146 \catcode64=11 %
147 \catcode123=1 %
148 \catcode125=2 %
149 \def\TMP@EnsureCode#1#2{%
150   \edef\eoI@AtEnd{%
151     \eoI@AtEnd
152     \catcode#1=\the\catcode#1\relax
153   }%
154   \catcode#1=#2\relax
155 }
156 \TMP@EnsureCode{40}{12}%
157 \TMP@EnsureCode{41}{12}%
158 \TMP@EnsureCode{42}{12}%
159 \TMP@EnsureCode{46}{12}%
160 \TMP@EnsureCode{47}{12}%
161 \TMP@EnsureCode{91}{12}%
162 \TMP@EnsureCode{93}{12}%
163 \TMP@EnsureCode{94}{7}%
164 \edef\eoI@AtEnd{\eoI@AtEnd\noexpand\endinput}

```

2.3 Resources

```

165 \begingroup\expandafter\expandafter\expandafter\endgroup
166 \expandafter\ifx\csname RequirePackage\endcsname\relax
167  \input ltxcmds.sty\relax
168  \input infwarerr.sty\relax
169 \else
170  \RequirePackage{ltxcmds}[2010/12/04]%
171  \RequirePackage{infwarerr}[2010/04/08]%
172 \fi

```

```
\eoI@IfDefinable
173 \ltx@ifUndefined{@\eoI@IfDefinable}{%
174  \def\eoI@IfDefinable#1#2{%
175    \ltx@ifundefined{#1}{#2}{%
```

```

176      \@PackageError{eolgrab}{%
177          Command \ltx@backslashchar#1 already defined%
178      }{\@ehc
179  }%
180 }{%
181 \def\@eolgrab@ifdefinable#1{%
182     \expandafter\@ifdefinable\csname#1\endcsname
183 }%
184 }%
185 }

```

2.4 Macro \eolgrab

```

\@eolgrab
186 \eolgrab@ifdefinable{eolgrab}{%
187   \ltx@ifundefined{protected}{%
188     \ltx@ifundefined{DeclareRobustCommand}{%
189       \def\@eolgrab#1{%
190     }{%
191       \newcommand\@eolgrab{}%
192       \ DeclareRobustCommand*\@eolgrab
193     }%
194   }{%
195     \protected\def\@eolgrab#1{%
196   }{%
197     \begingroup
198     \endlinechar=13 %
199     \catcode13=\ltx@active
200     \eolgrab@{#1}%
201   }%
202 }

\@eolgrabopt
203 \eolgrab@ifdefinable{eolgrabopt}{%
204   \ltx@ifundefined{protected}{%
205     \ltx@ifundefined{DeclareRobustCommand}{%
206       \def\@eolgrabopt#1{%
207     }{%
208       \newcommand\@eolgrabopt{}%
209       \ DeclareRobustCommand*\@eolgrabopt
210     }%
211   }{%
212     \protected\def\@eolgrabopt#1{%
213   }{%
214     \begingroup
215     \endlinechar=13 %
216     \catcode13=\ltx@active
217     \eolgrab@opt{#1}%
218   }%
219 }

220 \begingroup
221   \catcode13=\ltx@active %
222 \ltx@firstofone{\endgroup %

\@eolgrab@
223 \def\@eolgrab@#1#2^M{%
224   \endgroup %
225   #1{#2}%
226 }%

```

\@eolgrab@opt

```

227  \def\eoIgrab@opt#1#2^{M}{%
228      \endgroup %
229      \ltx@ifempty{#2}{%
230          #1%
231      }{%
232          #1[{#2}]%
233      }%
234  }%
235 }%
236 \eoIgrab@AtEnd%
237 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN²:

[CTAN:macros/latex/contrib/oberdiek/eoIgrab.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/eoIgrab.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for TeX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain TeX:

```
tex eoIgrab.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>eoIgrab.sty</code>	→ <code>tex/generic/oberdiek/eoIgrab.sty</code>
<code>eoIgrab.pdf</code>	→ <code>doc/latex/oberdiek/eoIgrab.pdf</code>
<code>example/eoIgrab-example-ltx.tex</code>	→ <code>doc/latex/oberdiek/example/eoIgrab-example-ltx.tex</code>
<code>example/eoIgrab-example-env.tex</code>	→ <code>doc/latex/oberdiek/example/eoIgrab-example-env.tex</code>
<code>example/eoIgrab-example-sec.tex</code>	→ <code>doc/latex/oberdiek/example/eoIgrab-example-sec.tex</code>
<code>eoIgrab.dtx</code>	→ <code>source/latex/oberdiek/eoIgrab.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

²[CTAN:pkg/eoIgrab](#)

3.4 Refresh file name databases

If your **T_EX** distribution (**T_EX Live**, **MiK_TE_X**, ...) relies on file name databases, you must refresh these. For example, **T_EX Live** users run **texhash** or **mktexlsr**.

3.5 Some details for the interested

Unpacking with L^AT_EX. The **.dtx** chooses its action depending on the format:

plain T_EX: Run **docstrip** and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for **docstrip** (really, **docstrip** does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{eolgrab.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the **.dtx** or the **.drv** to generate the documentation. The process can be configured by the configuration file **ltxdoc.cfg**. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex eolgrab.dtx
makeindex -s gind.ist eolgrab.idx
pdflatex eolgrab.dtx
makeindex -s gind.ist eolgrab.idx
pdflatex eolgrab.dtx
```

4 References

- [1] Arno Trautmann, *[texhax] read argument until EOL*; mailing list texhax@tug.org, 2011-01-06;
<https://tug.org/pipermail/texhax/2011-January/016517.html>.
- [2] Philip Taylor, *Re: [texhax] read argument until EOL*; mailing list texhax@tug.org, 2011-01-06;
<https://tug.org/pipermail/texhax/2011-January/016519.html>.
- [3] Heiko Oberdiek, *Re: [texhax] read argument until EOL*; mailing list texhax@tug.org, 2011-01-06;
<https://tug.org/pipermail/texhax/2011-January/016526.html>.

5 History

[2011/01/12 v1.0]

- First public version.

[2016/05/16 v1.1]

- Documentation updates.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	I
\@PackageError	176
\@ehc	178
\@ifdefinable	183
\@ifnextchar	9
\@ifstar	6
\@undefined	113
A	
\aftergroup	84
B	
\Begin	38, 41, 42, 48
\begin	20, 30, 38
C	
\catcode .	57, 58, 60, 61, 62, 63, 64, 65, 66, 67, 68, 88, 89, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 124, 125, 127, 128, 129, 133, 134, 135, 136, 137, 138, 139, 142, 143, 145, 146, 147, 148, 152, 154, 199, 216, 221
\csname .	69, 76, 105, 121, 131, 166, 183
D	
\DeclareRobustCommand	192, 209
\documentclass	2, 29, 36
E	
\emph	32
\empty	72, 73
\End	39, 47, 53, 54
\end	25, 33, 39
\endcsname .	69, 76, 105, 121, 131, 166, 183
\endinput	84, 164
\endlinechar 59, 90, 126, 132, 144, 198, 215
\eolgrab	2, 7, 12, 17, 29, 30, 31, 32, 33, 38, 39, 186
\eolgrab@	200, 223
\eolgrab@AtEnd	150, 151, 164, 236
\eolgrab@ifdefinable ..	173, 186, 203
\eolgrab@opt	217, 227
\eolgrabopt	2, 40, 203
\eoloptsection	10, 16
\eolsection	5, 22, 23, 24
I	
\ifx	70, 73, 76, 105, 113, 116, 166
\immediate	78, 107
\input	167, 168
\Item	40, 43, 45, 49, 51
\item	40
L	
\ltx@active	199, 216, 221
\ltx@backslashchar	177
\ltx@firstofone	222
\ltx@ifempty	229
\ltx@IfUndefined .	173, 187, 188, 204, 205
\ltx@ifundefined	175
M	
\makeatletter	4
\makeatother	19
N	
\newcommand .	5, 16, 38, 39, 40, 191, 208
P	
\PackageInfo	81
\protected	195, 212
\ProvidesPackage	74, 122
R	
\RequirePackage	28, 170, 171
S	
\section	7, 12, 17, 31
T	
\tableofcontents	21
\the	132, 133, 134, 135, 136, 137, 138, 139, 152
\TMP@EnsureCode	149, 156, 157, 158, 159, 160, 161, 162, 163
U	
\usepackage	3, 37
W	
\write	78, 107
X	
\x	69, 70, 73, 77, 81, 83, 106, 111, 121, 130, 142