

A L^AT_EX Package to Prepare Author and Affiliation Blocks

Patrick W. Daly

This paper describes L^AT_EX_{2 ϵ} package `authblk`
version 1.3 from 2001/02/27

*It is part of the **preprint** collection of packages*

Summary

The stripped version of this file contains the following brief description:

```
% A LaTeX2e package to redefine the \author command to work as normal or
% to allow a footnote style of author/affiliation input.
%
% Three methods of input:
% 1. Standard LaTeX
%   \author{Name1\\Affil1 /and Name2 and Name3\\Affil2 . . .}
% (use \authorcr, not \\, to force new line within the author text)
% 2. Automatic mode (selects modes 1 or 3 depending on number of affiliations)
%   \author{Name1}
%   \affil{Affil1}
%   \author{Name2}
%   \author{Name3}
%   \affil{Affil2}
%   . . .
% 3. Footnotes explicitly
%   \author[*]{Name1}
%   \author[**]{Name2}
%   \author[**]{Name3}
%   \affil[*]{Affil1}
%   \affil[**]{Affil2}
%   . . .
```

1 Introduction

The standard L^AT_EX syntax for entering author names and their affiliations is rather limited. The standard is to have *author blocks* consisting of all authors from one institute grouped together. However, if there are many

institutes, or if the authors are ordered in some other way (e.g. alphabetically) it is more appropriate to use a footnote system. Both methods should be available for any paper since the style depends more on the number of authors and affiliations and their mixture.

This package offers a syntax for entering author names and their affiliations that permits both styles, and is also compatible with the standard L^AT_EX syntax. It places its results in the control sequence `\@author`, which is the standard container for the author/affiliation names; in this way it can be used immediately with standard L^AT_EX classes, or with packages that modify the title/author block.

2 Invoking the Package

The macros in this package are included in the main document with the `\usepackage` command of L^AT_EX 2_ε,

```
\documentclass[...]{...}
\usepackage[options]{authblk}
```

where the possible *options* are described below in Section 5.

3 Usage

Authors and affiliations can be printed in author blocks, as

J. B. Smith
Institute for Research
Hamilton, Ontario
C. T. Appleton and P. R. Bailey
NASA, Greenbelt, MD

or in a line with footnote markers for the affiliations, as

J. B. Smith¹, C. T. Appleton², and P. R. Bailey²
¹Institute for Research, Hamilton, Ontario
²NASA, Greenbelt, MD

`\author` The user can enter the author and affiliation information in a number
`\affil` of different manners.

1. Standard L^AT_EX, with syntax

```
\author{... \and... \and... }
```

where each block of author(s)/affiliation comes between the `\and` commands, containing possibly `\\` for new lines;

2. Automatic switching between author block or footnote style, information input with a series of `\author`, `\affil` commands as

```

\author{author1}
\author{author2}
\affil{affil1}
\author{author3}
\author{author4}
\affil{affil2}
...

```

where the authors will appear all in one (possibly continued) line with automatic footnotes, and the affiliations appear in separate lines below;

3. Footnote style with manual footnote markers given as optional arguments; in this case, the `\author` and `\affil` commands can be fully separated:

```

\author[1]{author1}
\author[1]{author2}
\author[2]{author3}
\author[2]{author4}
\affil[1]{affil1}
\affil[2]{affil2}
...

```

Method 1 can only produce author blocks; method 3 only footnotes, while 2 can produce both. If the number of affiliations is greater than `Maxaffil`, footnotes are used, otherwise author blocks.

`\authorcr` With method 1, the `\` command is used to switch to affiliation text, possibly changing the font; if the author text is to be forced to a new line, use `\authorcr` instead.

Warning: methods 2 and 3 can only be used *after* `authblk` has been loaded, since `\affil` is otherwise not defined. However, a single `\author` command (method 1) can appear before `\usepackage`, or even before `\documentclass`, as is allowed in standard L^AT_EX.

4 Configuration

Certain aspects of the author/affiliation blocks can be controlled by the user through redefinitions.

`Maxaffil` As already mentioned, the maximum number of affiliations before automatically switching from author block to footnote mode is set in the counter `Maxaffil`. Redefine this with

```
\setcounter{Maxaffil}{2}
```

The default is 2.

`\Authfont` The author and affiliation lines can be set in different fonts, determined
`\Affilfont` by these macros. By default they are `\normalfont`. Redefine them with
`\renewcommand`, for example:

```
\renewcommand\Authfont{\scshape}
\renewcommand\Affilfont{\itshape\small}
```

`\affilsep` The interline spacing between the author and affiliation lines is set by
the length `\affilsep`. Change this with `\setlength`, as

```
\setlength{\affilsep}{1em}
```

This spacing applies to both footnote and author block modes.

`\Authsep` In footnote mode, one can change the texts that comes between the
`\Authand` authors' names, between two authors, and before the last author when
`\Authands` there are more than two. For example,

```
\renewcommand\Authsep{, }
\renewcommand\Authand{ and }
\renewcommand\Authands{, and }
```

This example actually shows the defaults.

5 Options during Loading

Some reconfigurations are provided for by means of options to the `\usepackage` command. These are:

`blocks` sets `Maxaffil` to ∞ so that the automatic selection will always be author/affiliation blocks;

`noblocks` sets `Maxaffil` to 0 so that the automatic selection will always be footnote mode;

`maxn` ($n = 2, 6$) sets `Maxaffil` to n ;

`auth-sc` sets author font to small caps;

`auth-sc-lg` sets author font to small caps, but with size `\large`;

`auth-lg` sets author font to normal, but in size `\large`;

`affil-sl` sets affiliation font to slanted;

`affil-it` sets affiliation font to italic;

`german` changes 'and' to 'und' in author lists.