

# Package ‘myvariant’

October 24, 2025

**Type** Package

**Title** Accesses MyVariant.info variant query and annotation services

**Version** 1.39.1

**Date** 2025-07-22

**Author** Adam Mark

**Maintainer** Adam Mark, Chunlei Wu <cwu@scripps.edu>

**Description** MyVariant.info is a comprehensive aggregation of variant annotation resources. myvariant is a wrapper for querying MyVariant.info services

**License** Artistic-2.0

**Depends** R (>= 3.2.1), VariantAnnotation

**Imports** httr, jsonlite, S4Vectors, Hmisc, plyr, magrittr, Seqinfo, GenomeInfoDb

**Suggests** BiocStyle

**biocViews** VariantAnnotation, Annotation, GenomicVariation

**NeedsCompilation** no

**git\_url** <https://git.bioconductor.org/packages/myvariant>

**git\_branch** devel

**git\_last\_commit** 236c7a9

**git\_last\_commit\_date** 2025-07-22

**Repository** Bioconductor 3.23

**Date/Publication** 2025-10-24

## Contents

|                            |   |
|----------------------------|---|
| formatHgvs . . . . .       | 2 |
| formatSingleHgvs . . . . . | 3 |
| getVariant . . . . .       | 4 |
| getVariants . . . . .      | 5 |
| metadata . . . . .         | 6 |

|                           |           |
|---------------------------|-----------|
| MyVariant . . . . .       | 7         |
| myvariant . . . . .       | 7         |
| MyVariant-class . . . . . | 8         |
| queryVariant . . . . .    | 9         |
| queryVariants . . . . .   | 10        |
| <b>Index</b>              | <b>11</b> |

---

|            |                                          |
|------------|------------------------------------------|
| formatHgvs | <i>Get all HGVS IDs from Vcf object.</i> |
|------------|------------------------------------------|

---

**Description**

Read in a Vcf object created by [readVcf](#) to extract all HGVS IDs for querying MyVariant.info.

**Usage**

```
formatHgvs(vcf, variant_type = c("snp", "insertion", "deletion"))
```

**Arguments**

|              |                                                                                                 |
|--------------|-------------------------------------------------------------------------------------------------|
| vcf          | Vcf object created by <a href="#">readVcf</a> .                                                 |
| variant_type | Type of variant HGVS IDs to retrieve from Vcf object. Default c("snp", "insertion", "deletion") |

**Value**

vector

**References**

<https://myvariant.info> <http://www.hgvs.org/mutnomen/recs-DNA.html>

**See Also**

[formatSingleHgvs](#)

**Examples**

```
## return HGVS IDs for all snps in a Vcf
file.path <- system.file("extdata", "dbsnp_mini.vcf", package="myvariant")
vcf <- readVcf(file.path, genome="hg19")
hgvs <- formatHgvs(vcf, variant_type="snp")
```

---

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| formatSingleHgvs | <i>Get Hgvs HGVS ID from chromosome, position, reference and alternate alleles.</i> |
|------------------|-------------------------------------------------------------------------------------|

---

## Description

Create a single HGVS ID for a variant from chromosome, position, reference and alternate alleles.

## Usage

```
formatSingleHgvs(chrom, pos, ref, alt, mutant_type=FALSE)
```

## Arguments

|             |                                                                                   |
|-------------|-----------------------------------------------------------------------------------|
| chrom       | Chromosome.                                                                       |
| pos         | Position of the variant on the reference genome (hg19).                           |
| ref         | Reference allele.                                                                 |
| alt         | Alternate allele.                                                                 |
| mutant_type | Logical indicating whether to return the type of mutation along with the HGVS ID. |

## Value

returns a string

## References

<https://myvariant.info> <http://www.hgvs.org/mutnomen/recs-DNA.html>

## See Also

[formatHgvs](#)

## Examples

```
## return HGVS ID for a variant
formatSingleHgvs(1, 35367, "G", "A")
```

---

|            |                                                         |
|------------|---------------------------------------------------------|
| getVariant | <i>Return the variant object for the given HGVS id.</i> |
|------------|---------------------------------------------------------|

---

## Description

This is a wrapper for GET query of `"/variant/<hgvsid>"` service.

## Usage

```
getVariant(hgvsid, fields=NULL,
           ..., return.as=c("records", "text"), myvariant)
```

## Arguments

|           |                                                                                                                                                                                                                         |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| hgvsid    | HGVS id                                                                                                                                                                                                                 |
| fields    | Fields to return, a list of a comma-sep string. If fields=="all", all available fields are returned.                                                                                                                    |
| ...       |                                                                                                                                                                                                                         |
| return.as | "records" (list), "text" (JSON).                                                                                                                                                                                        |
| myvariant | A MyVariant object that describes how to connect to data resources. See <a href="#">MyVariant-class</a> . If missing, default object will be used that accesses the main MyVariant.info portal. Default is recommended. |

## Value

returns a variant object containing the queried annotations

## References

[http://docs.myvariant.info/en/latest/doc/variant\\_annotation\\_service.html#get-request](http://docs.myvariant.info/en/latest/doc/variant_annotation_service.html#get-request) <http://docs.myvariant.info/en/latest/doc/parameters>

## See Also

[getVariants](#) [queryVariant](#) [queryVariants](#)

## Examples

```
## return the variant object for the given HGVS id
getVariant("chr7:g.55241707G>T")

## customize fields
getVariant("chr7:g.55241707G>T",
           fields=c("dbnsfp.cadd.phred", "dbnsfp.polyphen2"),
           return.as="text")
```

---

|             |                                                                           |
|-------------|---------------------------------------------------------------------------|
| getVariants | <i>Return the list of variant objects for the given list of HGVS ids.</i> |
|-------------|---------------------------------------------------------------------------|

---

## Description

This is a wrapper for POST query of "/variant" service.

## Usage

```
getVariants(hgvsids, fields=NULL, verbose=NULL, ...,
            return.as=c("DataFrame", "records", "text"), myvariant)
```

## Arguments

|           |                                                                                                                                                                                                                            |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| hgvsids   | A vector, list, or comm-sep string HGVS ids                                                                                                                                                                                |
| fields    | A vector of fields to return. If fields=="all", all available fields are returned.                                                                                                                                         |
| verbose   | A logical turning on or off process status messages. Default = TRUE.                                                                                                                                                       |
| ...       |                                                                                                                                                                                                                            |
| return.as | "DataFrame" (default), "records" (list), "text" (JSON).                                                                                                                                                                    |
| myvariant | A MyVariant object that describes how to connect to data resources. See <a href="#">MyVariant-class</a> .<br>If missing, default object will be used that accesses the main MyVariant.info portal. Default is recommended. |

## Value

returns a variant object (DataFrame, list, or JSON text) containing the queried annotations

## References

[http://docs.myvariant.info/en/latest/doc/variant\\_annotation\\_service.html#batch-queries-via-post](http://docs.myvariant.info/en/latest/doc/variant_annotation_service.html#batch-queries-via-post) [http://docs.myvariant.info/en/latest/doc/variant\\_annotation\\_service.html#batch-queries-via-post](http://docs.myvariant.info/en/latest/doc/variant_annotation_service.html#batch-queries-via-post)

## See Also

[getVariants](#) [queryVariant](#) [queryVariants](#)

## Examples

```
## given a list of HGVS ids
vars <- c('chr1:g.866422C>T',
          'chr1:g.876664G>A',
          'chr1:g.69635G>C',
          'chr1:g.69869T>A',
          'chr1:g.881918G>A',
          'chr1:g.865625G>A',
          'chr1:g.879368C>A',
          'chr1:g.889226C>T',
          'chr1:g.879492C>G',
```

```
'chr1:g.879423T>G',  
'chr1:g.881602C>T',  
'chr1:g.879115C>G',  
'chr1:g.69892T>C',  
'chr1:g.879381C>T',  
'chr1:g.878330C>G')  
  
## Return the list of variant object for the given list of HGVS ids.  
df <- getVariants(vars, fields="dbSNP, welllderly")
```

---

metadata

*metadata*

---

## Description

Get metadata for MyVariant.info services.

## Usage

```
metadata(x, ...)
```

## Arguments

|     |                                  |
|-----|----------------------------------|
| x   | MyVariant object                 |
| ... | MyVariant object slot parameters |

## Value

returns the metadata including available databases and number of documents.

## References

<http://myvariant.info/v1/metadata>

## Examples

```
## Get metadata  
myvariant<-MyVariant()  
metadata(myvariant)
```

---

**MyVariant***MyVariant*

---

**Description**

Construct a MyVariant object.

**Usage**

```
MyVariant(...)
```

**Arguments**

... See help page for MyVariant-class

**Value**

MyVariant object

**Examples**

```
MyVariant()
```

---

**myvariant***Access MyVariant.info variant annotation services*

---

**Description**

MyVariant.Info provides REST web services to query/retrieve variant annotations. myvariant is an easy-to-use R wrapper to access MyVariant.info services.

**Details**

|          |                     |
|----------|---------------------|
| Package: | myvariant           |
| Type:    | Package             |
| Version: | 0.99.0              |
| Date:    | 2014-12-18          |
| License: | Artistic-2.0        |
| Depends: | httr jsonlite Hmisc |

**Author(s)**

Adam Mark

Maintainer: Adam Mark <adammark@scripps.edu>

**References**

<https://github.com/Network-of-BioThings/myvariant.info/wiki>

---

|                 |                          |
|-----------------|--------------------------|
| MyVariant-class | <i>Class "MyVariant"</i> |
|-----------------|--------------------------|

---

**Description**

R Client to access MyVariant.Info annotation services

**Objects from the Class**

Objects can be created by calls of the form `MyVariant(base.url="http://myvariant.info/v1", delay=1, step=1000, version=version, verbose=TRUE, debug=FALSE)`.

**Slots**

`base.url`: "http://myvariant.info/v1". Object of class "character"  
`delay`: Sleep time between batch retrieval. Object of class "numeric"  
`step`: Batch limit. Object of class "numeric"  
`version`: httr package version. Object of class "character"  
`verbose`: Object of class "logical"  
`debug`: Object of class "logical"

**Methods**

`getVariant(hgvsid, fields=NULL, ..., return.as=c("records", "text"))`: Return the variant object for the given hgvsid  
`getVariants(hgvsids, fields=NULL, ..., return.as=c("DataFrame", "records", "text"))`: Return the list of variant object for the given list of hgvsids.  
`queryVariant(q, fields=NULL, ..., return.as=c("DataFrame", "records", "text"))`: Return the query result.  
`queryVariants(qterms, scopes=NULL, fields=NULL, ..., return.as=c("DataFrame", "records", "text"))`: Return the batch query result.

**Author(s)**

Adam Mark

References

<https://github.com/Network-of-BioThings/myvariant.info/wiki>

Examples

```
showClass("MyVariant")
```

---

|              |                                 |
|--------------|---------------------------------|
| queryVariant | <i>Return the query result.</i> |
|--------------|---------------------------------|

---

Description

This is a wrapper for GET query of "/query?q=<query>" service.

Usage

```
queryVariant(q, ..., return.as=c("DataFrame", "records", "text"),
             myvariant)
```

Arguments

- |           |                                                                                                                                                                                                                         |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| q         | query term(s).                                                                                                                                                                                                          |
| ...       | Commonly queried fields include fields, size as well as several other fields. View available fields by calling ?metadata.                                                                                               |
| return.as | "DataFrame" (default), "records" (list), or "text" (JSON).                                                                                                                                                              |
| myvariant | A MyVariant object that describes how to connect to data resources. See <a href="#">MyVariant-class</a> . If missing, default object will be used that accesses the main MyVariant.info portal. Default is recommended. |

Value

returns a variant object (DataFrame, list, or JSON text) containing the queried annotations

References

[http://docs.myvariant.info/en/latest/doc/variant\\_query\\_service.html#get-request](http://docs.myvariant.info/en/latest/doc/variant_query_service.html#get-request) [http://docs.myvariant.info/en/latest/doc/variant\\_query\\_syntax](http://docs.myvariant.info/en/latest/doc/variant_query_syntax)

See Also

[queryVariants](#) [getVariant](#) [getVariants](#)

Examples

```
## return the query result
queryVariant("dbnsfp.variantname:BRCA2")

queryVariant("chr1:1-1000000")
```

---

|               |                                       |
|---------------|---------------------------------------|
| queryVariants | <i>Return the batch query result.</i> |
|---------------|---------------------------------------|

---

### Description

This is a wrapper for POST query of "/query" service.

### Usage

```
queryVariants(qterms, scopes=NULL, ...,
              return.as=c("DataFrame", "records", "text"),
              myvariant)
```

### Arguments

|           |                                                                                                                                                                                                                                   |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| qterms    | A vector or list, or string of comma-separated query terms                                                                                                                                                                        |
| scopes    | Type of types of identifiers, either a list or a comma-separated fields to specify type of input qterms.                                                                                                                          |
| ...       | Commonly queried fields include fields, size as well as several other fields. returnall returns a list of all related data including duplicated and missing qterms. False by default. View available fields by calling ?metadata. |
| return.as | "DataFrame" (default), "records" (list), "text" (JSON).                                                                                                                                                                           |
| myvariant | A MyVariant object that describes how to connect to data resources. See <a href="#">MyVariant-class</a> . If missing, default object will be used that accesses the main MyVariant.info portal. Default is recommended.           |

### Value

returns a variant object (DataFrame, list, or JSON text) containing the queried annotations

### References

[http://docs.myvariant.info/en/latest/doc/variant\\_query\\_service.html#batch-queries-via-post](http://docs.myvariant.info/en/latest/doc/variant_query_service.html#batch-queries-via-post) [http://docs.myvariant.info/en/latest/doc/variant\\_query\\_service.html#batch-queries-via-post](http://docs.myvariant.info/en/latest/doc/variant_query_service.html#batch-queries-via-post)

### See Also

[queryVariant](#) [getVariant](#) [getVariants](#)

### Examples

```
## return the batch query result
```

# Index

## \* **classes**

MyVariant-class, [8](#)

## \* **package**

myvariant, [7](#)

formatHgvs, [2](#), [3](#)

formatSingleHgvs, [2](#), [3](#)

getVariant, [4](#), [9](#), [10](#)

getVariant,missing-method (getVariant),  
[4](#)

getVariant,MyVariant-method  
(getVariant), [4](#)

getVariants, [4](#), [5](#), [5](#), [9](#), [10](#)

getVariants,missing-method  
(getVariants), [5](#)

getVariants,MyVariant-method  
(getVariants), [5](#)

metadata, [6](#)

metadata,MyVariant-method (metadata), [6](#)

MyVariant, [7](#)

myvariant, [7](#)

MyVariant-class, [8](#)

queryVariant, [4](#), [5](#), [9](#), [10](#)

queryVariant,missing-method  
(queryVariant), [9](#)

queryVariant,MyVariant-method  
(queryVariant), [9](#)

queryVariants, [4](#), [5](#), [9](#), [10](#)

queryVariants,missing-method  
(queryVariants), [10](#)

queryVariants,MyVariant-method  
(queryVariants), [10](#)

readVcf, [2](#)