

# Package ‘agcounts’

July 22, 2025

**Type** Package

**Title** Calculate 'ActiGraph' Counts from Accelerometer Data

**Version** 0.6.6

**Description** Calculate 'ActiGraph' counts from the X, Y, and Z axes of a triaxial accelerometer. This work was inspired by Neishabouri et al. who published the article ``Quantification of Acceleration as Activity Counts in 'ActiGraph' Wearables'' on February 24, 2022. The link to the article (<<https://pubmed.ncbi.nlm.nih.gov/35831446>>) and 'python' implementation of this code (<<https://github.com/actigraph/agcounts>>).

**Depends** R (>= 3.5.0)

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**Imports** data.table, gsignal, lubridate, magrittr, Rcpp, GGIR, stats, utils, zoo, reticulate, dplyr, stringr, ggplot2, reactable, shiny, bslib, read.gt3x, DBI, RSQLite

**Suggests** parallel, devtools, foreach, testthat (>= 3.0.0), shinytest2, covr

**Config/testthat/edition** 3

**LinkingTo** Rcpp, RcppArmadillo

**NeedsCompilation** yes

**Author** Brian C. Helsel [aut, cre],  
Paul R. Hibbing [ctb],  
Robert N. Montgomery [ctb],  
Eric D. Vidoni [ctb],  
Jonathan Clutton [ctb],  
University of Kansas [cph]

**Maintainer** Brian C. Helsel <bhelsel@kumc.edu>

**Repository** CRAN

**Date/Publication** 2024-02-29 20:12:36 UTC

## Contents

agcalibrate . . . . .	2
agcounts . . . . .	3
agread . . . . .	3
agShinyDeployApp . . . . .	4
calculate_counts . . . . .	5
get_counts . . . . .	5
<b>Index</b>	<b>7</b>

---

agcalibrate	<i>Calibrate acceleration data</i>
-------------	------------------------------------

---

### Description

This function uses a C++ implementation of the GGIR ‘g.calibrate’ function.

### Usage

```
agcalibrate(raw, verbose = FALSE, tz = "UTC", ...)
```

### Arguments

raw	data frame of raw acceleration data obtained from
verbose	Print the progress of the calibration for the raw data, Default: FALSE
tz	the desired timezone, Default: UTC
...	Additional arguments to pass into the agreed function

### Details

This function uses a C++ implementation of the GGIR ‘g.calibrate’ function to return calibrated raw acceleration data.

### Value

Returns the calibrated raw acceleration data

### See Also

[force\\_tz](#)

### Examples

```
path <- system.file("extdata/example.gt3x", package = "agcounts")
data <- read.gt3x::read.gt3x(path, asDataFrame = TRUE)
data <- agcalibrate(raw = data)
```

---

agcounts	<i>agcounts: R Package for Extracting Actigraphy Counts from Accelerometer Data.</i>
----------	--

---

### Description

This R Package reads the X, Y, and Z axes in a GT3X accelerometer file and converts it to Actigraphy counts. This work was inspired by Neishabouri et al. who published the article "Quantification of Acceleration as Activity Counts in ActiGraph Wearables on February 24, 2022. The [link to the article](#) and Python implementation of this code <https://github.com/actigraph/agcounts>.

### agcounts functions

[get\\_counts](#)  
[calculate\\_counts](#)  
[agShinyDeployApp](#)

---

agread	<i>Read in raw acceleration data</i>
--------	--------------------------------------

---

### Description

This function reads in raw acceleration data with the pygt3x Python package, the read.gt3x R package with GGIR autocalibration, or the read.gt3x R package.

### Usage

```
agread(
  path,
  parser = c("pygt3x", "GGIR", "read.gt3x"),
  tz = "UTC",
  verbose = FALSE,
  ...
)
```

### Arguments

path	Path name to the GT3X file or the dataset with columns time, X, Y, and Z axis
parser	The parser to use when reading in the data. Parser values include pygt3x, GGIR, and read.gt3x options.
tz	the desired timezone, Default: UTC
verbose	Print the read method, Default: FALSE.
...	Additional arguments to pass into the agreed function

**Details**

This function reads in raw acceleration data with the pygt3x Python package, the read.gt3x R package with GGIR autocalibration, or the read.gt3x R package.

**Value**

Returns the raw acceleration data

**See Also**

[g.calibrate read.gt3x](#)

**Examples**

```
agread(system.file("extdata/example.gt3x", package = "agcounts"), parser = "pygt3x")
```

---

agShinyDeployApp	<i>agShinyDeployApp</i>
------------------	-------------------------

---

**Description**

This function deploys the agcounts Shiny app.

**Usage**

```
agShinyDeployApp(...)
```

**Arguments**

... arguments passed to [bs\\_theme](#)

**Details**

This function deploys the agcounts Shiny app for data visualization and exploration. It also provides an opportunity to compare ActiGraph counts generated from the agcounts package with those from ActiGraph's .agd files.

**Value**

Deploys a Shiny app on localhost. No data or values are returned.

**See Also**

[fluidPage](#), [titlePanel](#), [reexports](#), [shinyApp](#) [bs\\_theme](#)

---

calculate_counts	<i>calculate_counts</i>
------------------	-------------------------

---

### Description

Calculate ActiGraph activity counts from raw acceleration data by passing in a data frame with a time stamp, X, Y, and Z axis. This function allows the ability to work with the raw data from other files, but the data frame needs to have "start\_time" and "stop\_time" attributes. This is different from the [get\\_counts](#) function because it reads a raw data frame rather than a path name to a GT3X file.

### Usage

```
calculate_counts(raw, epoch, lfe_select = FALSE, tz = "UTC", verbose = FALSE)
```

### Arguments

raw	data frame of raw acceleration data obtained from <a href="#">read.gt3x</a>
epoch	The epoch length for which the counts should be summed.
lfe_select	Apply the Actigraph Low Frequency Extension filter, Default: FALSE
tz	the desired timezone, Default: UTC
verbose	Print the progress of the Actigraph raw data conversion to counts, Default: FALSE.

### Value

Returns a data.frame containing the ActiGraph count values

### Examples

```
f <- system.file("extdata/example.gt3x", package = "agcounts")
d <- read.gt3x::read.gt3x(f, asDataFrame = TRUE, imputeZeroes = TRUE)
calculate_counts(d, 60)
```

---

get_counts	<i>get_counts</i>
------------	-------------------

---

### Description

Main function to extract counts from the Actigraph GT3X Files.

**Usage**

```

get_counts(
  path,
  epoch,
  lfe_select = FALSE,
  write.file = FALSE,
  return.data = TRUE,
  verbose = FALSE,
  tz = "UTC",
  parser = c("pygt3x", "GGIR", "read.gt3x"),
  ...
)

```

**Arguments**

path	Full path name to the GT3X File
epoch	The epoch length for which the counts should be summed.
lfe_select	Apply the Actigraph Low Frequency Extension filter, Default: FALSE
write.file	Export a CSV file of the counts, Default: FALSE
return.data	Return the data frame to the R Global Environment, Default: TRUE
verbose	Print the progress of the Actigraph raw data conversion to counts, Default: FALSE.
tz	the desired timezone, Default: UTC
parser	The parser to use when reading in the data. Parser values include pygt3x, GGIR, and read.gt3x options.
...	arguments passed to <a href="#">fwrite</a>

**Details**

Main function to extract counts from the Actigraph GT3X Files.

**Value**

Writes a CSV file if write.file is TRUE and returns a data.frame if return.data is TRUE

**See Also**

[read.gt3x](#)

**Examples**

```

get_counts(
  path = system.file("extdata/example.gt3x", package = "agcounts"),
  epoch = 60, lfe_select = FALSE,
  write.file = FALSE, return.data = TRUE
)

```

# Index

agcalibrate, 2  
agcounts, 3  
agread, 3  
agShinyDeployApp, 3, 4  
  
bs\_theme, 4  
  
calculate\_counts, 3, 5  
  
fluidPage, 4  
force\_tz, 2  
fwrite, 6  
  
g.calibrate, 4  
get\_counts, 3, 5, 5  
  
read.gt3x, 4–6  
reexports, 4  
  
shinyApp, 4  
  
titlePanel, 4