

Package ‘rcssci’

February 15, 2023

Type Package

Title Visualization of Restricted Cubic Splines

Version 0.4.0

Maintainer Zhiqiang Nie <niezhiqiang@gdph.org.cn>

Description Restricted Cubic Splines were performed to explore the shape of association form of ``U, inverted U, L" shape and test linearity or non-linearity base on ``Cox,Logistic,linear,quasipoisson" regression, and auto output Restricted Cubic Splines figures. rcssci package could automatically draw RCS graphics with Y-axis ``OR,HR,RR,beta". The Restricted Cubic Splines method were based on Suli Huang (2022) <[doi:10.1016/j.ecoenv.2022.113183](https://doi.org/10.1016/j.ecoenv.2022.113183)>, Amit Kaura (2019) <[doi:10.1136/bmj.l6055](https://doi.org/10.1136/bmj.l6055)>, and Harrell Jr (2015, ISBN:978-3-319-19424-0 (Print) 978-3-319-19425-7 (Online)).

Depends R (>= 4.2.0)

LazyData true

Imports pacman, rms, ggplot2, survminer, segmented, survival, dplyr, patchwork, Cairo

Encoding UTF-8

License Artistic-2.0

BugReports <https://github.com/popnie/RCSSci/issues>

RoxygenNote 7.2.1

NeedsCompilation no

Author Zhiqiang Nie [aut, cre, cph] (ORCID = 0000-0001-7642-3286, wechat = Biostatistics-SCI), JunZhang [ctb], Chaolei Chen [ctb]

Repository CRAN

Date/Publication 2023-02-15 21:20:02 UTC

R topics documented:

ressci_cox	2
rcssci_linear	3
rcssci_logistic	4
ressci_quasipoisson	5
rcs_cox.lshap	6
rcs_cox.nshap	7
rcs_cox.prob	8
rcs_cox.ushap	9
rcs_linear.lshap	10
rcs_linear.nshap	11
rcs_linear.prob	12
rcs_linear.ushap	13
rcs_logistic.lshap	14
rcs_logistic.nshap	15
rcs_logistic.prob	16
rcs_logistic.ushap	17
rcs_quasipoisson.lshap	18
rcs_quasipoisson.nshap	19
rcs_quasipoisson.prob	20
rcs_quasipoisson.ushap	21
sbpdata	22

Index	23
--------------	-----------

rcssci_cox	<i>rcssci_cox</i>
-------------------	-------------------

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	censor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcssci_cox(data=sbpdata, y = "status",x = "sbp",time = "time",
prob=0.1,filepath=tempdir()
# library(rcssci)
# rcssci_cox(knot=4,data=sbpdata, y = "status",x = "sbp",covs=c("age"),
# time = "time", prob=0.1,filepath="D:/temp")
```

rcssci_linear

rcssci_linear

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariates, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcssci_linear(data=sbpdata, y = "sbp",x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcssci_linear(knot=4,data=sbpdata, y = "sbp",x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

rcssci_logistic *rcssci_logistic*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcssci_logistic(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcssci_logistic(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcssci_quasipoisson rcssci_quasipoisson

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

quasipoisson models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcssci_quasipoisson(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcssci_quasipoisson(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

`rcs_cox.lshap` *rcs_cox.lshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

<code>data</code>	<code>data.frame.Rdata</code>
<code>knot</code>	<code>knot=3-7</code> or automatic calculate by AIC min
<code>y</code>	<code>outcome=0,1</code>
<code>time</code>	censor time
<code>covs</code>	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
<code>prob</code>	position parameter,range from 0-1
<code>x</code>	main exposure and X-axis when plotting
<code>filepath</code>	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

`message.print` PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_cox.lshap(data=sbpdata, y = "status",x = "sbp",time = "time",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_cox.lshap(knot=4,data=sbpdata, y = "status",x = "sbp",covs=c("age"),
# time = "time", prob=0.1,filepath="D:/temp")
```

rcs_cox.nshap *rcs_cox.nshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	censor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_cox.nshap(data=sbpdata, y = "status",x = "sbp",time = "time",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_cox.nshap(knot=4,data=sbpdata, y = "status",x = "sbp",covs=c("age"),
# time = "time", prob=0.1,filepath="D:/temp")
```

rcs_cox.prob *rcs_cox.prob*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	censor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_cox.prob(data=sbpdata, y = "status",x = "sbp",time = "time",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_cox.prob(knot=4,data=sbpdata, y = "status",x = "sbp",covs=c("age"),
# time = "time", prob=0.1,filepath="D:/temp")
```

rcs_cox.ushap *rcs_cox.ushap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	censor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_cox.ushap(data=sbpdata, y = "status",x = "sbp",time = "time",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_cox.ushap(knot=4,data=sbpdata, y = "status",x = "sbp",covs=c("age"),
# time = "time", prob=0.1,filepath="D:/temp")
```

`rcs_linear.lshap` *rcs_linear.lshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_linear.lshap(data=sbpdata, y = "sbp",x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_linear.lshap(knot=4,data=sbpdata, y = "sbp",x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

rcs_linear.nshap *rcs_linear.nshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_linear.nshap(data=sbpdata, y = "sbp",x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci
# rcs_linear.nshap(knot=4,data=sbpdata, y = "sbp",x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

`rcs_linear.prob` *rcs_linear.prob*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

<code>data</code>	<code>data.frame.Rdata</code>
<code>knot</code>	<code>knot=3-7</code> or automatic calculate by AIC min
<code>y</code>	<code>outcome=0,1</code>
<code>covs</code>	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
<code>prob</code>	position parameter,range from 0-1
<code>x</code>	main exposure and X-axis when plotting
<code>filepath</code>	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

`message.print` PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhizhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_linear.prob(data=sbpdata, y = "sbp", x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_linear.prob(knot=4,data=sbpdata, y = "sbp",x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

rcs_linear.ushap

rcs_linear.ushap

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_linear.ushap(data=sbpdata, y = "sbp",x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_linear.ushap(knot=4,data=sbpdata, y = "sbp",x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

rcs_logistic.lshap *rcs_logistic.lshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_logistic.lshap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_logistic.lshap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcs_logistic.nshap *rcs_logistic.nshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_logistic.nshap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_logistic.nshap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

`rcs_logistic.prob` *rcs_logistic.prob*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

<code>data</code>	<code>data.frame.Rdata</code>
<code>knot</code>	<code>knot=3-7</code> or automatic calculate by AIC min
<code>y</code>	<code>outcome=0,1</code>
<code>covs</code>	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
<code>prob</code>	position parameter,range from 0-1
<code>x</code>	main exposure and X-axis when plotting
<code>filepath</code>	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

`message.print` PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhizhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_logistic.prob(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_logistic.prob(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcs_logistic.ushap rcs_logistic.ushap

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_logistic.ushap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_logistic.ushap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcs_quasipoisson.lshap
rcs_quasipoisson.lshap

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

quasipoisson models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_quasipoisson.lshap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_quasipoisson.lshap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcs_quasipoisson.nshap
rcs_quasipoisson.nshap

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

quasipoisson models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_quasipoisson.nshap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_quasipoisson.nshap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcs_quasipoisson.prob rcs_quasipoisson.prob

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

quasipoisson models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_quasipoisson.prob(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_quasipoisson.prob(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcs_quasipoisson.ushap
rcs_quasipoisson.ushap

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

quasipoisson models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_quasipoisson.ushap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_quasipoisson.ushap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

sbpdata *A data on sbp and status.*

Description

A data on sbp and status.

Usage

```
data(sbpdata)
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 3621 rows and 5 columns.

Examples

```
data(sbpdata)
```

Index

* datasets

`sbpdata`, 22

`rcs_cox.lshap`, 6
`rcs_cox.nshap`, 7
`rcs_cox.prob`, 8
`rcs_cox.ushap`, 9
`rcs_linear.lshap`, 10
`rcs_linear.nshap`, 11
`rcs_linear.prob`, 12
`rcs_linear.ushap`, 13
`rcs_logistic.lshap`, 14
`rcs_logistic.nshap`, 15
`rcs_logistic.prob`, 16
`rcs_logistic.ushap`, 17
`rcs_quasipoisson.lshap`, 18
`rcs_quasipoisson.nshap`, 19
`rcs_quasipoisson.prob`, 20
`rcs_quasipoisson.ushap`, 21
`rcssci_cox`, 2
`rcssci_linear`, 3
`rcssci_logistic`, 4
`rcssci_quasipoisson`, 5

`sbpdata`, 22