

Package ‘PortfolioAnalytics’

April 10, 2026

Type Package

Title Portfolio Analysis, Including Numerical Methods for Optimization of Portfolios

Version 2.1.2

Date 2026-04-08

Maintainer Brian G. Peterson <brian@braverock.com>

Description Portfolio optimization and analysis routines and graphics.

Depends R (>= 4.0.0), zoo, xts (>= 0.10-1), foreach, PerformanceAnalytics (>= 1.5.1)

Suggests quantmod, DEoptim (>= 2.2.1), iterators, doParallel, doMC, fGarch, Rglpk, quadprog, ROI (>= 0.1.0), ROI.plugin.glpk (>= 0.0.2), ROI.plugin.quadprog (>= 0.0.2), corpcor, testthat, nloptr (>= 1.0.0), MASS, robustbase, osqp, CVXR, data.table, knitr, rmarkdown, GSE, RobStatTM, PCRA, R.rsp, RPESE, TTR, Matrix

VignetteBuilder R.rsp

Imports methods, GenSA, ROI.plugin.symphony, mco, pso

License GPL-3

URL <https://github.com/braverock/PortfolioAnalytics>

Copyright (c) 2004-2026

RoxygenNote 7.3.3

Encoding UTF-8

NeedsCompilation yes

Author Brian G. Peterson [cre, aut, cph],
Peter Carl [aut, cph],
Ross Bennett [ctb, cph],
Kris Boudt [ctb, cph],
Xinran Zhao [ctb, cph],
R. Douglas Martin [ctb],
Guy Yollin [ctb],
Hezky Varon [ctb],

Xiaokang Feng [ctb],
Yifu Kang [ctb]

Repository CRAN

Date/Publication 2026-04-10 05:10:17 UTC

Contents

PortfolioAnalytics-package	5
ac.ranking	10
add.constraint	11
add.objective	14
add.sub.portfolio	16
applyFUN	17
backtest.plot	18
barplotGroupWeights	19
black.litterman	20
BlackLittermanFormula	21
box_constraint	22
CCCgarch.MM	23
center	24
centroid.buckets	24
centroid.complete.mc	25
centroid.sectors	26
centroid.sign	26
chart.Concentration	27
chart.EF.Weights	28
chart.EfficientFrontier	30
chart.EfficientFrontierCompare	33
chart.EfficientFrontierOverlay	35
chart.GroupWeights	36
chart.RiskBudget	38
chart.RiskReward	40
chart.Weights	43
check_constraints	46
cokurtosisMF	47
cokurtosisSF	47
combine.optimizations	48
combine.portfolios	49
constrained_objective	49
constraint_ROI	51
constraint_v1	52
coskewnessMF	53
coskewnessSF	54
covarianceMF	54
covarianceSF	55
create.EfficientFrontier	56
custom.covRob.Mcd	57

custom.covRob.MM	58
custom.covRob.Rocke	59
custom.covRob.TSGS	59
diversification	60
diversification_constraint	61
EntropyProg	62
equal.weight	63
etl_milp_opt	64
etl_opt	65
extractCokurtosis	65
extractCoskewness	66
extractCovariance	67
extractEfficientFrontier	67
extractGroups	68
extractObjectiveMeasures	69
extractStats	70
extractWeights	71
extract_risk	71
factor_exposure_constraint	72
fn_map	73
generatesequence	74
get_constraints	75
gmw_opt	76
gmw_opt_leverage	77
gmw_opt_ptc	77
gmw_opt_toc	78
group_constraint	79
group_fail	81
HHI	81
indexes	82
insert_constraints	82
insert_objectives	83
inverse.volatility.weight	83
is.constraint	84
is.objective	84
is.portfolio	85
leverage_exposure_constraint	85
maxret_milp_opt	86
maxret_opt	87
meancsm.efficient.frontier	88
meaneqs.efficient.frontier	89
meanetl.efficient.frontier	90
meanrisk.efficient.frontier	91
meanvar.efficient.frontier	92
meucci.moments	93
meucci.ranking	93
minmax_objective	94
mult.portfolio.spec	95

MycovRobMcd	96
MycovRobTSGS	97
name.replace	98
objective	99
opt.outputMvo	100
optimize.portfolio	101
optimize.portfolio.parallel	106
optimize.portfolio.rebalancing	107
pHist	110
plot.optimize.portfolio.DEoptim	111
plotFrontiers	113
portfolio.moments.bl	115
portfolio.moments.boudt	116
portfolio.spec	117
portfolio_risk_objective	118
position_limit_constraint	119
pos_limit_fail	120
print.constraint	121
print.efficient.frontier	121
print.optimize.portfolio.rebalancing	122
print.optimize.portfolio.ROI	122
print.portfolio	123
print.summary.optimize.portfolio	124
print.summary.optimize.portfolio.rebalancing	125
quadratic_utility_objective	125
randomize_portfolio	126
randomize_portfolio_v1	127
random_portfolios	127
random_portfolios_v1	129
random_walk_portfolios	130
regime.portfolios	130
return_constraint	131
return_objective	132
risk_budget_objective	133
rp_grid	134
rp_sample	135
rp_simplex	135
rp_transform	136
scatterFUN	138
set.portfolio.moments	138
set.portfolio.moments_v1	139
statistical.factor.model	140
summary.efficient.frontier	140
summary.optimize.portfolio	141
summary.optimize.portfolio.rebalancing	142
summary.portfolio	142
trailingFUN	143
transaction_cost_constraint	143

turnover	144
turnover_constraint	145
turnover_objective	146
update_constraint	147
update_constraint_v1tov2	147
var.portfolio	148
weight_concentration_objective	149
weight_sum_constraint	150

Index**152**

PortfolioAnalytics-package

*Numeric methods for optimization of portfolios***Description**

PortfolioAnalytics is an R package to provide numerical solutions for portfolio problems with complex constraints and objective sets. The goal of the package is to aid practitioners and researchers in solving portfolio optimization problems with complex constraints and objectives that mirror real-world applications.

One of the goals of the packages is to provide a common interface to specify constraints and objectives that can be solved by any supported solver (i.e. optimization method). Currently supported optimization methods include

- random portfolios
- differential evolution
- particle swarm optimization
- generalized simulated annealing
- linear and quadratic programming routines

The solver can be specified with the `optimize_method` argument in `optimize.portfolio` and `optimize.portfolio.rebalancing`. The `optimize_method` argument must be one of "random", "DEoptim", "pso", "GenSA", "ROI", "quadprog", "glpk", or "symphony".

Additional information on random portfolios is provided below. The differential evolution algorithm is implemented via the DEoptim package, the particle swarm optimization algorithm via the pso package, the generalized simulated annealing via the GenSA package, and linear and quadratic programming are implemented via the ROI package which acts as an interface to the Rglpk, Rsymphony, and quadprog packages.

A key strength of PortfolioAnalytics is the generalization of constraints and objectives that can be solved.

If `optimize_method="ROI"` is specified, a default solver will be selected based on the optimization problem. The `glpk` solver is the default solver for LP and MILP optimization problems. The `quadprog` solver is the default solver for QP optimization problems. For example, `optimize_method = "quadprog"` can be specified and the optimization problem will be solved via ROI using the `quadprog` plugin package.

The extension to ROI solves a limited type of convex optimization problems:

- Maximize portfolio return subject to leverage, box, group, position limit, target mean return, and/or factor exposure constraints on weights.
- Minimize portfolio variance subject to leverage, box, group, turnover, and/or factor exposure constraints (otherwise known as global minimum variance portfolio).
- Minimize portfolio variance subject to leverage, box, group, and/or factor exposure constraints and a desired portfolio return.
- Maximize quadratic utility subject to leverage, box, group, target mean return, turnover, and/or factor exposure constraints and risk aversion parameter. (The risk aversion parameter is passed into `optimize.portfolio` as an added argument to the `portfolio` object).
- Maximize portfolio mean return per unit standard deviation (i.e. the Sharpe Ratio) can be done by specifying `maxSR=TRUE` in `optimize.portfolio`. If both mean and `StdDev` are specified as objective names, the default action is to maximize quadratic utility, therefore `maxSR=TRUE` must be specified to maximize Sharpe Ratio.
- Minimize portfolio ES/ETL/CVaR optimization subject to leverage, box, group, position limit, target mean return, and/or factor exposure constraints and target portfolio return.
- Maximize portfolio mean return per unit ES/ETL/CVaR (i.e. the STARR Ratio) can be done by specifying `maxSTARR=TRUE` in `optimize.portfolio`. If both mean and ES/ETL/CVaR are specified as objective names, the default action is to maximize mean return per unit ES/ETL/CVaR.

These problems also support a `weight_concentration` objective where concentration of weights as measured by HHI is added as a penalty term to the quadratic objective.

Because these convex optimization problem are standardized, there is no need for a penalty term. The `multiplier` argument in `add.objective` passed into the complete constraint object are ignored by the ROI solver.

Many real-world portfolio optimization problems are global optimization problems, and therefore are not suitable for linear or quadratic programming routines. PortfolioAnalytics provides a random portfolio optimization method and also utilizes the R packages DEoptim, pso, and GenSA for solving non-convex global optimization problems.

PortfolioAnalytics supports three methods of generating random portfolios.

- The sample method to generate random portfolios is based on an idea by Pat Burns. This is the most flexible method, but also the slowest, and can generate portfolios to satisfy leverage, box, group, position limit, and leverage constraints.
- The simplex method to generate random portfolios is based on a paper by W. T. Shaw. The simplex method is useful to generate random portfolios with the full investment constraint (where the sum of the weights is equal to 1) and min box constraints. Values for `min_sum` and `max_sum` of the leverage constraint will be ignored, the sum of weights will equal 1. All other constraints such as the box constraint `max`, group and position limit constraints will be handled by elimination. If the constraints are very restrictive, this may result in very few feasible portfolios remaining. Another key point to note is that the solution may not be along the vertexes depending on the objective. For example, a risk budget objective will likely place the portfolio somewhere on the interior.
- The grid method to generate random portfolios is based on the `gridSearch` function in package NMOF. The grid search method only satisfies the min and max box constraints. The

`min_sum` and `max_sum` leverage constraint will likely be violated and the weights in the random portfolios should be normalized. Normalization may cause the box constraints to be violated and will be penalized in `constrained_objective`.

PortfolioAnalytics leverages the PerformanceAnalytics package for many common objective functions. The objective types in PortfolioAnalytics are designed to be used with PerformanceAnalytics functions, but any user supplied valid R function can be used as an objective.

Optimization

This summary attempts to provide an overview of how to construct a portfolio object with constraints and objectives, run the optimization, and chart the results.

The portfolio object is initialized with the `portfolio.spec` function. The main argument to `portfolio.spec` is `assets`. The `assets` argument can be a scalar value for the number of assets, a character vector of fund names, or a named vector of initial weights.

Adding constraints to the portfolio object is done with `add.constraint`. The `add.constraint` function is the main interface for adding and/or updating constraints to the portfolio object. This function allows the user to specify the portfolio to add the constraints to, the type of constraints, arguments for the constraint, and whether or not to enable the constraint. If updating an existing constraint, the `indexnum` argument can be specified.

Objectives can be added to the portfolio object with `add.objective`. The `add.objective` function is the main function for adding and/or updating objectives to the portfolio object. This function allows the user to specify the portfolio to add the objectives to, the type, name of the objective function, arguments to the objective function, and whether or not to enable the objective. If updating an existing objective, the `indexnum` argument can be specified.

With the constraints and objectives specified in the portfolio object, the portfolio object can be passed to `optimize.portfolio` or `optimize.portfolio.rebalancing` to run the optimization. Arguments to `optimize.portfolio` include asset returns, the portfolio object specifying constraints and objectives, optimization method, and other parameters specific to the solver. `optimize.portfolio.rebalancing` adds support for backtesting portfolio optimization through time with rebalancing or rolling periods.

Advanced Optimization

In addition to the more standard optimizations described above, PortfolioAnalytics also supports multi-layer optimization and regime switching optimization.

Support for multi-layer optimization allows one to construct a top level portfolio and several sub-portfolios with potentially different assets, constraints, and objectives. First, each sub-portfolio is optimized out-of-sample which creates a time series of returns. One can think of the out of sample returns for each sub-portfolio as the returns for a synthetic instrument. Finally, the out-of-sample returns of each sub-portfolio are then used as inputs for the top level optimization. The top level portfolio and sub-portfolios are created as normal using `portfolio.spec`, `add.constraint`, and `add.objective`. The multi-layer portfolio specification object is first initialized by passing the top level portfolio to `mult.portfolio.spec`. Sub-portfolios are then added with `add.sub.portfolio`. The multi-layer portfolio specification object can then be passed to `optimize.portfolio` and `optimize.portfolio.rebalancing`. See `demo(multi_layer_optimization)`.

Support for regime switching models allows one to change constraints and objectives depending on the current regime. Portfolios are created as normal with `portfolio.spec`, `add.constraint`, and

`add.objective`. The portfolios are then combined with a regime object using `regime.portfolios` to create a regime portfolio specification which can then be passed to `optimize.portfolio` and `optimize.portfolio.rebalancing`. Regime switching optimization is implemented in such a way that any arbitrary regime model can be used. See `demo(regime_switching)`.

Portfolio Moments

The PortfolioAnalytics framework to estimate solutions to constrained optimization problems is implemented in such a way that the moments of the returns are set once for use in lower level optimization functions. The `set.portfolio.moments` function computes the first, second, third, and fourth moments depending on the objective function(s) in the portfolio object. For example, if the third and fourth moments do not need to be calculated for a given objective, then `set.portfolio.moments` will try to detect this and not compute those moments. Currently, `set.portfolio.moments` implements methods to compute moments based on sample estimates, higher moments from fitting a statistical factor model based on the work of Kris Boudt, the Black Litterman model, and the Fully Flexible Framework based on the work of Attilio Meucci (NEED REFERENCE HERE). See the Custom Moment and Objective Functions vignette for a more detailed description and examples.

Charts and Graphs

Intuition into the optimization can be aided through visualization. The goal of creating the charts is to provide visualization tools for optimal portfolios regardless of the chosen optimization method.

`chart.Weights` plots the weights of the optimal portfolio. `chart.RiskReward` plots the optimal portfolio in risk-reward space. The random portfolios, DEoptim, and pso solvers will return trace portfolio information at each iteration when `optimize.portfolio` is run with `trace=TRUE`. If this is the case, `chart.RiskReward` will plot these portfolios so that the feasible space can be easily visualized. Although the GenSA and ROI solvers do not return trace portfolio information, random portfolios can be generated with the argument `rp=TRUE` in `chart.RiskReward`. A plot function is provided that will plot the weights and risk-reward scatter chart. The component risk contribution can be charted for portfolio optimization problems with risk budget objectives with `chart.RiskBudget`. Neighbor portfolios can be plotted in `chart.RiskBudget`, `chart.Weights`, and `chart.RiskReward`.

Efficient frontiers can be extracted from `optimize.portfolio` objects or created from a portfolio object. The efficient frontier can be charted in risk-reward space with `chart.EfficientFrontier`. The weights along the efficient frontier can be charted with `chart.EF.Weights`.

Multiple objects created via `optimize.portfolio` can be combined with `combine.optimizations` for visual comparison. The weights of the optimal portfolios can be plotted with `chart.Weights`. The optimal portfolios can be compared in risk-reward space with `chart.RiskReward`. The portfolio component risk contributions of the multiple optimal portfolios can be plotted with `chart.RiskBudget`.

Demos

PortfolioAnalytics contains a comprehensive collection of demos to demonstrate the functionality from very basic optimization problems such as estimating the solution to a minimum variance portfolio to more complex optimization problems with custom moment and objective functions.

Vignettes

TODO

Package Dependencies

Several of the functions in the PortfolioAnalytics package require time series data of returns and the `xts` package is used for working with time series data.

The PerformanceAnalytics package is used for many common objective functions. The objective types in PortfolioAnalytics are designed to be used with PerformanceAnalytics functions such as `StdDev`, `VaR`, and `ES`.

The `foreach` and `iterators` packages are used extensively throughout the package to support parallel programming. The primary functions where `foreach` loops are used is `optimize.portfolio`, `optimize.portfolio.rebalancing`, and `create.EfficientFrontier`.

In addition to a random portfolios optimization method, PortfolioAnalytics supports backend solvers by leveraging the following packages: `DEoptim`, `pso`, `GenSA`, `ROI` and associated `ROI` plugin packages.

Further Work

Continued work to improved charts and graphs.

Continued work to improve features to combine and compare multiple optimal portfolio objects.

Support for more solvers.

Comments, suggestions, and/or code patches are welcome.

Acknowledgements

TODO

Author(s)

Ross Bennett
Kris Boudt
Peter Carl
Brian G. Peterson

Maintainer: Brian G. Peterson <brian@braverock.com>

References

Boudt, Kris and Lu, Wanbo and Peeters, Benedict, *Higher Order Comoments of Multifactor Models and Asset Allocation* (June 16, 2014). Available at SSRN: <http://ssrn.com/abstract=2409603> or <http://dx.doi.org/10.2139/ssrn.2409603>

Chriss, Neil A and Almgren, Robert, *Portfolios from Sorts* (April 27, 2005). Available at SSRN: <http://ssrn.com/abstract=720041> or <http://dx.doi.org/10.2139/ssrn.720041>

Meucci, Attilio, *The Black-Litterman Approach: Original Model and Extensions* (August 1, 2008). Shorter version in, *THE ENCYCLOPEDIA OF QUANTITATIVE FINANCE*, Wiley, 2010. Available at SSRN: <http://ssrn.com/abstract=1117574> or <http://dx.doi.org/10.2139/ssrn.1117574>

Meucci, Attilio, *Fully Flexible Views: Theory and Practice* (August 8, 2008). Fully Flexible Views: Theory and Practice, Risk, Vol. 21, No. 10, pp. 97-102, October 2008. Available at SSRN: <http://ssrn.com/abstract=1213325>

Scherer, Bernd and Martin, Doug, *Modern Portfolio Optimization*. Springer. 2005.

Shaw, William Thornton, *Portfolio Optimization for VAR, CVaR, Omega and Utility with General Return Distributions: A Monte Carlo Approach for Long-Only and Bounded Short Portfolios with Optional Robustness and a Simplified Approach to Covariance Matching* (June 1, 2011). Available at SSRN: <http://ssrn.com/abstract=1856476> or <http://dx.doi.org/10.2139/ssrn.1856476>

See Also

CRAN task view on Empirical Finance

<https://cran.r-project.org/view=Econometrics>

CRAN task view on Optimization

<https://cran.r-project.org/view=Optimization>

Large-scale portfolio optimization with DEoptim

<https://cran.r-project.org/package=DEoptim>

ac.ranking

Asset Ranking

Description

Compute the first moment from a single complete sort

Usage

```
ac.ranking(R, order, ...)
```

Arguments

R	xts object of asset returns
order	a vector of indexes of the relative ranking of expected asset returns in ascending order. For example, <code>order = c(2, 3, 1, 4)</code> means that the expected returns of $R[, 2] < R[, 3], < R[, 1] < R[, 4]$.
...	any other passthrough parameters

Details

This function computes the estimated centroid vector from a single complete sort using the analytical approximation as described in R. Almgren and N. Chriss, "Portfolios from Sorts". The centroid is estimated and then scaled such that it is on a scale similar to the asset returns. By default, the centroid vector is scaled according to the median of the asset mean returns.

Value

The estimated first moments based on ranking views

References

R. Almgren and N. Chriss, "Portfolios from Sorts" https://papers.ssrn.com/sol3/papers.cfm?abstract_id=720041

See Also

[centroid.complete.mc](#) [centroid.sectors](#) [centroid.sign](#) [centroid.buckets](#)

Examples

```
data(edhec)
R <- edhec[, 1:4]
ac.ranking(R, c(2, 3, 1, 4))
```

add.constraint	<i>General interface for adding and/or updating optimization constraints.</i>
----------------	---

Description

This is the main function for adding and/or updating constraints to the [portfolio.spec](#) object.

Usage

```
add.constraint(
  portfolio,
  type,
  enabled = TRUE,
  message = FALSE,
  ...,
  indexnum = NULL
)
```

Arguments

portfolio	an object of class 'portfolio' to add the constraint to, specifying the constraints for the optimization, see portfolio.spec
type	character type of the constraint to add or update, currently 'weight_sum' (also 'leverage' or 'weight'), 'box', 'group', 'turnover', 'diversification', 'position_limit', 'return', 'factor_exposure', or 'leverage_exposure'
enabled	TRUE/FALSE. The default is enabled=TRUE.
message	TRUE/FALSE. The default is message=FALSE. Display messages if TRUE.
...	any other passthru parameters to specify constraints
indexnum	if you are updating a specific constraint, the index number in the \$constraints list to update

Details

The following constraint types may be specified:

`weight_sum`, `weight`, `leverage` Specify constraint on the sum of the weights, see [weight_sum_constraint](#)

`full_investment` Special case to set `min_sum=1` and `max_sum=1` of weight sum constraints

`dollar_neutral`, `active` Special case to set `min_sum=0` and `max_sum=0` of weight sum constraints

`box` box constraints for the individual asset weights, see [box_constraint](#)

`long_only` Special case to set `min=0` and `max=1` of box constraints

`group` specify the sum of weights within groups and the number of assets with non-zero weights in groups, see [group_constraint](#)

`turnover` Specify a constraint for target turnover. Turnover is calculated from a set of initial weights, see [turnover_constraint](#)

`diversification` target diversification of a set of weights, see [diversification_constraint](#)

`position_limit` Specify the number of non-zero, long, and/or short positions, see [position_limit_constraint](#)

`return` Specify the target mean return, see [return_constraint](#)

`factor_exposure` Specify risk factor exposures, see [factor_exposure_constraint](#)

`leverage_exposure` Specify a maximum leverage exposure, see [leverage_exposure_constraint](#)

Author(s)

Ross Bennett

See Also

[portfolio.spec](#) [weight_sum_constraint](#), [box_constraint](#), [group_constraint](#), [turnover_constraint](#), [diversification_constraint](#), [position_limit_constraint](#), [return_constraint](#), [factor_exposure_constraint](#), [leverage_exposure_constraint](#)

Examples

```
data(edhec)
returns <- edhec[, 1:4]
fund.names <- colnames(returns)
pspec <- portfolio.spec(assets=fund.names)

# Add the full investment constraint that specifies the weights must sum to 1.
pspec <- add.constraint(portfolio=pspec, type="weight_sum", min_sum=1, max_sum=1)

# The full investment constraint can also be specified with type="full_investment"
pspec <- add.constraint(portfolio=pspec, type="full_investment")

# Another common constraint is that portfolio weights sum to 0.
pspec <- add.constraint(portfolio=pspec, type="weight_sum", min_sum=0, max_sum=0)
pspec <- add.constraint(portfolio=pspec, type="dollar_neutral")
pspec <- add.constraint(portfolio=pspec, type="active")

# Add box constraints
```

```

pspec <- add.constraint(portfolio=pspec, type="box", min=0.05, max=0.4)

# min and max can also be specified per asset
pspec <- add.constraint(portfolio=pspec,
                        type="box",
                        min=c(0.05, 0, 0.08, 0.1),
                        max=c(0.4, 0.3, 0.7, 0.55))

# A special case of box constraints is long only where min=0 and max=1
# The default action is long only if min and max are not specified
pspec <- add.constraint(portfolio=pspec, type="box")
pspec <- add.constraint(portfolio=pspec, type="long_only")

# Add group constraints
pspec <- add.constraint(portfolio=pspec,
                        type="group",
                        groups=list(c(1, 2, 1), 4),
                        group_min=c(0.1, 0.15),
                        group_max=c(0.85, 0.55),
                        group_labels=c("GroupA", "GroupB"),
                        group_pos=c(2, 1))

# Add position limit constraint such that we have a maximum number
# of three assets with non-zero weights.
pspec <- add.constraint(portfolio=pspec, type="position_limit", max_pos=3)

# Add diversification constraint
pspec <- add.constraint(portfolio=pspec, type="diversification", div_target=0.7)

# Add turnover constraint
pspec <- add.constraint(portfolio=pspec, type="turnover", turnover_target=0.2)

# Add target mean return constraint
pspec <- add.constraint(portfolio=pspec, type="return", return_target=0.007)

# Example using the indexnum argument
portf <- portfolio.spec(assets=fund.names)
portf <- add.constraint(portf, type="full_investment")
portf <- add.constraint(portf, type="long_only")

# indexnum corresponds to the index number of the constraint
# The full_investment constraint was the first constraint added and has
# indexnum=1
portf$constraints[[1]]

# View the constraint with indexnum=2
portf$constraints[[2]]

# Update the constraint to relax the sum of weights constraint
portf <- add.constraint(portf, type="weight_sum",
                        min_sum=0.99, max_sum=1.01,
                        indexnum=1)

```

```
# Update the constraint to modify the box constraint
portf <- add.constraint(portf, type="box",
min=0.1, max=0.8,
indexnum=2)
```

add.objective	<i>General interface for adding optimization objectives, including risk, return, and risk budget</i>
---------------	--

Description

This function is the main function for adding and updating business objectives in an object of type `portfolio.spec`.

Usage

```
add.objective_v1(
  constraints,
  type,
  name,
  arguments = NULL,
  enabled = TRUE,
  ...,
  indexnum = NULL
)

add.objective(
  portfolio,
  constraints = NULL,
  type,
  name,
  arguments = NULL,
  enabled = TRUE,
  ...,
  indexnum = NULL
)
```

Arguments

constraints	a 'v1_constraint' object for backwards compatibility, see constraint
type	character type of the objective to add or update, currently 'return', 'risk', 'risk_budget', 'quadratic_utility', or 'weight_concentration'
name	name of the objective, should correspond to a function, though we will try to make allowances
arguments	default arguments to be passed to an objective function when executed
enabled	TRUE/FALSE

...	any other passthru parameters
indexnum	if you are updating a specific objective, the index number in the \$objectives list to update
portfolio	an object of type 'portfolio' to add the objective to, specifying the portfolio for the optimization, see portfolio

Details

In general, you will define your objective as one of the following types: 'return', 'risk', 'risk_budget', 'quadratic utility', or 'weight_concentration'. These have special handling and intelligent defaults for dealing with the function most likely to be used as objectives, including mean, median, VaR, ES, etc.

Objectives of type 'turnover' and 'minmax' are also supported.

Author(s)

Brian G. Peterson and Ross Bennett

See Also

[objective](#), [portfolio.spec](#)

Examples

```
data(edhec)
returns <- edhec[,1:4]
fund.names <- colnames(returns)
portf <- portfolio.spec(assets=fund.names)
# Add some basic constraints
portf <- add.constraint(portf, type="full_investment")
portf <- add.constraint(portf, type="long_only")

# Creates a new portfolio object using portf and adds a quadratic utility
# objective. This will add two objectives to the portfolio object; 1) mean and
# 2) var. The risk aversion parameter is commonly referred to as lambda in the
# quadratic utility formulation that controls how much the portfolio variance
# is penalized.
portf.maxQU <- add.objective(portf, type="quadratic_utility",
                             risk_aversion=0.25)

# Creates a new portfolio object using portf and adds mean as an objective
portf.maxMean <- add.objective(portf, type="return", name="mean")

# Creates a new portfolio object using portf and adds StdDev as an objective
portf.minStdDev <- add.objective(portf, type="risk", name="StdDev")

# Creates a new portfolio object using portf and adds ES as an objective.
# Note that arguments to ES are passed in as a named list.
portf.minES <- add.objective(portf, type="risk", name="ES",
                             arguments=list(p=0.925, clean="boudt"))
```

```

# Creates a new portfolio object using portf.minES and adds a risk budget
# objective with limits on component risk contribution.
# Note that arguments to ES are passed in as a named list.
portf.RiskBudgetES <- add.objective(portf.minES, type="risk_budget", name="ES",
                                   arguments=list(p=0.925, clean="boudt"),
                                   min_prisk=0, max_prisk=0.6)

# Creates a new portfolio object using portf.minES and adds a risk budget
# objective with equal component risk contribution.
# Note that arguments to ES are passed in as a named list.
portf.EqRiskES <- add.objective(portf.minES, type="risk_budget", name="ES",
                                arguments=list(p=0.925, clean="boudt"),
                                min_concentration=TRUE)

# Creates a new portfolio object using portf and adds a weight_concentration
# objective. The conc_aversion parameter controls how much concentration is
# penalized. The portfolio concentration is defined as the Herfindahl Hirschman
# Index of the weights.
portf.conc <- add.objective(portf, type="weight_concentration",
                             name="HHI", conc_aversion=0.01)

```

add.sub.portfolio *Add sub-portfolio*

Description

Add a sub-portfolio to a multiple layer portfolio specification object

Usage

```

add.sub.portfolio(
  mult.portfolio,
  portfolio,
  optimize_method = c("DEoptim", "random", "ROI", "pso", "GenSA"),
  search_size = 20000,
  rp = NULL,
  rebalance_on = NULL,
  training_period = NULL,
  trailing_periods = NULL,
  ...,
  indexnum = NULL
)

```

Arguments

mult.portfolio a mult.portfolio.spec object
 portfolio a portfolio object to add as a sub portfolio.
 optimize_method optimization method for the sub portfolio

search_size	integer, how many portfolios to test, default 20,000
rp	matrix of random portfolio weights, default NULL, mostly for automated use by rebalancing optimization or repeated tests on same portfolios
rebalance_on	character string of period to rebalance on. See endpoints for valid names.
training_period	an integer of the number of periods to use as a training data in the front of the returns data
trailing_periods	an integer with the number of periods to roll over (i.e. width of the moving or rolling window), the default is NULL will run using the returns data from inception
...	additional passthrough parameters to optimize.portfolio.rebalancing
indexnum	the index number of the sub portfolio. If indexnum=NULL (the default), then the sub portfolio object is appended to the list of sub portfolios in the <code>mult.portfolio</code> object. If indexnum is specified, the portfolio in that index number is overwritten.

Author(s)

Ross Bennett

See Also

[mult.portfolio.spec](#) [portfolio.spec](#) [optimize.portfolio](#) [optimize.portfolio.rebalancing](#)

applyFUN

Apply a risk or return function to a set of weights

Description

This function is used to calculate risk or return metrics given a matrix of weights and is primarily used as a convenience function used in `chart.Scatter` functions

Usage

```
applyFUN(R, weights, FUN = "mean", arguments)
```

Arguments

R	xts object of asset returns
weights	a matrix of weights generated from <code>random_portfolios</code> or <code>optimize.portfolio</code>
FUN	name of a function
arguments	named list of arguments to FUN

Author(s)

Ross Bennett

backtest.plot	<i>generate plots of the cumulative returns and drawdown for back-testing</i>
---------------	---

Description

generate plots of the cumulative returns and drawdown for back-testing

Usage

```
backtest.plot(  
  R,  
  log_return = FALSE,  
  drawdown_on = 1,  
  plotType = "both",  
  main = NULL,  
  colorSet = NULL,  
  ltySet = NULL,  
  lwdSet = NULL  
)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
log_return	arithmetic return or log return, the default is arithmetic return
drawdown_on	the plot will shadow the full time period of the maximum drawdown and recovery of the first portfolio. Use number (e.g. 1, 2, 3) to indicate which portfolio drawdown interval you wish to track, or NULL to not shadow any period.
plotType	"cumRet", "drawdown", or the default is both
main	users can design title by providing a character of main
colorSet	users can design the color by providing a vector of color
ltySet	users can design lty by providing a vector of lty
lwdSet	users can design lwd by providing a vector of lwd

Author(s)

Peter Carl, Xinran Zhao, Yifu Kang

barplotGroupWeights *barplot of group weights by group or category*

Description

This function is called by chart.GroupWeights function if chart.type="barplot"

Usage

```
barplotGroupWeights(
  object,
  ...,
  grouping = c("groups", "category"),
  main = "Group Weights",
  las = 3,
  xlab = NULL,
  cex.lab = 0.8,
  element.color = "darkgray",
  cex.axis = 0.8
)
```

Arguments

object	object of class optimize.portfolio
...	passthrough parameters to plot
grouping	groups: group the weights by group constraints category_labels: group the weights by category_labels in portfolio object
main	an overall title for the plot: see title
las	numeric in {0,1,2,3}; the style of axis labels 0: always parallel to the axis [<i>default</i>], 1: always horizontal, 2: always perpendicular to the axis, 3: always vertical.
xlab	a title for the x axis: see title
cex.lab	The magnification to be used for x and y labels relative to the current setting of cex
element.color	color for the default border and axis
cex.axis	The magnification to be used for x and y axis relative to the current setting of cex

Author(s)

Ross Bennett

black.litterman *Black Litterman Estimates*

Description

Compute the Black Litterman estimate of moments for the posterior normal.

Usage

```
black.litterman(R, P, Mu = NULL, Sigma = NULL, Views = NULL)
```

Arguments

R	returns
P	a K x N pick matrix
Mu	vector of length N of the prior expected values. The sample mean is used if Mu=NULL.
Sigma	an N x N matrix of the prior covariance matrix. The sample covariance is used if Sigma=NULL.
Views	a vector of length K of the views

Value

BLMu: posterior expected values

BLSigma: posterior covariance matrix

Note

This function is largely based on the work of Xavier Valls to port the matlab code of Attilio Meucci to R as documented in the Meucci package.

Author(s)

Ross Bennett, Xavier Valls

References

A. Meucci - "Exercises in Advanced Risk and Portfolio Management" <https://www.arpm.co/articles/exercises-in-advanced-risk-and-portfolio-management/>.

See Also

[BlackLittermanFormula](#)

BlackLittermanFormula *Computes the Black-Litterman formula for the moments of the posterior normal.*

Description

This function computes the Black-Litterman formula for the moments of the posterior normal, as described in A. Meucci, "Risk and Asset Allocation", Springer, 2005.

Usage

```
BlackLittermanFormula(Mu, Sigma, P, v, Omega)
```

Arguments

Mu	[vector] (N x 1) prior expected values.
Sigma	[matrix] (N x N) prior covariance matrix.
P	[matrix] (K x N) pick matrix.
v	[vector] (K x 1) vector of views.
Omega	[matrix] (K x K) matrix of confidence.

Value

BLMu [vector] (N x 1) posterior expected values.
BLSigma [matrix] (N x N) posterior covariance matrix.

Author(s)

Xavier Valls <flamejat@gmail.com>

References

A. Meucci - "Exercises in Advanced Risk and Portfolio Management" <https://www.arpm.co/articles/exercises-in-advanced-risk-and-portfolio-management/>.

See Meucci's script for "BlackLittermanFormula.m"

box_constraint	<i>constructor for box_constraint.</i>
----------------	--

Description

Box constraints specify the upper and lower bounds on the weights of the assets. This function is called by `add.constraint` when `type="box"` is specified. See [add.constraint](#).

Usage

```
box_constraint(
  type = "box",
  assets,
  min,
  max,
  min_mult,
  max_mult,
  enabled = TRUE,
  message = FALSE,
  ...
)
```

Arguments

<code>type</code>	character type of the constraint
<code>assets</code>	number of assets, or optionally a named vector of assets specifying initial weights
<code>min</code>	numeric or named vector specifying minimum weight box constraints
<code>max</code>	numeric or named vector specifying minimum weight box constraints
<code>min_mult</code>	numeric or named vector specifying minimum multiplier box constraint from initial weight in assets
<code>max_mult</code>	numeric or named vector specifying maximum multiplier box constraint from initial weight in assets
<code>enabled</code>	TRUE/FALSE
<code>message</code>	TRUE/FALSE. The default is <code>message=FALSE</code> . Display messages if TRUE.
<code>...</code>	any other passthru parameters to specify box constraints

Value

an object of class 'box_constraint'

Author(s)

Ross Bennett

See Also[add.constraint](#)**Examples**

```

data(edhec)
ret <- edhec[, 1:4]

pspec <- portfolio.spec(assets=colnames(ret))

# defaults to min=0 and max=1
pspec <- add.constraint(pspec, type="box")

# specify box constraints as a scalar
pspec <- add.constraint(pspec, type="box", min=0.05, max=0.45)

# specify box constraints per asset
pspec <- add.constraint(pspec,
                       type="box",
                       min=c(0.05, 0.10, 0.08, 0.06),
                       max=c(0.45, 0.55, 0.35, 0.65))

```

CCCgarch.MM

*compute comoments for use by lower level optimization functions
when the conditional covariance matrix is a CCC GARCH model*

Description

it first estimates the conditional GARCH variances, then filters out the time-varying volatility and estimates the higher order comoments on the innovations rescaled such that their unconditional covariance matrix is the conditional covariance matrix forecast

Usage

```
CCCgarch.MM(R, momentargs = NULL, ...)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
momentargs	list containing arguments to be passed down to lower level functions, default NULL
...	any other passthru parameters

center	<i>Center</i>
--------	---------------

Description

Center a matrix

Usage

```
center(x)
```

Arguments

x	matrix
---	--------

Details

This function is used primarily to center a time series of asset returns or factors. Each column should represent the returns of an asset or factor realizations. The expected value is taken as the sample mean.

$$x.\text{centered} = x - \text{mean}(x)$$
Value

matrix of centered data

centroid.buckets	<i>Buckets Centroid</i>
------------------	-------------------------

Description

Compute the centroid for buckets of assets

Usage

```
centroid.buckets(buckets, simulations = 1000)
```

Arguments

buckets	a list where each element contains the index of the assets in the respective bucket. The assets within each bucket have no order. The bucket elements are in ascending order such that $R_{\text{bucket}_1} < \dots < R_{\text{bucket}_n}$
simulations	number of simulations

Details

A common use of buckets is to divide the assets into quartiles or deciles, but is generalized here for an arbitrary number of buckets and arbitrary number of assets in each bucket.

Value

the centroid vector

Author(s)

Ross Bennett

centroid.complete.mc *Complete Cases Centroid*

Description

Numerical method to estimate complete cases centroid

Usage

```
centroid.complete.mc(order, simulations = 1000)
```

Arguments

order	a vector of indexes of the relative ranking of expected asset returns in ascending order. For example, <code>order = c(2, 3, 1, 4)</code> expresses a view on the expected returns such that $R_2 < R_3 < R_1 < R_4$
simulations	number of simulations

Value

the centroid vector

Author(s)

Ross Bennett

Examples

```
# Express a view on the assets such that  
#  $R_2 < R_1 < R_3 < R_4$   
centroid.complete.mc(c(2, 1, 3, 4))
```

centroid.sectors *Multiple Sectors Centroid*

Description

Compute the centroid for expressing views on the relative ranking of assets within sectors.

Usage

```
centroid.sectors(sectors, simulations = 1000)
```

Arguments

sectors a list where each list element contains the order of each asset in the given sector
simulations number of simulations

Value

the centroid vector

Author(s)

Ross Bennett

Examples

```
# Express a view on the assets in two sectors  
# Sector 1 View: R_2 < R_1 < R_3  
# Sector 2 View: R_5 < R_4  
x <- list()  
x[[1]] <- c(2, 1, 3)  
x[[2]] <- c(5, 4)  
centroid.sectors(x)
```

centroid.sign *Positive and Negative View Centroid*

Description

Compute the centroid for expressing a view on assets with positive or negative expected returns

Usage

```
centroid.sign(positive, negative, simulations = 1000)
```

Arguments

positive a vector of the index of assets with positive expected return in ascending order
negative a vector of the index of assets with negative expected return in ascending order.
simulations number of simulations

Value

the centroid vector

Author(s)

Ross Bennett

Examples

```
# Express a view that
# R_1 < R_2 < 0 < R_3 < R_4
centroid.sign(c(1, 2), c(4, 3))
```

chart.Concentration *Classic risk reward scatter and concentration*

Description

This function charts the optimize.portfolio object in risk-return space and the degree of concentration based on the weights or percentage component contribution to risk.

Usage

```
chart.Concentration(
  object,
  ...,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  conc.type = c("weights", "pct_contrib"),
  col = heat.colors(20),
  element.color = "darkgray",
  cex.axis = 0.8,
  xlim = NULL,
  ylim = NULL
)
```

Arguments

object	optimal portfolio created by optimize.portfolio .
...	any other passthru parameters.
return.col	string matching the objective of a 'return' objective, on vertical axis.
risk.col	string matching the objective of a 'risk' objective, on horizontal axis.
chart.assets	TRUE/FALSE. Includes a risk reward scatter of the assets in the chart.
conc.type	concentration type can be based on the concentration of weights or concentration of percentage component contribution to risk (only works with risk budget objective for the optimization).
col	color palette or vector of colors to use.
element.color	color for the border and axes.
cex.axis	The magnification to be used for axis annotation relative to the current setting of cex.
xlim	set the x-axis limit, same as in plot .
ylim	set the y-axis limit, same as in plot .

Author(s)

Peter Carl and Ross Bennett

See Also

[optimize.portfolio](#)

chart.EF.Weights	<i>Chart weights along an efficient frontier</i>
------------------	--

Description

This function produces a stacked barplot of weights along an efficient frontier.

Usage

```
chart.EF.Weights(object, ...)

## S3 method for class 'efficient.frontier'
chart.EF.Weights(
  object,
  ...,
  colorset = NULL,
  n.portfolios = 25,
  by.groups = FALSE,
  match.col = "ES",
  main = "",
```

```

    cex.lab = 0.8,
    cex.axis = 0.8,
    cex.legend = 0.8,
    legend.labels = NULL,
    element.color = "darkgray",
    legend.loc = "topright"
)

## S3 method for class 'optimize.portfolio'
chart.EF.Weights(
  object,
  ...,
  colorset = NULL,
  n.portfolios = 25,
  by.groups = FALSE,
  match.col = "ES",
  main = "",
  cex.lab = 0.8,
  cex.axis = 0.8,
  cex.legend = 0.8,
  legend.labels = NULL,
  element.color = "darkgray",
  legend.loc = "topright"
)

```

Arguments

object	object of class <code>efficient.frontier</code> or <code>optimize.portfolio</code> .
...	passthru parameters to <code>barplot</code> .
colorset	color palette or vector of colors to use.
n.portfolios	number of portfolios to extract along the efficient frontier.
by.groups	TRUE/FALSE. If TRUE, the group weights are charted.
match.col	string name of column to use for risk (horizontal axis). Must match the name of an objective.
main	title used in the plot.
cex.lab	the magnification to be used for x-axis and y-axis labels relative to the current setting of 'cex'.
cex.axis	the magnification to be used for sizing the axis text relative to the current setting of 'cex', similar to plot .
cex.legend	the magnification to be used for sizing the legend relative to the current setting of 'cex', similar to plot .
legend.labels	character vector to use for the legend labels.
element.color	provides the color for drawing less-important chart elements, such as the box lines, axis lines, etc.
legend.loc	NULL, "topright", "right", or "bottomright". If legend.loc is NULL, the legend will not be plotted.

Author(s)

Ross Bennett

 chart.EfficientFrontier

Chart the efficient frontier and risk-return scatter

Description

Chart the efficient frontier and risk-return scatter of the assets for `optimize.portfolio` or `efficient.frontier` objects

Usage

```
chart.EfficientFrontier(object, ...)

## S3 method for class 'optimize.portfolio.CVXR'
chart.EfficientFrontier(
  object,
  ...,
  optimize_method = "CVXR",
  match.col = "ES",
  n.portfolios = 25,
  xlim = NULL,
  ylim = NULL,
  cex.axis = 0.8,
  element.color = "darkgray",
  main = "Efficient Frontier",
  RAR.text = "SR",
  rf = 0,
  tangent.line = TRUE,
  cex.legend = 0.8,
  chart.assets = TRUE,
  labels.assets = TRUE,
  pch.assets = 21,
  cex.assets = 0.8
)

## S3 method for class 'optimize.portfolio.ROI'
chart.EfficientFrontier(
  object,
  ...,
  optimize_method = "ROI",
  match.col = "ES",
  n.portfolios = 25,
  xlim = NULL,
```

```
ylim = NULL,
cex.axis = 0.8,
element.color = "darkgray",
main = "Efficient Frontier",
RAR.text = "SR",
rf = 0,
tangent.line = TRUE,
cex.legend = 0.8,
chart.assets = TRUE,
labels.assets = TRUE,
pch.assets = 21,
cex.assets = 0.8
)

## S3 method for class 'optimize.portfolio'
chart.EfficientFrontier(
  object,
  ...,
  match.col = "ES",
  n.portfolios = 25,
  xlim = NULL,
  ylim = NULL,
  cex.axis = 0.8,
  element.color = "darkgray",
  main = "Efficient Frontier",
  RAR.text = "SR",
  rf = 0,
  tangent.line = TRUE,
  cex.legend = 0.8,
  chart.assets = TRUE,
  labels.assets = TRUE,
  pch.assets = 21,
  cex.assets = 0.8
)

## S3 method for class 'efficient.frontier'
chart.EfficientFrontier(
  object,
  ...,
  match.col = "ES",
  n.portfolios = NULL,
  xlim = NULL,
  ylim = NULL,
  cex.axis = 0.8,
  element.color = "darkgray",
  main = "Efficient Frontier",
  RAR.text = "SR",
  rf = 0,
```

```

    tangent.line = TRUE,
    cex.legend = 0.8,
    chart.assets = TRUE,
    labels.assets = TRUE,
    pch.assets = 21,
    cex.assets = 0.8
)

```

Arguments

object	object to chart.
...	passthru parameters to plot
optimize_method	the optimize method to get the efficient frontier
match.col	string name of column to use for risk (horizontal axis). match.col must match the name of an objective measure in the objective_measures or opt_values slot in the object created by optimize.portfolio .
n.portfolios	number of portfolios to use to plot the efficient frontier.
xlim	set the x-axis limit, same as in plot .
ylim	set the y-axis limit, same as in plot .
cex.axis	numerical value giving the amount by which the axis should be magnified relative to the default.
element.color	provides the color for drawing less-important chart elements, such as the box lines, axis lines, etc.
main	a main title for the plot.
RAR.text	string name for risk adjusted return text to plot in the legend.
rf	risk free rate. If rf is not null, the maximum Sharpe Ratio or modified Sharpe Ratio tangency portfolio will be plotted.
tangent.line	TRUE/FALSE to plot the tangent line.
cex.legend	numerical value giving the amount by which the legend should be magnified relative to the default.
chart.assets	TRUE/FALSE to include the assets.
labels.assets	TRUE/FALSE to include the asset names in the plot. chart.assets must be TRUE to plot asset names.
pch.assets	plotting character of the assets, same as in plot .
cex.assets	numerical value giving the amount by which the asset points and labels should be magnified relative to the default.

Details

For objects created by `optimize.portfolio` with 'DEoptim', 'random', or 'pso' specified as the `optimize_method`:

- The efficient frontier plotted is based on the the trace information (sets of portfolios tested by the solver at each iteration) in objects created by `optimize.portfolio`.

For objects created by `optimize.portfolio` with 'ROI' specified as the `optimize_method`:

- The mean-StdDev or mean-ETL efficient frontier can be plotted for optimal portfolio objects created by `optimize.portfolio`.
- If `match.col="StdDev"`, the mean-StdDev efficient frontier is plotted.
- If `match.col="ETL"` (also "ES" or "CVaR"), the mean-ETL efficient frontier is plotted.

Note that `trace=TRUE` must be specified in `optimize.portfolio`

GenSA does not return any useable trace information for portfolios tested at each iteration, therefore we cannot extract and chart an efficient frontier.

By default, the tangency portfolio (maximum Sharpe Ratio or modified Sharpe Ratio) will be plotted using a risk free rate of 0. Set `rf=NULL` to omit this from the plot.

Author(s)

Ross Bennett, Xinran Zhao

chart.EfficientFrontierCompare

Overlay the efficient frontiers of different minRisk portfolio objects on a single plot.

Description

Overlay the efficient frontiers of different minRisk portfolio objects on a single plot.

Usage

```
chart.EfficientFrontierCompare(
  R,
  portfolio,
  risk_type,
  n.portfolios = 25,
  match.col = c("StdDev", "ES"),
  guideline = NULL,
  main = "Efficient Frontiers",
  plot_type = "1",
  cex.axis = 0.5,
  element.color = "darkgray",
  legend.loc = NULL,
  legend.labels = NULL,
  cex.legend = 0.8,
  xlim = NULL,
  ylim = NULL,
  ...,
  chart.assets = TRUE,
```

```

labels.assets = TRUE,
pch.assets = 21,
cex.assets = 0.8,
col = NULL,
lty = NULL,
lwd = NULL
)

```

Arguments

R	an xts object of asset returns
portfolio	same constrained portfolio created by portfolio.spec
risk_type	type of risk that you want to compare
n.portfolios	number of portfolios to extract along the efficient frontier. This is only used for objects of class <code>optimize.portfolio</code>
match.col	string name of column to use for portfolio object. Must match the name of an objective.
guideline	show the risk difference and mean difference between efficient frontiers
main	title used in the plot.
plot_type	define the plot_type, default is "1"
cex.axis	the magnification to be used for sizing the axis text relative to the current setting of 'cex', similar to plot .
element.color	provides the color for drawing less-important chart elements, such as the box lines, axis lines, etc.
legend.loc	location of the legend; NULL, "bottomright", "bottom", "bottomleft", "left", "topleft", "top", "topright", "right" and "center".
legend.labels	character vector to use for the legend labels.
cex.legend	The magnification to be used for sizing the legend relative to the current setting of 'cex', similar to plot .
xlim	set the x-axis limit, same as in plot .
ylim	set the y-axis limit, same as in plot .
...	passthrough parameters to plot .
chart.assets	TRUE/FALSE to include the assets.
labels.assets	TRUE/FALSE to include the asset names in the plot.
pch.assets	plotting character of the assets, same as in plot .
cex.assets	A numerical value giving the amount by which the asset points and labels should be magnified relative to the default.
col	vector of colors with length equal to the number of portfolios in <code>portfolio_list</code> . Add two more to customize guideline color.
lty	vector of line types with length equal to the number of portfolios in <code>portfolio_list</code> . Add two more to customize guideline type.
lwd	vector of line widths with length equal to the number of portfolios in <code>portfolio_list</code> . Add two more to customize guideline width.

Author(s)

Xinran Zhao

```
chart.EfficientFrontierOverlay
    Plot multiple efficient frontiers
```

Description

Overlay the efficient frontiers of multiple portfolio objects on a single plot.

Usage

```
chart.EfficientFrontierOverlay(
  R,
  portfolio_list,
  type,
  n.portfolios = 25,
  match.col = "ES",
  search_size = 2000,
  main = "Efficient Frontiers",
  cex.axis = 0.8,
  element.color = "darkgray",
  legend.loc = NULL,
  legend.labels = NULL,
  cex.legend = 0.8,
  xlim = NULL,
  ylim = NULL,
  ...,
  chart.assets = TRUE,
  labels.assets = TRUE,
  pch.assets = 21,
  cex.assets = 0.8,
  col = NULL,
  lty = NULL,
  lwd = NULL
)
```

Arguments

R	an xts object of asset returns
portfolio_list	list of portfolio objects created by portfolio.spec and combined with combine.portfolios
type	type of efficient frontier, see create.EfficientFrontier
n.portfolios	number of portfolios to extract along the efficient frontier. This is only used for objects of class <code>optimize.portfolio</code>

match.col	string name of column to use for risk (horizontal axis). Must match the name of an objective.
search_size	passed to optimize.portfolio for type="DEoptim" or type="random".
main	title used in the plot.
cex.axis	the magnification to be used for sizing the axis text relative to the current setting of 'cex', similar to plot .
element.color	provides the color for drawing less-important chart elements, such as the box lines, axis lines, etc.
legend.loc	location of the legend; NULL, "bottomright", "bottom", "bottomleft", "left", "topleft", "top", "topright", "right" and "center".
legend.labels	character vector to use for the legend labels.
cex.legend	The magnification to be used for sizing the legend relative to the current setting of 'cex', similar to plot .
xlim	set the x-axis limit, same as in plot .
ylim	set the y-axis limit, same as in plot .
...	passthrough parameters to plot .
chart.assets	TRUE/FALSE to include the assets.
labels.assets	TRUE/FALSE to include the asset names in the plot.
pch.assets	plotting character of the assets, same as in plot .
cex.assets	A numerical value giving the amount by which the asset points and labels should be magnified relative to the default.
col	vector of colors with length equal to the number of portfolios in portfolio_list.
lty	vector of line types with length equal to the number of portfolios in portfolio_list.
lwd	vector of line widths with length equal to the number of portfolios in portfolio_list.

Author(s)

Ross Bennett

chart.GroupWeights	<i>Chart weights by group or category</i>
--------------------	---

Description

Chart weights by group or category

Usage

```
chart.GroupWeights(  
  object,  
  ...,  
  grouping = c("groups", "category"),  
  plot.type = "line",  
  main = "Group Weights",  
  las = 3,  
  xlab = NULL,  
  cex.lab = 0.8,  
  element.color = "darkgray",  
  cex.axis = 0.8  
)
```

Arguments

object	object of class <code>optimize.portfolio</code> .
...	passthrough parameters to <code>plot</code> .
grouping	groups: group the weights by group constraints. category_labels: group the weights by category_labels in the portfolio object.
plot.type	"line" or "barplot".
main	an overall title for the plot: see <code>title</code> .
las	numeric in {0,1,2,3}; the style of axis labels 0: always parallel to the axis, 1: always horizontal, 2: always perpendicular to the axis, 3: always vertical[<i>default</i>].
xlab	a title for the x axis: see <code>title</code> .
cex.lab	the magnification to be used for x and y labels relative to the current setting of <code>cex</code> .
element.color	color for the default border and axis.
cex.axis	the magnification to be used for x and y axis relative to the current setting of <code>cex</code> .

Author(s)

Ross Bennett

chart.RiskBudget	<i>Generic method to chart risk contribution</i>
------------------	--

Description

This function is the generic method to chart risk budget objectives for `optimize.portfolio`, `optimize.portfolio.rebalancing`, and `opt.list` objects. This function charts the contribution or percent contribution of the resulting objective measures of a `risk_budget_objective`. The risk contributions for `optimize.portfolio.rebalancing` objects are plotted through time with [chart.StackedBar](#).

Usage

```
chart.RiskBudget(object, ...)
```

```
## S3 method for class 'optimize.portfolio'
chart.RiskBudget(
  object,
  ...,
  neighbors = NULL,
  risk.type = "absolute",
  main = "Risk Contribution",
  ylab = "",
  xlab = NULL,
  cex.axis = 0.8,
  cex.lab = 0.8,
  element.color = "darkgray",
  las = 3,
  ylim = NULL
)
```

```
## S3 method for class 'optimize.portfolio.rebalancing'
chart.RiskBudget(
  object,
  ...,
  match.col = "ES",
  risk.type = "absolute",
  regime = NULL,
  main = "Risk Contribution"
)
```

```
## S3 method for class 'opt.list'
chart.RiskBudget(
  object,
  ...,
  match.col = "ES",
  risk.type = "absolute",
```

```

    main = "Risk Budget",
    plot.type = "line",
    cex.axis = 0.8,
    cex.lab = 0.8,
    element.color = "darkgray",
    las = 3,
    ylim = NULL,
    colorset = NULL,
    legend.loc = NULL,
    cex.legend = 0.8
)

```

Arguments

object	optimal portfolio object created by optimize.portfolio or optimize.portfolio.rebalancing
...	any other passthru parameters to plot
neighbors	risk contribution or pct_contrib of neighbor portfolios to be plotted, see Details.
risk.type	"absolute" or "percentage" to plot risk contribution in absolute terms or percentage contribution.
main	main title for the chart.
ylab	label for the y-axis.
xlab	label for the x-axis.
cex.axis	the magnification to be used for axis annotation relative to the current setting of cex.
cex.lab	the magnification to be used for axis annotation relative to the current setting of cex.
element.color	provides the color for drawing less-important chart elements, such as the box lines, axis lines, etc.
las	numeric in {0,1,2,3}; the style of axis labels 0: always parallel to the axis [<i>default</i>], 1: always horizontal, 2: always perpendicular to the axis, 3: always vertical.
ylim	set the y-axis limit, same as in plot
match.col	string of risk column to match. The <code>opt.list</code> object may contain risk budgets for ES or StdDev and this will match the proper column names of the objectives list outp (e.g. ES.contribution).
regime	integer of the regime number. For use with optimize.portfolio.rebalancing run with regime switching portfolios.
plot.type	"line" or "barplot".
colorset	color palette or vector of colors to use
legend.loc	legend.loc NULL, "topright", "right", or "bottomright". If legend.loc is NULL, the legend will not be plotted
cex.legend	The magnification to be used for the legend relative to the current setting of cex

Details

neighbors may be specified in three ways. The first is as a single number of neighbors. This will extract the neighbors closest to the portfolios in terms of the out numerical statistic. The second method consists of a numeric vector for neighbors. This will extract the neighbors with portfolio index numbers that correspond to the vector contents. The third method for specifying neighbors is to pass in a matrix. This matrix should look like the output of [extractStats](#), and should contain properly named contribution and pct_contrib columns.

See Also

[optimize.portfolio](#) [optimize.portfolio.rebalancing](#) [chart.StackedBar](#)

chart.RiskReward *classic risk reward scatter*

Description

This function charts the `optimize.portfolio` object in risk-return space.

Usage

```
chart.RiskReward(object, ...)

## S3 method for class 'optimize.portfolio.DEoptim'
chart.RiskReward(
  object,
  ...,
  neighbors = NULL,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  element.color = "darkgray",
  cex.axis = 0.8,
  xlim = NULL,
  ylim = NULL
)

## S3 method for class 'optimize.portfolio.GenSA'
chart.RiskReward(
  object,
  ...,
  neighbors = NULL,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  element.color = "darkgray",
  cex.axis = 0.8,
```

```
    ylim = NULL,
    xlim = NULL,
    rp = FALSE
)

## S3 method for class 'optimize.portfolio.pso'
chart.RiskReward(
  object,
  ...,
  neighbors = NULL,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  element.color = "darkgray",
  cex.axis = 0.8,
  xlim = NULL,
  ylim = NULL
)

## S3 method for class 'optimize.portfolio.ROI'
chart.RiskReward(
  object,
  ...,
  neighbors = NULL,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  element.color = "darkgray",
  cex.axis = 0.8,
  xlim = NULL,
  ylim = NULL,
  rp = FALSE
)

## S3 method for class 'optimize.portfolio.random'
chart.RiskReward(
  object,
  ...,
  neighbors = NULL,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  element.color = "darkgray",
  cex.axis = 0.8,
  xlim = NULL,
  ylim = NULL
)
```

```
## S3 method for class 'opt.list'
chart.RiskReward(
  object,
  ...,
  risk.col = "ES",
  return.col = "mean",
  main = "",
  ylim = NULL,
  xlim = NULL,
  labels.assets = TRUE,
  chart.assets = FALSE,
  pch.assets = 1,
  cex.assets = 0.8,
  cex.axis = 0.8,
  cex.lab = 0.8,
  colorset = NULL,
  element.color = "darkgray"
)
```

Arguments

object	optimal portfolio created by optimize.portfolio .
...	any other passthru parameters.
neighbors	set of 'neighbor' portfolios to overplot, see Details.
return.col	string matching the objective of a 'return' objective, on vertical axis.
risk.col	string matching the objective of a 'risk' objective, on horizontal axis.
chart.assets	TRUE/FALSE. Includes a risk reward scatter of the assets in the chart.
element.color	color for the default plot scatter points.
cex.axis	The magnification to be used for axis annotation relative to the current setting of cex.
xlim	set the x-axis limit, same as in plot .
ylim	set the y-axis limit, same as in plot .
rp	TRUE/FALSE to generate random portfolios to plot the feasible space
main	a main title for the plot.
labels.assets	TRUE/FALSE to include the names in the plot.
pch.assets	plotting character of the assets, same as in plot
cex.assets	numerical value giving the amount by which the asset points should be magnified relative to the default.
cex.lab	numerical value giving the amount by which the labels should be magnified relative to the default.
colorset	color palette or vector of colors to use.

Details

neighbors may be specified in three ways. The first is as a single number of neighbors. This will extract the neighbors closest portfolios in terms of the out numerical statistic. The second method consists of a numeric vector for neighbors. This will extract the neighbors with portfolio index numbers that correspond to the vector contents. The third method for specifying neighbors is to pass in a matrix. This matrix should look like the output of [extractStats](#), and should contain risk.col,return.col, and weights columns all properly named.

See Also

[optimize.portfolio](#)

chart.Weights	<i>boxplot of the weights of the optimal portfolios</i>
---------------	---

Description

This function charts the optimal weights of a portfolio run via [optimize.portfolio](#) or [optimize.portfolio.rebalancing](#). The upper and lower bounds on weights can be plotted for single period optimizations. The optimal weights will be charted through time for [optimize.portfolio.rebalancing](#) objects. For [optimize.portfolio.rebalancing](#) objects, the weights are plotted with [chart.StackedBar](#).

Usage

```
chart.Weights(object, ...)

## S3 method for class 'optimize.portfolio.rebalancing'
chart.Weights(object, ..., main = "Weights")

## S3 method for class 'optimize.portfolio.DEoptim'
chart.Weights(
  object,
  ...,
  neighbors = NULL,
  main = "Weights",
  las = 3,
  xlab = NULL,
  cex.lab = 1,
  element.color = "darkgray",
  cex.axis = 0.8,
  colorset = NULL,
  legend.loc = "topright",
  cex.legend = 0.8,
  plot.type = "line"
)

## S3 method for class 'optimize.portfolio.GenSA'
```

```
chart.Weights(  
  object,  
  ...,  
  neighbors = NULL,  
  main = "Weights",  
  las = 3,  
  xlab = NULL,  
  cex.lab = 1,  
  element.color = "darkgray",  
  cex.axis = 0.8,  
  colorset = NULL,  
  legend.loc = "topright",  
  cex.legend = 0.8,  
  plot.type = "line"  
)  
  
## S3 method for class 'optimize.portfolio.pso'  
chart.Weights(  
  object,  
  ...,  
  neighbors = NULL,  
  main = "Weights",  
  las = 3,  
  xlab = NULL,  
  cex.lab = 1,  
  element.color = "darkgray",  
  cex.axis = 0.8,  
  colorset = NULL,  
  legend.loc = "topright",  
  cex.legend = 0.8,  
  plot.type = "line"  
)  
  
## S3 method for class 'optimize.portfolio.ROI'  
chart.Weights(  
  object,  
  ...,  
  neighbors = NULL,  
  main = "Weights",  
  las = 3,  
  xlab = NULL,  
  cex.lab = 1,  
  element.color = "darkgray",  
  cex.axis = 0.8,  
  colorset = NULL,  
  legend.loc = "topright",  
  cex.legend = 0.8,  
  plot.type = "line"
```

```

)

## S3 method for class 'optimize.portfolio.random'
chart.Weights(
  object,
  ...,
  neighbors = NULL,
  main = "Weights",
  las = 3,
  xlab = NULL,
  cex.lab = 1,
  element.color = "darkgray",
  cex.axis = 0.8,
  colorset = NULL,
  legend.loc = "topright",
  cex.legend = 0.8,
  plot.type = "line"
)

## S3 method for class 'opt.list'
chart.Weights(
  object,
  neighbors = NULL,
  ...,
  main = "Weights",
  las = 3,
  xlab = NULL,
  cex.lab = 1,
  element.color = "darkgray",
  cex.axis = 0.8,
  colorset = NULL,
  legend.loc = "topright",
  cex.legend = 0.8,
  plot.type = "line"
)

```

Arguments

object	optimal portfolio object created by optimize.portfolio .
...	any other passthru parameters .
main	an overall title for the plot: see title
neighbors	set of 'neighbor' portfolios to overplot. See Details.
las	numeric in {0,1,2,3}; the style of axis labels <ul style="list-style-type: none"> 0: always parallel to the axis, 1: always horizontal, 2: always perpendicular to the axis, 3: always vertical [<i>default</i>].

xlab	a title for the x axis: see title
cex.lab	The magnification to be used for x and y labels relative to the current setting of cex
element.color	provides the color for drawing less-important chart elements, such as the box lines, axis lines, etc.
cex.axis	The magnification to be used for axis annotation relative to the current setting of cex.
colorset	color palette or vector of colors to use.
legend.loc	location of the legend. If NULL, the legend will not be plotted.
cex.legend	The magnification to be used for legend annotation relative to the current setting of cex.
plot.type	"line" or "barplot" to plot.

See Also

[optimize.portfolio](#) [optimize.portfolio.rebalancing](#) [chart.StackedBar](#)

check_constraints	<i>check if a set of weights satisfies the constraints</i>
-------------------	--

Description

This function checks if a set of weights satisfies all constraints. This is used as a helper function for random portfolios created with `rp_simplex` and `rp_grid` to eliminate portfolios that do not satisfy the constraints.

Usage

```
check_constraints(weights, portfolio)
```

Arguments

weights	vector of weights
portfolio	object of class 'portfolio'

Value

TRUE if all constraints are satisfied, FALSE if any constraint is violated

Author(s)

Ross Bennett

 cokurtosisMF

Cokurtosis Matrix Estimate

Description

Estimate cokurtosis matrix using a statistical factor model

Usage

```
cokurtosisMF(beta, stockM2, stockM4, factorM2, factorM4)
```

Arguments

beta	(N x k) matrix of factor loadings (i.e. the betas) from a statistical factor model
stockM2	vector of length N of the 2nd moment of the model residuals
stockM4	vector of length N of the 4th moment of the model residuals
factorM2	(k x k) matrix of the 2nd moment of the factor realizations from a statistical factor model
factorM4	(k x k ³) matrix of the 4th moment of the factor realizations from a statistical factor model

Details

This function estimates an (N x N³) cokurtosis matrix from a statistical factor model with k factors, where N is the number of assets.

Value

(N x N³) cokurtosis matrix

 cokurtosisSF

Cokurtosis Matrix Estimate

Description

Estimate cokurtosis matrix using a single factor statistical factor model

Usage

```
cokurtosisSF(beta, stockM2, stockM4, factorM2, factorM4)
```

Arguments

beta	vector of length N or (N x 1) matrix of factor loadings (i.e. the betas) from a single factor statistical factor model
stockM2	vector of length N of the 2nd moment of the model residuals
stockM4	vector of length N of the 4th moment of the model residuals
factorM2	scalar of the 2nd moment of the factor realizations from a single factor statistical factor model
factorM4	scalar of the 4th moment of the factor realizations from a single factor statistical factor model

Details

This function estimates an $(N \times N^3)$ cokurtosis matrix from a statistical factor model with k factors, where N is the number of assets.

Value

$(N \times N^3)$ cokurtosis matrix

combine.optimizations *Combine objects created by optimize.portfolio*

Description

This function takes a list of objects created by [optimize.portfolio](#) and sets the class name attribute to 'opt.list' for use in generic functions

Usage

```
combine.optimizations(x)
```

Arguments

x a list of objects created by [optimize.portfolio](#)

Value

an opt.list object

combine.portfolios *Combine a list of portfolio objects*

Description

This function takes a list of objects created by [portfolio.spec](#) and sets the class name attribute to 'portfolio.list' for use in generic functions

Usage

```
combine.portfolios(x)
```

Arguments

x a list of objects created by [portfolio.spec](#)

Value

a portfolio.list object

constrained_objective *calculate a numeric return value for a portfolio based on a set of constraints and objectives*

Description

Function to calculate a numeric return value for a portfolio based on a set of constraints and objectives. We'll try to make as few assumptions as possible and only run objectives that are enabled by the user.

Usage

```
constrained_objective_v1(  
  w,  
  R,  
  constraints,  
  ...,  
  trace = FALSE,  
  normalize = TRUE,  
  storage = FALSE  
)
```

```
constrained_objective(  
  w,  
  R,  
  portfolio,
```

```

    ...,
    trace = FALSE,
    normalize = TRUE,
    storage = FALSE,
    env = NULL
)

```

Arguments

<code>w</code>	a vector of weights to test.
<code>R</code>	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns.
<code>constraints</code>	a <code>v1_constraint</code> object for backwards compatibility with <code>constrained_objective_v1</code> .
<code>...</code>	any other passthru parameters.
<code>trace</code>	TRUE/FALSE whether to include debugging and additional detail in the output list. The default is FALSE. Several charting functions require that <code>trace=TRUE</code> .
<code>normalize</code>	TRUE/FALSE whether to normalize results to min/max sum (TRUE), or let the optimizer penalize portfolios that do not conform (FALSE)
<code>storage</code>	TRUE/FALSE default TRUE for DEoptim with trace, otherwise FALSE. not typically user-called.
<code>portfolio</code>	an object of class <code>portfolio</code> specifying the constraints and objectives for the optimization, see portfolio .
<code>env</code>	environment of moments calculated in <code>optimize.portfolio</code>

Details

If the user has passed in either `min_sum` or `max_sum` constraints for the portfolio, or both, and are using a numerical optimization method like DEoptim, and `normalize=TRUE`, we'll normalize the weights passed in to whichever boundary condition has been violated. If using random portfolios, all the portfolios generated will meet the constraints by construction. NOTE: this means that the weights produced by a numeric optimization algorithm like DEoptim, pso, or GenSA might violate constraints, and will need to be renormalized after optimizing. We apply the same normalization in `optimize.portfolio` so that the weights you see have been normalized to `min_sum` if the generated portfolio is smaller than `min_sum` or `max_sum` if the generated portfolio is larger than `max_sum`. This normalization increases the speed of optimization and convergence by several orders of magnitude in many cases.

You may find that for some portfolios, normalization is not desirable, if the algorithm cannot find a direction in which to move to head towards an optimal portfolio. In these cases, it may be best to set `normalize=FALSE`, and penalize the portfolios if the sum of the weighting vector lies outside the `min_sum` and/or `max_sum`.

Whether or not we normalize the weights using `min_sum` and `max_sum`, and are using a numerical optimization engine like DEoptim, we will penalize portfolios that violate weight constraints in much the same way we penalize other constraints. If a `min_sum`/`max_sum` normalization has not occurred, convergence can take a very long time. We currently do not allow for a non-normalized full investment constraint. Future version of this function could include this additional constraint penalty.

When you are optimizing a return objective, you must specify a negative multiplier for the return objective so that the function will maximize return. If you specify a target return, any return that deviates from your target will be penalized. If you do not specify a target return, you may need to specify a negative VTR (value to reach) , or the function will not converge. Try the maximum expected return times the multiplier (e.g. -1 or -10). Adding a return objective defaults the multiplier to -1.

Additional parameters for other solvers (e.g. random portfolios or [DEoptim.control](#) or pso or GenSA may be passed in via ...

Author(s)

Kris Boudt, Peter Carl, Brian G. Peterson, Ross Bennett

See Also

[constraint](#), [objective](#), [DEoptim.control](#)

constraint_ROI	<i>constructor for class constraint_ROI</i>
----------------	---

Description

constructor for class constraint_ROI

Usage

```
constraint_ROI(
  assets = NULL,
  op.problem,
  solver = c("glpk", "quadprog"),
  weight_seq = NULL
)
```

Arguments

assets	number of assets, or optionally a named vector of assets specifying seed weights
op.problem	an object of type "OP" (optimization problem, of ROI) specifying the complete optimization problem, see ROI help pages for proper construction of OP object.
solver	string argument for what solver package to use, must have ROI plugin installed for that solver. Currently support is for glpk and quadprog.
weight_seq	seed sequence of weights, see generateSequence

Author(s)

Hezky Varon

constraint_v1 *constructors for class constraint*

Description

See main documentation entry in [add.constraint](#).

Usage

```
constraint_v1(
  assets = NULL,
  ...,
  min,
  max,
  min_mult,
  max_mult,
  min_sum = 0.99,
  max_sum = 1.01,
  weight_seq = NULL
)
```

```
constraint(type, enabled = TRUE, ..., constrclass = "v2_constraint")
```

Arguments

assets	number of assets, or optionally a named vector of assets specifying initial weights
...	any other passthru parameters
min	numeric or named vector specifying minimum weight box constraints
max	numeric or named vector specifying minimum weight box constraints
min_mult	numeric or named vector specifying minimum multiplier box constraint from initial weight in assets
max_mult	numeric or named vector specifying maximum multiplier box constraint from initial weight in assets
min_sum	minimum sum of all asset weights, default .99
max_sum	maximum sum of all asset weights, default 1.01
weight_seq	seed sequence of weights, see generatesequence
type	character type of the constraint to add or update
enabled	TRUE/FALSE to enabled the constraint
constrclass	name of class for the constraint

Details

This includes the deprecated constructor for the v1_constraint object for backwards compatibility.

Author(s)

Peter Carl, Brian G. Peterson, Ross Bennett

See Also

[add.constraint](#)

coskewnessMF

Coskewness Matrix Estimate

Description

Estimate coskewness matrix using a statistical factor model

Usage

```
coskewnessMF(beta, stockM3, factorM3)
```

Arguments

beta	(N x k) matrix of factor loadings (i.e. the betas) from a statistical factor model
stockM3	vector of length N of the 3rd moment of the model residuals
factorM3	(k x k ²) matrix of the 3rd moment of the factor realizations from a statistical factor model

Details

This function estimates an (N x N²) coskewness matrix from a statistical factor model with k factors, where N is the number of assets.

Value

(N x N²) coskewness matrix

coskewnessSF	<i>Coskewness Matrix Estimate</i>
--------------	-----------------------------------

Description

Estimate coskewness matrix using a single factor statistical factor model

Usage

```
coskewnessSF(beta, stockM3, factorM3)
```

Arguments

beta	vector of length N or (N x 1) matrix of factor loadings (i.e. the betas) from a single factor statistical factor model
stockM3	vector of length N of the 3rd moment of the model residuals
factorM3	scalar of the 3rd moment of the factor realizations from a single factor statistical factor model

Details

This function estimates an (N x N²) coskewness matrix from a single factor statistical factor model with k=1 factors, where N is the number of assets.

Value

(N x N²) coskewness matrix

covarianceMF	<i>Covariance Matrix Estimate</i>
--------------	-----------------------------------

Description

Estimate covariance matrix using a statistical factor model

Usage

```
covarianceMF(beta, stockM2, factorM2)
```

Arguments

beta	(N x k) matrix of factor loadings (i.e. the betas) from a statistical factor model
stockM2	vector of length N of the variance (2nd moment) of the model residuals (i.e. idiosyncratic variance of the stock)
factorM2	(k x k) matrix of the covariance (2nd moment) of the factor realizations from a statistical factor model

Details

This function estimates an (N x N) covariance matrix from a statistical factor model with k factors, where N is the number of assets.

Value

(N x N) covariance matrix

covarianceSF	<i>Covariance Matrix Estimate</i>
--------------	-----------------------------------

Description

Estimate covariance matrix using a single factor statistical factor model

Usage

```
covarianceSF(beta, stockM2, factorM2)
```

Arguments

beta	vector of length N or (N x 1) matrix of factor loadings (i.e. the betas) from a single factor statistical factor model
stockM2	vector of length N of the variance (2nd moment) of the model residuals (i.e. idiosyncratic variance of the stock)
factorM2	scalar value of the 2nd moment of the factor realizations from a single factor statistical factor model

Details

This function estimates an (N x N) covariance matrix from a single factor statistical factor model with k=1 factors, where N is the number of assets.

Value

(N x N) covariance matrix

```
create.EfficientFrontier
      create an efficient frontier
```

Description

create an efficient frontier

Usage

```
create.EfficientFrontier(
  R,
  portfolio,
  type,
  optimize_method = "CVXR",
  n.portfolios = 25,
  risk_aversion = NULL,
  match.col = "ES",
  search_size = 2000,
  ...
)
```

Arguments

R	xts object of asset returns
portfolio	object of class 'portfolio' specifying the constraints and objectives, see portfolio.spec .
type	type of efficient frontier, see Details.
optimize_method	the optimize method to get the efficient frontier, default is CVXR
n.portfolios	number of portfolios to calculate along the efficient frontier
risk_aversion	vector of risk_aversion values to construct the efficient frontier. n.portfolios is ignored if risk_aversion is specified and the number of points along the efficient frontier will be equal to the length of risk_aversion.
match.col	column to match when extracting the efficient frontier from an objected created by optimize.portfolio .
search_size	passed to optimize.portfolio for type="DEoptim" or type="random".
...	passthrough parameters to optimize.portfolio .

Details

Currently there are 4 'types' supported to create an efficient frontier:

"mean-var", "mean-sd", or "mean-StdDev": This is a special case for an efficient frontier that can be created by a QP solver. The portfolio object should have two objectives: 1) mean and 2) var. If the portfolio object does not contain these objectives, they will be added using default parameters. The efficient frontier will be created via [meanvar.efficient.frontier](#).

- "mean-ETL", "mean-ES", "mean-CVaR", "mean-etl"**: This is a special case for an efficient frontier that can be created by an LP solver. The `portfolio` object should have two objectives: 1) mean and 2) ETL/ES/CVaR. If the `portfolio` object does not contain these objectives, they will be added using default parameters. The efficient frontier is created via `meanetl.efficient.frontier`.
- "mean-CSM"**: This is a special case for an efficient frontier that can be created by CVXR solvers. The `portfolio` object should have two objectives: 1) mean and 2) CSM. If the `portfolio` object does not contain these objectives, they will be added using default parameters. The efficient frontier is created via `meanrisk.efficient.frontier`.
- "mean-risk"**: This is a special case for multiple efficient frontiers. The efficient frontier is created via `meanrisk.efficient.frontier`.
- "DEoptim"**: This can handle more complex constraints and objectives than the simple mean-var and mean-ETL cases. For this type, we actually call `optimize.portfolio` with `optimize_method="DEoptim"` and then extract the efficient frontier with `extract.efficient.frontier`.
- "random"**: This can handle more complex constraints and objectives than the simple mean-var and mean-ETL cases. For this type, we actually call `optimize.portfolio` with `optimize_method="random"` and then extract the efficient frontier with `extract.efficient.frontier`.

Value

an object of class 'efficient.frontier' with the objective measures and weights of portfolios along the efficient frontier.

Author(s)

Ross Bennett, Xinran Zhao

See Also

`optimize.portfolio`, `portfolio.spec`, `meanvar.efficient.frontier`, `meanetl.efficient.frontier`

custom.covRob.Mcd	<i>Compute returns mean vector and covariance matrix with custom.covRob.Mcd</i>
-------------------	---

Description

`custom.covRob.Mcd` uses the `robustbase` package function `covMcd` to compute a robust mean vector and robust covariance matrix for a portfolio's asset returns

Usage

```
custom.covRob.Mcd(R, ...)
```

Arguments

R	xts object of asset returns
...	parameters for <code>covRob.Mcd</code>

Details

For parameter details, see covMcd in the robustbase Reference Manual at <https://CRAN.R-project.org/package=robustbase>

Value

a list containing covariance matrix sigma and mean vector mu

custom.covRob.MM	<i>Compute returns mean vector and covariance matrix with custom.covRob.MM</i>
------------------	--

Description

custom.covRob.MM uses the RobStatTM package function covRobMM to compute a robust mean vector and robust covariance matrix for a portfolio's asset returns

Usage

```
custom.covRob.MM(R, ...)
```

Arguments

R	xts object of asset returns
...	parameters for covRob.MM

Value

a list containing covariance matrix sigma and mean vector mu

Author(s)

Yifu Kang, Xinran Zhao

References

For parameter details, see covRobMM in the RobStatTM Reference Manual at <https://CRAN.R-project.org/package=RobStatTM>

custom.covRob.Rocke *Compute returns mean vector and covariance matrix with custom.covRob.Rocke*

Description

custom.covRob.Rocke uses the RobStatTM package function covRobRocke to compute a robust mean vector and robust covariance matrix for a portfolio's asset returns

Usage

```
custom.covRob.Rocke(R, ...)
```

Arguments

R xts object of asset returns
... parameters for covRob.Rocke

Details

For parameter details, see covRobRocke in the RobStatTM Reference Manual at <https://CRAN.R-project.org/package=RobStatTM>

Value

a list containing covariance matrix sigma and mean vector mu

Author(s)

Yifu Kang

custom.covRob.TSGS *Compute returns mean vector and covariance matrix with custom.covRob.TSGS*

Description

This is a function uses the TSGS function from GSE package to compute the Two-Step Generalized S-Estimate, a robust estimate of location and scatter for data with cell-wise and case-wise contamination.

Usage

```
custom.covRob.TSGS(R, ...)
```

Arguments

R xts object of asset returns
... parameters for covRob.TSGS

Value

a list contains mean and covariance matrix of the stock return matrix

References

Claudio Agostinelli, Andy Leung, "Robust estimation of multivariate location and scatter in the presence of cellwise and casewise contamination", 2014.

diversification *Function to compute diversification as a constraint*

Description

Diversification is defined as 1 minus the sum of the squared weights

$$\text{diversification} = 1 - \text{sum}(w^2)$$

Usage

diversification(weights)

Arguments

weights vector of asset weights

Author(s)

Ross Bennett

diversification_constraint
constructor for diversification_constraint

Description

The diversification constraint specifies a target diversification value. This function is called by `add.constraint` when `type="diversification"` is specified, see [add.constraint](#). Diversification is computed as $1 - \text{sum}(\text{weights}^2)$.

Usage

```
diversification_constraint(  
  type = "diversification",  
  div_target = NULL,  
  enabled = TRUE,  
  message = FALSE,  
  ...  
)
```

Arguments

<code>type</code>	character type of the constraint
<code>div_target</code>	diversification target value
<code>enabled</code>	TRUE/FALSE
<code>message</code>	TRUE/FALSE. The default is <code>message=FALSE</code> . Display messages if TRUE.
<code>...</code>	any other passthru parameters to specify diversification constraint an object of class 'diversification_constraint'

Author(s)

Ross Bennett

See Also

[add.constraint](#)

Examples

```
data(edhec)  
ret <- edhec[, 1:4]  
  
pspec <- portfolio.spec(assets=colnames(ret))  
  
pspec <- add.constraint(portfolio=pspec, type="diversification", div_target=0.7)
```

EntropyProg	<i>Entropy pooling program for blending views on scenarios with a prior scenario-probability distribution</i>
-------------	---

Description

Entropy program will change the initial predictive distribution 'p' to a new set 'p_' that satisfies specified moment conditions but changes other properties of the new distribution the least by minimizing the relative entropy between the two distributions. Theoretical note: Relative Entropy (Kullback-Leibler information criterion KLIC) is an asymmetric measure.

Usage

EntropyProg(p, A = NULL, b = NULL, Aeq, beq, verbose = FALSE)

Arguments

p	a vector of initial probabilities based on prior (reference model, empirical distribution, etc.). Sum of 'p' must be 1
A	matrix consisting of inequality constraints (paired with argument 'b'). Denoted as 'F' in the Meucci paper
b	vector consisting of inequality constraints (paired with matrix A). Denoted as 'f' in the Meucci paper
Aeq	matrix consisting of equality constraints (paired with argument 'beq'). Denoted as 'H' in the Meucci paper. (denoted as 'H' in the "Meucci - Flexible Views Theory & Practice" paper formula 86 on page 22)
beq	vector corresponding to the matrix of equality constraints (paired with argument 'Aeq'). Denoted as 'h' in the Meucci paper
verbose	If TRUE, prints out additional information. Default FALSE.

$$\tilde{p} \equiv \operatorname{argmin}_{F x \leq f, H x = h} \left\{ \sum_1^J x_j (\ln(x_j) - \ln(p_j)) \right\} \ell(x, \lambda, \nu) \equiv x' (\ln(x) - \ln(p)) + \lambda' (F x - f) + \nu' (H x - h)$$

Details

We retrieve a new set of probabilities for the joint-scenarios using the Entropy pooling method. Of the many choices of 'p' that satisfy the views, we choose 'p' that minimize the entropy or distance of the new probability distribution to the prior joint-scenario probabilities.

We use Kullback-Leibler divergence or relative entropy $\operatorname{dist}(p, q)$: $\sum p \cdot \ln(p/q)$. Therefore we define solution as $p^* = \operatorname{argmin}(\text{choice of } p) [\sum \text{ across all scenarios: } p \cdot \ln(p/q)]$, such that 'p' satisfies views. The views modify the prior in a coherent manner (minimizing distortion). We formulate the stress tests of the baseline scenarios as linear constraints on yet-to-be defined probabilities. Note that the numerical optimization acts on a very limited number of variables equal to the number of views. It does not act directly on the very large

number of variables of interest, namely the probabilities of the Monte Carlo scenarios. This feature guarantees the numerical feasibility of entropy optimization.

Note that new probabilities are generated in much the same way that the state-price density modifies objective probabilities of pay-offs to risk-neutral probabilities in contingent-claims asset pricing

Compute posterior (=change of measure) with Entropy Pooling, as described in

Value

a list with

`p_`: revised probabilities based on entropy pooling

`optimizationPerformance`: a list with status of optimization, value, number of iterations, and sum of probabilities

Author(s)

Ram Ahluwalia <ram@wingedfootcapital.com>

References

A. Meucci - "Fully Flexible Views: Theory and Practice". See page 22 for illustration of numerical implementation Symmys site containing original MATLAB source code <https://www.arpm.co/> NLOPT open-source optimization site containing background on algorithms <https://nlopt.readthedocs.io/en/latest/> We use the information-theoretic estimator of Kitamura and Stutzer (1997). Reversing 'p' and 'p_' leads to the empirical likelihood" estimator of Qin and Lawless (1994). See Robertson et al, "Forecasting Using Relative Entropy" (2002) for more theory

equal.weight

Create an equal weight portfolio

Description

This function calculates objective measures for an equal weight portfolio.

Usage

```
equal.weight(R, portfolio, ...)
```

Arguments

<code>R</code>	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
<code>portfolio</code>	an object of type "portfolio" specifying the constraints and objectives for the optimization
<code>...</code>	any other passthru parameters to <code>constrained_objective</code>

Details

This function is simply a wrapper around [constrained_objective](#) to calculate the objective measures in the given portfolio object of an equal weight portfolio. The portfolio object should include all objectives to be calculated.

Value

a list containing the returns, weights, objective measures, call, and portfolio object

Author(s)

Ross Bennett

 etl_milp_opt

Minimum ETL MILP Optimization

Description

This function is called by `optimize.portfolio` to solve minimum ETL problems via mixed integer linear programming.

Usage

```
etl_milp_opt(
  R,
  constraints,
  moments,
  target,
  alpha,
  solver = "glpk",
  control = NULL
)
```

Arguments

R	xts object of asset returns
constraints	object of constraints in the portfolio object extracted with <code>get_constraints</code>
moments	object of moments computed based on objective functions
target	target return value
alpha	alpha value for ETL/ES/CVaR
solver	solver to use
control	list of solver control parameters

Author(s)

Ross Bennett

etl_opt	<i>Minimum ETL LP Optimization</i>
---------	------------------------------------

Description

This function is called by `optimize.portfolio` to solve minimum ETL problems.

Usage

```
etl_opt(
  R,
  constraints,
  moments,
  target,
  alpha,
  solver = "glpk",
  control = NULL
)
```

Arguments

R	xts object of asset returns
constraints	object of constraints in the portfolio object extracted with <code>get_constraints</code>
moments	object of moments computed based on objective functions
target	target return value
alpha	alpha value for ETL/ES/CVaR
solver	solver to use
control	list of solver control parameters

Author(s)

Ross Bennett

extractCokurtosis	<i>Cokurtosis Estimate</i>
-------------------	----------------------------

Description

Extract the cokurtosis matrix estimate from a statistical factor model

Usage

```
extractCokurtosis(model, ...)
```

Arguments

model statistical factor model estimated via [statistical.factor.model](#)
... not currently used

Value

co-kurtosis matrix estimate

Author(s)

Ross Bennett

See Also

[statistical.factor.model](#)

extractCoskewness *Coskewness Estimate*

Description

Extract the coskewness matrix estimate from a statistical factor model

Usage

```
extractCoskewness(model, ...)
```

Arguments

model statistical factor model estimated via [statistical.factor.model](#)
... not currently used

Value

coskewness matrix estimate

Author(s)

Ross Bennett

See Also

[statistical.factor.model](#)

extractCovariance	<i>Covariance Estimate</i>
-------------------	----------------------------

Description

Extract the covariance matrix estimate from a statistical factor model

Usage

```
extractCovariance(model, ...)
```

Arguments

model	statistical factor model estimated via statistical.factor.model
...	not currently used

Value

covariance matrix estimate

Author(s)

Ross Bennett

See Also

[statistical.factor.model](#)

extractEfficientFrontier

Extract the efficient frontier data points

Description

This function extracts the efficient frontier from an object created by [optimize.portfolio](#).

Usage

```
extractEfficientFrontier(  
  object,  
  match.col = "ES",  
  n.portfolios = 25,  
  risk_aversion = NULL  
)
```

Arguments

object	an optimal portfolio object created by <code>optimize.portfolio</code>
match.col	string name of column to use for risk (horizontal axis). <code>match.col</code> must match the name of an objective measure in the <code>objective_measures</code> or <code>opt_values</code> slot in the object created by <code>optimize.portfolio</code> .
n.portfolios	number of portfolios to use to plot the efficient frontier
risk_aversion	vector of <code>risk_aversion</code> values to construct the efficient frontier. <code>n.portfolios</code> is ignored if <code>risk_aversion</code> is specified and the number of points along the efficient frontier is equal to the length of <code>risk_aversion</code> .

Details

If the object is an `optimize.portfolio.ROI` object and `match.col` is "ES", "ETL", or "CVaR", then the mean-ETL efficient frontier will be created via `meanetl.efficient.frontier`.

If the object is an `optimize.portfolio.ROI` object and `match.col` is "StdDev", then the mean-StdDev efficient frontier will be created via `meanvar.efficient.frontier`. Note that if 'var' is specified as the name of an objective, the value returned will be 'StdDev'.

For objects created by `optimize.portfolio` with the DEoptim, random, or pso solvers, the efficient frontier will be extracted from the object via `extract.efficient.frontier`. This means that `optimize.portfolio` must be run with `trace=TRUE`.

Value

an `efficient.frontier` object with weights and other metrics along the efficient frontier

Author(s)

Ross Bennett

extractGroups	<i>Extract the group and/or category weights</i>
---------------	--

Description

This function extracts the weights by group and/or category from an object of class `optimize.portfolio`. Group constraints or `category_labels` must be specified for this to return group constraints.

Usage

```
extractGroups(object, ...)
```

Arguments

object	object of class <code>optimize.portfolio</code>
...	passthrough parameters. Not currently used

Value

a list with two elements

weights: Optimal set of weights from the `optimize.portfolio` object

category_weights: Weights by category if `category_labels` are supplied in the `portfolio` object

group_weights: Weights by group if `group` is a constraint type

Author(s)

Ross Bennett

`extractObjectiveMeasures`

Extract the objective measures

Description

This function will extract the objective measures from the optimal portfolio run via `optimize.portfolio`

Usage

```
extractObjectiveMeasures(object)
```

Arguments

`object` list returned by `optimize.portfolio`

Value

list of objective measures

Author(s)

Ross Bennett

See Also

[optimize.portfolio](#)

extractStats	<i>extract some stats and weights from a portfolio run via optimize.portfolio</i>
--------------	---

Description

This function will dispatch to the appropriate class handler based on the input class of the `optimize.portfolio` output object.

Usage

```
extractStats(object, prefix = NULL, ...)
```

Arguments

object	list returned by <code>optimize.portfolio</code>
prefix	prefix to add to output row names
...	any other passthru parameters

Details

For `optimize.portfolio` objects:

In general, `extractStats` will extract the values objective measures and weights at each iteration of a set of weights. This is the case for the `DEoptim`, random portfolios, and `pso` solvers that return trace information. Note that `trace=TRUE` must be specified in `optimize.portfolio` to return the trace information.

For `optimize.portfolio.pso` objects, this function will extract the weights (swarm positions) from the PSO output and the out values (swarm fitness values) for each iteration of the optimization. This function can be slow because we need to run `constrained_objective` to calculate the objective measures on the transformed weights.

For `optimize.portfolio.rebalancing` objects:

The `extractStats` function will return a list of the objective measures and weights at each rebalance date for `optimize.portfolio.rebalancing` objects. The objective measures and weights of each iteration or permutation will be returned if the optimization was done with `DEoptim`, random portfolios, or `pso`. This could potentially result in a very large list object where each list element has thousands of rows of at each rebalance period.

The output from the `GenSA` solver does not store weights evaluated at each iteration. The `GenSA` output for `trace.mat` contains `nb.steps`, `temperature`, `function.value`, and `current.minimum`

See Also

[optimize.portfolio](#)

extractWeights	<i>Extract weights from a portfolio run via optimize.portfolio or optimize.portfolio.rebalancing</i>
----------------	--

Description

This function will dispatch to the appropriate class handler based on the input class of the optimize.portfolio or optimize.portfolio.rebalancing output object

Usage

```
extractWeights(object, ...)
```

Arguments

object	list returned by optimize.portfolio
...	any other passthru parameters

See Also

[optimize.portfolio](#), [optimize.portfolio.rebalancing](#)

extract_risk	<i>extract the risk value when knowing the weights</i>
--------------	--

Description

extract the risk value when knowing the weights

Usage

```
extract_risk(  
  R,  
  w,  
  ES_alpha = 0.05,  
  CSM_alpha = 0.05,  
  EQS_alpha = 0.05,  
  moment_setting = NULL  
)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
w	the weight of the portfolio
ES_alpha	the default value is 0.05, but could be specified as any value between 0 and 1
CSM_alpha	the default value is 0.05, but could be specified as any value between 0 and 1
EQS_alpha	the default value is 0.05, but could be specified as any value between 0 and 1
moment_setting	the default is NULL, should provide moment_setting=list(mu=, sigma=) if customize momentFUN

factor_exposure_constraint

Constructor for factor exposure constraint

Description

The factor exposure constraint sets upper and lower bounds on exposures to risk factors. This function is called by `add.constraint` when `type="factor_exposure"` is specified, see [add.constraint](#)

Usage

```
factor_exposure_constraint(
  type = "factor_exposure",
  assets,
  B,
  lower,
  upper,
  enabled = TRUE,
  message = FALSE,
  ...
)
```

Arguments

type	character type of the constraint
assets	named vector of assets specifying initial weights
B	vector or matrix of risk factor exposures
lower	vector of lower bounds of constraints for risk factor exposures
upper	vector of upper bounds of constraints for risk factor exposures
enabled	TRUE/FALSE
message	TRUE/FALSE. The default is message=FALSE. Display messages if TRUE.
...	any other passthru parameters to specify risk factor exposure constraints

Details

B can be either a vector or matrix of risk factor exposures (i.e. betas). If B is a vector, the length of B must be equal to the number of assets and lower and upper must be scalars. If B is passed in as a vector, it will be converted to a matrix with one column.

If B is a matrix, the number of rows must be equal to the number of assets and the number of columns represent the number of factors. The length of lower and upper must be equal to the number of factors. The B matrix should have column names specifying the factors and row names specifying the assets. Default column names and row names will be assigned if the user passes in a B matrix without column names or row names.

Value

an object of class 'factor_exposure_constraint'

Author(s)

Ross Bennett

See Also

[add.constraint](#)

fn_map	<i>mapping function to transform or penalize weights that violate constraints</i>
--------	---

Description

The purpose of the mapping function is to transform a weights vector that does not meet all the constraints into a weights vector that does meet the constraints, if one exists, hopefully with a minimum of transformation.

Usage

```
fn_map(weights, portfolio, relax = FALSE, verbose = FALSE, ...)
```

Arguments

weights	vector of weights
portfolio	object of class portfolio
relax	TRUE/FALSE, default FALSE. Enable constraints to be relaxed.
verbose	print error messages for debuggin purposes
...	any other passthru parameters

Details

The first step is to test for violation of the constraint. If the constraint is violated, we will apply a transformation such that the weights vector satisfies the constraints. The following constraint types are tested in the mapping function: leverage, box, group, and position limit. The transformation logic is based on code from the random portfolio sample method.

If relax=TRUE, we will attempt to relax the constraints if a feasible portfolio could not be formed with an initial call to rp_transform. We will attempt to relax the constraints up to 5 times. If we do not have a feasible portfolio after attempting to relax the constraints, then we will default to returning the weights vector that violates the constraints.

Value

weights: vector of transformed weights meeting constraints.

min: vector of min box constraints that may have been modified if relax=TRUE.

max: vector of max box constraints that may have been modified if relax=TRUE.

cLO: vector of lower bound group constraints that may have been modified if relax=TRUE.

cUP: vector of upper bound group constraints that may have been modified if relax=TRUE.

Author(s)

Ross Bennett

generatesequence	<i>create a sequence of possible weights for random or brute force portfolios</i>
------------------	---

Description

This function creates the sequence of min<->max weights for use by random or brute force optimization engines.

Usage

```
generatesequence(min = 0.01, max = 1, by = min/max, rounding = 3)
```

Arguments

min	minimum value of the sequence
max	maximum value of the sequence
by	number to increment the sequence by
rounding	integer how many decimals should we round to

Details

The sequence created is not constrained by asset.

Author(s)

Peter Carl, Brian G. Peterson

See Also

[constraint](#), [objective](#)

get_constraints	<i>Helper function to get the enabled constraints out of the portfolio object When the v1_constraint object is instantiated via constraint, the arguments min_sum, max_sum, min, and max are either specified by the user or default values are assigned. These are required by other functions such as optimize.portfolio and constrained_objective . This function will check that these variables are in the portfolio object in the constraints list. We will default to min_sum=1 and max_sum=1 if leverage constraints are not specified. We will default to min=-Inf and max=Inf if box constraints are not specified. This function is used at the beginning of optimize.portfolio and other functions to extract the constraints from the portfolio object. We Use the same naming as the v1_constraint object.</i>
-----------------	--

Description

Helper function to get the enabled constraints out of the portfolio object

When the v1_constraint object is instantiated via constraint, the arguments min_sum, max_sum, min, and max are either specified by the user or default values are assigned. These are required by other functions such as optimize.portfolio and constrained_objective . This function will check that these variables are in the portfolio object in the constraints list. We will default to min_sum=1 and max_sum=1 if leverage constraints are not specified. We will default to min=-Inf and max=Inf if box constraints are not specified. This function is used at the beginning of optimize.portfolio and other functions to extract the constraints from the portfolio object. We Use the same naming as the v1_constraint object.

Usage

```
get_constraints(portfolio)
```

Arguments

portfolio an object of class 'portfolio'

Value

an object of class 'constraint' which is a flattened list of enabled constraints

Author(s)

Ross Bennett

See Also

[portfolio.spec](#)

gmv_opt

GMV/QU QP Optimization

Description

This function is called by `optimize.portfolio` to solve minimum variance or maximum quadratic utility problems

Usage

```
gmv_opt(
  R,
  constraints,
  moments,
  lambda,
  target,
  lambda_hhi,
  conc_groups,
  solver = "quadprog",
  control = NULL
)
```

Arguments

R	xts object of asset returns
constraints	object of constraints in the portfolio object extracted with <code>get_constraints</code>
moments	object of moments computed based on objective functions
lambda	risk_aversion parameter
target	target return value
lambda_hhi	concentration aversion parameter
conc_groups	list of vectors specifying the groups of the assets.
solver	solver to use
control	list of solver control parameters

Author(s)

Ross Bennett

gmv_opt_leverage	<i>GMV/QU QP Optimization with Turnover Constraint</i>
------------------	--

Description

This function is called by `optimize.portfolio` to solve minimum variance or maximum quadratic utility problems with a leverage constraint

Usage

```
gmv_opt_leverage(
  R,
  constraints,
  moments,
  lambda,
  target,
  solver = "quadprog",
  control = NULL
)
```

Arguments

R	xts object of asset returns
constraints	object of constraints in the portfolio object extracted with <code>get_constraints</code>
moments	object of moments computed based on objective functions
lambda	risk_aversion parameter
target	target return value
solver	solver to use
control	list of solver control parameters

Author(s)

Ross Bennett

gmv_opt_ptc	<i>GMV/QU QP Optimization with Proportional Transaction Cost Constraint</i>
-------------	---

Description

This function is called by `optimize.portfolio` to solve minimum variance or maximum quadratic utility problems with proportional transaction cost constraint

Usage

```

gmv_opt_ptc(
  R,
  constraints,
  moments,
  lambda,
  target,
  init_weights,
  solver = "quadprog",
  control = NULL
)

```

Arguments

R	xts object of asset returns
constraints	object of constraints in the portfolio object extracted with get_constraints
moments	object of moments computed based on objective functions
lambda	risk_aversion parameter
target	target return value
init_weights	initial weights to compute turnover
solver	solver to use
control	list of solver control parameters

Author(s)

Ross Bennett

gmv_opt_toc

GMV/QU QP Optimization with Turnover Constraint

Description

This function is called by optimize.portfolio to solve minimum variance or maximum quadratic utility problems with turnover constraint

Usage

```

gmv_opt_toc(
  R,
  constraints,
  moments,
  lambda,
  target,
  init_weights,
  solver = "quadprog",
  control = NULL
)

```

Arguments

R	xts object of asset returns
constraints	object of constraints in the portfolio object extracted with <code>get_constraints</code>
moments	object of moments computed based on objective functions
lambda	risk_aversion parameter
target	target return value
init_weights	initial weights to compute turnover
solver	solver to use
control	list of solver control parameters

Author(s)

Ross Bennett

group_constraint *constructor for group_constraint*

Description

Group constraints specify the grouping of the assets, weights of the groups, and number of positions (i.e. non-zero weights) of the groups. This function is called by `add.constraint` when `type="group"` is specified. see [add.constraint](#)

Usage

```
group_constraint(
  type = "group",
  assets,
  groups,
  group_labels = NULL,
  group_min,
  group_max,
  group_pos = NULL,
  enabled = TRUE,
  message = FALSE,
  ...
)
```

Arguments

type	character type of the constraint
assets	number of assets, or optionally a named vector of assets specifying initial weights
groups	list of vectors specifying the groups of the assets
group_labels	character vector to label the groups (e.g. size, asset class, style, etc.)


```
group_max=c(0.65, 0.55, 0.5, 0.4))
```

group_fail

Test if group constraints have been violated

Description

The function loops through each group and tests if cLO or cUP have been violated for the given group. This is a helper function for [rp_transform](#).

Usage

```
group_fail(weights, groups, cLO, cUP, group_pos = NULL)
```

Arguments

weights	weights vector to test
groups	list of vectors specifying the groups of the assets
cLO	numeric or vector specifying minimum weight group constraints
cUP	numeric or vector specifying minimum weight group constraints
group_pos	vector specifying the number of non-zero weights per group

Value

logical vector: TRUE if group constraints are violated for a given group

Author(s)

Ross Bennett

HHI

Concentration of weights

Description

This function computes the concentration of weights using the Herfindahl Hirschman Index

Usage

```
HHI(weights, groups = NULL)
```

Arguments

weights	set of portfolio weights
groups	list of vectors of grouping

Author(s)

Ross Bennett

`indexes`*Six Major Economic Indexes*

Description

Monthly data of five indexes beginning on 1980-01-31 and ending 2009-12-31. The indexes are: US Bonds, US Equities, International Equities, Commodities, US T-Bills, and Inflation

Usage`data(indexes)`**Format**

CSV converted into xts object with montly observations

Examples

```
data(indexes)

#preview the data
head(indexes)

#summary period statistics
summary(indexes)
```

`insert_constraints`*Insert a list of constraints into the constraints slot of a portfolio object*

Description

This is a helper function primarily for backwards compatibility to insert constraints from a 'v1_constraint' object into the v2 'portfolio' object.

Usage`insert_constraints(portfolio, constraints)`**Arguments**

<code>portfolio</code>	object of class 'portfolio'
<code>constraints</code>	list of constraint objects

Author(s)

Ross Bennett

insert_objectives	<i>Insert a list of objectives into the objectives slot of a portfolio object</i>
-------------------	---

Description

This is a helper function primarily for backwards compatibility to insert objectives from a 'v1_constraint' object into the v2 'portfolio' object.

Usage

```
insert_objectives(portfolio, objectives)
```

Arguments

portfolio	object of class 'portfolio'
objectives	list of objective objects

Author(s)

Ross Bennett

inverse.volatility.weight	<i>Create an inverse volatility weighted portfolio</i>
---------------------------	--

Description

This function calculates objective measures for an equal weight portfolio.

Usage

```
inverse.volatility.weight(R, portfolio, ...)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
portfolio	an object of type "portfolio" specifying the constraints and objectives for the optimization
...	any other passthru parameters to constrained_objective

Details

This function is simply a wrapper around [constrained_objective](#) to calculate the objective measures in the given portfolio object of an inverse volatility weight portfolio. The portfolio object should include all objectives to be calculated.

Value

a list containing the returns, weights, objective measures, call, and portfolio object

Author(s)

Peter Carl

is.constraint *check function for constraints*

Description

check function for constraints

Usage

```
is.constraint(x)
```

Arguments

x object to test for type constraint

Author(s)

Brian G. Peterson

is.objective *check class of an objective object*

Description

check class of an objective object

Usage

```
is.objective(x)
```

Arguments

x an object potentially of type 'objective' to test

Author(s)

Brian G. Peterson

is.portfolio	<i>check function for portfolio</i>
--------------	-------------------------------------

Description

check function for portfolio

Usage

```
is.portfolio(x)
```

Arguments

x	object to test for type portfolio
---	-----------------------------------

Author(s)

Ross Bennett

leverage_exposure_constraint	<i>constructor for leverage_exposure_constraint</i>
------------------------------	---

Description

The leverage_exposure constraint specifies a maximum leverage where leverage is defined as the sum of the absolute value of the weights. Leverage exposure is computed as the sum of the absolute value of the weights, `sum(abs(weights))`.

Usage

```
leverage_exposure_constraint(
  type = "leverage_exposure",
  leverage = NULL,
  enabled = TRUE,
  message = FALSE,
  ...
)
```

Arguments

type	character type of the constraint
leverage	maximum leverage value
enabled	TRUE/FALSE
message	TRUE/FALSE. The default is message=FALSE. Display messages if TRUE.
...	any other passthru parameters to specify diversification constraint an object of class 'diversification_constraint'

Details

This should be used for constructing, for example, 130/30 portfolios or dollar neutral portfolios with 2:1 leverage. For the ROI solvers, this is implemented as a MILP problem and is not supported for problems formulated as a quadratic programming problem. This may change in the future if a MIQP solver is added.

This function is called by `add.constraint` when `type="leverage_exposure"` is specified, see [add.constraint](#).

Author(s)

Ross Bennett

See Also

[add.constraint](#)

Examples

```
data(edhec)
ret <- edhec[, 1:4]

pspec <- portfolio.spec(assets=colnames(ret))

pspec <- add.constraint(portfolio=pspec, type="leverage_exposure", leverage=1.6)
```

maxret_milp_opt

Maximum Return MILP Optimization

Description

This function is called by `optimize.portfolio` to solve maximum return problems via mixed integer linear programming.

Usage

```
maxret_milp_opt(
  R,
  constraints,
  moments,
  target,
  solver = "glpk",
  control = NULL
)
```

Arguments

R	xts object of asset returns
constraints	object of constraints in the portfolio object extracted with get_constraints
moments	object of moments computed based on objective functions
target	target return value
solver	solver to use
control	list of solver control parameters

Author(s)

Ross Bennett

maxret_opt

Maximum Return LP Optimization

Description

This function is called by optimize.portfolio to solve maximum return

Usage

```
maxret_opt(R, moments, constraints, target, solver = "glpk", control = NULL)
```

Arguments

R	xts object of asset returns
moments	object of moments computed based on objective functions
constraints	object of constraints in the portfolio object extracted with get_constraints
target	target return value
solver	solver to use
control	list of solver control parameters

Author(s)

Ross Bennett

`meancsm.efficient.frontier`*Generate the efficient frontier for a mean-CSM portfolio*

Description

This function generates the mean-CSM efficient frontier of a portfolio specifying the constraints and objectives. The `portfolio` object should have two objectives: 1) mean and 2) CSM. If the portfolio object does not contain these objectives, they will be added using default parameters.

Usage

```
meancsm.efficient.frontier(  
  portfolio,  
  R,  
  optimize_method = "CVXR",  
  n.portfolios = 25,  
  ...  
)
```

Arguments

<code>portfolio</code>	a portfolio object with constraints and objectives created via portfolio.spec
<code>R</code>	an xts or matrix of asset returns
<code>optimize_method</code>	the optimize method to get the efficient frontier, default is CVXR
<code>n.portfolios</code>	number of portfolios to generate the efficient frontier
<code>...</code>	passthru parameters to optimize.portfolio

Value

a matrix of objective measure values and weights along the efficient frontier

Author(s)

Xinran Zhao

`meaneqs.efficient.frontier`*Generate the efficient frontier for a mean-EQS portfolio*

Description

This function generates the mean-EQS efficient frontier of a portfolio specifying the constraints and objectives. The `portfolio` object should have two objectives: 1) mean and 2) EQS. If the portfolio object does not contain these objectives, they will be added using default parameters.

Usage

```
meaneqs.efficient.frontier(  
  portfolio,  
  R,  
  optimize_method = "CVXR",  
  n.portfolios = 25,  
  ...  
)
```

Arguments

<code>portfolio</code>	a portfolio object with constraints and objectives created via portfolio.spec
<code>R</code>	an xts or matrix of asset returns
<code>optimize_method</code>	the optimize method to get the efficient frontier, default is CVXR
<code>n.portfolios</code>	number of portfolios to generate the efficient frontier
<code>...</code>	passthru parameters to optimize.portfolio

Value

a matrix of objective measure values and weights along the efficient frontier

Author(s)

Xinran Zhao

`meanetl.efficient.frontier`*Generate the efficient frontier for a mean-etl portfolio*

Description

This function generates the mean-ETL efficient frontier of a portfolio specifying the constraints and objectives. The `portfolio` object should have two objectives: 1) mean and 2) ES (or ETL or cVaR). If the portfolio object does not contain these objectives, they will be added using default parameters.

Usage

```
meanetl.efficient.frontier(  
  portfolio,  
  R,  
  optimize_method = "CVXR",  
  n.portfolios = 25,  
  ...  
)
```

Arguments

<code>portfolio</code>	a portfolio object with constraints and objectives created via portfolio.spec
<code>R</code>	an xts or matrix of asset returns
<code>optimize_method</code>	the optimize method to get the efficient frontier, default is CVXR
<code>n.portfolios</code>	number of portfolios to generate the efficient frontier
<code>...</code>	passthru parameters to optimize.portfolio

Value

a matrix of objective measure values and weights along the efficient frontier

Author(s)

Ross Bennett

```
meanrisk.efficient.frontier
```

Generate multiple efficient frontiers for the same portfolio

Description

This function generates the mean-risk efficient frontier of a portfolio specifying the constraints and objectives. The `risk_type` object is for the basic mean-risk efficient frontier, other efficient frontiers will be generated with the same target returns. All mean-StdDev, mean-ES, mean-CSM, and mean-EQS efficient frontiers will be generated.

Usage

```
meanrisk.efficient.frontier(  
  portfolio,  
  R,  
  optimize_method = "CVXR",  
  n.portfolios = 25,  
  risk_type = "StdDev",  
  compare_port = c("StdDev", "ES"),  
  ...  
)
```

Arguments

<code>portfolio</code>	a portfolio object with constraints and objectives created via portfolio.spec
<code>R</code>	an xts or matrix of asset returns
<code>optimize_method</code>	the optimize method to get the efficient frontier, default is CVXR
<code>n.portfolios</code>	number of portfolios to generate the efficient frontier
<code>risk_type</code>	one of "StdDev", "ES" and "CSM", which determines the type of basic efficient frontier.
<code>compare_port</code>	vector composed of any risk "StdDev", "ES", "CSM", for example, <code>compare_port=c("StdDev", "ES")</code>
<code>...</code>	passthru parameters to optimize.portfolio

Value

a matrix of objective measure values and weights along the efficient frontier

Author(s)

Xinran Zhao

`meanvar.efficient.frontier`*Generate the efficient frontier for a mean-variance portfolio*

Description

This function generates the mean-variance efficient frontier of a portfolio specifying the constraints and objectives. The `portfolio` object should have two objectives: 1) mean and 2) var (or sd or StdDev). If the portfolio object does not contain these objectives, they will be added using default parameters.

Usage

```
meanvar.efficient.frontier(  
  portfolio,  
  R,  
  optimize_method = "CVXR",  
  n.portfolios = 25,  
  risk_aversion = NULL,  
  ...  
)
```

Arguments

<code>portfolio</code>	a portfolio object with constraints created via portfolio.spec
<code>R</code>	an xts or matrix of asset returns
<code>optimize_method</code>	the optimize method to get the efficient frontier, default is CVXR
<code>n.portfolios</code>	number of portfolios to plot along the efficient frontier
<code>risk_aversion</code>	vector of <code>risk_aversion</code> values to construct the efficient frontier. <code>n.portfolios</code> is ignored if <code>risk_aversion</code> is specified and the number of points along the efficient frontier is equal to the length of <code>risk_aversion</code> .
<code>...</code>	passthru parameters to optimize.portfolio

Value

a matrix of objective measure values and weights along the efficient frontier

Author(s)

Ross Bennett

meucci.moments	<i>Compute moments</i>
----------------	------------------------

Description

Compute the first and second moments using the Fully Flexible Views framework as described in A. Meucci - "Fully Flexible Views: Theory and Practice".

Usage

```
meucci.moments(R, posterior_p)
```

Arguments

R	xts object of asset returns
posterior_p	vector of posterior probabilities

Value

a list with the first and second moments

mu: vector of expected returns

sigma: covariance matrix

Author(s)

Ross Bennett

References

A. Meucci - "Fully Flexible Views: Theory and Practice".

meucci.ranking	<i>Asset Ranking</i>
----------------	----------------------

Description

Express views on the relative expected asset returns as in A. Meucci, "Fully Flexible Views: Theory and Practice" and compute the first and second moments.

Usage

```
meucci.ranking(R, p, order)
```

Arguments

R	xts object of asset returns
p	a vector of the prior probability values
order	a vector of indexes of the relative ranking of expected asset returns in ascending order. For example, order = c(2, 3, 1, 4) means that the expected returns of $R[,2] < R[,3], < R[,1] < R[,4]$.

Value

The estimated moments based on ranking views

Note

This function is based on the ViewRanking function written by Ram Ahluwalia in the Meucci package.

References

A. Meucci, "Fully Flexible Views: Theory and Practice" <https://www.arpm.co/articles/fully-flexible-views-theo>
See Meucci script for "RankingInformation/ViewRanking.m"

See Also

[meucci.moments](#)

Examples

```
data(edhec)
R <- edhec[,1:4]
p <- rep(1 / nrow(R), nrow(R))
meucci.ranking(R, p, c(2, 3, 1, 4))
```

minmax_objective

constructor for class tmp_minmax_objective

Description

This objective allows for min and max targets to be specified.

Usage

```
minmax_objective(
  name,
  target = NULL,
  arguments = NULL,
  multiplier = 1,
  enabled = TRUE,
```

```

    ...,
    min,
    max
)

```

Arguments

name	name of the objective, should correspond to a function, though we will try to make allowances
target	univariate target for the objective
arguments	default arguments to be passed to an objective function when executed
multiplier	multiplier to apply to the objective, usually 1 or -1
enabled	TRUE/FALSE
...	any other passthru parameters
min	minimum value
max	maximum value

Details

If target is set, we'll try to meet the metric

If target is NULL and min and max are specified, then do the following:

If max is violated to the upside, penalize the metric. If min is violated to the downside, penalize the metric. The purpose of this objective is to try to meet the range between min and max

Value

object of class 'minmax_objective'

Author(s)

Ross Bennett

mult.portfolio.spec *Multiple Layer Portfolio Specification*

Description

Create and specify a multiple layer portfolio

Usage

```
mult.portfolio.spec(portfolio, levels = 2, ...)
```

Arguments

portfolio	the "top level" portfolio
levels	number of levels of sub-portfolios
...	any additional parameters

Details

The `sub.portfolios` slot is a list where each element contains the portfolio object and rebalancing parameters for the optimization of the sub portfolio. This allows, for example, each sub portfolio to have different rebalancing frequencies (i.e. monthly or quarterly), optimization methods, etc.

Each sub portfolio is optimized with `optimize.portfolio.rebalancing` to create a time series of proxy returns.

The "top level" portfolio is used to specify the constraints and objectives to control the optimization given the proxy returns of each sub portfolio.

Value

a `mult.portfolio.spec` object with the top level portfolio and sub portfolios with optimization parameters for each sub portfolio

Author(s)

Ross Bennett

MycovRobMcd

Control settings for custom.covRob.Mcd

Description

Auxiliary function for passing the estimation options as parameters to the estimation function `MCD.robust.moment`

Usage

```
MycovRobMcd(
  alpha = 1/2,
  nsamp = 500,
  nmini = 300,
  kmini = 5,
  scalefn = "hrv2012",
  maxcsteps = 200,
  seed = NULL,
  tolSolve = 0.00000000000001,
  wgtFUN = "01.original",
  beta,
  use.correction = TRUE
)
```

Arguments

alpha	numeric parameter controlling the size of the subsets over which the determinant is minimized. Allowed values are between 0.5 and 1 and the default is 0.5.
nsamp	number of subsets used for initial estimates or "best", "exact", or "deterministic". Default is nsamp = 500. For nsamp = "best" exhaustive enumeration is done, as long as the number of trials does not exceed 100'000, which is the value of nlarge. For "exact", exhaustive enumeration will be attempted however many samples are needed. In this case a warning message may be displayed saying that the computation can take a very long time. For "deterministic", the deterministic MCD is computed; as proposed by Hubert et al. (2012) it starts from the h most central observations of six (deterministic) estimators.
nmini, kmini	for $n \geq 2 \cdot n_0$, $n_0 := n_{\text{mini}}$, the algorithm splits the data into maximally kmini (by default 5) subsets, of size approximately, but at least nmini. When $n_{\text{mini}} \cdot k_{\text{mini}} < n$, the initial search uses only a subsample of size $n_{\text{mini}} \cdot k_{\text{mini}}$. The original algorithm had $n_{\text{mini}} = 300$ and $k_{\text{mini}} = 5$ hard coded.
scaleftn	function to compute a robust scale estimate or character string specifying a rule determining such a function for the deterministic MCD. The default is "hrv2012". Another option value is "v2014".
maxcsteps	maximal number of concentration steps in the deterministic MCD
seed	initial seed for random generator
tolSolve	numeric tolerance to be used for inversion of the covariance matrix
wgtFUN	a character string or function, specifying how the weights for the reweighting step should be computed. Default is "01.originalz".
beta	a quantile, experimentally used for some of the prespecified wgtFUNs. For our MCD method, the default is 0.975.
use.correction	whether to use finite sample correction factors; defaults to TRUE.

Value

a list of passed parameters

MycovRobTSGS

Control settings for custom.covRob.TSGS

Description

Auxiliary function for passing the estimation options as parameters to the estimation function custom.TSGS

Usage

```

MycovRobTSGS(
  filter = c("UBF-DDC", "UBF", "DDC", "UF"),
  partial.impute = FALSE,
  tol = 0.0001,
  maxiter = 150,
  loss = c("bisquare", "rocke"),
  init = c("emve", "qc", "huber", "imputed", "emve_c")
)

```

Arguments

`filter` the filter to be used in the first step. Available choices are "UBF-DDC", "UBF", "DDC", "UF". The default one is "UBF-DDC".

`partial.impute` whether partial imputation is used prior to estimation. The default is FALSE.

`tol` tolerance for the convergence criterion. Default is 1e-4.

`maxiter` maximum number of iterations. Default is 150.

`loss` loss function to use, "bisquare" or "rocke". Default is "bisquare"

`init` type of initial estimator. Options include "emve", "qc", "huber", "imputed", "emve_c"

Value

a list of passed parameters

name.replace	<i>utility function to replace awkward named from unlist</i>
--------------	--

Description

utility function to replace awkward named from unlist

Usage

```
name.replace(rnames)
```

Arguments

`rnames` character vector of names to check for cleanup

objective	<i>constructor for class 'objective'</i>
-----------	--

Description

Typically called as a sub-function by the user function [add.objective](#). See main documentation there.

Usage

```
objective(  
  name,  
  target = NULL,  
  arguments,  
  enabled = TRUE,  
  ...,  
  multiplier = 1,  
  objclass = "objective"  
)
```

Arguments

name	name of the objective which will be used to call a function, like 'ES', 'VaR', 'mean'
target	univariate target for the objective, default NULL
arguments	default arguments to be passed to an objective function when executed
enabled	TRUE/FALSE
...	any other passthrough parameters
multiplier	multiplier to apply to the objective, usually 1 or -1
objclass	string class to apply, default 'objective'

Author(s)

Brian G. Peterson

See Also

[add.objective](#), [portfolio.spec](#)

`opt.outputMvo`*Optimal Portfolio Weights and Performance Values*

Description

Converts output of ‘optimize.portfolio’ to a list of the portfolio weights, mean, volatility and Sharpe Ratio.

Usage

```
opt.outputMvo(  
  opt,  
  returns,  
  digits = NULL,  
  annualize = TRUE,  
  frequency = "monthly",  
  rf = 0  
)
```

Arguments

<code>opt</code>	List output of ‘optimize.portfolio’
<code>returns</code>	Multivariate xts object of portfolio assets returns
<code>digits</code>	Integer number of significant digits with default NULL
<code>annualize</code>	Logical with default TRUE
<code>frequency</code>	Returns frequency: "monthly", "weekly" or "daily"
<code>rf</code>	Numeric value with default 0.0

Details

This function uses the weights returned by `optimize.portfolio`, along with the portfolio assets returns, and a risk-free rate, to compute the portfolio mean return, volatility, and Sharpe Ratio.

Value

A list containing the portfolio numeric weights, mean value, volatility and Sharpe Ratio.

Author(s)

R. Douglas Martin

Examples

```
args(opt.outputMvo)
```

optimize.portfolio *Constrained optimization of portfolios*

Description

This function aims to provide a wrapper for constrained optimization of portfolios that specify constraints and objectives.

Usage

```
optimize.portfolio_v1(
  R,
  constraints,
  optimize_method = c("DEoptim", "random", "ROI", "ROI_old", "pso", "GenSA"),
  search_size = 20000,
  trace = FALSE,
  ...,
  rp = NULL,
  momentFUN = "set.portfolio.moments_v1"
)

optimize.portfolio(
  R,
  portfolio = NULL,
  constraints = NULL,
  objectives = NULL,
  optimize_method = c("DEoptim", "random", "ROI", "pso", "GenSA", "Rglpk", "osqp", "mco",
    "CVXR", "cvxr", ...),
  search_size = 20000,
  trace = FALSE,
  ...,
  rp = NULL,
  momentFUN = "set.portfolio.moments",
  message = FALSE
)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
constraints	default=NULL, a list of constraint objects. An object of class 'v1_constraint' can be passed in here.
optimize_method	one of "DEoptim", "random", "ROI", "pso", "GenSA", "osqp", "Rglpk", "mco", "CVXR", or a vector to specify CVXR solver. A solver of ROI or CVXR can also be specified and will be solved via ROI or CVXR. See details.
search_size	integer, how many portfolios to test, default 20,000

trace	TRUE/FALSE if TRUE will attempt to return additional information on the path or portfolios searched
...	any other passthru parameters
rp	matrix of random portfolio weights, default NULL, mostly for automated use by rebalancing optimization or repeated tests on same portfolios
momentFUN	the name of a function to call to set portfolio moments, default set.portfolio.moments_v2
portfolio	an object of type "portfolio" specifying the constraints and objectives for the optimization
objectives	default=NULL, a list of objective objects.
message	TRUE/FALSE. The default is message=FALSE. Display messages if TRUE.

Details

This function currently supports DEoptim, random portfolios, pso, GenSA, ROI, osqp, Rglpk, mco, and CVXR solvers as back ends. Additional back end contributions for Rmetrics, ghyp, etc. would be welcome.

When using random portfolios, search_size is precisely that, how many portfolios to test. You need to make sure to set your feasible weights in generateSequence to make sure you have search_size unique portfolios to test, typically by manipulating the 'by' parameter to select something smaller than .01 (I often use .002, as .001 seems like overkill)

When using DE, search_size is decomposed into two other parameters which it interacts with, NP and itermax.

NP, the number of members in each population, is set to cap at 2000 in DEoptim, and by default is the number of parameters (assets/weights) * 10.

itermax, if not passed in dots, defaults to the number of parameters (assets/weights) * 50.

When using GenSA and want to set verbose=TRUE, instead use trace.

If optimize_method="ROI" is specified, a default solver will be selected based on the optimization problem. The glpk solver is the default solver for LP and MILP optimization problems. The quadprog solver is the default solver for QP optimization problems. For example, optimize_method = "quadprog" can be specified and the optimization problem will be solved via ROI using the quadprog solver.

The extension to ROI solves a limited type of convex optimization problems:

- Maximize portfolio return subject leverage, box, group, position limit, target mean return, and/or factor exposure constraints on weights.
- Minimize portfolio variance subject to leverage, box, group, turnover, and/or factor exposure constraints (otherwise known as global minimum variance portfolio).
- Minimize portfolio variance subject to leverage, box, group, and/or factor exposure constraints and a desired portfolio return.
- Maximize quadratic utility subject to leverage, box, group, target mean return, turnover, and/or factor exposure constraints and risk aversion parameter. (The risk aversion parameter is passed into optimize.portfolio as an added argument to the portfolio object).

- Maximize portfolio mean return per unit standard deviation (i.e. the Sharpe Ratio) can be done by specifying `maxSR=TRUE` in `optimize.portfolio`. If both mean and `StdDev` are specified as objective names, the default action is to maximize quadratic utility, therefore `maxSR=TRUE` must be specified to maximize Sharpe Ratio.
- Minimize portfolio ES/ETL/CVaR optimization subject to leverage, box, group, position limit, target mean return, and/or factor exposure constraints and target portfolio return.
- Maximize portfolio mean return per unit ES/ETL/CVaR (i.e. the STARR Ratio) can be done by specifying `maxSTARR=TRUE` in `optimize.portfolio`. If both mean and ES/ETL/CVaR are specified as objective names, the default action is to maximize mean return per unit ES/ETL/CVaR.

These problems also support a `weight_concentration` objective where concentration of weights as measured by HHI is added as a penalty term to the quadratic objective.

Because these convex optimization problem are standardized, there is no need for a penalty term. The `multiplier` argument in `add.objective` passed into the complete constraint object are ignored by the ROI solver.

If `optimize_method="CVXR"` is specified, a default solver will be selected based on the optimization problem. The default solver for Quadratic Programming will be OSQP, and the default solver for Linear Problem and Second-Order Cone Programming will be SCS. Specified CVXR solver can be given by using `optimize_method=c("CVXR", "CVXRsolver")`. CVXR supports some commercial solvers, including CBC, CPLEX, GUROBI and MOSEK, and some open source solvers, including GLPK, GLPK_MI, OSQP, SCS and ECOS. For example, `optimize_method = c("CVXR", "ECOS")` can be specified and the optimization problem will be solved via CVXR using the ECOS solver.

The extension to CVXR solves a limited type of convex optimization problems:

- Maximize portfolio mean return subject leverage, box, group, and/or target mean return constraints
- Minimize portfolio variance subject to leverage, box, group, and/or target mean return constraints (otherwise known as global minimum variance portfolio).
- Maximize quadratic utility subject to leverage, box, group, and/or target mean return constraints and risk aversion parameter. (The default risk aversion is 1, and specified risk aversion could be given by `risk_aversion = 1`. The risk aversion parameter is passed into `optimize.portfolio` as an added argument to the `portfolio` object.)
- Minimize portfolio ES/ETL/CVaR optimization subject to leverage, box, group, and/or target mean return constraints and tail probability parameter. (The default tail probability is 0.05, and specified tail probability could be given by `arguments = list(p=0.95)`. The tail probability parameter is passed into `optimize.portfolio` as an added argument to the `portfolio` object.)
- Minimize portfolio CSM optimization subject to leverage, box, group, and/or target mean return constraints and tail probability parameter. (The default tail probability is 0.05, and specified tail probability could be given by `arguments = list(p=0.95)`. The tail probability parameter is passed into `optimize.portfolio` as an added argument to the `portfolio` object.)
- Maximize portfolio mean return per unit standard deviation (i.e. the Sharpe Ratio) subject to leverage, box, group, and/or target mean return constraints. It should be specified by `maxSR=TRUE` in `optimize.portfolio` with both mean and `var/StdDev` objectives. Otherwise, the default action is to maximize quadratic utility.

- Maximize portfolio mean return per unit ES (i.e. the ES ratio/STARR) subject to leverage, box, group, and/or target mean return constraints. It could be specified by `maxSTARR=TRUE` or `ESratio=TRUE` in `optimize.portfolio` with both mean and ES objectives. The default action is to maximize ES ratio. If `maxSTARR=FALSE` or `ESratio=FALSE` is given, the action will be minimizing ES.
- Maximize portfolio mean return per unit CSM (i.e. the CSM ratio) subject to leverage, box, group, and/or target mean return constraints. It could be specified by `CSMratio=TRUE` in `optimize.portfolio` with both mean and CSM objectives. The default action is to maximize CSM ratio. If `CSMratio=FALSE` is given, the action will be minimizing CSM.

Because these convex optimization problem are standardized, there is no need for a penalty term. The multiplier argument in `add.objective` passed into the complete constraint object are ignored by the CVXR solver.

Value

a list containing the following elements

weights: The optimal set weights.

objective_measures: A list containing the value of each objective corresponding to the optimal weights.

opt_values: A list containing the value of each objective corresponding to the optimal weights.

out: The output of the solver.

call: The function call.

portfolio: The portfolio object.

R: The asset returns.

data summary: The first row and last row of R.

elapsed_time: The amount of time that elapses while the optimization is run.

end_t: The date and time the optimization completed.

When `Trace=TRUE` is specified, the following elements will be returned in addition to the elements above. The output depends on the optimization method and is specific to each solver. Refer to the documentation of the desired solver for more information.

`optimize_method="random"`

random_portfolios: A matrix of the random portfolios.

random_portfolio_objective_results: A list of the following elements for each random portfolio.

out: The output value of the solver corresponding to the random portfolio weights.

weights: The weights of the random portfolio.

objective_measures: A list of each objective measure corresponding to the random portfolio weights.

`optimize_method="DEoptim"`

DEoutput: A list (of length 2) containing the following elements:

- optim
- member

DEoptim_objective_results: A list containing the following elements for each intermediate population.

- out: The output of the solver.
- weights: Population weights.
- init_weights: Initial population weights.
- objective_measures: A list of each objective measure corresponding to the weights

optimize_method="pso"

- PSOoutput: A list containing the following elements:
 - par
 - value
 - counts
 - convergence
 - message
 - stats

optimize_method="GenSA"

- GenSAoutput: A list containing the following elements:
 - value
 - par
 - trace.mat
 - counts

Note

An object of class `v1_constraint` can be passed in for the `constraints` argument. The `v1_constraint` object was used in the previous 'v1' specification to specify the constraints and objectives for the optimization problem, see [constraint](#). We will attempt to detect if the object passed into the `constraints` argument is a `v1_constraint` object and update to the 'v2' specification by adding the constraints and objectives to the `portfolio` object.

Author(s)

Kris Boudt, Peter Carl, Brian G. Peterson, Ross Bennett, Xiaokang Feng, Xinran Zhao

See Also

[portfolio.spec](#)

```
optimize.portfolio.parallel
```

Execute multiple optimize.portfolio calls, presumably in parallel

Description

This function will not speed up optimization!

Usage

```
optimize.portfolio.parallel(  
  R,  
  portfolio,  
  optimize_method = c("DEoptim", "random", "ROI", "pso", "GenSA", "CVXR"),  
  search_size = 20000,  
  trace = FALSE,  
  ...,  
  rp = NULL,  
  momentFUN = "set.portfolio.moments",  
  message = FALSE,  
  nodes = 4  
)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
portfolio	an object of type "portfolio" specifying the constraints and objectives for the optimization
optimize_method	one of "DEoptim", "random", "pso", "GenSA".
search_size	integer, how many portfolios to test, default 20,000
trace	TRUE/FALSE if TRUE will attempt to return additional information on the path or portfolios searched
...	any other passthru parameters
rp	matrix of random portfolio weights, default NULL, mostly for automated use by rebalancing optimization or repeated tests on same portfolios
momentFUN	the name of a function to call to set portfolio moments, default set.portfolio.moments_v2
message	TRUE/FALSE. The default is message=FALSE. Display messages if TRUE.
nodes	how many processes to run in the foreach loop, default 4

Details

This function exists to run multiple copies of optimize.portfolio, presumably in parallel using foreach.

This is typically done to test your parameter settings, specifically total population size, but also possibly to help tune your convergence settings, number of generations, stopping criteria, etc.

If you want to use all the cores on your multi-core computer, use the parallel version of the appropriate optimization engine, not this function.

Value

a list containing the optimal weights, some summary statistics, the function call, and optionally trace information

Author(s)

Kris Boudt, Peter Carl, Brian G. Peterson

optimize.portfolio.rebalancing

Portfolio Optimization with Rebalancing Periods

Description

Portfolio optimization with support for rebalancing periods for out-of-sample testing (i.e. backtesting)

Usage

```
optimize.portfolio.rebalancing_v1(  
  R,  
  constraints,  
  optimize_method = c("DEoptim", "random", "ROI"),  
  search_size = 20000,  
  trace = FALSE,  
  ...,  
  rp = NULL,  
  rebalance_on = NULL,  
  training_period = NULL,  
  rolling_window = NULL  
)
```

```
optimize.portfolio.rebalancing(  
  R,  
  portfolio = NULL,  
  constraints = NULL,  
  objectives = NULL,
```

```

optimize_method = c("DEoptim", "random", "ROI", "CVXR"),
search_size = 20000,
trace = FALSE,
...,
rp = NULL,
rebalance_on = NULL,
training_period = NULL,
rolling_window = NULL
)

```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
constraints	default NULL, a list of constraint objects
optimize_method	one of "DEoptim", "random", "pso", "GenSA", or "ROI"
search_size	integer, how many portfolios to test, default 20,000
trace	TRUE/FALSE if TRUE will attempt to return additional information on the path or portfolios searched
...	any other passthru parameters to optimize.portfolio
rp	a set of random portfolios passed into the function to prevent recalculation
rebalance_on	character string of period to rebalance on. See endpoints for valid names.
training_period	an integer of the number of periods to use as a training data in the front of the returns data
rolling_window	an integer of the width (i.e. number of periods) of the rolling window, the default of NULL will run the optimization using the data from inception.
portfolio	an object of type "portfolio" specifying the constraints and objectives for the optimization
objectives	default NULL, a list of objective objects

Details

Run portfolio optimization with periodic rebalancing at specified time periods. Running the portfolio optimization with periodic rebalancing can help refine the constraints and objectives by evaluating the out of sample performance of the portfolio based on historical data.

If both `training_period` and `rolling_window` are NULL, then `training_period` is set to a default value of 36.

If `training_period` is NULL and a `rolling_window` is specified, then `training_period` is set to the value of `rolling_window`.

The user should be aware of the following behavior when both `training_period` and `rolling_window` are specified and have different values

training_period < rolling_window: For example, if you have `rolling_window=60`, `training_period=50`, and the periodicity of the data is the same as the rebalance frequency (i.e. monthly data with `rebalance_on="months"`) then the returns data used in the optimization at each iteration are as follows:

- 1: R[1:50,]
- 2: R[1:51,]
- ...
- 11: R[1:60,]
- 12: R[1:61,]
- 13: R[2:62,]
- ...

This results in a growing window for several optimizations initially while the endpoint iterator (i.e. [50, 51, ...]) is less than the rolling window width.

`training_period > rolling_window`: The data used in the initial optimization is `R[(training_period - rolling_window):training_period,]`. This results in some of the data being "thrown away", i.e. periods 1 to $(\text{training_period} - \text{rolling_window} - 1)$ are not used in the optimization.

This function is essentially a wrapper around `optimize.portfolio` and thus the discussion in the Details section of the [optimize.portfolio](#) help file is valid here as well.

This function is massively parallel and requires the 'foreach' package. It is suggested to register a parallel backend.

Value

a list containing the following elements

`portfolio`: The portfolio object.

`R`: The asset returns.

`call`: The function call.

`elapsed_time`: The amount of time that elapses while the optimization is run.

`opt_rebalancing`: A list of `optimize.portfolio` objects computed at each rebalancing period.

Author(s)

Kris Boudt, Peter Carl, Brian G. Peterson

See Also

[portfolio.spec](#) [optimize.portfolio](#)

Examples

```
## Not run:
data(edhec)
R <- edhec[, 1:4]
funds <- colnames(R)

portf <- portfolio.spec(funds)
portf <- add.constraint(portf, type = "full_investment")
portf <- add.constraint(portf, type = "long_only")
portf <- add.objective(portf, type = "risk", name = "StdDev")
```

```
# Quarterly rebalancing with 5 year training period
bt.opt1 <- optimize.portfolio.rebalancing(R, portf,
  optimize_method = "ROI",
  rebalance_on = "quarters",
  training_period = 60
)

# Monthly rebalancing with 5 year training period and 4 year rolling window
bt.opt2 <- optimize.portfolio.rebalancing(R, portf,
  optimize_method = "ROI",
  rebalance_on = "months",
  training_period = 60,
  rolling_window = 48
)

## End(Not run)
```

pHist

Generates histogram

Description

Generates histogram

Usage

```
pHist(X, p, nBins, freq = FALSE)
```

Arguments

X	a vector containing the data points
p	a vector containing the probabilities for each of the data points in X
nBins	expected number of Bins the data set is to be broken down into
freq	a boolean variable to indicate whether the graphic is a representation of frequencies

Value

a list with f the frequency for each midpoint x the midpoints of the nBins intervals

Author(s)

Ram Ahluwalia <ram@wingedfootcapital.com> and Xavier Valls <flamejat@gmail.com>

References

<https://www.arpm.co/> See Meucci script pHist.m used for plotting

```
plot.optimize.portfolio.DEoptim
      plot method for objects of class optimize.portfolio
```

Description

Scatter and weights chart for portfolio optimizations run with trace=TRUE

Usage

```
## S3 method for class 'optimize.portfolio.DEoptim'
plot(
  x,
  ...,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  neighbors = NULL,
  main = "optimized portfolio plot",
  xlim = NULL,
  ylim = NULL
)
```

```
## S3 method for class 'optimize.portfolio.GenSA'
plot(
  x,
  ...,
  rp = FALSE,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  cex.axis = 0.8,
  element.color = "darkgray",
  neighbors = NULL,
  main = "GenSA.Portfolios",
  xlim = NULL,
  ylim = NULL
)
```

```
## S3 method for class 'optimize.portfolio.pso'
plot(
  x,
  ...,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  cex.axis = 0.8,
```

```
    element.color = "darkgray",
    neighbors = NULL,
    main = "PSO.Portfolios",
    xlim = NULL,
    ylim = NULL
  )

## S3 method for class 'optimize.portfolio.ROI'
plot(
  x,
  ...,
  rp = FALSE,
  risk.col = "ES",
  return.col = "mean",
  chart.assets = FALSE,
  element.color = "darkgray",
  neighbors = NULL,
  main = "ROI.Portfolios",
  xlim = NULL,
  ylim = NULL
)

## S3 method for class 'optimize.portfolio.random'
plot(
  x,
  ...,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  neighbors = NULL,
  xlim = NULL,
  ylim = NULL,
  main = "optimized portfolio plot"
)

## S3 method for class 'optimize.portfolio'
plot(
  x,
  ...,
  return.col = "mean",
  risk.col = "ES",
  chart.assets = FALSE,
  neighbors = NULL,
  xlim = NULL,
  ylim = NULL,
  main = "optimized portfolio plot"
)
```

Arguments

<code>x</code>	set of portfolios created by <code>optimize.portfolio</code>
<code>...</code>	any other passthru parameters
<code>return.col</code>	string name of column to use for returns (vertical axis)
<code>risk.col</code>	string name of column to use for risk (horizontal axis)
<code>chart.assets</code>	TRUE/FALSE to include risk-return scatter of assets
<code>neighbors</code>	set of 'neighbor portfolios to overplot
<code>main</code>	an overall title for the plot: see <code>title</code>
<code>xlim</code>	set the limit on coordinates for the x-axis
<code>ylim</code>	set the limit on coordinates for the y-axis
<code>rp</code>	TRUE/FALSE to plot feasible portfolios generated by <code>random_portfolios</code>
<code>cex.axis</code>	the magnification to be used for axis annotation relative to the current setting of <code>cex</code> .
<code>element.color</code>	provides the color for drawing less-important chart elements, such as the box lines, axis lines, etc.

Details

`return.col` must be the name of a function used to compute the return metric on the random portfolio weights `risk.col` must be the name of a function used to compute the risk metric on the random portfolio weights

`neighbors` may be specified in three ways. The first is as a single number of neighbors. This will extract the neighbors closest portfolios in terms of the out numerical statistic. The second method consists of a numeric vector for neighbors. This will extract the neighbors with portfolio index numbers that correspond to the vector contents. The third method for specifying neighbors is to pass in a matrix. This matrix should look like the output of `extractStats`, and should contain `risk.col`, `return.col`, and weights columns all properly named.

The ROI and GenSA solvers do not store the portfolio weights like DEoptim or random portfolios, random portfolios can be generated for the scatter plot with the `rp` argument.

plotFrontiers

Generate efficient frontiers plot by providing frontiers.

Description

Generate efficient frontiers plot by providing frontiers.

Usage

```

plotFrontiers(
  R,
  frontiers,
  risk,
  ES_alpha = 0.05,
  CSM_alpha = 0.05,
  EQS_alpha = 0.05,
  moment_setting = NULL,
  main = "Efficient Frontiers",
  plot_type = "1",
  cex.axis = 0.5,
  element.color = "darkgray",
  legend.loc = NULL,
  legend.labels = NULL,
  cex.legend = 0.8,
  xlim = NULL,
  ylim = NULL,
  ...,
  labels.assets = TRUE,
  pch.assets = 21,
  cex.assets = 0.8,
  col = NULL,
  lty = NULL,
  lwd = NULL
)

```

Arguments

R	an xts object of asset returns
frontiers	a list of frontiers, for example, list(ef1=meanvar.efficient.frontier(), ef2=meanvar.efficient.frontier())
risk	type of risk that you want to compare, could be 'StdDev', 'ES', 'CSM', 'EQS'
ES_alpha	the default value is 0.05, but could be specified as any value between 0 and 1
CSM_alpha	the default value is 0.05, but could be specified as any value between 0 and 1
EQS_alpha	the default value is 0.05, but could be specified as any value between 0 and 1
moment_setting	the default is NULL, if customize momentFUN please provide moment_setting=list(mu=, sigma=)
main	title used in the plot.
plot_type	define the plot_type, default is "1"
cex.axis	the magnification to be used for sizing the axis text relative to the current setting of 'cex', similar to plot .
element.color	provides the color for drawing less-important chart elements, such as the box lines, axis lines, etc.
legend.loc	location of the legend; NULL, "bottomright", "bottom", "bottomleft", "left", "topleft", "top", "topright", "right" and "center".

legend.labels	character vector to use for the legend labels.
cex.legend	The magnification to be used for sizing the legend relative to the current setting of 'cex', similar to plot .
xlim	set the x-axis limit, same as in plot .
ylim	set the y-axis limit, same as in plot .
...	passthrough parameters to plot .
labels.assets	TRUE/FALSE to include the asset names in the plot.
pch.assets	plotting character of the assets, same as in plot .
cex.assets	A numerical value giving the amount by which the asset points and labels should be magnified relative to the default.
col	vector of colors with length equal to the number of portfolios in frontiers.
lty	vector of line types with length equal to the number of portfolios in frontiers.
lwd	vector of line widths with length equal to the number of portfolios in frontiers.

Details

This function provides the ability to plot frontiers based on the result of 'meanvar.efficient.frontier', 'meanetl.efficient.frontier', 'meancsm.efficient.frontier' or 'meaneqs.efficient.frontier'.

When using meanvar.efficient.frontier, meanetl.efficient.frontier, meancsm.efficient.frontier and meaneqs.efficient.frontier, the result will be frontiers data, including the weights for each point on the mean-risk efficient frontiers. Before using this function, user should declare which risk that they want to compare, and what parameters that they want to use to calculate the risk, e.g. ES_alpha for ES, moment_setting for var. Then this function will calculate back mean and risk based on the weight, and draw a plot.

Default settings use colors and line types to differentiate portfolios, and set the portfolio name as 'Portfolio 1' and so on. Users could customize col, lty, lwd and legend.labels to better the plot.

Author(s)

Xinran Zhao

Description

Set portfolio moments for use by lower level optimization functions using a basic Black Litterman model.

Usage

```
portfolio.moments.bl(
  R,
  portfolio,
  momentargs = NULL,
  P,
  Mu = NULL,
  Sigma = NULL,
  ...
)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
portfolio	an object of type portfolio specifying the constraints and objectives for the optimization, see portfolio.spec
momentargs	list containing arguments to be passed down to lower level functions, default NULL
P	a K x N pick matrix representing views
Mu	vector of length N of the prior expected values. The sample mean is used if Mu=NULL.
Sigma	an N x N matrix of the prior covariance matrix. The sample covariance is used if Sigma=NULL.
...	any other passthru parameters

Note

If any of the objectives in the portfolio object have clean as an argument, the cleaned returns are used to fit the model.

```
portfolio.moments.boudt
```

Portfolio Moments

Description

Set portfolio moments for use by lower level optimization functions using a statistical factor model based on the work of Kris Boudt.

Usage

```
portfolio.moments.boudt(R, portfolio, momentargs = NULL, k = 1, ...)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
portfolio	an object of type portfolio specifying the constraints and objectives for the optimization, see portfolio.spec
momentargs	list containing arguments to be passed down to lower level functions, default NULL
k	number of factors used for fitting statistical factor model
...	any other passthru parameters

Note

If any of the objectives in the portfolio object have clean as an argument, the cleaned returns are used to fit the model.

portfolio.spec	<i>constructor for class portfolio</i>
----------------	--

Description

The portfolio object is created with `portfolio.spec`. The portfolio object is an S3 object of class 'portfolio' used to hold the initial asset weights, constraints, objectives, and other information about the portfolio. The only required argument to `portfolio.spec` is `assets`.

Usage

```
portfolio.spec(
  assets = NULL,
  name = "portfolio",
  category_labels = NULL,
  weight_seq = NULL,
  message = FALSE
)
```

Arguments

assets	number of assets, or optionally a named vector of assets specifying seed weights. If seed weights are not specified, an equal weight portfolio will be assumed.
name	give the portfolio a name, the default name will be 'portfolio'
category_labels	character vector to categorize assets by sector, industry, geography, market-cap, currency, etc. Default NULL
weight_seq	seed sequence of weights, see generatesequence Default NULL
message	TRUE/FALSE. The default is message=FALSE. Display messages if TRUE.

Details

The portfolio object contains the following elements:

`assets` named vector of the seed weights

`category_labels` character vector to categorize the assets by sector, geography, etc.

`weight_seq` sequence of weights used by `random_portfolios`. See `generatesequence`

`constraints` a list of constraints added to the portfolio object with `add.constraint`

`objectives` a list of objectives added to the portfolio object with `add.objective`

`call` the call to `portfolio.spec` with all of the specified arguments

Value

an object of class `portfolio`

Author(s)

Ross Bennett, Brian G. Peterson

See Also

[add.constraint](#), [add.objective](#), [optimize.portfolio](#)

Examples

```
data(edhec)
pspec <- portfolio.spec(assets=colnames(edhec))
pspec <- portfolio.spec(assets=10, weight_seq=generatesequence())
```

`portfolio_risk_objective`

constructor for class portfolio_risk_objective

Description

if target is null, we'll try to minimize the risk metric

Usage

```
portfolio_risk_objective(
  name,
  target = NULL,
  arguments = NULL,
  multiplier = 1,
  enabled = TRUE,
  ...
)
```

Arguments

name	name of the objective, should correspond to a function, though we will try to make allowances
target	univariate target for the objective
arguments	default arguments to be passed to an objective function when executed
multiplier	multiplier to apply to the objective, usually 1 or -1
enabled	TRUE/FALSE
...	any other passthru parameters

Value

object of class 'portfolio_risk_objective'

Author(s)

Brian G. Peterson

position_limit_constraint
constructor for filter_constraint

Description

This function is called by `add.constraint` when `type="filter"` is specified, [add.constraint](#)

Usage

```
position_limit_constraint(
  type = "position_limit",
  filter_name = NULL,
  enabled = TRUE,
  message = FALSE,
  ...
)
```

Arguments

type	character type of the constraint
filter_name	either a function to apply, or a name of a function to apply
enabled	TRUE/FALSE
message	TRUE/FALSE. The default is <code>message=FALSE</code> . Display messages if TRUE.
...	any other passthru parameters to specify position limit constraints

Details

Allows the user to specify a filter function which will take returns, weights, and constraints as inputs, and can return a modified weights vector as output.

Fundamentally, it could be used to filter out certain assets, or to ensure that they must be long or short.

Typically, filter functions will be called by the random portfolio simulation function or via the `fn_map` function.

Value

an object of class 'position_limit_constraint'

Author(s)

Ross Bennett

See Also

[add.constraint](#)

Examples

```
data(edhec)
ret <- edhec[, 1:4]

pspec <- portfolio.spec(assets=colnames(ret))

pspec <- add.constraint(portfolio=pspec, type="position_limit", max_pos=3)
pspec <- add.constraint(portfolio=pspec, type="position_limit", max_pos_long=3, max_pos_short=1)
```

<code>pos_limit_fail</code>	<i>function to check for violation of position limits constraints</i>
-----------------------------	---

Description

This is used as a helper function for `rp_transform` to check for violation of position limit constraints. The position limit constraints checked are `max_pos`, `max_pos_long`, and `max_pos_short`.

Usage

```
pos_limit_fail(weights, max_pos, max_pos_long, max_pos_short)
```

Arguments

<code>weights</code>	vector of weights to test
<code>max_pos</code>	maximum number of assets with non-zero weights
<code>max_pos_long</code>	maximum number of assets with long (i.e. buy) positions
<code>max_pos_short</code>	maximum number of assets with short (i.e. sell) positions

Value

TRUE if any position_limit is violated. FALSE if all position limits are satisfied

print.constraint *print method for constraint objects*

Description

print method for constraint objects

Usage

```
## S3 method for class 'constraint'  
print(x, ...)
```

Arguments

x object of class constraint
... any other passthru parameters

Author(s)

Ross Bennett

print.efficient.frontier
Print an efficient frontier object

Description

Print method for efficient frontier objects. Display the call to create or extract the efficient frontier object and the portfolio from which the efficient frontier was created or extracted.

Usage

```
## S3 method for class 'efficient.frontier'  
print(x, ...)
```

Arguments

x objective of class efficient.frontier
... any other passthru parameters

Author(s)

Ross Bennett

See Also

[create.EfficientFrontier](#)

`print.optimize.portfolio.rebalancing`

Printing output of `optimize.portfolio.rebalancing`

Description

print method for `optimize.portfolio.rebalancing` objects

Usage

```
## S3 method for class 'optimize.portfolio.rebalancing'  
print(x, ..., digits = 4)
```

Arguments

<code>x</code>	an object used to select a method
<code>...</code>	any other passthru parameters
<code>digits</code>	the number of significant digits to use when printing.

Author(s)

Ross Bennett

See Also

[optimize.portfolio.rebalancing](#)

`print.optimize.portfolio.ROI`

Printing output of `optimize.portfolio`

Description

print method for `optimize.portfolio` objects

Usage

```
## S3 method for class 'optimize.portfolio.ROI'  
print(x, ..., digits = 4)  
  
## S3 method for class 'optimize.portfolio.CVXR'  
print(x, ..., digits = 4)  
  
## S3 method for class 'optimize.portfolio.random'  
print(x, ..., digits = 4)  
  
## S3 method for class 'optimize.portfolio.DEoptim'  
print(x, ..., digits = 4)  
  
## S3 method for class 'optimize.portfolio.GenSA'  
print(x, ..., digits = 4)  
  
## S3 method for class 'optimize.portfolio.pso'  
print(x, ..., digits = 4)
```

Arguments

x	an object used to select a method
...	any other passthru parameters
digits	the number of significant digits to use when printing.

Author(s)

Ross Bennett

See Also

[optimize.portfolio](#)

print.portfolio *Printing Portfolio Specification Objects*

Description

Print method for objects of class portfolio created with [portfolio.spec](#)

Usage

```
## S3 method for class 'portfolio'  
print(x, ...)
```

Arguments

x an object of class `portfolio`
... any other passthru parameters

Author(s)

Ross Bennett

See Also

[portfolio.spec](#)

`print.summary.optimize.portfolio`

Printing summary output of `optimize.portfolio`

Description

print method for objects of class `summary.optimize.portfolio`

Usage

```
## S3 method for class 'summary.optimize.portfolio'  
print(x, ...)
```

Arguments

x an object of class `summary.optimize.portfolio`.
... any other passthru parameters. Currently not used.

Author(s)

Ross Bennett

See Also

[summary.optimize.portfolio](#)

```
print.summary.optimize.portfolio.rebalancing
```

Printing summary output of optimize.portfolio.rebalancing

Description

print method for objects of class summary.optimize.portfolio.rebalancing

Usage

```
## S3 method for class 'summary.optimize.portfolio.rebalancing'  
print(x, ..., digits = 4)
```

Arguments

x	an object of class summary.optimize.portfolio.rebalancing.
...	any other passthru parameters
digits	number of digits used for printing

Author(s)

Ross Bennett

See Also

[summary.optimize.portfolio.rebalancing](#)

```
quadratic_utility_objective
```

constructor for quadratic utility objective

Description

This function calls [return_objective](#) and [portfolio_risk_objective](#) to create a list of the objectives to be added to the portfolio.

Usage

```
quadratic_utility_objective(risk_aversion = 1, target = NULL, enabled = TRUE)
```

Arguments

risk_aversion	risk_aversion (i.e. lambda) parameter to penalize variance
target	target mean return value
enabled	TRUE/FALSE, default enabled=TRUE

Value

a list of two elements

- return_objective
- portfolio_risk_objective

Author(s)

Ross Bennett

randomize_portfolio *version 2 generate random permutations of a portfolio seed meeting your constraints on the weights of each asset*

Description

version 2 generate random permutations of a portfolio seed meeting your constraints on the weights of each asset

Usage

```
randomize_portfolio(portfolio, max_permutations = 200)
```

Arguments

portfolio an object of type "portfolio" specifying the constraints for the optimization, see [portfolio.spec](#)

max_permutations integer: maximum number of iterations to try for a valid portfolio, default 200

Value

named weighting vector

Author(s)

Peter Carl, Brian G. Peterson, (based on an idea by Pat Burns)

randomize_portfolio_v1

Random portfolio sample method

Description

This function generates random permutations of a portfolio seed meeting leverage and box constraints. The final step is to run [fn_map](#) on the random portfolio weights to transform the weights so they satisfy other constraints such as group or position limit constraints. This is the 'sample' method for random portfolios and is based on an idea by Pat Burns.

Usage

```
randomize_portfolio_v1(rpconstraints, max_permutations = 200, rounding = 3)
```

Arguments

`rpconstraints` an object of type "constraints" specifying the constraints for the optimization, see [constraint](#)

`max_permutations` integer: maximum number of iterations to try for a valid portfolio, default 200

`rounding` integer how many decimals should we round to

Value

named weights vector

Author(s)

Peter Carl, Brian G. Peterson, (based on an idea by Pat Burns)

random_portfolios	<i>version 2 generate an arbitrary number of constrained random portfolios</i>
-------------------	--

Description

Generate random portfolios using the 'sample', 'simplex', or 'grid' method. See details.

Usage

```
random_portfolios(
  portfolio,
  permutations = 100,
  rp_method = "sample",
  eliminate = TRUE,
  ...
)
```

Arguments

portfolio	an object of class 'portfolio' specifying the constraints for the optimization, see portfolio.spec
permutations	integer: number of unique constrained random portfolios to generate
rp_method	method to generate random portfolios. Currently "sample", "simplex", or "grid". See Details.
eliminate	TRUE/FALSE, eliminate portfolios that do not satisfy constraints
...	any other passthru parameters

Details

Random portfolios can be generate using one of three methods.

sample: The 'sample' method to generate random portfolios is based on an idea pioneered by Pat Burns. This is the most flexible method, but also the slowest, and can generate portfolios to satisfy leverage, box, group, position limit, and leverage exposure constraints.

simplex: The 'simplex' method to generate random portfolios is based on a paper by W. T. Shaw. The simplex method is useful to generate random portfolios with the full investment constraint, where the sum of the weights is equal to 1, and min box constraints. Values for min_sum and max_sum of the leverage constraint will be ignored, the sum of weights will equal 1. All other constraints such as group and position limit constraints will be handled by elimination. If the constraints are very restrictive, this may result in very few feasible portfolios remaining.

grid: The 'grid' method to generate random portfolios is based on the gridSearch function in package 'NMOF'. The grid search method only satisfies the min and max box constraints. The min_sum and max_sum leverage constraints will likely be violated and the weights in the random portfolios should be normalized. Normalization may cause the box constraints to be violated and will be penalized in constrained_objective.

The constraint types checked are leverage, box, group, position limit, and leverage exposure. Any portfolio that does not satisfy all these constraints will be eliminated. This function is particularly sensitive to min_sum and max_sum leverage constraints. For the sample method, there should be some "wobble room" between min_sum and max_sum in order to generate a sufficient number of feasible portfolios. For example, min_sum=0.99 and max_sum=1.01 is recommended instead of min_sum=1 and max_sum=1. If min_sum=1 and max_sum=1, the number of feasible portfolios may be 1/3 or less depending on the other constraints.

Value

matrix of random portfolio weights

Author(s)

Peter Carl, Brian G. Peterson, Ross Bennett

See Also

[portfolio.spec](#), [objective](#), [rp_sample](#), [rp_simplex](#), [rp_grid](#)

random_portfolios_v1 *generate an arbitrary number of constrained random portfolios*

Description

repeatedly calls [randomize_portfolio](#) to generate an arbitrary number of constrained random portfolios.

Usage

```
random_portfolios_v1(rpconstraints, permutations = 100, ...)
```

Arguments

rpconstraints an object of type "constraints" specifying the constraints for the optimization, see [constraint](#)

permutations integer: number of unique constrained random portfolios to generate

... any other passthru parameters

Value

matrix of random portfolio weights

Author(s)

Peter Carl, Brian G. Peterson, (based on an idea by Pat Burns)

See Also

[constraint](#), [objective](#), [randomize_portfolio](#)

Examples

```
rpconstraint<-constraint_v1(assets=10,
                           min_mult=-Inf,
                           max_mult=Inf,
                           min_sum=.99,
                           max_sum=1.01,
                           min=.01,
                           max=.4,
                           weight_seq=generatesequence())

rp<- random_portfolios_v1(rpconstraints=rpconstraint,permutations=1000)
head(rp)
```

random_walk_portfolios

deprecated random portfolios wrapper until we write a random trades function

Description

deprecated random portfolios wrapper until we write a random trades function

Usage

```
random_walk_portfolios(...)
```

Arguments

... any other passthru parameters

Author(s)

bpeterson

regime.portfolios *Regime Portfolios*

Description

Construct a regime.portfolios object that contains a time series of regimes and portfolios corresponding to the regimes.

Usage

```
regime.portfolios(regime, portfolios)
```

Arguments

regime xts or zoo object specifying the regime
portfolios list of portfolios created by combine.portfolios with corresponding regimes

Details

Create a regime.portfolios object to support regime switching optimization. This object is then passed in as the portfolio argument in optimize.portfolio. The regime is detected and the corresponding portfolio is selected. For example, if the current regime is 1, then portfolio 1 will be selected and used in the optimization.

Value

a regime.portfolios object with the following elements

regime: An xts object of the regime

portfolio: List of portfolios corresponding to the regime

Author(s)

Ross Bennett

return_constraint *constructor for return_constraint*

Description

The return constraint specifies a target mean return value. This function is called by add.constraint when type="return" is specified, [add.constraint](#)

Usage

```
return_constraint(  
  type = "return",  
  return_target,  
  enabled = TRUE,  
  message = FALSE,  
  ...  
)
```

Arguments

type	character type of the constraint
return_target	return target value
enabled	TRUE/FALSE
message	TRUE/FALSE. The default is message=FALSE. Display messages if TRUE.
...	any other passthru parameters

Value

an object of class 'return_constraint'

Author(s)

Ross Bennett

See Also

[add.constraint](#)

Examples

```

data(edhec)
ret <- edhec[, 1:4]

pspec <- portfolio.spec(assets=colnames(ret))

pspec <- add.constraint(portfolio=pspec, type="return", return_target=mean(colMeans(ret)))

```

return_objective *constructor for class return_objective*

Description

if target is null, we'll try to maximize the return metric

Usage

```

return_objective(
  name,
  target = NULL,
  arguments = NULL,
  multiplier = -1,
  enabled = TRUE,
  ...
)

```

Arguments

name	name of the objective, should correspond to a function, though we will try to make allowances
target	univariate target for the objective
arguments	default arguments to be passed to an objective function when executed
multiplier	multiplier to apply to the objective, usually 1 or -1
enabled	TRUE/FALSE
...	any other passthru parameters

Details

if target is set, we'll try to meet or exceed the metric, penalizing a shortfall

Value

object of class 'return_objective'

Author(s)

Brian G. Peterson

risk_budget_objective *constructor for class risk_budget_objective*

Description

constructor for class risk_budget_objective

Usage

```
risk_budget_objective(
    assets,
    name,
    target = NULL,
    arguments = NULL,
    multiplier = 1,
    enabled = TRUE,
    ...,
    min_prisk,
    max_prisk,
    min_concentration = FALSE,
    min_difference = FALSE
)
```

Arguments

assets	vector of assets to use, should come from constraints object
name	name of the objective, should correspond to a function, though we will try to make allowances
target	univariate target for the objective
arguments	default arguments to be passed to an objective function when executed
multiplier	multiplier to apply to the objective, usually 1 or -1
enabled	TRUE/FALSE
...	any other passthru parameters
min_prisk	minimum percentage contribution to risk
max_prisk	maximum percentage contribution to risk
min_concentration	TRUE/FALSE whether to minimize concentration, default FALSE, always TRUE if min_prisk and max_prisk are NULL
min_difference	TRUE/FALSE whether to minimize difference between concentration, default FALSE

Value

object of class 'risk_budget_objective'

Author(s)

Brian G. Peterson

rp_grid

Generate random portfolios based on grid search method

Description

This function generates random portfolios based on the gridSearch function from the 'NMOF' package.

Usage

```
rp_grid(portfolio, permutations = 2000, normalize = TRUE)
```

Arguments

portfolio	an object of class 'portfolio' specifying the constraints for the optimization, see portfolio.spec
permutations	integer: number of unique constrained random portfolios to generate
normalize	TRUE/FALSE to normalize the weights to satisfy min_sum or max_sum

Details

The number of levels is calculated based on permutations and number of assets. The number of levels must be an integer and may not result in the exact number of permutations. We round up to the nearest integer for the levels so the number of portfolios generated will be greater than or equal to permutations.

The grid search method only satisfies the min and max box constraints. The min_sum and max_sum leverage constraints will likely be violated and the weights in the random portfolios should be normalized. Normalization may cause the box constraints to be violated and will be penalized in constrained_objective.

Value

matrix of random portfolio weights

rp_sample	<i>Generate random portfolios using the sample method</i>
-----------	---

Description

This function generates random portfolios based on an idea by Pat Burns.

Usage

```
rp_sample(portfolio, permutations, max_permutations = 200)
```

Arguments

portfolio	an object of type "portfolio" specifying the constraints for the optimization, see portfolio.spec
permutations	integer: number of unique constrained random portfolios to generate
max_permutations	integer: maximum number of iterations to try for a valid portfolio, default 200

Details

The 'sample' method to generate random portfolios is based on an idea pioneered by Pat Burns. This is the most flexible method, but also the slowest, and can generate portfolios to satisfy leverage, box, group, and position limit constraints.

Value

a matrix of random portfolio weights

rp_simplex	<i>Generate random portfolios using the simplex method</i>
------------	--

Description

This function generates random portfolios based on the method outlined in the Shaw paper. Need to add reference.

Usage

```
rp_simplex(portfolio, permutations, fev = 0:5)
```

Arguments

portfolio	an object of class 'portfolio' specifying the constraints for the optimization, see portfolio.spec
permutations	integer: number of unique constrained random portfolios to generate
fev	scalar or vector for FEV biasing

Details

The simplex method is useful to generate random portfolios with the full investment constraint where the sum of the weights is equal to 1 and min box constraints with no upper bound on max constraints. Values for min_sum and max_sum will be ignored, the sum of weights will equal 1. All other constraints such as group and position limit constraints will be handled by elimination. If the constraints are very restrictive, this may result in very few feasible portfolios remaining.

The random portfolios are created by first generating a set of uniform random numbers.

$$U \sim [0, 1]$$

The portfolio weights are then transformed to satisfy the min of the box constraints.

$$w_i = \min_i + (1 - \sum_{j=1}^N \min_j) \frac{\log(U_i^q)}{\sum_{k=1}^N \log(U_k^q)}$$

fev controls the Face-Edge-Vertex (FEV) biasing where

$$q = 2^{fev}$$

As q approaches infinity, the set of weights will be concentrated in a single asset. To sample the interior and exterior, fev can be passed in as a vector. The number of portfolios, permutations, and the length of fev affect how the random portfolios are generated. For example, if permutations=10000 and fev=0:4, 2000 portfolios will be generated for each value of fev.

Value

a matrix of random portfolio weights

rp_transform

Transform a weights vector to satisfy constraints

Description

This function uses a block of code from [randomize_portfolio](#) to transform the weight vector if either the weight_sum (leverage) constraints, box constraints, group constraints, position_limit constraints, or leverage exposure constraints are violated. The logic from randomize_portfolio is heavily utilized here with extensions to handle more complex constraints. The resulting weights vector might be quite different from the original weights vector.

Usage

```
rp_transform(
  w,
  min_sum,
  max_sum,
  min_box,
  max_box,
```

```

    groups = NULL,
    cLO = NULL,
    cUP = NULL,
    max_pos = NULL,
    group_pos = NULL,
    max_pos_long = NULL,
    max_pos_short = NULL,
    leverage = NULL,
    weight_seq = NULL,
    max_permutations = 200
)

```

Arguments

w	weights vector to be transformed
min_sum	minimum sum of all asset weights, default 0.99
max_sum	maximum sum of all asset weights, default 1.01
min_box	numeric or named vector specifying minimum weight box constraints
max_box	numeric or named vector specifying maximum weight box constraints
groups	vector specifying the groups of the assets
cLO	numeric or vector specifying minimum weight group constraints
cUP	numeric or vector specifying maximum weight group constraints
max_pos	maximum assets with non-zero weights
group_pos	vector specifying maximum number assets with non-zero weights per group
max_pos_long	maximum number of assets with long (i.e. buy) positions
max_pos_short	maximum number of assets with short (i.e. sell) positions
leverage	maximum leverage exposure where leverage is defined as $\text{sum}(\text{abs}(\text{weights}))$
weight_seq	vector of seed sequence of weights
max_permutations	integer: maximum number of iterations to try for a valid portfolio, default 200

Value

named weighting vector

Author(s)

Peter Carl, Brian G. Peterson, Ross Bennett (based on an idea by Pat Burns)

scatterFUN	<i>Apply a risk or return function to asset returns</i>
------------	---

Description

This function is used to calculate risk or return metrics given a matrix of asset returns and will be used for a risk-reward scatter plot of the assets

Usage

```
scatterFUN(R, FUN, arguments = NULL)
```

Arguments

R	xts object of asset returns
FUN	name of function
arguments	named list of arguments to FUN

Author(s)

Ross Bennett

set.portfolio.moments	<i>Portfolio Moments</i>
-----------------------	--------------------------

Description

Set portfolio moments for use by lower level optimization functions. Currently three methods for setting the moments are available

Usage

```
set.portfolio.moments(  
  R,  
  portfolio,  
  momentargs = NULL,  
  method = c("sample", "boudt", "black_litterman", "meucci"),  
  ...  
)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
portfolio	an object of type "portfolio" specifying the constraints and objectives for the optimization, see portfolio.spec
momentargs	list containing arguments to be passed down to lower level functions, default NULL
method	the method used to estimate portfolio moments. Valid choices include "sample", "boudt", and "black_litterman".
...	any other passthru parameters

Details

sample: sample estimates are used for the moments

boudt: estimate the second, third, and fourth moments using a statistical factor model based on the work of Kris Boudt. See [statistical.factor.model](#)

black_litterman: estimate the first and second moments using the Black Litterman Formula. See [black.litterman](#).

```
set.portfolio.moments_v1
```

set portfolio moments for use by lower level optimization functions

Description

set portfolio moments for use by lower level optimization functions

Usage

```
set.portfolio.moments_v1(R, constraints, momentargs = NULL, ...)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
constraints	an object of type "constraints" specifying the constraints for the optimization, see constraint
momentargs	list containing arguments to be passed down to lower level functions, default NULL
...	any other passthru parameters FIXME NOTE: this isn't perfect as it overwrites the moments for all objectives, not just one with clean='boudt'

```
statistical.factor.model
```

Statistical Factor Model

Description

Fit a statistical factor model using Principal Component Analysis (PCA)

Usage

```
statistical.factor.model(R, k = 1, ...)
```

Arguments

R	xts of asset returns
k	number of factors to use
...	additional arguments passed to prcomp

Details

The statistical factor model is fitted using `prcomp`. The factor loadings, factor realizations, and residuals are computed and returned given the number of factors used for the model.

Value

#'

factor_loadings N x k matrix of factor loadings (i.e. betas)

factor_realizations m x k matrix of factor realizations

residuals m x N matrix of model residuals representing idiosyncratic risk factors

Where N is the number of assets, k is the number of factors, and m is the number of observations.

```
summary.efficient.frontier
```

Summarize an efficient frontier object

Description

Summary method for efficient frontier objects. Display the call to create or extract the efficient frontier object as well as the weights and risk and return metrics along the efficient frontier.

Usage

```
## S3 method for class 'efficient.frontier'
summary(object, ..., digits = 3)
```

Arguments

object	object of class <code>efficient.frontier</code>
...	passthrough parameters
digits	number of digits to round to

Author(s)

Ross Bennett

summary.optimize.portfolio
Summarizing output of optimize.portfolio

Description

summary method for class `optimize.portfolio`

Usage

```
## S3 method for class 'optimize.portfolio'  
summary(object, ...)
```

Arguments

object	an object of class <code>optimize.portfolio</code> .
...	any other passthru parameters. Currently not used.

Author(s)

Ross Bennett

See Also

[optimize.portfolio](#)

summary.optimize.portfolio.rebalancing
summary method for optimize.portfolio.rebalancing

Description

summary method for optimize.portfolio.rebalancing

Usage

```
## S3 method for class 'optimize.portfolio.rebalancing'  
summary(object, ...)
```

Arguments

object	object of type optimize.portfolio.rebalancing
...	any other passthru parameters

summary.portfolio *Summarize Portfolio Specification Objects*

Description

summary method for class portfolio created with [portfolio.spec](#)

Usage

```
## S3 method for class 'portfolio'  
summary(object, ...)
```

Arguments

object	an object of class portfolio
...	any other passthru parameters

Author(s)

Ross Bennett

See Also

[portfolio.spec](#)

trailingFUN	<i>apply a function over a configurable trailing period</i>
-------------	---

Description

this function is primarily designed for use with portfolio functions passing 'x' or 'R' and weights, but may be usable for other things as well, see Example for a vector example.

Usage

```
trailingFUN(R, weights, n = 0, FUN, FUNargs = NULL, ...)
```

Arguments

R	an xts, vector, matrix, data frame, timeSeries or zoo object of asset returns
weights	a vector of weights to test
n	numeric number of trailing periods
FUN	string describing the function to be called
FUNargs	list describing any additional arguments
...	any other passthru parameters

Details

called with e.g.

```
trailingFUN(seq(1:100), weights=NULL, n=12, FUN='mean', FUNargs=list())
```

transaction_cost_constraint	<i>constructor for transaction_cost_constraint</i>
-----------------------------	--

Description

The transaction cost constraint specifies a proportional cost value. This function is called by `add.constraint` when `type="transaction_cost"` is specified, see [add.constraint](#).

Usage

```
transaction_cost_constraint(
  type = "transaction_cost",
  assets,
  ptc,
  enabled = TRUE,
  message = FALSE,
  ...
)
```

Arguments

type	character type of the constraint
assets	number of assets, or optionally a named vector of assets specifying initial weights
ptc	proportional transaction cost value
enabled	TRUE/FALSE
message	TRUE/FALSE. The default is message=FALSE. Display messages if TRUE.
...	any other passthru parameters to specify box and/or group constraints

Details

Note that with the ROI solvers, proportional transaction cost constraint is currently only supported for the global minimum variance and quadratic utility problems with ROI quadprog plugin.

Value

an object of class 'transaction_cost_constraint'

Author(s)

Ross Bennett

See Also

[add.constraint](#)

Examples

```
data(edhec)
ret <- edhec[, 1:4]

pspec <- portfolio.spec(assets=colnames(ret))

pspec <- add.constraint(portfolio=pspec, type="transaction_cost", ptc=0.01)
```

turnover	<i>Calculates turnover given two vectors of weights. This is used as an objective function and is called when the user adds an objective of type turnover with add.objective</i>
----------	--

Description

Calculates turnover given two vectors of weights. This is used as an objective function and is called when the user adds an objective of type turnover with [add.objective](#)

Usage

```
turnover(weights, wts.init = NULL)
```

Arguments

weights	vector of weights from optimization
wts.init	vector of initial weights used to calculate turnover from

Author(s)

Ross Bennett

turnover_constraint *constructor for turnover_constraint*

Description

The turnover constraint specifies a target turnover value. This function is called by `add.constraint` when `type="turnover"` is specified, see [add.constraint](#). Turnover is calculated from a set of initial weights. Turnover is computed as $\text{sum}(\text{abs}(\text{initial_weights} - \text{weights})) / N$ where N is the number of assets.

Usage

```
turnover_constraint(
  type = "turnover",
  turnover_target,
  turnover_penalty = NULL,
  weight_initial = NULL,
  enabled = TRUE,
  message = FALSE,
  ...
)
```

Arguments

type	character type of the constraint
turnover_target	target turnover value
turnover_penalty	optional penalty parameter for turnover constraint
weight_initial	optional initial weights vector to compute turnover from
enabled	TRUE/FALSE
message	TRUE/FALSE. The default is <code>message=FALSE</code> . Display messages if TRUE.
...	any other passthru parameters to specify box and/or group constraints

Details

Note that with the ROI solvers, turnover constraint is currently only supported for the global minimum variance and quadratic utility problems with ROI quadprog plugin.

Value

an object of class 'turnover_constraint'

Author(s)

Ross Bennett

See Also

[add.constraint](#)

Examples

```
data(edhec)
ret <- edhec[, 1:4]

pspec <- portfolio.spec(assets=colnames(ret))

pspec <- add.constraint(portfolio=pspec, type="turnover", turnover_target=0.6)
```

turnover_objective *constructor for class turnover_objective*

Description

if target is null, we'll try to minimize the turnover metric

Usage

```
turnover_objective(
  name,
  target = NULL,
  arguments = NULL,
  multiplier = 1,
  enabled = TRUE,
  ...
)
```

Arguments

name	name of the objective, should correspond to a function, though we will try to make allowances
target	univariate target for the objective
arguments	default arguments to be passed to an objective function when executed
multiplier	multiplier to apply to the objective, usually 1 or -1
enabled	TRUE/FALSE
...	any other passthru parameters

Details

if target is set, we'll try to meet the metric

Value

an objective of class 'turnover_objective'

Author(s)

Ross Bennett

update.constraint *function for updating constraints, not well tested, may be broken*

Description

can we use the generic update.default function?

Usage

```
## S3 method for class 'constraint'
update(object, ...)
```

Arguments

object object of type `constraint` to update
 ... any other passthru parameters, used to call `constraint`

Author(s)

bpeterson

update_constraint_v1tov2
Helper function to update v1_constraint objects to v2 specification in the portfolio object

Description

The function takes the constraints and objectives specified in the `v1_constraint` object and updates the portfolio object with those constraints and objectives. This function is used inside `optimize.portfolio` to maintain backwards compatibility if the user passes in a `v1_constraint` object for the `constraint` arg in `optimize.portfolio`.

Usage

```
update_constraint_v1tov2(portfolio, v1_constraint)
```

Arguments

portfolio portfolio object passed into optimize.portfolio
v1_constraint object of type v1_constraint passed into optimize.portfolio

Value

portfolio object containing constraints and objectives from v1_constraint

Author(s)

Ross Bennett

See Also

[portfolio.spec](#), [add.constraint](#)

var.portfolio *Calculate portfolio variance*

Description

This function is used to calculate the portfolio variance via a call to `constrained_objective` when `var` is an object for mean variance or quadratic utility optimization.

Usage

```
var.portfolio(R, weights)
```

Arguments

R xts object of asset returns
weights vector of asset weights

Value

numeric value of the portfolio variance

Author(s)

Ross Bennett

```
weight_concentration_objective
    Constructor for weight concentration objective
```

Description

This function penalizes weight concentration using the Herfindahl-Hirschman Index as a measure of concentration.

Usage

```
weight_concentration_objective(
    name,
    conc_aversion,
    conc_groups = NULL,
    arguments = NULL,
    enabled = TRUE,
    ...
)
```

Arguments

name	name of concentration measure, currently only "HHI" is supported.
conc_aversion	concentration aversion value(s)
conc_groups	list of vectors specifying the groups of the assets. Similar to groups in group_constraint
arguments	default arguments to be passed to an objective function when executed
enabled	TRUE/FALSE
...	any other passthru parameters

Details

The `conc_aversion` argument can be a scalar or vector of concentration aversion values. If `conc_aversion` is a scalar and `conc_groups` is `NULL`, then the concentration aversion value will be applied to the overall weights.

If `conc_groups` is specified as an argument, then the concentration aversion value(s) will be applied to each group.

Value

an object of class 'weight_concentration_objective'

Author(s)

Ross Bennett

weight_sum_constraint *constructor for weight_sum_constraint*

Description

The constraint specifies the upper and lower bound on the sum of the weights. This function is called by `add.constraint` when "weight_sum", "leverage", "full_investment", "dollar_neutral", or "active" is specified as the type. see [add.constraint](#)

Usage

```
weight_sum_constraint(  
    type = "weight_sum",  
    min_sum = 0.99,  
    max_sum = 1.01,  
    enabled = TRUE,  
    ...  
)
```

Arguments

type	character type of the constraint
min_sum	minimum sum of all asset weights, default 0.99
max_sum	maximum sum of all asset weights, default 1.01
enabled	TRUE/FALSE
...	any other passthru parameters to specify weight_sum constraints

Details

Special cases for the weight_sum constraint are "full_investment" and "dollar_nuetral" or "active"

If type="full_investment", min_sum=1 and max_sum=1

If type="dollar_neutral" or type="active", min_sum=0, and max_sum=0

Value

an object of class 'weight_sum_constraint'

Author(s)

Ross Bennett

See Also

[add.constraint](#)

Examples

```
data(edhec)
ret <- edhec[, 1:4]

pspec <- portfolio.spec(assets=colnames(ret))

# min_sum and max_sum can be specified with type="weight_sum" or type="leverage"
pspec <- add.constraint(pspec, type="weight_sum", min_sum=1, max_sum=1)

# Specify type="full_investment" to set min_sum=1 and max_sum=1
pspec <- add.constraint(pspec, type="full_investment")

# Specify type="dollar_neutral" or type="active" to set min_sum=0 and max_sum=0
pspec <- add.constraint(pspec, type="dollar_neutral")
pspec <- add.constraint(pspec, type="active")
```

Index

- * **datasets**
 - indexes, 82
- ac.ranking, 10
- add.constraint, 7, 11, 22, 23, 52, 53, 61, 72, 73, 79, 80, 86, 118–120, 131, 143–146, 148, 150
- add.objective, 6, 7, 14, 99, 103, 104, 118, 144
- add.objective_v1 (add.objective), 14
- add.objective_v2 (add.objective), 14
- add.sub.portfolio, 16
- applyFUN, 17

- backtest.plot, 18
- barplotGroupWeights, 19
- black.litterman, 20, 139
- BlackLittermanFormula, 20, 21
- box_constraint, 12, 22

- CCCgarch.MM, 23
- center, 24
- centroid.buckets, 11, 24
- centroid.complete.mc, 11, 25
- centroid.sectors, 11, 26
- centroid.sign, 11, 26
- chart.Concentration, 27
- chart.EF.Weights, 8, 28
- chart.EfficientFrontier, 8, 30
- chart.EfficientFrontierCompare, 33
- chart.EfficientFrontierOverlay, 35
- chart.GroupWeights, 36
- chart.RiskBudget, 8, 38
- chart.RiskReward, 8, 40
- chart.StackedBar, 38, 40, 43, 46
- chart.Weights, 8, 43
- check_constraints, 46
- cokurtosisMF, 47
- cokurtosisSF, 47
- combine.optimizations, 8, 48

- combine.portfolios, 35, 49
- constrained_objective, 49, 64, 83
- constrained_objective_v1 (constrained_objective), 49
- constrained_objective_v2 (constrained_objective), 49
- constraint, 14, 51, 75, 105, 127, 129, 139, 147
- constraint (constraint_v1), 52
- constraint_ROI, 51
- constraint_v1, 52
- constraint_v2 (constraint_v1), 52
- coskewnessMF, 53
- coskewnessSF, 54
- covarianceMF, 54
- covarianceSF, 55
- create.EfficientFrontier, 9, 35, 56, 122
- custom.covRob.Mcd, 57
- custom.covRob.MM, 58
- custom.covRob.Rocke, 59
- custom.covRob.TSGS, 59

- DEoptim.control, 51
- diversification, 60
- diversification_constraint, 12, 61

- endpoints, 17, 108
- EntropyProg, 62
- equal.weight, 63
- ES, 9
- etl_milp_opt, 64
- etl_opt, 65
- extract_risk, 71
- extractCokurtosis, 65
- extractCoskewness, 66
- extractCovariance, 67
- extractEfficientFrontier, 67
- extractGroups, 68
- extractObjectiveMeasures, 69
- extractStats, 40, 43, 70, 113

- extractWeights, 71
- factor_exposure_constraint, 12, 72
- fn_map, 73, 127
- generatesequence, 51, 52, 74, 117, 118
- get_constraints, 75
- gmw_opt, 76
- gmw_opt_leverage, 77
- gmw_opt_ptc, 77
- gmw_opt_toc, 78
- group_constraint, 12, 79, 149
- group_fail, 81
- HHI, 81
- indexes, 82
- insert_constraints, 82
- insert_objectives, 83
- inverse.volatility.weight, 83
- is.constraint, 84
- is.objective, 84
- is.portfolio, 85
- leverage_exposure_constraint, 12, 85
- maxret_milp_opt, 86
- maxret_opt, 87
- meancsm.efficient.frontier, 88
- meaneqs.efficient.frontier, 89
- meanetl.efficient.frontier, 57, 90
- meanrisk.efficient.frontier, 57, 91
- meanvar.efficient.frontier, 56, 57, 92
- meucci.moments, 93, 94
- meucci.ranking, 93
- minmax_objective, 94
- mult.portfolio.spec, 17, 95
- MycovRobMcd, 96
- MycovRobTSGS, 97
- name.replace, 98
- objective, 15, 51, 75, 99, 128, 129
- opt.outputMvo, 100
- optimize.portfolio, 7–9, 17, 28, 32, 33, 39, 40, 42, 43, 45, 46, 48, 50, 56, 57, 67–71, 88–92, 101, 108, 109, 113, 118, 123, 141
- optimize.portfolio.parallel, 106
- optimize.portfolio.rebalancing, 7, 9, 17, 39, 40, 43, 46, 71, 107, 122
- optimize.portfolio.rebalancing_v1 (optimize.portfolio.rebalancing), 107
- optimize.portfolio_v1 (optimize.portfolio), 101
- optimize.portfolio_v2 (optimize.portfolio), 101
- pHist, 110
- plot, 19, 28, 29, 32, 34, 36, 37, 39, 42, 114, 115
- plot.optimize.portfolio (plot.optimize.portfolio.DEoptim), 111
- plot.optimize.portfolio.DEoptim, 111
- plotFrontiers, 113
- portfolio, 15, 50
- portfolio(portfolio.spec), 117
- portfolio.moments.bl, 115
- portfolio.moments.boudt, 116
- portfolio.spec, 7, 11, 12, 14, 15, 17, 34, 35, 49, 56, 57, 76, 88–92, 99, 105, 109, 116, 117, 117, 123, 124, 126, 128, 134, 135, 139, 142, 148
- portfolio_risk_objective, 118, 125
- PortfolioAnalytics (PortfolioAnalytics-package), 5
- PortfolioAnalytics-package, 5
- pos_limit_fail, 120
- position_limit_constraint, 12, 119
- print.constraint, 121
- print.efficient.frontier, 121
- print.optimize.portfolio.CVXR (print.optimize.portfolio.ROI), 122
- print.optimize.portfolio.DEoptim (print.optimize.portfolio.ROI), 122
- print.optimize.portfolio.GenSA (print.optimize.portfolio.ROI), 122
- print.optimize.portfolio.pso (print.optimize.portfolio.ROI), 122
- print.optimize.portfolio.random (print.optimize.portfolio.ROI), 122

print.optimize.portfolio.rebalancing, 122
 print.optimize.portfolio.ROI, 122
 print.portfolio, 123
 print.summary.optimize.portfolio, 124
 print.summary.optimize.portfolio.rebalancing, 125

 quadratic_utility_objective, 125

 random_portfolios, 113, 118, 127
 random_portfolios_v1, 129
 random_portfolios_v2
 (random_portfolios), 127
 random_walk_portfolios, 130
 randomize_portfolio, 126, 129, 136
 randomize_portfolio_v1, 127
 randomize_portfolio_v2
 (randomize_portfolio), 126
 regime.portfolios, 130
 return_constraint, 12, 131
 return_objective, 125, 132
 risk_budget_objective, 133
 rp_grid, 128, 134
 rp_sample, 128, 135
 rp_simplex, 128, 135
 rp_transform, 81, 120, 136

 scatterFUN, 138
 set.portfolio.moments, 138
 set.portfolio.moments_v1, 139
 set.portfolio.moments_v2, 102, 106
 set.portfolio.moments_v2
 (set.portfolio.moments), 138
 statistical.factor.model, 66, 67, 139, 140
 StdDev, 9
 summary.efficient.frontier, 140
 summary.optimize.portfolio, 124, 141
 summary.optimize.portfolio.rebalancing, 125, 142
 summary.portfolio, 142

 title, 19, 37, 45, 46, 113
 trailingFUN, 143
 transaction_cost_constraint, 143
 turnover, 144
 turnover_constraint, 12, 145
 turnover_objective, 146

 update.constraint, 147
 update_constraint_v1tov2, 147

 VaR, 9
 var.portfolio, 148

 weight_concentration_objective, 149
 weight_sum_constraint, 12, 150

 xts, 9