

Package ‘qdapTools’

May 9, 2026

Type Package

Title Tools for the 'qdap' Package

Version 1.3.7

Maintainer Tyler Rinker <tyler.rinker@gmail.com>

Depends R (>= 3.0.0)

Imports chron, data.table (>= 1.9.6), methods, RCurl, XML

Suggests testthat

Description A collection of tools associated with the 'qdap' package that may be useful outside of the context of text analysis.

License GPL-2

URL <https://github.com/trinker/qdapTools>

BugReports <https://github.com/trinker/qdapTools/issues>

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Bryan Goodrich [ctb],
Dason Kurkiewicz [ctb],
Kirill Muller [ctb],
Tyler Rinker [aut, cre]

Repository CRAN

Date/Publication 2023-05-10 07:20:02 UTC

Contents

hash	2
hms2sec	4
id	4
list2df	5
loc_split	8
lookup	10

lookup_e	12
mtabulate	14
pad	15
print.v_outer	16
read_docx	17
repo2github	18
run_split	20
shift	21
split_vector	21
start_end	23
text2color	23
url_dl	24
v_outer	25
%l*%	27

Index 29

hash	<i>Hash/Dictionary Lookup</i>
------	-------------------------------

Description

hash - Creates a **data.table** based hash table for quick hash style dictionary lookup.

hash_look - Works with a hash table such as is returned from hash, to lookup values.

%h1% - A binary operator version of hash_look.

%h1+% - A binary operator version of hash_look for when missing is assumed to be NULL.

hash_e - Creates a new environment for quick hash style dictionary lookup.

Usage

```
hash(x)

hash_look(terms, key, missing = NA)

terms %h1% key

terms %h1+% key

hash_e(x, mode.out = "numeric")
```

Arguments

x	A two column dataframe.
terms	A vector of terms to undergo a lookup.
key	The hash key to use.
missing	Value to assign to terms not found in the hash table.
mode.out	The type of output (column 2) expected (e.g., "character", "numeric", etc.)

Value

hash - Creates a "hash table", a two column **data.table**.

hash_e - Creates a "hash table", a two column data.frame in its own environment.

Author(s)

hash_e - Bryan Goodrich and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://www.talkstats.com/showthread.php/22754-Create-a-fast-dictionary>

See Also

[setDT, hash](#)
[environment](#)

Examples

```
##=====##
## data.table Hashes ##
##=====##
(DF <- aggregate(mpg~as.character(carb), mtcars, mean))
x <- sample(DF[, 1], 20, TRUE)
new.hash <- hash(DF)
x2 <- c(9, 12, x)
hash_look(x, new.hash)

x %h1% new.hash
x2 %h1% new.hash
x2 %h1+% new.hash

## Create generic functions
hfun <- function(x, ...) {
  hsh <- hash(x, ...)
  function(x, ...) hash_look(x, hsh, ...)
}

m <- hfun(DF)
m(x)

##=====##
## Environment Hashes ##
##=====##
new.hash2 <- hash_e(DF)

x %h1% new.hash2
x2 %h1% new.hash2
x2 %h1+% new.hash2
```

hms2sec	<i>Convert h:m:s To/From Seconds</i>
---------	--------------------------------------

Description

hms2sec - Converts a vector of h:m:s to seconds.

sec2hms - Converts a vector of seconds to h:m:s.

Usage

```
hms2sec(x)
```

```
sec2hms(x)
```

Arguments

x A vector of times in h:m:s (for hms2sec) or seconds (for sec2hms) .

Value

hms2sec - Returns a vector of times in seconds.

sec2hms - Returns a vector of times in h:m:s format.

See Also

[times](#)

Examples

```
hms2sec(c("02:00:03", "04:03:01"))
hms2sec(sec2hms(c(222, 1234, 55)))
sec2hms(c(256, 3456, 56565))
```

id	<i>ID By Row Number or Sequence Along</i>
----	---

Description

Generate a sequence of integers the `length/ncol` of an object.

Usage

```
id(x, prefix = FALSE, pad = TRUE, ...)
```

Arguments

x	A dataframe, matrix, vector, or list object.
prefix	A character string to use as a prefix. FALSE or NULL results in no prefix being used. TRUE will utilize the prefix "X.".
pad	logical. If TRUE the beginning number will be padded with zeros.
...	Other arguments passed to <code>pad</code> .

Value

Returns a vector of sequential integers.

Examples

```
id(list(1, 4, 6))
id(matrix(1:10, ncol=1))
id(mtcars)
id(mtcars, TRUE)
id("w")
id(mtcars, prefix="id-")
## Not run:
library(qdap)
question_type(DATA.SPLIT$state, id(DATA.SPLIT, TRUE))

## End(Not run)
```

list2df

List/Matrix/Vector to Dataframe/List/Matrix

Description

`list2df` - Convert a named list of vectors to a dataframe.

`matrix2df` - Convert a matrix to a dataframe and convert the rownames to the first column.

`vect2df` - Convert a named vector to a dataframe.

`list_df2df` - Convert a list of equal numbered/named columns to a dataframe using the list names as the level two variable.

`list_vect2df` - Convert a list of named vectors to a hierarchical dataframe.

`counts2list` - Convert a count matrix to a named list of elements.

`vect2list` - Convert a vector to a named list.

`df2matrix` - Convert a dataframe to a matrix and simultaneously move a column (default is the first column) to the rownames of a matrix.

`matrix2long` - Convert a matrix to a long format dataframe where column names become column 1, row names, column 2 and the values become column 3.

Usage

```
list2df(list.object, col1 = "X1", col2 = "X2")

matrix2df(matrix.object, col1 = "var1")

vect2df(vector.object, col1 = "X1", col2 = "X2", order = TRUE, rev = FALSE)

list_df2df(list.df.object, col1 = "X1")

list_vect2df(
  list.vector.object,
  col1 = "X1",
  col2 = "X2",
  col3 = "X3",
  order = TRUE,
  ...
)

counts2list(mat, nm = rownames(mat))

vect2list(vector.object, use.names = TRUE, numbered.names = FALSE)

df2matrix(data.frame.object, i = 1)

matrix2long(matrix.object, col1 = "cols", col2 = "rows", col3 = "vals")
```

Arguments

list.object	A named <code>list</code> of vectors..
col1	Name for column 1 (the vector elements if converting a list or the rownames if converting a matrix).
col2	Name for column 2 (the names of the vectors).
matrix.object	A matrix or <code>simple_triplet_matrix</code> object.
vector.object	A vector object.
order	logical. If TRUE the dataframe will be ordered.
rev	logical. If TRUE and order = TRUE the dataframe will be ordered in descending order.
list.df.object	A list of dataframes with equal number/named of columns.
list.vector.object	A list of dataframes with equal number/named of columns.
col3	The name of the third column (<code>list_vect2df</code>).
...	Further arguments passed to <code>vect2df</code> .
mat	A matrix of counts.
nm	A character vector of names to assign to the list.

use.names	logical. If TRUE and the vector is named, these names will be transferred to the list names.
numbered.names	logical. If TRUE padded numbers will be used as list names. If FALSE the vector elements themselves will become the list names.
data.frame.object	A data.frame object.
i	The column number or name to become the rownames of the matrix.

Value

list2df - Returns a dataframe with two columns.
matrix2df - Returns a dataframe.
vect2df - Returns a dataframe.
list_df2df - Returns a dataframe.
list_vect2df - Returns a dataframe.
counts2list - Returns a list of elements.
vect2list - Returns a list of named elements.
df2matrix - Returns a matrix.
matrix2long - Returns a long format dataframe.

See Also

[mtabulate](#)

Examples

```
lst1 <- list(x=c("foo", "bar"), y=1:5)
list2df(lst1)

lst2 <- list(a=c("hello", "everybody"), b = mtcars[1:6, 1])
list2df(lst2, "col 1", "col 2")

matrix2df(mtcars)
matrix2df(cor(mtcars))
matrix2df(matrix(1:9, ncol=3))

vect2df(1:10)
vect2df(c(table(mtcars[, "gear"])))

list_df2df(list(mtcars, mtcars))

L1 <- list(a=1:10, b=1:6, c=5:8)
list_vect2df(L1)

L2 <- list(
  months=setNames(1:12, month.abb),
  numbers=1:6,
  states=setNames(factor(state.name[1:4]), state.abb[1:4])
)
```

```

)

list_vect2df(L2)

set.seed(10)
cnts <- data.frame(month=month.name,
  matrix(sample(0:2, 36, TRUE), ncol=3))

counts2list(cnts[, -1], cnts[, 1])
df2matrix(cnts)
counts2list(df2matrix(cnts))
counts2list(t(df2matrix(cnts)))

mat <- matrix(1:9, ncol=3)
matrix2long(mat)
matrix2long(mtcars)

## Not run:
library(qdap)
term <- c("the ", "she", " wh")
(out <- with(raj.act.1, termco(dialogue, person, term)))
x <- counts(out)

counts2list(x[, -c(1:2)], x[, 1])

## End(Not run)

vect2list(LETTERS[1:10])
vect2list(LETTERS[1:10], numbered.names = TRUE)
x <- setNames(LETTERS[1:4], paste0("Element_", 1:4))
vect2list(x)
vect2list(x, FALSE)
vect2list(x, FALSE, TRUE)

```

loc_split

Split Data Forms at Specified Locations

Description

Split data forms at specified integer locations.

Usage

```
loc_split(x, locs, names = NULL, ...)
```

```
## S3 method for class 'list'
loc_split(x, locs, names = NULL, ...)
```

```
## S3 method for class 'data.frame'
loc_split(x, locs, names = NULL, ...)
```

```
## S3 method for class 'matrix'
loc_split(x, locs, names = NULL, ...)

## S3 method for class 'numeric'
loc_split(x, locs, names = NULL, ...)

## S3 method for class 'factor'
loc_split(x, locs, names = NULL, ...)

## S3 method for class 'character'
loc_split(x, locs, names = NULL, ...)

## Default S3 method:
loc_split(x, locs, names = NULL, ...)
```

Arguments

x	A data form (list, vector, data.frame, matrix).
locs	A vector of integer locations to split at. If locs contains the index 1, it will be silently dropped.
names	Optional vector of names to give to the list elements.
...	Ignored.

Value

Returns of list of data forms broken at the locs.

Note

Two dimensional object will retain dimension (i.e., drop = FALSE is used).

See Also

[run_split](https://github.com/trinker/loc_split_example), [split_vector](https://github.com/trinker/loc_split_example) https://github.com/trinker/loc_split_example for practical usage.

Examples

```
## character
loc_split(LETTERS, c(4, 10, 16))
loc_split(LETTERS, c(4, 10, 16), c("dog", "cat", "chicken", "rabbit"))

## numeric
loc_split(1:100, c(33, 66))

## factor
(p_chng <- head(1 + cumsum(rle(as.character(CO2[["Plant"]])))[[1]]), -1))
loc_split(CO2[["Plant"]], p_chng)
```

```
## list
loc_split(as.list(LETTERS), c(4, 10, 16))

## data.frame
(vs_change <- head(1 + cumsum(rle(as.character(mtcars[["vs"]])))[[1]]), -1))
loc_split(mtcars, vs_change)

## matrix
(mat <- matrix(1:50, nrow=10))
loc_split(mat, c(3, 6, 10))
```

lookup	<i>Hash Table/Dictionary Lookup lookup - Rhrefhttp://datatable.r-forge.r-project.org/data.table based hash table useful for large vector lookups.</i>
--------	---

Description

`%l%` - A binary operator version of `lookup` for when `key.match` is a data.frame or named list.

`%l+%` - A binary operator version of `lookup` for when `key.match` is a data.frame or named list and missing is assumed to be NULL.

`%lc%` - A binary operator version of `lookup` for when `key.match` is a data.frame or named list and all arguments are converted to character.

`%lc+%` - A binary operator version of `lookup` for when `key.match` is a data.frame or named list, missing is assumed to be NULL, and all arguments are converted to character.

Usage

```
lookup(terms, key.match, key.reassign = NULL, missing = NA)
```

```
## S3 method for class 'list'
```

```
lookup(terms, key.match, key.reassign = NULL, missing = NA)
```

```
## S3 method for class 'data.frame'
```

```
lookup(terms, key.match, key.reassign = NULL, missing = NA)
```

```
## S3 method for class 'matrix'
```

```
lookup(terms, key.match, key.reassign = NULL, missing = NA)
```

```
## S3 method for class 'numeric'
```

```
lookup(terms, key.match, key.reassign, missing = NA)
```

```
## S3 method for class 'factor'
```

```
lookup(terms, key.match, key.reassign, missing = NA)
```

```
## S3 method for class 'character'
```

```
lookup(terms, key.match, key.reassign, missing = NA)
```

```

terms %l% key.match
terms %l+% key.match
terms %lc% key.match
terms %lc+% key.match

```

Arguments

terms	A vector of terms to undergo a lookup.
key.match	Takes one of the following: (1) a two column data.frame of a match key and reassignment column, (2) a named list of vectors (Note: if data.frame or named list supplied no key reassign needed) or (3) a single vector match key.
key.reassign	A single reassignment vector supplied if key.match is not a two column data.frame/named list.
missing	Value to assign to terms not matching the key.match. If set to NULL the original values in terms corresponding to the missing elements are retained.

Value

Outputs A new vector with reassigned values.

See Also

[setDT](#), [hash](#)

Examples

```

## Supply a dataframe to key.match

lookup(1:5, data.frame(1:4, 11:14))

## Retain original values for missing
lookup(1:5, data.frame(1:4, 11:14), missing=NULL)

lookup(LETTERS[1:5], data.frame(LETTERS[1:5], 100:104))
lookup(LETTERS[1:5], factor(LETTERS[1:5]), 100:104)

## Supply a named list of vectors to key.match

codes <- list(
  A = c(1, 2, 4),
  B = c(3, 5),
  C = 7,
  D = c(6, 8:10)
)

lookup(1:10, codes)

```

```

## Supply a single vector to key.match and key.reassign

lookup(mtcars$carb, sort(unique(mtcars$carb)),
       c("one", "two", "three", "four", "six", "eight"))

lookup(mtcars$carb, sort(unique(mtcars$carb)),
       seq(10, 60, by=10))

## %l%, a binary operator version of lookup
1:5 %l% data.frame(1:4, 11:14)
1:10 %l% codes

1:12 %l% codes
1:12 %l+% codes

(key <- data.frame(a=1:3, b=factor(paste0("1", 1:3))))
1:3 %l% key

##Larger Examples
key <- data.frame(x=1:2, y=c("A", "B"))
big.vec <- sample(1:2, 3000000, TRUE)
out <- lookup(big.vec, key)
out[1:20]

## A big string to recode with variation
## means a bigger dictionary
recode_me <- sample(1:(length(LETTERS)*10), 10000000, TRUE)

## Time it
tic <- Sys.time()

output <- recode_me %l% split(1:(length(LETTERS)*10), LETTERS)
difftime(Sys.time(), tic)

## view it
sample(output, 100)

```

lookup_e

Hash Table/Dictionary Lookup lookup_e - Environment based hash table useful for large vector lookups.

Description

%le% - A binary operator version of lookup_e for when key.match is a data.frame or named list.

%le+% - A binary operator version of lookup_e for when key.match is a data.frame or named list and missing is assumed to be NULL.

Usage

```
lookup_e(terms, key.match, key.reassign = NULL, missing = NA)

## S3 method for class 'matrix'
lookup_e(terms, key.match, key.reassign = NULL, missing = NA)

## S3 method for class 'data.frame'
lookup_e(terms, key.match, key.reassign = NULL, missing = NA)

## S3 method for class 'list'
lookup_e(terms, key.match, key.reassign = NULL, missing = NA)

## S3 method for class 'numeric'
lookup_e(terms, key.match, key.reassign = NULL, missing = NA)

## S3 method for class 'factor'
lookup_e(terms, key.match, key.reassign = NULL, missing = NA)

## S3 method for class 'character'
lookup_e(terms, key.match, key.reassign = NULL, missing = NA)

terms %l% key.match

terms %le+% key.match
```

Arguments

terms	A vector of terms to undergo a lookup_e.
key.match	Takes one of the following: (1) a two column data.frame of a match key and reassignment column, (2) a named list of vectors (Note: if data.frame or named list supplied no key reassign needed) or (3) a single vector match key.
key.reassign	A single reassignment vector supplied if key.match is not a two column data.frame/named list.
missing	Value to assign to terms not matching the key.match. If set to NULL the original values in terms corresponding to the missing elements are retained.

Value

Outputs A new vector with reassigned values.

See Also

[new.env](#), [lookup](#),

Examples

```
lookup_e(1:5, data.frame(1:4, 11:14))
```

```

## Retain original values for missing
lookup_e(1:5, data.frame(1:4, 11:14), missing=NULL)

lookup_e(LETTERS[1:5], data.frame(LETTERS[1:5], 100:104))
lookup_e(LETTERS[1:5], factor(LETTERS[1:5]), 100:104)

## Supply a named list of vectors to key.match

codes <- list(
  A = c(1, 2, 4),
  B = c(3, 5),
  C = 7,
  D = c(6, 8:10)
)

lookup_e(1:10, codes)

## Supply a single vector to key.match and key.reassign

lookup_e(mtcars$carb, sort(unique(mtcars$carb)),
  c("one", "two", "three", "four", "six", "eight"))

lookup_e(mtcars$carb, sort(unique(mtcars$carb)),
  seq(10, 60, by=10))

## %le%, a binary operator version of lookup
1:5 %le% data.frame(1:4, 11:14)
1:10 %le% codes

1:12 %le% codes
1:12 %le+% codes

```

mtabulate

Tabulate Frequency Counts for Multiple Vectors

Description

Similar to [tabulate](#) that works on multiple vectors.

Usage

```
mtabulate(vects)
```

Arguments

`vects` A [vector](#), [list](#), or [data.frame](#) of named/unnamed vectors.

Value

Returns a `data.frame` with columns equal to number of unique elements and the number of rows equal to the original length of the `vector`, `list`, or `data.frame` (length equals `ncols` in `data.frame`). If list of vectors is named these will be the rownames of the dataframe.

Author(s)

Joran Elias and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://stackoverflow.com/a/9961324/1000343>

See Also

`tabulate`, `counts2list`

Examples

```
mtabulate(list(w=letters[1:10], x=letters[1:5], z=letters))
mtabulate(list(mtcars$cyl[1:10]))

## Dummy coding
mtabulate(mtcars$cyl[1:10])
mtabulate(CO2[, "Plant"])

dat <- data.frame(matrix(sample(c("A", "B"), 30, TRUE), ncol=3))
mtabulate(dat)
t(mtabulate(dat))
counts2list(mtabulate(dat))
```

pad

Pad Strings

Description

A convenience wrapper for `sprintf` that pads the front end of strings with spaces or 0s. Useful for creating multiple uniform directories that will maintain correct order.

Usage

```
pad(x, padding = max(nchar(as.character(x))), sort = TRUE, type = "detect")
```

Arguments

x	A character, factor, numeric vector.
padding	Number of characters to pad. Default makes all elements of a string the number of characters of the element with the maximum characters.
sort	logical. If TRUE the outcome is sorted.
type	A character string of "detect", "numeric", "character", "d" or "s". If numeric zeros are padded. If character spaces are padded. The detect attempts to determine if x is numeric (d) or not (s).

Value

Returns a character vector every element padded with 0/spaces.

Note

pad is a wrapper for the [sprintf](#) function. pad may behave differently on various platforms in accordance with the documentation for [sprintf](#): "actual implementation will follow the C99 standard and fine details (especially the behaviour under user error) may depend on the platform." See [sprintf](#) for more information.

See Also

[sprintf](#)

Examples

```
pad(sample(1:10, 10))
pad(sample(1:10, 10), sort=FALSE)
pad(as.character(sample(1:10, 10)))
pad(as.character(sample(1:10, 10)), sort=FALSE)
pad(as.character(sample(1:10, 10)), 4)
pad(month.name)
```

print.v_outer

Prints a v_outer Object.

Description

Prints a v_outer object.

Usage

```
## S3 method for class 'v_outer'
print(x, digits = 3, ...)
```

Arguments

x	The v_outer object
digits	Number of decimal places to print.
...	ignored

read_docx	<i>Read in .docx Content</i>
-----------	------------------------------

Description

Read in the content from a .docx file.

Usage

```
read_docx(file, skip = 0)
```

Arguments

file	The path to the .docx file.
skip	The number of lines to skip.

Value

Returns a character vector.

Author(s)

Bryan Goodrich and Tyler Rinker <tyler.rinker@gmail.com>.

Examples

```
## Not run:
## Mining Citation
url_dl("http://umlreading.weebly.com/uploads/2/5/2/5/25253346/whole_language_timeline-updated.docx")

(txt <- read_docx("whole_language_timeline-updated.docx"))

library(qdapTools); library(ggplot2); library(qdap)
txt <- rm_non_ascii(txt)

parts <- split_vector(txt, split = "References", include = TRUE, regex=TRUE)

parts[[1]]

rm_citation(unbag(parts[[1]]), extract=TRUE)[[1]]

## By line
rm_citation(parts[[1]], extract=TRUE)
```

```

## Frequency
left_just(cites <- list2df(sort(table(rm_citation(unbag(parts[[1]]),
  extract=TRUE)), T), "freq", "citation")[2:1])

## Distribution of citations (find locations and then plot)
cite_locs <- do.call(rbind, lapply(cites[[1]], function(x){
  m <- grexpr(x, unbag(parts[[1]]), fixed=TRUE)
  data.frame(
    citation=x,
    start = m[[1]] -5,
    end = m[[1]] + 5 + attributes(m[[1]])[["match.length"]]
  )
}))

ggplot(cite_locs) +
  geom_segment(aes(x=start, xend=end, y=citation, yend=citation), size=3,
    color="yellow") +
  xlab("Duration") +
  scale_x_continuous(expand = c(0,0),
    limits = c(0, nchar(unbag(parts[[1]])) + 25)) +
  theme_grey() +
  theme(
    panel.grid.major=element_line(color="grey20"),
    panel.grid.minor=element_line(color="grey20"),
    plot.background = element_rect(fill="black"),
    panel.background = element_rect(fill="black"),
    panel.border = element_rect(colour = "grey50", fill=NA, size=1),
    axis.text=element_text(color="grey50"),
    axis.title=element_text(color="grey50")
  )

## End(Not run)

```

 repo2github

Upload a Local Repo to GitHub

Description

Allows uploading a local repository to **GitHub** without first creating the repository in the clouds. [repo2github](#) is designed for the initial push to GitHub. Future pushes can be handled via RStudio or other **Git** interface.

Usage

```

repo2github(
  password,
  project.dir = getwd(),
  repo = basename(getwd()),
  github.user = getOption("github.user"),

```

```
    gitpath = NULL,  
    readme = TRUE  
)
```

Arguments

password	GitHub user password (character string). If this is not supplied the user will be prompted to enter a password.
project.dir	The path to the root directory of the report/presentation.
repo	A character string naming the repo; default attempts to use the report project directory name.
github.user	GitHub user name (character string).
gitpath	Path to the location of Git . If NULL repo2github will attempt to locate the path if necessary.
readme	logical. If TRUE repo initializes with a README.md file.

Details

The arguments `project.dir` and `repo` use `getwd`. This assumes is the current working directory is the root directory and is done for convenience. The user should ensure that either their working directory is the root directory or supply the correct root directory/name to these arguments.

Value

Creates GitHub repository.

Warning

For Windows users this function creates a temporary `_netrc` file in the home directory and attempts to delete this file. The `_netrc` contains username and password information for GitHub. `repo2github` attempts to delete this file but care should be taken. The file is created in: `file.path(Sys.getenv()["HOME"], "DELETE_ME_REPORTS_PACKAGE/_netrc")`.

Suggestion

The user may want to set `options` for `github.user` in the user's primary `.Rprofile`.

Note

The user will need to have a **GitHub** account established.

Author(s)

Simon O'Hanlon, Daniel Chaffiol, and Tyler Rinker <tyler.rinker@gmail.com>

References

<https://stackoverflow.com/a/15047013/1000343>
<https://stackoverflow.com/a/18692400/1000343>

Examples

```
## Not run:  
repo2github()  
  
## End(Not run)
```

`run_split`*Split a String Into Run Chunks*

Description

Splits a string into a vector of runs.

Usage

```
run_split(x)
```

Arguments

`x` A string.

Value

Returns a list of vectors.

Author(s)

Robert Reed and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://stackoverflow.com/a/24319217/1000343>

See Also

[loc_split](#), [split_vector](#)

Examples

```
run_split(c("12233344445555566666", NA, "abbccddddeeeeffffff"))
```

shift	<i>Shift Vector Left/Right</i>
-------	--------------------------------

Description

Shift a vector left or right n spaces.

Usage

```
shift(x, n, direction = "right")
```

```
shift_right(x, n)
```

```
shift_left(x, n)
```

Arguments

x	A vector.
n	The number of moves left or right to shift.
direction	A direction to shift; must be either "left" or "right". Use explicit directional shift functions <code>shift_right</code> and <code>shift_left</code> for better performance.

Value

Returns a shifted vector.

Examples

```
lapply(0:9, function(i) shift(1:10, i))
lapply(0:9, function(i) shift(1:10, i, "left"))

## Explicit, faster shifting
lapply(0:9, function(i) shift_right(1:10, i))
lapply(0:9, function(i) shift_left(1:10, i))
lapply(0:25, function(i) shift_left(LETTERS, i))
```

split_vector	<i>Split a Vector By Split Points</i>
--------------	---------------------------------------

Description

Splits a vector into a list of vectors based on split points.

Usage

```
split_vector(x, split = "", include = FALSE, regex = FALSE, ...)
```

Arguments

x	A vector with split points.
split	A vector of places (elements) to split on or a regular expression if regex argument is TRUE.
include	An integer of 1 (split character(s) are not included in the output), 2 (split character(s) are included at the beginning of the output), or 3 (split character(s) are included at the end of the output).
regex	logical. If TRUE regular expressions will be enabled for split argument.
...	other arguments passed to <code>grep</code> and <code>grepl</code> .

Value

Returns a list of vectors.

Author(s)

Matthew Flickinger and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://stackoverflow.com/a/24319217/1000343>

See Also

[loc_split](#), [run_split](#)

Examples

```
set.seed(15)
x <- sample(c("", LETTERS[1:10]), 25, TRUE, prob=c(.2, rep(.08, 10)))

split_vector(x)
split_vector(x, "C")
split_vector(x, c("", "C"))

split_vector(x, include = 0)
split_vector(x, include = 1)
split_vector(x, include = 2)

set.seed(15)
x <- sample(1:11, 25, TRUE, prob=c(.2, rep(.08, 10)))
split_vector(x, 1)

## relationship to `loc_split`
all.equal(
  split_vector(x, include = 1),
  loc_split(x, which(x == ""), names=1:6)
)
```

start_end	<i>Get Location of Start/End Points</i>
-----------	---

Description

Get the locations of start/end places for the ones in a binary vector.

Usage

```
start_end(x)
```

Arguments

x A vector of 1 and 0 or `logical`.

Value

Returns a two column `data.frame` of start and end locations for ones.

Author(s)

Roland (<https://stackoverflow.com/users/1412059/roland>) and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://stackoverflow.com/a/29184841/1000343>

Examples

```
set.seed(10); (x <- sample(0:1, 50, TRUE, c(.35, .65)))
start_end(x)
(y <- sample(c(TRUE, FALSE), 50, TRUE, c(.35, .65)))
start_end(y)
```

text2color	<i>Map Words to Colors</i>
------------	----------------------------

Description

A dictionary lookup that maps words to colors.

Usage

```
text2color(words, recode.words, colors)
```

Arguments

words	A vector of words.
recode.words	A vector of unique words or a list of unique word vectors that will be matched against corresponding colors.
colors	A vector of colors of equal in length to recode.words +1 (the +1 is for unmatched words).

Value

Returns a vector of mapped colors equal in length to the words vector.

See Also

[lookup](#)

Examples

```
x <- structure(list(X1 = structure(c(3L, 1L, 8L, 4L, 7L, 2L, 2L, 2L,
  4L, 8L, 4L, 3L, 5L, 3L, 1L, 8L, 7L, 2L, 1L, 6L), .Label = c("a",
  "and", "in", "is", "of", "that", "the", "to"), class = "factor")),
  .Names = "X1", row.names = c(NA, -20L), class = "data.frame")

#blue was recycled
text2color(x$X1, c("the", "and", "is"), c("red", "green", "blue"))
text2color(x$X1, c("the", "and", "is"), c("red", "green", "blue", "white"))
x$X2 <- text2color(x$X1, list(c("the", "and", "is"), "that"),
  c("red", "green", "white"))
x
```

url_dl

Download Instructional Documents

Description

This function enables downloading documents for future instructional training.

Usage

```
url_dl(..., url = 61803503)
```

Arguments

url	The download url or Dropbox key.
...	Document names to download. Quoted strings (complete urls) can also be supplied (if so no url argument is supplied).

Value

Places a copy of the downloaded document in the users working directory.

Examples

```
## Not run:
## Example 1 (download from Dropbox)
# download transcript of the debate to working directory
library(qdap)
url_dl(pres.deb1.docx, pres.deb2.docx, pres.deb3.docx)

# load multiple files with read transcript and assign to working directory
dat1 <- read.transcript("pres.deb1.docx", c("person", "dialogue"))
dat2 <- read.transcript("pres.deb2.docx", c("person", "dialogue"))
dat3 <- read.transcript("pres.deb3.docx", c("person", "dialogue"))

docs <- qcv(pres.deb1.docx, pres.deb2.docx, pres.deb3.docx)
dir() %in% docs
library(reports); delete(docs) #remove the documents
dir() %in% docs

## Example 2 (quoted string urls)
url_dl("https://dl.dropboxusercontent.com/u/61803503/qdap.pdf",
       "http://www.cran.r-project.org/doc/manuals/R-intro.pdf")

delete(c("qdap.pdf", "R-intro.pdf"))

## End(Not run)
```

v_outer

Vectorized Version of outer

Description

Vectorized [outer](#).

Usage

```
v_outer(x, FUN, ...)
```

S3 method for class 'list'

```
v_outer(x, FUN, ...)
```

S3 method for class 'data.frame'

```
v_outer(x, FUN, ...)
```

S3 method for class 'matrix'

```
v_outer(x, FUN, ...)
```

Arguments

x A matrix, dataframe or equal length list of vectors.
 FUN A vectorized function.
 ... Other arguments passed to the function supplied to FUN.

Value

Returns a matrix with the vectorized `outer` function.

Author(s)

Vincent Zoonekynd, eddi of stackoverflow.com, and Tyler Rinker <tyler.rinker@gmail.com>.

References

<https://stackoverflow.com/a/9917425/1000343>
<https://stackoverflow.com/q/23817341/1000343>

See Also

`outer`, `cor`

Examples

```
#|-----|
#|   SETTING UP VARIOUS FUNCTIONS THAT WILL BE USED   |
#|-----|
pooled_sd <- function(x, y) {
  n1 <- length(x)
  n2 <- length(y)
  s1 <- sd(x)
  s2 <- sd(y)
  sqrt(((n1-1)*s1 + (n2-1)*s2)/((n1-1) + (n2-1)))
}

## Effect Size: Cohen's d
cohens_d <- function(x, y) {
  (mean(y) - mean(x))/pooled_sd(x, y)
}

## Euclidean Distance
euc_dist <- function(x,y) sqrt(sum((x - y) ^ 2))

## Cosine similarity
cos_sim <- function(x, y) x %>% y / sqrt(x%%x * y%%y)

sum2 <- function(x, y) sum(x, y)
arbitrary <- function(x, y) round(sqrt(sum(x)) - sum(y), digits=1)
#-----#
```

```

## A data.frame
v_outer(mtcars, cor)
v_outer(mtcars, pooled_sd)
v_outer(mtcars[, 1:7], euc_dist)
v_outer(mtcars[, 1:7], sum2)
v_outer(mtcars[, 1:7], arbitrary)

## mtcars as a list
mtcars2 <- lapply(mtcars[, 1:7], "[")
v_outer(mtcars2, cor)
v_outer(mtcars2, cor, method = "spearman")
v_outer(mtcars2, pooled_sd)
v_outer(split(mtcars[["mpg"]], mtcars[["carb"]]), cohens_d)
v_outer(split(CO2[["uptake"]], CO2[["Plant"]]), cohens_d)
print(v_outer(mtcars[, 1:7], pooled_sd), digits = 1)
print(v_outer(mtcars[, 1:7], pooled_sd), digits = NULL)
v_outer(mtcars2, euc_dist)
v_outer(mtcars2, sum2)
v_outer(mtcars2, arbitrary)

## A matrix
mat <- matrix(rbinom(500, 0:1, .45), ncol=10)
v_outer(mat, cos_sim)
v_outer(mat, euc_dist)
v_outer(mat, arbitrary)

## Not run:
library(qdap)
wc3 <- function(x, y) sum(sapply(list(x, y), wc, byrow = FALSE))
L1 <- word_list(DATA$state, DATA$person)$cwl
(x <- v_outer(L1, wc3))
diag(x) <- (sapply(L1, length))
x

v_outer(with(DATA, wfm(state, person)), cos_sim)
with(DATA, Dissimilarity(state, person))

## End(Not run)

```

%l*%

Hash/Dictionary Lookup

Description

%l*% - A deprecated binary operator version of lookup. This will be removed in a subsequent version of **qdapTools**. Use %l% instead.

%ha% - A deprecated binary operator version of hash_lookup. This will be removed in a subsequent version of **qdapTools**. Use %h1% instead.

Usage

```
terms %l*% key.match
```

```
terms %ha% key
```

Arguments

terms	A vector of terms to undergo a lookup.
key.match	Takes one of the following: (1) a two column data.frame of a match key and reassignment column, (2) a named list of vectors (Note: if data.frame or named list supplied no key reassign needed) or (3) a single vector match key.
key	The hash key to use.

Index

- * **begin**
 - start_end, 23
- * **collapse**
 - list2df, 5
- * **docx**
 - read_docx, 17
- * **end**
 - start_end, 23
- * **frequency**
 - mtabulate, 14
- * **id**
 - id, 4
- * **list**
 - list2df, 5
- * **shift**
 - shift, 21
- * **start**
 - start_end, 23
- * **stop**
 - start_end, 23
- * **tabulate**
 - mtabulate, 14
- %ha% (%l*%), 27
- %hl+% (hash), 2
- %hl% (hash), 2
- %l+% (lookup), 10
- %l% (lookup), 10
- %lc+% (lookup), 10
- %lc% (lookup), 10
- %le+% (lookup_e), 12
- %le% (lookup_e), 12
- %l*%, 27

- cor, 26
- counts2list, 15
- counts2list (list2df), 5

- data.frame, 14, 15, 23
- df2matrix (list2df), 5

- environment, 3
- getwd, 19
- grep, 22
- grep1, 22

- hash, 2, 3, 11
- hash_e (hash), 2
- hash_look (hash), 2
- hms2sec, 4

- id, 4

- length, 4
- list, 6, 14, 15
- list2df, 5
- list_df2df (list2df), 5
- list_vect2df (list2df), 5
- loc_split, 8, 20, 22
- logical, 23
- lookup, 10, 13, 24
- lookup_e, 12

- matrix2df (list2df), 5
- matrix2long (list2df), 5
- mtabulate, 7, 14

- ncol, 4
- new.env, 13

- options, 19
- outer, 25, 26

- pad, 5, 15
- print.v_outer, 16

- read_docx, 17
- repo2github, 18, 18, 19
- run_split, 9, 20, 22

- sec2hms (hms2sec), 4

setDT, [3](#), [11](#)
shift, [21](#)
shift_left (shift), [21](#)
shift_right (shift), [21](#)
split_vector, [9](#), [20](#), [21](#)
sprintf, [15](#), [16](#)
start_end, [23](#)

tabulate, [14](#), [15](#)
text2color, [23](#)
times, [4](#)

url_dl, [24](#)

v_outer, [25](#)
vect2df (list2df), [5](#)
vect2list (list2df), [5](#)
vector, [14](#), [15](#)