

Package ‘rbtt’

May 9, 2026

Title Alternative Bootstrap-Based t-Test Aiming to Reduce Type-I Error for Non-Negative, Zero-Inflated Data

Version 0.1.0

Description Tu & Zhou (1999) <[doi:10.1002/\(SICI\)1097-0258\(19991030\)18:20%3C2749::AID-SIM195%3E3.0.CO;2-C](https://doi.org/10.1002/(SICI)1097-0258(19991030)18:20%3C2749::AID-SIM195%3E3.0.CO;2-C)> showed that comparing the means of populations whose data-generating distributions are non-negative with excess zero observations is a problem of great importance in the analysis of medical cost data. In the same study, Tu & Zhou discuss that it can be difficult to control type-I error rates of general-purpose statistical tests for comparing the means of these particular data sets. This package allows users to perform a modified bootstrap-based t-test that aims to better control type-I error rates in these situations.

Depends R (>= 3.3.0)

Imports stats, data.table, parallel

License GPL-3 | file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1.9000

NeedsCompilation no

Author Ian Waudby-Smith [aut, cre],
Pengfei Li [aut]

Maintainer Ian Waudby-Smith <iwaudbysmith@gmail.com>

Repository CRAN

Date/Publication 2017-09-17 17:15:22 UTC

Contents

rbtt	2
Index	4

 rbtt

Perform robust bootstrapped t-tests

Description

Perform robust bootstrapped two-sample t-tests that aim to better control type-I error rates when comparing means of non-negative distributions with excess zero observations.

Usage

```
rbtt(x, y, n.boot, n.cores = 1, method = "combined", conf.level = 0.95)
```

Arguments

x	a (non-empty) numeric vector of data values.
y	a (non-empty) numeric vector of data values.
n.boot	number of bootstrap resamples to perform
n.cores	number of cores to use for parallelization. Defaults to 1. If using Windows, set n.cores = 1.
method	Which robust bootstrapped t-test to perform. Set 'method=1' for a two-sample t-test under the equal variance assumption, 'method = 2' for a two-sample t-test without the equal variance assumption, and 'method = "both"' to perform both methods simultaneously.
conf.level	Desired confidence level for computing confidence intervals: a number between 0 and 1.

Value

A list (or two lists in the case of method = "combined") containing the following components:

statistic	the value of the t-statistic.
p.value	the p-value for the test.
conf.int	a bootstrap-based confidence interval for the difference in means.
estimate	the estimated difference in means.
null.value	the hypothesized value of the mean difference, zero.
alternative	a character string describing the alternative hypothesis.
method	a character string describing the type of two-sample bootstrapped t-test used
data.name	a character string giving the names of the data

Examples

```
x=rbinom(50,1,0.5)*rlnorm(50,0,1)
y=rbinom(150,1,0.3)*rlnorm(150,2,1)

rbtt(x, y, n.boot=999)

# Perform bootstrap resamples on 2 cores
rbtt(x, y, n.boot=999, n.cores=2)

# Use methods 1 or 2 individually
rbtt(x, y, n.boot = 999, method = 1)
rbtt(x, y, n.boot = 999, method = 2)

# Use a confidence level of 0.99
rbtt(x, y, n.boot = 999, conf.level = 0.99)
```

Index

rbtt, [2](#)