

# Package ‘CSOA’

October 1, 2025

**Type** Package

**Title** Calculate per-cell gene signature scores using cell set overlaps

**Version** 0.99.2

**Description** Cell Set Overlap Analysis (CSOA) is a tool for calculating per-cell gene signature scores in a scRNA-seq dataset. CSOA constructs a set for each gene in the signature, consisting of the cells that highly express the gene. Next, all overlaps of pairs of cell sets are computed, ranked, filtered and scored. The CSOA per-cell score is calculated by summing up all products of the overlap scores and the min-max-normalized expression of the two involved genes. CSOA can run on a Seurat object, a SingleCellExperiment object, a matrix and a dgCMatix.

**License** MIT + file LICENSE

**Imports** bayesbio, dplyr, ggeasy, ggforce, ggnewscale, ggplot2, ggraph, ggrepel, graphics, grDevices, kerntools, methods, qs, reshape2, Seurat, SeuratObject, SingleCellExperiment, SummarizedExperiment, sgof, spatstat.utils, stats, textshape, tidygraph, viridis, wesanderson

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Suggests** BiocStyle, knitr, patchwork, rmarkdown, scRNAseq, scuttle, stringr, testthat (>= 3.0.0)

**biocViews** Software, SingleCell, GeneSetEnrichment, GeneExpression

**VignetteBuilder** knitr

**URL** <https://github.com/andrei-stoica26/CSOA>

**BugReports** <https://github.com/andrei-stoica26/CSOA/issues>

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/CSOA>

**git\_branch** devel

**git\_last\_commit** c31b17a

**git\_last\_commit\_date** 2025-09-19

**Repository** Bioconductor 3.22

**Date/Publication** 2025-10-01

**Author** Andrei-Florian Stoica [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-5253-0826>>)

**Maintainer** Andrei-Florian Stoica <[andreistoica@foxmail.com](mailto:andreistoica@foxmail.com)>

## Contents

|                          |           |
|--------------------------|-----------|
| attachCellScores.default | 2         |
| basicHeatmap             | 3         |
| borderCoords             | 4         |
| breakWeakTies            | 5         |
| byCorrectDF              | 6         |
| cellDistribution         | 6         |
| cellSetsOverlaps         | 7         |
| circleCoords             | 7         |
| computePairScores        | 8         |
| computePCPairScores      | 8         |
| connectedComponents      | 9         |
| edgeLists.default        | 9         |
| expMat                   | 10        |
| featureWes               | 11        |
| geneRadialPlot           | 12        |
| generateOverlaps         | 13        |
| getPairs                 | 14        |
| networkPlot              | 14        |
| networkPlotDF            | 15        |
| overlapCutoffPlot        | 16        |
| overlapGenes             | 16        |
| overlapPairs             | 17        |
| percentileSets           | 17        |
| processOverlaps          | 18        |
| qGrab                    | 19        |
| runCSOA                  | 19        |
| scoreCells               | 21        |
| scoreCellsCore           | 22        |
| scoreModules             | 23        |
| wesBinaryGradient        | 24        |
| <b>Index</b>             | <b>25</b> |

---

attachCellScores.default

*Attach CSOA scores to object*

---

## Description

This function attaches the data frame of CSOA scores to the input object.

## Usage

```
## Default S3 method:
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'Seurat'
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'SingleCellExperiment'
```

```
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'matrix'
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'dgCMatrx'
attachCellScores(scObj, scoreDF, ...)

attachCellScores(scObj, ...)
```

### Arguments

|         |                                                                     |
|---------|---------------------------------------------------------------------|
| scObj   | A Seurat object, SingleCellExperiment object, or expression matrix. |
| scoreDF | Dataframe of CSOA scores                                            |
| ...     | Additional arguments.                                               |

### Details

If the input object is of the Seurat or SingleCellExpression class, it will be returned with added CSOA scores. Otherwise, a list containing the expression matrix and the CSOA scores data frame will be returned.

### Value

A Seurat object with CSOA scores added to metadata.

A SingleCellExperiment object with CSOA scores added to colData.

A list containing the expression matrix and the CSOA scores data frame.

A list containing the expression matrix and the CSOA scores data frame.

### Examples

```
library(Seurat)
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- sample(20, 8000, TRUE)
seuratObj <- CreateSeuratObject(mat)
seuratObj <- NormalizeData(seuratObj)
scores <- data.frame(CSOA = runif(300))
seuratObj <- attachCellScores(seuratObj, scores)
head(seuratObj$CSOA)
```

---

basicHeatmap

*Plot a simple heatmap*


---

### Description

This function plots a simple heatmap, with clustering but no dendograms.

**Usage**

```
basicHeatmap(
  mat,
  aesNames = c("x", "y", "Score"),
  title = "Heatmap",
  axisTextSize = 7,
  palType = "fillCont",
  wesPal = "Royal1",
  wesLow = 3,
  wesHigh = 2
)
```

**Arguments**

|              |                                                                                                                                                                                                                                  |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mat          | A matrix.                                                                                                                                                                                                                        |
| aesNames     | A character vector of length 3 representing the y, x and fill aes elements.                                                                                                                                                      |
| title        | Plot title.                                                                                                                                                                                                                      |
| axisTextSize | Axis text size.                                                                                                                                                                                                                  |
| palType      | Palette type: color or fill, continuous or discrete. Accepted values are 'colorCont', 'fillCont', 'colDis' and 'fillDis'. The function shows a warning and does not change the color scheme if a different value is passed here. |
| wesPal       | A wesanderson palette.                                                                                                                                                                                                           |
| wesLow       | Index of color marking low values.                                                                                                                                                                                               |
| wesHigh      | Index of color marking high values.                                                                                                                                                                                              |

**Value**

A ggplot object.

**Examples**

```
mat <- matrix(0, 10, 20)
mat[sample(length(mat), 50)] <- runif(50, max = 2.5)
basicHeatmap(mat)
```

---

|              |                                                                                   |
|--------------|-----------------------------------------------------------------------------------|
| borderCoords | <i>Find the coordinates where vertical or horizontal line intersects the hull</i> |
|--------------|-----------------------------------------------------------------------------------|

---

**Description**

This function finds the coordinates where vertical or horizontal line intersects the hull.

**Usage**

```
borderCoords(df, axis, axisIntersect)
```

**Arguments**

|               |                                                                                                  |
|---------------|--------------------------------------------------------------------------------------------------|
| df            | A four-column data frame representing segments.                                                  |
| axis          | An integer representing the axis intersected by the vertical or horizontal line, x (1) or y (2). |
| axisIntersect | The coordinate where the vertical or horizontal line intersects the relevant axis.               |

**Value**

A vector of size two representing the coordinates of the two intersection points between the vertical or horizontal line and the convex hull on the axis different from the input axis.

---

|               |                                                     |
|---------------|-----------------------------------------------------|
| breakWeakTies | <i>Remove overlap pairs with low Jaccard scores</i> |
|---------------|-----------------------------------------------------|

---

**Description**

This function iteratively removes all overlap pairs with neighbor Jaccard score below a fixed cutoff until no overlap pairs can be removed. Subsequently, overlap ranks are recalculated.

**Usage**

```
breakWeakTies(overlapDF, cutoff = 1/3, doConnComp = FALSE)
```

**Arguments**

|            |                                                                  |
|------------|------------------------------------------------------------------|
| overlapDF  | An overlap data frame.                                           |
| cutoff     | A cutoff used in the filtering of edges with low Jaccard scores. |
| doConnComp | Whether to calculate the connected components.                   |

**Details**

The functions removes overlaps for which the two involved genes record too few shared neighbors—genes whose cell set significantly overlaps with those of both overlap genes.

**Value**

An overlap data frame in which edges with low Jaccard scores have been removed.

**Examples**

```
overlapDF <- data.frame(gene1=paste0('G', c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
  gene2=paste0('G', c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
  ratio=runif(10, 2, 10),
  pval=runif(10, 0, 1e-10))
breakWeakTies(overlapDF, cutoff=0.1)
```

---

|             |                                                                                   |
|-------------|-----------------------------------------------------------------------------------|
| byCorrectDF | <i>Perform multiple testing correction and filtering with Benjamini-Yekutieli</i> |
|-------------|-----------------------------------------------------------------------------------|

---

### Description

This function performs the Benjamini-Yekutieli correction for multiple testing in a dataframe column of p-values and filters the data-frame based on p-values.

### Usage

```
byCorrectDF(df, pvalThr = 0.05, colStr = "pval")
```

### Arguments

|         |                                        |
|---------|----------------------------------------|
| df      | A dataframe with a column of p-values. |
| pvalThr | p-value threshold.                     |
| colStr  | Name of the column of p-values.        |

### Value

The data frame with Benjamini-Yekutieli-corrected p-values.

---

|                  |                                                       |
|------------------|-------------------------------------------------------|
| cellDistribution | <i>Show the distribution of cell sets among cells</i> |
|------------------|-------------------------------------------------------|

---

### Description

This function returns a logical matrix that shows the representation of cell sets among all cells.

### Usage

```
cellDistribution(cellSets, allCells)
```

### Arguments

|          |                                    |
|----------|------------------------------------|
| cellSets | A list of character vectors.       |
| allCells | Names of all cells in the dataset. |

### Value

A logical matrix with genes as rows and cells as columns.

### Examples

```
cellSets <- list(c('A', 'H', 'J'),
c('B', 'D', 'E', 'F', 'J'),
c('C', 'I', 'L'))
allCells <- LETTERS[seq(15)]
cellDistribution(cellSets, allCells)
```

---

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| cellSetsOverlaps | <i>Calculates the significance of overlaps of pairs of cells sets</i> |
|------------------|-----------------------------------------------------------------------|

---

**Description**

This function computes the statistical significance of overlaps of pairs of cell sets.

**Usage**

```
cellSetsOverlaps(cellSets, nCells, pairs = NULL)
```

**Arguments**

|          |                                                                                      |
|----------|--------------------------------------------------------------------------------------|
| cellSets | A list of character arrays.                                                          |
| nCells   | The total number of cells in the Seurat object.                                      |
| pairs    | Pairs of cell sets to be assessed. If NULL (as default), all pairs will be assessed. |

**Value**

A data frame listing statistics for all cell set overlaps: cell set sizes, recorded and expected shared cells, the recorded-over-expected ratio and the hypergeometric p-value.

**Examples**

```
cellSets <- list(G1 = c('A', 'H', 'J'),
  G2 = c('B', 'D', 'E', 'F', 'J'),
  G3 = c('C', 'I', 'L'))
cellSetsOverlaps(cellSets, 40)
```

---

|              |                                                                             |
|--------------|-----------------------------------------------------------------------------|
| circleCoords | <i>Store the radii of the circles and the corresponding number of edges</i> |
|--------------|-----------------------------------------------------------------------------|

---

**Description**

This function store the radii of the circles and the corresponding number of edges

**Usage**

```
circleCoords(geneCoordsDF, extraCircles = 0)
```

**Arguments**

|              |                                                                                           |
|--------------|-------------------------------------------------------------------------------------------|
| geneCoordsDF | Dataframe with gene coordinates                                                           |
| extraCircles | Number of circles drawn beyond those needed to include the points representing the genes. |

**Value**

A data frame containing the radius and the number of edges for each circle

---

|                   |                                           |
|-------------------|-------------------------------------------|
| computePairScores | <i>Compute aggregate gene pair scores</i> |
|-------------------|-------------------------------------------|

---

### Description

This function assesses the relative contribution of each gene pair to the CSOA score

### Usage

```
computePairScores(
  overlapDF,
  pcPairScores,
  pairFileName = "pairs",
  keepOverlapOrder = FALSE
)
```

### Arguments

|                  |                                                                                                                                 |
|------------------|---------------------------------------------------------------------------------------------------------------------------------|
| overlapDF        | An overlap data frame.                                                                                                          |
| pcPairScores     | A date frame of pair scores in each cell for each pair in the overlap data frame.                                               |
| pairFileName     | The name of the file where the pair data frame will be saved.                                                                   |
| keepOverlapOrder | Whether to keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. |

### Value

A data frame with overlap and pair scores and ranks.

---

|                     |                                          |
|---------------------|------------------------------------------|
| computePCPairScores | <i>Compute per-cell gene pair scores</i> |
|---------------------|------------------------------------------|

---

### Description

This function scores each gene pair corresponding to a top overlap in each cell.

### Usage

```
computePCPairScores(overlapDF, normExp)
```

### Arguments

|           |                                                                               |
|-----------|-------------------------------------------------------------------------------|
| overlapDF | An overlap data frame.                                                        |
| normExp   | A min-max normalized expression matrix of the genes involved in top overlaps. |

### Details

The score is calculated by multiplying the overlap score with the min-max-normalized expression of the two corresponding genes.



**Value**

A data frame with gene pairs as rows and cells as columns.

---

|                     |                                                                              |
|---------------------|------------------------------------------------------------------------------|
| connectedComponents | <i>Find the connected components of the graph determined by the overlaps</i> |
|---------------------|------------------------------------------------------------------------------|

---

**Description**

This function finds the connected components of the graph having the filtered overlaps as edges.

**Usage**

```
connectedComponents(df, colName = "component")
```

**Arguments**

|         |                                                      |
|---------|------------------------------------------------------|
| df      | A data frame with gene1 and gene2 columns.           |
| colName | Name of the connected components column to be added. |

**Value**

An overlap data frame with a column indicated the number of the connected component.

**Examples**

```
df <- data.frame(
  gene1 = paste('G', c(1, 2, 6, 7, 8, 9,
    11, 25, 32, 17, 18)),
  gene2 = paste('G', c(2, 8, 8, 8, 1, 25,
    32, 24, 24, 26, 26))
)
connectedComponents(df)
```

---

|                   |                                                                                     |
|-------------------|-------------------------------------------------------------------------------------|
| edgeLists.default | <i>Extract the edge list from overlap data frame or list of overlap data frames</i> |
|-------------------|-------------------------------------------------------------------------------------|

---

**Description**

This function creates a list of data frames with three columns: gene1, gene2 and group. If overlapObj is an overlap data frame, the groups correspond to the connected components. If it is a list of overlap data frames, the groups must be specified as groupNames.

**Usage**

```
## Default S3 method:
edgeLists(overlapObj, ...)

## S3 method for class 'data.frame'
edgeLists(overlapObj, ...)

## S3 method for class 'list'
edgeLists(overlapObj, groupNames, cutoff = NULL, ...)

edgeLists(overlapObj, ...)
```

**Arguments**

|            |                                                                                                                                 |
|------------|---------------------------------------------------------------------------------------------------------------------------------|
| overlapObj | An overlap data frame or list of overlap data frames.                                                                           |
| ...        | Additional arguments.                                                                                                           |
| groupNames | Names of groups. If provided, must be a vector of the same length as the list of overlap data frames                            |
| cutoff     | Number of retained edges from each overlap data frame after refiltering. If NULL (as default), no refiltering will be performed |

**Value**

A list of data frames.

---

|        |                                                        |
|--------|--------------------------------------------------------|
| expMat | <i>Extracts the data expression matrix from object</i> |
|--------|--------------------------------------------------------|

---

**Description**

This function extracts the data expression matrix from object as a non-sparse matrix. Selected genes can be specified as input.

**Usage**

```
expMat(scObj, ...)

## Default S3 method:
expMat(scObj, genes = NULL, ...)

## S3 method for class 'Seurat'
expMat(scObj, ...)

## S3 method for class 'SingleCellExperiment'
expMat(scObj, ...)

## S3 method for class 'dgCMatix'
expMat(scObj, ...)

## S3 method for class 'matrix'
expMat(scObj, ...)
```

**Arguments**

|       |                                                                              |
|-------|------------------------------------------------------------------------------|
| scObj | A Seurat object, SingleCellExperiment object, or expression matrix.          |
| ...   | Additional arguments.                                                        |
| genes | Genes retained in the expression matrix. If NULL, all genes will be retained |

**Value**

An expression matrix.

**Examples**

```
library(Seurat)
mat <- matrix(0, 6, 4)
mat[sample(length(mat), 7)] <- sample(3, 7, TRUE)
seuratObj <- CreateSeuratObject(counts = mat)
seuratObj <- NormalizeData(seuratObj)
expMat(seuratObj)
```

---

|            |                                                             |
|------------|-------------------------------------------------------------|
| featureWes | <i>A feature plot with a more distinctive color scheme.</i> |
|------------|-------------------------------------------------------------|

---

**Description**

This function customizes the appearance of `Seurat::FeaturePlot` for improved distinctiveness and aesthetics.

**Usage**

```
featureWes(
  seuratObj,
  feature,
  title = feature,
  idClass = NULL,
  labelSize = 3,
  titleSize = 12,
  wesPal = "Royal1",
  wesLow = 3,
  wesHigh = 2,
  ...
)
```

**Arguments**

|           |                                                                                     |
|-----------|-------------------------------------------------------------------------------------|
| seuratObj | A Seurat object.                                                                    |
| feature   | Seurat feature.                                                                     |
| title     | Plot title.                                                                         |
| idClass   | Column to be used for labelling. If NULL, no column-based labels will be generated. |
| labelSize | Size of labels. Ignored if idClass is NULL.                                         |

|           |                                                                   |
|-----------|-------------------------------------------------------------------|
| titleSize | Title size.                                                       |
| wesPal    | A wesanderson palette.                                            |
| wesLow    | Index of color marking low values.                                |
| wesHigh   | Index of color marking high values.                               |
| ...       | Additional arguments passed to <code>Seurat::FeaturePlot</code> . |

**Value**

A ggplot object.

**Examples**

```
library(Seurat)
mat <- matrix(0, 3000, 800)
mat[sample(length(mat), 90000)] <- sample(8, 90000, TRUE)
seuratObj <- CreateSeuratObject(counts = mat)
seuratObj <- FindVariableFeatures(seuratObj, nfeatures=200)
seuratObj <- NormalizeData(seuratObj)
seuratObj <- ScaleData(seuratObj)
seuratObj <- RunPCA(seuratObj, verbose=FALSE)
seuratObj <- RunUMAP(seuratObj, dims=1:20, verbose=FALSE)
featureWes(seuratObj, 'Feature3')
```

---

geneRadialPlot

*Radial plot for an overlap data frame*

---

**Description**

This function draws a radial plot for an overlap data frame to illustrate gene participation in top overlaps.

**Usage**

```
geneRadialPlot(
  overlapObj,
  groupLegendName = NULL,
  groupNames = NULL,
  cutoff = NULL,
  title = "Top overlap genes plot",
  extraCircles = 2
)
```

**Arguments**

|                 |                                                                                                      |
|-----------------|------------------------------------------------------------------------------------------------------|
| overlapObj      | An overlap data frame or list of overlap data frames.                                                |
| groupLegendName | The title of the group legend; if NULL, no groups will be distinguished.                             |
| groupNames      | Names of groups. If provided, must be a vector of the same length as the list of overlap data frames |

|              |                                                                                                                                 |
|--------------|---------------------------------------------------------------------------------------------------------------------------------|
| cutoff       | Number of retained edges from each overlap data frame after refiltering. If NULL (as default), no refiltering will be performed |
| title        | Plot title.                                                                                                                     |
| extraCircles | Number of circles drawn beyond those needed to include the points representing the genes.                                       |

### Details

The function can separate genes by groups. The groups can be, for instance, different gene sets, or different connected components of the same overlap data frame.

### Value

A ggplot object.

### Examples

```
edgesDF <- data.frame(gene1 = paste0('G', c(1, 2, 3, 4, 7, 8, 10,
11, 11, 10, 10, 10)),
gene2 = paste0('G', c(2, 5, 1, 8, 4, 9, 12,
13, 14, 13, 16, 14)))
edgesDF <- connectedComponents(edgesDF, 'group')
geneRadialPlot(edgesDF, 'component', extraCircles=1)
```

---

|                  |                                                       |
|------------------|-------------------------------------------------------|
| generateOverlaps | <i>Generate overlaps of cell sets for input genes</i> |
|------------------|-------------------------------------------------------|

---

### Description

This function constructs, for each gene in the expression matrix, a set of cells expressing the gene at or above the input percentile. Subsequently, overlaps of pairs of the constructed cell sets are assessed for statistical significance.

### Usage

```
generateOverlaps(geneSetExp, percentile = 90, pairs = NULL)
```

### Arguments

|            |                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------|
| geneSetExp | A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed. |
| percentile | A positive number under 100.                                                                                    |
| pairs      | Pairs of cell sets to be assessed. If NULL (as default), all pairs will be assessed.                            |

### Details

Wrapper around percentileSets and cellSetsOverlaps.

### Value

A data frame listing statistics for all cell set overlaps

**Examples**

```
mat <- matrix(0, 2000, 500)
rownames(mat) <- paste0('G', seq(2000))
colnames(mat) <- paste0('C', seq(500))
mat[sample(length(mat), 270000)] <- sample(50, 270000, TRUE)
mat <- mat[paste0('G', sample(2000, 5)), ]
generateOverlaps(mat)
```

---

getPairs

*Get all unordered pairs of two elements from a vector*


---

**Description**

This function returns all unordered pairs of two elements from a vector.

**Usage**

```
getPairs(v)
```

**Arguments**

v                      A vector.

**Value**

A list of vectors of length 2.

**Examples**

```
v <- c('ASD', 'VBN', 'HJKL')
getPairs(v)
```

---

networkPlot

*Plot the overlaps as a network*


---

**Description**

This function plots the graph of the overlap data frame, with genes as vertices and overlaps as edges.

**Usage**

```
networkPlot(
  overlapDF,
  title = "Top overlaps network plot",
  rankCol = "rank",
  edgeScale = 2,
  nodePointSize = 10,
  nodeTextSize = 2.3,
  ...
)
```

**Arguments**

|               |                                                 |
|---------------|-------------------------------------------------|
| overlapDF     | Overlap data frame.                             |
| title         | Plot title.                                     |
| rankCol       | Name of the rank column.                        |
| edgeScale     | Scaling factor used in generating edge weights. |
| nodePointSize | Point size of graph nodes.                      |
| nodeTextSize  | Text size of graph nodes.                       |
| ...           | Additional parameters passed to titlePlot.      |

**Value**

A network plot.

**Examples**

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 5, 6, 7, 17)),
  gene2 = paste0('G', c(2, 5, 8, 11, 11, 11)),
  rank = c(1, 1, 3, 3, 3, 3))
networkPlot(overlapDF)
```

---

|               |                                                    |
|---------------|----------------------------------------------------|
| networkPlotDF | <i>Prepare overlap data frame for network plot</i> |
|---------------|----------------------------------------------------|

---

**Description**

This function prepares a ranked and filtered overlap data frame for network plot.

**Usage**

```
networkPlotDF(overlapDF, rankCol = "rank", edgeScale = 2)
```

**Arguments**

|           |                                                 |
|-----------|-------------------------------------------------|
| overlapDF | Overlap data frame.                             |
| rankCol   | Name of the rank column.                        |
| edgeScale | Scaling factor used in generating edge weights. |

**Value**

A data frame ready to serve as input to networkPlot.

---

|                   |                                       |
|-------------------|---------------------------------------|
| overlapCutoffPlot | <i>Plot the selection of overlaps</i> |
|-------------------|---------------------------------------|

---

### Description

This function illustrates the process of selecting the overlap rank cutoff by plotting rank frequencies against ranks and showcasing the convex hull of the rank-frequency points.

### Usage

```
overlapCutoffPlot(overlapDF, title = "Overlap cutoff plot")
```

### Arguments

|           |                                                            |
|-----------|------------------------------------------------------------|
| overlapDF | Processed overlap data frame created with processOverlaps. |
| title     | Plot title.                                                |

### Value

A ggplot object.

### Examples

```
overlapDF <- data.frame(gene1=paste0('G', c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
  gene2=paste0('G', c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
  rank=c(1, 2, 3, 4, 4, 6, 7, 7, 7, 10))
overlapCutoffPlot(overlapDF)
```

---

|              |                                                 |
|--------------|-------------------------------------------------|
| overlapGenes | <i>Get all genes from an overlap data frame</i> |
|--------------|-------------------------------------------------|

---

### Description

This function gets all genes from an overlap data frame.

### Usage

```
overlapGenes(overlapDF)
```

### Arguments

|           |                     |
|-----------|---------------------|
| overlapDF | Overlap data frame. |
|-----------|---------------------|

### Value

A character vector of genes.



**Examples**

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 3)),
  gene1 = paste0('G', c(2, 7, 8)))
overlapGenes(overlapDF)
```

---

 overlapPairs

*Extract gene pairs from overlap data frame*


---

**Description**

This function extracts the gene pairs from an overlap data frame.

**Usage**

```
overlapPairs(overlapDF)
```

**Arguments**

overlapDF      Overlap data frame.

**Value**

A list of gene pairs.

**Examples**

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 3)),
  gene1 = paste0('G', c(2, 7, 8)))
overlapPairs(overlapDF)
```

---

 percentileSets

*Generates cell expressing input genes at an input percentile*


---

**Description**

This function constructs, for each gene in the expression matrix, a set of cells expressing the gene at or above the input percentile.

**Usage**

```
percentileSets(geneSetExp, percentile = 90)
```

**Arguments**

geneSetExp      A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.

percentile      A positive number under 100.

**Value**

A named list of character vectors of length equaling the number of input genes. Each vector stores the cells expressing the gene at or above the input percentile.

**Examples**

```
mat <- matrix(0, 1000, 500)
rownames(mat) <- paste0('G', seq(1000))
colnames(mat) <- paste0('C', seq(500))
mat[sample(length(mat), 70000)] <- sample(50, 70000, TRUE)
mat <- mat[paste0('G', sample(1000, 3)), ]
percentileSets(mat)
```

---

processOverlaps

*Process data frame of overlaps of cell sets*


---

**Description**

This function filters, ranks and scores previously generated overlaps of cell sets.

**Usage**

```
processOverlaps(
  overlapDF,
  pvalThr = 0.05,
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax")
)
```

**Arguments**

|               |                                                                                                                                      |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------|
| overlapDF     | Overlap data frame.                                                                                                                  |
| pvalThr       | P-value threshold used for initial filtering.                                                                                        |
| jaccardCutoff | A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed. |
| osMethod      | Method used to compute overlap scores. Options are "log" and "minmax".                                                               |

**Details**

Wrapper around `byCorrectDF`, `rankOverlaps`, `prepareFiltering`, `filterOverlaps` and `scoreOverlaps`. If `jaccardCutoff` is not NULL, it also calls `breakWeakTies` between `filterOverlaps` and `scoreOverlaps`.

**Value**

A data frame consisting of filtered, ranked and scored cell sets overlaps

**Examples**

```

overlapDF <- data.frame(gene1=paste0('G',
c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
gene2=paste0('G',
c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
ratio=runif(10, 2, 10),
pval=runif(10, 0, 1e-10))
processOverlaps(overlapDF)

```

---

|       |                                   |
|-------|-----------------------------------|
| qGrab | <i>Read and delete a .qs file</i> |
|-------|-----------------------------------|

---

**Description**

This functions reads a .qs file, deletes it, and returns its content.

**Usage**

```
qGrab(qsFile)
```

**Arguments**

|        |                             |
|--------|-----------------------------|
| qsFile | Name of .qs file with path. |
|--------|-----------------------------|

**Value**

The content of the .qs file.

**Examples**

```

library(qs)
qsave(c(1, 2, 3), 'temp.qs')
qGrab('temp.qs')

```

---

|         |                              |
|---------|------------------------------|
| runCSOA | <i>Run the CSOA pipeline</i> |
|---------|------------------------------|

---

**Description**

This function generates cell set overlaps for input gene sets based on percentiles of gene expression, computes the significance of these overlaps, ranks, filters and scores the overlaps, and builds a per-cell score by summing the products of overlap scores and the min-max-normalized expression of the corresponding pairs of genes.

**Usage**

```
runCSOA(
  scObj,
  geneSets,
  percentile = 90,
  pvalThr = 0.05,
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileTemplate = NULL,
  keepOverlapOrder = FALSE
)
```

**Arguments**

|                  |                                                                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| scObj            | A Seurat object, SingleCellExperiment object, or expression matrix.                                                                                       |
| geneSets         | Named list of character vectors of which each must contain at least two genes.                                                                            |
| percentile       | A positive number under 100.                                                                                                                              |
| pvalThr          | P-value threshold used for initial filtering.                                                                                                             |
| jaccardCutoff    | A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.                      |
| osMethod         | Method used to compute overlap scores. Options are "log" and "minmax".                                                                                    |
| pairFileTemplate | Character object used in the naming of the files where the pair data frames will be saved. Default is NULL (the pair data frames will not be saved).      |
| keepOverlapOrder | Keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. Ignored if pairFileTemplate is NULL. |

**Details**

#' @details Wrapper around expMat, generateOverlaps, scoreCellsMultiple and attachCellScores.

**Value**

An object of the same class as scObj with per-gene-set CSOA scores assigned for each cell.

**Examples**

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes <- paste0('G', seq(200))
mat[genes, 20:50] <- matrix(runif(200 * 31, min = 14, max = 15),
  nrow = 200, ncol = 31)
geneSet1 <- paste0('G', seq(1, 150))
geneSet2 <- paste0('G', seq(50, 200))
df <- runCSOA(mat, list(a = geneSet1, b = geneSet2))
head(df)
```

scoreCells

*Generate CSOA scores from overlap data frame and list of pairs***Description**

This function scores an overlap data frame using its associated list of pairs. The overlap data frame is split based on the overlaps corresponding to each gene set and scored, and the output is rejoined as a data frame.

**Usage**

```
scoreCells(
  geneSetExp,
  overlapDF,
  setPairs,
  geneSetNames,
  pvalThr = 0.05,
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileTemplate = NULL,
  keepOverlapOrder = FALSE
)
```

**Arguments**

|                  |                                                                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| geneSetExp       | A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.                                           |
| overlapDF        | Overlap data frame.                                                                                                                                       |
| setPairs         | A list of overlaps corresponding to each input gene set.                                                                                                  |
| geneSetNames     | Character vector of names of gene sets.                                                                                                                   |
| pvalThr          | P-value threshold used for initial filtering.                                                                                                             |
| jaccardCutoff    | A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.                      |
| osMethod         | Method used to compute overlap scores. Options are "log" and "minmax".                                                                                    |
| pairFileTemplate | Character object used in the naming of the files where the pair data frames will be saved. Default is NULL (the pair data frames will not be saved).      |
| keepOverlapOrder | Keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. Ignored if pairFileTemplate is NULL. |

**Details**

This function calls scoreCells to score each gene set data frame split from the full overlap data frame.

**Value**

A data frame whose columns correspond to the CSOA scores of the input gene sets.

## Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes <- paste0('G', seq(200))
mat[genes, 20:50] <- matrix(runif(200 * 31, min=14, max=15),
  nrow=200, ncol=31)
geneSet1 <- paste0('G', seq(1, 150))
geneSet2 <- paste0('G', seq(50, 200))
geneSets <- list(geneSet1, geneSet2)
geneSets <- lapply(geneSets, sort)
setPairs <- lapply(geneSets, getPairs)
pairs <- Reduce(union, setPairs)
genes <- union(geneSet1, geneSet2)
mat <- mat[genes, ]
overlapDF <- generateOverlaps(mat, pairs=pairs)
scoreDF <- scoreCells(mat, overlapDF, setPairs, c('set1', 'set2'))
head(scoreDF)
```

---

scoreCellsCore

*Generate CSOA scores from overlap data frame for a single gene set*

---

## Description

This function computes per-cell CSOA scores from overlap data frame for a single gene set.

## Usage

```
scoreCellsCore(
  geneSetExp,
  overlapDF,
  colStr = "CSOA",
  pvalThr = 0.05,
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileName = NULL,
  keepOverlapOrder = FALSE
)
```

## Arguments

|               |                                                                                                                                      |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------|
| geneSetExp    | A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.                      |
| overlapDF     | Overlap data frame.                                                                                                                  |
| colStr        | Name of column where CSOA scores will be stored.                                                                                     |
| pvalThr       | P-value threshold used for initial filtering.                                                                                        |
| jaccardCutoff | A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed. |
| osMethod      | Method used to compute overlap scores. Options are "log" and "minmax".                                                               |

pairFileName    The name of the file where the pair data frame will be saved.  
 keepOverlapOrder    Whether to keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order.

### Value

A data frame with a column corresponding to the CSOA scores.

---

|              |                                                                             |
|--------------|-----------------------------------------------------------------------------|
| scoreModules | <i>Run CSOA separately on the connected components of the overlap graph</i> |
|--------------|-----------------------------------------------------------------------------|

---

### Description

This function runs CSOA on the connected components of the graph having the filtered overlaps as edges.

### Usage

```
scoreModules(scObj, df, components, colStrTemplate = "CSOA_component", ...)
```

### Arguments

scObj            A Seurat object, SingleCellExperiment object, or expression matrix.  
 df              A data frame with gene1, gene2 and component columns.  
 components     Vector of connected components that will be scored  
 colStrTemplate Character used in the naming of the component gene sets.  
 ...            Additional parameters passed to runCSOAMultiple.

### Value

An object of the same class as scObj with CSOA scores corresponding to the genes defining each connected components assigned for each cell.

### Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes1 <- paste0('G', seq(100))
mat[genes1, 20:50] <- matrix(runif(100 * 31, min = 14, max = 15),
  nrow = 100, ncol = 31)
genes2 <- paste0('G', seq(101, 200))
mat[genes2, 70:100] <- matrix(runif(100 * 31, min = 14, max = 15),
  nrow = 100, ncol = 31)
genes <- union(genes1, genes2)
mat <- mat[genes, ]
overlapDF <- generateOverlaps(mat)
overlapDF <- processOverlaps(overlapDF)
overlapDF <- connectedComponents(overlapDF)
```

```
df <- scoreModules(mat, overlapDF, unique(overlapDF$component))[[2]]  
head(df)
```

---

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| wesBinaryGradient | <i>Adds a gradient color scale using two wesanderson colors</i> |
|-------------------|-----------------------------------------------------------------|

---

### Description

This function adds a gradient color scale to a ggplot object using a wesanderson palette, an index marking low values, and an index marking high values. The indices are used to select colors from the wesanderson palette of choice.

### Usage

```
wesBinaryGradient(p, palType, wesPal = "Royal1", wesLow = 3, wesHigh = 2, ...)
```

### Arguments

|         |                                                                                                                                                                                                                                   |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| p       | A ggplot object.                                                                                                                                                                                                                  |
| palType | Palette type: color or fill, continuous or discrete. Accepted values are 'color-Cont', 'fillCont', 'colDis' and 'fillDis'. The function shows a warning and does not change the color scheme if a different value is passed here. |
| wesPal  | A wesanderson palette.                                                                                                                                                                                                            |
| wesLow  | Index of color marking low values.                                                                                                                                                                                                |
| wesHigh | Index of color marking high values.                                                                                                                                                                                               |
| ...     | Arguments passed to other functions.                                                                                                                                                                                              |

### Value

A ggplot object with a new color scheme.



# Index

## \* internal

- [borderCoords](#), 4
- [byCorrectDF](#), 6
- [circleCoords](#), 7
- [computePairScores](#), 8
- [computePCPairScores](#), 8
- [edgeLists.default](#), 9
- [networkPlotDF](#), 15
- [scoreCellsCore](#), 22
- [wesBinaryGradient](#), 24

- [attachCellScores](#)
  - [\(attachCellScores.default\)](#), 2
- [attachCellScores.default](#), 2

- [basicHeatmap](#), 3
- [borderCoords](#), 4
- [breakWeakTies](#), 5
- [byCorrectDF](#), 6

- [cellDistribution](#), 6
- [cellSetsOverlaps](#), 7
- [circleCoords](#), 7
- [computePairScores](#), 8
- [computePCPairScores](#), 8
- [connectedComponents](#), 9

- [edgeLists \(edgeLists.default\)](#), 9
- [edgeLists.default](#), 9
- [expMat](#), 10

- [featureWes](#), 11

- [geneRadialPlot](#), 12
- [generateOverlaps](#), 13
- [getPairs](#), 14

- [networkPlot](#), 14
- [networkPlotDF](#), 15

- [overlapCutoffPlot](#), 16
- [overlapGenes](#), 16
- [overlapPairs](#), 17

- [percentileSets](#), 17

- [processOverlaps](#), 18

- [qGrab](#), 19

- [runCSOA](#), 19

- [scoreCells](#), 21
- [scoreCellsCore](#), 22
- [scoreModules](#), 23

- [wesBinaryGradient](#), 24