

# Package ‘chevreulPlot’

October 1, 2025

**Type** Package

**Title** Plots used in the chevreulPlot package

**Version** 1.1.2

**Description** Tools for plotting SingleCellExperiment objects in the chevreulPlot package. Includes functions for analysis and visualization of single-cell data. Supported by NIH grants R01CA137124 and R01EY026661 to David Cobrinik.

**License** MIT + file LICENSE

**URL** <https://github.com/whtns/chevreulPlot>,  
<https://whtns.github.io/chevreulPlot/>

**Date** 2024-11-17

**BugReports** <https://github.com/cobriniklab/chevreulPlot/issues>

**Depends** R (>= 4.5.0), SingleCellExperiment, chevreulProcess

**Imports** base, cluster, clustree, ComplexHeatmap (>= 2.5.4), circlize, dplyr, EnsDb.Hsapiens.v86, forcats, fs, ggplot2, grid, plotly, purrr, S4Vectors, scales, scater, scan, scuttle, stats, stringr, tibble, tidyr, utils, wigglyplotr (>= 1.13.1), tidyselect, patchwork

**Suggests** BiocStyle, knitr, RefManageR, rmarkdown, testthat (>= 3.0.0)

**VignetteBuilder** knitr

**Encoding** UTF-8

**LazyData** false

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.1

**biocViews** Coverage, RNASeq, Sequencing, Visualization, GeneExpression, Transcription, SingleCell, Transcriptomics, Normalization, Preprocessing, QualityControl, DimensionReduction, DataImport

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/chevreulPlot>

**git\_branch** devel

**git\_last\_commit** 3745106

**git\_last\_commit\_date** 2025-06-04

**Repository** Bioconductor 3.22  
**Date/Publication** 2025-10-01  
**Author** Kevin Stachelek [aut, cre] (ORCID:  
    <<https://orcid.org/0000-0003-2085-695X>>),  
    Bhavana Bhat [aut]  
**Maintainer** Kevin Stachelek <kevin.stachelek@gmail.com>

Contents

|                                       |           |
|---------------------------------------|-----------|
| chevreulPlot-package . . . . .        | 2         |
| cc.genes.cyclone . . . . .            | 3         |
| enframe_markers . . . . .             | 3         |
| ensembl_version . . . . .             | 4         |
| grch38 . . . . .                      | 4         |
| grch38_tx2gene . . . . .              | 5         |
| human_to_mouse_homologs . . . . .     | 6         |
| make_complex_heatmap . . . . .        | 6         |
| plotly_settings . . . . .             | 7         |
| plot_all_transcripts . . . . .        | 8         |
| plot_colData_histogram . . . . .      | 8         |
| plot_colData_on_embedding . . . . .   | 9         |
| plot_feature_on_embedding . . . . .   | 10        |
| plot_gene_coverage_by_var . . . . .   | 11        |
| plot_marker_features . . . . .        | 12        |
| plot_transcript_composition . . . . . | 13        |
| plot_violin . . . . .                 | 13        |
| small_example_dataset . . . . .       | 14        |
| tiny_sce . . . . .                    | 15        |
| <b>Index</b>                          | <b>16</b> |

---

|                      |                                                             |
|----------------------|-------------------------------------------------------------|
| chevreulPlot-package | <i>chevreulPlot: Plots used in the chevreulPlot package</i> |
|----------------------|-------------------------------------------------------------|

---

Description

Tools for plotting SingleCellExperiment objects in the chevreulPlot package. Includes functions for analysis and visualization of single-cell data. Supported by NIH grants R01CA137124 and R01EY026661 to David Cobrinik.

Author(s)

**Maintainer:** Kevin Stachelek <kevin.stachelek@gmail.com> (ORCID)

Authors:

- Bhavana Bhat <bhavanabhat29@gmail.com>

**See Also**

Useful links:

- <https://github.com/whtns/chevreulPlot>
- <https://whtns.github.io/chevreulPlot/>
- Report bugs at <https://github.com/cobriniklab/chevreulPlot/issues>

---

`cc.genes.cyclone`*Cyclone cell cycle pairs by symbol*

---

**Description**

cell cycle genes with paired expression represented by HGNC symbol

**Usage**

```
cc.genes.cyclone
```

**Format**

a list of dataframes with G1, G2, and S gene expression

**G1** G1 gene symbols

**G2** G2 gene symbols

**S** S gene symbols ...

**Source**

cyclone

---

`enframe_markers`*Enframe Cluster Markers*

---

**Description**

Enframe Cluster Markers

**Usage**

```
enframe_markers(tbl)
```

**Arguments**

`tbl` a tibble of marker genes

**Value**

a pivoted tibble of marker genes

---

|                 |                                       |
|-----------------|---------------------------------------|
| ensembl_version | <i>Ensembl version used for build</i> |
|-----------------|---------------------------------------|

---

**Description**

Ensembl version used for build

**Usage**

```
ensembl_version
```

**Format**

An object of class character of length 1.

**Source**

<http://www.ensembl.org/>

**Examples**

```
# ensembl_version
```

---

|        |                              |
|--------|------------------------------|
| grch38 | <i>Human annotation data</i> |
|--------|------------------------------|

---

**Description**

Human (*Homo sapiens*) annotations based on genome assembly GRCH38 from Ensembl.

**Usage**

```
grch38
```

**Format**

An object of class tbl\_df (inherits from tbl, data.frame) with 76062 rows and 9 columns.

**Details**

Variables:

- ensgene
- entrez
- symbol
- chr
- start
- end
- strand
- biotype
- description

**Source**

[http://ensembl.org/homo\\_sapiens](http://ensembl.org/homo_sapiens)

**Examples**

```
data("grch38")
head(grch38)
```

---

|                |                                   |
|----------------|-----------------------------------|
| grch38_tx2gene | <i>Human transcripts to genes</i> |
|----------------|-----------------------------------|

---

**Description**

Lookup table for converting Human (*Homo sapiens*) Ensembl transcript IDs to gene IDs based on genome assembly GRCH38 from Ensembl.

**Usage**

```
grch38_tx2gene
```

**Format**

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 277081 rows and 2 columns.

**Details**

Variables:

- `enstxp`
- `ensgene`

**Source**

[http://ensembl.org/homo\\_sapiens](http://ensembl.org/homo_sapiens)

**Examples**

```
data(grch38_tx2gene)
head(grch38_tx2gene)
```

---

human\_to\_mouse\_homologs

*Gene Homologs Between Human and Mouse*

---

### Description

Homologs drawn from Biomart

### Usage

human\_to\_mouse\_homologs

### Format

A data frame with 23188 rows and 2 columns

**HGNC.symbol** human gene symbols

**MGI.symbol** mouse gene symbols ...

### Source

bioMart

---

make\_complex\_heatmap    *Plot Annotated Complexheatmap from SingleCellExperiment object*

---

### Description

Plot Annotated Complexheatmap from SingleCellExperiment object

### Usage

```
make_complex_heatmap(
  object,
  features = NULL,
  group.by = "ident",
  cells = NULL,
  assayName = "logcounts",
  experiment = NULL,
  group.bar.height = 0.01,
  column_split = NULL,
  col_arrangement = "ward.D2",
  mm_col_dend = 30,
  ...
)
```

**Arguments**

|                  |                                                                                                               |
|------------------|---------------------------------------------------------------------------------------------------------------|
| object           | A SingleCellExperiment object                                                                                 |
| features         | Vector of features to plot. Features can come                                                                 |
| group.by         | Name of one or more metadata columns to annotate columns by (for example, orig.ident)                         |
| cells            | Cells to retain                                                                                               |
| assayName        | "counts" for raw data "scale.data" for log-normalized data                                                    |
| experiment       | experiment to display                                                                                         |
| group.bar.height | height for group bars                                                                                         |
| column_split     | whether to split columns by metadata value                                                                    |
| col_arrangement  | how to arrange columns whether with a dendrogram (Ward.D2, average, etc.) or exclusively by metadata category |
| mm_col_dend      | height of column dendrogram                                                                                   |
| ...              | additional arguments passed to Heatmap                                                                        |

**Value**

a complexheatmap

**Examples**

```
data("tiny_sce")
make_complex_heatmap(tiny_sce)
```

---

|                 |                        |
|-----------------|------------------------|
| plotly_settings | <i>Plotly settings</i> |
|-----------------|------------------------|

---

**Description**

Change settings of a plotly plot

**Usage**

```
plotly_settings(plotly_plot, width = 600, height = 700)
```

**Arguments**

|             |                      |
|-------------|----------------------|
| plotly_plot | A plotly plot        |
| width       | Default set to '600' |
| height      | Default set to '700' |

**Value**

a plotly plot with altered settings

---

plot\_all\_transcripts    *Plot All Transcripts*

---

### Description

plot expression all transcripts for an input gene superimposed on embedding

### Usage

```
plot_all_transcripts(
  object,
  features,
  embedding = "UMAP",
  from_gene = TRUE,
  ...
)
```

### Arguments

|           |                                                          |
|-----------|----------------------------------------------------------|
| object    | A object                                                 |
| features  | gene or vector of transcripts                            |
| embedding | umap                                                     |
| from_gene | whether to look up transcripts for an input gene         |
| ...       | additional arguments passed to plot_feature_on_embedding |

### Value

a list of embedding plots colored by a feature of interest

### Examples

```
data("tiny_sce")
plot_all_transcripts(tiny_sce, "NRL", from_gene = TRUE)
```

---

plot\_colData\_histogram    *Plot Read Count*

---

### Description

Draw a box plot for read count data of a metadata variable

### Usage

```
plot_colData_histogram(
  object,
  group_by = NULL,
  fill_by = NULL,
  yscale = "linear",
  return_plotly = FALSE
)
```

**Arguments**

|               |                                                        |
|---------------|--------------------------------------------------------|
| object        | A object                                               |
| group_by      | Metadata variable to plot. Default set to "nCount_RNA" |
| fill_by       | Variable to color bins by. Default set to "batch"      |
| yscale        | Scale of y axis. Default set to "linear"               |
| return_plotly | whether to return an interactive plotly plot           |

**Value**

a histogram of read counts

**Examples**

```
data(small_example_dataset)
small_example_dataset <- sce_calcn(small_example_dataset)
# static plot
plot_colData_histogram((small_example_dataset), return_plotly = FALSE)
```

---

plot\_colData\_on\_embedding

*Plot Metadata Variables*

---

**Description**

Plots static or interactive plot where each point represents a cell metadata variable whose position on the map depends on cell embeddings determined by the reduction technique used

**Usage**

```
plot_colData_on_embedding(
  object,
  group = "batch",
  embedding = "UMAP",
  dims = c(1, 2),
  highlight = NULL,
  return_plotly = FALSE,
  ...
)
```

**Arguments**

|               |                                                                |
|---------------|----------------------------------------------------------------|
| object        | A SingleCellExperiment object                                  |
| group         | Name of one or more metadata columns to group (color) cells by |
| embedding     | The dimensional reduction technique to be used                 |
| dims          | Dimensions to plot, must be a two-length numeric vector        |
| highlight     | A list of vectors of cells to highlight                        |
| return_plotly | Convert plot to interactive web-based graph                    |
| ...           | extra parameters passed to ggplot                              |

**Value**

a ggplot

**Examples**

```
data(small_example_dataset)

# static mode
plot_colData_on_embedding(small_example_dataset, "Mutation_Status", return_plotly = FALSE)
```

---

```
plot_feature_on_embedding
      Plot Feature
```

---

**Description**

Plots gene or transcript expression overlaid on a given embedding.

**Usage**

```
plot_feature_on_embedding(
  object,
  embedding = c("UMAP", "PCA", "TSNE"),
  features,
  dims = c(1, 2),
  return_plotly = FALSE,
  ...
)
```

**Arguments**

|               |                                                         |
|---------------|---------------------------------------------------------|
| object        | A SingleCellExperiment object                           |
| embedding     | Dimensional reduction technique to be used              |
| features      | Feature to plot                                         |
| dims          | Dimensions to plot, must be a two-length numeric vector |
| return_plotly | return plotly object                                    |
| ...           | additional arguments passed to plotReduceDim            |

**Value**

an embedding colored by a feature of interest

**Examples**

```
data(small_example_dataset)
plot_feature_on_embedding(small_example_dataset, embedding = "UMAP",
  features = "Gene_0001")
```

---

plot\_gene\_coverage\_by\_var

*Plot BigWig Coverage for Genes of Interest by a Given Variable*


---

## Description

Plot BigWig coverage for genes of interest colored by a given variable

## Usage

```
plot_gene_coverage_by_var(
  genes_of_interest = "NRL",
  cell_metadata,
  bigwig_tbl,
  group_by = "batch",
  values_of_interest = NULL,
  organism = c("human", "mouse"),
  edb = NULL,
  heights = c(3, 1),
  scale_y = "log10",
  reverse_x = FALSE,
  start = NULL,
  end = NULL,
  summarize_transcripts = FALSE,
  ...
)
```

## Arguments

|                       |                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| genes_of_interest     | Gene of interest                                                                                                                                  |
| cell_metadata         | a dataframe with cell metadata from object                                                                                                        |
| bigwig_tbl            | a tibble with colnames "name", "bigWig", and "sample_id" matching the file-name, absolute path, and sample name of each cell in the cell_metadata |
| group_by              | Variable to color by                                                                                                                              |
| values_of_interest    | values of interest                                                                                                                                |
| organism              | human (default) or mouse                                                                                                                          |
| edb                   | ensembl db object                                                                                                                                 |
| heights               | The heights of each row in the grid of plot                                                                                                       |
| scale_y               | whether to scale coverage                                                                                                                         |
| reverse_x             | whether to reverse x axis                                                                                                                         |
| start                 | start coordinates                                                                                                                                 |
| end                   | end coordinates                                                                                                                                   |
| summarize_transcripts | whether to summarize transcript counts                                                                                                            |
| ...                   | extra arguments passed to plotCoverageFromEnsemblDb                                                                                               |

**Value**

a ggplot with coverage faceted by group\_by

---

plot\_marker\_features    *Plot Cluster Marker Genes*

---

**Description**

Plot a dot plot of n marker features grouped by cell metadata available methods are wilcoxon rank-sum test

**Usage**

```
plot_marker_features(
  object,
  group_by = "batch",
  num_markers = 5,
  selected_values = NULL,
  return_plotly = FALSE,
  marker_method = "wilcox",
  experiment = "gene",
  hide_technical = NULL,
  unique_markers = FALSE,
  p_val_cutoff = 1,
  ...
)
```

**Arguments**

|                 |                                                     |
|-----------------|-----------------------------------------------------|
| object          | a object                                            |
| group_by        | the metadata variable from which to pick clusters   |
| num_markers     | default is 5                                        |
| selected_values | selected values to display                          |
| return_plotly   | whether to return an interactive plotly plot        |
| marker_method   | "wilcox"                                            |
| experiment      | experiment to plot default gene                     |
| hide_technical  | whether to exclude mitochondrial or ribosomal genes |
| unique_markers  | whether to plot only unique marker genes for group  |
| p_val_cutoff    | cutoff for p value display                          |
| ...             | extra parameters passed to ggplot2                  |

**Value**

a ggplot with marker genes from group\_by

**Examples**

```
data(small_example_dataset)
plot_marker_features(small_example_dataset, group_by = "gene_snn_res.1")
```

---

|                             |                                    |
|-----------------------------|------------------------------------|
| plot_transcript_composition | <i>Plot Transcript Composition</i> |
|-----------------------------|------------------------------------|

---

**Description**

plot the proportion of reads of a given gene map to each transcript

**Usage**

```
plot_transcript_composition(  
  object,  
  gene_symbol,  
  group.by = "batch",  
  standardize = FALSE,  
  drop_zero = FALSE  
)
```

**Arguments**

|             |                                                                                       |
|-------------|---------------------------------------------------------------------------------------|
| object      | A object                                                                              |
| gene_symbol | Gene symbol of gene of interest                                                       |
| group.by    | Name of one or more metadata columns to annotate columns by (for example, orig.ident) |
| standardize | whether to standardize values                                                         |
| drop_zero   | Drop zero values                                                                      |

**Value**

a stacked barplot of transcript counts

**Examples**

```
data(tiny_sce)  
plot_transcript_composition(tiny_sce, "NRL")
```

---

|             |                         |
|-------------|-------------------------|
| plot_violin | <i>Plot Violin plot</i> |
|-------------|-------------------------|

---

**Description**

Plots a Violin plot of a single data (gene expression, metrics, etc.) grouped by a metadata variable

**Usage**

```
plot_violin(
  object,
  group_by = "batch",
  plot_vals = NULL,
  features = "NRL",
  experiment = "gene",
  ...
)
```

**Arguments**

|            |                                                          |
|------------|----------------------------------------------------------|
| object     | A SingleCellExperiment object                            |
| group_by   | Variable to group (color) cells by                       |
| plot_vals  | plot values                                              |
| features   | Features to plot                                         |
| experiment | Name of experiment to use, defaults to active experiment |
| ...        | extra parameters passed to ggplot2                       |

**Value**

a violin plot

**Examples**

```
data("tiny_sce")
plot_violin(tiny_sce, "Prep.Method", features = "NRL")
```

---

small\_example\_dataset *Small example SingleCellExperiment*

---

**Description**

created with `scuttle::mockSCE`

**Usage**

```
small_example_dataset
```

**Format**

An SCE with 200 cells and 1000 genes

**Source**

`scuttle::mockSCE`

---

tiny\_sce

---

*Tiny example SingleCellExperiment***Description**

subset to only NRL from chevreuldata::human\_gene\_transcript\_sce()

**Usage**

tiny\_sce

**Format**

An SCE with only expression of NRL gene and NRL transcripts

**Source**

chevreuldata::human\_gene\_transcript\_sce()

# Index

## \* datasets

- cc.genes.cyclone, [3](#)
- ensembl\_version, [4](#)
- grch38, [4](#)
- grch38\_tx2gene, [5](#)
- human\_to\_mouse\_homologs, [6](#)
- small\_example\_dataset, [14](#)
- tiny\_sce, [15](#)

## \* internal

- chevreulPlot-package, [2](#)

- cc.genes.cyclone, [3](#)
- chevreulPlot (chevreulPlot-package), [2](#)
- chevreulPlot-package, [2](#)

- enframe\_markers, [3](#)
- ensembl\_version, [4](#)

- grch38, [4](#)
- grch38\_tx2gene, [5](#)

- human\_to\_mouse\_homologs, [6](#)

- make\_complex\_heatmap, [6](#)

- plot\_all\_transcripts, [8](#)
- plot\_colData\_histogram, [8](#)
- plot\_colData\_on\_embedding, [9](#)
- plot\_feature\_on\_embedding, [10](#)
- plot\_gene\_coverage\_by\_var, [11](#)
- plot\_marker\_features, [12](#)
- plot\_transcript\_composition, [13](#)
- plot\_violin, [13](#)
- plotly\_settings, [7](#)

- small\_example\_dataset, [14](#)

- tiny\_sce, [15](#)