

# Package ‘interactiveDisplayBase’

October 2, 2025

**Type** Package

**Title** Base package for enabling powerful shiny web displays of  
Bioconductor objects

**Version** 1.47.1

**Date** 2021-07-30

**Imports** shiny, DT

**Depends** R (>= 2.10), methods, BiocGenerics

**Suggests** knitr, markdown

**Enhances** rstudioapi

**Description** The interactiveDisplayBase package contains the basic  
methods needed to generate interactive Shiny based display  
methods for Bioconductor objects.

**License** Artistic-2.0

**Collate** interactiveDisplayBase.R dataframe.R dot\_runApp.R zzz.R

**VignetteBuilder** knitr

**biocViews** GO, GeneExpression, Microarray, Sequencing, Classification,  
Network, QualityControl, Visualization, Visualization,  
Genetics, DataRepresentation, GUI, AnnotationData, ShinyApps

**RoxygenNote** 7.1.1

**PackageStatus** Deprecated

**git\_url** <https://git.bioconductor.org/packages/interactiveDisplayBase>

**git\_branch** devel

**git\_last\_commit** 3d6db31

**git\_last\_commit\_date** 2025-06-18

**Repository** Bioconductor 3.22

**Date/Publication** 2025-10-01

**Author** Bioconductor Package Maintainer [cre],  
Shawn Balcome [aut],  
Marc Carlson [ctb],  
Marcel Ramos [ctb]

**Maintainer** Bioconductor Package Maintainer <maintainer@bioconductor.org>

## Contents

|                   |          |
|-------------------|----------|
| .runApp . . . . . | 2        |
| display . . . . . | 3        |
| <b>Index</b>      | <b>4</b> |

---

|         |                                                            |
|---------|------------------------------------------------------------|
| .runApp | <i>Run a shiny app, capturing results to the R session</i> |
|---------|------------------------------------------------------------|

---

## Description

This utility function launches a shiny visualization application, either in the RStudio viewer pane (if run under RStudio) or in the browser.

## Usage

```
.runApp(app, ...)
```

## Arguments

|     |                                                       |
|-----|-------------------------------------------------------|
| app | The shiny application definition, see ?shiny::runApp. |
| ... | additional arguments passed to shiny::runApp().       |

## Value

The return value of shiny::runApp.

## Author(s)

Martin Morgan

## Examples

```
if (interactive()) {
  require(shiny)

  app <- list(
    ui = fluidPage(
      title="Who Am I?",
      sidebarLayout(
        position="left",
        sidebarPanel(
          h1("Your name"),
          textInput("your_name", "Your name?", "Anonymous"),
          actionButton("done", "Done")),
        mainPanel(
          "Hi", textOutput("your_name", inline=TRUE))
      )),
    server = function(input, output) {
      output$your_name <- renderText(input$your_name)
      observe({
        if (input$done > 0)
```

```
        isolate(stopApp(returnValue = input$your_name))
      })
    })
  .runApp(app)
}
```

---

**display***display: Open a Shiny application for a Bioconductor object*

---

**Description**

This opens a shiny visualization application in the browser based on the submitted object.

**Usage**

```
display(object, ...)
```

**Arguments**

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| <code>object</code> | data object to display                                    |
| <code>...</code>    | additional arguments passed to methods; currently unused. |

**Value**

Usually some variation of the initial input object, but it may be altered by the display widget (subset for example).

**Author(s)**

Shawn Balcome and Marc Carlson

**See Also**

<http://bioconductor.org/packages/2.13/bioc/html/interactiveDisplayBase.html>

**Examples**

```
if(interactive()) {

  ## draw a data.frame
  display(mtcars)

  ## subset a data.frame:
  mtcars2 <- display(mtcars)

}
```

# Index

\* **manip, internal**

[.runApp, 2](#)

\* **methods**

[display, 3](#)

[.runApp, 2](#)

[display, 3](#)

[display, ANY-method \(display\), 3](#)

[display, data.frame-method \(display\), 3](#)

[display, missing-method \(display\), 3](#)