

Package ‘RJMCMCNucleosomes’

November 19, 2025

Version 1.35.0

Date 2025-07-28

Title Bayesian hierarchical model for genome-wide nucleosome positioning with high-throughput short-read data (MNase-Seq)

Description This package does nucleosome positioning using informative Multinomial-Dirichlet prior in a t-mixture with reversible jump estimation of nucleosome positions for genome-wide profiling.

Depends R (≥ 3.5), IRanges, GenomicRanges

Imports Rcpp ($\geq 0.12.5$), consensusSeeker, BiocGenerics, Seqinfo, S4Vectors ($\geq 0.23.10$), BiocParallel, stats, graphics, methods, grDevices

Suggests BiocStyle, knitr, rmarkdown, nucleoSim, RUnit

LinkingTo Rcpp

SystemRequirements Rcpp

Encoding UTF-8

License Artistic-2.0

URL <https://github.com/ArnaudDroitLab/RJMCMCNucleosomes>

BugReports <https://github.com/ArnaudDroitLab/RJMCMCNucleosomes/issues>

VignetteBuilder knitr

biocViews BiologicalQuestion, ChIPSeq, NucleosomePositioning, Software, StatisticalMethod, Bayesian, Sequencing, Coverage

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/RJMCMCNucleosomes>

git_branch devel

git_last_commit e3d8d0f

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2025-11-18

Author Pascal Belleau [aut],
 Rawane Samb [aut],
 Astrid Deschênes [cre, aut],
 Khader Khadraoui [aut],
 Lajmi Lakhel-Chaieb [aut],
 Arnaud Droit [aut]

Maintainer Astrid Deschênes <adeschen@hotmail.com>

Contents

RJMCMCNucleosomes-package	2
mergeAllRDSFiles	3
mergeAllRDSFilesFromDirectory	4
mergeRDSFiles	5
plotNucleosomes	6
postMerge	7
postTreatment	9
print.rjmcNucleosomes	10
print.rjmcNucleosomesBeforeAndAfterPostTreatment	11
print.rjmcNucleosomesMerge	12
reads_demo_01	13
reads_demo_02	13
rjmc	14
rjmcCHR	16
rjmcNucleo	18
RJCMC_result	20
runCHR	21
segmentation	23
syntheticNucleosomeReads	24
validateDirectoryParameters	25
validatePlotNucleosomesParameters	25
validatePrepMergeParameters	27
validateRDSFilesParameters	28
validateRJCMCParameters	29
validateSegmentationParameters	30

Index	32
--------------	-----------

RJCMCNucleosomes-package

RJCMCNucleosomes: Bayesian hierarchical model for genome-wide nucleosome positioning with high-throughput short-read data (MNase-Seq)

Description

This package does nucleosome positioning using informative Multinomial-Dirichlet prior in a t-mixture with reversible jump estimation of nucleosome positions for genome-wide profiling.

Author(s)

Pascal Belleau, Rawane Samb, Astrid Deschênes, Khader Khadraoui, Lajmi Lakhal and Arnaud Droit

Maintainer: Astrid Deschenes <adeschen@hotmail.com>

See Also

- [rjmc](#) for profiling of nucleosome positions for a segment
- [rjmcCHR](#) for profiling of nucleosome positions for a large region. The function will take care of splitting and merging.
- [segmentation](#) for splitting a GRanges containing reads in a list of smaller segments for the rjmc function.
- [postTreatment](#) for merging closely positioned nucleosomes
- [mergeRDSFiles](#) for merging nucleosome information from selected RDS files.
- [plotNucleosomes](#) for generating a graph containing the nucleosome positions and the read coverage.

mergeAllRDSFiles	<i>Merge nucleosome information</i>
------------------	-------------------------------------

Description

Merge nucleosome information present in multiple RDS files.

Usage

```
mergeAllRDSFiles(arrayOfFiles)
```

Arguments

arrayOfFiles	a array, the name of each file that must be used to merge nucleosome information.
--------------	---

Value

a list of class "rjmcNucleosomesMerge" containing:

- k a integer, the number of nucleosomes.
- mu a GRanges containing the positions of the nucleosomes.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```
## Loading two files containing nucleosomes informations for two sections of
## the same chromosome
file_1 <- dir(system.file("extdata", package = "RJMCMCNucleosomes"),
              pattern = "RJMCMC_seg_01.RDS",
              full.names = TRUE)

file_2 <- dir(system.file("extdata", package = "RJMCMCNucleosomes"),
              pattern = "RJMCMC_seg_02.RDS",
              full.names = TRUE)

## Merging nucleosomes informations from the two files
result <- RJMCMCNucleosomes::mergeAllRDSFiles(c(file_1, file_2))
```

mergeAllRDSFilesFromDirectory

Merge nucleosome information from all RDS files present in a same directory. Beware that only nucleosome information from same chromosome should be merged together.

Description

Merge nucleosome information, from all RDS files present in a same directory, into one object of class "rjmcNucleosomesMerge".

Usage

```
mergeAllRDSFilesFromDirectory(directory)
```

Arguments

directory	a character, the name of the directory (relative or absolute path) containing RDS files. The RDS files must contain R object of class "rjmcNucleosomes" or "rjmcNucleosomesMerge".
-----------	--

Value

a list of class "rjmcNucleosomesMerge" containing:

- k a integer, the number of nucleosomes.
- mu a GRanges containing the positions of the nucleosomes.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```
## Use a directory present in the RJMCMC package
directoryWithRDSFiles <- system.file("extdata",
package = "RJMCMCNucleosomes")

## Merge nucleosomes info from RDS files present in directory
## It is assumed that all files present in the directory are nucleosomes
## result for the same chromosome
result <- mergeAllRDSFilesFromDirectory(directoryWithRDSFiles)

## Print the number and the position of the nucleosomes
result$k
result$mu

## Class of the output object
class(result)
```

mergeRDSFiles

Merge nucleosome information from selected RDS files.

Description

Merge nucleosome information present in RDS files into one object of class "rjmcNucleosomesMerge".

Usage

```
mergeRDSFiles(RDSFiles)
```

Arguments

RDSFiles a array, the names of all RDS used to merge nucleosome information. The files must contain R object of class "rjmcNucleosomes" or "rjmcNucleosomesMerge".

Value

a list of class "rjmcNucleosomesMerge" containing:

- k a integer, the number of nucleosomes.
- mu a GRanges containing the positions of the nucleosomes.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```
## Use RDS files present in the RJMCMC package
RDSFiles <- dir(system.file("extdata", package = "RJMCMCNucleosomes"),
full.names = TRUE, pattern = "*.RDS")

## Merge nucleosomes info from RDS files present in directory
result <- mergeRDSFiles(RDSFiles)

## Print the number and the position of the nucleosomes
result$k
result$mu

## Class of the output object
class(result)
```

plotNucleosomes

Generate a graph of nucleosome positions with read coverage

Description

Generate a graph for a GRanges or a GRangesList of nucleosome positions. In presence of only one prediction (with multiples nucleosome positions), a GRanges is used. In presence of more than one predictions (as example, before and after post-treatment or results from different software), a GRangesList with one entry per prediction is used. All predictions must have been obtained using the same reads.

Usage

```
plotNucleosomes(nucleosomePositions, reads, seqName = NULL,
xlab = "position", ylab = "coverage", names = NULL)
```

Arguments

nucleosomePositions

a GRanges or a GRangesList containing the nucleosome positions for one or multiples predictions obtained using the same reads. In presence of only one prediction (with multiples nucleosome positions), a GRanges is used. In presence of more than one predictions (as example, before and after post-treatment or results from different software), a GRangesList with one entry per prediction is used.

reads

a GRanges containing forward and reverse reads. The GRanges should contain at least one read.

seqName	a character string containing the label of the chromosome, present in the GRanges object, that will be used. The NULL value is accepted when only one seqname is present in the GRanges; the only seqname present will be used. Default: NULL.
xlab	a character string containing the label of the x-axis.
ylab	a character string containing the label of the y-axis.
names	a vector of a character string containing the label of each prediction set. The vector must be the same length of the nucleosomePositions list or 1 in presence of a vector. When NULL, the name of the elements of the list are used or the string "Nucleosome" for a vector are used. Default: NULL.

Value

a graph containing the nucleosome positions and the read coverage

Author(s)

Astrid Deschenes

Examples

```
## Load reads dataset
data(reads_demo_01)

## Run RJMCMC method
result <- rjmc(mreads = reads_demo_01,
  seqName = "chr_SYNTHETIC",
  nbrIterations = 4000, lambda = 2, kMax = 30,
  minInterval = 146, maxInterval = 292, minReads = 5,
  vSeed = 10213)

## Create graph using the synthetic map
plotNucleosomes(nucleosomePositions = result$mu, seqName = "chr_SYNTHETIC",
  reads = reads_demo_01)
```

postMerge	<i>A internal post treatment function to merge closely positioned nucleosomes, from the same chromosome, identified by the <code>rjmc</code> function</i>
-----------	---

Description

A internal helper function which merges closely positioned nucleosomes to rectify the over splitting and provide a more conservative approach. Beware that each chromosome must be treated separately. The function uses the Bioconductor package consensusSeeker to group closely positioned nucleosomes.

Usage

```
postMerge(reads, resultRJCMC, extendingSize, chrLength, minReads = 5,
          seqName = NULL)
```

Arguments

<code>reads</code>	a GRanges containing all forward and reverse reads. The start positions of both reads are going to be used for the analysis. Beware that the start position of a reverse read is always higher than the end position.
<code>resultRJCMC</code>	an object of class 'rjcmcNucleosomes' or 'rjcmcNucleosomesMerge' containing informations about nucleosomes.
<code>extendingSize</code>	a positive numeric or a positive integer indicating the size of the consensus region used to group closely positioned nucleosomes. The minimum size of the consensus region is equal to twice the value of the <code>extendingSize</code> parameter. The numeric will be treated as an integer.
<code>chrLength</code>	a positive numeric or a positive integer indicating the length of the current chromosome. The length of the chromosome is used to ensure that the consensus positions are all located inside the chromosome.
<code>minReads</code>	a positive integer or numeric, the minimum number of reads in a potential candidate region. Non-integer values of <code>minReads</code> will be casted to integer and truncated towards zero. Default: 5.

Value

a array of numeric, the updated values of the nucleosome positions. When no nucleosome is present, NULL is returned.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```
## Loading dataset
data(RJCMC_result)
data(reads_demo_02)

## Results before post-treatment
RJCMC_result$mu

## Post-treatment function which merged closely positioned nucleosomes
postResult <- RJCMCNucleosomes:::postMerge(reads = reads_demo_02,
                                           resultRJCMC = RJCMC_result,
                                           extendingSize = 80, chrLength = 73500)

## Results after post-treatment
postResult
```

postTreatment	<i>A post-treatment function to merge closely positioned nucleosomes, from the same chromosome, identified by the rjmcnc function.</i>
---------------	--

Description

A helper function which merges closely positioned nucleosomes to rectify the over splitting and provide a more conservative approach. Beware that each chromosome must be treated separately.

Usage

```
postTreatment(reads, seqName = NULL, resultRJMCNC, extendingSize = 74L,  
              chrLength)
```

Arguments

reads	a GRanges containing forward and reverse reads. Beware that the start position of a reverse read is always higher than the end position.
seqName	a character string containing the label of the chromosome, present in the GRanges object, that will be used. The NULL value is accepted when only one seqname is present in the GRanges; the only seqname present will be used. Default: NULL.
resultRJMCNC	an object of class "rjmcncNucleosomes" or "rjmcncNucleosomesMerge", the information about nucleosome positioning for an entire chromosome or a region that must be treated as one unit.
extendingSize	a positive numeric or a positive integer indicating the size of the consensus region used to group closely positioned nucleosomes. The minimum size of the consensus region is equal to twice the value of the extendingSize parameter. The numeric will be treated as an integer. Default: 74.
chrLength	a positive numeric or a positive integer indicating the length of the current chromosome. The length of the chromosome is used to ensure that the consensus positions are all located inside the chromosome.

Value

a GRanges, the updated nucleosome positions. When no nucleosome is present, NULL is returned.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```
## Loading dataset  
data(reads_demo_02)  
  
## Nucleosome positioning, running both merge and split functions
```

```
result <- rjmc(reads = reads_demo_02,
              seqName = "chr_SYNTHETIC", nbrIterations = 1000,
              lambda = 2, kMax = 30, minInterval = 146,
              maxInterval = 490, minReads = 3, vSeed = 11)

## Before post-treatment
result

##Post-treatment function which merged closely positioned nucleosomes
postResult <- postTreatment(reads = reads_demo_02,
                           seqName = "chr_SYNTHETIC", result, 100, 73500)

## After post-treatment
postResult
```

```
print.rjmcNucleosomes
```

Formatted output of predicted nucleosomes

Description

Generated a formatted output of a list marked as an `rjmcNucleosomes` class

Usage

```
## S3 method for class 'rjmcNucleosomes'
print(x, ...)
```

Arguments

<code>x</code>	the output object from <code>rjmc</code> function to be printed
<code>...</code>	arguments passed to or from other methods

Value

An object of class `rjmcNucleosomes`

Author(s)

Astrid Deschenes

Examples

```
## Loading dataset
data(RJCMC_result)

print(RJCMC_result)
```

```
print.rjmcNucleosomesBeforeAndAfterPostTreatment
```

Formatted output of predicted nucleosomes

Description

Generated a formatted output of a list marked as an rjmcNucleosomesBeforeAndAfterPostTreatment class

Usage

```
## S3 method for class 'rjmcNucleosomesBeforeAndAfterPostTreatment'
print(x, ...)
```

Arguments

x	the output object from rjmcCHR function to be printed
...	arguments passed to or from other methods

Value

an object of class rjmcNucleosomesBeforeAndAfterPostTreatment

Author(s)

Astrid Deschenes

Examples

```
## Load synthetic dataset of reads
data(syntheticNucleosomeReads)

## Use dataset of reads to create GRanges object
sampleGRanges <- GRanges(syntheticNucleosomeReads$dataIP)

## Run nucleosome detection on the entire sample
## Not run: result <- rjmcCHR(reads = sampleGRanges, zeta = 147, delta=50,
maxLength=1200, nbrIterations = 1000, lambda = 3, kMax = 30,
minInterval = 146, maxInterval = 292, minReads = 5, vSeed = 10113,
nbCores = 2, saveAsRDS = FALSE)
## End(Not run)

## Print result
## Not run: print(result)
```

```
print.rjmcNucleosomesMerge
```

Formatted output of predicted nucleosomes

Description

Generated a formatted output of a list marked as an rjmcNucleosomesMerge class

Usage

```
## S3 method for class 'rjmcNucleosomesMerge'
print(x, ...)
```

Arguments

x	the output object from mergeAllRDSFilesFromDirectory function to be printed
...	arguments passed to or from other methods

Value

an object of class mergeAllRDSFilesFromDirectory

Author(s)

Astrid Deschenes

Examples

```
## Use a directory present in the RJMCMC package
directoryWithRDSFiles <- system.file("extdata",
package = "RJMCMCNucleosomes")

## Merge nucleosomes info from RDS files present in directory
## It is assumed that all files present in the directory are nucleosomes
## result for the same chromosome
result <- mergeAllRDSFilesFromDirectory(directoryWithRDSFiles)

## Show resulting nucleosomes
print(result)

## or simply
result
```

reads_demo_01	<i>Forward reads and reverse reads in GRanges format (for demo purpose).</i>
---------------	--

Description

A group of forward and reverse reads, in a GRanges, that can be used to test the `rjmc` function.

Usage

```
data(reads_demo_01)
```

Format

A GRanges containing forward and reverse reads.

Value

A GRanges containing forward and reverse reads.

See Also

- [rjmc](#) for profiling of nucleosome positions

Examples

```
## Loading dataset
data(reads_demo_01)

## Nucleosome positioning
rjmc(reads = reads_demo_01, nbrIterations = 100, lambda = 3, kMax = 30,
      minInterval = 146, maxInterval = 292, minReads = 5)
```

reads_demo_02	<i>Forward reads and reverse reads in GRanges format (for demo purpose).</i>
---------------	--

Description

A group of forward and reverse reads that can be used to test the `rjmc` function.

Usage

```
data(reads_demo_02)
```

Format

A GRanges containing forward and reverse reads.

Value

A GRanges containing forward and reverse reads.

See Also

- [rjmcmc](#) for profiling of nucleosome positions
- [rjmcmcCHR](#) for profiling of nucleosome positions for a large region. The function will take care of splitting and merging.
- [segmentation](#) for splitting a GRanges containing reads in a list of smaller segments for the rjmcmc function.
- [postTreatment](#) for merging closely positioned nucleosomes
- [mergeRDSFiles](#) for merging nucleosome information from selected RDS files.
- [plotNucleosomes](#) for generating a graph containing the nucleosome positions and the read coverage.

Examples

```
## Loading dataset
data(reads_demo_02)

## Nucleosome positioning
## Since there is only one chromosome present in reads_demo_02, the name
## of the chromosome does not need to be specified
rjmcmc(reads = reads_demo_02, nbrIterations = 150, lambda = 3, kMax = 30,
        minInterval = 144, maxInterval = 290, minReads = 6)
```

rjmcmc

Nucleosome positioning mapping on a segment

Description

Use of a fully Bayesian hierarchical model for chromosome-wide profiling of nucleosome positions based on high-throughput short-read data (MNase-Seq data). Beware that for a genome-wide profiling, each chromosome must be treated separately. This function is optimized to run on segments that are smaller sections of the chromosome.

Usage

```
rjmcmc(reads, seqName = NULL, nbrIterations, kMax, lambda = 3, minInterval,
        maxInterval, minReads = 5, adaptIterationsToReads = TRUE, vSeed = -1,
        saveAsRDS = FALSE)
```

Arguments

reads	a GRanges containing forward and reverse reads. Beware that the start position of a reverse read is always higher than the end position.
seqName	a character string containing the label of the chromosome, present in the GRanges object, that will be used. The NULL value is accepted when only one seqname is present in the GRanges; the only seqname present will be used. Default: NULL.
nbrIterations	a positive integer or numeric, the number of iterations. Non-integer values of nbrIterations will be casted to integer and truncated towards zero.
kMax	a positive integer or numeric, the maximum number of degrees of freedom per region. Non-integer values of kMax will be casted to integer and truncated towards zero.
lambda	a positive numeric, the theoretical mean of the Poisson distribution. Default: 3.
minInterval	a numeric, the minimum distance between two nucleosomes.
maxInterval	a numeric, the maximum distance between two nucleosomes.
minReads	a positive integer or numeric, the minimum number of reads in a potential candidate region. Non-integer values of minReads will be casted to integer and truncated towards zero. Default: 5.
adaptIterationsToReads	a logical indicating if the number of iterations must be modified in function of the number of reads. Default: TRUE.
vSeed	a integer. A seed used when reproducible results are needed. When a value inferior or equal to zero is given, a random integer is used. Default: -1.
saveAsRDS	a logical. When TRUE, a RDS file containing the complete output of the c++ rjmcnc() function is created. Default : FALSE.

Value

a list of class "rjmcncNucleosomes" containing:

- call the matched call.
- k a integer, the final estimation of the number of nucleosomes. 0 when no nucleosome is detected.
- mu a GRanges containing the positions of the nucleosomes and '*' as strand. The seqnames of the GRanges correspond to the seqName input value. NA when no nucleosome is detected.
- k_max a integer, the maximum number of nucleosomes obtained during the iteration process. NA when no nucleosome is detected.

Author(s)

Rawane Samb, Pascal Belleau, Astrid Deschenes

Examples

```
## Loading dataset
data(reads_demo_01)

## Nucleosome positioning, running both merge and split functions
result <- rjmcchr(reads = reads_demo_01, seqName = "chr_SYNTHETIC",
  nbrIterations = 1000, lambda = 2, kMax = 30,
  minInterval = 146, maxInterval = 292, minReads = 5,
  vSeed = 10113, saveAsRDS = FALSE)

## Print the final estimation of the number of nucleosomes
result$k

## Print the position of nucleosomes
result$mu

## Print the maximum number of nucleosomes obtained during the iteration
## process
result$k_max
```

rjmcchr

Nucleosome positioning mapping on a large segment, up to a chromosome

Description

Use of a fully Bayesian hierarchical model for chromosome-wide profiling of nucleosome positions based on high-throughput short-read data (MNase-Seq data). Beware that for a genome-wide profiling, each chromosome must be treated separately. This function is optimized to run on an entire chromosome.

The function will process by splitting the GRanges of reads (as example, the reads from a chromosome) in a list of smaller GRanges segments that can be run by the rjmcchr function. All those steps are done automatically.

Usage

```
rjmcchr(reads, seqName = NULL, zeta = 147, delta, maxLength,
  nbrIterations, kMax, lambda = 3, minInterval, maxInterval, minReads = 5,
  adaptIterationsToReads = TRUE, vSeed = -1, nbCores = 1,
  dirOut = "out", saveAsRDS = FALSE, saveSEG = TRUE)
```

Arguments

reads	a GRanges, the forward and reverse reads that need to be segmented.
seqName	a character string containing the label of the chromosome, present in the GRanges object, that will be used. The NULL value is accepted when only one seqname is present in the GRanges; the only seqname present will be used. Default: NULL.

zeta	a positive integer or numeric, the length of the nucleosomes. Default: 147.
delta	a positive integer or numeric, the accepted range of overlapping section between segments. The overlapping section being zeta + delta.
maxLength	a positive integer or numeric, the length of each segment.
nbrIterations	a positive integer or numeric, the number of iterations. Non-integer values of nbrIterations will be casted to integer and truncated towards zero.
kMax	a positive integer or numeric, the maximum number of degrees of freedom per region. Non-integer values of kMax will be casted to integer and truncated towards zero.
lambda	a positive numeric, the theoretical mean of the Poisson distribution. Default: 3.
minInterval	a numeric, the minimum distance between two nucleosomes.
maxInterval	a numeric, the maximum distance between two nucleosomes.
minReads	a positive integer or numeric, the minimum number of reads in a potential candidate region. Non-integer values of minReads will be casted to integer and truncated towards zero. Default: 5.
adaptIterationsToReads	a logical indicating if the number of iterations must be modified in function of the number of reads. Default: TRUE.
vSeed	a integer. A seed used when reproducible results are needed. When a value inferior or equal to zero is given, a random integer is used. Default: -1.
nbCores	a positive integer, the number of cores used to run in parallel. Default: 1.
dirOut	a character string. The name of the directory where 2 directories are created (if they don't already exists). The directory "dirOut/results" contents the rjmcchr results for each segment. The directory "dirOut/done" contents file a log file for each segment in RData format. If the log file for a segment is in the directory, the program considers that it is has been processed and run the next segment. Default: "out".
saveAsRDS	a logical. When TRUE, a RDS file containing the complete output of the rjmcchr function is created. Default: FALSE.
saveSEG	a logical. When TRUE, a RDS file containing the segments generated by segmentation function is saved in directory named from paramter dirOut. Default: FALSE.

Value

a list of class "rjmcchrNucleosomesBeforeAndAfterPostTreatment" containing:

- k a integer, the number of nucleosomes.
- mu a GRanges containing the positions of the nucleosomes.
- kPost a integer, the number of nucleosomes after post-treatment and '*' as strand. The seqnames of the GRanges correspond to the seqName input value. NA when no nucleosome is detected.
- muPost a GRanges containing the positions of the nucleosomes after post-treatment and '*' as strand. The seqnames of the GRanges correspond to the seqName input value. NA when no nucleosome is detected.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```
## Load synthetic dataset of reads
data(syntheticNucleosomeReads)

## Use dataset of reads to create GRanges object
sampleGRanges <- GRanges(syntheticNucleosomeReads$dataIP)

## Run nucleosome detection on the entire sample
## Not run: result <- rjmcCHR(reads = sampleGRanges, zeta = 147, delta=50,
maxLength=1200, nbrIterations = 1000, lambda = 3, kMax = 30,
minInterval = 146, maxInterval = 292, minReads = 5, vSeed = 10113,
nbCores = 2, saveAsRDS = FALSE)
## End(Not run)
```

rjmcNucleo

Interface for the RJMCMC nucleosome mapping method in C++

Description

Function that calls the core of the nucleosome positioning mapping function that is implemented in C++.

Usage

```
rjmcNucleo(startPosForwardReads, startPosReverseReads, nbrIterations, kMax,
lambda, minInterval, maxInterval, minReads = 5L,
adaptIterationsToReads = TRUE, vSeed = -1)
```

Arguments

startPosForwardReads	a vector of numeric, the start position of all the forward reads.
startPosReverseReads	a vector of numeric, the start position of all the reverse reads. Beware that the start position of a reverse read is always higher than the end position.
nbrIterations	a positive integer or numeric, the number of iterations. Non-integer values of nbrIterations will be casted to integer and truncated towards zero.
kMax	a positive integer or numeric, the maximum number of nucleosomes per region. Non-integer values of kMax will be casted to integer and truncated towards zero.
lambda	a positive numeric, the theoretical mean of the Poisson distribution. Default: 3.
minInterval	a numeric, the minimum distance between two nucleosomes.

maxInterval	a numeric, the maximum distance between two nucleosomes.
minReads	a positive integer or numeric, the minimum number of reads in a potential candidate region. Non-integer values of minReads will be casted to integer and truncated towards zero. Default: 5.
adaptIterationsToReads	a logical indicating if the number of iterations must be modified in function of the number of reads. Default: TRUE.
vSeed	a integer. A seed used when reproducible results are needed. When a value inferior or equal to zero is given, a random integer is used. Default: -1.

Value

a list containing:

- k a integer, the number of nucleosomes.
- k_max a integer, the maximum number of nucleosomes obtained during the iteration process.
- it a vector of integer of length k, the variance of the forward reads for each nucleosome.
- nbState a integer, the number of changes of state.
- mu a matrix of numeric with k_max columns and nbState row containing, in each row, the mu values associated the the state identified by the row number.
- muHat a matrix of numeric with k_max columns and k_max rows containing, in each row, the mean mu values associated the number of nucleosomes detected. The row number corresponds to the number of nucleosomes detected.
- nbK a vector of length k_max containing integer, the number of iterations which detected a specific number of nucleosomes. The position in the vector correspond to the number of nucleosomes.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```
data(reads_demo_01)

forward <- start(reads_demo_01[strand(reads_demo_01) == "+"])
reverse <- end(reads_demo_01[strand(reads_demo_01) == "-"])

## Run nucleosome positioning
result <- RJMCMCNucleosomes::rjmcNucleo(
  startPosForwardReads = forward,
  startPosReverseReads = reverse,
  nbrIterations = 1000, lambda = 2, kMax = 30,
  minInterval = 146, maxInterval = 292, minReads = 5,
  adaptIterationsToReads = TRUE, vSeed = -1)

## Print the final estimation of the number of nucleosomes
```

```

result$k

## Print the position of nucleosomes
result$mu

```

RJCMC_result	<i>Nucleosomes obtained by running RJCMC function using reads from reads_demo_02 dataset (for demo purpose).</i>
--------------	--

Description

A list of class "rjcmcNucleosomes" which contains the information about the detected nucleosomes.

Usage

```
data(RJCMC_result)
```

Format

A list of class "rjcmcNucleosomes" containing:

- call the matched call.
- k a integer, the final estimation of the number of nucleosomes. 0 when no nucleosome is detected.
- mu a vector of numeric of length k, the positions of the nucleosomes. NA when no nucleosome is detected.
- k_max a integer, the maximum number of nucleosomes obtained during the iteration process. NA when no nucleosome is detected.

Value

A list of class "rjcmcNucleosomes" containing:

- call the matched call.
- k a integer, the final estimation of the number of nucleosomes. 0 when no nucleosome is detected.
- mu a vector of numeric of length k, the positions of the nucleosomes. NA when no nucleosome is detected.
- k_max a integer, the maximum number of nucleosomes obtained during the iteration process. NA when no nucleosome is detected.

See Also

- [rjmc](#) for profiling of nucleosome positions
- [rjmcCHR](#) for profiling of nucleosome positions for a large region. The function will take care of splitting and merging.
- [segmentation](#) for splitting a GRanges containing reads in a list of smaller segments for the rjmc function.
- [postTreatment](#) for merging closely positioned nucleosomes
- [mergeRDSFiles](#) for merging nucleosome information from selected RDS files.
- [plotNucleosomes](#) for generating a graph containing the nucleosome positions and the read coverage.

Examples

```
## Loading dataset
data(RJCMC_result)
data(reads_demo_02)

## Results before post-treatment
RJCMC_result$mu

## Post-treatment function which merged closely positioned nucleosomes
postResult <- postTreatment(reads = reads_demo_02,
  extendingSize = 60, chrLength = 100000, resultRJCMC = RJCMC_result)

## Results after post-treatment
postResult
```

runCHR

Run [rjmc](#) on multiples segments and merge results.

Description

Run [rjmc](#) on a segment that is contained in a list of segments. Files generated by the function are all saved in a directory specified by user. A RData log file is created when a segment has been run while the result is saved in a RDS file.

If the same output directory is used more than once, the [rjmc](#) won't be called for segments that have the a corresponding RData log file.

Usage

```
runCHR(p, seg, niter, kmax, lambda, ecartmin, ecartmax, minReads,
  adaptNbrIterations, vSeed = -1, saveAsRDS = FALSE, dirOut = "out")
```

Arguments

<code>p</code>	a integer, the position of the segment to treat in a list of GRanges.
<code>seg</code>	a list a GRanges containing the segments to be process.
<code>niter</code>	a positive integer or numeric, the number of iterations. Non-integer values of <code>nbrIterations</code> will be casted to integer and truncated towards zero.
<code>lambda</code>	a positive numeric, the theoretical mean of the Poisson distribution. Default: 3.
<code>minReads</code>	a positive integer or numeric, the minimum number of reads in a potential candidate region. Non-integer values of <code>minReads</code> will be casted to integer and truncated towards zero. Default: 5.
<code>adaptNbrIterations</code>	a logical indicating if the number of iterations must be modified in function of the number of reads.
<code>vSeed</code>	a integer. A seed used when reproducible results are needed. When a value inferior or equal to zero is given, a random integer is used. Default: -1.
<code>saveAsRDS</code>	a logical. When TRUE, a RDS file containing the complete output of the <code>c++rjmcnc()</code> function is created. Default : FALSE.
<code>kMax</code>	a positive integer or numeric, the maximum number of degrees of freedom per region. Non-integer values of <code>kMax</code> will be casted to integer and truncated towards zero.
<code>minInterval</code>	a numeric, the minimum distance between two nucleosomes.
<code>maxInterval</code>	a numeric, the maximum distance between two nucleosomes.
<code>maxLength</code>	a positive integer or numeric, the length of each segment.

Value

0.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```
## Load synthetic dataset of reads
data(syntheticNucleosomeReads)

## Use dataset of reads to create GRanges object
sampleGRanges <- GRanges(seqnames = syntheticNucleosomeReads$dataIP$chr,
  ranges = IRanges(start = syntheticNucleosomeReads$dataIP$start,
    end = syntheticNucleosomeReads$dataIP$end),
  strand = syntheticNucleosomeReads$dataIP$strand)

# Segmentation of the reads
seg <- segmentation(sampleGRanges, zeta = 147, delta = 50, maxLength = 1000)
## Not run:
dir.create("out")
dir.create("out/done")
```

```

dir.create("out/results")

runCHR(p=1, seg=seg, niter=1000, kmax=330, lambda=3,
       ecartmin=147, ecartmax=297, minReads=5)
## End(Not run)

```

segmentation	<i>Split a GRanges containing reads in a list of smaller segments for the rjmc function.</i>
--------------	--

Description

Split a GRanges of reads (as example, the reads from a chromosome) in a list of smaller GRanges so that the rjmc function can be run on each segments.

Usage

```
segmentation(reads, zeta = 147, delta, maxLength)
```

Arguments

reads	a GRanges, the reads that need to be segmented.
zeta	a positive integer or numeric, the length of the nucleosomes. Default: 147.
delta	a positive integer or numeric, the accepted range of overlapping section between segments. The overlapping section being zeta + delta.
maxLength	a positive integer or numeric, the length of each segment.

Value

a GRangesList containing all the segments.

Author(s)

Pascal Belleau, Astrid Deschenes

Examples

```

## Load synthetic dataset of reads
data(syntheticNucleosomeReads)

## Use dataset of reads to create GRanges object
sampleGRanges <- GRanges(seqnames = syntheticNucleosomeReads$dataIP$chr,
  ranges = IRanges(start = syntheticNucleosomeReads$dataIP$start,
    end = syntheticNucleosomeReads$dataIP$end),
  strand = syntheticNucleosomeReads$dataIP$strand)

# Segmentation of the reads

```

```
segmentation(reads = sampleGRanges, zeta = 147, delta = 50,  
maxLength = 1000)
```

syntheticNucleosomeReads

Simulated dataset of reads generated by nucleoSim package (for demo purpose).

Description

A list of class "syntheticNucReads" which contains the information about synthetic reads related to nucleosomes. The dataset has been created using a total of 300 well-positioned nucleosomes, 30 fuzzy nucleosomes with variance of reads following a Normal distribution.

Usage

```
data(syntheticNucleosomeReads)
```

Format

A list containing:

- call the called that generated the dataset.
- dataIP a data.frame with the chromosome name, the starting and ending positions and the direction of all forward and reverse reads for all well-positioned and fuzzy nucleosomes. Paired-end reads are identified with a unique id.
- wp a data.frame with the positions of all the well-positioned nucleosomes, as well as the number of paired-reads associated to each one.
- fuz a data.frame with the positions of all the fuzzy nucleosomes, as well as the number of paired-reads associated to each one.
- paired a data.frame with the starting and ending positions of the reads used to generate the paired-end reads. Paired-end reads are identified with a unique id.

Value

A list containing:

- call the called that generated the dataset.
- dataIP a data.frame with the chromosome name, the starting and ending positions and the direction of all forward and reverse reads for all well-positioned and fuzzy nucleosomes. Paired-end reads are identified with a unique id.
- wp a data.frame with the positions of all the well-positioned nucleosomes, as well as the number of paired-reads associated to each one.
- fuz a data.frame with the positions of all the fuzzy nucleosomes, as well as the number of paired-reads associated to each one.
- paired a data.frame with the starting and ending positions of the reads used to generate the paired-end reads. Paired-end reads are identified with a unique id.

`validateDirectoryParameters`*Parameters validation for the [mergeAllRDSFilesFromDirectory](#) function*

Description

Validation of all parameters needed by the public [mergeAllRDSFilesFromDirectory](#) function.

Usage

```
validateDirectoryParameters(directory)
```

Arguments

<code>directory</code>	a character, the name of the directory (relative or absolute path) containing RDS files.
------------------------	--

Value

0 indicating that all parameters validations have been successful.

Author(s)

Astrid Deschenes

Examples

```
## Load an existing directory
directory <- system.file("extdata", package = "RJMCNucleosomes")

## Testing using a real directory
RJMCNucleosomes::validateDirectoryParameters(directory)
```

`validatePlotNucleosomesParameters`*Parameters validation for the [plotNucleosomes](#) function*

Description

Validation of all parameters needed by the public [plotNucleosomes](#) function.

Usage

```
validatePlotNucleosomesParameters(nucleosomePositions, reads, seqName, xlab,
  ylab, names)
```

Arguments

nucleosomePositions	a GRanges or a GRangesList containing the nucleosome positions for one or multiples predictions obtained using the same reads. In presence of only one prediction (with multiples nucleosome positions), a GRanges is used. In presence of more than one predictions (as example, before and after post-treatment or results from different software), a GRangesList with one entry per prediction is used.
reads	a GRanges containing forward and reverse reads. The GRanges should contain at least one read.
seqName	a character string containing the label of the chromosome, present in the GRanges object, that will be used. The NULL value is accepted when only one seqname is present in the GRanges; the only seqname present will be used.
xlab	a character string containing the label of the x-axis.
ylab	a character string containing the label of the y-axis.
names	a vector of a character string containing the label of each prediction set. The vector must be the same length of the nucleosomePositions list or 1 in presence of a vector.

Value

0 indicating that all parameters validations have been successful.

Author(s)

Astrid Deschenes, Pascal Belleau

Examples

```
## Load GRanges dataset
data(reads_demo_01)

## Load RJMCMC result
data(RJMCMC_result)

## The function returns 0 when all parameters are valid
RJMCMCNucleosomes::validatePlotNucleosomesParameters(nucleosomePositions =
RJMCMC_result$mu, reads = reads_demo_01, seqName = "chr_SYNTHETIC",
xlab = "position", ylab = "coverage", names = c("test"))

## The function raises an error when at least one parameter is not valid
#\dontrun{RJMCMCNucleosomes::validatePlotNucleosomesParameters(
#nucleosomePositions = c("hi"), reads = reads,
#xlab = "position", ylab = "coverage", names = c("test"))}

#\dontrun{RJMCMCNucleosomes::validatePlotNucleosomesParameters(
#nucleosomePositions = RJMCMC_result$mu, reads = reads_demo_01,
#seqName = "chr_SYNTHETIC", xlab = "position", ylab = "coverage",
#names = c("test_one", "test_false"))}
```

`validatePrepMergeParameters`*Parameters validation for the `postMerge` function*

Description

Validation of all parameters needed by the public `postMerge` function.

Usage

```
validatePrepMergeParameters(reads, seqName, resultRJCMC, extendingSize,  
                             chrLength)
```

Arguments

<code>reads</code>	a GRanges containing all forward and reverse reads. The start positions of both reads are going to be used for the analysis. Beware that the start position of a reverse read is always higher than the end position. The GRanges should at least contain one read.
<code>seqName</code>	a character string containing the label of the chromosome, present in the GRanges object, that will be used. The NULL value is accepted when only one seqname is present in the GRanges; the only seqname present will be used.
<code>resultRJCMC</code>	an object of class "rjcmcNucleosomes" or "rjcmcNucleosomesMerge" that contain information about nucleosome positioning for an entire chromosome.
<code>extendingSize</code>	a positive numeric or a positive integer indicating the size of the consensus region used to group closely positioned nucleosomes. The minimum size of the consensus region is equal to twice the value of the extendingSize parameter. The numeric will be treated as an integer.
<code>chrLength</code>	a positive numeric or a positive integer indicating the length of the current chromosome. The length of the chromosome is used to ensure that the consensus positions are all located inside the chromosome.

Value

0 indicating that all parameters validations have been successful.

Author(s)

Astrid Deschenes

Examples

```
## Load dataset containing forward and reverse reads
data(reads_demo_01)

## Load dataset containing nucleosome information
file_002 <- dir(system.file("extdata", package = "RJMCNucleosomes"),
pattern = "RJMCN_seg_02.RDS", full.names = TRUE)
nucleosome_info <- readRDS(file_002)

## The function returns 0 when all parameters are valid
RJMCNucleosomes::validatePrepMergeParameters(reads = reads_demo_01,
seqName = "chr_SYNTHETIC", resultRJMCN = nucleosome_info,
extendingSize = 74, chrLength = 10000000)

## The function raises an error when at least one parameter is not valid
## Not run: RJMCNucleosomes::validatePrepMergeParameters(
reads = c(72400, 72431, 72428, 72429, 72426),
resultRJMCN = NA, extendingSize = 74, chrLength = 10000000)
## End(Not run)
```

validateRDSFilesParameters

Parameters validation for the [mergeRDSFiles](#) function

Description

Validation of all parameters needed by the public [mergeRDSFiles](#) function.

Usage

```
validateRDSFilesParameters(RDSFiles)
```

Arguments

RDSFiles	a array, the names of all RDS used to merge nucleosome information. The files must contain R object of class "rjmcNucleosomes" or "rjmcNucleosomesMerge".
----------	---

Value

0 indicating that all parameters validations have been successful.

Author(s)

Astrid Deschenes

Examples

```
## Loading a file
file_test <- dir(system.file("extdata", package = "RJMCNucleosomes"),
pattern = "RJCMC_seg_02.RDS", full.names = TRUE)

## Testing using a real file
RJMCNucleosomes::validateRDSFilesParameters(file_test)
```

```
validateRJMCMPParameters
```

Parameters validation for the `rjcmc` function

Description

Validation of all parameters needed by the public `rjcmc` function.

Usage

```
validateRJMCMPParameters(reads, seqName, nbrIterations, kMax, lambda,
minInterval, maxInterval, minReads, adaptIterationsToReads, vSeed)
```

Arguments

<code>reads</code>	a GRanges containing all forward and reverse reads. The start positions of both reads are going to be used for the analysis. Beware that the start position of a reverse read is always higher than the end position.
<code>seqName</code>	a character string containing the label of the chromosome, present in the GRanges object, that will be used. The NULL value is accepted when only one seqname is present in the GRanges; the only seqname present will be used.
<code>nbrIterations</code>	a positive integer or numeric, the number of iterations. Non-integer values of <code>nbrIterations</code> will be casted to integer and truncated towards zero.
<code>kMax</code>	a positive integer or numeric, the maximum number of nucleosomes per region. Non-integer values of <code>kMax</code> will be casted to integer and truncated towards zero.
<code>lambda</code>	a positive numeric, the theoretical mean of the Poisson distribution.
<code>minInterval</code>	a numeric, the minimum distance between two nucleosomes.
<code>maxInterval</code>	a numeric, the maximum distance between two nucleosomes.
<code>minReads</code>	a positive integer or numeric, the minimum number of reads in a potential candidate region. Non-integer values of <code>minReads</code> will be casted to integer and truncated towards zero.
<code>adaptIterationsToReads</code>	a logical indicating if the number of iterations must be modified in function of the number of reads.
<code>vSeed</code>	a integer. A seed used when reproducible results are needed. When a value inferior or equal to zero is given, a random integer is used.

Value

0 indicating that all parameters validations have been successful.

Author(s)

Astrid Deschenes

Examples

```
reads <- GRanges(seqnames = Rle(c("chr1"), c(10)),
  ranges = IRanges(101:110, end = 111:120, names = head(letters, 10)),
  strand = Rle(strand(c("-", "+", "-", "+", "-")), c(1, 2, 2, 3, 2)))

## The function returns 0 when all paramaters are valid
RJMCNucleosomes::validateRJMCNParameters(reads = reads,
seqName = "chr1", nbrIterations = 2, kMax = 10, lambda = 1, minReads = 1,
minInterval = 100, maxInterval = 200, adaptIterationsToReads = TRUE,
vSeed = 100)

## The function raises an error when at least one paramater is not valid
## Not run: RJMCNucleosomes::validateRJMCNParameters(
reads = NA, seqName = "chr1",
nbrIterations = 2, kMax = 10, lambda = 1, minReads = 1, minInterval = 100,
maxInterval = 200, adaptIterationsToReads = TRUE, vSeed = -1)
## End(Not run)
```

validateSegmentationParameters

Parameters validation for the [segmentation](#) function

Description

Validation of all parameters needed by the public [segmentation](#) function.

Usage

```
validateSegmentationParameters(reads, zeta = 147, delta, maxLength)
```

Arguments

reads	a GRanges, the reads that need to be segmented.
zeta	a positive integer or numeric, the length of the nucleosomes. Default: 147.
delta	a positive integer or numeric, the accepted range of overlapping section between segments. The overlapping section being zeta + delta.
maxLength	a positive integer or numeric, the length of each segment.

Value

0 indicating that all parameters validations have been successful.

Author(s)

Astrid Deschenes, Pascal Belleau

Examples

```
## Load synthetic dataset of reads
data(syntheticNucleosomeReads)

## Use dataset of reads to create GRanges object
sampleGRanges <- GRanges(seqnames = syntheticNucleosomeReads$dataIP$chr,
  ranges = IRanges(start = syntheticNucleosomeReads$dataIP$start,
    end = syntheticNucleosomeReads$dataIP$end),
  strand = syntheticNucleosomeReads$dataIP$strand)

## The function returns 0 when all parameters are valid
RJMCMCNucleosomes::validateSegmentationParameters(reads = sampleGRanges,
  zeta = 147, delta = 30, maxLength = 12000)

## The function raises an error when at least one parameter is not valid
#\dontrun{RJMCMCNucleosomes::validateSegmentationParameters(
  #reads = c(100), zeta = 147, delta = 30, maxLength = 12000)}

#\dontrun{RJMCMCNucleosomes::validateSegmentationParameters(
  #reads = sampleGRanges, zeta = "hi", delta = 30, maxLength = 12000)}
```

Index

- * **datasets**
 - reads_demo_01, [13](#)
 - reads_demo_02, [13](#)
 - RJMCMC_result, [20](#)
 - syntheticNucleosomeReads, [24](#)
- * **internal**
 - mergeAllRDSFiles, [3](#)
 - postMerge, [7](#)
 - rjmcNucleo, [18](#)
 - runCHR, [21](#)
 - validateDirectoryParameters, [25](#)
 - validatePlotNucleosomesParameters, [25](#)
 - validatePrepMergeParameters, [27](#)
 - validateRDSFilesParameters, [28](#)
 - validateRJMCMCParameters, [29](#)
 - validateSegmentationParameters, [30](#)
- * **package**
 - RJMCMCNucleosomes-package, [2](#)

[mergeAllRDSFiles](#), [3](#)
[mergeAllRDSFilesFromDirectory](#), [4](#), [25](#)
[mergeRDSFiles](#), [3](#), [5](#), [14](#), [21](#), [28](#)

[plotNucleosomes](#), [3](#), [6](#), [14](#), [21](#), [25](#)
[postMerge](#), [7](#), [27](#)
[postTreatment](#), [3](#), [9](#), [14](#), [21](#)
[print.rjmcNucleosomes](#), [10](#)
[print.rjmcNucleosomesBeforeAndAfterPostTreatment](#),
[11](#)
[print.rjmcNucleosomesMerge](#), [12](#)

[reads_demo_01](#), [13](#)
[reads_demo_02](#), [13](#)
[rjmc](#), [3](#), [7](#), [9](#), [13](#), [14](#), [14](#), [21](#), [29](#)
[RJMCMC_result](#), [20](#)
[rjmcCHR](#), [3](#), [14](#), [16](#), [21](#)
[rjmcNucleo](#), [18](#)
[RJMCMCNucleosomes](#)
 ([RJMCMCNucleosomes-package](#)), [2](#)

[RJMCMCNucleosomes-package](#), [2](#)
[runCHR](#), [21](#)

[segmentation](#), [3](#), [14](#), [17](#), [21](#), [23](#), [30](#)
[syntheticNucleosomeReads](#), [24](#)

[validateDirectoryParameters](#), [25](#)
[validatePlotNucleosomesParameters](#), [25](#)
[validatePrepMergeParameters](#), [27](#)
[validateRDSFilesParameters](#), [28](#)
[validateRJMCMCParameters](#), [29](#)
[validateSegmentationParameters](#), [30](#)