

Package ‘MetaPhOR’

May 2, 2026

Type Package

Title Metabolic Pathway Analysis of RNA

Version 1.15.0

Description MetaPhOR was developed to enable users to assess metabolic dysregulation using transcriptomic-level data (RNA-sequencing and Microarray data) and produce publication-quality figures. A list of differentially expressed genes (DEGs), which includes fold change and p value, from DESeq2 or limma, can be used as input, with sample size for MetaPhOR, and will produce a data frame of scores for each KEGG pathway. These scores represent the magnitude and direction of transcriptional change within the pathway, along with estimated p-values. MetaPhOR then uses these scores to visualize metabolic profiles within and between samples through a variety of mechanisms, including: bubble plots, heatmaps, and pathway models.

License Artistic-2.0

Encoding UTF-8

RoxygenNote 7.2.1

Imports utils, ggplot2, ggrepel, stringr, pheatmap, grDevices, stats, clusterProfiler, RecordLinkage, RCy3

Depends R (>= 4.2.0)

biocViews Metabolomics, RNASeq, Pathways, GeneExpression, DifferentialExpression, KEGG, Sequencing, Microarray

Suggests BiocStyle, knitr, rmarkdown, kableExtra

VignetteBuilder knitr

LazyData false

SystemRequirements Cytoscape (>= 3.9.0) for the cytoPath() examples

git_url <https://git.bioconductor.org/packages/MetaPhOR>

git_branch devel

git_last_commit db96ea

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-05-01

Author Emily Isenhardt [aut, cre],
Spencer Rosario [aut]

Maintainer Emily Isenhardt <emily.isenhardt@roswellpark.org>

Contents

| | |
|---------------------------|----------|
| bubblePlot | 2 |
| cytoPath | 3 |
| datasummary | 3 |
| metaHeatmap | 4 |
| pathwayAnalysis | 5 |
| pathwayList | 6 |
| Index | 7 |

| | |
|------------|----------------------------------------------------|
| bubblePlot | <i>Create a Bubble Plot for Individual Samples</i> |
|------------|----------------------------------------------------|

Description

Create a Bubble Plot for Individual Samples

Usage

```
bubblePlot(scorelist, labeltext, labelsizesize = 0.25)
```

Arguments

| | |
|---------------|-----------------------------------------------------|
| scorelist | dataframe(1) the output of Pathway Analysis fun |
| labeltext | character(1) what to label points by: LogFC or Pval |
| labelsizesize | numeric(1) size of text labels for points |

Value

bubblePlot() returns a bubble plot using pathway scores, pval, logfc

Examples

```
brca <- read.csv(system.file("extdata/BRCA_Scores.csv",
                             package = "MetaPhOR"),
                 header = TRUE,
                 row.names = 1)

#Bubble Plot Labeled By P Value
bubblePlot(scorelist = brca,
            labeltext = "Pval",
            labelsizesize = .85)

#Bubble Plot Labeled by LogFC
bubblePlot(scorelist = brca,
            labeltext = "LogFC",
            labelsizesize = .85)
```

cytoPath

Map Differentially Expressed Genes to Dysregulated Pathways

Description

requires the package RCy3 and a local instance of Cytoscape

Usage

```
cytoPath(  
  pathway,  
  DEGpath,  
  figpath,  
  genename,  
  headers = c("log2FoldChange", "padj")  
)
```

Arguments

| | |
|----------|-------------------------------------------------------------------------------------------------|
| pathway | character, the name of the pathway to be visualized |
| DEGpath | character, the path to a DEG file by DESeq2 or limma |
| figpath | character, the path to which the figure will be saved |
| genename | character, column name with HUGO Gene Names in DEG file |
| headers | character vector of length 2 in the form c(log fold change col name, adjusted p value col name) |

Value

cytoPath() Returns a Cytoscape figure of DEG data on rWikiPathways

Examples

```
cytoPath(pathway = "Tryptophan Metabolism",  
  DEGpath = system.file("extdata/BRCA_DEGS.csv", package = "MetaPhOR"),  
  figpath = file.path(tempdir(), "example_map"),  
  genename = "X",  
  headers = c("logFC", "adj.P.Val"))
```

datasummary

MetaPhOR: Metabolic Pathway Analysis of RNA

Description

MetaPhOR was developed to enable users to assess metabolic dysregulation using transcriptomic-level data (RNA-sequencing and Microarray data) and produce publication-quality figures. A list of differentially expressed genes (DEGs), which includes fold change and p value, from DESeq2 or limma, can be used as input, with sample size for MetaPhOR, and will produce a data frame of scores for each KEGG pathway. These scores represent the magnitude and direction of transcriptional change within the pathway, along with estimated p-values. MetaPhOR then uses these scores to visualize metabolic profiles within and between samples through a variety of mechanisms, including: bubble plots, heatmaps, and pathway models.

Author(s)

Maintainer: Emily Isenhardt <emily.isenhardt@roswellpark.org>

Authors:

- Spencer Rosario

metaHeatmap

Create a Heatmap for Comparing Multiple Samples

Description

Create a Heatmap for Comparing Multiple Samples

Usage

```
metaHeatmap(scorelist, samplenames, pvalcut = 0.05)
```

Arguments

| | |
|-------------|-------------------------------------------------------------|
| scorelist | list of outputs from pathwayAnalysis() |
| samplenames | vector of samples names for axis labels |
| pvalcut | numeric, the p val over which pathways will not be included |

Value

metaHeatmap() returns a heatmap of significant dysregulated pathways for each sample included

Examples

```
brca <- read.csv(system.file("extdata/BRCA_Scores.csv",
                             package = "MetaPhOR"), header = TRUE, row.names = 1)

ovca <- read.csv(system.file("extdata/OVCA_Scores.csv",
                             package = "MetaPhOR"), header = TRUE, row.names = 1)

prad <- read.csv(system.file("extdata/PRAD_Scores.csv",
                             package = "MetaPhOR"), header = TRUE, row.names = 1)

all.scores <- list(brca, ovca, prad)
```

```
names <- c("BRCA", "OVCA", "PRAD")

metaHeatmap(scorelist = all.scores,
             samplenames = names,
             pvalcut = 0.05)
```

pathwayAnalysis *Metabolic Pathway Analysis of RNAseq Data*

Description

Metabolic Pathway Analysis of RNAseq Data

Usage

```
pathwayAnalysis(
  DEGpath,
  genename,
  sampsize,
  iters = 1e+05,
  headers = c("log2FoldChange", "padj")
)
```

Arguments

| | |
|----------|------------------------------------------------------------------------------------------------|
| DEGpath | character, the path to a txt or csv DEG file |
| genename | character, column name with HUGO Gene Names in DEG file |
| sampsize | numeric, the sample size of the experiment to be analyzed |
| iters | numeric, the number of iterations of resampling to perform in bootstrapping |
| headers | character vector of length2 in the form c(log fold change col name, adjusted p value col name) |

Value

pathwayAnalysis() returns a dataframe of pathway scores and pvals

Examples

```
#iterations (iters) of resampling in bootstrapping set to 30,000 for speed
#100,000 iterations recommended for improved power

set.seed(1234)

scores <- pathwayAnalysis(
  DEGpath = system.file("extdata/BRCA_DEGS.csv",
                        package = "MetaPhOR"),
  genename = "X",
  sampsize = 1095,
  iters = 30000,
  headers = c("logFC", "adj.P.Val"))

scores
```

pathwayList

List Available Metabolic rWikiPathways

Description

List Available Metabolic rWikiPathways

Usage

```
pathwayList()
```

Value

pathwayList() returns a list of rWikiPathways for use in CytoPath()

Examples

```
pathwayList()
```

Index

[bubblePlot](#), [2](#)

[cytoPath](#), [3](#)

[datasummary](#), [3](#)

[metaHeatmap](#), [4](#)

[MetaPhOR \(datasummary\)](#), [3](#)

[MetaPhOR-package \(datasummary\)](#), [3](#)

[pathwayAnalysis](#), [5](#)

[pathwayList](#), [6](#)