

Package ‘OMICsPCAdata’

October 17, 2019

Type Package

Title Supporting data for package OMICsPCA

Date 21/08/2018

Author Author: Subhadeep Das

Version 1.2.0

Depends R (>= 3.5.0), MultiAssayExperiment

Suggests knitr, kableExtra, rmarkdown

biocViews RepositoryData, TechnologyData, ChIPSeqData, SequencingData,
ExpressionData, ENCODE

Maintainer Subhadeep Das <subhadeep1024@gmail.com>

Description Supporting data for package OMICsPCA

License GPL-3

Encoding UTF-8

VignetteBuilder knitr

LazyData TRUE

git_url <https://git.bioconductor.org/packages/OMICsPCAdata>

git_branch RELEASE_3_9

git_last_commit c9a2281

git_last_commit_date 2019-05-02

Date/Publication 2019-10-17

R topics documented:

clustered_data	2
groupinfo_ext	2
multi_assay	3
transcript_details	3

Index	5
--------------	----------

clustered_data	<i>cluster object</i>
----------------	-----------------------

Description

a matrix containing cluster information

Usage

```
data("clustered_data")
```

Format

The format is: num [1:300, 1:5] 3.37 -5.26 2.07 2.32 1.94 ... - attr(*, "dimnames")=List of 2 ..\$: chr [1:300] "ENST00000456433.1;ENST00000443722.1;ENST00000444457.1;ENST00000498530.1;ENST00000420236.1;ENST00000423207.2" "ENST00000429514.2;ENST00000263893.6;ENST00000492639.1;ENST00000495272.1;ENST00000487884.1"\$: chr [1:5] "Dim.1" "Dim.2" "Dim.3" "Dim.4" ...

Examples

```
data(clustered_data)
## maybe str(clustered_data) ; plot(clustered_data) ...
```

groupinfo_ext	<i>An out put of create_group</i>
---------------	-----------------------------------

Description

An output of create_group()

Usage

```
data("groupinfo_ext")
```

Format

A data frame with 28770 observations on the following variable.

group a factor with levels IntE NE RE WE

Examples

```
data(groupinfo_ext)
## maybe str(groupinfo_ext) ; plot(groupinfo_ext) ...
```

 multi_assay

Example data sets

Description

Histone modification ChIP-seq and CAGE data

Usage

```
data("multi_assay")
```

Format

The datasets included in multi_assay are: 1) Histone modification ChIP-seq peaks of H2az, H3k9ac and H3k4me1. Each of these three datasets are in dataframe format, where the rows correspond to the TSSs and the columns correspond to various cell lines/tissues etc. Each value represents ChIP-seq peak intensity.

2) TSS expression data, measured by CAGE is also in data frame format and the row and column specification is same as the ChIP-seq data. Each value represents an normalized expression value (tpm).

Source

The Histone modification are collected from : https://www.encodeproject.org/matrix/?type=Experiment&assay_title=ChIP-seq&target.investigated_as=broad+histone+mark The DNaseI hypersensitivity (DHS) datasets are collected from : http://ftp.ebi.ac.uk/pub/databases/ensembl/encode/integration_data_jan2011/byDataType/openchrom/ja

The Histone and DHS files are downloaded as bigbed(.bb) format and converted to bed(.bed) format

The CAGE datasets are collected from : https://www.encodeproject.org/search/?type=Experiment&assay_slms=Transcript

Examples

```
data(multi_assay)
## maybe str(multi_assay) ; plot(multi_assay) ...
```

 transcript_details

details of GENCODE(v 17) TSSs

Description

details of GENCODE(v 17) TSSs

Usage

```
data("transcript_details")
```

Format

A data frame with 194871 observations on the following 8 variables.

Examples

```
data(transcript_details)
## maybe str(transcript_details) ; plot(transcript_details) ...
```

Index

*Topic **datasets**

clustered_data, [2](#)

groupinfo_ext, [2](#)

multi_assay, [3](#)

transcript_details, [3](#)

clustered_data, [2](#)

groupinfo_ext, [2](#)

multi_assay, [3](#)

transcript_details, [3](#)