

# MyGene.info R Client

*Adam Mark, Ryan Thompson, Chunlei Wu*

May 1, 2024

## Contents

1	Overview . . . . .	2
2	Gene Annotation Service . . . . .	2
2.1	<code>getGene</code> . . . . .	2
2.2	<code>getGenes</code> . . . . .	2
3	Gene Query Service . . . . .	3
3.1	<code>query</code> . . . . .	3
3.2	<code>queryMany</code> . . . . .	4
4	<code>makeTxDbFromMyGene</code> . . . . .	5
5	Tutorial, ID mapping . . . . .	6
5.1	Mapping gene symbols to Entrez gene ids . . . . .	6
5.2	Mapping gene symbols to Ensembl gene ids . . . . .	7
5.3	When an input has no matching gene . . . . .	8
5.4	When input ids are not just symbols . . . . .	8
5.5	When an input id has multiple matching genes . . . . .	9
5.6	Can I convert a very large list of ids? . . . . .	11
6	References . . . . .	11

## 1 Overview

---

MyGene.Info provides simple-to-use REST web services to query/retrieve gene annotation data. It's designed with simplicity and performance emphasized. *mygene* is an easy-to-use R wrapper to access MyGene.Info services.

## 2 Gene Annotation Service

---

### 2.1 `getGene`

- Use `getGene`, the wrapper for GET query of `"/gene/<geneid>"` service, to return the gene object for the given geneid.

```
> gene <- getGene("1017", fields="all")
> length(gene)

[1] 1

> gene["name"]

[[1]]
NULL

> gene["taxid"]

[[1]]
NULL

> gene["uniprot"]

[[1]]
NULL

> gene["refseq"]

[[1]]
NULL
```

### 2.2 `getGenes`

- Use `getGenes`, the wrapper for POST query of `"/gene"` service, to return the list of gene objects for the given character vector of geneids.

```
> getGenes(c("1017", "1018", "ENSG00000148795"))

DataFrame with 3 rows and 7 columns
```

	query	_id	X_version	entrezgene	name
	<character>	<character>	<integer>	<character>	<character>
1	1017	1017	3	1017 cyclin dependent kin..	
2	1018	1018	1	1018 cyclin dependent kin..	
3	ENSG00000148795	1586	3	1586 cytochrome P450 fami..	
	symbol	taxid			
	<character>	<integer>			
1	CDK2	9606			
2	CDK3	9606			
3	CYP17A1	9606			

## 3 Gene Query Service

### 3.1 query

- Use `query`, a wrapper for GET query of `"/query?q=<query>"` service, to return the query result.

```
> query(q="cdk2", size=5)

$took
[1] 9

$total
[1] 1518

$max_score
[1] 88.58517

$hits
  _id  _score entrezgene      name symbol  taxid
1  1017 88.58517    1017  cyclin dependent kinase 2  CDK2   9606
2  12566 74.29723   12566  cyclin dependent kinase 2  Cdk2  10090
3  362817 62.86689  362817  cyclin dependent kinase 2  Cdk2  10116
4  143384 62.17202  143384 CDK2 associated cullin domain 1 CACUL1  9606
5  116827777 57.15172 116827777  cyclin dependent kinase 2  CDK2  106734
```

```
> query(q="NM_013993")

$took
[1] 20
```

```
$total
[1] 1

$max_score
[1] 1.662678

$hits
  _id  _score entrezgene name symbol
1 780 1.662678      780 discoidin domain receptor tyrosine kinase 1  DDR1
  taxid
1 9606
```

### 3.2 queryMany

- Use `queryMany`, a wrapper for POST query of `"/query"` service, to return the batch query result.

```
> queryMany(c('1053_at', '117_at', '121_at', '1255_g_at', '1294_at'),
+           scopes="reporter", species="human")

Finished
Pass returnall=TRUE to return lists of duplicate or missing query terms.
DataFrame with 6 rows and 7 columns
```

	query	_id	X_score	entrezgene	name	
	<character>	<character>	<numeric>	<character>	<character>	
1	1053_at	5982	19.6520	5982	replication factor C..	
2	117_at	3310	19.7662	3310	heat shock protein f..	
3	121_at	7849	19.7581	7849	paired box 8	
4	1255_g_at	2978	19.7712	2978	guanylate cyclase ac..	
5	1294_at	100847079	17.9611	100847079	microRNA 5193	
6	1294_at	7318	17.9611	7318	ubiquitin like modif..	
	symbol	taxid				
	<character>	<integer>				
1	RFC2	9606				
2	HSPA6	9606				
3	PAX8	9606				
4	GUCA1A	9606				
5	MIR5193	9606				
6	UBA7	9606				

## 4 makeTxDbFromMyGene

TxDb is a container for storing transcript annotations. `makeTxDbFromMyGene` allows the user to make a TxDb object in the Genomic Features package from a mygene "exons" query using a default mygene object.

```
> xli <- c('CCDC83',
+         'MAST3',
+         'RPL11',
+         'ZDHHC20',
+         'LUC7L3',
+         'SNORD49A',
+         'CTSH',
+         'ACOT8')
> txdb <- makeTxDbFromMyGene(xli,
+                             scopes="symbol", species="human")
> transcripts(txdb)
```

GRanges object with 17 ranges and 2 metadata columns:

	seqnames	ranges	strand	tx_id	tx_name
	<Rle>	<IRanges>	<Rle>	<integer>	<character>
[1]	11	85855382-85920013	+	1	NM_001286159
[2]	11	85855382-85920013	+	2	NM_173556
[3]	19	18097777-18151686	+	3	NM_015016
[4]	1	23691805-23696835	+	4	NM_000975
[5]	1	23691778-23696426	+	5	NM_001199802
...	...	...	...	...	...
[13]	17	50719602-50756215	+	13	NM_016424
[14]	17	16440035-16440106	+	14	NR_002744
[15]	15	78921749-78945098	-	15	NM_001319137
[16]	15	78921059-78945046	-	16	NM_004390
[17]	20	45841720-45857392	-	17	NM_005469

-----

seqinfo: 7 sequences from an unspecified genome; no seqlengths

`makeTxDbFromMyGene` invokes either the `query` or `queryMany` method and passes the response to construct a TxDb object. See `?TxDb` for methods to utilize and access transcript annotations.

## 5 Tutorial, ID mapping

ID mapping is a very common, often not fun, task for every bioinformatician. Supposedly you have a list of gene symbols or reporter ids from an upstream analysis, and then your next analysis requires to use gene ids (e.g. Entrez gene ids or Ensembl gene ids). So you want to convert that list of gene symbols or reporter ids to corresponding gene ids.

Here we want to show you how to do ID mapping quickly and easily.

### 5.1 Mapping gene symbols to Entrez gene ids

Suppose `xli` is a list of gene symbols you want to convert to entrez gene ids:

```
> xli <- c('DDX26B',
+         'CCDC83',
+         'MAST3',
+         'FLOT1',
+         'RPL11',
+         'ZDHHC20',
+         'LUC7L3',
+         'SNORD49A',
+         'CTSH',
+         'ACOT8')
```

You can then call `queryMany` method, telling it your input is `symbol`, and you want `entrezgene` (Entrez gene ids) back.

```
> queryMany(xli, scopes="symbol", fields="entrezgene", species="human")
```

Finished

Pass `returnall=TRUE` to return lists of duplicate or missing query terms.

DataFrame with 10 rows and 5 columns

	query	notfound	_id	X_score	entrezgene
	<character>	<logical>	<character>	<numeric>	<character>
1	DDX26B	TRUE	NA	NA	NA
2	CCDC83	NA	220047	17.9274	220047
3	MAST3	NA	23031	18.1892	23031
4	FLOT1	NA	10211	18.4333	10211
5	RPL11	NA	6135	16.6178	6135
6	ZDHHC20	NA	253832	18.1483	253832
7	LUC7L3	NA	51747	17.6362	51747
8	SNORD49A	NA	26800	23.3298	26800

9	CTSH	NA	1512	17.6274	1512
10	ACOT8	NA	10005	17.6107	10005

## 5.2 Mapping gene symbols to Ensembl gene ids

Now if you want Ensembl gene ids back:

```
> out <- queryMany(xli, scopes="symbol", fields="ensembl.gene", species="human")
```

Finished

Pass returnall=TRUE to return lists of duplicate or missing query terms.

```
> out
```

DataFrame with 10 rows and 5 columns

	query	notfound	_id	X_score
	<character>	<logical>	<character>	<numeric>
1	DDX26B	TRUE	NA	NA
2	CCDC83	NA	220047	17.9272
3	MAST3	NA	23031	18.1892
4	FL0T1	NA	10211	18.4352
5	RPL11	NA	6135	16.6171
6	ZDHHC20	NA	253832	18.1478
7	LUC7L3	NA	51747	17.6369
8	SNORD49A	NA	26800	23.3298
9	CTSH	NA	1512	17.6249
10	ACOT8	NA	10005	17.6109

  

	ensembl
	<list>
1	
2	ENSG00000150676
3	ENSG00000099308
4	ENSG00000206480, ENSG00000230143, ENSG00000206379
5	ENSG00000142676
6	ENSG00000180776
7	ENSG00000108848
8	ENSG00000277370
9	ENSG00000103811
10	ENSG00000101473

```
> out$ensembl[[4]]$gene
```

```
[1] "ENSG00000206480" "ENSG00000230143" "ENSG00000206379" "ENSG00000223654"
[5] "ENSG00000232280" "ENSG00000137312" "ENSG00000236271" "ENSG00000224740"
```

## 5.3 When an input has no matching gene

In case that an input id has no matching gene, you will be notified from the output. The returned list for this query term contains `notfound` value as `True`.

```
> xli <- c('DDX26B',
+         'CCDC83',
+         'MAST3',
+         'FLOT1',
+         'RPL11',
+         'Gm10494')
> queryMany(xli, scopes="symbol", fields="entrezgene", species="human")
```

Finished

Pass `returnall=TRUE` to return lists of duplicate or missing query terms.

DataFrame with 6 rows and 5 columns

	query	notfound	_id	X_score	entrezgene
	<character>	<logical>	<character>	<numeric>	<character>
1	DDX26B	TRUE	NA	NA	NA
2	CCDC83	NA	220047	17.9267	220047
3	MAST3	NA	23031	18.1892	23031
4	FLOT1	NA	10211	18.4387	10211
5	RPL11	NA	6135	16.6150	6135
6	Gm10494	TRUE	NA	NA	NA

## 5.4 When input ids are not just symbols

```
> xli <- c('DDX26B',
+         'CCDC83',
+         'MAST3',
+         'FLOT1',
+         'RPL11',
+         'Gm10494',
+         '1007_s_at',
+         'AK125780')
>
```

Above id list contains symbols, reporters and accession numbers, and supposedly we want to get back both Entrez gene ids and uniprot ids. Parameters `scopes`, `fields`, `species` are all flexible enough to support multiple values, either a list or a comma-separated string:



```
> out <- queryMany(xli, scopes=c("symbol", "reporter", "accession"),
+                  fields=c("entrezgene", "uniprot"), species="human")

Finished
Pass returnall=TRUE to return lists of duplicate or missing query terms.

> out

DataFrame with 9 rows and 7 columns
      query  notfound      _id  X_score  entrezgene uniprot.Swiss.Prot
  <character> <logical> <character> <numeric> <character>      <character>
1      DDX26B      TRUE        NA        NA        NA            NA
2      CCDC83       NA      220047    17.9263    220047      Q8IWF9
3       MAST3       NA      23031    18.1903     23031      060307
4       FLOT1       NA     10211    18.4368     10211      075955
5       RPL11       NA      6135    16.6195      6135      P62913
6    Gm10494      TRUE        NA        NA        NA            NA
7  1007_s_at       NA  100616237    18.0718  100616237            NA
8  1007_s_at       NA       780    18.0718       780      Q08345
9   AK125780       NA  118142757    21.0062  118142757      P43080
      uniprot.TrEMBL
      <list>
1
2
3      H0YDV3
4  A0A8V8TLL8, A0A994J700, V9GYV0, ...
5      A2AB11, Q5ST80, A2AB09, ...
6      A0A2R8Y447, Q5VVD0, Q5VVC8
7
8  A0A0A0MSX3, A0A024RCQ1, Q96T61, ...
9      A0A7I2V6E2, B2R9P6

> out$uniprot.Swiss.Prot[[5]]

[1] "P62913"
```

## 5.5 When an input id has multiple matching genes

From the previous result, you may have noticed that query term `1007_s_at` matches two genes. In that case, you will be notified from the output, and the returned result will include both matching genes.

By passing `returnall=TRUE`, you will get both duplicate or missing query terms

## MyGene.info R Client

```
> queryMany(xli, scopes=c("symbol", "reporter", "accession"),
+           fields=c("entrezgene", "uniprot"), species='human', returnall=TRUE)

Finished
$response
DataFrame with 9 rows and 7 columns
      query  notfound      _id  X_score  entrezgene uniprot.Swiss.Prot
  <character> <logical> <character> <numeric> <character>      <character>
1      DDX26B      TRUE      NA      NA      NA      NA
2      CCDC83      NA    220047  17.9274    220047    Q8IWF9
3      MAST3      NA    23031  18.1896    23031    060307
4      FL0T1      NA    10211  18.4375    10211    075955
5      RPL11      NA     6135  16.6164     6135    P62913
6    Gm10494      TRUE      NA      NA      NA      NA
7  1007_s_at      NA  100616237  18.0767  100616237      NA
8  1007_s_at      NA     780  18.0767     780    Q08345
9   AK125780      NA  118142757  21.0093  118142757    P43080
      uniprot.TrEMBL
      <list>
1
2      H0YDV3
3 A0A8V8TLL8,A0A994J700,V9GYV0,...
4      A2AB11,Q5ST80,A2AB09,...
5      A0A2R8Y447,Q5VVD0,Q5VVC8
6
7
8 A0A0A0MSX3,A0A024RCQ1,Q96T61,...
9      A0A7I2V6E2,B2R9P6

$duplicates
  X1007_s_at
1          2

$missing
[1] "DDX26B" "Gm10494"
```

The returned result above contains `out` for mapping output, `missing` for missing query terms (a list), and `dup` for query terms with multiple matches (including the number of matches).

## 5.6 Can I convert a very large list of ids?

Yes, you can. If you pass an id list (i.e., `ids` above) larger than 1000 ids, we will do the id mapping in-batch with 1000 ids at a time, and then concatenate the results all together for you. So, from the user-end, it's exactly the same as passing a shorter list. You don't need to worry about saturating our backend servers. Large lists, however, may take a while longer to query, so please wait patiently.

## 6 References

---

Wu C, MacLeod I, Su AI (2013) BioGPS and MyGene.info: organizing online, gene-centric information. Nucl. Acids Res. 41(D1): D561-D565. [help@mygene.info](mailto:help@mygene.info)