

# Package ‘TaxSEA’

August 25, 2025

**Type** Package

**Title** Taxon Set Enrichment Analysis

**Version** 1.1.9

**Description** TaxSEA is an R package for Taxon Set Enrichment Analysis, which utilises a Kolmogorov-Smirnov test analyses to investigate differential abundance analysis output for whether there are alternations in a-priori defined sets of taxa from public databases (BugSigDB, MiMeDB, GutMGene, mBodyMap, BacDive and GMRepoV2) and collated from the literature. TaxSEA takes as input a list of taxonomic identifiers (e.g. species names, NCBI IDs etc.) and a rank (E.g. fold change, correlation coefficient). TaxSEA be applied to any microbiota taxonomic profiling technology (array-based, 16S rRNA gene sequencing, shotgun metagenomics & metatranscriptomics etc.) and enables researchers to rapidly contextualize their findings within the broader literature to accelerate interpretation of results.

**License** GPL-3

**Encoding** UTF-8

**LazyData** false

**VignetteBuilder** knitr

**RoxygenNote** 7.3.2

**biocViews** Microbiome, Metagenomics, Sequencing, GeneSetEnrichment, RNASeq

**URL** <https://github.com/feargalr/taxsea>

**BugReports** <https://github.com/feargalr/taxsea/issues>

**Depends** R (>= 4.5.0)

**Suggests** BiocStyle, bugsigdbr, fgsea, knitr, rmarkdown, testthat

**Imports** stats, utils

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/TaxSEA>

**git\_branch** devel

**git\_last\_commit** 0d5c5f1

**git\_last\_commit\_date** 2025-08-18

**Repository** Bioconductor 3.22  
**Date/Publication** 2025-08-24  
**Author** Feargal Ryan [aut, cre] (ORCID:  
    <<https://orcid.org/0000-0002-1565-4598>>)  
**Maintainer** Feargal Ryan <feargalr@gmail.com>

Contents

|                              |          |
|------------------------------|----------|
| get_ncbi_taxon_ids . . . . . | 2        |
| get_taxon_sets . . . . .     | 3        |
| NCBI_ids . . . . .           | 3        |
| TaxSEA . . . . .             | 4        |
| TaxSEA_db . . . . .          | 5        |
| TaxSEA_test_data . . . . .   | 5        |
| <b>Index</b>                 | <b>6</b> |

---

|                    |                                                             |
|--------------------|-------------------------------------------------------------|
| get_ncbi_taxon_ids | <i>Retrieve NCBI Taxonomy IDs for a list of taxon names</i> |
|--------------------|-------------------------------------------------------------|

---

Description

This function takes a vector of taxon names and returns a vector of NCBI taxonomy IDs by querying the NCBI Entrez API.

Usage

```
get_ncbi_taxon_ids(taxon_names)
```

Arguments

taxon\_names      A character vector of taxon names

Value

A character vector of NCBI taxonomy IDs corresponding to the input taxon names

Examples

```
taxon_names <- c("Escherichia coli", "Staphylococcus aureus")
taxon_ids <- get_ncbi_taxon_ids(taxon_names)
```

---

`get_taxon_sets`*Retrieve Taxon Sets from TaxSEA Library*

---

**Description**

Retrieve from the TaxSEA database which taxon sets (metabolite producers and disease signatures) contain a taxon of interest.

**Usage**

```
get_taxon_sets(taxon_to_fetch = taxon)
```

**Arguments**

`taxon_to_fetch` The taxon to search for in the TaxSEA database.

**Value**

A character vector containing the names of taxonomic sets where the specified taxon is present.

**Examples**

```
# Retrieve sets for Bifidobacterium longum
get_taxon_sets(taxon="Bifidobacterium_longum")
```

---

`NCBI_ids`*NCBI IDs Dataset*

---

**Description**

A dataset for mapping NCBI IDs to species/genus names. This named vector allows for lookup of NCBI IDs associated with species or genus names.

**Usage**

```
NCBI_ids
```

**Format**

A named vector where:

**names** NCBI IDs

**values** Species or genus names

**Source**

NCBI

## Examples

```
data(NCBI_ids)
# Can look up either with or without spaces
NCBI_ids["Bifidobacterium_breve"]
NCBI_ids["Bifidobacterium breve"]
```

---

TaxSEA

*TaxSEA: Taxon Set Enrichment Analysis*


---

## Description

TaxSEA enables rapid annotation of changes by testing for enrichment of pre-defined taxon sets.

## Usage

```
TaxSEA(
  taxon_ranks,
  lookup_missing = FALSE,
  min_set_size = 5,
  max_set_size = 100,
  custom_db = NULL
)
```

## Arguments

|                             |                                                                                       |
|-----------------------------|---------------------------------------------------------------------------------------|
| <code>taxon_ranks</code>    | A named vector of log2 fold changes between control and test groups.                  |
| <code>lookup_missing</code> | Logical indicating whether to fetch missing NCBI IDs. Default is FALSE.               |
| <code>min_set_size</code>   | Minimum size of taxon sets to include in the analysis. Default is 5.                  |
| <code>max_set_size</code>   | Maximum size of taxon sets to include in the analysis. Default is 100.                |
| <code>custom_db</code>      | A user-provided list of taxon sets. If NULL (default), the built-in database is used. |

## Value

A list of data frames with taxon set enrichment results.

## See Also

- <https://doi.org/10.1093/nar/gkac868> for MiMeDB
- <https://doi.org/10.1093/nar/gkab1019> for GMrepo
- <https://doi.org/10.1093/nar/gkab786> for gutMGene
- <https://doi.org/10.1038/s41587-023-01872-y> for BugSigDB

## Examples

```
data("TaxSEA_test_data")
taxsea_results <- TaxSEA(TaxSEA_test_data)
```

---

TaxSEA\_db

*TaxSEA Database A dataset containing taxon sets. Each item in the list is a taxon set, and each member within a taxon set is a taxon.*

---

### Description

TaxSEA Database A dataset containing taxon sets. Each item in the list is a taxon set, and each member within a taxon set is a taxon.

### Usage

TaxSEA\_db

### Format

A list of vectors. Each vector contains character strings representing taxa.

### Source

See READ ME.

### Examples

```
data(TaxSEA_db)
all_sets <- names(TaxSEA_db)
GABA_producers<-TaxSEA_db[["MiMeDB_producers_of_GABA"]]
```

---

TaxSEA\_test\_data

*TaxSEA Test Data*

---

### Description

A dataset containing taxon ranks and taxon IDs.

### Usage

TaxSEA\_test\_data

### Format

A data frame with two columns:

**rank** Character vector representing taxon ranks

**id** Character vector representing taxon IDs

### Source

See READ ME.

### Examples

```
data(TaxSEA_test_data)
test_results <- TaxSEA(TaxSEA_test_data)
```

# Index

## \* **datasets**

NCBI\_ids, [3](#)

TaxSEA\_db, [5](#)

TaxSEA\_test\_data, [5](#)

get\_ncbi\_taxon\_ids, [2](#)

get\_taxon\_sets, [3](#)

NCBI\_ids, [3](#)

TaxSEA, [4](#)

TaxSEA\_db, [5](#)

TaxSEA\_test\_data, [5](#)