

GeneRfold

March 27, 2012

fold

Folding routine

Description

Folds the sequence and returns the minimum free energy in kcal/mol; the mfe structure in bracket notation is returned.

Usage

```
fold(s, t=37)
```

Arguments

s	Sequence (character string)
t	Temperature (double)

Value

a list with Energy and Structure

References

<http://www.tbi.univie.ac.at/~ivo/RNA/>

See Also

[dotPlot](#),[rnaPlot](#)

Examples

```
s <- "TTAGCTCAATTGGTAAAGACCCTAGGCGAAGCTTAGAGGTGCCGGTT"  
fold(s)  
dotPlot(s,file="dot.ps")  
rnaPlot(s,file="rna.ps")
```

rnaPlot

Plot Rna structure / Dot plot

Description

Plot (to a postscript file) a structure (rnaPlot) made by fold or the dot plot.

Usage

```
dotPlot(s,t,file="toto.ps")
rnaPlot(s,struc=fold(s)[[1]],file="toto.ps")
```

Arguments

s	Sequence (character string)
t	Temperature
struc	Rna structure (given by fold)
file	postscript file (output)

Value

A graphic in postscript file

References

<http://www.tbi.univie.ac.at/~ivo/RNA/>

See Also

[fold](#)

Examples

```
s <- "TTAGCTCAATTGGTAAAGACCCCTAGGCGAAGCTTAGAGGTGCCGGTT"
fold(s)
dotPlot(s,file="dot.ps")
rnaPlot(s,file="rna.ps")
```

Index

*Topic **utilities**

fold, [1](#)

rnaPlot, [2](#)

dotPlot, [1](#)

dotPlot (rnaPlot), [2](#)

fold, [1](#), [2](#)

rnaPlot, [1](#), [2](#)