

Package ‘ggtut’

September 23, 2012

Title support for tutorial on genetics of gene expression ISMB 2011

Version 0.0.42

Author VJ Carey <stvjc@channing.harvard.edu>

Description various resources for genetics of expression with R/bioc

Suggests rtracklayer, GenomicFeatures, ChIPpeakAnno, TxDb.Hsapiens.UCSC.hg18.knownGene

Depends R (>= 2.14.0), GGtools (>= 3.11.32), ff, GenomicRanges, snpStats, GGdata, GenomicFeatures, ChIPpeakAnno, Rsamtools (>= 1.5.35), cheung2010, SNPlocs.Hsapiens.dbSNP.20090506, hmyriB36

Maintainer VJ Carey <stvjc@channing.harvard.edu>

License Artistic-2.0

LazyLoad yes

R topics documented:

ggtut-package	1
c17imp	2
g17rngsnr	3
observed17ceu	4
rules.n43	5
snpr17	6
Index	7

ggtut-package	<i>support for tutorial on genetics of gene expression ISMB 2011</i>
---------------	----------------------------------------------------------------------

Description

various resources for genetics of expression with R/bioc

Details

Package:

Version:

Suggests:

Depends:

License:

LazyLoad:

Built:

CPS17 is a cisProxScores instance, as is PERMCPS17, serialized to reduce vignette computation time. SVA1 is an sva() o

Index:

observed17ceu obtain access to ff-based archives of eQTL test
 results

hg18tx a function that returns a reference to a transcriptDb
 instance for hg18

getFixedBFL retrieve a BamFileList of 41 small RNA seq extracts
 with nicely formatted HapMap names

Further information is available in the following vignettes:

tut11 (source, pdf)

Author(s)

VJ Carey <stvj@channing.harvard.edu>

Maintainer: VJ Carey <stvj@channing.harvard.edu>

Examples

```
library(ggtut)
o17 = observed17ceu()
o17
ch41 = getFixedBFL()
ch41
```

c17imp*SnpMatrix instance with imputations from 1KG to CEU chr 17*

Description

SnpMatrix instance with imputations from 1KG to CEU chr 17

Usage

data(c17imp)

Format

The format is:
 Formal class 'SnpMatrix' [package "snpStats"] with 1 slots
 ..@ .Data: raw [1:90, 1:175170] 77 d6 77 2d ...
- attr(*, "dimnames")=List of 2
\$: chr [1:90] "NA06985" "NA06991" "NA06993" "NA06994" ...
\$: chr [1:175170] "chr17:1869" "rs17055023" "rs6565733" "rs34663111" ...

Source

uses rules.n43

Examples

```
library(snpStats)
data(c17imp)
c17imp
```

g17rngsnr

ranges of genes on chrom 17 (uses hg18)

Description

ranges of genes on chrom 17 (uses hg18)

Usage

```
data(g17rngsnr)
```

Format

The format is:
 Formal class 'GRanges' [package "GenomicRanges"] with 6 slots
 ..@ seqnames :Formal class 'Rle' [package "IRanges"] with 4 slots
@ values : Factor w/ 1 level "chr17": 1
@ lengths : int 475
@ elementMetadata: NULL
@ metadata : list()
 ..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
@ start : int [1:475] 39509647 50333051 46294586 77439016 38229969 37098653 45133689
 58981554 44263371 17349602 ...
@ width : int [1:475] 46894 61277 5753 3743 19335 2772 6839 43820 33858 86118 ...
@ NAMES : chr [1:475] "GI_21237796-A" "GI_4885638-S" "GI_22035666-S" "GI_17572809-S" ...
@ elementType : chr "integer"
@ elementMetadata: NULL
@ metadata : list()
 ..@ strand :Formal class 'Rle' [package "IRanges"] with 4 slots
@ values : Factor w/ 3 levels "+","-","*": 3
@ lengths : int 475

```

.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots
.. ..@ rownames : NULL
.. ..@ nrows : int 475
.. ..@ listData :List of 1
.. .. .$ probeid: chr [1:475] "GI_21237796-A" "GI_4885638-S" "GI_22035666-S" "GI_17572809-S" ...
.. ..@ elementType : chr "ANY"
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ seqinfo :Formal class 'Seqinfo' [package "GenomicRanges"] with 3 slots
.. ..@ seqnames : chr "chr17"
.. ..@ seqlengths : int NA
.. ..@ is_circular: logi NA
..@ metadata : list()

```

Examples

```

data(g17rngsnr)
g17rngsnr
## maybe str(g17rngsnr) ; plot(g17rngsnr) ...

```

observed17ceu

obtain access to ff-based archives of eQTL test results

Description

obtain access to ff-based archives of eQTL test results

Usage

```

observed17ceu()
onePerm17ceu()

```

Details

The underlying ff data were obtained as follows

```

dropMonomorphies = function(sms) { sl = smList(sms) summs = lapply(sl, col.summary)
todrop = lapply(summs, function(x) which(x[,"RAF"]==1 | x[,"RAF"]==0)) for (i in 1:length(todrop))
if (length(todrop[[i]])>0) sl[[i]] = sl[[i]][,-todrop[[i]]] sms@smEnv$smList = sl
sms } library(GGdata) library(multicore) data(eset) ex library(genefilter) exf1 = nsFilter(ex)
length(get("17", revmap(illuminaHumanv1CHR)))->ZZ) kp = intersect(ZZ, featureNames(exf1[[1]]))
c17 = getSS("GGdata", "17", renameChrs="chr17", probesToKeep=kp, wrapperEndo=dropMonomorphies)
f1dm = eqtlTests(c17, ~male, targdir="c17c", genegran=1, geneApply=mclapply) save(f1dm, file="f1dm.rda")
set.seed(1234); permf1dm = eqtlTests(permEx(c17), ~male, targdir="c17c_perm", genegran=1, geneApply=mclapply)
save(permf1dm, file="permf1dm.rda")

```

Value

an instance of `eqtlTestsManager-class`

Examples

```
f1 = observed17ceu()
f1
f1@call
f1[ rsid("rs7502145"), probeId("GI_10190685-S")]
pf1 = onePerm17ceu()
pf1[ rsid("rs7502145"), probeId("GI_10190685-S")]
```

rules.n43

*snpStats imputation rules instance***Description**

snpStats imputation rules instance

Usage

```
data(rules.n43)
```

Format

The format is:

Formal class 'ImputationRules' [package "snpStats"] with 1 slots

```
..@ .Data:List of 470806
```

```
.. ..$: NULL
```

```
.. ..$:List of 4
```

```
.. ...$ maf : num 0.128
```

```
.. ...$ r.squared: num 0.901
```

```
.. ...$ snps : chr [1:4] "rs11654695" "rs9789059" "rs8073513" "rs7225087"
```

```
.. ...$ hap.probs: num [1:32] 0.00 1.02e-21 0.00 1.45e-07 1.52e-07 ...
```

```
.. ..$:List of 4
```

```
.. ...$ maf : num 0.163
```

```
.. ...$ r.squared: num 0.802
```

```
.. ...$ snps : chr [1:4] "rs11654695" "rs12449775" "rs8078223" "rs9907102"
```

```
.. ...$ hap.probs: num [1:32] 0.02863 0.0253 0.00342 0.07866 0.01717 ...
```

```
.. ..$:List of 4
```

```
.. ...$ maf : num 0.116
```

```
.. ...$ r.squared: num 0.881
```

```
.. ...$ snps : chr [1:4] "rs11654695" "rs9789059" "rs8073513" "rs4968164"
```

```
.. ...$ hap.probs: num [1:32] 0.00 1.96e-13 0.00 4.91e-05 1.05e-06 ...
```

```
.. ..$: NULL
```

```
.. .. [list output truncated]
```

Examples

```
library(snpStats)
data(rules.n43)
rules.n43[1:4]
## maybe str(rules.n43) ; plot(rules.n43) ...
```

 snpgr17

SNP locations for chr 17

Description

SNP locations for chr 17

Usage

```
data(snpgr17)
```

Format

The format is:

```
Formal class 'GRanges' [package "GenomicRanges"] with 6 slots
..@ seqnames :Formal class 'Rle' [package "IRanges"] with 4 slots
.. ..@ values : Factor w/ 1 level "chr17": 1
.. ..@ lengths : int 316396
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
.. ..@ start : int [1:316396] 6934 7214 7242 8611 11743 11830 13546 13905 14122 14300 ...
.. ..@ width : int [1:316396] 1 1 1 1 1 1 1 1 1 1 ...
.. ..@ NAMES : chr [1:316396] "rs1106176" "rs6420494" "rs6420495" "rs62054996" ...
.. ..@ elementType : chr "integer"
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ strand :Formal class 'Rle' [package "IRanges"] with 4 slots
.. ..@ values : Factor w/ 3 levels "+","-","*": 3
.. ..@ lengths : int 316396
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots
.. ..@ rownames : NULL
.. ..@ nrows : int 316396
.. ..@ listData : Named list()
.. ..@ elementType : chr "ANY"
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ seqinfo :Formal class 'Seqinfo' [package "GenomicRanges"] with 3 slots
.. ..@ seqnames : chr "chr17"
.. ..@ seqlengths : int NA
.. ..@ is_circular: logi NA
..@ metadata : list()
```

Examples

```
data(snpgr17)
snpgr17
## maybe str(snpgr17) ; plot(snpgr17) ...
```

Index

*Topic **datasets**

- c17imp, [2](#)
- g17rngsnr, [3](#)
- rules.n43, [5](#)
- snpgr17, [6](#)

*Topic **models**

- observed17ceu, [4](#)

*Topic **package**

- ggtut-package, [1](#)

bestGenesPerSNP_obs (ggtut-package), [1](#)
bestGenesPerSNP_perm (ggtut-package), [1](#)

c17imp, [2](#)
CPS17 (ggtut-package), [1](#)

g17rngsnr, [3](#)
getFixedBFL (ggtut-package), [1](#)
ggtut (ggtut-package), [1](#)
ggtut-package, [1](#)

hg18tx (ggtut-package), [1](#)

observed17ceu, [4](#)
onePerm17ceu (observed17ceu), [4](#)

PERMCPS17 (ggtut-package), [1](#)
permsb1 (ggtut-package), [1](#)

rsb2_list (ggtut-package), [1](#)
rsb2_perm_list (ggtut-package), [1](#)
rules.n43, [5](#)

sb1 (ggtut-package), [1](#)
snpgr17, [6](#)
SVA1 (ggtut-package), [1](#)

tr17_1_9 (observed17ceu), [4](#)
tr17_1_9_perm (observed17ceu), [4](#)