

Package ‘Rdisop’

March 26, 2013

Title Decomposition of Isotopic Patterns

Version 1.18.0

Date 2012-04-21

Author Anton Pervukhin <apervukh@minet.uni-jena.de>, Steffen Neumann <sneumann@ipb-halle.de>

Maintainer Steffen Neumann <sneumann@ipb-halle.de>

Description Identification of metabolites using high precision mass spectrometry. MS Peaks are used to derive a ranked list of sum formulae, alternatively for a given sum formula the theoretical isotope distribution can be calculated to search in MS peak lists.

Depends R (>= 2.0.0), RcppClassic, Rcpp

LinkingTo RcppClassic, Rcpp

Suggests RUnit

SystemRequirements None

License GPL-2

URL <http://msbi.ipb-halle.de/>

bioViews MassSpectrometry

R topics documented:

| | |
|-----------------------------|----------|
| addMolecules | 2 |
| decomposeIsotopes | 3 |
| getMolecule | 4 |
| initializeCHNOPS | 5 |
| Index | 7 |

| | |
|--------------|----------------------------------|
| addMolecules | <i>Add/subtract sum formulae</i> |
|--------------|----------------------------------|

Description

Simple arithmetic modifications of sum formulae.

Usage

```
addMolecules(formula1, formula2, elements = NULL, maxisotopes = 10)
subMolecules(formula1, formula2, elements = NULL, maxisotopes = 10)
```

Arguments

| | |
|-------------|---|
| formula1 | Sum formula |
| formula2 | Sum formula |
| elements | list of allowed chemical elements, defaults to full periodic system of elements |
| maxisotopes | maximum number of isotopes shown in the resulting molecules |

Details

`addMolecules()` adds the second argument to the first. `subMolecules()` subtracts the second argument from the first.

This can be useful to revert e.g. adduct/fragment formation found in ESI mass spectrometry, or to mimick simple chemical reactions. No chemical checks are performed.

Value

A list with the elements

| | |
|----------|-------------------------------------|
| formula | repeated sum formula |
| mass | exact monoisotopic mass of molecule |
| score | dummy value, always 1.0 |
| isotopes | a list of isotopes |

Author(s)

Steffen Neumann <sneumann@IPB-Halle.DE>

Examples

```
# For proton-Adduct of Ethanol:
subMolecules("C2H7O", "H")
```

decomposeIsotopes *Mass Decomposition of Isotope Patterns*

Description

Calculate the elementary compositions from an exact Mass or Isotope Pattern, obtained e.g.\ by FTICR or TOF mass spectrometers

Usage

```
decomposeMass(mass, ppm=2.0, mzabs=0.0001, elements=NULL, filter=NULL, z=0, maxisotopes = 10)
decomposeIsotopes(masses, intensities, ppm=2.0, mzabs=0.0001,
elements=NULL, filter=NULL, z=0, maxisotopes = 10)
isotopeScore(molecule, masses, intensities, elements = NULL, filter = NULL, z = 0)
```

Arguments

| | |
|-------------|--|
| mass | A single exact mass (or m/z value) |
| masses | A vector of masses (or m/z values) of an isotope cluster |
| intensities | Absolute or relative intensities of the masses peaks |
| ppm | allowed deviation of hypotheses from given mass |
| mzabs | absolute deviation in dalton (mzabs and ppm will be added) |
| z | charge z of m/z peaks for calculation of real mass. 0 is for auto-detection |
| maxisotopes | maximum number of isotopes shown in the resulting molecules |
| elements | list of allowed chemical elements, defaults to CHNOPS |
| filter | NYI, will be a selection of DU, DBE and Nitrogen rules |
| molecule | a molecule as obtained from getMolecule() or decomposeMass / decomposeIsotopes |

Details

Sum formulas are calculated which explain the given mass or isotope pattern.

Value

| | |
|--|---------------------------------------|
| A list of molecules, which contain the sub-lists | |
| formula | potential formulae |
| mass | exact monoisotopic mass of hypothesis |
| score | calculated score |
| isotopes | a list of isotopes |

Author(s)

Steffen Neumann <sneumann@IPB-Halle.DE>

References

For a description of the underlying IMS see: see citation("Rdisop")

See Also

[decomposeMass](#)

Examples

```
# For Glutamate:  
decomposeIsotopes(c(147.0529,148.0563), c(100.0,5.561173))
```

getMolecule

Calculate mass and isotope information for a molecule given as sum formula

Description

Parse the sum formula and calculate the theoretical exact mass and the isotope distribution.

Usage

```
getMolecule(formula, elements = NULL, z = 0, maxisotopes = 10)  
getMass(molecule)  
getFormula(molecule)  
getIsotope(molecule, index)  
getScore(molecule)  
getValid(molecule)
```

Arguments

| | |
|-------------|---|
| formula | Sum formula |
| elements | list of allowed chemical elements, defaults to full periodic system of elements |
| z | charge z of molecule for exact mass calculation |
| maxisotopes | maximum number of isotopes shown in the resulting molecules |
| molecule | an initialized molecule as returned by <code>getMolecule()</code> or the <code>decomposeMass()</code> and <code>decomposeIsotope()</code> functions |
| index | return the n-th isotope mass/abundance pair of the molecule |

Details

`getMolecule()` Parse the sum formula and calculate the theoretical exact monoisotopic mass and the isotope distribution. For a given element, return the different mass values.

Value

`getMolecule`: A list with the elements

| | |
|----------|--|
| formula | repeated sum formula |
| mass | exact monoisotopic mass of molecule |
| score | probability, for given molecules a dummy value which is always 1.0 |
| valid | result of neutron rule check |
| isotopes | a list of isotopes |

`getMass`, `getFormula` and `getScore`: return the mass of the molecule as string or real value

Author(s)

Steffen Neumann <sneumann@IPB-Halle.DE>

References

For a description of the underlying IMS see: see citation("Rdisop")

Examples

```
# For Ethanol:  
getMolecule("C2H6O")
```

initializeCHNOPS

*Initialize (a subset of) elements of the periodic system of elements
(PSE)*

Description

Initialize the information about name, mass and isotopes. To reduce the number of decomposition hypotheses, subsets of elements can be created.

Usage

```
initializeCHNOPS()  
initializeCHNOPSMgKCaFe()  
initializePSE()  
initializeElements(names)
```

Arguments

names vector of element names within PSE

Details

These functions return full, pre-defined or user-defined (sub-) lists of elements.

Value

A list with the elements

| | |
|---------|--------------------------|
| name | repeated sum formula |
| mass | nominal mass of molecule |
| isotope | a list of isotopes |

The initializeCharges() is special, since it allows to parse charges such as getMolecule("H₃O⁺", elements=c(initialize

Author(s)

Steffen Neumann <sneumann@IPB-Halle.DE>

References

For a description of the underlying IMS see: see citation("Rdisop")
Isotope patterns obtained through wikipedia.org

See Also

[getMolecule](#)

Examples

```
# For Ethanol:  
elements <- initializeCHNOPS()
```

Index

*Topic methods

addMolecules, [2](#)
decomposeIsotopes, [3](#)
getMolecule, [4](#)
initializeCHNOPS, [5](#)

addMolecules, [2](#)

decomposeIsotopes, [3](#)
decomposeMass, [4](#)
decomposeMass (decomposeIsotopes), [3](#)

getFormula (getMolecule), [4](#)
getIsotope (getMolecule), [4](#)
getMass (getMolecule), [4](#)
getMolecule, [4, 6](#)
getScore (getMolecule), [4](#)
getValid (getMolecule), [4](#)

initializeCharges (initializeCHNOPS), [5](#)
initializeCHNOPS, [5](#)
initializeCHNOPSMgKCaFe
 (initializeCHNOPS), [5](#)
initializeCHNOPSNaK
 (initializeCHNOPS), [5](#)
initializeElements (initializeCHNOPS), [5](#)
initializePSE (initializeCHNOPS), [5](#)
isotopeScore (decomposeIsotopes), [3](#)

subMolecules (addMolecules), [2](#)