

# MAQCsubsetILM: MAQC reference subset for the Illumina platform

Laurent Gatto

April 4, 2013

## Contents

<b>1</b>	<b>The MAQC reference datasets</b>	<b>1</b>
<b>2</b>	<b>Loading the reference data</b>	<b>2</b>

## 1 The MAQC reference datasets

The MAQC (MicroArray Quality Control) project<sup>1</sup> provides a set of reference datasets for a set of 10 platforms (see *Summary of the MAQC Data Sets*<sup>2</sup> for more details). This package provides a subset of the Illumina MAQC dataset<sup>3</sup>.

Regarding the Illumina platform (ILM prefix), a total of 59 Human-6 BeadChip 48K v1.0 have been generated. Four different reference RNAs have been used: (A) 100% of Stratagene's *Universal Human Reference RNA*, (B) 100% of Ambion's Human Brain Reference RNA, (C) 75% of A and 25% of B and (D) 25% of A and 75% of B. Each reference has been repeated 5<sup>4</sup> times (noted `_A1_` to `_A5_`)<sup>5</sup> on three different test sites (noted `_1_` to `_3_`). As an example, the `.CEL` result file for the first replicate of test site 2, for the reference ARN C is named `ILM_2_C1.CEL`.

---

<sup>1</sup><http://www.fda.gov/nctr/science/centers/toxicoinformatics/maq>

<sup>2</sup>[http://edkb.fda.gov/MAQC/MainStudy/upload/Summary\\_MAQC\\_DataSets.pdf](http://edkb.fda.gov/MAQC/MainStudy/upload/Summary_MAQC_DataSets.pdf)

<sup>3</sup>Packages for the datasets of other platforms will follow and will all be named MAQCsubsetXXX where XXX is the three-letter code used by the MAQC consortium.

<sup>4</sup>except for site 1, reference C, where 4 replicates are available

<sup>5</sup>the replicates for site 2, reference D are labelled `_D1_`, `_D2_`, `_D4_`, `_D6_` and `_D7_`

These datasets are freely available and allow, for example, researchers to compare the reproducibility of their own Human-6 BeadChip 48K v1.0 data with the MAQC data. *MAQCsubsetILM* offers 3 randomly chosen BeadChips for each reference RNA, one for each test site. Each reference RNA subset is accessible as an R data object, respectively called `refA`, `refB`, `refC` and `refD`.

More information concerning the MAQC initiative can be found in the September 2006 special issue of *Nature Biotechnology*.

## 2 Loading the reference data

Once the library has been installed and loaded, the reference datasets can be loaded using the `(data())` function as shown below.

```
> library("MAQCsubsetILM")
> data(refA)
> refA
```

Summary of data information:

Major Operation History:

	submitted	finished	command	lumiVersion
1	2008-02-29 12:24:41	2008-02-29 12:24:43		1.5.17
2	2008-02-29 12:24:43	2008-02-29 12:24:43		1.5.17
...				
72	2008-02-29 12:25:22	2008-02-29 12:25:22	combine(x = x.lumi, y = x.lumi.i)	
73	2008-02-29 12:27:25	2008-02-29 12:27:25	Subsetting 3 samples.	
			lumiVersion	
72				1.5.17
73				1.5.17

Object Information:

```
LumiBatch (storageMode: lockedEnvironment)
assayData: 47293 features, 3 samples
  element names: beadNum, detection, exprs, se.exprs
```

protocolData: none  
phenoData  
  sampleNames: ILM\_1\_A5 ILM\_2\_A1 ILM\_3\_A2  
  varLabels: sampleID site ref replicate  
  varMetadata: labelDescription  
featureData  
  featureNames: GI\_10047089-S GI\_10047091-S ... trpF (47293 total)  
  fvarLabels: TargetID  
  fvarMetadata: labelDescription  
experimentData: use 'experimentData(object)'  
Annotation:  
Control Data: N/A  
QC information: Please run summary(x, 'QC') for details!