

Package ‘fmcsR’

April 5, 2014

Type Package

Title Mismatch Tolerant Maximum Common Substructure Searching

Version 1.4.0

Date 2013-10-10

Author Yan Wang, Tyler Backman, Kevin Horan, Thomas Girke

Maintainer ChemmineR Team <see@url>

Description The fmcsR package introduces an efficient maximum common substructure (MCS) algorithms combined with a novel matching strategy that allows for atom and/or bond mismatches in the substructures shared among two small molecules. The resulting flexible MCSs (FMCSs) are often larger than strict MCSs, resulting in the identification of more common features in their source structures, as well as a higher sensitivity in finding compounds with weak structural similarities. The fmcsR package provides several utilities to use the FMCS algorithm for pairwise compound comparisons, structure similarity searching and clustering.

Depends R (>= 2.10.0), ChemmineR, methods

biocViews MicrotitrePlateAssay, CellBasedAssays, Visualization, Infrastructure, DataImport, Clustering, Bioinformatics, Proteomics

Suggests BiocStyle

License Artistic-2.0

LazyLoad yes

URL <http://manuals.bioinformatics.ucr.edu/home/chemminer>

R topics documented:

fmcsR-package	2
fmcs	3
fmcsBatch	4

fmcstest	5
MCS-class	6
mcs2sdfset	7
plotMCS	9

Index**11**

fmcsR-package	<i>A FMCS solver package.</i>
----------------------	-------------------------------

Description

The package consists of two main functions, `fmcs` which computes the flexible MCS between two SDF objects. And `fmcsBatch` runs the FMCS algorithm on a SDFset.

Details

Package:	fmcsR
Type:	Package
Version:	1.0
Date:	2012-02-01

Author(s)

Yan Wang

Maintainer: Yan Wang <wangya@cs.ucr.edu>

Examples

```

library(fmcsR)
data(sdfsmpale)
sdfset <- sdfsmpale
result1 <- fmcs(sdfset[[1]], sdfset[[2]])
result2 <- fmcs(sdfset[[1]], sdfset[[2]], au=3)
result3 <- fmcs(sdfset[[1]], sdfset[[2]], bu=3)
result4 <- fmcs(sdfset[[1]], sdfset[[2]], au=1, bu=1)
result5 <- fmcs(sdfset[[1]], sdfset[[2]], matching.mode="aromatic")
result6 <- fmcs(sdfset[[1]], sdfset[[2]], au=2, bu=1, matching.mode="aromatic")

fmcsBatch(sdfset[[1]], sdfset[1:3])
fmcsBatch(sdfset[[1]], sdfset[1:3], au=2)
fmcsBatch(sdfset[[1]], sdfset[1:3], bu=1)
fmcsBatch(sdfset[[1]], sdfset[1:3], matching.mode="aromatic", au=1, bu=1)

```

fmcs*Flexible MCS (FMCS) Finder*

Description

R function to call the C++ implementation of the flexible common substructure (FMCS) algorithm. The FMCS algorithm provides an improved maximum common substructure (MCS) search method that allows atom and/or bond mismatches in the substructures shared among two small molecules. The resulting flexible MCSs (FMCSs) are often larger than strict MCSs, resulting in the identification of more common features in their source structures, as well as a higher sensitivity in detecting weak similarities among compounds.

Usage

```
fmcs(sdf1, sdf2, al = 0, au = 0, bl = 0, bu = 0, matching.mode = "static", fast = FALSE)
```

Arguments

sdf1	Input query SDF object or SDFset object with a single molecule.
sdf2	Input target SDF object SDFset object with a single molecule.
al	Lower bound for the number of atom mismatches.
au	Upper bound for the number of atom mismatches.
bl	Lower bound for the number of bond mismatches.
bu	Upper bound for the number of bond mismatches.
matching.mode	Three modes for bond matching are supported: "static", "aromatic", and "ring".
fast	If fast is set to TRUE, then the fast computing mode will be turned on. In this case, the algorithm will only return the size information about the source structures and their MCSs, while omitting all structural information.

Details

...

Value

Returns object of class MCS

Author(s)

Yan Wang, Thomas Girke

References

Publication in preparation.

See Also

`plotMCS`, `fmcsBatch`, `?"MCS-class"`

Examples

```
library(fmcsR)
data(sdfsample)
sdfset <- sdfsample
mcs1 <- fmcs(sdfset[[1]], sdfset[[2]])
mcsfast <- fmcs(sdfset[[1]], sdfset[[2]], fast=TRUE)
mcs2 <- fmcs(sdfset[[1]], sdfset[[2]], au=3)
mcs3 <- fmcs(sdfset[[1]], sdfset[[2]], bu=3)
mcs4 <- fmcs(sdfset[[1]], sdfset[[2]], au=1, bu=1)
mcs5 <- fmcs(sdfset[[1]], sdfset[[2]], matching.mode="aromatic")
mcs6 <- fmcs(sdfset[[1]], sdfset[[2]], au=2, bu=1, matching.mode="aromatic")

## Plot MCS objects
plotMCS(mcs6)

## Methods to return components of MCS objects
stats(mcs6)
mcs6[["stats"]]
mcs1(mcs6)
mcs6[["mcs1"]]
mcs2(mcs6)
mcs6[["mcs2"]]

## Constructor method from list
mylist <- list(stats=stats(mcs6), mcs1=mcs1(mcs6), mcs2=mcs2(mcs6))
mymcs <- as(mylist, "MCS")
```

fmcsBatch

FMCS Search Function

Description

Compound search function that runs the FMCS algorithm for a query compound against a set of molecules stored in an SDFset container.

Usage

```
fmcsBatch(querySdf, sdfset, al = 0, au = 0, bl = 0, bu = 0, matching.mode = "static")
```

Arguments

<code>querySdf</code>	Input query SDF object or SDFset object of length one.
<code>sdfset</code>	Input target SDFset object.
<code>al</code>	Lower bound for the number of atom mismatches.

au	Upper bound for the number of atom mismatches.
bl	Lower bound for the number of bond mismatches.
bu	Upper bound for the number of bond mismatches.
matching.mode	Three matching mode are supported, "static", "aromatic", and "ring".

Details

This function runs the FMCS algorithm in fast computing mode. Thus, it will only return the similarity scores and size information about the source structures and their MCSs, while omitting all structural information.

Value

Returns a matrix with compound IDs as row names and the following columns: Query_Size, Target_Size, MCS_Size, Tanimoto_Coefficient and Overlap_Coefficient. For details see vignette of this package.

Author(s)

Yan Wang, Thomas Girke

See Also

plotMCS, fmcs, ?"MCS-class"

Examples

```
library(fmcsR)
data(sdfsample)
sdfset <- sdfsample
fmcsBatch(sdfset[[1]], sdfset[1:3])
fmcsBatch(sdfset[[1]], sdfset[1:3], au=2)
fmcsBatch(sdfset[[1]], sdfset[1:3], bu=1)
fmcsBatch(sdfset[[1]], sdfset[1:3], matching.mode="aromatic", au=1, bu=1)
```

fmctest

SD file stored in SDFset object

Description

Sample compound structures stored in SDF format.

Usage

```
data(fmctest)
```

Format

Object of class `SDFset`

Details

Object stores X molecules from a sample SD file.

Source

<ftp://ftp.ncbi.nih.gov/pubchem/>

References

SDF format definition: <http://www.symyx.com/downloads/public/ctfile/ctfile.jsp>

Examples

```
data(fmcstest)
sdfset <- fmcstest
view(sdfset)
```

MCS-class

Class "MCS"

Description

List-like container for storing results from `fmcs` function.

Objects from the Class

Objects can be created by calls of the form `new("MCS", ...)`.

Slots

```
stats: Object of class "numeric" ~~
mcs1: Object of class "SDFset" ~~
mcs2: Object of class "SDFset" ~~
```

Methods

```
[[ signature(x = "MCS"): ...
coerce signature(from = "list", to = "MCS"): ...
mcs1 signature(x = "MCS"): ...
mcs2 signature(x = "MCS"): ...
stats signature(x = "MCS"): ...
```

Note

...

Author(s)

Yan Wang

References

...

See Also

Related classes: SDF, SDFstr

Examples

```
## Create MCS instance
showClass("MCS")
data(sdfsample)
sdfset <- sdfsample
mcs <- fmcs(sdfset[[1]], sdfset[[2]], au=2, bu=2)

## Methods to return components of MCS
stats(mcs)
mcs[["stats"]]
mcs1(mcs)
mcs[["mcs1"]]
mcs2(mcs)
mcs[["mcs2"]]

## Constructor method from list
mylist <- list(stats=stats(mcs), mcs1=mcs1(mcs), mcs2=mcs2(mcs))
mymcs <- as(mylist, "MCS")
```

mcs2 sdfset

Return MCS object as SDFset

Description

Helper function to run atomsubset from ChemmineR library on MCS objects in order to obtain their results in SDFset format.

Usage

```
mcs2 sdfset(x, ...)
```

Arguments

- x Object of class MCS
... Arguments to be passed to/from other methods.

Details

Returns MCS data in form of a list containing two SDFset objects, one for the query and one for the target structure.

Value

List with two SDFset objects.

Note

...

Author(s)

Thomas Girke

References

...

See Also

`fmcs`

Examples

```
library(fmcsR)
data(sdfsample)
sdfset <- sdfsample
mcs <- fmcs(sdfset[[1]], sdfset[[2]], au=2, bu=1, matching.mode="aromatic")
mcs2sdfset(x=mcs, type="new")
mcs2sdfset(x=mcs, type="old")[[1]][[1]]
plot(mcs2sdfset(x=mcs, type="new")[[1]][1])
```

plotMCS*Plot MCS*

Description

Convenience plotting function to visualize and compare MCSs generated by `fmcS` function.

Usage

```
plotMCS(x, mcs = 1, print = FALSE, ...)
```

Arguments

<code>x</code>	MCS object
<code>mcs</code>	Selection of MCS solution by position number, default is 1.
<code>print</code>	<code>print=FALSE</code> turns off printing behavior of class.
<code>...</code>	Arguments to be passed to/from other methods.

Details

The two structures, target and query, used to generate `x` with a call to `fmcS` are plotted next to each other, and the corresponding MCS substructures are highlighted in color.

Value

Prints summary of MCS to screen and plots their structures to graphics device.

Note

...

Author(s)

Yan Wang

References

...

See Also

`sdf.visualize`

Examples

```
library(fmcsR)
data(sdfsample)
sdfset <- sdfsample
mcs <- fmcs(sdfset[[1]], sdfset[[2]], au=2, bu=1, matching.mode="aromatic")
plotMCS(mcs, mcs=1)
```

Index

- *Topic **classes**
 - MCS-class, 6
- *Topic **datasets**
 - fmcstest, 5
- *Topic **package**
 - fmcsR-package, 2
- *Topic **utilities**
 - fmcs, 3
 - mcs2sdfset, 7
 - plotMCS, 9
- *Topic **utility**
 - fmcsBatch, 4
- [[],MCS-method (MCS-class), 6
- coerce, list,MCS-method (MCS-class), 6
- fmcs, 3
- fmcsBatch, 4
- fmcsR (fmcsR-package), 2
- fmcsR-package, 2
- fmcstest, 5
- MCS-class, 6
- mcs1 (MCS-class), 6
- mcs1,MCS-method (MCS-class), 6
- mcs2 (MCS-class), 6
- mcs2,MCS-method (MCS-class), 6
- mcs2sdfset, 7
- plotMCS, 9
- show,MCS-method (MCS-class), 6
- stats (MCS-class), 6
- stats,MCS-method (MCS-class), 6