

Package ‘rols’

October 8, 2014

Type Package

Title An R interface to the Ontology Lookup Service

Version 1.6.1

Author@R person(given = ``Laurent", family = ``Gatto", email =
``lg390@cam.ac.uk", role = c(``aut``, ``cre``))

Author Laurent Gatto <lg390@cam.ac.uk>

Maintainer Laurent Gatto <lg390@cam.ac.uk>

Description This package allows to query EBI's Ontology
Lookup Service (OLS) using Simple Object Access Protocol (SOAP).

Depends methods

Imports XML, XMLSchema (>= 0.6.0), SSOAP (>= 0.8.0), Biobase

Suggests xtable, GO.db, knitr (>= 1.1.0), BiocStyle

biocViews Software, Annotation, MassSpectrometry, GO

License GPL-2

URL <http://lgatto.github.com/rols/>

Collate AllClasses.R AllGenerics.R iface.R cvparam.R environment.R
queries.R rols-package.R utils.R zzz.R

VignetteBuilder knitr

R topics documented:

rols-package	2
allIds	3
as.character.Map	4
as.character.mapItem	4
childrenRelations	5

CVParam-class	6
isIdObsolete	7
key,mapItem-method	8
map,ANY-method	9
olsQuery	9
olsVersion	10
ontologies	11
ontologyLoadDate	12
ontologyNames	13
parents	13
rootId	14
show,Map-method	15
term	15
termMetadata	16
termXrefs	17
value,mapItem-method	18
Index	19

 rols-package

R OLS interface

Description

An R interface to the Ontology Lookup Service

Details

The Ontology Lookup Service (OLS) is a spin-off of the PRIDE project. It provides a web service interface to query multiple ontologies from a single location with a unified output format. This package allows to query the OLS from within R.

Author(s)

Laurent Gatto <lg390@cam.ac.uk>

References

<http://www.ebi.ac.uk/ontology-lookup/>

allIds	<i>Returns all identifiers and terms of an ontology</i>
--------	---

Description

This function returns all identifiers and terms available for given valid ontology. It sends a `getAllTermsFromOntologyRequest` SOAP message and retrieves and parses the `getAllTermsFromOntologyResponse`. The original interface is `public Map getAllTermsFromOntology(String ontologyName)`.

Usage

```
allIds(ontologyName, simplify = TRUE)
```

Arguments

<code>ontologyName</code>	A character with the name of a valid ontology name.
<code>simplify</code>	A logical indicating whether the S4 Map instance should be simplified. Default is TRUE.

Value

A named character if `simplify` is TRUE. An instance of class `Map` otherwise.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [isIdObsolete](#), [olsQuery](#), [olsVersion](#), [ontologies](#), [ontologyLoadDate](#), [ontologyNames](#), [rootId](#), [term](#), [termMetadata](#), [termXrefs](#)

Examples

```
allIds("MS", simplify=FALSE)
```

as.character.Map *Coerce Map to a data.frame*

Description

as method to coerce an instance of Map to a character. The maps keys are used to name the map values.

Usage

```
## S3 method for class Map
as.character(x, ...)
```

Arguments

x An instance Map.
... not used.

Value

A character of length length(map).

Author(s)

Laurent Gatto

See Also

Other as: [as.character.mapItem](#)

as.character.mapItem *Coerce mapItem to a character*

Description

as method to coerce an instance of mapItem to a character by concatenating the key and value variabls.

Usage

```
## S3 method for class mapItem
as.character(x, ...)
```

Arguments

x An instance of mapItem.
... not used

Value

A character of length 2.

Author(s)

Laurent Gatto

See Also

Other as: [as.character.Map](#)

childrenRelations *Returns the children relation type(s).*

Description

This function returns the relation type of a ontology term termId and its children. The function sends a getTermRelationsRequest SOAP message and retrieves and parses the getTermRelationsResponse. The original corresponding interface is public Map getTermRelations(String termId, String ontologyName).

Usage

```
childrenRelations(termId = termId,  
                 ontologyName = ontologyName, simplify = TRUE)
```

Arguments

termId	A character with a valid ontology identifier.
ontologyName	A character with the name of a valid ontology name.
simplify	A logical indicating whether the S4 Map instance should be simplified. Default is TRUE.

Value

A named character if simplify is TRUE. An instance of class Map otherwise.

Author(s)

Laurent Gatto

Examples

```
childrenRelations("GO:0005802", "GO")
```

CVParam-class	Class "CVParam"
---------------	-----------------

Description

CVParam objects instantiate controlled vocabulary entries.

Usage

```
CVParam(label, name, accession, value, exact = TRUE)
```

Arguments

label	A character with the ontology label. If missing, a user-defined parameter is created.
name	A character with the name of the CVParam to be constructed. This argument can be omitted if accession is used and label is not missing.
accession	A character with the accession of the CVParam to be constructed. This argument can be omitted if name is used. Ignored for user-defined instances.
value	A character with the value of the CVParam to be constructed. This argument is optional.
exact	A logical defining whether the query to retrieve the accession (when name is used) should be an exact match.

Objects from the Class

Objects can be created with the CVParam constructor.

Slots

label: Object of class "character" that defines the label of the instance, i.e the ontology abbreviation. See [ontologyNames](#) for a complete list.

accession: Object of class "character" with the parameter's valid label ontology accession number. See below for validity constrains.

name: Object of class "character" with the instance's valid name, i.e matching with the accession. name and accession must follow `term(accession, label) == name` for the instance to be valid.

value: Object of class "character" with the CVParams value, if applicable, of empty string ("") otherwise.

user: Object of class "logical" defining if the instance is a user-defined parameter (also called User params).

.__classVersion__: Object of class "[Versions](#)" describing the instance's class definition version. For development use.

Extends

Class "[Versioned](#)", directly.

Methods

coerce signature(from = "CVParam", to = "character"): Coerces CVParam from to a character of the following form: [label, accession, name,value]. as.character is also defined.

show signature(object = "CVParam"): Prints the CVParam instance as text.

rep signature(x = "CVParam", times = "numeric"): Replicates the CVParam x times times.

Author(s)

Laurent Gatto <lg390@cam.ac.uk>

Examples

```
## a user param
CVParam(name = "A user param", value = "the value")
## a CVParam from PSIs Mass Spectrometry ontology
term("MS:1000073", "MS")
CVParam(label = "MS", accession = "MS:1000073")
CVParam(label = "MS", name = "electrospray ionization")
CVParam(label = "MS", name = "ESI") ## using a synonym
```

isIdObsolete

Is the ontology id obsolete

Description

When terms are found to be outside the scope of an ontology, are misleadingly named or defined or describe a concept that would be better represented in another way, the terms are marked obsolete rather than deleted. This function tests this by sending an isObsoleteRequest SOAP message and retrieves and parses the isObsoleteResponse. The original interface is public boolean isObsolete(String termId, String ontologyName).

Usage

```
isIdObsolete(termId, ontologyName)
```

Arguments

termId A character with a valid ontology identifier.
ontologyName A character with the name of a valid ontology name.

Value

A logical specifying if the term id is obsolete.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [olsQuery](#), [olsVersion](#), [ontologies](#), [ontologyLoadDate](#), [ontologyNames](#), [rootId](#), [term](#), [termMetadata](#), [termXrefs](#)

Examples

```
## is obsolete
term("GO:0005563", "GO")
isIdObsolete(termId = "GO:0005563", ontologyName = "GO")
stopifnot(isIdObsolete(termId = "GO:0005563", ontologyName = "GO"))
## replaced by
term("GO:0030533", "GO")
isIdObsolete(termId = "GO:0030533", ontologyName = "GO")
```

key,mapItem-method key *slot accessor*.

Description

key slot accessor for the mapItem instances.

key slot accessor for the Map instances.

Arguments

object	An instance of class mapItem.
object	An instance of class Map.

Value

A character.

A character.

Author(s)

Laurent Gatto

map,ANY-method	Map <i>slot accessor</i> .
----------------	----------------------------

Description

Accessor for the Map data of the OLS return messages converted to their respective S4 classes. The actual data is stored in Map slots.

Arguments

from	An S4 class produced by an OLS return message.
------	--

Value

A instance of class Map.

Author(s)

Laurent Gatto

olsQuery	<i>Returns matching identifiers</i>
----------	-------------------------------------

Description

This function queries one or all ontologies for a pattern and returns all identifiers/terms. If a valid ontologyName is provided, only that ontology is queried. The function then sends a `getTermsByNameRequest` SOAP message and retrieves and parses the `getTermsByNameResponse`. The original corresponding interface is `public Map getTermsByName(String partialName, String ontologyName, boolean reverseKeyOrder)`. If no ontologyName is provided, all ontologies are used; the function then sends a `getPrefixedTermsByNameRequest` SOAP message and retrieves and parses the `getPrefixedTermsByNameResponse`. The original corresponding interface is `public Map getPrefixedTermsByName(String partialName, boolean reverseKeyOrder)`.

Usage

```
olsQuery(pattern, ontologyName, exact = FALSE, n = 3,
          simplify = TRUE)
```

Arguments

pattern	A character used to query the OLS.
ontologyName	Optional. A character with the name of a valid ontology name. If missing, all ontologies are searched for pattern.
exact	Require pattern to match term exactly. Default is FALSE. Note that if ontologyName is missing, exact is ignored.
n	Number of attempts to repeat the query if no result is found. Default is 3.
simplify	A logical indicating whether the S4 Map instance should be simplified. Default is TRUE.

Details

Some valid queries sometimes return empty results due to network instabilities. For this reason, each `olsQuery` is repeated 3 times (see `n` parameter) as long as empty results are obtained. In general, when the ontology is specified, queries are fast and reliable.

Value

A named character if `simplify` is TRUE. An instance of class `Map` otherwise.

Author(s)

Laurent Gatto

See Also

Other `ols`-queries: [allIds](#), [isIdObsolete](#), [olsVersion](#), [ontologies](#), [ontologyLoadDate](#), [ontologyNames](#), [rootId](#), [term](#), [termMetadata](#), [termXrefs](#)

Examples

```
olsQuery("tgn","GO") ## search GO for tgn
olsQuery("tgn") ## search all ontologies
olsQuery("ESI", "MS")
olsQuery("ESI", "MS", exact = TRUE)
```

`olsVersion`

Returns the OLS version

Description

This function returns the Ontology Lookup Webservice version, build data and author. It sends a `getVersionRequest` SOAP message and retrieves and parses the `getVersionResponse`. The original interface is `public String getVersion()`.

Usage

```
olsVersion()
```

Value

A character of length 5.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [isIdObsolete](#), [olsQuery](#), [ontologies](#), [ontologyLoadDate](#), [ontologyNames](#), [rootId](#), [term](#), [termMetadata](#), [termXrefs](#)

Examples

```
olsVersion()
```

ontologies

Returns all available ontologies

Description

This function returns available ontologies. It sends a `getOntologyNamesRequest` SOAP message and retrieves and parses the `getOntologyNamesResponse`. The original interface is `public Map getOntologyNames()`.

Usage

```
ontologies(simplify = TRUE)
```

Arguments

`simplify` A logical indicating whether the S4 Map instance should be simplified. Default is TRUE.

Value

If `simplify` is TRUE, a `data.frame` with available ontologies names and descriptions. An instance of class `Map` otherwise.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [isIdObsolete](#), [olsQuery](#), [olsVersion](#), [ontologyLoadDate](#), [ontologyNames](#), [rootId](#), [term](#), [termMetadata](#), [termXrefs](#)

Examples

```
head(ontologies())
ontologies(simplify=FALSE)
```

ontologyLoadDate	<i>Returns the ontology load date</i>
------------------	---------------------------------------

Description

This function returns the load date of a given ontology. The ontology name must be valid, i.e. exists in `ontologies()`. It sends a `getOntologyLoadDateRequest` SOAP message and retrieves and parses the `getOntologyLoadDateResponse`. The original interface is `public String getOntologyLoadDate(String on`

Usage

```
ontologyLoadDate(ontologyName)
```

Arguments

ontologyName A character with the name of a valid ontology name.

Value

A character with the ontology's load date.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [isIdObsolete](#), [olsQuery](#), [olsVersion](#), [ontologies](#), [ontologyNames](#), [rootId](#), [term](#), [termMetadata](#), [termXrefs](#)

Examples

```
ontologyLoadDate("GO")
ontologyLoadDate("FIX")
```

ontologyNames	<i>Returns all ontologyNames</i>
---------------	----------------------------------

Description

Returns the names of the OLS ontologies.

Usage

```
ontologyNames()
```

Value

A character with all ontology names.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [isIdObsolete](#), [olsQuery](#), [olsVersion](#), [ontologies](#), [ontologyLoadDate](#), [rootId](#), [term](#), [termMetadata](#), [termXrefs](#)

Examples

```
head(ontologyNames())
```

parents	<i>Returns the parent(s) of a term.</i>
---------	---

Description

This function returns the parent term(s) of term `termId` in ontology `ontologyName`. The function sends a `getTermParentsRequest` SOAP message and retrieves and parses the `getTermParentsResponse`. The original corresponding interface is `public Map getTermParents(String termId, String ontologyName)`

Usage

```
parents(termId = termId, ontologyName = ontologyName,  
        simplify = TRUE)
```

Arguments

termId	A character with a valid ontology identifier.
ontologyName	A character with the name of a valid ontology name.
simplify	A logical indicating whether the S4 Map instance should be simplified. Default is TRUE.

Value

A named character if simplify is TRUE. An instance of class Map otherwise.

Author(s)

Laurent Gatto

Examples

```
parents("GO:0005802", "GO")
```

rootId	<i>Returns the root identifiers of an ontology</i>
--------	--

Description

This function returns root identifier(s) for a given valid ontology name. It sends a `getRootTermsRequest` SOAP message and retrieves and parses the `getRootTermsResponse`. The original interface is `public Map getRootTerms(String ontologyName)`.

Usage

```
rootId(ontologyName, simplify = TRUE)
```

Arguments

ontologyName	A character with the name of a valid ontology name.
simplify	A logical indicating whether the S4 Map instance should be simplified. Default is TRUE.

Value

A named character if simplify is TRUE. An instance of class Map otherwise.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [isIdObsolete](#), [olsQuery](#), [olsVersion](#), [ontologies](#), [ontologyLoadDate](#), [ontologyNames](#), [term](#), [termMetadata](#), [termXrefs](#)

Examples

```
rootId("GO")
rootId("NEWT")
rootId("MS")
```

show, Map-method	Map <i>show method</i>
------------------	------------------------

Description

show method for Map instances

Arguments

object An Map instance.

Value

Returns an invisible 'NULL'. This function is used for its side-effect of printing a textual description of object.

Author(s)

Laurent Gatto

term	<i>Returns the term of a given identifier</i>
------	---

Description

This function returns the term (description) of a given ontology identifier in a specific ontology. The ontology name must be valid, i.e. exists in `ontologies()`. It sends a `getTermByIdRequest` SOAP message and retrieves and parses the `getTermByIdResponse`. The original interface is `public String getTermById(String termId, String ontologyName)`.

Usage

```
term(termId, ontologyName)
```

Arguments

termId A character with a valid ontology identifier.
ontologyName A character with the name of a valid ontology name.

Value

A string with the description of that identifier, as found in ontology ontologies. If termId was not found in ontologies(), as warning is issued and NULL is returned.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [isIdObsolete](#), [olsQuery](#), [olsVersion](#), [ontologies](#), [ontologyLoadDate](#), [ontologyNames](#), [rootId](#), [termMetadata](#), [termXrefs](#)

Examples

```
term("GO:0005794", "GO") ## valid description
term("GO:0000000", "GO") ## returns NULL
term("210797", "NEWT")
```

termMetadata	<i>Returns an identifier's metadata</i>
--------------	---

Description

This function returns the metadata (definition and synonyms) for a specific ontology identifier. The term for that identifier can be retrieved with [term](#). The function sends a getTermMetadataRequest SOAP message and retrieves and parses the getTermMetadataResponse. The original interface is `public Map getTermMetadata(String termId, String ontologyName)`.

Usage

```
termMetadata(termId, ontologyName, simplify = TRUE)
```

Arguments

termId A character with a valid ontology identifier.
ontologyName A character with the name of a valid ontology name.
simplify A logical indicating whether the S4 Map instance should be simplified. Default is TRUE.

Value

A named character if simplify is TRUE. An instance of class Map otherwise.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [isIdObsolete](#), [olsQuery](#), [olsVersion](#), [ontologies](#), [ontologyLoadDate](#), [ontologyNames](#), [rootId](#), [term](#), [termXrefs](#)

Examples

```
termMetadata("GO:0005794", "GO")
termMetadata("210797", "NEWT")
```

termXrefs

Returns the identifier's ontology cross references

Description

This function returns ontology cross references for an identifier. The function sends a `getTermXrefsRequest` SOAP message and retrieves and parses the `getTermXrefsResponse`. The original interface is `public Map getTermXrefs(String termId, String ontologyName)`.

Usage

```
termXrefs(termId, ontologyName, simplify = TRUE)
```

Arguments

<code>termId</code>	A character with a valid ontology identifier.
<code>ontologyName</code>	A character with the name of a valid ontology name.
<code>simplify</code>	A logical indicating whether the S4 Map instance should be simplified. Default is TRUE.

Value

A named character if `simplify` is TRUE. An instance of class `Map` otherwise.

Author(s)

Laurent Gatto

See Also

Other ols-queries: [allIds](#), [isIdObsolete](#), [olsQuery](#), [olsVersion](#), [ontologies](#), [ontologyLoadDate](#), [ontologyNames](#), [rootId](#), [term](#), [termMetadata](#)

value,mapItem-method value *slot accessor*.

Description

value slot accessor for the mapItem instances.

value slot accessor for the Map instances.

Arguments

object An instance of class mapItem.

object An instance of class Map.

Value

A character.

A character.

Author(s)

Laurent Gatto

Index

*Topic **classes**

CVParam-class, 6

*Topic **package**

rols-package, 2

allIds, 3, 8, 10–13, 15–17

as.character.CVParam (CVParam-class), 6

as.character.Map, 4, 5

as.character.mapItem, 4, 4

childrenRelations, 5

coerce, CVParam, character-method
(CVParam-class), 6

CVParam (CVParam-class), 6

CVParam-class, 6

isIdObsolete, 3, 7, 10–13, 15–17

key (key, mapItem-method), 8

key, Map-method (key, mapItem-method), 8

key, mapItem-method, 8

map (map, ANY-method), 9

map, ANY-method, 9

olsQuery, 3, 8, 9, 11–13, 15–17

olsVersion, 3, 8, 10, 10, 12, 13, 15–17

ontologies, 3, 8, 10, 11, 11–13, 15–17

ontologyLoadDate, 3, 8, 10, 11, 12, 12, 13,
15–17

ontologyNames, 3, 6, 8, 10–12, 13, 15–17

parents, 13

rep, CVParam-method (CVParam-class), 6

rols (rols-package), 2

rols-package, 2

rootId, 3, 8, 10–13, 14, 16, 17

show (show, Map-method), 15

show, CVParam-method (CVParam-class), 6

show, Map-method, 15

show?Map (show, Map-method), 15

term, 3, 8, 10–13, 15, 15–17

termMetadata, 3, 8, 10–13, 15, 16, 16, 17

termXrefs, 3, 8, 10–13, 15, 16, 17, 17

value (value, mapItem-method), 18

value, Map-method

(value, mapItem-method), 18

value, mapItem-method, 18

Versioned, 7

Versions, 6