

convert

April 19, 2009

coerce

Convert Data Objects

Description

Convert between limma, marray and Biobase data objects.

Details

Objects can be converted (coerced) from one class to another using `as(object, Class)` where `object` is an object to convert and `Class` is the name of the class to convert to. The following conversions are provided:

| From: | To: |
|------------|---------------|
| RGList | marrayRaw |
| marrayRaw | RGList |
| MAList | marrayNorm |
| marrayNorm | MAList |
| RGList | NChannelSet |
| marrayRaw | NChannelSet |
| MAList | ExpressionSet |
| marrayNorm | ExpressionSet |

RGList and marrayRaw are coerced to NChannelSet. Channel values are not transformed.

MAList and marrayNorm are coerced so that the ExpressionSet slot contains log-ratios (M-values) and the ExpressionSet object has the same number of columns as the original object. In this case, information on the A-values is lost.

There is intentionally no conversion from RGList or marrayRaw to ExpressionSet, as ExpressionSet is intended for expression values, not intensities.

Author(s)

Gordon Smyth and others

See Also

[as](#) in the `methods` package.

Examples

```

##first set up some fake intensity matrices
testRed <- matrix(rnorm(5*2),5,2,
  dimnames=list(paste("gene",1:5, sep=""), c("S1", "S2")))
testGreen <- matrix(rnorm(5*2),5,2,
  dimnames=list(paste("gene",1:5, sep=""), c("S1", "S2")))

##some sample/target info
testTarget <- data.frame(slide=c("S1", "S2"), Cy3=c("T", "C"),
  Cy5=c("C", "T"), row.names=c("S1", "S2"))

maT <- new("marrayInfo", maLabels=c("S1", "S2"),
  maInfo= testTarget)

##now create instances and convert
x <- new("RGList")
x$R <- testRed
x$G <- testGreen
y <- as(x,"marrayRaw")
z <- as(x, "NChannelSet")

x <- new("marrayRaw")
x@maGf <- testGreen
x@maRf <- testRed
x@maTargets = maT
y <- as(x,"RGList")
z <- as(x, "NChannelSet")

x <- new("MAList")
y <- as(x,"marrayNorm")

##we construct a reasonably complete fake, small
##instance of the marrayNorm class
x <- new("marrayNorm")
x@maM <- testRed
x@maA <- testGreen
maTargets(x) = maT
y <- as(x,"MAList")
y <- as(x, "ExpressionSet")

x <- new("MAList")
x$M <- testRed
x$A <- testGreen
x$targets <- testTarget
y <- as(x,"ExpressionSet")

```

Index

*Topic **classes**

coerce, 1

*Topic **data**

coerce, 1

as, 1

coerce, 1

coerce, MAList, ExpressionSet-method
(coerce), 1

coerce, MAList, marrayNorm-method
(coerce), 1

coerce, marrayNorm, ExpressionSet-method
(coerce), 1

coerce, marrayNorm, MAList-method
(coerce), 1

coerce, marrayRaw, NChannelSet-method
(coerce), 1

coerce, marrayRaw, RGList-method
(coerce), 1

coerce, RGList, marrayRaw-method
(coerce), 1

coerce, RGList, NChannelSet-method
(coerce), 1

convert (coerce), 1