

# MAQCsubset

April 13, 2009

## R topics documented:

MAQCsubset . . . . .	1
gehMAQCsubDef . . . . .	2
gnfCerebHi . . . . .	2
proboStruct-class . . . . .	3
proboscis . . . . .	4

<b>Index</b>	<b>6</b>
--------------	----------

---

MAQCsubset	<i>Experimental Data Package: MAQCsubset</i>
------------	--

---

## Description

selected data from the MAQC project (Nature Biotechnology, Sept. 2006)

## Usage

```
data (afxsubRMAES)
data (afxsubRMA)
data (afxsub)
```

## Format

The format is: An `ExpressionSetObject` with covariates:

- `site`: from `cel`
- `samp`: rna src/mixture code
- `repl`: replicate

## Note

`afxsubRMA` is an `exprSet` (deprecated) and `afxsub` is an `AffyBatch`. `afxsubRMAES` is a proper `ExpressionSet` instance.

`ilmMAQCsubR` is the result of applying `lumiR` to the files in the vicinity of GEO GSM122901 with filename suffixes matching those of the `sampleNames` in the set.

**Examples**

```
data (afxsubRMAES)
```

---

```
gehMAQCsubDef      Excerpt from GE Codelink array contributions to MAQC
```

---

**Description**

Excerpt from GE Codelink contributions to MAQC

**Usage**

```
data (gehSubRaw)
data (gehMAQCsubDef)
```

**Details**

gehSubRaw is a `codelink::Codelink` instance based on reading the raw GEO files: "GSM123122\_GEH\_1\_A1.TXT" "GSM123123\_GEH\_1\_A2.TXT" "GSM123127\_GEH\_1\_B1.TXT" "GSM123128\_GEH\_1\_B2.TXT" "GSM123132\_GEH\_1\_C1.TXT" "GSM123133\_GEH\_1\_C2.TXT" "GSM123137\_GEH\_1\_D1.TXT" "GSM123138\_GEH\_1\_D2.TXT"

gehMAQCsubDef is an `ExpressionSet` instance based on default background correction and normalization of the `codelink` package. The original feature names include duplicates; these were made unique by `make.names` with `unique=TRUE`.

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**Examples**

```
data (gehMAQCsubDef)
gehMAQCsubDef
```

---

```
gnfCerebHi      Gene lists for hi or low abundance in cerebellum according to Novartis GNF symatlas
```

---

**Description**

Data frames with gene lists for hi or low abundance in cerebellum according to Novartis GNF symatlas

**Usage**

```
data (gnfCerebHi)
data (gnfCerebLow)
```

## Details

The symatlas.gnf.org database was searched using the gcrma version of human gene atlas for genes having expression in cerebellum at least 3 times (or at most 1/3 times) median expression over all organs surveyed. The resulting gene lists were intersected with genes present on GE codelink (version used in MAQCsubset) and hgu95a.

## Value

data.frame instances with columns providing gene name, affy probe set identifier, codelink probe identifier, illuminaHumanv1 identifier.

## Author(s)

Vince Carey <stvjc@channing.harvard.edu>

## Examples

```
data(gnfCerebHi)
gnfCerebHi[1:3,]
```

---

proboStruct-class *Class "proboStruct"*

---

## Description

structure for managing proboscis plot data

## Objects from the Class

Objects can be created by calls of the form `new("proboStruct", ...)`.

## Slots

**.Data:** Object of class "list"

**call:** Object of class "call"

## Extends

Class "list", from data part. Class "vector", by class "list", distance 2. Class `AssayData-class`, by class "list", distance 2.

## Methods

plot

## Note

The proboscis plot shows how the probability of self-consistent monotone titration (SCMT) varies with the spiked difference in concentrations of two mRNA preparations in an MAQC dataset.

**Author(s)**

V Carey <stvjc@channing.harvard.edu>

**References**

For Figure 2 of Shippy et al., Using RNA sample titrations... (Nat Biotech, 24(9):1123-1131, Sep 2006)

**Examples**

```
data(afxsubRMAES)
NN1 = proboscis(afxsubRMAES)
plot(NN1)
showClass("proboStruct")
```

---

proboscis	<i>Produce a plot similar to Figure 2 of the Shippy MAQC paper (PMID 16964226).</i>
-----------	---

---

**Description**

Produce a plot similar to Figure 2 of the Shippy MAQC paper (PMID 16964226).

**Usage**

```
proboscis(es, site=1, ABp=0.001, CDp=0.01, mmrad=100)
```

**Arguments**

es	<a href="#">ExpressionSet</a> instance with MAQC assay results
site	numeric code – site to be assessed
ABp	ABp – p-value threshold to declare concentration of gene in sample A to be different from the concentration in sample B
CDp	CDp – p-value threshold to declare concentration of gene in sample C to be different from the concentration in sample D
mmrad	numeric radius of the moving mean used to smooth the proportions differentially expressed

**Details**

Figure 2 of the Shippy paper consists of a collection of plots of estimated probabilities of self-consistent monotone titration – briefly, samples are such that A has 100% USRNA, B has 100% Ambion brain, C has 75% USRNA+25% brain, D has 25% USRNA, 75% brain. Self-consistent monotone titration holds for gene g if microarray measures for that gene satisfy  $A > C > D > B$  or  $B > C > D > A$ . The estimated probability functions look like a creature sticking its nose over a wall, thus the name of this function.

**Value**

an instance of [proboStruct](#), for which a plot and lines method are available.

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**References**

PMID 16964226

**Examples**

```
data (afxsubRMAES)
NN2 = proboscis (afxsubRMAES, site=2)
plot (NN2)
```

# Index

## \*Topic classes

proboStruct-class, 3

## \*Topic datasets

MAQCsubset, 1

## \*Topic models

gehMAQCsubDef, 2

gnfCerebHi, 2

proboscis, 4

afxsub (MAQCsubset), 1

afxsubRMA (MAQCsubset), 1

afxsubRMAES (MAQCsubset), 1

AssayData-class, 3

ExpressionSet, 4

gehMAQCsubDef, 2

gehSubRaw (gehMAQCsubDef), 2

gnfCerebHi, 2

gnfCerebLow (gnfCerebHi), 2

ilmMAQCsubR (MAQCsubset), 1

lines, proboStruct-method  
(proboStruct-class), 3

list, 3

make.names, 2

MAQCsubset, 1

plot, proboStruct-method  
(proboStruct-class), 3

proboscis, 4

proboStruct, 4

proboStruct-class, 3

show, proboStruct-method  
(proboStruct-class), 3

vector, 3