

rMAT

April 19, 2010

BMAPCelParser *BPMAP and CEL files Reader*

Description

One-step reading of BPMAP and CEL files, using Fusion SDK and affxparser.

Usage

```
BMAPCelParser(BMAPFileName, CelFileNames, genomeName=NULL, verbose=FALSE, group
```

Arguments

<code>BMAPFileName</code>	String containing the full filename of the BPMAP file.
<code>CelFileNames</code>	Vector of strings containing full filenames of CEL files. i.e. <code>c("F1.CEL", "F2.CEL")</code>
<code>genomeName</code>	String containing the genome name used.
<code>groupName</code>	String containing the group of genome name used.
<code>seqName</code>	String containing the group of sequence name (e.g. chromosome) used.
<code>verbose</code>	If verbose is selected, the progress and additional information will be displayed while the function is running

Details

This function returns an object of class `tilingSet` containing all necessary information: probe sequences, genomic positions, chromosomes as well as the probe intensities.

Value

An object of class `tilingSet`.

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
Arnaud Droit, <arnaud.droit@ircm.qc.ca>

See Also

affyTile for information about the package.

Examples

```
#####
#The data are in inst/doc folder in rMAT package
#####

pwd<-" #INPUT FILES- BMAP, ARRAYS, etc.
path<- system.file("doc/Sc03b_MR_v04_10000.bmap",package="rMAT")

bmapFile<-paste(pwd,path,sep="")

pathCEL<- system.file("doc/Swr1WTIP_Short.CEL",package="rMAT")
arrayFile<-paste(pwd,c(pathCEL),sep="")

# Show the all the different sequences
ReadBMAPAllSeqHeader(bmapFile)

# create a tiling Set from the corresponding data
# This will only grep the sequences with Sc
ScSet<-BMAPCelParser(bmapFile, arrayFile, verbose=FALSE,groupName="Sc")

# show the object
show(ScSet)

# summarize its content
summary(ScSet)
```

callEnrichedRegions

Detection of enriched regions

Description

This function is used to locate putative enriched regions.

Usage

```
callEnrichedRegions(MatScore, dMax=600, dMerge=300, nProbesMin=8, method="score")
```

Arguments

MatScore	This object contains an Range Data file
dMax	An integer value. The sliding window side of which the adjacent probes are to average upon in order to compute the rMAT score.
dMerge	An integer value. The maximum size to merge adjacent probes and categorize them as one region for scores of adjacent probes uniformly above the input threshold.

nProbesMin	An integer value. The minimum number of probes to average upon. If the number of probes within the interval is less than nProbesMin, the rMAT score of the region will not be computed.
method	A character string value equal to "score", "pValue" or "FDR". "score" denotes the method of calling enriched regions based sliding widow scores. "pValue" denotes the method of calling enriched regions based on p-values. Method "FDR" uses an FDR procedure to call regions. See Details below.
threshold	An integer value. The threshold of rMAT Score to be labeled as an enriched region. For method=1 or 3, the higher the score, the more confident we are about enriched regions. For method=2, the lower the score, the more confident we are about enriched regions.
verbose	A logical value. If verbose is TRUE, progress information would be displayed.

Details

For more details on the calculation of the rMAT score, pvalues, etc, please refer to the following paper: Johnson et al. Model-based analysis of tiling-arrays for ChIP-chip. Proc Natl Acad Sci USA (2006) vol. 103 (33) pp. 12457-62

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
Arnaud Droit, <arnaud.droit@ircm.qc.ca>

See Also

NormalizeProbes, computeMATScore.

Examples

```
#####
#The data are in inst/doc folder in rMAT package.
#####

pwd<-" " #INPUT FILES- BMAP, ARRAYS, etc.
path<- system.file("doc/Sc03b_MR_v04_10000.bmap",package="rMAT")

bmapFile<-paste(pwd,path,sep="")

pathCEL<- system.file("doc/Swr1WTIP_Short.CEL",package="rMAT")
arrayFile<-paste(pwd,c(pathCEL),sep="")

# Show the all the different sequences
ReadBMAPAllSeqHeader(bmapFile)

# create a tiling Set from the corresponding data
# This will only grep the sequences with Sc
ScSet<-BMAPCellParser(bmapFile, arrayFile, verbose=FALSE,groupName="Sc")

# show the object
show(ScSet)
```

```
# summarize its content
summary(ScSet)

ScSetNorm<-NormalizeProbes(ScSet, method="MAT", robust=FALSE, all=FALSE, standard=TRUE, ve

RD<-computeMATScore(ScSetNorm, cName=NULL, dMax=600, verbose=TRUE)
Enrich<-callEnrichedRegions(RD, dMax=600, dMerge=300, nProbesMin=8, method="score", thresh
```

computeMATScore *Detection of enriched regions*

Description

This function is used to compute the rMAT scores following normalization of expression values in order to locate putative enriched regions. This function is now defunct now defunct and you should instead use 'computeMATScore'.

Usage

```
computeMATScore(tilingSet, cName=NULL, dMax=600, verbose=FALSE)
```

Arguments

tilingSet	This object contains an ExpressionSet
cName	Unique identifier of control name
dMax	An integer value. The sliding window side of which the adjacent probes are to average upon in order to compute the rMAT score.
verbose	A logical value. If verbose is TRUE, progress information would be displayed.

Details

For more details on the calculation of the rMAT score, pvalues, etc, please refer to the following paper: Johnson et al. Model-based analysis of tiling-arrays for ChIP-chip. Proc Natl Acad Sci USA (2006) vol. 103 (33) pp. 12457-62

Value

The rMAT Score, pValues, and regions. For the regions vector, let 0 denotes the unenriched region. If an enriched region is found, the interval of the region is labeled by a none 0 value. The first region detected is abeled 1 and the next regions are subsequently incremented.

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
 Arnaud Droit, <arnaud.droit@ircm.qc.ca>

See Also

NormalizeProbes, computeMATScore, callEnrichedRegions for normalizing expression values before computing the rMAT enriched regions.

Examples

```
#####
#The data are in inst/doc folder in rMAT package.
#####

pwd<-" #INPUT FILES- BMAP, ARRAYS, etc.
path<- system.file("doc/Sc03b_MR_v04_10000.bmap",package="rMAT")

bmapFile<-paste(pwd,path,sep="")

pathCEL<- system.file("doc/Swr1WTIP_Short.CEL",package="rMAT")
arrayFile<-paste(pwd,c(pathCEL),sep="")

# Show the all the different sequences
ReadBMAPAllSeqHeader(bmapFile)

# create a tiling Set from the corresponding data
# This will only grep the sequences with Sc
ScSet<-BMAPCelParser(bmapFile, arrayFile, verbose=FALSE,groupName="Sc")

# show the object
show(ScSet)

# summarize its content
summary(ScSet)

ScSetNorm<-NormalizeProbes(ScSet, method="MAT",robust=FALSE, all=FALSE, standard=TRUE, ve

RD<-computeMATScore(ScSetNorm,cName=NULL, dMax=600, verbose=TRUE)
```

MAT

This object contains an ExpressionSet

Description

An object summarizing the output from the MAT function with the following slots : genome-Name,featurePosition,featureChromosome,score,regIndex,method,threshold

Usage

```
NewMAT<-new('MAT', genomeName="Sc", featurePosition, featureChromosome, score, r
```

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
 Arnaud Droit, <arnaud.droit@ircm.qc.ca>

References

Lo, K., Brinkman, R. R. and Gottardo, R. (2008) Automated Gating of Flow Cytometry Data via Robust Model-based Clustering. *Cytometry A* **73**, 321-332.

See Also

[tilingSet](#)

Examples

```
# genomeName="Sc03b_MR_v04"
# featurePosition="4"
# featureChromosome="chr1"
# score="8.8623"
# regIndex="177"
# method=""
# threshold="5"

#NewMAT<-new('MAT', genomeName="Sc", featurePosition, featureChromosome, score, regIndex,
```

MATScore

Detection of enriched regions

Description

This function is used to compute the rMAT scores following normalization of expression values in order to locate putative enriched regions. This function is now defunct now defunct and you should instead use 'computeMATScore'.

Usage

```
MATScore(tilingSet, cName="NULL", dMax=600, nProbesMin=8, dMerge=300, method="sc
```

Arguments

tilingSet	This object contains an ExpressionSet
cName	Unique identifier of control name
dMax	An integer value. The sliding window size of which the adjacent probes are to average upon in order to compute the rMAT score.
nProbesMin	An integer value. The minimum number of probes to average upon. If the number of probes within the interval is less than nProbesMin, the rMAT score of the region will not be computed.
dMerge	An integer value. The maximum size to merge adjacent probes and categorize them as one region for scores of adjacent probes uniformly above the input threshold.

method	A character string value equal to "score", "pValue" or "FDR". "score" denotes the method of calling enriched regions based sliding widow scores. "pValue" denotes the method of calling enriched regions based on p-values. Method "FDR" uses an FDR procedure to call regions. See Details below.
threshold	An integer value. The threshold of rMAT Score to be labeled as an enriched region. For method=1 or 3, the higher the score, the more confident we are about enriched regions. For method=2, the lower the score, the more confident we are about enriched regions.
verbose	A logical value. If verbose is TRUE, progress information would be displayed.
bedName	This file file includes columns "chromosome rMATScore region pValue" for each probe.

Details

For more details on the calculation of the rMAT score, pvalues, etc, please refer to the following paper: Johnson et al. Model-based analysis of tiling-arrays for ChIP-chip. Proc Natl Acad Sci USA (2006) vol. 103 (33) pp. 12457-62

Value

The rMAT Score, pValues, and regions. For the regions vector, let 0 denotes the unenriched region. If an enriched region is found, the interval of the region is labeled by a none 0 value. The first region detected is labeled 1 and the next regions are subsequently incremented.

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
Arnaud Droit, <arnaud.droit@ircm.qc.ca>

See Also

NormalizeProbes, computeMATScore, callEnrichedRegions for normalizing expression values before computing the rMAT enriched regions.

Examples

```
#####
#The data are in inst/doc folder in rMAT package.
#####

#pwd<-" #INPUT FILES- BMAP, ARRAYS, etc.
#path<- system.file("doc/Sc03b_MR_v04_10000.bmap",package="rMAT")

#bmapFile<-paste(pwd,path,sep="")

#pathCEL<- system.file("doc/Swr1WTIP_Short.CEL",package="rMAT")
#arrayFile<-paste(pwd,c(pathCEL),sep="")

# Show the all the different sequences
#ReadBMAPAllSeqHeader(bmapFile)
```

```

# create a tiling Set from the corresponding data
# This will only grep the sequences with Sc
#ScSet<-BMAPCelParser(bpmapFile, arrayFile, verbose=FALSE,groupName="Sc")

# show the object
#show(ScSet)

# summarize its content
#summary(ScSet)

#ScSetNorm<-NormalizeProbes(ScSet, method="MAT",robust=FALSE, all=FALSE, standard=TRUE, v

#ScScore<- MATScore(ScSetNorm, cName=NULL, dMax=600,nProbesMin=8, dMerge=300,method="scor

```

NormalizeProbes *Normalize tiling array data using sequence information*

Description

This function is used to normalize tiling array data using sequence information. Users can chose between two different normalization methods. Please refer to the arguments section below.

Usage

```
ScSetNorm<-NormalizeProbes(tilingSet, method="MAT",robust=FALSE, all=FALSE, stan
```

Arguments

tilingSet	This object contains an ExpressionSet and has the following additional slots
method	The normalization method to be used. User can choose from "MAT", or "PairBinned". As an upgrade to MAT, the Pair option also takes into account of the interaction between adjacent pairs along the probe as covariates for linear regression.
robust	A logical value. If TRUE, reweighted least-squares estimates are computed.
all	A logical value. If not using all probes to compute (for faster computation and memory efficiency) the regression parameters, then use the minimum of 300,000 or number of probes, whichever is less.
verbose	A logical value. If verbose is TRUE, progress information would be displayed.

Details

For the original rMAT normalization: method is set to be rMAT in string, robust is set to be false, copyNumber is set to be your copy number's vector, rMATScaling is set to be true, and logTransform is set to be true for untransformed data. The output can be saved as BAR file if the BAR argument specifies a filename, or as a parsed BAR file if argument output specifies a filename.

For more details on normalization, please refer to the following paper: Johnson et al. Model-based analysis of tiling-arrays for ChIP-chip. Proc Natl Acad Sci USA (2006) vol. 103 (33) pp. 12457-62

Value

The matrix of normalized expression values.

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
Arnaud Droit, <arnaud.droit@ircm.qc.ca>

See Also

PairInMatrix() for generating neighbouring pair-codes from sequences and affyTile for information about the package.

Examples

```
#####
#The data are in inst/doc folder in rMAT package.
#####

pwd<-" #INPUT FILES- BMAP, ARRAYS, etc.
path<- system.file("doc/Sc03b_MR_v04_10000.bmap",package="rMAT")

bmapFile<-paste(pwd,path,sep="")

pathCEL<- system.file("doc/Swr1WTIP_Short.CEL",package="rMAT")
arrayFile<-paste(pwd,c(pathCEL),sep="")

# Show the all the different sequences
ReadBMAPAllSeqHeader(bmapFile)

# create a tiling Set from the corresponding data
# This will only grep the sequences with Sc

ScSet<-BMAPCelParser(bmapFile, arrayFile, verbose=FALSE,groupName="Sc")
ScSetNorm<-NormalizeProbes(ScSet, method="MAT",robust=FALSE, all=FALSE, standard=TRUE, ve
```

ReadBMAPAllSeqHeader

Reading All the BMAP Sequence Header

Description

Reading the header of a specified sequence in the BMAP file. Several sequences could be stored in a single Affymetrix Tiling Array. For example, an array could contain probes from Chromosome 21 and Chromosome 22. The sequenceNum uniquely specifies a sequence. Information about this sequence could be determined in this function. The total number of sequences a tiling array contains can be determined in ReadBMAPHeader(fileName). The sequenceNum indexes from 0 to (total number of sequences -1).

Usage

```
ReadBPMAPAllSeqHeader(fileName)
```

Arguments

`fileName` the full path of the BMAP file to be read.

Details

The BMAP Sequence Header gives information about the design of the tiling array.

Value

A list of vectors containing SeqName, GroupName, version, npnrobeMapping, seqNum, and NumHits.

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
Arnaud Droit, <arnaud.droit@ircm.qc.ca>

See Also

`BMAPCelParser()` for an one-step BMAP/CEL parser and `affyTile` for information about the package.

Examples

```
#####
#The data are in inst/doc folder in rMAT package.
#####

pwd<-" " #INPUT FILES- BMAP, ARRAYS, etc.
path<- system.file("doc/Sc03b_MR_v04_10000.bmap", package="rMAT")

bmapFile<-paste(pwd, path, sep=" ")

pathCEL<- system.file("doc/Swr1WTIP_Short.CEL", package="rMAT")
arrayFile<-paste(pwd, c(pathCEL), sep=" ")

# Show the all the different sequences
ReadBPMAPAllSeqHeader(bmapFile)
```

```
show,tilingSet-method  
    show Method for tiling set object
```

Description

This methods show the content of tilinSet objets

Usage

```
## S4 method for signature 'tilingSet':  
show(object)
```

Arguments

object Object returned of class tilingSet

Details

TilingSet contains an ExpressionSet and has the following additional slots: genomeName, feature-Sequence, featurePosition, featureChromosome, featureCopyNumber, featureSequence.

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
Arnaud Droit, <arnaud.droit@ircm.qc.ca>

See Also

[BPMAPCelParser](#), [NormalizeProbes](#)

```
summary,tilingSet-method  
    Summary Method for MAT Object
```

Description

This methods summarize tilinSet object

Usage

```
## S4 method for signature 'tilingSet':  
summary(object)
```

Arguments

object A tilingSet object.

Details

This function will give a basic summary of a tilingSet object including chromosome/genome information.

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
Arnaud Droit, <arnaud.droit@ircm.qc.ca>

See Also

[BPMAPCelParser](#), [NormalizeProbes](#)

tilingSet	<i>This object contains an ExpressionSet</i>
-----------	--

Description

This object contains an ExpressionSet and has the following additional slots: genomeName, featureSequence, featurePosition, featureChromosome, featureCopyNumber

Usage

```
newSet<-new('tilingSet', featureChromosome, featurePosition, featureCopyNumber,
```

Arguments

tilingSet	This object contains an ExpressionSet
genomeName	String containing the genome name used (vector).
featureChromosome	Factor containing the name of chromosome used (vector).
featurePosition	String containing the Position of the sequences (vector).
featureCopyNumber	String containing the copy number of sequence (vector).
exprs	String containing the expression data of enriched region (matrix with n column).
featureSequence	String containing the sequence (vector).
experimentData	String containing the type of experiments.

Details

Tiling set objects can also be combined using the `rbind` methods. This is particularly useful when several arrays span a genome/chromosome.

Author(s)

Charles Cheung, <cykc@interchange.ubc.ca> and Raphael Gottardo, <raphael.gottardo@ircm.qc.ca>
Arnaud Droit, <arnaud.droit@ircm.qc.ca>

References

W. E. Johnson, Li, W., Meyer, C. A., Gottardo, R., Carroll, J. S., Brown, M., and Liu, X. S. (2006). Model-based analysis of tiling-arrays for ChIP-chip. PNAS 103:12457-12462.

See Also

[BPMAPCelParser](#), [NormalizeProbes](#)

Examples

```
featureChromosome=factor(c("chr1", "chr1", "chr1", "chr1"))
featurePosition=c(as.integer(47193), as.integer(47197), as.integer(47201), as.integer(47205))
featureCopyNumber=c(as.integer(1), as.integer(1), as.integer(1), as.integer(1))
a=5.379897
exprs=matrix(a, nrow=4)
genomeName="Sc03b_MR_v04_10000"
featureSequence=c("TCATCAAGGGAAGAGAGTCTCTCAG", "TGATCATCACGGGACTTCTGGTTTA", "CGGGACTTCTGGTTT")

newSet<-new('tilingSet', featureChromosome=featureChromosome, featurePosition=featurePosition, featureCopyNumber=featureCopyNumber, featureSequence=featureSequence)
```

Index

*Topic **IO**

BPMAPCelParser, 1
callEnrichedRegions, 2
computeMATScore, 4
MATScore, 6
NormalizeProbes, 8
ReadBMAPAllSeqHeader, 9

*Topic **file**

BPMAPCelParser, 1
callEnrichedRegions, 2
computeMATScore, 4
MATScore, 6
NormalizeProbes, 8
ReadBMAPAllSeqHeader, 9

*Topic **models**

MAT, 5
tilingSet, 12

*Topic **print**

show, tilingSet-method, 11
summary, tilingSet-method, 11

%in%, ANY, MAT-method (*MAT*), 5

%in%, ANY, tilingSet-method
(*tilingSet*), 12

BPMAPCelParser, 1, 11–13

callEnrichedRegions, 2
callEnrichedRegions-defunct
(*callEnrichedRegions*), 2
computeMATScore, 4

MAT, 5
MAT-class (*MAT*), 5
MATScore, 6

NormalizeProbes, 8, 11–13

rbind, tilingSet-method
(*tilingSet*), 12

ReadBMAPAllSeqHeader, 9

show, tilingSet-method, 11
summary, tilingSet-method, 11

tilingSet, 6, 12
tilingSet-class (*tilingSet*), 12