

rbsurv

April 20, 2011

gliomaSet

Gene expression and survival data of the patients with gliomas

Description

These data sets consist of gene expression and survival of the patients with gliomas. Note that it contains a subset of the data published in Freije et al. (2004).

Source

Freije et al. (2004). Gene Expression Profiling of Gliomas Strongly Predicts Survival, Cancer Research, 64: 6503-6510.

rbsurv.default

Robust likelihood-based survival modeling

Description

This selects survival-associated genes with microarray data.

Usage

```
## Default S3 method:
rbsurv(time, status, x, z=NULL, alpha=1, gene.ID=NULL, method="efron",
        n.iter=10, n.fold=3, n.seq=1, seed=1234, max.n.genes=nrow(x))
```

Arguments

time	a vector for survival times
status	a vector for survival status, 0=censored, 1=event
x	a matrix for expression values (genes in rows, samples in columns)
z	a matrix for risk factors
alpha	significance level for evaluating risk factors; significant risk factors included with the alpha level if $\alpha < 1$
gene.ID	a vector for gene IDs; if NULL, row numbers are assigned.

<code>method</code>	a character string specifying the method for tie handling. Choose one of "efron", "breslow", "exact". The default is "efron". If there are no tied death times all the methods are equivalent.
<code>n.iter</code>	the number of iterations for gene selection
<code>n.fold</code>	the number of partitions of samples
<code>n.seq</code>	the number of sequential runs or multiple models
<code>seed</code>	a seed for sample partitioning
<code>max.n.genes</code>	the maximum number of genes considered. If the number of the input genes is greater than the given number, it is reduced by fitting individual Cox models.
<code>...</code>	other arguments

Value

<code>model</code>	survival-associated gene model
<code>n.genes</code>	number of genes
<code>n.samples</code>	number of samples
<code>method</code>	method for tie handling
<code>covariates</code>	covariates
<code>n.iter</code>	number of iterations for gene selection
<code>n.fold</code>	number of partitions of samples
<code>n.seq</code>	number of sequential runs or multiple models
<code>gene.list</code>	a list of genes included in the models

Author(s)

HyungJun Cho, Sukwoo Kim, Soo-heang Eo, and Jaewoo Kang

References

Cho,H., Yu,A., Kim,S., Kang,J., and Hong S-M. (2009). Robust likelihood-based survival modeling for microarray gene expression Data, *Journal of Statistical Software*, 29(1):1-16. URL <http://www.jstatsoft.org/v29/i01/>.

See Also

[rbsurv](#)

rbsurv

Robust likelihood-based survival modeling

Description

This selects survival-associated genes with microarray data.

Usage

```
rbsurv(time, ...)
```

Arguments

time an object for which the extraction of model rbsurv is meaningful.
... other arguments

Author(s)

HyungJun Cho, Sukwoo Kim, Soo-heang Eo, and Jaewoo Kang

References

Cho,H., Yu,A., Kim,S., Kang,J., and Hong S-M. (2009). Robust likelihood-based survival modeling for microarray gene expression Data, *Journal of Statistical Software*, 29(1):1-16. URL <http://www.jstatsoft.org/v29/i01/>.

See Also

[rbsurv.default](#)

Examples

```
library(rbsurv)
data(gliomaSet)
x <- exprs(gliomaSet)
x <- log2(x)
time <- gliomaSet$Time
status <- gliomaSet$Status
z <- cbind(gliomaSet$Age, gliomaSet$Gender)

fit <- rbsurv(time=time, status=status, x=x, method="efron", max.n.genes=20, n.iter=10,
fit$model
```

Index

***Topic datasets**

gliomaSet, 1

***Topic models**

rbsurv, 2

rbsurv.default, 1

gliomaSet, 1

rbsurv, 2, 2

rbsurv.default, 1, 3