

sizepower

October 25, 2011

power.matched

Power Calculations for Matched-Pairs Designs in Microarray Studies

Description

This routine computes the individual power value for a matched-pairs design having n treatment units and n matched control units. This power value is the expected fraction of truly differentially expressed genes that will be correctly declared as differentially expressed by the tests.

Usage

```
power.matched(ER0, G0, absMu1, sigmad, n)
```

Arguments

| | |
|--------|---|
| ER0 | mean number of false positives. |
| G0 | anticipated number of genes in the experiment that are not differentially expressed. |
| absMu1 | absolute mean difference in log-expression between treatment and control conditions as postulated under the alternative hypothesis H1. |
| sigmad | anticipated standard deviation of the difference in log-expression between matched treatment and control units. The relation between the standard deviation of the difference (sigmad) and the experimental error standard deviation (sigma) is $\text{sigmad} = \sqrt{2} / \text{sigma}$. |
| n | the sample size for each group. |

Value

| | |
|-------|---------------------------|
| power | power. |
| psil | non-centrality parameter. |

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-power-matched050510.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>),
George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers*, ISBN 0-7923-7087-2.

Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine*, **21**:3543-3570.

See Also

[power.randomized](#), [power.multi](#), [sampleSize.randomized](#), [sampleSize.matched](#)

Examples

```
power.matched(ER0=2, G0=5000, absMu1=1, sigmad=0.4243, n=4)
```

power.multi

Power Calculations for Multiple Treatments Design with an Isolated

Description

Assume `numTrt` treatment conditions are being studied in either a completely randomized or randomized block design. Under the alternative hypothesis H_1 , one treatment is distinguished from the other `numTrt - 1` treatments by exhibiting differential expression for the gene. This computer routine calculates the individual power value for the design. This power value is the expected fraction of truly differentially expressed genes that will be correctly declared as differentially expressed by the tests.

Usage

```
power.multi(ER0, G0, numTrt, absMu1, sigma, n)
```

Arguments

| | |
|--------|--|
| ER0 | mean number of false positives. |
| G0 | anticipated number of genes in the experiment that are not differentially expressed. |
| numTrt | total number of treatment conditions. |
| absMu1 | the absolute difference in expression between the distinguished treatment and the other treatments on the log-intensity scale. |
| sigma | anticipated experimental error standard deviation of the difference in log-expression between treatments. |
| n | the sample size for each group. |

Value

| | |
|-------|---------------------------|
| power | power. |
| psi1 | non-centrality parameter. |

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-power-isolated050510.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers, ISBN 0-7923-7087-2*.

Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine, 21:3543-3570*.

See Also

[power.randomized](#), [power.matched](#), [sampleSize.randomized](#), [sampleSize.matched](#)

Examples

```
power.multi(ER0=2, G0=10000, numTrt=6, absMu1=0.585, sigma=0.3, n=8)
```

| | |
|------------------|--|
| power.randomized | <i>Power Calculation for Completely Randomized Treatment-Control Designs</i> |
|------------------|--|

Description

This routine computes the individual power value for a completely randomized design with n treatment units and n control units ($2n$ units in total). This power value is the expected fraction of truly differentially expressed genes that will be correctly declared as differentially expressed by the tests.

Usage

```
power.randomized(ER0, G0, absMu1, sigmad, n)
```

Arguments

| | |
|--------|--|
| ER0 | mean number of false positives. |
| G0 | anticipated number of genes in the experiment that are not differentially expressed. |
| absMu1 | absolute mean difference in log-expression between treatment and control conditions as postulated under the alternative hypothesis H_1 . |

| | |
|--------|--|
| sigmad | anticipated standard deviation of the difference in log-expression between treatment and control conditions. The relation between the standard deviation of the difference (sigmad) and the experimental error standard deviation (sigma) is $\text{sigmad} = \sqrt{2} / \text{sigma}$. |
| n | the sample size for each group. |

Value

| | |
|-------|---------------------------|
| power | power. |
| psil | non-centrality parameter. |

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-power-trt-cont050510.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

- Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers*, ISBN 0-7923-7087-2.
- Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine*, **21**:3543-3570.

See Also

[power.matched](#), [power.multi](#), [sampleSize.randomized](#), [sampleSize.matched](#)

Examples

```
power.randomized(ER0=2, G0=5000, absMu1=1, sigmad=0.5657, n=8)
```

sampleSize.matched *Sample Size Calculation for Matched-Pairs Designs in Microarray Studies*

Description

This routine computes the sample size n required to achieve a specified power level for a matched-pairs design in which differential expression between n treatment units and n matched control units is of interest. The total number of experimental units for the study is $2n$.

Usage

```
sampleSize.matched(ER0, G0, power, absMu1, sigmad)
```

Arguments

| | |
|--------|--|
| ER0 | mean number of false positives. |
| G0 | anticipated number of genes in the experiment that are not differentially expressed. |
| power | specified power level for an individual gene, which represents the expected proportion of differentially expressed genes that will be declared as such by the tests. |
| absMul | absolute mean difference in log-expression between treatment and control units as postulated under the alternative hypothesis H1. |
| sigmad | anticipated standard deviation of the difference in log-expression between matched treatment and control units. |

Value

| | |
|---|---|
| n | sample size for each group. |
| d | statistical difference between treatment and control conditions under H1 (i.e. $d = \text{absMul} / \text{sigmad}$). |

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-sampsize-matched050510.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

- Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers, ISBN 0-7923-7087-2*.
- Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine, 21*:3543-3570.

See Also

[power.randomized](#), [power.matched](#) [power.multi](#), [sampleSize.randomized](#)

Examples

```
sampleSize.matched(ER0=1, G0=2000, power=0.9, absMul=1, sigmad=0.5)
```

sampleSize.randomized

Sample Size Calculation for Completely Randomized Treatment-Control

Description

For any specified power, this routine computes the required sample size n for completely randomized designs in which differential expression between n treatment units and n control units is of interest. The total number of experimental units for the study is $2n$.

Usage

```
sampleSize.randomized(ER0, G0, power, absMu1, sigmad)
```

Arguments

| | |
|--------|--|
| ER0 | mean number of false positives. |
| G0 | anticipated number of genes in the experiment that are not differentially expressed. |
| power | specified power level for an individual gene, which represents the expected proportion of differentially expressed genes that will be declared as such by the tests. |
| absMu1 | absolute mean difference in log-expression between treatment and control conditions as postulated under the alternative hypothesis H1. |
| sigmad | anticipated standard deviation of the difference in log-expression between treatment and control conditions. The relation between the standard deviation of the difference (<code>sigmad</code>) and the experimental error standard deviation (<code>sigma</code>) is $\text{sigmad} = \sqrt{2} / \text{sigma}$. |

Value

| | |
|----------------|---|
| <code>n</code> | sample size for each group. |
| <code>d</code> | statistical difference between treatment and control conditions under H1 (i.e. $d = \text{absMu1} / \text{sigmad}$). |

Note

Examples and explanations can be found in <http://www.biostat.harvard.edu/people/faculty/mltlee/pdf/Web-sampsize-trt-cont-050511r.pdf>.

Author(s)

Weiliang Qiu (<weiliang.qiu@gmail.com>), Mei-Ling Ting Lee (<meilinglee@sph.osu.edu>), George Alex Whitmore (<george.whitmore@mcgill.ca>)

References

- Lee, M.-L. T. (2004). Analysis of Microarray Gene Expression Data. *Kluwer Academic Publishers, ISBN 0-7923-7087-2*.
- Lee, M.-L. T., Whitmore, G. A. (2002). Power and sample size for DNA microarray studies. *Statistics in Medicine, 21*:3543-3570.

See Also

[power.randomized](#), [power.matched](#), [power.multi](#), [sampleSize.matched](#)

Examples

```
sampleSize.randomized(ER0=1, G0=2000, power=0.9, absMu1=1, sigmad=0.566)
```

Index

*Topic **design**

- power.matched, 1
- power.multi, 2
- power.randomized, 3
- sampleSize.matched, 4
- sampleSize.randomized, 6

*Topic **htest**

- power.matched, 1
- power.multi, 2
- power.randomized, 3
- sampleSize.matched, 4
- sampleSize.randomized, 6

- power.matched, 1, 3–5, 7
- power.multi, 2, 2, 4, 5, 7
- power.randomized, 2, 3, 3, 5, 7

- sampleSize.matched, 2, 3, 4, 4, 7
- sampleSize.randomized, 2–5, 6