

SNPlocs.Hsapiens.dbSNP.20090506

June 9, 2011

```
SNPlocs.Hsapiens.dbSNP.20090506
      SNP locations for Homo sapiens (dbSNP BUILD 130)
```

Description

SNP locations and alleles for Homo sapiens extracted from dbSNP BUILD 130.

Usage

```
## Convenience wrappers for loading the SNP data:
getSNPcount()
getSNPlocs(seqname)

## Datasets:
data(SNPcount)
data(chr1_snplocs)
data(chr2_snplocs)
data(chr3_snplocs)
data(chr4_snplocs)
data(chr5_snplocs)
data(chr6_snplocs)
data(chr7_snplocs)
data(chr8_snplocs)
data(chr9_snplocs)
data(chr10_snplocs)
data(chr11_snplocs)
data(chr12_snplocs)
data(chr13_snplocs)
data(chr14_snplocs)
data(chr15_snplocs)
data(chr16_snplocs)
data(chr17_snplocs)
data(chr18_snplocs)
data(chr19_snplocs)
data(chr20_snplocs)
data(chr21_snplocs)
data(chr22_snplocs)
```

```
data(chrX_snplocs)  
data(chrY_snplocs)
```

Arguments

seqname The name of the sequence for which to get the SNP locations.

Details

`getSNPcount` and `getSNPlocs` are convenience wrappers for loading the SNP data. `getSNPcount` returns a named integer vector containing the number of SNPs mapped to each sequence in the genome. `getSNPlocs` returns a data frame containing the RefSNP id, alleles and location for each SNP mapped to the specified sequence. The alleles is represented by an IUPAC nucleotide ambiguity code. See [?IUPAC_CODE_MAP](#) in the Biostrings package for more information.

Note

The source data files used for this package were created by NCBI on 5-6 May 2009. The SNPs in this package map the hg18 genome (NCBI Build 36.1) and therefore can be "injected" in BSgenome.Hsapiens.UCSC.hg18. See [?injectSNPs](#) in the BSgenome software package for more information.

Author(s)

H. Pages

See Also

[IUPAC_CODE_MAP](#), [injectSNPs](#)

Examples

```
getSNPcount()  
chr22snps <- getSNPlocs("chr22")  
dim(chr22snps)  
colnames(chr22snps)  
head(chr22snps)
```

Index

***Topic data** (SNPlocs.Hsapiens.dbSNP.20090506),
SNPlocs.Hsapiens.dbSNP.20090506, 1
1 chr22_snplocs
***Topic package** (SNPlocs.Hsapiens.dbSNP.20090506),
SNPlocs.Hsapiens.dbSNP.20090506, 1
1 chr2_snplocs
chr10_snplocs (SNPlocs.Hsapiens.dbSNP.20090506),
1 chr3_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr11_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr4_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr12_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr5_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr13_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr6_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr14_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr7_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr15_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr8_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr16_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr9_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr17_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chrX_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr18_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chrY_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1 chr19_snplocs
(SNPlocs.Hsapiens.dbSNP.20090506),
1
1 getSNPcount
chr1_snplocs (SNPlocs.Hsapiens.dbSNP.20090506),
(SNPlocs.Hsapiens.dbSNP.20090506), 1
1
1 getSNPlocs
chr20_snplocs (SNPlocs.Hsapiens.dbSNP.20090506),
(SNPlocs.Hsapiens.dbSNP.20090506), 1
1
chr21_snplocs injectSNPs, 2

IUPAC_CODE_MAP, 2

SNPcount

(*SNPlocs.Hsapiens.dbSNP.20090506*),

[1](#)

SNPlocs.Hsapiens.dbSNP.20090506,

[1](#)

SNPlocs.Hsapiens.dbSNP.20090506-package

(*SNPlocs.Hsapiens.dbSNP.20090506*),

[1](#)