

# ggtut

March 23, 2012

---

c17imp

*SnpMatrix instance with imputations from 1KG to CEU chr 17*

---

## Description

SnpMatrix instance with imputations from 1KG to CEU chr 17

## Usage

```
data(c17imp)
```

## Format

The format is:

Formal class 'SnpMatrix' [package "snpStats"] with 1 slots

..@ .Data: raw [1:90, 1:175170] 77 d6 77 2d ...

.. ..- attr(\*, "dimnames")=List of 2

.. ...\$. : chr [1:90] "NA06985" "NA06991" "NA06993" "NA06994" ...

.. ...\$. : chr [1:175170] "chr17:1869" "rs17055023" "rs6565733" "rs34663111" ...

## Source

uses rules.n43

## Examples

```
library(snpStats)
data(c17imp)
c17imp
```

g17rngsnr

*ranges of genes on chrom 17 (uses hg18)***Description**

ranges of genes on chrom 17 (uses hg18)

**Usage**

data(g17rngsnr)

**Format**

The format is:

Formal class 'GRanges' [package "GenomicRanges"] with 6 slots

..@ seqnames :Formal class 'Rle' [package "IRanges"] with 4 slots

.. ..@ values : Factor w/ 1 level "chr17": 1

.. ..@ lengths : int 475

.. ..@ elementMetadata: NULL

.. ..@ metadata : list()

..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots

.. ..@ start : int [1:475] 39509647 50333051 46294586 77439016 38229969 37098653 45133689

58981554 44263371 17349602 ...

.. ..@ width : int [1:475] 46894 61277 5753 3743 19335 2772 6839 43820 33858 86118 ...

.. ..@ NAMES : chr [1:475] "GI\_21237796-A" "GI\_4885638-S" "GI\_22035666-S" "GI\_17572809-S" ...

.. ..@ elementType : chr "integer"

.. ..@ elementMetadata: NULL

.. ..@ metadata : list()

..@ strand :Formal class 'Rle' [package "IRanges"] with 4 slots

.. ..@ values : Factor w/ 3 levels "+","-", "\*": 3

.. ..@ lengths : int 475

.. ..@ elementMetadata: NULL

.. ..@ metadata : list()

..@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots

.. ..@ rownames : NULL

.. ..@ nrows : int 475

.. ..@ listData :List of 1

.. .. .\$ probeid: chr [1:475] "GI\_21237796-A" "GI\_4885638-S" "GI\_22035666-S" "GI\_17572809-S" ...

.. ..@ elementType : chr "ANY"

.. ..@ elementMetadata: NULL

.. ..@ metadata : list()

..@ seqinfo :Formal class 'Seqinfo' [package "GenomicRanges"] with 3 slots

.. ..@ seqnames : chr "chr17"

.. ..@ seqlengths : int NA

.. ..@ is\_circular: logi NA

..@ metadata : list()

**Examples**

```
data(g17rngsnr)
g17rngsnr
## maybe str(g17rngsnr) ; plot(g17rngsnr) ...
```

---

ggtut-package

*support for tutorial on genetics of gene expression ISMB 2011*

---

**Description**

various resources for genetics of expression with R/bioc

**Details**

Package:

Version:

Suggests:

Depends:

License:

LazyLoad:

Built:

CPS17 is a cisProxScores instance, as is PERMCPS17, serialized to reduce vignette computation time. SVA1 is an sva() o

Index:

observed17ceu obtain access to ff-based archives of eQTL test results

hg18tx a function that returns a reference to a transcriptDb instance for hg18

getFixedBFL retrieve a BamFileList of 41 small RNA seq extracts with nicely formatted HapMap names

Further information is available in the following vignettes:

tut11 (source, pdf)

**Author(s)**

VJ Carey <stvjc@channing.harvard.edu>

Maintainer: VJ Carey <stvjc@channing.harvard.edu>

**Examples**

```
library(ggtut)
o17 = observed17ceu()
o17
ch41 = getFixedBFL()
ch41
```

---

observed17ceu	<i>obtain access to ff-based archives of eQTL test results</i>
---------------	--

---

### Description

obtain access to ff-based archives of eQTL test results

### Usage

```
observed17ceu()
onePerm17ceu()
```

### Details

The underlying ff data were obtained as follows

```
dropMonomorphies = function(sms) { sl = smList(sms) sums = lapply(sl,
col.summary) todrop = lapply(sums, function(x) which(x[, "RAF"]==1
| x[, "RAF"]==0)) for (i in 1:length(todrop)) if (length(todrop[[i]])>0)
sl[[i]] = sl[[i]][,-todrop[[i]]] sms@smlEnv$smList = sl sms } library(GGdata)
library(multicore) data(eset) ex library(genefilter) exfl = nsFilter(ex)
length(get("17", revmap(illuminaHumanv1CHR))->ZZ) kp = intersect(ZZ,
featureNames(exfl[[1]])) c17 = getSS("GGdata", "17", renameChrs="chr17",
probesToKeep=kp, wrapperEndo=dropMonomorphies) fldm = eqtlTests(c17,
~male, targdir="c17c", genegran=1, geneApply=mclapply) save(fldm, file="fldm.rda")
set.seed(1234); permfldm = eqtlTests(permEx(c17), ~male, targdir="c17c_perm",
genegran=1, geneApply=mclapply) save(permfldm, file="permfldm.rda")
```

### Value

an instance of `eqtlTestsManager-class`

### Examples

```
f1 = observed17ceu()
f1
f1@call
f1[ rsid("rs7502145"), probeId("GI_10190685-S")]
pfl = onePerm17ceu()
pfl[ rsid("rs7502145"), probeId("GI_10190685-S")]
```

---

rules.n43	<i>snpStats imputation rules instance</i>
-----------	---

---

### Description

snpStats imputation rules instance

### Usage

```
data(rules.n43)
```

**Format**

The format is:  
 Formal class 'ImputationRules' [package "snpStats"] with 1 slots  
 ..@ .Data:List of 470806  
 .. ..\$: NULL  
 .. ..\$:List of 4  
 .. .. ..\$ maf : num 0.128  
 .. .. ..\$ r.squared: num 0.901  
 .. .. ..\$ snps : chr [1:4] "rs11654695" "rs9789059" "rs8073513" "rs7225087"  
 .. .. ..\$ hap.probs: num [1:32] 0.00 1.02e-21 0.00 1.45e-07 1.52e-07 ...  
 .. ..\$:List of 4  
 .. .. ..\$ maf : num 0.163  
 .. .. ..\$ r.squared: num 0.802  
 .. .. ..\$ snps : chr [1:4] "rs11654695" "rs12449775" "rs8078223" "rs9907102"  
 .. .. ..\$ hap.probs: num [1:32] 0.02863 0.0253 0.00342 0.07866 0.01717 ...  
 .. ..\$:List of 4  
 .. .. ..\$ maf : num 0.116  
 .. .. ..\$ r.squared: num 0.881  
 .. .. ..\$ snps : chr [1:4] "rs11654695" "rs9789059" "rs8073513" "rs4968164"  
 .. .. ..\$ hap.probs: num [1:32] 0.00 1.96e-13 0.00 4.91e-05 1.05e-06 ...  
 .. ..\$: NULL  
 .. .. [list output truncated]

**Examples**

```
library(snpStats)
data(rules.n43)
rules.n43[1:4]
## maybe str(rules.n43) ; plot(rules.n43) ...
```

---

snpgr17

*SNP locations for chr 17*


---

**Description**

SNP locations for chr 17

**Usage**

```
data(snpgr17)
```

**Format**

The format is:  
 Formal class 'GRanges' [package "GenomicRanges"] with 6 slots  
 ..@ seqnames :Formal class 'Rle' [package "IRanges"] with 4 slots  
 .. ..@ values : Factor w/ 1 level "chr17": 1  
 .. ..@ lengths : int 316396  
 .. ..@ elementMetadata: NULL  
 .. ..@ metadata : list()

```

..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
.. ..@ start : int [1:316396] 6934 7214 7242 8611 11743 11830 13546 13905 14122 14300 ...
.. ..@ width : int [1:316396] 1 1 1 1 1 1 1 1 1 1 ...
.. ..@ NAMES : chr [1:316396] "rs1106176" "rs6420494" "rs6420495" "rs62054996" ...
.. ..@ elementType : chr "integer"
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ strand :Formal class 'Rle' [package "IRanges"] with 4 slots
.. ..@ values : Factor w/ 3 levels "+","-","*": 3
.. ..@ lengths : int 316396
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots
.. ..@ rownames : NULL
.. ..@ nrows : int 316396
.. ..@ listData : Named list()
.. ..@ elementType : chr "ANY"
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ seqinfo :Formal class 'Seqinfo' [package "GenomicRanges"] with 3 slots
.. ..@ seqnames : chr "chr17"
.. ..@ seqlengths : int NA
.. ..@ is_circular: logi NA
..@ metadata : list()

```

### Examples

```

data(snpgr17)
snpgr17
## maybe str(snpgr17) ; plot(snpgr17) ...

```

# Index

## \*Topic **datasets**

c17imp, 1  
g17rngsnr, 2  
rules.n43, 4  
snpgr17, 5

## \*Topic **models**

observed17ceu, 4

## \*Topic **package**

ggtut-package, 3

bestGenesPerSNP\_obs  
(ggtut-package), 3

bestGenesPerSNP\_perm  
(ggtut-package), 3

c17imp, 1  
CPS17 (ggtut-package), 3

eqtlTestsManager-class, 4

g17rngsnr, 2  
getFixedBFL (ggtut-package), 3  
ggtut (ggtut-package), 3  
ggtut-package, 3

hg18tx (ggtut-package), 3

observed17ceu, 4  
onePerm17ceu (observed17ceu), 4

PERMCPS17 (ggtut-package), 3  
permsb1 (ggtut-package), 3

rsb2\_list (ggtut-package), 3  
rsb2\_perm\_list (ggtut-package), 3  
rules.n43, 4

sb1 (ggtut-package), 3  
snpgr17, 5  
SVA1 (ggtut-package), 3

tr17\_1\_9 (observed17ceu), 4  
tr17\_1\_9\_perm (observed17ceu), 4