

Package ‘AnalysisPageServer’

October 8, 2015

Type Package

Title A framework for sharing interactive data and plots from R through the web.

Version 1.0.0

Date 2015-04-15

Author Brad Friedman <friedman.brad@gene.com>, Adrian Nowicki, Hunter Whitney <hunter@hunterwhitney.com>, Matthew Brauer <brauer.matthew@gene.com>

Maintainer Brad Friedman <friedmab@gene.com>

Description AnalysisPageServer is a modular system that enables sharing of customizable R analyses via the web.

License Artistic-2.0

LazyLoad yes

Imports log4r, tools, rjson, Biobase, graph

Suggests RUnit, XML, SVGAnnotation, knitr

Enhances Rook (>= 1.1), fork, FastRWeb, ggplot2

VignetteBuilder knitr

biocViews GUI, Visualization, DataRepresentation

NeedsCompilation yes

R topics documented:

add.event	4
add.event.handler	5
analysis.link	6
analysis.page.link	7
analysis.page.of.current.app	8
annotate.analysis.page.svg	9
annotate.data.frame	10
apache.httpd.conf	11
aps.dataset.divs	12

aps.one.dataset.div	13
aps.urlEncode	14
array.param	15
autosignal.on.bloated.memory	16
bind.memory.checker	17
bool.param	18
build.service	19
check.memory	20
check.same.svg	21
check.signal	21
checkPackageInstalled	22
checkRookForkForVignettes	23
clear.event.handlers	24
client.ip	25
combobox.param	25
compound.param	27
config.js	28
copy.front.end	29
current.app	30
custom.body.attr	30
custom.body.html	31
custom.html.headers	31
data.frame.to.json	32
data.frame.to.list	33
default.param	34
default.param.set	35
default.service.paramset	35
default.stylesheets	36
dieIfWindows	37
dies.ok	37
embed.APS.dataset	38
encode.datanode	39
eval.within.time	40
event.names	42
execute.handler	42
file.param	44
get.APS.outdir	45
get.page	46
getTraceback	47
has.event	47
has.page	48
ignore.lots.of.stuff	49
is.registry	50
kill.process	50
known.param.sizes	51
lives.ok	51
make.standard.ids	52
new.analysis.page	53

new.datanode.array	56
new.datanode.html	56
new.datanode.plot	57
new.datanode.simple	58
new.datanode.table	59
new.event.registry	60
new.FastRWeb.analysis.page.run	60
new.registry	63
new.response	64
new.rook.analysis.page.app	65
pages	66
param.set	67
persistent.param.dependencies	68
persistent.params	69
platformIsWindows	70
protect.rapache.memory	70
rapache.app.from.registry	71
rapache.trig.app	73
register.page	74
remove.event	75
remove.old.files	76
reset.APS.outdir	76
rook.analysis.page.server.landing.page	77
search.replace	78
select.param	79
service.link	80
set.APS.outdir	80
setup.APS.knitr	81
simple.param	82
sine.handler	84
slider.param	85
startRookAnalysisPageServer	86
static.analysis.page	87
static.analysis.page.query.string	90
test.package	91
trig.registry	91
trigger.event	92
tryKeepConditions	93
tryKeepTraceback	94
uniquify.ids.in.svg.files	95
urlDecode	96
urlEncode	97
validate.array.param.value	97
validate.bool.param.value	98
validate.combobox.param.value	99
validate.compound.param.value	99
validate.file.param.value	100
validate.labeled.param.value	101

validate.param.list	102
validate.param.value	102
validate.select.param.value	103
validate.text.param.value	104
vwc.conditions	105
vwc.error	106
vwc.error.condition	106
vwc.error.traceback	107
vwc.is.error	108
vwc.messages	109
vwc.messages.conditions	109
vwc.messages.tracebacks	110
vwc.n	111
vwc.n.messages	112
vwc.n.warnings	112
vwc.tracebacks	113
vwc.value	114
vwc.warnings	115
vwc.warnings.conditions	115
vwc.warnings.tracebacks	116

Index **118**

add.event	<i>add.event</i>
-----------	------------------

Description

Add a new event to a registry

Usage

```
add.event(registry, event, overwrite = FALSE)
```

Arguments

registry	EventRegistry
event	String. Name for the Event.
overwrite	Logical. If the Event already exists, should I overwrite it? If TRUE then yes, without warning. If FALSE (default) then no, throw an error.

Details

Add a new event to a registry. If an Event of that name already exists then if `overwrite` is not set then an error is thrown, and if `overwrite` is set then the contents of the old Event are simply replaced. Use `add.handler` to add a handler to an existing Event.

Value

Nothing good.

Author(s)

Brad Friedman

Examples

```
r <- new.event.registry()
has.event(r, "mouseclick")
add.event(r, "mouseclick")
has.event(r, "mouseclick")
```

`add.event.handler` *add.event.handler*

Description

Add a Handler to an Event

Usage

```
add.event.handler(registry, event, handler)
```

Arguments

registry	EventRegistry
event	String. Name of the Event
handler	Function. The new Handler to add to the Event.

Details

A Handler is any function to be called when the event is triggered. If the return value of the Handler has a "CatchEvent" attribute which is TRUE then the event will be caught and not bubble to the next handler, and the "CatchEvent" attribute will be stripped before returning the value to the triggering context.

If the Event does not yet exist an error is thrown.

Value

Nothing good.

Author(s)

Brad Friedman

Examples

```
r <- new.event.registry()
add.event(r, "mouseclick")
add.event.handler(r, "mouseclick", function(x, y) message("Mouse clicked at coordinates (", x, ", ", y, ")"))
trigger.event(r, "mouseclick", x = 30, y = 50)
```

analysis.link	<i>analysis.link</i>
---------------	----------------------

Description

Build a URL to run an analysis on the server

Usage

```
analysis.link(page, params = list(), app.base.url, width = 9, height = 7,
  device = "svg", include.plot.params = TRUE)
```

Arguments

page	Name of page
params	List of parameter values (as R objects—this function will encode them). Default: list() (no parameters).
app.base.url	Base URL for application. This is usually the prefix in which the app landing HTML page is found.
width	Width parameter for graphics devices. Normally this is in inches, although it depends on exactly how you set up your application. Default: 9. Ignored if include.plot.params = FALSE
height	Height parameter for graphics devices. Normally this is in inches, although it depends on exactly how you set up your application. Default: 7. Ignored if include.plot.params = FALSE
device	Device to use for plotting. Default: "svg". (This is going to be sent to the server, not run in the same process as this function. It would be ignored if the page was built with no.plot = TRUE.) Ignored if include.plot.params = FALSE
include.plot.params	Boolean, default TRUE. If TRUE then include the width, height, device and textarea_wrap parameters in the URL. Otherwise omit them.

Details

Unlike [analysis.page.link](#) this is not a URL to open in the web browser, but rather the kind of URL used internally by the front end for its AJAX request to the server to perform an analysis, or retrieve the analyses as web services.

Value

URL

Author(s)

Brad Friedman

analysis.page.link *app.link*

Description

Link into the app in a particular state

Usage

```
analysis.page.link(page, params = list(), submit = TRUE, relative = "")
```

Arguments

page	AnalysisPage object. The name will be extracted from this object and its AnalysisPageParamSet will be used to validate the params argument. Or, you can provide a character string. Then you won't get the parameter value checking for free but you will get the page name.
params	Named list of parameter values. If page is an AnalysisPage then they will be validated using the parameter set of that page.
submit	If submit is true then turn on a flag that says that the analysis should be submitted. Otherwise the link will open the primary parameter area. It is an error to supply params if submit = FALSE (this may be allowed in the future, but right now it is not supported.). Default: TRUE
relative	String. This string will be prepended to the relative URL beginning with "?". Default is empty string, so you would get something like "#page/2way/...". If you gave, for example "http://research.gene.com/expressionplot/app.html" then you would get "http://research.gene.com/expressionplot/app.html#page/2way/...". In RApache context the Global variable SERVER\$headers_in\$Referer is very useful for this.

Details

It is possible to encode the application state into a URL which will then be executed by the front end. There are 2 parts to the state, and each is supplied as one argument to this function (which then becomes one URL-encoded parameter in the link)

"page" The name of the page within the app, such as "2way"

"params" A subset of parameters and their values, already filled out

Value

A relative URL beginning with "#", or a full URL if `relative` is provide

Author(s)

Brad Friedman

Examples

```
analysis.page.link("mypage", params=list(foo=1))
```

```
analysis.page.of.current.app
```

Retrieve an Analysis page from the current app

Description

If the current app (as returned by `current.app`) has a page of the given name then it is returned. If the current app can't be found, or if it does not have such a page, then NULL is returned.

Usage

```
analysis.page.of.current.app(page)
```

Arguments

`page` String, name of desired page.

Value

AnalysisPage, or NULL

Author(s)

Brad Friedman

annotate.analysis.page.svg

annotate.analysis.page.svg

Description

Annotate an AnalysisPage SVG plot

Usage

```
annotate.analysis.page.svg(svg.filename, x, y, ids, group.lengths = length(x),
  class.name = "plot-point", start = 0, uniquify.ids.suffix = NULL,
  verbose = FALSE)
```

Arguments

svg.filename	Path to SVG file
x	Vector of x values
y	Vector of y values (same length as x)
ids	Vector of ids (same length as x)
group.lengths	Positive integer vector summing to x (an ordered partition of length(x)) giving length of contiguous groups of elements. Each integer must be at least 3. The search will be for contiguous elements, then continue where the last one left off, possibly after a gap. Default: length(x), look for a single contiguous block.
class.name	Class name to apply to points (default: "plot-point")
start	This is a 0-based integer. It is an offset of where to start looking for the plot elements. Default is 0, to start at the beginning. The meaning of the index after that is not exposed to the interface, however this function returns numbers that you can then use to "continue looking where you left off".
uniquify.ids.suffix	NULL or a string. If NULL then do not modify the identifiers in the SVG file. If a string, then call uniquify.ids.in.svg.files to modify the "glyph" and "clip" identifiers, using this word as the suffixes parameter).
verbose	Logical. Default, FALSE. Passed through (as integer) to C++

Details

The plot points are found by looking for a sequence of points whose x and y coordinates correlation ≥ 0.999 with the query x and y vectors.

Then each is tagged with class.name, and with the corresponding ID from the vector.

The file is overwritten.

Value

Integer, the "next start" position, or where to start looking to continue after this stretch. (Invisibly).
If no match was found then returns NULL.

Author(s)

Brad Friedman

annotate.data.frame *annotate.data.frame*

Description

Clean up and annotate a data frame

Usage

```
annotate.data.frame(obj, required.fields = c("x", "y"), signif.digits = 3)
```

Arguments

<code>obj</code>	data.frame or AnnotatedDataFrame: the return value of a handler.
<code>required.fields</code>	Character vector of required fields. Default: <code>c("x", "y")</code> . You could set to <code>character(0)</code> , for example, if you don't want to force a check that "x" and "y" be present.
<code>signif.digits</code>	Integer, default 3, giving the number of significant digits to which "numeric" (but not "integer") columns should be rounded, using <code>signif()</code> . NULL means to not round at all.

Details

The `obj` argument should be a return value from a handler, either a data.frame or an annotated data.frame. If a data.frame then an AnnotatedDataFrame is built. Then three special fields in `varMetadata` are checked: "labelDescription" and "type"

If any is missing then they are built as follows:

labelDescription labelDescription always exists, but sometimes it has NA entries. In those cases it is set to the name of the variable (rowname of the varMetadata). This is the one that you most likely might want to set yourself.

type If not present, then it is calculated from the `pData` like this: `sapply(1apply(pData(obj), is), "[", 1)`. This will become one of "integer", "factor", "logical", "numeric" or "character", and the front end should know how to render these.

Columns that have type "numeric" (but not "integer") are rounded to the given number of significant digits.

Also, this throws an error if "x" or "y" field is missing

Value

AnnotatedDataFrame

Author(s)

Brad Friedman

apache.httpd.conf	<i>apache.httpd.conf</i>
-------------------	--------------------------

Description

Generate httpd.conf file for RApache deployment

Usage

```
apache.httpd.conf(driver.path, app.location, config.js.path,
  front.end.dir = system.file("htdocs/client/dist-aps", package =
    "AnalysisPageServer"), mod.R.path, skip.checks = FALSE)
```

Arguments

driver.path	Path to driver. Must contain call to <code>add.handlers.to.global()</code> .
app.location	Location from which app will be deployed (e.g. <code>"/myapp"</code> to make the URL start <code>"http://myserver.com/myapp"</code>).
config.js.path	Path to modified <code>config.js</code> file. This would have been generated with a call to config.js .
front.end.dir	Path to front end directory content. An alias will be set up to serve it directly from this location. Default is from the installed R package (found via <code>system.file</code>).
mod.R.path	Path to <code>mod_R.so</code>
skip.checks	Boolean, default FALSE. If TRUE then don't check for file existence or for the presence of <code>"add.handlers.to.global"</code> in the startup script.

Details

Generate httpd.conf file for RApache deployment. This returns a charvec of lines of the files. You still have to call `writelnLines`. See the `ApacheDeployment` vignette for more information.

Value

Charvec

Author(s)

Brad Friedman

aps.dataset.divs *aps.dataset.divs*

Description

Generate HTML for multiple DIV elements corresponding to a paths list

Usage

```
aps.dataset.divs(paths.list, show.sidebar = rep(TRUE, length(paths.list)),
  show.table = rep(TRUE, length(paths.list)),
  extra.html.class = rep(list(character()), length(paths.list)),
  extra.div.attr = rep(list(NULL), length(paths.list)))
```

Arguments

paths.list	List of lists. The outer list corresponds to data sets and the inner lists have names in \$plot and \$data, giving relative paths to the SVG and JSON files (OK to omit one). Or a list with a \$paths.list element, which would be used (this lets you pass the return value of static.analysis.page directly to this function).
show.sidebar	Logical vector of same length as paths.list to pass through corresponding elements to aps.one.dataset.div . Default: all TRUE.
show.table	Logical vector of same length as paths.list to pass through corresponding elements to aps.one.dataset.div . Default: all TRUE.
extra.html.class	List (of charvecs) of same length as paths.list to pass through corresponding elements to aps.one.dataset.div . Default: All empty charvec.
extra.div.attr	List (of named charvecs or NULLs) of same length as paths.list to pass through corresponding elements to aps.one.dataset.div . Default: all NULL.

Details

This function is meant to work with the return value of [static.analysis.page](#). That function returns an object with a \$paths.list element which contains the relative paths to each of the plots and datasets. You pass that through as the first argument to this function and it will make divs corresponding to those plots. The other arguments are either vectors or lists of corresponding lengths to pass through to [aps.one.dataset.div](#).

Value

Charvec of HTML divs corresponding to datasets in paths.list.

Author(s)

Brad Friedman

aps.one.dataset.div *aps.one.dataset.div*

Description

Create HTML for a div element to contain one AnalysisPageServer data set

Usage

```
aps.one.dataset.div(svg.path = NULL, data.path = NULL,  
  show.sidebar = TRUE, show.table = TRUE, extra.html.class = character(),  
  extra.div.attr = NULL)
```

Arguments

svg.path	Path (could be relative to index.html) to (annotated) SVG file. NULL to only have data table and no picture.
data.path	Path (could be relative to index.html) to JSON file containing data set. NULL to only have SVG and no table
show.sidebar	Boolean. If TRUE (default) then show sidebar. If FALSE then omit it.
show.table	Boolean. If TRUE (default) then show sidebar. If FALSE then omit it.
extra.html.class	These are extra classes to add to the div. This could be used for whatever extended purpose you want, like extra styling or logic. Should be an unnamed charvec. Default is character(), just use the basic required for APS.
extra.div.attr	These are extra attributes to add to the div. For example you could add an id attribute. It should be a named charvec, or NULL (default) to not anything extra beyond that required for APS.

Details

Create HTML for a div element to contain one AnalysisPageServer data set. This function does not created, modify, or even check for existence of the SVG and JSON files. You provide paths and this function just includes those paths, however awful, in the HTML returned.

Value

HTML string

Author(s)

Brad Friedman

See Also

[aps.dataset.divs](#), a convenience wrapper for this function to create multiple divs at once.

aps.urlEncode

aps.urlEncode

Description

urlEncode all the strings in a character vector

Usage

```
aps.urlEncode(vec)
```

Arguments

vec Vector to encode. Will be coerced to character.

Details

The urlEncode function supplied by RApache has a few behaviors I don't expect. First, it requires only character arguments, so urlEncode(1) throws an exception. Second, it dies on the empty string.

This function is a wrapper for RApache's urlEncode that handles all these cases. It might later be replaced with another implementation, but the interface will stay. (The "aps" stands for AnalysisPageServer.)

Value

charvec of same length, with encoded strings

Author(s)

Brad Friedman - Regular

Examples

```
aps.urlEncode(1)
aps.urlEncode("")
aps.urlEncode("foo/bar")
```

array.param	<i>array.param</i>
-------------	--------------------

Description

Create an Array AnalysisPageParam

Usage

```
array.param(..., prototype, start = 1, min = 0, max = Inf)
```

Arguments

...	Passed through to simple.param . This includes at least "name", optionally "label" and "description". but not "type" (which is set to "array") or "value" (which is set to empty string, but ignored anyway, since the prototype parameter will have its own value).
prototype	A single AnalysisPageParam that is the prototype for each of the elements in the array. Note that while only one param is allowed, it could potentially be either a compound or another array parameter.
start	The starting length of the array that should be rendered
min	The minimum allowed length of the array. Buttons to remove elements should be de-activated below this level (default 0).
max	The maximum allowed length of the array. Buttons to add elements should be de-activated above this level (default Inf).

Details

An array AnalysisPageParam is a way of having a single parameter with multiple repetitions of some other (fixed) parameter type. The starting length, as well as minimum and maximum allowable lengths, are provided. If `min != max` then the front end should render some widget to add/remove elements.

By combining with `compound.param` a fairly complex data structure can now be specified.

Value

AnalysisPageParam of type "array"

Author(s)

Brad Friedman

Examples

```
one.gene <- simple.param(name="gene", label="Gene Symbol")
gene.set <- array.param(name="geneset", prototype=one.gene)
```

autosignal.on.bloated.memory
autosignal.on.bloated.memory

Description

Send signal to self on BloatedMemory

Usage

```
autosignal.on.bloated.memory(events, signal = tools::SIGUSR1,  
    pid = Sys.getpid(), logger = NULL, event.name = "BloatedMemory")
```

Arguments

events	EventRegistry object
signal	Signal to throw. Default is SIGUSR1 (defined in tools package). Normally this elicits similar behavior to SIGINT however when running inside Apache it lets the worker process finish the current request before killing itself.
pid	Process ID to which the signal should be sent. Default: Sys.getpid(), the current process. (If you provide something else it is no longer really an autosignal, just a signal).
logger	log4r object, optional
event.name	Name of event to listen for. Default: "BloatedMemory"

Details

Have the process send a signal to itself when BloatedMemory event is triggered.

Value

Nothing

Note

This attaches a listener—it does not actually do anything until the BloatedMemory event is triggered, if ever.

Author(s)

Brad Friedman

bind.memory.checker *bind.*

Description

Bind the memory checker to the FinishAnalysis event

Usage

```
bind.memory.checker(app, max.mb, app.event = "FinishAnalysis",  
memory.event = "BloatedMemory")
```

Arguments

app	AnalysisPageRApacheApp
max.mb	Memory threshold for triggering BloatedMemory, in Megabytes. Required.
app.event	Name of existing event on which the new memory check listener should be registered. Default: "FinishAnalysis".
memory.event	Name of event to fire in case of memory usage above threshold. Default: "BloatedMemory".

Details

You supply an AnalysisPageRApacheApp. It also has a FinishAnalysis event. I add a new event (by default called BloatedMemory), and also a listener for FinishAnalysis, which calls [check.memory](#) each time FinishAnalysis is triggered. (this will then trigger BloatedMemory if memory usage is above threshold). Although the BloatedMemory event would now be triggered, unless a listener is attached to **it** nothing special will happen. (See [autosignal.on.bloated.memory](#) for this.)

Value

Nothing of note.

Author(s)

Brad Friedman

See Also

[check.memory](#), [autosignal.on.bloated.memory](#)

<code>bool.param</code>	<i>bool.param</i>
-------------------------	-------------------

Description

Build a boolean `AnalysisPageParam`

Usage

```
bool.param(...)
```

Arguments

... Passed through to [simple.param](#). This includes at least "name", and optionally "label", "description" and "value" (which should be either TRUE or FALSE), but not "type".

Details

Build a boolean `AnalysisPageParam`. This is probably rendered as a checkbox. The value returned to the server should be either JSON "true" (corresponding to checked) or JSON "false".

If you do not provide a value (or if you provide `value=""`, which is what happens in the parent constructor `simple.param` when you don't provide a value) then the default will be FALSE.

Value

An `AnalysisPageParam`

Author(s)

Brad Friedman

Examples

```
show.ids <- bool.param("show_ids", label="Show IDs", description="Show sample IDs on the plot", value=TRUE)
```

build.service	<i>build.service</i>
---------------	----------------------

Description

Build an AnalysisPage service

Usage

```
build.service(handler, param.set = default.service.paramset(handler),
  annotate.plot = FALSE, annotate.data.frame = FALSE, no.plot = TRUE,
  service = TRUE, skip.checks = TRUE, ...)
```

Arguments

handler	The handler function to convert
param.set	AnalysisPageParamSet for the handler. Default: <code>default.service.paramset(handler)</code>
annotate.plot	Default: FALSE
annotate.data.frame	Default: FALSE
no.plot	Default: TRUE
service	Default: TRUE
skip.checks	Default: TRUE. This is passed through to new.analysis.page and should normally not be modified. (we don't check services because they are not required to provide default arguments.)
...	Further arguments to pass to new.analysis.page

Details

Convert a functions into an AnalysisPage service. An AnalysisPage service is an AnalysisPage with the service flag set. That means that `pages()` will not return it, so it will not be directly available through the front end. The reason to do this would normally be so that it can be used to populate a combobox or other part of the website. In practice it also means that the return value will probably not use the AnalysisPageDataNode system—it is free to return some arbitrary JSON string or other text.

It is a wrapper for [new.analysis.page](#), and passes all of its arguments through (but with different defaults now)

Value

AnalysisPage

Author(s)

Brad Friedman

See Also

[new.analysis.page](#)

Examples

```
poem.file <- system.file("examples/in-a-station-of-the-metro.html", package="AnalysisPageServer")
poem.html <- readLines(poem.file, warn = FALSE)
poem <- build.service(function() {
  new.response(paste0(poem.html, "\n"),
    content.type = "text/html")
}, name = "poem")
```

check.memory

check.memory

Description

Check memory usage and trigger an event if it exceeds some threshold.

Usage

```
check.memory(events, max.mb, logger = NULL, event.name = "BloatedMemory")
```

Arguments

events	EventRegistry object
max.mb	If the total "used" memory (Ncells + Vcells) is at least this much (in Mb) then trigger the next handler.
logger	log4r object. If non-NULL then memory usage is printed there with info(). Default: NULL, don't log.
event.name	Name of the event to trigger. Default: "BloatedMemory". It is passed used.mb and max.mb arguments

Details

Call gc() to check memory, possibly print the result to STDERR, then possibly call the next handler you supply if too much memory is being used.

Value

Nothing

Author(s)

Brad Friedman

check.same.svg	<i>check.same.svg</i>
----------------	-----------------------

Description

Test that 2 SVG files have the same content

Usage

```
check.same.svg(got.lines, exp.lines, ...)
```

Arguments

got.lines	Charvec of the lines of the SVG to test
exp.lines	Charvec of the lines of the reference SVG
...	Passed through to <code>checkEquals</code> (such as test name).

Details

Test that 2 SVG files have the same content. Most differences in whitespace are ignored, as are all "id", "class" and "type" tags.

Value

As [checkEquals](#)

Author(s)

Brad Friedman

check.signal	<i>check.signal</i>
--------------	---------------------

Description

Check if an expression results in a signal being delivered

Usage

```
check.signal(expr, signo, testname, no.signal = FALSE)
```

Arguments

<code>expr</code>	The expression to evaluate
<code>signo</code>	The signal number (consider using constants like SIGUSR1 from the tools package).
<code>testname</code>	Name for this test. Default is to build from <code>signo</code> argument.
<code>no.signal</code>	Logical, to invert the sense of the test. Default, FALSE, means to test that the signal was delivered. TRUE means to test that the signal was not delivered.

Details

Check if an expression results in a signal being delivered. The signal will be caught: you can safely deliver a signal such as SIGUSR1 that would normally cause the process to die.

Value

The value of the evaluated expression, invisibly, so you can do more testing if desired.

Author(s)

Brad Friedman - Regular

`checkPackageInstalled` *Checks if a given package is installed.*

Description

Checks if a given package is installed.

Usage

```
checkPackageInstalled(pkg, version = "0.0.0", required = FALSE)
```

Arguments

<code>pkg</code>	A character string containing a package name.
<code>version</code>	A minimum version number. Default: "0.0.0" (no version requirement)
<code>required</code>	A boolean. The functions stops if set to TRUE and if the required package is not present. Default is FALSE.

Value

A boolean.

Author(s)

Cory Barr

Examples

```
checkPackageInstalled("AnalysisPageServer")
```

```
checkRookForkForVignettes  
checkRookForkForVignettes
```

Description

Check availability of Rook and fork for vignettes

Usage

```
checkRookForkForVignettes(rookforkOK)
```

Arguments

rookforkOK Provide FALSE here if you want to simulate not having valid installed copies of rook/fork, without actually having to delete them. Normally you should not supply this argument

Details

Check availability of Rook and fork for vignettes. This function is only meant to be called at the top of the ExampleServers.Rmd and InteractiveApps.Rmd vignettes. It checks that the user has Rook ≥ 1.1 and fork installed. If not, then it emits a useful message about how to install it, and that the vignette will not build with all features. It also writes functions `kill.process`, `readLines` (yes! be careful!), `startRookAnalysisPageServer` and `new.rook.analysis.page.app` in the Global namespace to avoid calling the real functions and instead just emit a short message that Rook/fork are not available. The message is also available in the global variable `no.rook.fork.msg`.

Really, you shouldn't use this function except if you are writing a new vignette.

Value

TRUE if Rook (≥ 1.1) and fork are available, otherwise FALSE.

Note

Are you sure you really want to use this function? Probably not, unless you are calling it from the top of a new vignette. Otherwise you are really asking for trouble messing up your global namespace. See Details.

Why are you still here? Didn't I tell you not to call this function?

Author(s)

Brad Friedman

`clear.event.handlers` *clear.event.handlers*

Description

Clear the Handlers list for one Event

Usage

```
clear.event.handlers(registry, event)
```

Arguments

<code>registry</code>	EventRegistry
<code>event</code>	String. Name of the Event.

Details

Clear the Handlers list for one Event. Does not remove the Event from the EventRegistry.

Value

Nothing good.

Author(s)

Brad Friedman

Examples

```
r <- new.event.registry()
add.event(r, "mouseclick")
add.event.handler(r, "mouseclick", function(x, y) message("Mouse clicked at coordinates (", x, ", ", y, ")"))
trigger.event(r, "mouseclick", x = 30, y = 50)
clear.event.handlers(r, "mouseclick")
trigger.event(r, "mouseclick", x = 30, y = 50)
```

client.ip	<i>client.ip</i>
-----------	------------------

Description

Return client IP address

Usage

```
client.ip()
```

Details

This is the "X-Forwarded-For" header, if available, and otherwise the "remote_ip" component of the global SERVER variable

Value

```
SERVER$remote_ip
```

Author(s)

Brad Friedman

Examples

```
SERVER <<- list(remote_ip = "127.0.0.1")
client.ip()
```

combobox.param	<i>combobox.param</i>
----------------	-----------------------

Description

Build a combobox AnalysisPageParam

Usage

```
combobox.param(..., uri, dependent.params, prompt = "Enter search term",
  n.param = NULL, allow.multiple = FALSE, response.type = "simple",
  persistent = NULL, extra.persistent.dependencies = NULL, delay.ms = 0)
```

Arguments

...	Passed through to simple.param . This includes at least "name", optionally "label", "description" and "value", but not "type".
uri	URI, possibly with :-prefixed parameter names. For example "/get?x=:x;y=:y" has parameters "x" and "y". (See <code>dependent.params</code> next)
<code>dependent.params</code>	A character vector whose names are parameters from the uri, and whose values are the names of other form elements.
prompt	A prompt to display in disabled style before user starts typing (for self-dependent comboboxes only). Default is "Enter search term".
n.param	The name of a parameter that controls the maximum number of search hits, if the URL has such a parameter. Default is NULL, which means it does not have a parameter. If it does have such a parameter, then 0 means to return all hits, and otherwise a positive integer will limit the number of hits returned.
<code>allow.multiple</code>	If TRUE then render search hits as checkbox group and allow multiple selections. (The function will be provided a vector of all selected values.) If the search term changes then the old values are still accumulated. If other dependent parameter changes then they are reset. Default: FALSE
<code>response.type</code>	A string. "simple" means that the response will be a simple array of strings. The "id-long_name-reason" type is a special type for search hits, where an array of hashes is returned, each hash having "id", "long_name" and "reason" components.
<code>persistent</code>	Character or NULL. If non-NULL then it is passed to the front-end. It names a variable in persistent storage that should be used to initialize the value of the parameter. The front end will provide some mechanism to change the persistent value, but until the user does so the param will be initialized from the value in the persistent space.
<code>extra.persistent.dependencies</code>	Character vector specifying names of other parameters on which this one is conditionally persistent. See arg <code>persistent.dependencies</code> in simple.param . Whatever is provided in <code>extra.persistent.dependencies</code> is taken <i>in addition to</i> with <code>unname(dependent.params)</code> . This is because if a combobox is persistent then it must be so conditional on its dependent parameters. It is an error to specify this for a non-persistent parameter.
<code>delay.ms</code>	Delay, in milliseconds, that the front-end should wait after keystrokes or paste before submitting queries. Default, 0, means no delay.

Details

Build a combobox `AnalysisPageParam`. This is a widget with both text and drop-down. However, the values in the drop-down depend on an AJAX query whose URI is built from current form element values, possibly including the current widget (namely the text typed so far). The drop-down values should be updated whenever one of the dependedent elements changes.

Value

An `AnalysisPageParam`

Author(s)

Brad Friedman

Examples

```
## Note the :query parameter is dependent on the same gene element. This makes it a type-ahead query.
gene <- combobox.param(name="gene", uri="/find_gene_id/:genome/:query/", dependent.params=c(genome="genome", c
```

compound.param	<i>compound.param</i>
----------------	-----------------------

Description

Create a Compound AnalysisPageParam

Usage

```
compound.param(..., children)
```

Arguments

...	Passed through to simple.param . This includes at least "name", optionally "label" and "description". but not "type" (which is set to "compound") or "value" (which is set to empty string, but ignored anyway, since each of the contained parameters will have its own value).
children	AnalysisPageParamSet An AnalysisPageParamSet representing all of the nested parameters

Details

A compound AnalysisPageParam is a single parameter that has multiple parts. The parts are represented by an AnalysisPageParamSet, so could be arbitrarily nested. The front end is responsible for wrapping up all of the values in a JSON hash and passing in a single value.

This can be thought of as a way of building a hash out of other parameter types.

Value

AnalysisPageParam of type "compound"

Author(s)

Brad Friedman

Examples

```
plist <- list(simple.param(name="study"), simple.param(name="comp"), simple.param("feature.type", value="gene"))
comp <- compound.param(name="comp", label="Comparison", children=param.set(plist))
```

 config.js

config.js

Description

Build Javascript configuration

Usage

```
config.js(app.prefix = "/custom/RAPS", client.r.url = file.path(app.prefix,
  "R"), client.rest.url = "",
  template.file = system.file("config-template.js", package =
  "AnalysisPageServer"), static = FALSE, parameter.collection.url = if
  (static) "" else "params", page.collection.url = if (static) "" else
  "pages")
```

Arguments

app.prefix	Prefix for the path to your application. This will be used as the value for the "history.root" parameter in the Javascript file, and also to build the default client.r.url.
client.r.url	Location of R resources. Default: file.path(app.prefix, "R").
client.rest.url	Location of Sloth REST resources. Default: "". This is a poorly documented feature that most people should ignore.
template.file	Path to template file for config.js. Default is taken from "inst" directory of AnalysisPageServer package.
static	Boolean, default FALSE. Controls the default values for parameter.collection.url and page.collection.url.
parameter.collection.url	Default: If static = TRUE then "" else "params"
page.collection.url	Default: If static = TRUE then "" else "pages"

Details

Build Javascript configuration. This function returns Javascript which can be used as the config.js file for the front-end client.

The only reason to call this directly would be to set up specialized deployments.

Value

Charvec of Javascript

Author(s)

Brad Friedman

copy.front.end	<i>copy.front.end</i>
----------------	-----------------------

Description

Copy the APS front end (HTML, CSS, JS, etc) to a web directory

Usage

```
copy.front.end(outdir, client.basedir = system.file("htdocs/client/dist-apss",  
package = "AnalysisPageServer"), include.landing.page = TRUE, ...)
```

Arguments

outdir	Target directory. This directory will contain your index.html file.
client.basedir	Path to client files. Default: <code>system.file("htdocs/client/dist-apss", package = "AnalysisPageServer")</code> . Probably should not be modified except during development work on the client.
include.landing.page	Boolean. Should I include the landing page "analysis-page-server-static.html"? Default: TRUE
...	Passed through to <code>file.copy</code> , such as <code>overwrite = TRUE</code>

Details

This makes a copy of the complete APS *static* front end (HTML, CSS, JS, etc) to a web directory.

Value

Whatever `file.copy` returns.

Author(s)

Brad Friedman

Examples

```
message("See vignette embedding.html")
```

current.app	<i>Return the currently running AnalysisPage app</i>
-------------	--

Description

Return the currently running AnalysisPage app. The way this is done is to first try to chase up the call stack and find the first environment which is an AnalysisPageRApacheApp, and return that. If that fails then it looks for app in the GlobalEnv and returns that. IF that also fails then it reutrns NULL.

Usage

```
current.app()
```

Value

Current AnalysisPageRApacheApp, or NULL if it can't be found.

Author(s)

Brad Friedman

custom.body.attr	<i>custom.body.attr</i>
------------------	-------------------------

Description

Return custom attributes required for body element

Usage

```
custom.body.attr()
```

Details

This attribute must be included in the <body> element.

Value

Name charvec of attributes for body

Author(s)

Brad Friedman

custom.body.html	<i>custom.body.html</i>
------------------	-------------------------

Description

Generate a <body> HTML line including attributes for APS

Usage

```
custom.body.html(extra.attr = NULL)
```

Arguments

extra.attr Other attributes, provided in a named charvec.

Details

Generate a <body> HTML line including attributes for APS. Your <body> element must have the special attribute returned by the [custom.body.attr\(\)](#). This function makes a line of HTML code containing that, and any other attributes you want to include. It just opens the <body> element, but does not close it.

Value

One line of HTML with a <body> element opening tag.

Author(s)

Brad Friedman

custom.html.headers	<i>custom.html.headers</i>
---------------------	----------------------------

Description

Generate HTML for custom headers to load AnalysisPageServer CSS and viewport

Usage

```
custom.html.headers(libbase.prefix = "",  
  viewport = "width=device-width, initial-scale=1.0",  
  stylesheets = default.stylesheets(), ep.svg.styles = "css/svg.css")
```

Arguments

<code>libbase.prefix</code>	Prefix where your shared CSS files will be located. Default "" will be relative to the index.html file. Otherwise you'll need to end with a "/".
<code>viewport</code>	Default: "width=device-width, initial-scale=1.0". This will be used in a <meta name="viewport"> tag.
<code>stylesheets</code>	Charvec of stylesheets to load. Default is <code>default.stylesheets()</code> .
<code>ep.svg.styles</code>	ep-svg-styles stylesheet. Default: "css/svg.css".

Details

Generate HTML for custom headers to load AnalysisPageServer CSS and viewport. To be honest I don't understand how all this works. The main thing is that it you put this stuff up top, in the header section. The only argument you should consider touching is `libbase.prefix`, if you are going to put your common libraries in a shared area instead making a copy next to each dataset.

Value

HTML string to be included in <head> section.

Author(s)

Brad Friedman

`data.frame.to.json` *data.frame.to.json*

Description

Create a JSON representation of a `data.frame`

Usage

```
data.frame.to.json(df)
```

Arguments

`df` `data.frame` to represent as a JSON

Details

We represent a `data.frame` as an hash of hashes. Factors are first coerced into characters.

The outer hash is keyed by the rownames of your `data.frame` The inner hash is keyed by the colnames of your `data.frame`

Value

JSON string

Author(s)

Brad Friedman

Examples

```
df <- data.frame(A=1:3, B=3:1, C=factor(c("foo", "bar", "foo")), row.names = c("one", "two", "three"))
## Should give the following
## '{"one":{"A":1,"B":3,"C":"foo"},"two":{"A":2,"B":2,"C":"bar"},"three":{"A":3,"B":1,"C":"foo"}}'
data.frame.to.json(df)
```

data.frame.to.list *data.frame.to.json*

Description

Create a list representation of a data.frame

Usage

```
data.frame.to.list(df)
```

Arguments

df data.frame to represent as a list

Details

We represent a data.frame as an hash of hashes. Factors are first coerced into characters.

The outer hash is keyed by the rownames of your data.frame The inner hash is keyed by the col-names of your data.frame

Value

list

Author(s)

Brad Friedman

Examples

```
df <- data.frame(A=1:3, B=3:1, C=factor(c("foo", "bar", "foo")), row.names = c("one", "two", "three"))
## Should give the following
## list(one=list(A=1, B=3, C="foo"),
##      two=list(A=2, B=2, C="bar"),
##      three=list(A=3, B=1, C="foo"))
data.frame.to.list(df)
```

default.param	<i>default.param</i>
---------------	----------------------

Description

Build a default AnalysisPageParam for one argument

Usage

```
default.param(name, prototype, ...)
```

Arguments

name	Name of the parameter
prototype	Default value on which the parameter should be built.
...	Further arguments passed to the constructor for the appropriate parameter type. For example, you can include label, description, advanced and show.if.

Details

You provide the name of the argument and default and I build an AnalysisPageParam. The magic here is as follows:

1. Named lists become compound.param, with default.param() then called recursively.
2. Unnamed lists of become array.param, with default.param() called on the first element of the list to build the prototype. The length of the list is taken as the start value. min/max default to 0/Inf. (Advanced Note: the name is copied to the sub-element)
3. Vectors of length > 1 become select.params
4. Vectors of length 0 or 1 and NULLs become simple.params

On any other type of argument it throws an error.

Value

AnalysisPageParam

Author(s)

Brad Friedman

Examples

```
default.param(name = "word", prototype = c("foo", "bar", "baz"), label = "Choose a word")
```

default.param.set *default.param.set*

Description

Build a basic ParamSet for your handler

Usage

```
default.param.set(handler)
```

Arguments

handler A function. (Typically one you are using as an AnalysisPage handler)

Details

Each argument to your handler is rendered into a simple AnalysisPageParam with the name of the argument and type "text". The idea is that you will then modify it as necessary to get more complicated widgets.

Value

AnalysisPageParamSet

Author(s)

Brad Friedman

Examples

```
f <- function(A=1, B=2) {}  
# param set with 2 form elements rendered as text inputs; something like A [_____] B [_____]
pset <- default.param.set(f)
```

default.service.paramset
 default.service.paramset

Description

Create an AnalysisPageParamSet for a service handler

Usage

```
default.service.paramset(handler)
```

Arguments

handler Handler function of service

Details

The services are not required to supply default values since they don't have to be rendered as parameters. AnalysisPageServer still wants to have a param set. It can be used, for example, to check arguments when building URLs. So we artifically provide default values of 0 for everything, so you get a bunch of simple params.

Value

AnalysisPageParamSet

Author(s)

Brad Friedman

`default.stylesheets` *default.stylesheets*

Description

Default stylesheets for HTML headers

Usage

```
default.stylesheets()
```

Details

Default stylesheets for HTML headers

Value

character vector

Author(s)

Brad Friedman

dieIfWindows	<i>Throw an error if platform is windows</i>
--------------	--

Description

Throw an error if platform is windows

Usage

```
dieIfWindows(caller = as.character(sys.call(-1))[1],
             errMsg = paste0(caller, "() does not run under windows"),
             isWindows = platformIsWindows())
```

Arguments

caller	Name of calling function. Default: <code>as.character(sys.call(-1))[1]</code>
errMsg	Error message to throw under windows. Default: <code>paste0(caller, "() does not run under windows")</code>
isWindows	Boolean, indicating if current platform is windows. Default: <code>platformIsWindows()</code> .

Value

Nothing

dies.ok	<i>dies.ok</i>
---------	----------------

Description

Test that an expression throws an error

Usage

```
dies.ok(call, regex, testname)
```

Arguments

call	An expression to evaluate
regex	A regular expression to match the error against. If omitted then don't test the exception text.
testname	A name for the test. Defaults to deparsing the call.

Details

Test that an expression throws an error.

Value

Runs one or two tests (the second test to match the error message against regex, if it was provided and if an error was successfully thrown).

Author(s)

Brad Friedman

Examples

```
dies.ok(stop("foo"), "foo", "it stops")
```

```
embed.APS.dataset      embed.APS.dataset
```

Description

Embed an APS dataset

Usage

```
embed.APS.dataset(plot, df, title, show.sidebar = TRUE, show.table = TRUE,
  extra.html.classes = character(), extra.div.attr = character(),
  svg.args = list(), eval.args = list(envir = parent.frame()),
  outdir = get.APS.outdir(), randomize.filename = TRUE, ...)
```

Arguments

<code>plot</code>	If present, then either an expression, a function, or a path to SVG file (not yet annotated). If an then the expression will be evaluated after opening a plotting device. The expression will be evaluated in the calling frame, so your local variables will be accessible, but this can be changed by modifying <code>eval.args</code> . If a function, then the function will be called with no arguments. In that case you would control the context yourself by setting the function's environment. If path to an SVG then you would have already made the plot, and that would be used. If missing then no plot is drawn—only the table is shown.
<code>df</code>	data.frame of data. If omitted, then the return value of evaluating the plotting expression or function is used (if <code>plot</code> is not a character).
<code>title</code>	Caption for plot
<code>show.sidebar</code>	Boolean, default TRUE. Set to FALSE to not show the sidebar (filtering, tagging). (This is passed through directly to aps.dataset.divs .)
<code>show.table</code>	Boolean, default TRUE. Set to FALSE to not show the data table (still available on download. (This is passed through directly to aps.dataset.divs .)
<code>extra.html.classes</code>	Charvec of extra HTML classes to include in the div. (This is embedded in a list then passed through directly to aps.dataset.divs .)

extra.div.attr	Names charvec of extra attributes to include in the div. (This is embedded in a list then passed through directly to <code>aps.dataset.divs</code> .)
svg.args	Arguments (other than filename) to pass to the <code>svg</code> function. This should be a named list. In particular, consider something like <code>list(width = 8, height=5)</code> to change the aspect ratio.
eval.args	Arguments to pass to <code>evalq</code> when evaluating your plot code. Ignored if plot is character or a function. Otherwise it should be a named list. Default is <code>list(envir = parent.frame())</code> , which means the evaluation will happen in the calling frame.
outdir	Output directory. Default: <code>get.APS.outdir()</code> , which is either "." or the directory of your <code>knit2html</code> target .html file.
randomize.filename	Passed through to <code>static.analysis.page</code> (but here the default is TRUE).
...	Passed through to <code>static.analysis.page</code> . t not overwrite, outdir, or write.client

Details

This function is meant to be called in a knitr document that is being knit with `knit2html`. It makes a few assumptions that are valid in that context.

It makes a call to `static.analysis.page` for you to annotate and write the SVG and JSON files, then emits the `<div>` element to `STDOUT`. `outdir` defaults to ".". It only does one plot/dataset at a time.

Value

Returns the div, invisibly.

Author(s)

Brad Friedman

Examples

```
message("See vignette embedding.html")
```

encode.datanode	<i>JSON-Encode an AnalysisPageDataNode for the front end</i>
-----------------	--

Description

JSON-Encode an AnalysisPageDataNode for the front end. This just calls toJSON, but before doing so it makes sure that `$warnings` will be sent as an array.

Usage

```
encode.datanode(datanode)
```

Arguments

`datanode` `AnalysisPageDataNode` or other object

Details

Mostly this function is only called once, from the `$analysis` method of an `AnalysisPageRAapacheApp`.

Value

JSON-encoded string

Author(s)

Brad Friedman

`eval.within.time` *eval.within.time*

Description

Evaluate an R expression in a fork within a given time frame

Usage

```
eval.within.time(expr, secs, dsecs = c(0.001, 0.1), time = as.difftime(secs,
  units = "secs"), verbose = FALSE, write.obj = saveRDS,
  read.obj = readRDS, make.con = tempfile, cleanup.con = function(con) if
  (file.exists(con)) unlink(con), touch.con = function(con)
  writeLines(character(), con), con.touched = file.exists,
  make.signal.con = make.con, cleanup.signal.con = cleanup.con)
```

Arguments

`expr` Expression to evaluate

`secs` Seconds to timeout. Example: 10. Ignored if `time` is provided.

`dsecs` Seconds for parent process to sleep between checking the child process. It will be recycled to length 2. The first interval will be the first element, then each time it will wait twice as long until the interval is at least as long as the second element, then it will wait the second element. This keep the ratio of time required to run and time actually taken to run close to 1 without having excessive checking for longer processes. Default: `c(0.001, 0.1)` (seconds).

`time` `difftime` object giving the timeout interval. Default: `as.difftime(secs, units = "secs")`, which simply means to build a `difftime` object from the `secs` argument. If this argument is provided then `secs` is ignored.

`verbose` Boolean, default `FALSE`. If `TRUE` then emit messages with process IDs, etc.

<code>write.obj</code>	Function to serialize and write the resulting R object to the connection. First argument is the object and second is the connection. Default: <code>saveRDS</code> .
<code>read.obj</code>	Function to read and deserialize the resulting R object from the connection. Argument is the connection. Default: <code>readRDS</code> .
<code>make.con</code>	A function to make the connection for communication between child and parent. The function will be called once with no arguments. The child will then write to it with <code>saveRDS</code> and the parent will read from it with <code>readRDS</code> . Default: <code>tempfile</code> .
<code>cleanup.con</code>	A function to clean up a connection. Default: <code>function(con) if(file.exists(con)) unlink(con)</code> .
<code>touch.con</code>	A function to "touch" a connection. Default: <code>function(con) writeLines(character(), con)</code> . This is used to signal through the signal file.
<code>con.touched</code>	A predicate to check if the connection has been touched. Default: <code>file.exists</code> .
<code>make.signal.con</code>	Same as <code>make.con</code> , but for the signal file. Default: <code>make.con</code> .
<code>cleanup.signal.con</code>	Like <code>cleanup.con</code> , but for the signal file. Default: <code>cleanup.con</code> .

Details

The expression is evaluated in a child process while the parent process waits up to the given time interval. If the child process finishes quickly enough it will signal to the parent process to wake up and return a particular value. If the time interval elapses before the child process finishes then the parent wakes up anyway and kills the child, then throws an error. (You may want to wrap this function in a `tryCatch` block to handle the error gracefully.)

The implementation uses the `fork` package, which is loaded—an error is thrown if unavailable. In fact, the parent sleeps for short intervals (controlled by `dsecs` param), each time waking up to check if either the time has elapsed or the child has finished, then acting accordingly.

The way the child signals to the parent is via the filesystem. There are two such files: the result file and the signal file. The child writes the result of the calculation to disk as a serialized R object. Usually you should try to keep this small. Then the child touches a second file, called the "signal" file, which signals that it is finished. Both of these are temporary files. While in loop, the parent checks for existence of the signal file. After exiting the loop, the parent reads the result file. An attempt is made to delete both files before returning or throwing an error.

The child process evaluates your expression within a `try` block. If this evaluation results in an error, then the captured error object is passed to the parent, which then throws it again.

It is possible that the child would *start* writing the result but not finish before the time elapses. That would be considered a timeout. The thing which the parent checks is if the signal file exists.

Don't be intimidated by the large number of arguments. Typically usage involves only the first two.

Value

The result of evaluating `expr`

Author(s)

Brad Friedman

event.names *event.names*

Description

Get vector of names of all existing Events.

Usage

```
event.names(registry)
```

Arguments

registry EventRegistry

Details

Get vector of names of all existing Events.

Value

Charvec

Author(s)

Brad Friedman

Examples

```
r <- new.event.registry()
event.names(r)
add.event(r, "mouseclick")
event.names(r)
```

execute.handler *execute.handler*

Description

Execute the handler

Usage

```
execute.handler(analysis.page, params, plot.file, file.params = list(),
  device = svg, annotate.plot = analysis.page$annotate.plot,
  max.annotated.regions = 5000, logger = create.logger(stderr(),
  log4r:::FATAL + 1))
```

Arguments

analysis.page	AnalysisPage object
params	Named list of parameters. These can include arguments to <code>svg</code> and arguments to the handler function. If there are any extra arguments then an error is thrown.
plot.file	Path to file to create. Should not exist already.
file.params	Named list of parameters (but defaults to empty list). These will be passed through as-is and should correspond to FILE uploads (being length-2 lists with <code>\$name</code> and <code>\$tmp_name</code> elements).
device	The plotting device function to use. Default: <code>svg</code> . You might specify <code>png</code> instead (you are passing the actual function here, not its name).
annotate.plot	Logical, indicating whether I should try to annotate the SVG plot. (If you aren't using the SVG device then this should be set to <code>FALSE</code> to not waste time trying to annotate the plot.) Default: <code>analysis.page\$annotate.plot</code>
max.annotated.regions	Integer. If the handler returns more than this many regions then do not try to annotate them in the plot. Default: 5000
logger	log4r object. Default: no logging (FATAL + 1)

Details

`execute.handler` executes the plot function in the handler based on the parameter list, checks that the output is valid, adds the SVG attributes to the plot, and returns an `AnnotatedDataFrame`.

All of the parameters in the parameter list are JSON decoded. Even though this is really just extra work for the scalar parameters, we do it because otherwise it is confusing who needs to be de/encoded and who doesn't.

It is OK if your handler doesn't turn off the device when it's done. This wrapper will check if the current device hasn't changed. If so, it will call `dev.off`. This is useful because then you can use the same function in an interactive session, and also saves you one line of code. It's also OK if your handler *does* turn off the device. Then the current device will have decreased and the wrapper will know not to call `dev.off` again.

It is also OK if your handler returns a `data.frame` instead of an `AnnotatedDataFrame`. It just has to have `x`, `y`. An `AnnotatedDataFrame` will be built. The interpretation of the fields in the `AnnotatedDataFrame` depend on your front end, but the guidelines are like this:

`type` "text", "numeric" or "none", to set sorting and filtering options.

`labelDescription` A display name for the column, instead of showing the actual name.

If `$no.plot` is true then the plotting device won't be opened or closed, and of course the plot won't be annotated.

If `annotate.data.frame` is set then your `data.frame` is converted to an `AnnotatedDataFrame` and your `AnnotatedDataFrame` is converted to an `AnalysisPageDataNode` of "table" type automatically.

Value

`AnnotatedDataFrame`, but throws error if the handler is not making a plot, or is returning invalid data.

Author(s)

Brad Friedman

See Also[new.analysis.page](#)**Examples**

```
page <- new.analysis.page(AnalysisPageServer:::sine.handler)
plot.file <- tempfile(fileext = ".svg")
plist <- lapply(list(xmin=-2*pi, xmax=2*pi, n= 50), rjson::toJSON)
sine.data <- AnalysisPageServer:::execute.handler(page, plist, plot.file=plot.file)
# now sine.data is an AnnotatedDataFrame
```

file.param

*file.param***Description**

Build a file upload AnalysisPageParam

Usage

```
file.param(..., template.uri = NULL, dependent.params = NULL)
```

Arguments

- ... Pass through to [simple.param](#), including at least "name" but not including "type".
- template.uri URI, possibly with :-prefixed parameter names. For example "/get?x=:x;y=:y" has parameters "x" and "y". (See `dependent.params` next). (Note: this follows the way of doing it in `combobox.param`). This is optional. If provided, then the front-end can use this callback to allow the user to download a template. This is a template in two senses: the URI itself may be a template whose parameter values should be filled in, and the return value of the request is an excel file which is a template for the user to fill in.
- dependent.params A character vector whose names are parameters from the uri, and whose values are the names of other form elements. Error to provide this without providing `template.uri`

Details

Build a file upload AnalysisPageParam. This is rendered as a file upload element, to be uploaded along with the submission. (Currently there is no server-side mechanism for storing uploaded files, so asynchronous upload is not possible.) The description field should describe what type of file is expected.

On the server side your handler will get a list with "name", "tmp_name" and "fh" elements giving the filename, and path to a local file (usually in /tmp), and the filehandle open for reading.

Value

An AnalysisPageParam

Author(s)

Brad Friedman

Examples

```
cov.param <- file.param("cov", label="Covariate Data", description="A two-column Excel file, first column being t
```

get.APS.outdir	<i>Get current AnalysisPageServer output directory</i>
----------------	--

Description

Get current AnalysisPageServer output directory

Usage

```
get.APS.outdir()
```

Value

Path

Author(s)

Brad Friedman

See Also

[set.APS.outdir](#), [reset.APS.outdir](#)

Examples

```
set.APS.outdir("/some/path")
get.APS.outdir()
reset.APS.outdir()
```

`get.page``get.page`

Description

Return a registered function

Usage

```
get.page(registry, page.name)
```

```
## S3 method for class 'AnalysisPageRegistry'  
get.page(registry, page.name)
```

Arguments

<code>registry</code>	AnalysisPageRegistry object
<code>page.name</code>	Name of the registered function

Details

Return a registered function

Value

The registered function. Stops if no such function is registered

Author(s)

Brad Friedman

See Also

[new.registry](#), [register.page](#), [has.page](#), [pages](#)

Examples

```
example(register.page, ask=FALSE) # register the sine page  
get.page(registry, "sine")       # should return the sine.handler function
```

getTraceback	<i>getTraceback</i>
--------------	---------------------

Description

Get traceback from tryKeepTraceback()

Usage

```
getTraceback(mto)
```

Arguments

mto An object of the try-error class

Value

Traceback as a string

Examples

```
x <- tryKeepTraceback(stop("no way"))
if(is(x, "try-error")) cat(getTraceback(x))
```

has.event	<i>has.event</i>
-----------	------------------

Description

Predicate to test if an EventRegistry has an Event of a given name

Usage

```
has.event(registry, event)
```

Arguments

registry EventRegistry
event String. Name of the Event.

Details

Predicate to test if an EventRegistry has an Event of a given name

Value

Logical

Author(s)

Brad Friedman

Examples

```
r <- new.event.registry()
has.event(r, "mouseclick")
add.event(r, "mouseclick")
has.event(r, "mouseclick")
```

*has.page**has.page*

Description

Predicate to test if some page is already registered under a name

Usage

```
has.page(registry, page.name)
```

```
## S3 method for class 'AnalysisPageRegistry'
has.page(registry, page.name)
```

Arguments

registry	Registry
page.name	An AnalysisPageRegistry

Details

Predicate to test if some page is already registered under a name

Value

Logical, indicating if a page is already registered under than name

Author(s)

Brad Friedman

See Also

[new.registry](#), [register.page](#), [get.page](#), [pages](#)

Examples

```
example(register.page, ask=FALSE) # register the sine page
has.page(registry, "sine")       # should return TRUE now.
```

`ignore.lots.of.stuff` *ignore.lots.of.stuff*

Description

Transformer for ignoring id, class, type and some whitespace

Usage

```
ignore.lots.of.stuff(lines)
```

Arguments

`lines` Character vector of lines from the SVG file.

Details

This transformer strips all id, class and type tags, with one preceding space, from the SVG lines.

It also ignores what it thinks is space between tags, namely `>\s+<`

This is meant primary as an argument for transformer in [check.same.svg](#)s.

Not exported—you should fully qualify it with `AnalysisPageServer:::ignore.lots.of.stuff` if you want to use it.

All the lines will be concatenated, too, into a single character string.

Value

Character vector. Same lines, with id and class tags transformed.

Author(s)

Brad Friedman

See Also

[check.same.svg](#)s

<code>is.registry</code>	<i>is.registry</i>
--------------------------	--------------------

Description

Test if an argument is an AnalysisPageRegistry

Usage

```
is.registry(registry)
```

Arguments

<code>registry</code>	A candidate object
-----------------------	--------------------

Value

Logical, indicating that the object is an "AnalysisPageRegistry"

<code>kill.process</code>	<i>kill.process</i>
---------------------------	---------------------

Description

Kill a process and wait for it.

Usage

```
kill.process(pid)
```

Arguments

<code>pid</code>	Process ID, or list with \$pid component
------------------	--

Details

Kill a process and wait for it. Nothing more than `kill(pid); wait(pid)`, but handy to have a single function so you don't forget the `wait()` call.

Value

Same as `wait` in the `fork` package.

Author(s)

Brad Friedman

`known.param.sizes` *known.param.sizes*

Description

Get the controlled vocabulary of parameter size words

Usage

`known.param.sizes()`

Details

Returns the controlled vocabulary of parameter size words

Value

Character vector

Author(s)

Brad Friedman

`lives.ok` *lives.ok*

Description

Test that an expression lives OK

Usage

`lives.ok(call, testname)`

Arguments

`call` An expression to evaluate
`testname` A name for the test. Defaults to deparsing the call.

Details

Test that evaluating an expression lives OK (does not throw an exception)

Value

Runs one test. Returns the value of the evaluated expression

Author(s)

Brad Friedman

Examples

```
lives.ok(3+5, "addition lives OK")
```

```
make.standard.ids      make.standard.ids
```

Description

Make a vector of standardized IDs

Usage

```
make.standard.ids(n, prefix = "Reg")
```

Arguments

n	Desired length of vector
prefix	String, default "Reg".

Details

Make a vector of standardized IDs.

Value

Character vector. Currently just "Reg1", "Reg2", ..., "Regn" (or starting with whatever prefix is).

Author(s)

Brad Friedman - Regular

new.analysis.page *new.analysis.page*

Description

Validate and prepare a handler for installation

Usage

```
new.analysis.page(handler, param.set = NULL, annotate.plot = TRUE,
  class.name = "plot-point", standard.ids = TRUE, skip.checks = FALSE,
  plot.pars.transformer = NULL, annotate.data.frame = TRUE,
  numeric.sig.digs = 3, no.plot = FALSE, name = NULL, label = name,
  description = label, advanced = 0, thumbnail = NULL, service = FALSE,
  in.menu = !service)
```

Arguments

handler	A handler function, as described above.
param.set	An AnalysisPageParamSet to use for the function. Or NULL, to call default.param.set . Note that it is not a requirement that all of the function arguments be included in the param set—they just won't be provided.
annotate.plot	Logical. Should plots generated by this handler be automatically annotated? Default: TRUE.
class.name	Character. What class label should be applied to automatically annotated points? Default: "plot-point". (Ignored if annotate.plot is FALSE.)
standard.ids	Logical. By default (TRUE), the rownames of your return value are ignored, and new ones are created like "Reg1", "Reg2". The advantage of this is that these IDs are guaranteed to be standard-compliant HTML and SVG id tags. If you want to force using your real rownames as IDs (for example, to help in debugging), then set this to FALSE (FALSE is implemented but not tested). Or you can provide a function with the same signature as <code>AnalysisPageServer:::make.standard.ids</code> that will generate IDs for you (this is also implemented but not tested). When annotate.plot is FALSE (for example, when a PNG is requested) the rownames are always left alone and <code>make.standard.ids</code> is not called.
skip.checks	Logical. By default (FALSE) your handler is run once on its default arguments, and it is checked that it makes an SVG and that the SVG can be annotated (if annotate.plot was set). This is important to get right, but doesn't really need to be done during production—it just slows down the server start up.
plot.pars.transformer	A function to transform plot parameters. It should have the signature <code>function(plot=list(), other=list())</code> and return a list. The first argument is the plot parameters extracted from the user request (these are the parameters like "width" and "height" that are not related to the business of the request but are simply passed through to the device function), and the second is all the other parameters from the user request.

The function returns a (named) list of further arguments to pass to the device function. The main use for this is to set the image dimensions based on the user request. In that case your function would return a list with "width" and "height" elements. The units would be inches for svg plot. png plot uses pixel units, but if you add the parameter units="in" then you can use inches units. You can do this if "units" %in% names(formals(device)). The default plot.pars.transformer=NULL is to not transform the parameters at all.

annotate.data.frame	Logical, indicating whether your return value should be passed throughg annotate.data.frame. Default: TRUE. several checks appropriate for the standard case of data associated with plotted regions.
numeric.sig.digs	Number of significant digits to which numeric columns in your data should be rounded. Default: 3. Set to NULL to not round (you could still round within your function if you wanted tighter control). "numeric" here means either that you set the a varMetadata "type" of the column to the string "numeric", or, if that is not available that is(column)[1] is "numeric". This means, in particular that integer columns will not be rounded.
no.plot	This page is meant to return data but no plot. Default: FALSE (it *is* expected to return a plot).
name	A name for the analysis page. Defaults to deparsing the handler argument. This meant to be an internal identifier for the page, only displayed to the user if label and description are unavailable.
label	A display label for the page. This should be 1-3 words, to fit in the navbar. Default: name.
description	A longer description for the page. This should be 1-2 sentences, to appear on rollover or in a summary page. Default: label
advanced	An integer. 0 means not advanced (always display the page). 1, 2, 3 are increasing levels of advanced (only display the page in advanced mode). Default: 0
thumbnail	A URL for a thumbnail to use when listing the page. NULL means to not store any thumbnail.
service	A logical, default FALSE. TRUE means that this page should only be called as a service and should not be rendered as a user page. This also means that the return value will not be processed at all except for JSON-encoding (unless of course you return an AnalysisPageResponse).
in.menu	A logical, default !service. TRUE means that the front-end should display this page in the menu. FALSE means that the front-end should not display the page in the menu, but should still be ready to render it, for example by app state link (contrast with service which the front end can't do anything with except provide a download link or use (as a service) to populate an input widget). The special condition service = FALSE, in.menu = TRUE builds a Page that the front end can use but doesn't show up in the menu. The combination of service = TRUE, in.menu = TRUE, doesn't make any sense and leads to an error.

Details

An AnalysisPage handler is a function that satisfies the following properties:

1. Can be called with no arguments and return a valid value (to be used for testing in the next steps).
2. It creates a plot but does not open the device
3. It returns a data.frame with x and y fields. Alternatively it may return an [AnnotatedDataFrame](#).
4. x and y fields are numeric.
5. The points in test plot can be successfully found (based on the x and y coordinates) and labeled.

This function throws an error if the argument does not satisfy one of these. Otherwise it returns void.

The function will be called once at the time of running this function (typically during registration) with all of its defaults to verify the second and third requirements.

The return value is a list of class "AnalysisPage" with the following components:

`$handler` The handler function

`$params` An AnalysisPageParamSet (see [param.set](#))

`$annotate.plot` An logical indicating whether the plots generated by the handler should be automatically annotated

`$class.name` A character giving the class to be applied to the annotated SVG elements

A list will be built with the information necessary to render the page. It will contain the handler function in the `$function` slot, as well as a `$params` slot listing all of the parameters and their relevant information. The class name of "AnalysisPage" will be slapped on this object for good measure.

Value

See above

Author(s)

Brad Friedman

See Also

[register.page](#), [execute.handler](#), [AnnotatedDataFrame](#)

Examples

```
page <- new.analysis.page(AnalysisPageServer:::sine.handler)
registry <- register.page(new.registry(), "sine", page)
## Note: above is equivalent to the following:
## registry <- register.page(registry, "sine", AnalysisPageServer:::sine.handler)
```

new.datanode.array *new.datanode.array*

Description

Construct a new array-type data node

Usage

```
new.datanode.array(name, children, ...)
```

Arguments

name	Name of the node
children	List of AnalysisPageDataNodes
...	Passed through to new.datanode, in particular label and description

Details

Construct a new array-type data node from a list of AnalysisPageDataNodes

Value

AnalysisPageDataNode

Author(s)

Brad Friedman

Examples

```
html.node <- example(new.datanode.html)$value
simple.node <- example(new.datanode.simple)$value
new.datanode.array(name = "arr", children = list(html.node, simple.node))
```

new.datanode.html *new.datanode.html*

Description

Construct a new HTML-type data node

Usage

```
new.datanode.html(name, value, ...)
```


Arguments

name	Name of the node
value	The value, an HTML string or charvec.
...	Passed through to new.datanode, in particular label and description

Details

Construct a new HTML-type data node. An HTML-type data node is like a simple data node but it has an HTML string or character vector as its value. It should be rendered as-is, but with activated analysis-page-data-set containers.

Value

AnalysisPageDataNode

Author(s)

Brad Friedman

See Also

[is.atomic](#)

Examples

```
new.datanode.html(name = "shakespeare",
                 value = "<i>Shall I compute thee to a summer's data?</i>")
```

new.datanode.plot *new.datanode.plot*

Description

Construct a new plot-type data node

Usage

```
new.datanode.plot(name, plot.file, table, ...)
```

Arguments

name	Name of the node
plot.file	Path to plot file, relative to server tempdir.
table	A table-type AnalysisPageDataNode
...	Passed through to new.datanode, in particular label and description

Details

Construct a new plot-type data node from a `plot.file` and an `AnnotatedDataFrame`. Note: `caption` is included implicitly in the table object.

Value

`AnalysisPageDataNode`

Author(s)

Brad Friedman

`new.datanode.simple` *new.datanode.simple*

Description

Construct a new simple-type data node

Usage

```
new.datanode.simple(name, value, ...)
```

Arguments

<code>name</code>	Name of the node
<code>value</code>	The value
<code>...</code>	Passed through to <code>new.datanode</code> , in particular <code>label</code> and <code>description</code>

Details

Construct a new simple-type data node. A simple data node must have either a `NULL` value or a "scalar" value, which means length 1 atomic

Value

`AnalysisPageDataNode`

Author(s)

Brad Friedman

See Also

[is.atomic](#)

Examples

```
new.datanode.simple(name = "x", value = 100)
```

new.datanode.table	<i>new.datanode.table</i>
--------------------	---------------------------

Description

Construct a new table-type data node

Usage

```
new.datanode.table(name, data, caption = "", ...)
```

Arguments

name	Name of the node
data	An AnnotatedDataFrame. Unless "label" is already available, "labelDescription" in the varMetadata will be changed to "label" to agree with the syntax we use in the rest of the AnalysisPage interface.
caption	Caption for the table. Default: ""
...	Passed through to new.datanode, in particular label and description

Details

Construct a new table-type data node either from an AnnotatedDataFrame.

Value

AnalysisPageDataNode

Note

Captions for plots are included implicitly in the table component of their responses.

Author(s)

Brad Friedman

```
new.event.registry    new.event.registry
```

Description

EventRegistry constructor

Usage

```
new.event.registry()
```

Details

An EventRegistry is a collection of Events. Each Event has a name and a list of functions, each known as a handler. Events can be modified or triggered. When triggered, each function is called in turn, and the final return value is returned to the triggering context.

Value

EventRegistry

Author(s)

Brad Friedman

Examples

```
r <- new.event.registry()
```

```
new.FastRWeb.analysis.page.run
    new.FastRWeb.analysis.page.run
```

Description

Given an RApacheAnalysisPageServer object, create a FastRWeb-compatible handler

Usage

```
new.FastRWeb.analysis.page.run(app, FastRWeb.scriptname,
  FastRWeb.prefix = "/cgi-bin/R", APS.resources.location = "/R",
  front.end.location = "/dist-aps",
  front.end.dir = system.file("htdocs/client/dist-aps", package =
    "AnalysisPageServer"), tmpdir = tmpdir(), FastRWeb.tmpdir = getwd(),
  referer = "", EP = NULL, REST.location = "/REST", verbose = FALSE,
  logger = create.logger(stderr(), if (verbose) log4r:::INFO else
    log4r:::FATAL), ...)
```

Arguments

app	AnalysisPageRApacheApp. Or an AnalysisPageRegistry from which to build an app (see ...).
FastRWeb.scriptname	Name for the app within FastRWeb. A script called FastRWeb.R would be created, and the URL would be FastRWeb.prefix/FastRWeb.scriptname.
FastRWeb.prefix	Prefix for all the FastRWeb resources on your server. For example, if you are using a typical CGI deployment, as described in the FastRWeb INSTALL document, it would be "/cgi-bin/R", and your AnalysisPageServer app would be a group of URLs like /cgi-bin/R/APS/client/analysis-page-server.html etc (but see FastRWeb.scriptname for APS and front.end.location for client).
APS.resources.location	Location relative to App base URL from which to serve dynamic AnalysisPageServer resources (like analysis, pages, and other details that normal users don't have to worry about). Default, "R", is probably fine.
front.end.location	Location relative to App base URL from which to serve front end files. Default, "/client", is probably fine.
front.end.dir	Path (in filesystem) to front end files. Default: system.file("htdocs", package = 'AnalysisPageServer')
tmpdir	Path to temporary directory to store files needed while the server is running. Default: tmpdir(). This is ignored if app is an AnalysisPageRApacheApp. This is a directory private (in the OOP sense, not necessarily in the filesystem sense of the word "private") to the AnalysisPageServer system—FastRWeb never sees it directly. This means in particular that it doesn't have to be within the AnalysisPageServer hierarchy.
FastRWeb.tmpdir	This is the path to FastRWeb's tmpdir. FastRWeb will only serve temporary files out of that directory.
referer	FastRWeb does not (currently) parse the Referer from the headers, but you can put a string here which will be interpreted as such. I only put this here if you have an app which fails catastrophically if referer is unavaiable.
EP	ExpressionPlotClient object, if needed for your app. Deprecated, and to be removed in a future version.
REST.location	If EP is non-NULL, then the location from which to serve REST requests (relative to app base URL). Default: "/REST". Deprecated, and to be removed in a future version.
verbose	Boolean, default FALSE. If TRUE then send progress messages.
logger	log4r object, optional
...	If app is actually an AnalysisPageRegistry then ... is passed through h it to rapache.app.from.registry to build the AnalysisPageRApacheApp. just a convenient

Details

FastRWeb is another alternative for deployment of AnalysisPageServer applications. The benefit relative to Apache/RApache is that it may be easier to deploy. The benefit relative to Rook/Rhttpd is that it actually works (Rhttpd cannot handle concurrent connections). See <http://rforge.net/FastRWeb/> (and <http://rforge.net/Rserve/>) for information about the FastRWeb/Rserve system. This function assumes that you've already got a working installation of Rserve and fastRWeb, as described there. As with that example, FastRWeb is a layer between Rserve and either CGI or PHP, so you would also have to have a CGI or PHP server running. Or, you could try the experimental http server that comes starting in Rserve 1.7.

This function, `new.FastRWeb.analysis.page.run` returns a function which can be used as the run function for a FastRWeb script. So, typically, your FastRWeb script would do whatever necessary to create your AnalysisPageServer Registry (or App object). Then, the last line of the script would be to pass that object to this function, and assign the return value to `run`. In other words, this function would not normally be called interactively, but only within the FastRWeb framework.

For development purposes it is quite convenient to build your AnalysisPageServer application within the FastRWeb script. For example, in the default configuration, you could put this into `"/var/FastRWeb/web.R/APS.R"`:

```
library(AnalysisPageServer)  reg <- trig.registry()  run <- new.FastRWeb.analysis.page.run(reg, F
```

This allows you to make changes to code and reload the page without restarting the server. In fact, any libraries will be reloaded, so you can change your package and re-install without restarting the server.

Once you want to move more into testing or production you'll want to do all the heavy lifting in the startup script. You would have to save the `run` object somewhere in the Global namespace and then simply return it in the FastRWeb script. Under default FastRWeb configuration you could add this code to the end of the startup script `"/var/FastRWeb/code/rserve.R"`:

```
library(AnalysisPageServer)  myRun <- new.FastRWeb.analysis.page.run(trig.registry(), FastRWeb.sc
```

Then, in `"/var/FastRWeb/web.R/APS.R"`, you could just have nothing more than this:

```
run <- myRun
```

Note that the name of the FastRWeb script must be the same as `FastRWeb.scriptname`, but with a `".R"` suffix appended.

It would be possible to extend this system to server multiple AnalysisPageServer apps from the same FastRWeb setup. Each one would get its own FastRWeb script, and I leave it as an exercise for the reader to build them all in the Rserve startup and assign the correct handler to run in each script.

In this example I point my browser to <http://localhost/cgi-bin/R/APS/dist-aps/analysis-page-server.html> to open the page.

Value

Not sure yet....

Author(s)

Brad Friedman

Examples

```
## Not run:
library(AnalysisPageServer)
reg <- trig.registry()
run <- new.FastRWeb.analysis.page.run(reg)

## End(Not run)
message("See vignette FastRWebDeployment.html")
```

new.registry	<i>new.registry</i>
--------------	---------------------

Description

Make a new (empty) registry.

Usage

```
new.registry(...)
```

Arguments

... AnalysisPages with which to initially populate the registry

Value

A new registry, which is just an empty list with class AnalysisPageRegistry.

Author(s)

Brad Friedman

See Also

[register.page](#), [has.page](#), [get.page](#), [pages](#)

Examples

```
r <- new.registry()
```

new.response	<i>new.response</i>
--------------	---------------------

Description

Build a new AnalysisPageResponse object

Usage

```
new.response(body, content.type, status = 200, headers = character())
```

Arguments

body	Either a raw vector or a character vector that constitutes the response body.
content.type	A string giving the content-type, such as "text/plain"
status	Integer. An HTTP response status. Default, 200, means HTTP_OK
headers	Named charvec of extra HTTP headers. Default: character() (none)

Details

A handler may return an AnalysisPageResponse object, which is basically a complete response, if it doesn't want the framework to do any extra processing. This allows complete control over the response.

Value

AnalysisPageResponse object

Author(s)

Brad Friedman

Examples

```
poem.file <- system.file("examples/in-a-station-of-the-metro.html", package="AnalysisPageServer")
poem.html <- readLines(poem.file, warn = FALSE)
new.response(paste0(poem.html, "\n"), content.type = "text/html")
```

```
new.rook.analysis.page.app
    new.rook.analysis.page.app
```

Description

Given an RApacheAnalysisPageServer object, return a Rook app that can run it.

Usage

```
new.rook.analysis.page.app(app, EP = NULL, front.end.location = "/dist-aps",
  front.end.dir = system.file("htdocs/client", package =
    "AnalysisPageServer"), app.name = "RAPS",
  app.prefix = file.path("/custom", app.name), tmpdir = tmpdir(), ...)
```

Arguments

app	AnalysisPageRApacheApp. Or an AnalysisPageRegistry from which to build an app
EP	ExpressionPlotClient object, if needed for your app.
front.end.location	Location relative to App base directory from which to serve front end files. Default: "/dist-aps".
front.end.dir	Path (in filesystem) to front end files. Default: system.file("htdocs", package = 'AnalysisPageServer')
app.name	The name of the app you are going to use within Rook. This is used to build the prefix /custom/\${app.name} from where the app will be served—the Javascript front end has to be notified of this. Ignored if app.prefix is supplied.
app.prefix	The prefix from which the app will be served. Default: /custom/\${app.name}.
tmpdir	Path to temporary directory to store files needed while the server is running. Default: tmpdir().
...	If app is actually an AnalysisPageRegistry then ... is passed through along with it to rapache.app.from.registry to build the AnalysisPageRApacheApp.

Details

```
new.rook.analysis.page.app
```

Value

Your app, as a Rook App

Author(s)

Brad Friedman

See Also

[startRookAnalysisPageServer](#), [kill.process](#)

Examples

```
message("See vignette ExamplesServers.html")
```

pages

pages

Description

Get names of all pages in registry

Usage

```
pages(registry, include.services = FALSE)
```

```
## S3 method for class 'AnalysisPageRegistry'  
pages(registry, include.services = FALSE)
```

Arguments

registry AnalysisPageRegistry object

include.services

Logical. Should I include services in my list of all pages? Default: FALSE, do not include services.

Details

Get names of all pages in registry

Value

Character vector of names of pages in registry

Note

Service pages are identified as those having their service flag set, which is done at page build time using the service parameter of the `new.analysis.page` constructor.

Author(s)

Brad Friedman

See Also

[new.registry](#), [register.page](#), [has.page](#), [get.page](#)

Examples

```
empty.pages <- pages(new.registry()) # should be empty character vector
example(register.page, ask=FALSE)   # see register.page example---registers the sine handler
pages(registry)                     # should now be the character vector "sine"
```

param.set

param.set

Description

Build a new AnalysisPageParamSet from a list of AnalysisPageParam's.

Usage

```
param.set(...)
```

Arguments

... AnalysisPageParam objects. Or a single argument, being a list of AnalysisPageParam objects.

Details

Build a new AnalysisPageParamSet from a list of AnalysisPageParam's: Check for non-AnalysisPageParam elements and for duplicate names. Apply \$name elements to names of param set. Set class to AnalysisPageParamSet

Value

AnalysisPageParamSet

Author(s)

Brad Friedman

Examples

```
par1 <- simple.param(name = "par1")
par2 <- bool.param(name = "par2")
pset <- param.set(par1, par2)
```

`persistent.param.dependencies`*Return persistent parameter dependencies for an object*

Description

Return persistent parameters dependencies for an object.

For an `AnalysisPageParam` the return value is either a charvec of the object's persistent dependencies. It is important to note that The namespace for persistent dependencies of an `AnalysisPageParam` is the same as the namespace of the page Parameters. This is because when calling a constructor for an `AnalysisPageParam` at most we might specify the names of other Parameters (for example for combobox dependencies). But the other Parameters are not available at that time, so we can't look up their corresponding names in the persistent namespace.

For an `AnalysisPageParamSet` or an `AnalysisPage`, the return value is a list named after all of the persistent params, the values being charvecs of their dependencies. Note that The namespace for persistent dependencies of an `AnalysisPageParamSet` is the persistent namespace, not the Page Parameter namespace.

For an `AnalysisPageRegistry` the return value is a list named after all of the persistent params of any of the pages, the values being charvecs of their dependencies. If there is an discrepancy in the dependencies for a given persistent param, then the union of all dependencies is taken. (This will be checked for acyclicity by `.validate.registry`.) The namespace for persistent dependencies of an `AnalysisPageRegistry` is the persistent namespace, not the Page Parameter namespace.

Usage

```
persistent.param.dependencies(x)
```

```
## S3 method for class 'AnalysisPageParam'  
persistent.param.dependencies(x)
```

```
## S3 method for class 'AnalysisPageParamSet'  
persistent.param.dependencies(x)
```

```
## S3 method for class 'AnalysisPage'  
persistent.param.dependencies(x)
```

```
## S3 method for class 'AnalysisPageRegistry'  
persistent.param.dependencies(x)
```

Arguments

`x` An object for which there is a `persistent.param.dependencies` method.

Details

This is a named list. The names are the names of persistent parameters, and the values are the other persistent parameters on which they depend.

Value

Named list of charvecs, see Details.

Author(s)

Brad Friedman

persistent.params	<i>Return names of persistent parameters for an object</i>
-------------------	--

Description

Return names of persistent parameters for an object. The exact meaning depends on the type of object. For an AnalysisPage it would be the persistent params for that page. For an AnalysisPageRegistry it would be the persistent params for any of its pages.

Usage

```

persistent.params(x)

## S3 method for class 'AnalysisPageParam'
persistent.params(x)

## S3 method for class 'AnalysisPageParamSet'
persistent.params(x)

## S3 method for class 'AnalysisPage'
persistent.params(x)

## S3 method for class 'AnalysisPageRegistry'
persistent.params(x)

```

Arguments

x An object for which there is a persistent.params method.

Details

Note that the names are from the shared namespace, which are the values passed as the persistent argument to the AnalysisPageParam constructor functions such as [simple.param](#). Although this is usually the same as actual names of the AnalysisPageParams themselves there is no requirement that they be the same.

Value

Charvec of persistent params

Author(s)

Brad Friedman

platformIsWindows	<i>Predicate to test if running on a windows platform</i>
-------------------	---

Description

Predicate to test if running on a windows platform

Usage

platformIsWindows()

Value

Boolean: TRUE on windows, FALSE on other platforms

Author(s)

Brad Friedman

protect.rapache.memory	<i>protect.rapache.memory</i>
------------------------	-------------------------------

Description

Set up events and handler to turn over memory-bloated worker processes

Usage

```
protect.rapache.memory(app, max.mb, app.event = "FinishAnalysis",
    memory.event = "BloatedMemory")
```

Arguments

app	AnalysisPageRApacheApp
max.mb	Maximum allowed memory usage before triggering turnover.
app.event	Name of event which should trigger this memory check. Default: "FinishAnalysis".
memory.event	Name of event which excess memory usage should trigger. Default: "BloatedMemory".

Details

Set up events and handler to turn over memory-bloated worker processes. When Rapache processes process requests that require large amounts of memory they don't return the memory to the OS. Eventually it can build up, slowing down the server when then has to turn to cache. Calling this function will add a check at each FinishAnalysis which, if the process is using more memory than the threshold specified by `max.mb`, delivers a SIGUSR1 signal to itself. This is a signal to Apache that the process should be turned over after finish the current request, thus pruning bloated workers.

Value

Nothing

Author(s)

Brad Friedman

rapache.app.from.registry
rapache.app.from.registry

Description

Build rapache app from an AnalysisPageRegistry

Usage

```
rapache.app.from.registry(registry, page.param = "page",
    textarea.wrap.param = "textarea_wrap", device.param = "device",
    decoder.param = "decoder", max.regions.param = "max_annotated_regions",
    default.max.regions = 10000, force = FALSE,
    tmpdir = Sys.getenv("WEB_TMPDIR"), tmpdir.timeout.seconds = 600,
    devices = .default.device.list, other.mime.types = c(json =
    "application/json"), mime.types = c(sapply(devices, "[[", "mime.type"),
    other.mime.types),
    query.param.decoders = .build.default.query.param.decoders(),
    brand.builder = .default.brand.builder, logger = create.logger(stderr(),
    log4r:::FATAL))
```

Arguments

<code>registry</code>	AnalysisPageRegistry from which to build you app.
<code>page.param</code>	Character. Name for the parameter which specifies the page. Default "page"
<code>textarea.wrap.param</code>	Character. Name for the parameter which specifies whether the response should be wrapped in a <textarea> tag. This is needed to support file uploads in browsers, like IE9, that don't support XMLHttpRequest2. Default "textarea_wrap". In addition to wrapping in textarea the response type will be set to "text/html", another hack that such browsers require.

<code>device.param</code>	Character. Name for the parameter which specifies the plotting device. Default: "device".
<code>decoder.param</code>	Character. Name for the parameter which specifies the form query parameter decoding method. Default: "decoder".
<code>max.regions.param</code>	String. Name for the parameter which specifies the maximum number of regions for annotation. Default: "max_annotated_regions".
<code>default.max.regions</code>	Default maximum number of regions for annotation. If a plot has more than this many elements then it will not be annotated. Default: 10000.
<code>force</code>	Logical. If set then an invalid registry is a warning instead of an error.
<code>tmpdir</code>	Temporary directory into which plot files should be written. By default this is taken from the <code>WEB_TMPDIR</code> environment variable. It is checked upon opening. It is important under Apache that all of the processes use the same directory, otherwise they won't be able to find the plots made by other processes.
<code>tmpdir.timeout.seconds</code>	Temporary files will expire after this time. Default: 600 (10 minutes)
<code>devices</code>	Named list. The names of the vector are the names of allowed plotting devices. The values are themselves lists, each having a <code>\$mime.type</code> and <code>\$function</code> , being the plotting function. Default is given by the private variable <code>.default.device.list</code> , and includes <code>svg</code> and <code>png</code> (but uses a modified <code>png</code> function so that it accepts units inches). Which one to be used (in the default scenario, a choice between <code>svg</code> and <code>png</code>) is controlled by the special <code>device.param</code> parameter. If that is not provided then the first device from this vector is used (default default is therefore "svg", which is the best since it can be annotated, but older browsers such as IE8 will need to do PNGs).
<code>other.mime.types</code>	Named charvec giving a mapping from file extensions other than those already in <code>devices</code> to MIME types that can be served out of the temporary storage/retrieval area. Default: <code>c(json = "application/json")</code> .
<code>mime.types</code>	This is a named charvec giving a mapping from file extensions to mime types. Only files with extensions in this list can be served from the temporary storage/retrieval area. The default is to take the extensions/MIME-types defined in <code>devices</code> and add to them those in <code>other.mime.tpyes</code> .
<code>query.param.decoders</code>	Names list. The names are the names of allowed query param decoders (valid values for the <code>decoder.param</code> parameter). The values are functions which do the decoding. Default is just <code>list(url=urlDecode)</code> . <code>urlDecode</code> is a function supplied by RApache (or by testing framework).
<code>brand.builder</code>	This is a function that takes a single argument called "persistent" which is a list of key value pairs representing the internal "persistent" state of the app. The persistent state is a namespace that particular parameters of particular pages can draw from, with the possible option of locking those parameters to the values in the persistent namespace. The purpose of the <code>brand.builder</code> function is to return a string that should be used in the top-left corner of the web page to briefly summarize the current state. The default brand builder always returns the string "AnalysisPageServer".

logger log4r object, optional

Details

This does most but not all of the work. You should create an R script that builds your page registry, then builds an rapache.app with this function. Within that R script you call `add.handlers.to.global` to install the 5 handlers (`handle.pages/handle.params/handle.plot/handle.data/handle.meta.data`).

Next you have to tell apache to source your script upon startup. The directive for your `httpd.conf` is as follows: `RSourceOnStartup "/gne/home/friedmab/scr/apache-test/R-startup.R"`

Finally, you have to register the five handlers. This is done as follows

Value

AnalysisPageRApacheApp

Author(s)

Brad Friedman

rapache.trig.app *rapache.trig.app*

Description

Build the AnalysisPageRApacheApp for the trig example

Usage

rapache.trig.app(...)

Arguments

... Other parameters to pass through to `rapache.app.from.registry`, such as `con`

Details

The toy registry has a sine page, a cosine page and the scattergram tool.

Value

AnalysisPageRegistry

Author(s)

Brad Friedman

See Also

[trig.registry](#)

register.page *register.page*

Description

Register a page

Usage

```
register.page(registry, page.name, page, overwrite = FALSE)
```

Arguments

registry	AnalysisPageRegistry object
page.name	Character. Name of the page to register
page	AnalysisPage or function. If a function is supplied instead of an AnalysisPage object then it will be coerced into an AnalysisPage object calling new.analysis.page .
overwrite	Logical. If FALSE (default) then throw an error if a page is already registered under that name. If TRUE then just warn.

Details

Register a page

Value

void

Author(s)

Brad Friedman

See Also

[new.registry](#), [has.page](#), [get.page](#), [pages](#), [new.analysis.page](#)

Examples

```
# Make a new registry
registry <- new.registry()

# Now register it under the name "sine" (in the "example" registry)
# and keep the modified registry.
registry <- register.page(registry, "sine", AnalysisPageServer:::sine.handler)
```

remove.event	<i>remove.event</i>
--------------	---------------------

Description

Remove an Event entirely

Usage

```
remove.event(registry, event)
```

Arguments

registry	EventRegistry
event	String. Name of the Event to remove

Details

Remove an Event entirely from the EventRegistry. Contrast with [clear.event.handlers](#), which only removes the handlers for that event.

Value

Nothing good.

Author(s)

Brad Friedman

Examples

```
r <- new.event.registry()
add.event(r, "mouseclick")
has.event(r, "mouseclick")
remove.event(r, "mouseclick")
has.event(r, "mouseclick")
```

remove.old.files *remove.old.files*

Description

Remove old files from a directory

Usage

```
remove.old.files(tmpdir, tmpdir.timeout.seconds)
```

Arguments

tmpdir Path to directory whose old files you want to delete
tmpdir.timeout.seconds Time in seconds. An attempt will be made to delete files with ctimes older than this many seconds before the current time.

Details

Remove old files from a directory

Value

see [unlink](#)

Author(s)

Brad Friedman

reset.APS.outdir *Reset AnalysisPageServer output directory*

Description

This directory is used by [embed.APS.dataset](#) to decide where to save the .svg and .json files. This function resets it to its default, ".".

Usage

```
reset.APS.outdir()
```

Value

Nothing of note

Author(s)

Brad Friedman

See Also

[get.APS.outdir](#), [set.APS.outdir](#)

Examples

```
set.APS.outdir("/some/path")
get.APS.outdir()
reset.APS.outdir()
```

rook.analysis.page.server.landing.page
rook.analysis.page.server.landing.page

Description

Return URL for landing page of a Rook AnalysisPageServer

Usage

```
rook.analysis.page.server.landing.page(baseUrl)
```

Arguments

baseUrl	String. Base URL (typically ending in "/custom/RAPS"), or a list with \$url element.
---------	--

Details

Return URL for landing page of a Rook AnalysisPageServer

Value

String, full URL to landing page.

Author(s)

Brad Friedman

Examples

```
message("See vignette ExamplesServers.html")
```

search.replace	<i>search.replace</i>
----------------	-----------------------

Description

Search and replace strings in a file

Usage

```
search.replace(infile, outfile, replacements, overwrite = FALSE)
```

Arguments

<code>infile</code>	Path to input file
<code>outfile</code>	Path to output file (must be different)
<code>replacements</code>	Named charvec of length 1 (single replacement) or 2 (double replacement)
<code>overwrite</code>	Boolean. If FALSE then outfile must not yet exist. If TRUE and it already exists then it will be overwritten.

Details

This is a very limited interface and only meant for internal use.

It will replace all occurrences of a string with another string. It may do 1 or 2 replacements.

The result is written to a second file.

This is done in C++ so very fast (I hope).

Value

Nothing, but might throw an error.

Author(s)

Brad Friedman

select.param	<i>select.param</i>
--------------	---------------------

Description

Build a select AnalysisPageParam

Usage

```
select.param(..., value, choices, allow.multiple = FALSE,
             style = "dropdown")
```

Arguments

...	Passed through to simple.param . This includes at least "name", optionally "label" and "description" t not "type".
value	Default value. If not specified then the first entry in choices is taken to be the default.
choices	A character vector giving the choices to display. If named, then the values are used for display and names are used for the actual form values. If unnamed, then the values are used for both display and names.
allow.multiple	If TRUE then render as checkbox group and allow multiple selections. (The function will be provided a vector of all selected values.) If allow.multiple is TRUE then style must be "dropdown". Default: FALSE
style	Either "dropdown" (default), to render as dropdown list, or "radio", to render as radio group. If allow.multiple is TRUE then style must be "dropdown".

Details

Build a select AnalysisPageParam. This is probably rendered either as a dropdown or radio group. It is a selection from a fixed list of possible values. The list is known before page load time

Value

An AnalysisPageParam

Author(s)

Brad Friedman

Examples

```
color <- select.param("color", label="Color", description="Color of your house", choices=c("red","green","mauve"
```

service.link	<i>Build a URL to call a AnalysisPageServer webservice</i>
--------------	--

Description

This function is simply a specialization of `analysis.link` with a few conveniences for webservice-type pages. In particular, the parameters of that function about plotting are not available.

Usage

```
service.link(page, params = list(), app.base.url)
```

Arguments

page	Name of page
params	List of parameter values (as R objects—this function will encode them). Default: <code>list()</code> (no parameters).
app.base.url	Base URL for application. This is usually the prefix in which the app landing HTML page is found.

Value

URL

Author(s)

Brad Friedman

set.APS.outdir	<i>Set current AnalysisPageServer output directory</i>
----------------	--

Description

This directory is used by `embed.APS.dataset` to decide where to save the `.svg` and `.json` files.

Usage

```
set.APS.outdir(outdir)
```

Arguments

outdir	New output directory
--------	----------------------

Value

Nothing important

Note

It seems like it would be a good idea to follow this call with an `on.exit(reset.APS.outdir())`. But `on.exit` within a knitr chunk it will just first at the end of the chunk. If you are using knitr then you should just call `setup.APS.knitr()` at the top of your document then each document will have its output directory correctly set and you don't really have to worry. If you want to be really anal you could call `reset.APS.outdir()` at the bottom of your knitr document.

Author(s)

Brad Friedman

See Also

[get.APS.outdir](#), [reset.APS.outdir](#)

Examples

```
set.APS.outdir("/some/path")
get.APS.outdir()
reset.APS.outdir()
```

setup.APS.knitr

Set up knitr documents to contain AnalysisPageServer data sets

Description

If you want to embed APS data sets within a knitr document then this function should be called at the top of the document like this:

Usage

```
setup.APS.knitr(outdir, include.css = system.file("AnalysisPageServer.css",
  package = "AnalysisPageServer"), include.toc = TRUE, quiet = TRUE)
```

Arguments

<code>outdir</code>	Output directory to which front end files should be written. Default: see details.
<code>include.css</code>	Paths to CSS files to include. See details.
<code>include.toc</code>	Boolean, default TRUE. Should I include a table of contents?
<code>quiet</code>	Boolean, default TRUE. Set to FALSE to turn on some diagnostic messages

Details

```
```${r echo = FALSE} AnalysisPageServer::setup.knitr() ```
```

Calling this function has the following effects:

1. The first effect is a heinous crime. It looks up the call stack to see if you are in the middle of a `buildVignettes` call. If so then it sets `clean = FALSE` for that call. The reason for this is that for the document to work it will need a bunch of auxiliary files like `.css` and `.js`, and if `clean = TRUE` then these files won't be left and your data sets will not show at all. During R CMD build `buildVignettes` is explicitly called with `clean = TRUE` so this is the only way I could figure out how to turn it off. If it can't find `buildVignettes` in the call stack then nothing special happens. This would be the case if you are just calling `knit2html` yourself.
2. The next effect is to copy all the front end files to the output directory. The default output directory is also kind of heinous. The files need to be next to the output file. So the function again looks up the call stack to find the `knit2html` call, then grabs the name of the output file from there and uses its directory as `outdir`. If it can't find a `knit2html` call then it throws an error.

The output directory is saved with a call to the private function `set.APS.outdir`. This is then read back by `embed.APS.dataset` so that the data sets get written to the write place. You could add a `reset.APS.outdir()` call in a chunk at the bottom of your knitr document.

3. Any files in `include.css` are copied to the output directory and included as CSS. The default is a default stylesheet that will make your reports look like the vignettes.

Finally it returns the html headers as a "knit\_asis" object to be included in your document. See [custom.html.headers](#).

**Value**

HTML headers as `knit_asis` objects.

**Author(s)**

Brad Friedman

**Examples**

```
message("See vignette embedding.html")
```

---

simple.param

*simple.param*

---

**Description**

Build a simple `AnalysisPageParam`

**Usage**

```
simple.param(name, label = name, description = label, value = "",
 type = "text", advanced = 0, show.if = NULL, display.callback = NULL,
 size = "medium", required = TRUE, persistent = NULL,
 persistent.dependencies = NULL)
```

**Arguments**

name	Name of form element
label	Label for form element (typically rendered to the left of the element)
description	Description for form element (typically rendered as roll-over text)
value	The default, starting value, for the form (default: "")
type	Type of form element. This can be "text", "textarea", "checkbox", "password" or "file"
advanced	Integer. 0 means the option is not advanced, and increasing levels indicate the option is for more advanced users. Advanced > 0 should be hidden under default mode.
show.if	A list of two elements: \$name, giving the name of some other param in the set and \$values, a character vector of values. The parameter under construction should only be shown if the named parameter takes on any of the values in the \$values vector. Default (NULL) is to always show the parameter under construction.
display.callback	NULL, to follow show.if logic in deciding when/if to display the element, or a list with the two elements \$uri and \$dependent, which follow the same format as the corresponding arguments to combobox.param and provide a templated uri and a mapping from template variables to form parameters. The service should return JSON true if the widget is to be shown and false if not. It is allowed to have both a display.callback and a show.if—both conditions must be met in order to display the element.
size	A word giving the size of the element. The interpretation of this size is up to the front-end. Must from a defined set of words, which you can see by calling known.param.sizes() (currently no way to change this). Default: medium
required	Logical. Is this a required param? Default: TRUE. If set, then the front-end will require the user to set this parameter before submitting the request. The meaning of "set this parameter" is not entirely clear.
persistent	Character or NULL. If non-NULL then it is passed to the front-end. It names a variable in persistent storage that should be used to initialize the value of the parameter. The front end will provide some mechanism to change the persistent value, but until the user does so the param will be initialized from the value in the persistent space.
persistent.dependencies	A character vector or NULL (default) specifying the names of other parameters on which this one "depends". It is an error to provide this when persistent is NULL. When persistent is non-NULL, providing persistent.dependencies

makes this parameter not just "persistent" but "conditionally persistent", which is to say that the persistent value for this parameter is actually a hash lookup based on the the other parameters specified in this vector. A typical example would be a pheno fields parameter which is dependent on the study parameter. The names are taken from the Page namespace, which means that a parameter's \$name is used when this differs from its \$persistent slot.

### Details

Build a simple AnalysisPageParam. These include mainly parameters that can be rendered simply as HTML `<input>` tags.

### Value

An AnalysisPageParam. This is just a list with class name slapped on.

### Author(s)

Brad Friedman

### Examples

```
x <- simple.param("xmin", label="X-min", description="Minimum x value", type="text")
```

---

sine.handler

*sine.handler*

---

### Description

An example handler just for testing and development

### Usage

```
sine.handler(xmin = 0, xmax = 3 * pi, n = 100)
```

### Arguments

xmin	Numeric. Minimum x value to plot
xmax	Numeric. Maximum x value to plot
n	Integer. Number of points to plot

### Details

This handler takes three parameters, xmin, xmax and n, makes a plot of the sin curve from xmin to xmax (using n equally spaced points), and returns a data.frame with the x and y coordinates, with IDs A-Z, A.1-Z.1, ...

**Value**

data.frame

**Author(s)**

Brad Friedman

---

`slider.param`*slider.param*

---

**Description**

Build a slider AnalysisPageParam

**Usage**`slider.param(..., min, max, step, value = min)`**Arguments**

<code>...</code>	Passed through to <a href="#">simple.param</a> . This includes at least "name", optionally "label" and "description" but not "type".
<code>min</code>	Minimum value (number)
<code>max</code>	Maximum value (number)
<code>step</code>	Size of one step (must be $\leq$ max-min)
<code>value</code>	Default value. If not specified then the minimum is taken to be the default

**Details**

Build a slider AnalysisPageParam. This is a numeric variable. It has a minimum value, a maximum value, and a step size

**Value**

An AnalysisPageParam

**Author(s)**

Brad Friedman

**Examples**

```
slider <- slider.param("children", label="No. Children", description="Number of Children", min = 0, max = 10, step = 1)
```

---

```
startRookAnalysisPageServer
```

*Start a new Rook AnalysisPage server*

---

### Description

Start a new Rook AnalysisPage server. This is a convenience wrapper around [new.rook.analysis.page.app](#) which builds the Rook App and then also makes a Rook server (Rhttpd object) which just contains the one App. It then starts the server in a fork and returns the PID of the child process.

### Usage

```
startRookAnalysisPageServer(reg, tmpdir = tmpdir(), ...,
 app = new.rook.analysis.page.app(reg, tmpdir = tmpdir, app.name = app.name,
 ...), app.name = "RAPS", port = 5000)
```

### Arguments

reg	AnalysisPageRegistry from which to build application. Passed through to <a href="#">new.rook.analysis.page.app</a>
tmpdir	Directory for temporary files. Passed through to <a href="#">new.rook.analysis.page.app</a> . Default: tmpdir().
...	Passed through to <a href="#">new.rook.analysis.page.app</a> .
app	Rook App to put into the server. Default: <a href="#">new.rook.analysis.page.app</a> (reg, tmpdir = tmpdir, ...). Normally you would omit this argument.
app.name	Name for App within server, default "RAPS" (for Rook AnalysisPageServer). This will determine the second part of the URL, for example "/custom/RAPS".
port	Port on which to start listening.

### Value

list with two components:

\$url URL to base of application

\$pid Process ID of server

### Note

This function used to be called `start.rook.analysis.page.server` but that led to an R CMD check warning about S3 method inconsistency.

### Author(s)

Brad Friedman

### See Also

[new.rook.analysis.page.app](#), [kill.process](#)

**Examples**

```
Not run:
registry <- AnalysisPageServer:::trig.registry()
server <- startRookAnalysisPageServer(registry, port = 5102)

do some stuff
For example
landing.page.url <- rook.analysis.page.server.landing.page(server)
now go to your web browser and open landing.page.url

Or maybe something in this R process. See what the pages are
pages.url <- file.path(server$url, "R", "pages")
pages <- fromJSON(readLines(pages.url, warn = FALSE))
sapply(pages, "[[", "name")

Kill the server
kill.process(server)

End(Not run)
message("See vignette ExamplesServers.html")
```

---

static.analysis.page    *static.analysis.page*

---

**Description**

Create interactive AnalysisPage plots from static data

**Usage**

```
static.analysis.page(outdir, svg.files, dfs, titles, show.xy = FALSE,
 use.rownames.for.ids = FALSE, check.rowname.case = TRUE,
 check.html4.ids = TRUE, group.length.vecs = NULL, signif.digits = 3,
 verbose = FALSE, overwrite = FALSE, write.client = TRUE,
 client.basedir = system.file("htdocs/client/dist-apss", package =
 "AnalysisPageServer"), app.html = "analysis-page-server-static.html",
 build.full.url = write.client, data.subdir = if (write.client) "data" else
 ".", randomize.filename = FALSE)
```

**Arguments**

outdir	Base directory for output files. Will be created if it does not already exist (however, its parent directory must already exist).
svg.files	Character vector of paths to SVG files. NAs can be used as placeholders for datasets that have data but no plot. Length must be at least 1. If omitted then all NAs are used, something like <code>rep(NA, length(dfs))</code> , but a bit more careful about corner cases and types. (So you have to provide at least one of <code>svg.files</code> and <code>dfs</code> ).

<code>dfs</code>	List of data frames of the same length as <code>svg.files</code> or, if <code>length(svg.files) == 1</code> , a single <code>data.frame</code> . NULLs can be used as placeholders for datasets that have plot but no data, but an error is thrown if the corresponding entry in <code>svg.files</code> is also NA. If omitted then all NULLs are used. (So you have to provide at least one of <code>svg.files</code> and <code>dfs</code> ). Note that for <code>dfs</code> we use NULLs since it is a list but for <code>svg.files</code> we use NAs since it is a vector and you can't hold a place in a vector with NULL.
<code>titles</code>	A character vector of titles of the same length as <code>svg.files</code> to display above each plot. Default is <code>rep("", length(svg.files))</code> .
<code>show.xy</code>	Logical. If FALSE (default) then the first two columns of your data (the x and y coordinates) are used to annotate the plot but not actually exposed to the user in the table or on rollover. If TRUE then they are exposed. Recycled to <code>length(svg.files)</code> .
<code>use.rownames.for.ids</code>	Logical, default FALSE. The default behavior is to generate and assign unique IDs to each point. This makes it impossible to tag two elements in the same plot, or even in different plots with the same ID. If you set this to TRUE then your rownames are used. This means that if you are not careful you might accidentally couple between multiple datasets on the page! Recycled to length of <code>svg.files</code> , so you can set it for each data set independently if you so choose.
<code>check.rowname.case</code>	Logical, default TRUE. For data frames with <code>use.rownames.for.ids</code> TRUE a check is made that there are not two rownames that are equal without case sensitivity but not with (such as "FirstRow" and "firstrow"). If any is found then an error is thrown. This could possibly be a problem with some browsers, which might treat them the same. FALSE means to skip this check.
<code>check.html4.ids</code>	Logical, default TRUE. For data frames with <code>use.rownames.for.ids</code> TRUE a check is made that rownames are valid HTML4 IDs: begin with a letter ([A-Za-z]), then followed by any number of letters, digits ([0-9]), hyphens ("-"), underscores ("_"), colons (":"), and periods ("."). (Taken from <a href="http://www.w3.org/TR/html4/types.html#h-6.2">http://www.w3.org/TR/html4/types.html#h-6.2</a> ) FALSE means to skip this check and try to use whatever IDs are there.
<code>group.length.vecs</code>	List of integer vectors or NULLs of the same length as <code>svg.files</code> (or a single vector or NULL if <code>length(svg.files) == 1</code> ). If non-NULL, each one is passed through to <a href="#">annotate.analysis.page.svg</a> as the <code>group.lengths</code> argument, which allows you to specify that the elements might be organized into multiple non-contiguous groups, for example separate panels. A single NULL is recycled to length.
<code>signif.digits</code>	Passed through to <a href="#">annotate.data.frame</a> . The number of significant digits to which non-integer numeric fields should be rounded.
<code>verbose</code>	Boolean, default FALSE. If TRUE then <code>message()</code> will be used for progress updates.
<code>overwrite</code>	If FALSE (default) then an error is thrown if the base directory is not empty. If TRUE then files will be added to the directory, possibly overwriting existing files of the same name.



<code>write.client</code>	Boolean, default TRUE. Should I write the HTML/Javascript/CSS files necessary for the client, or just write the data files. The default is to write everything necessary. Use FALSE if you want to have only a single instance of the client files and only write data and plots with this function.
<code>client.basedir</code>	Path to client files. Default: <code>system.file("htdocs/client/dist-apss", package = "AnalysisPage")</code> . Probably should not be modified except during development work on the client.
<code>app.html</code>	Path to application <code>.html</code> file, relative to <code>client.basedir</code> . Default: <code>"analysis-page-server-static.html"</code> .
<code>build.full.url</code>	Boolean, default is the same as <code>write.client</code> . For the return value build a full URL starting with <code>"file://"</code> , using the full (normalized) path to output directory and <code>index.html</code> , then the full query string. If FALSE then just return the query string.
<code>data.subdir</code>	Subdirectory of <code>outdir</code> which will hold the data files. Special value of <code>."</code> means to put them in <code>outdir</code> itself and not create a subdirectory. Default: <code>"data"</code> if <code>write.client</code> is TRUE and <code>."</code> if it is FALSE.
<code>randomize.filename</code>	Boolean, default FALSE. Should I add some random characters to the names of the plot and dataset files? Sometimes web browsers do not refresh these files properly and so adding these random characters can overcome these stubborn cache issues.

## Details

Create interactive AnalysisPage plots from static data. An `index.html` file will be created which, when opened, will have all the data and interactivity.

Also in that subdirectory there will be other HTML and Javascript files as necessary.

Finally, your SVGs and data will be stored in subdirectories.

The first two columns of the data frame should be `x` and `y` coordinates of the points (or regions) in the plot that you want to associate with the rows of the data frame.

## Value

List with two components. First is `$URL`, which is the URL to `index.html` file, or, if `build.full.url = FALSE` then just the query string. and second is `$paths.list`, which lists the paths to all of the written plot and data files, in the format described in `link{static.analysis.page.query.string}` (and suitable for passing to that function as the parameter of the same name).

## Author(s)

Brad Friedman

## Examples

```
message("See vignette StaticContent.html")
```

---

```
static.analysis.page.query.string
 static.analysis.page.query.string
```

---

## **Description**

Build the query string for a static analysis page

## **Usage**

```
static.analysis.page.query.string(paths.list)
```

## **Arguments**

`paths.list`      `paths.list` is (for example) the return value from `.write.plots.and.data.for.static.analysis.p`. It is a list whose entries correspond to the datasets on your page. Each entry is in turn a list with a `$plot` and/or `$data` element, each of which is a URL (but could be relative to the application `.html` file) to the encoded SVG and JSON data files.

## **Details**

All static analysis pages are deployed on top of the same HTML/Javascript/CSS stack. To point the client to the correct plots and data, their paths are encoded into the query part of the URL. This function performs that encoding.

The query string will begin with "#".

To form a URL to view your data, simply append this query string to the URL for the application `.html` file.

## **Value**

Query string, starting with "#"

## **Author(s)**

Brad Friedman

---

test.package	<i>test.package</i>
--------------	---------------------

---

**Description**

Run the RUnit test harness for this package

**Usage**

```
test.package(pattern = "^test.*R$", package = "AnalysisPageServer")
```

**Arguments**

pattern	String. Regular expression. Only filenames matching
package	Name of package to test. Default: "AnalysisPageServer" this expression will be included in the test harness. Default: "^test.*R\$".

**Details**

Run the RUnit test harness for this package

**Value**

RUnitTestData

**Author(s)**

Brad Friedman, Cory Barr

**See Also**

[runTestSuite](#), [require](#)

---

trig.registry	<i>trig.registry</i>
---------------	----------------------

---

**Description**

Build a toy registry for examples and testing

**Usage**

```
trig.registry()
```

**Details**

The toy registry has a sine and a cosine page and the scattergram page.

**Value**

AnalysisPageRegistry

**Author(s)**

Brad Friedman

**Examples**

```
tr <- trig.registry()
pages(tr)
```

---

trigger.event	<i>trigger.event</i>
---------------	----------------------

---

**Description**

Trigger a registered Event

**Usage**

```
trigger.event(registry, event, ...)
```

**Arguments**

registry	EventRegistry
event	Name of event to trigger
...	Further parameters are passed to each handler in turn.

**Details**

Trigger a registered Event.

Every handler is called in turn. If any handler returns a value with a "CatchEvent" attribute set to TRUE then no further handlers are called. That attribute is removed from the return value and the value is returned to the triggering context. Otherwise the return value of only the last function is called.

If no handlers are registered then NULL is returned.

If no Event exists of that name then an error is thrown.

**Value**

See Details

**Author(s)**

Brad Friedman

## Examples

```
r <- new.event.registry()
add.event(r, "mouseclick")
add.event.handler(r, "mouseclick", function(x, y) message("Mouse clicked at coordinates (", x, ", ", y, ")"))
trigger.event(r, "mouseclick", x = 30, y = 50)
```

---

tryKeepConditions      *tryKeepConditions*

---

## Description

Try-catch wrapper, keeping error traceback and conditions

## Usage

```
tryKeepConditions(expr)
```

## Arguments

expr                      Expression to evaluate

## Details

This is a try-catch wrapper. It returns a list with four elements:

**\$value** The value of the evaluated expression, or NULL if an error was thrown and execution did not complete

**\$messages** A list of message objects, each being a message thrown during the execution, in order

**\$warnings** A list of condition objects, each being a message thrown during the execution, in order

**\$error** NULL if there was no error, otherwise the error object, which can then be passed to `getTraceback` to retrieve the error

The elements of the `$messages`, `$warnings` and `$error` are all actually two-element lists, the first being the condition object itself (named `$message`, `$warning` or `$error`) and the second begin the call stack as returned by `sys.calls()` and named `$calls`.

The class of this object is set as "AnalysisPageValueWithConditions"

## Value

AnalysisPageValueWithConditions

## Author(s)

Brad Friedman

**See Also**

`vwc.is.error`

[vwc.conditions](#) [vwc.error](#) [vwc.error.condition](#) [vwc.error.traceback](#) [vwc.is.error](#) [vwc.messages](#)  
[vwc.messages.conditions](#) [vwc.messages.tracebacks](#) [vwc.n](#) [vwc.n.messages](#) [vwc.n.warnings](#)  
[vwc.tracebacks](#) [vwc.value](#) [vwc.warnings](#) [vwc.warnings.conditions](#) [vwc.warnings.tracebacks](#)

**Examples**

```
value.with.warning <- tryKeepConditions({warning("warning message"); 3})
value.with.error <- tryKeepConditions({stop("err message")})
```

---

<code>tryKeepTraceback</code>	<i>tryKeepTraceback</i>
-------------------------------	-------------------------

---

**Description**

Wrapper around try-catch

**Usage**

```
tryKeepTraceback(expr)
```

**Arguments**

<code>expr</code>	Expression to evaluate
-------------------	------------------------

**Value**

Result of expression or error if thrown

**Examples**

```
x <- tryKeepTraceback(stop("no way"))
if(is(x, "try-error")) cat(getTraceback(x))
```

---

```
uniquify.ids.in.svg.files
 uniquify.ids.in.svg.files
```

---

## Description

Uniquify IDs in a set of SVG filename

## Usage

```
uniquify.ids.in.svg.files(svg_filenames,
 suffixes = unique.words(length(svg_filenames)),
 prefixes = .default.uniquify.ids.prefixes)
```

## Arguments

<code>svg_filenames</code>	Paths to SVG files
<code>suffixes</code>	Charvec. Suffixes to add to IDs, corresponding to <code>svg_filenames</code> . These are added after the word "glyph" and before the next character. An underscore character is added on both sides, too, to separate your suffix visually from the word "glyph" and the numbers after it. Ignored if <code>new.glyph.word</code> is provided.
<code>prefixes</code>	Named list. The names are the tokens that need to be replaced, such as "glyph" and "path". The values are charvec of prefixes. Only when those words appear after one of their prefixes is it substituted. Default is taken from <code>AnalysisPageServer:::default.uniquify.ids.prefixes</code> .

## Details

The SVG files made by R use identifiers like "glyph1-3", "glyph1-4" etc. In particular these are used to define paths for different characters in order to render text. Also there are "clip1", "clip2" etc which represent clip paths, which I think limits the viewable area in a layer of a plot, but whatever it is looks awful if it goes wrong.

If multiple SVG files are embedded in the same page then this is a big problem because they will all share the same namespace and may grab the paths defined in a different file.

This function will process a set of SVG files replacing each word "glyph" with a file-specific suffix like "glyph\_123\_", and each word "clip" with "clip\_123\_" You can provide the suffixes explicitly or let this function generate some random words, one for each file.

This function does search-and-replace with these two cleverness-es:

1. It uses C++ so it is faster (I hope) than calling `gsub`.
2. It checks the context of the words "glyph" and "clip", so if you had an SVG containing that word other than identifier it should be preserved. This is not 100% bulletproof since it doesn't actually parse the SVG file but it should be 99.99% bulletproof, unless you go out of your way to break it.

**Value**

Nothing, modifies SVG file in place.

**Note**

Typical (and recommended) usage is to only provide the `svg.files` argument and leave the rest as defaults.

**Author(s)**

Brad Friedman

**Examples**

```
svg.files <- sapply(1:2, function(i) {
 fn <- tempfile(fileext = ".svg")
 svg(fn)
 plot(1:10, main = paste("Plot", i), col = i)
 dev.off()
 fn
})
grep("glyph", readLines(svg.files[1]), value = TRUE)
uniquify.ids.in.svg.files(svg.files)
grep("glyph", readLines(svg.files[1]), value = TRUE)
```

---

urlDecode

*urlDecode a string*

---

**Description**

When a function of this name is available from the global environment (such as when running under RApache) then that function is used. Otherwise a pure R implementation is provided.

**Arguments**

x                      Character vector of strings to urlDecode

**Value**

Character vector of same length as x containing decoded strings

**Author(s)**

Brad Friedman



---

urlEncode	<i>urlEncode a string</i>
-----------	---------------------------

---

**Description**

When a function of this name is available from the global environment (such as when running under RApache) then that function is used. Otherwise a pure R implementation is provided.

**Arguments**

x                      Character vector of strings to urlEncode

**Value**

Character vector of same length as x containing encoded strings

**Author(s)**

Brad Friedman

---

validate.array.param.value	<i>validate.compound.param.value</i>
----------------------------	--------------------------------------

---

**Description**

Validate an array-type AnalysisPageParam value

**Usage**

```
validate.array.param.value(app, val, transform.labeled = FALSE)
```

**Arguments**

app                      AnalysisPageParam  
val                        Candidate value  
transform.labeled        Passed through to [validate.param.value](#). Default: FALSE.

**Details**

Validate an array-type AnalysisPageParam value:

1. val must be a list.
2. length(val) must be in the acceptable range (between app\$min and app\$max inclusive).
3. Each element of val must be validate by app\$prototype. transform.labeled is passed on.

**Value**

value, possibly with elements transformed

**Author(s)**

Brad Friedman

---

*validate.bool.param.value*

*validate.bool.param.value*

---

**Description**

Validate a boolean-type AnalysisPageParam value

**Usage**

```
validate.bool.param.value(app, val)
```

**Arguments**

app	AnalysisPageParam
val	Candidate value

**Details**

Validate a boolean-type AnalysisPageParam value:

1. val must be length 1
2. val must be a logical

**Value**

val unmodified

**Author(s)**

Brad Friedman

---

`validate.combobox.param.value`*Validate a combobox-type AnalysisPageParam value*

---

**Description**

Alias for [validate.labeled.param.value](#)

**Usage**

```
validate.combobox.param.value(app, val, transform.labeled = FALSE)
```

**Arguments**

<code>app</code>	AnalysisPageParam
<code>val</code>	Candidate value
<code>transform.labeled</code>	Logical. See details.

**Value**

Candidate value, possibly transformed into list.

---

`validate.compound.param.value`*validate.compound.param.value*

---

**Description**

Validate a compound-type AnalysisPageParam value

**Usage**

```
validate.compound.param.value(app, val, transform.labeled = FALSE)
```

**Arguments**

<code>app</code>	AnalysisPageParam
<code>val</code>	Candidate value
<code>transform.labeled</code>	Passed through to <a href="#">validate.param.value</a> of children. Default: FALSE.

**Details**

Validate a compound-type AnalysisPageParam value:

1. val must be a list. If length 0 then it is valid with no further checks.
2. names(val) must not have any duplicates.
3. names(val) must be a subset of names(app\$children).
4. Each of the values in the list must be validated by the corresponding child. transform.labeled is passed on.

**Value**

value, possibly with labeled children transformed

**Author(s)**

Brad Friedman

---

`validate.file.param.value`

*validate.file.param.value*

---

**Description**

Validate a file-type AnalysisPageParam value

**Usage**

`validate.file.param.value(app, val)`

**Arguments**

<code>app</code>	AnalysisPageParam
<code>val</code>	Candidate value

**Details**

Validate a file-type AnalysisPageParam value:

Current all values are invalid and result in an error being thrown. The reason for this is that the use case I have in mind is to check values when constructing a URL, and I don't think file-uploads will be allowed to be URL-encoded. So I can't think what values will be valid. Once I have another use case where they ought be valid then I will know what form they should take.

**Value**

Never returns

**Author(s)**

Brad Friedman

---

validate.labeled.param.value  
*validate.labeled.param.value*

---

**Description**

Validate a labeled AnalysisPageParam value

**Usage**

validate.labeled.param.value(app, val, transform.labeled = FALSE)

**Arguments**

app	AnalysisPageParam
val	Candidate value
transform.labeled	Logical. See details.

**Details**

Validate a labeled AnalysisPageParam value. Currently the labeled param types are "combobox" and "select".

Unnamed scalars are OK and named scalars are also OK.

If the scalar is unnamed then its own name will be applied: `names(val) <- val`.

If `transform.labeled` is set then instead of returning the candidate value as-is, it is transformed into `list(v=real.value, r=readable.value)`.

If `$allow.multiple == TRUE` then `length(val) > 1` is OK. The encoding is simply `list(v=real.values, r=readable.values)` where `real.values` and `readable.values` are equal-length vectors.

**Value**

Candidate value, possibly transformed into list.

**Author(s)**

Brad Friedman

validate.param.list    *validate.param.list*

---

**Description**

Validate a list of parameter values for an AnalysisPageParamSet

**Usage**

```
validate.param.list(pset, plist, transform.labeled = FALSE)
```

**Arguments**

pset                    AnalysisPageParamSet

plist                   List of parameter values for a subset of the parameters.

transform.labeled

If TRUE, then labeled parameters (combobox and select) will be transformed as necessary so that they have the list(v=value, r=readable.value) format.>

If FALSE (default), then they will be left as-is.

**Details**

Validate a list of parameter values for an AnalysisPageParamSet.

**Value**

Copy of plist, possibly transformed.

**Author(s)**

Brad Friedman

---

validate.param.value    *validate.param.value*

---

**Description**

Validate a parameter value for an AnalysisPageParam

**Usage**

```
validate.param.value(app, val, transform.labeled = FALSE)
```

**Arguments**

app	AnalysisPageParam
val	Candidate value
transform.labeled	Logical. Should the parameter value be transformed if necessary to have the list(v=value, r=readable.value) format?

**Details**

This function dispatches to the type-specific validator.

transform.labeled is passed on only if that validator accepts such an argument. This should be just combobox and select types, and indicates that the parameter value should be transformed to have the list(v=value, r=readable.value) format.

**Value**

The candidate value, possibly transformed. Throws error if the value is invalid.

**Author(s)**

Brad Friedman

**Examples**

```
sp <- simple.param("foo")
validate.param.value(sp, 3)
```

---

validate.select.param.value  
*validate.select.param.value*

---

**Description**

Validate a select-type AnalysisPageParam value

**Usage**

```
validate.select.param.value(app, val, transform.labeled = FALSE)
```

**Arguments**

app	AnalysisPageParam
val	Candidate value
transform.labeled	Logical. See details.

**Details**

Validate a select-type AnalysisPageParam value.

1. The value must be a real value among the choices.
2. The value must validate by `validate.labeled.param.value`

If `transform.labeled` is set then instead of returning the candidate value as-is, it is transformed into `list(v=real.value, r=readable.value)`.

**Value**

Candidate value, possibly transformed into list.

**Author(s)**

Brad Friedman

---

`validate.text.param.value`

*validate.text.param.value*

---

**Description**

Validate a text-type AnalysisPageParam value

**Usage**

`validate.text.param.value(app, val)`

**Arguments**

<code>app</code>	AnalysisPageParam
<code>val</code>	Candidate value

**Details**

Validate a text-type AnalysisPageParam value:

1. `val` must be a scalar (length-1 atomic)
2. `val` must be unnamed

**Value**

`val` unmodified

**Author(s)**

Brad Friedman



---

vwc.conditions	<i>vwc.conditions</i>
----------------	-----------------------

---

**Description**

Return condition object(s) for an AnalysisPageValueWithConditions

**Usage**

```
vwc.conditions(vwc, type = "messages")
```

**Arguments**

vwc	AnalysisPageValueWithConditions
type	"messages" "warnings" or "error"

**Details**

Return condition object(s) for an AnalysisPageValueWithConditions

**Value**

List of condition objects for "messages" or "warnings" or a single condition object or NULL for "error".

**Author(s)**

Brad Friedman

**See Also**

[vwc.error.condition](#), [vwc.messages.conditions](#), [vwc.warnings.conditions](#)

**Examples**

```
vwc <- tryKeepConditions({message("whatever"); warning("warning message"); 3})
vwc.conditions(vwc, "messages")
vwc.conditions(vwc, "warnings")
vwc.conditions(vwc, "error")
```

vwc.error

*vwc.error*

---

### **Description**

Access error message from AnalysisPageValueWithConditions

### **Usage**

```
vwc.error(vwc)
```

### **Arguments**

vwc                    AnalysisPageValueWithConditions

### **Details**

Access error message from AnalysisPageValueWithConditions

### **Value**

Charvec of warning messages

### **Author(s)**

Brad Friedman

### **Examples**

```
vwc <- tryKeepConditions({stop("This isn't going to work")})
vwc.error(vwc)
```

---

vwc.error.condition

*vwc.error.condition*

---

### **Description**

Get condition object for error

### **Usage**

```
vwc.error.condition(vwc)
```

### **Arguments**

vwc                    AnalysisPageValueWithCondition

**Details**

Get condition object for error

**Value**

condition object for error, or NULL

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({stop("error!")})
vwc.error.condition(vwc)
```

---

`vwc.error.traceback`    *vwc.error.traceback*

---

**Description**

Get traceback for error

**Usage**

```
vwc.error.traceback(vwc)
```

**Arguments**

`vwc`                      AnalysisPageValueWithConditions

**Details**

Get traceback for error

**Value**

Charvecs, or NULL if there was no error. (In this it differs from [vwc.tracebacks](#), which throws an error).

**Author(s)**

Brad Friedman

**See Also**

[vwc.tracebacks](#)

## Examples

```
f <- function(msg) {
 stop(msg)
}
vwc <- tryKeepConditions({
 f("foo")
})
vwc.error.traceback(vwc)
```

---

vwc.is.error

*vwc.is.error*

---

## Description

Predicate to test if an AnalysisPageValueWithConditions had an error

## Usage

```
vwc.is.error(vwc)
```

## Arguments

vwc                    AnalysisPageValueWithConditions, as returned by [tryKeepConditions](#)

## Details

Predicate to test if an AnalysisPageValueWithConditions had an error

## Value

Logical

## Author(s)

Brad Friedman

## Examples

```
vwc <- tryKeepConditions({3+5})
vwc.is.error(vwc)

vwc <- tryKeepConditions({stop("error!")})
vwc.is.error(vwc)
```

---

vwc.messages	<i>vwc.messages</i>
--------------	---------------------

---

**Description**

Return condition Messages for an AnalysisPageValueWithConditions

**Usage**

```
vwc.messages(vwc, type = "messages")
```

**Arguments**

vwc	AnalysisPageValueWithConditions
type	Type of conditions. Must be "messages" or "warnings". Default: messages.

**Details**

Return condition Messages for an AnalysisPageValueWithConditions.

**Value**

Charvec of message strings

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({message("I've got something to say.")})
vwc.messages(vwc)
```

---

vwc.messages.conditions	<i>vwc.messages.conditions</i>
-------------------------	--------------------------------

---

**Description**

Get condition object for messages

**Usage**

```
vwc.messages.conditions(vwc)
```

**Arguments**

vwc                    AnalysisPageValueWithCondition

**Details**

Get condition object for messages

**Value**

List of condition objects for messages (might be of length 0)

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({message("I've got something to say.")})
vwc.messages.conditions(vwc)
```

---

vwc.messages.tracebacks

*vwc.messages.tracebacks*

---

**Description**

Get list of messages tracebacks

**Usage**

```
vwc.messages.tracebacks(vwc)
```

**Arguments**

vwc                    AnalysisPageValueWithConditions

**Details**

Get list of tracebacks for messages.

**Value**

List of charvecs.

**Author(s)**

Brad Friedman

**See Also**[vwc.tracebacks](#)**Examples**

```
f <- function(msg) {
 message(msg)
}
vwc <- tryKeepConditions({
 f("foo")
 f("bar")
})
vwc.messages.tracebacks(vwc)
```

---

*vwc.n**vwc.n*

---

**Description**

Get number of conditions of a given type for an `AnalysisPageValueWithConditions`

**Usage**

```
vwc.n(vwc, type)
```

**Arguments**

vwc	<code>AnalysisPageValueWithConditions</code>
type	"messages", "warnings" or "error"

**Details**

Get number of conditions of a given type for an `AnalysisPageValueWithConditions`.

**Value**

Number of conditions. (For "error" it can only be 0 or 1, and is equivalent to calling as `.integer(vwc.is.error())`).

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({stop("This isn't going to work")})
vwc.n(vwc, "error")
```

---

vwc.n.messages	<i>vwc.n.messages</i>
----------------	-----------------------

---

**Description**

Get number of messages for an AnalysisPageValueWithConditions

**Usage**

```
vwc.n.messages(vwc)
```

**Arguments**

vwc	AnalysisPageValueWithConditions
-----	---------------------------------

**Details**

Get number of messages for an AnalysisPageValueWithConditions

**Value**

Non-negative Integer

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({message("Message")})
vwc.n.messages(vwc)
```

---

vwc.n.warnings	<i>vwc.n.warnings</i>
----------------	-----------------------

---

**Description**

Get number of warnings for an AnalysisPageValueWithConditions

**Usage**

```
vwc.n.warnings(vwc)
```

**Arguments**

vwc	AnalysisPageValueWithConditions
-----	---------------------------------



**Details**

Get number of warnings for an AnalysisPageValueWithConditions

**Value**

Non-negative Integer

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({warning("I'm warning you.")})
vwc.n.warnings(vwc)
```

---

vwc.tracebacks	<i>vwc.tracebacks</i>
----------------	-----------------------

---

**Description**

Return traceback(s) for an AnalysisPageValueWithConditions

**Usage**

```
vwc.tracebacks(vwc, type = "messages")
```

**Arguments**

vwc	AnalysisPageValueWithConditions
type	Type of conditions. Must be "messages", "warnings" or "error". Default: "messages". A (new) error is thrown if type is "error" but the vwc is not an error (that is, does not have an error, or more specifically, !vwc.is.error(vwc)).

**Details**

Return traceback(s) for an AnalysisPageValueWithConditions

**Value**

For "messages" or "warnings" it gives a list of Charvecs of tracebacks, as built by [getTraceback](#). For "error" it only gives a single charvec, since there is only one error.

**Author(s)**

Brad Friedman

**Examples**

```
f <- function(msg) {
 warning(msg)
}
vwc <- tryKeepConditions({
 f("foo")
 f("bar")
})
vwc.tracebacks(vwc, "warnings")
```

---

vwc.value

*vwc.value*

---

**Description**

Get value of any AnalysisPageValueWithConditions

**Usage**

```
vwc.value(vwc)
```

**Arguments**

vwc                    AnalysisPageValueWithConditions

**Details**

Get value of any AnalysisPageValueWithConditions. If an error was thrown then the value will be NULL.

**Value**

Value of original evaluated expression, or NULL if an error was thrown.

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({3+5})
vwc.value(vwc)
```

---

vwc.warnings	<i>vwc.warnings</i>
--------------	---------------------

---

**Description**

Access warning messages from AnalysisPageValueWithConditions

**Usage**

```
vwc.warnings(vwc)
```

**Arguments**

vwc	AnalysisPageValueWithConditions
-----	---------------------------------

**Details**

Access warning messages from AnalysisPageValueWithConditions

**Value**

Charvec of warning messages

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({warning("I'm warning you!"); warning("Again")})
vwc.warnings(vwc)
```

---

vwc.warnings.conditions	<i>vwc.warnings.conditions</i>
-------------------------	--------------------------------

---

**Description**

Get condition object for warnings

**Usage**

```
vwc.warnings.conditions(vwc)
```

**Arguments**

vwc	AnalysisPageValueWithCondition
-----	--------------------------------

**Details**

Get condition object for warnings

**Value**

List of condition object for warnings (might be of length 0 if no warnings were thrown).

**Author(s)**

Brad Friedman

**Examples**

```
vwc <- tryKeepConditions({warning("I'm warning you!")})
vwc.warnings.conditions(vwc)
```

---

vwc.warnings.tracebacks

*vwc.warnings.tracebacks*

---

**Description**

Get list of warnings tracebacks

**Usage**

```
vwc.warnings.tracebacks(vwc)
```

**Arguments**

vwc                    AnalysisPageValueWithConditions

**Details**

Get list of tracebacks for warnings.

**Value**

List of charvecs.

**Author(s)**

Brad Friedman

**See Also**

[vwc.tracebacks](#)

**Examples**

```
f <- function(msg) {
 warning(msg)
}
vwc <- tryKeepConditions({
 f("foo")
 f("bar")
})
vwc.warnings.tracebacks(vwc)
```

# Index

add.event, 4  
add.event.handler, 5  
analysis.link, 6  
analysis.page.link, 6, 7  
analysis.page.of.current.app, 8  
AnalysisPageValueWithConditions  
    (trypKeepConditions), 93  
annotate.analysis.page.svg, 9, 88  
annotate.data.frame, 10, 88  
AnnotatedDataFrame, 55  
apache.httpd.conf, 11  
aps.dataset.divs, 12, 13, 38, 39  
aps.one.dataset.div, 12, 13  
aps.urlEncode, 14  
array.param, 15  
autosignal.on.bloated.memory, 16, 17  
  
bind.memory.checker, 17  
bool.param, 18  
build.service, 19  
buildVignettes, 82  
  
check.memory, 17, 20  
check.same.svg, 21, 49  
check.signal, 21  
checkEquals, 21  
checkPackageInstalled, 22  
checkRookForkForVignettes, 23  
clear.event.handlers, 24, 75  
client.ip, 25  
combobox.param, 25  
compound.param, 27  
config.js, 11, 28  
copy.front.end, 29  
current.app, 8, 30  
custom.body.attr, 30, 31  
custom.body.html, 31  
custom.html.headers, 31, 82  
  
data.frame.to.json, 32  
  
data.frame.to.list, 33  
default.param, 34  
default.param.set, 35, 53  
default.service.paramset, 35  
default.stylesheets, 36  
dieIfWindows, 37  
dies.ok, 37  
  
embed.APS.dataset, 38, 76, 80, 82  
encode.datanode, 39  
eval.within.time, 40  
event.names, 42  
execute.handler, 42, 55  
  
file.param, 44  
  
get.APS.outdir, 45, 77, 81  
get.page, 46, 48, 63, 66, 74  
getTraceback, 47, 113  
  
has.event, 47  
has.page, 46, 48, 63, 66, 74  
  
ignore.lots.of.stuff, 49  
is.atomic, 57, 58  
is.registry, 50  
  
kill.process, 50, 66, 86  
knit2html, 39, 82  
known.param.sizes, 51  
  
lives.ok, 51  
  
make.standard.ids, 52  
  
new.analysis.page, 19, 20, 44, 53, 74  
new.datanode.array, 56  
new.datanode.html, 56  
new.datanode.plot, 57  
new.datanode.simple, 58  
new.datanode.table, 59

new.event.registry, 60  
new.FastRWeb.analysis.page.run, 60  
new.registry, 46, 48, 63, 66, 74  
new.response, 64  
new.rook.analysis.page.app, 65, 86

pages, 46, 48, 63, 66, 74  
param.set, 55, 67  
persistent.param.dependencies, 68  
persistent.params, 69  
platformIsWindows, 70  
protect.rapache.memory, 70

rapache.app.from.registry, 71  
rapache.trig.app, 73  
register.page, 46, 48, 55, 63, 66, 74  
remove.event, 75  
remove.old.files, 76  
require, 91  
reset.APS.outdir, 45, 76, 81, 82  
rook.analysis.page.server.landing.page,  
77  
runTestSuite, 91

search.replace, 78  
select.param, 79  
service.link, 80  
set.APS.outdir, 45, 77, 80, 82  
setup.APS.knitr, 81  
simple.param, 15, 18, 26, 27, 44, 69, 79, 82,  
85  
sine.handler, 84  
slider.param, 85  
startRookAnalysisPageServer, 66, 86  
static.analysis.page, 12, 39, 87  
static.analysis.page.query.string, 90  
svg, 43

test.package, 91  
trig.registry, 73, 91  
trigger.event, 92  
tryKeepConditions, 93, 108  
tryKeepTraceback, 94

uniquify.ids.in.svg.files, 9, 95  
unlink, 76  
urlDecode, 96  
urlEncode, 97

validate.array.param.value, 97  
validate.bool.param.value, 98  
validate.combobox.param.value, 99  
validate.compound.param.value, 99  
validate.file.param.value, 100  
validate.labeled.param.value, 99, 101  
validate.param.list, 102  
validate.param.value, 97, 99, 102  
validate.select.param.value, 103  
validate.text.param.value, 104  
vwc.conditions, 94, 105  
vwc.error, 94, 106  
vwc.error.condition, 94, 105, 106  
vwc.error.traceback, 94, 107  
vwc.is.error, 94, 108, 111  
vwc.messages, 94, 109  
vwc.messages.conditions, 94, 105, 109  
vwc.messages.tracebacks, 94, 110  
vwc.n, 94, 111  
vwc.n.messages, 94, 112  
vwc.n.warnings, 94, 112  
vwc.tracebacks, 94, 107, 111, 113, 116  
vwc.value, 94, 114  
vwc.warnings, 94, 115  
vwc.warnings.conditions, 94, 105, 115  
vwc.warnings.tracebacks, 94, 116