

# Package ‘flagme’

April 12, 2022

**Version** 1.50.0

**Date** 2015/04/06

**Title** Analysis of Metabolomics GC/MS Data

**Author** Mark Robinson <mark.robinson@imls.uzh.ch>, Riccardo Romoli <riccardo.romoli@unifi.it>

**Maintainer** Mark Robinson <mark.robinson@imls.uzh.ch>, Riccardo Romoli <riccardo.romoli@unifi.it>

**Depends** gcspikelite, xcms, CAMERA

**Imports** gplots, graphics, MASS, methods, SparseM, stats, utils

**Description** Fragment-level analysis of gas chromatography - mass spectrometry metabolomics data

**License** LGPL (>= 2)

**Collate** 0classes.R clusterAlignment.R init.R multipleAlignment.R peaksAlignment.R progressiveAlignment.R betweenAlignment.R dp.R metrics.R parse.R peaksDataset.R gatherInfo.R plotFragments.R rmaFitUnit.R addXCMSPeaks.R retFatMatrix.R plotSpectra.R exportSpectra.R

**biocViews** ImmunoOncology, DifferentialExpression, MassSpectrometry

**RoxygenNote** 6.0.1

**git\_url** <https://git.bioconductor.org/packages/flagme>

**git\_branch** RELEASE\_3\_14

**git\_last\_commit** 4dd88f1

**git\_last\_commit\_date** 2021-10-26

**Date/Publication** 2022-04-12

## R topics documented:

addAMDISPeaks . . . . .	2
addChromaTOFPeaks . . . . .	3
addXCMSPeaks . . . . .	5

betweenAlignment . . . . .	6
calcTimeDiffs . . . . .	7
clusterAlignment . . . . .	8
compress . . . . .	10
corPrt . . . . .	11
dp . . . . .	12
dynRT . . . . .	13
eitherMatrix-class . . . . .	14
exportSpectra . . . . .	15
gatherInfo . . . . .	16
imputePeaks . . . . .	17
multipleAlignment-class . . . . .	19
ndpRT . . . . .	21
normDotProduct . . . . .	22
parseChromaTOF . . . . .	23
parseELU . . . . .	24
peaksAlignment-class . . . . .	26
peaksDataset . . . . .	28
plot.peaksDataset . . . . .	29
plotImage . . . . .	31
plotMultipleSpectra . . . . .	32
plotSpectra . . . . .	33
progressiveAlignment-class . . . . .	34
retFatMatrix . . . . .	36
rmaFitUnit . . . . .	37

## Index 39

---

addAMDISPeaks	<i>Add AMDIS peak detection results</i>
---------------	---

---

### Description

Reads ASCII ELU-format files (output from AMDIS) and attaches them to an already created peaksDataset object

### Usage

```
addAMDISPeaks(object, fns=dir("[Eu][Ll][Uu]"), verbose=TRUE, ...)
```

### Arguments

object	a peaksDataset object.
fns	character vector of same length as object@rawdata (user ensures the order matches)
verbose	whether to give verbose output, default TRUE
...	arguments passed on to parseELU

**Details**

Repeated calls to parseELU to add peak detection results to the original peaksDataset object.

**Value**

peaksDataset object

**Author(s)**

Mark Robinson

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[parseELU](#), [peaksDataset](#)

**Examples**

```
# need access to CDF (raw data) and ELU files
require(gcspikelite)
gcmsPath<-paste(find.package("gcspikelite"),"data",sep="/")

# full paths to file names
cdfFiles<-dir(gcmsPath,"CDF",full=TRUE)
eluFiles<-dir(gcmsPath,"ELU",full=TRUE)

# create a 'peaksDataset' object and add AMDIS peaks to it
pd<-peaksDataset(cdfFiles[1],mz=seq(50,550),rtRange=c(7.5,8.5))
pd<-addAMDISPeaks(pd,eluFiles[1])
```

---

addChromaTOFPeaks      *Add ChromaTOF peak detection results*

---

**Description**

Reads ASCII tab-delimited format files (output from ChromaTOF) and attaches them to an already created peaksDataset object

**Usage**

```
addChromaTOFPeaks(object, fns=dir(,"[Tt][Xx][Tx]"),rtDivide=60,verbose=TRUE,...)
```

**Arguments**

object	a peaksDataset object.
fns	character vector of same length as object@rawdata (user ensures the order matches)
rtDivide	number giving the amount to divide the retention times by.
verbose	whether to give verbose output, default TRUE
...	arguments passed on to parseChromaTOF

**Details**

Repeated calls to parseChromaTOF to add peak detection results to the original peaksDataset object.

**Value**

peaksDataset object

**Author(s)**

Mark Robinson

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[parseChromaTOF](#), [peaksDataset](#)

**Examples**

```
# need access to CDF (raw data) and ChromaTOF files
require(gcspikelite)
gcmsPath<-paste(find.package("gcspikelite"),"data",sep="/")

# full paths to file names
cdfFiles<-dir(gcmsPath,"CDF",full=TRUE)
# [not run] cTofFiles<-dir(gcmsPath,"txt",full=TRUE)

# create a 'peaksDataset' object and add ChromaTOF peaks to it
pd<-peaksDataset(cdfFiles[1],mz=seq(50,550),rtrange=c(7.5,8.5))
# [not run] pd<-addChromTOFPeaks(pd,...)
```

---

addXCMSPeaks	<i>Add xcms/CAMERA peak detection results</i>
--------------	---

---

**Description**

Reads the raw data using xcms, group each extracted ion according to their retention time using CAMERA and attaches them to an already created peaksDataset object

**Usage**

```
addXCMSPeaks(files, object, peakPicking=c('cwt','mF'), ...)
```

**Arguments**

files	character vector of same length as object@rawdata (user ensures the order matches)
object	a peaksDataset object.
peakPicking	Methods to use for peak detection. See details.
...	arguments passed on to xcmsSet and annotate

**Details**

Repeated calls to xcmsSet and annotate to perform peak-picking and deconvolution. The peak detection results are added to the original peaksDataset object. Two peak detection algorithms are available: continuous wavelet transform (peakPicking=c('cwt')) and the matched filter approach (peakPicking=c('mF')) described by Smith et al (2006). For further information consult the xcms package manual.

**Value**

peaksDataset object

**Author(s)**

Riccardo Romoli <riccardo.romoli@unifi.it>

**See Also**

[peaksDataset](#) [findPeaks.matchedFilter](#) [findPeaks.centWave](#) [xcmsRaw-class](#)

**Examples**

```
# need access to CDF (raw data)
require(gcspikelite)
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")

# full paths to file names
cdfFiles <- dir(gcmsPath, "CDF", full=TRUE)
```

```
# create a 'peaksDataset' object and add XCMS peaks to it
pd <- peaksDataset(cdfFiles[1], mz=seq(50,550), rtrange=c(7.5,8.5))
pd <- addXCMSPeaks(cdfFiles[1], pd, peakPicking=c('mF'),
                  snthresh=3, fwhm=4, step=1, steps=2, mzdif=0.5)
```

---

betweenAlignment      *Data Structure for "between" alignment of many GCMS samples*

---

### Description

This function creates a "between" alignment (i.e. comparing merged peaks)

### Usage

```
betweenAlignment(pD, cAList, pAList, impList, filterMin = 1, gap = 0.7,
                 D = 10, usePeaks = TRUE, df = 30, verbose = TRUE,
                 metric = 2, type = 2, penalty = 0.2)
```

### Arguments

pD	a peaksDataset object
cAList	list of clusterAlignment objects, one for each experimental group
pAList	list of progressiveAlignment objects, one for each experimental group
impList	list of imputation lists
filterMin	minimum number of peaks within a merged peak to be kept in the analysis
gap	gap parameter
D	retention time penalty parameter
usePeaks	logical, whether to use peaks (if TRUE) or the full 2D profile alignment (if FALSE)
df	distance from diagonal to calculate similarity
verbose	logical, whether to print information
metric	numeric, different algorithm to calculate the similarity matrix between two mass spectrum. metric=1 call normDotProduct(); metric=2 call ndpRT(); metric=3 call corPrt()
type	numeric, two different type of alignment function
penalty	penalization applied to the matching between two mass spectra if $(t_1 - t_2) > D$

### Details

betweenAlignment objects gives the data structure which stores the result of an alignment across several "pseudo" datasets. These pseudo datasets are constructed by merging the "within" alignments.

**Value**

betweenAlignment object

**Author(s)**

Mark Robinson

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[multipleAlignment](#)

**Examples**

```
require(gcspikelite)
## see 'multipleAlignment'
```

---

calcTimeDiffs

*Calculate retention time shifts from profile alignments*

---

**Description**

This function takes the set of all pairwise profile alignments and use these to estimate retention time shifts between each pair of samples. These will then be used to normalize the retention time penalty of the signal peak alignment.

**Usage**

```
calcTimeDiffs(pd, ca.full, verbose=TRUE)
```

**Arguments**

pd	a peaksDataset object
ca.full	a clusterAlignment object, fit with
verbose	logical, whether to print out information

**Details**

Using the set of profile alignments,

**Value**

list of same length as ca.full@alignments with the matrices giving the retention time penalties.

**Author(s)**

Mark Robinson

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[peaksAlignment](#), [clusterAlignment](#)

**Examples**

```
require(gcspikelite)

# paths and files
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath, "CDF", full=TRUE)
eluFiles <- dir(gcmsPath, "ELU", full=TRUE)

# read data, peak detection results
pd <- peaksDataset(cdfFiles[1:2], mz=seq(50, 550), rtrange=c(7.5, 8.5))
pd <- addAMDISPeaks(pd, eluFiles[1:2])

# pairwise alignment using all scans
fullca <- clusterAlignment(pd, usePeaks=FALSE, df=100)

# calculate retention time shifts
timedf <- calcTimeDiffs(pd, fullca)
```

---

clusterAlignment	<i>Data Structure for a collection of all pairwise alignments of GCMS runs</i>
------------------	--

---

**Description**

Store the raw data and optionally, information regarding signal peaks for a number of GCMS runs

**Usage**

```
clusterAlignment(pd, runs=1:length(pd@rawdata), timedf=NULL,
                 usePeaks=TRUE, verbose=TRUE, ...)
```



**Arguments**

pD	a peaksDataset object.
runs	vector of integers giving the samples to calculate set of pairwise alignments over.
timedf	list (length = the number of pairwise alignments) of matrices giving the expected time differences expected at each pair of peaks used with usePeaks=TRUE, passed to peaksAlignment
usePeaks	logical, TRUE uses peakdata list, FALSE uses rawdata list for computing similarity.
verbose	logical, whether to print out info.
...	other arguments passed to peaksAlignment

**Details**

clusterAlignment computes the set of pairwise alignments.

**Value**

clusterAlignment object

**Author(s)**

Mark Robinson, Riccardo Romoli

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[peaksDataset](#), [peaksAlignment](#)

**Examples**

```
require(gcspikelite)

# paths and files
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath, "CDF", full=TRUE)
eluFiles <- dir(gcmsPath, "ELU", full=TRUE)

# read data, peak detection results
pd <- peaksDataset(cdfFiles[1:2], mz=seq(50,550), rtrange=c(7.5,8.5))
pd <- addAMDISPeaks(pd, eluFiles[1:2])

ca <- clusterAlignment(pd, gap=0.5, D=0.05, df=30, metric=1, type=1)
```

---

compress	<i>Compress an alignment object</i>
----------	-------------------------------------

---

### Description

Many of the peaks are not similar. So, the set of pairwise similarity matrices can be compressed.

### Usage

```
compress(object, verbose=TRUE, ...)  
decompress(object, verbose=TRUE, ...)
```

### Arguments

object	a peaksAlignment, peaksAlignment or peaksAlignment object to be compressed
verbose	logical, whether to print out information
...	further arguments

### Details

Using sparse matrix representations, a significant compression can be achieved. Here, we use the `matrix.csc` class of the `SparseM` package.

### Value

an object of the same type as the input object

### Author(s)

Mark Robinson

### References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

### See Also

[peaksAlignment](#), [clusterAlignment](#), [progressiveAlignment](#)

## Examples

```
require(gcspikelite)

# paths and files
gcmsPath<-paste(find.package("gcspikelite"),"data",sep="/")
cdfFiles<-dir(gcmsPath,"CDF",full=TRUE)
eluFiles<-dir(gcmsPath,"ELU",full=TRUE)

# read data, peak detection results
pd<-peaksDataset(cdfFiles[1:2],mz=seq(50,550),rtrange=c(7.5,8.5))
pd<-addAMDISPeaks(pd,eluFiles[1:2])

# pairwise alignment (it is compressed by default)
ca<-clusterAlignment(pd, usePeaks = TRUE, df = 20, metric=1, type=1)
object.size(ca)

# decompress
ca<-decompress(ca)
object.size(ca)
```

---

corPrt

*Retention Time Penalized Correlation*

---

## Description

This function calculates the similarity of all pairs of peaks from 2 samples, using the spectra similarity and the retention time differences

## Usage

```
corPrt(d1, d2, t1, t2, D, penalty=0.2)
```

## Arguments

d1	data matrix for sample 1
d2	data matrix for sample 2
t1	vector of retention times for sample 1
t2	vector of retention times for sample 2
D	retention time window for the matching
penalty	penalization applied to the matching between two mass spectra if $(t_1 - t_2) > D$

## Details

Computes the Pearson correlation between every pair of peak vectors in the retention time window (D) and returns the similarity matrix.

**Value**

matrix of similarities

**Author(s)**

Riccardo Romoli

**See Also**

[peaksAlignment](#)

**Examples**

```
## Not Run
require(gcspikelite)
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath,"CDF", full=TRUE)
## read data, peak detection results
pd <- peaksDataset(cdfFiles[1:3], mz=seq(50,550), rtrange=c(7.5,10.5))
pd <- addXCMSPeaks(files=cdfFiles[1:3], object=pd, peakPicking=c('mF'),
                  snthresh=3, fwhm=10, step=0.1, steps=2, mzdiff=0.5,
                  sleep=0)
## review peak picking
plot(pd, rtrange=c(7.5, 10.5), runs=c(1:3))

r <- corPrt(pd@peaksdata[[1]], pd@peaksdata[[2]],
           pd@peaksrt[[1]], pd@peaksrt[[2]], D=50, penalty=0.2)
## End (Not Run)
```

---

dp

*Dynamic programming algorithm, given a similarity matrix*

---

**Description**

This function calls C code for a bare-bones dynamic programming algorithm, finding the best cost path through a similarity matrix.

**Usage**

```
dp(M, gap=.5, big=1000000000, verbose=FALSE)
```

**Arguments**

M	similarity matrix
gap	penalty for gaps
big	large value used for matrix margins
verbose	logical, whether to print out information

**Details**

This is a pretty standard implementation of a bare-bones dynamic programming algorithm, with a single gap parameter and allowing only simple jumps through the matrix (up, right or diagonal).

**Value**

list with element match with the set of pairwise matches.

**Author(s)**

Mark Robinson

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[normDotProduct](#)

**Examples**

```
require(gcspikelite)

# paths and files
gcmsPath<-paste(find.package("gcspikelite"),"data",sep="/")
cdfFiles<-dir(gcmsPath,"CDF",full=TRUE)
eluFiles<-dir(gcmsPath,"ELU",full=TRUE)

# read data, peak detection results
pd<-peaksDataset(cdfFiles[1:2],mz=seq(50,550),rtrange=c(7.5,8.5))
pd<-addAMDISPeaks(pd,eluFiles[1:2])

# similarity matrix
r<-normDotProduct(pd@peaksdata[[1]],pd@peaksdata[[2]])

# dynamic-programming-based matching of peaks
v<-dp(r,gap=.5)
```

---

dynRT

*dynRT*

---

**Description**

Dynamic Retention Time Based Alignment algorithm, given a similarity matrix

**Usage**

```
dynRT(S)
```

**Arguments**

S                    similarity matrix

**Details**

This function align two chromatograms finding the maximum similarity among the mass spectra

**Value**

list containing the matched peaks between the two chromatograms. The number represent position of the spectra in the S matrix

**Author(s)**

riccardo.romoli@unifi.it

**Examples**

```
require(gcspikelite)
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath,"CDF", full=TRUE)
## read data, peak detection results
pd <- peaksDataset(cdfFiles[1:3], mz=seq(50,550),
  rrange=c(7.5,10.5))
pd <- addXCMSPeaks(files=cdfFiles[1:3], object=pd,
  peakPicking=c('mF'),snthresh=3, fwhm=10, step=0.1, steps=2,
  mzdiff=0.5, sleep=0)
## review peak picking
plot(pd, rrange=c(7.5, 10.5), runs=c(1:3))
## similarity
r <- ndpRT(pd@peaksdata[[1]], pd@peaksdata[[2]], pd@peaksrt[[1]],
  pd@peaksrt[[2]], D=50)
## dynamic retention time based alignment algorithm
v <- dynRT(S=r)
```

---

eitherMatrix-class     *The eitherMatrix class*

---

**Description**

A container to store either matrix or matrix.csc objects

**Author(s)**

Mark Robinson

## References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

## See Also

[peaksAlignment](#)

---

exportSpectra	<i>exportSpectra</i>
---------------	----------------------

---

## Description

Write the deconvoluted mass spectra to an external file

## Usage

```
exportSpectra(object, sample, spectraID, normalize = TRUE)
```

## Arguments

object	an object of class "peaksDataset" where to keep the mass spectra; both abundance (y) than m/z (x)
sample	character, the sample from were to plot the mass spectra
spectraID	numerical, a vector containing the index of the spectra to be plotted.
normalize	logical, if TRUE normalize the intensity of the mass peak to 100, the most abundant is 100 are scaled consequentially

## Details

Write a .msp file of the deconvoluted mass spectra. Usfull to try to identify the unknown spectra using NIST Search.

## Value

a .msp file ready to be read using NIST search

## Author(s)

riccardo.romoli@unifi.it

gatherInfo

*Gathers abundance informations from an alignment***Description**

Given an alignment table (indices of matched peaks across several samples) such as that within a `progressiveAlignment` or `multipleAlignment` object, this routines goes through the raw data and collects the abundance of each fragment peak, as well as the retention times across the samples.

**Usage**

```
gatherInfo(pD, obj, newind = NULL, method = c("apex"), findmzind = TRUE,
           useTIC = FALSE, top = NULL, intensity.cut = 0.05)
```

**Arguments**

<code>pD</code>	a <code>peaksDataset</code> object, to get the abundance data from
<code>obj</code>	either a <code>multipleAlignment</code> or <code>progressiveAlignment</code> object
<code>newind</code>	list giving the
<code>method</code>	method used to gather abundance information, only <code>apex</code> implemented currently.
<code>findmzind</code>	logical, whether to take a subset of all m/z indices
<code>useTIC</code>	logical, whether to use total ion current for abundance summaries
<code>top</code>	only use the top top peaks
<code>intensity.cut</code>	percentage of the maximum intensity

**Details**

This procedure loops through the the table of matched peaks and gathers the

**Value**

Returns a list (of lists) for each row in the alignment table. Each list has 3 elements:

<code>mz</code>	a numerical vector of the m/z fragments used
<code>rt</code>	a numerical vector for the exact retention time of each peak across all samples
<code>data</code>	matrix of fragment intensities. If <code>useTIC = TRUE</code> , this matrix will have a single row

**Author(s)**

Mark Robinson



## References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

## See Also

[imputePeaks](#)

## Examples

```
require(gcspikelite)

## paths and files
gcmsPath <- paste(find.package("gcspikelite"), "data", sep = "/")
cdfFiles <- dir(gcmsPath, "CDF", full = TRUE)
eluFiles <- dir(gcmsPath, "ELU", full = TRUE)

## read data, peak detection results
pd <- peaksDataset(cdfFiles[1:2], mz = seq(50, 550), rtrange = c(7.5, 8.5))
pd <- addAMDISPeaks(pd, eluFiles[1:2])

## multiple alignment
ma <- multipleAlignment(pd, c(1,1), wn.gap = 0.5, wn.D = 0.05, bw.gap = 0.6,
                       bw.D = 0.2, usePeaks = TRUE, filterMin = 1, df = 50,
                       verbose = TRUE, metric = 1, type = 1)

## gather apex intensities
d <- gatherInfo(pd, ma)

## table of retention times
nm <- list(paste("MP", 1:length(d), sep = ""), c("S1", "S2"))
rts <- matrix(unlist(sapply(d, .subset, "rt")), byrow = TRUE, nc = 2,
             dimnames = nm)
```

---

imputePeaks

*Imputation of locations of peaks that were undetected*

---

## Description

Using the information within the peaks that are matched across several runs, we can impute the location of the peaks that are undetected in a subset of runs

## Usage

```
imputePeaks(pd, obj, typ = 1, obj2 = NULL, filterMin = 1, verbose = TRUE)
```

## Arguments

pD	a peaksDataset object
obj	the alignment object, either multipleAlignment or progressiveAlignment, that is used to infer the unmatched peak locations
typ	type of imputation to do, 1 for simple linear interpolation (default), 2 only works if obj2 is a clusterAlignment object
obj2	a clusterAlignment object
filterMin	minimum number of peaks within a merged peak to impute
verbose	logical, whether to print out information

## Details

If you are aligning several samples and for a (small) subset of the samples in question, a peak is undetected, there is information within the alignment that can be useful in determining where the undetected peak is, based on the surrounding matched peaks. Instead of moving forward with missing values into the data matrices, this procedure goes back to the raw data and imputes the location of the apex (as well as the start and end), so that we do not need to bother with post-hoc imputation or removing data because of missing components.

We realize that imputation is prone to error and prone to attributing intensity from neighbouring peaks to the unmatched peak. We argue that this is still better than having to deal with these in statistical models after that fact. This may be an area of future improvement.

## Value

list with 3 elements apex, start and end, each masked matrices giving the scan numbers of the imputed peaks.

## Author(s)

Mark Robinson

## References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

## See Also

[multipleAlignment](#), [progressiveAlignment](#), [peaksDataset](#)

## Examples

```
require(gcspikelite)

## paths and files
gcmsPath <- paste(find.package("gcspikelite"), "data", sep = "/")
cdfFiles <- dir(gcmsPath, "CDF", full = TRUE)
eluFiles <- dir(gcmsPath, "ELU", full = TRUE)
```

```
## read data, peak detection results
pd <- peaksDataset(cdfFiles[1:3], mz = seq(50,550), rtrange = c(7.5,8.5))
pd <- addAMDISPeaks(pd, eluFiles[1:3])

## alignments
ca <- clusterAlignment(pd, gap = 0.5, D = 0.05, df = 30, metric = 1, type = 1)
pa <- progressiveAlignment(pd, ca, gap = 0.6, D = 0.1, df = 30)

v <- imputePeaks(pd, pa, filterMin = 1)
```

---

multipleAlignment-class

*Data Structure for multiple alignment of many GCMS samples*

---

## Description

Store the raw data and optionally, information regarding signal peaks for a number of GCMS runs

## Usage

```
multipleAlignment(pd, group, bw.gap = 0.8, wn.gap = 0.6, bw.D = 0.20,
                 wn.D = 0.05, filterMin = 1, lite = FALSE, usePeaks = TRUE,
                 df = 50, verbose = TRUE, timeAdjust = FALSE,
                 doImpute = FALSE, metric = 2, type = 2, penalty = 0.2)
```

## Arguments

pd	a peaksDataset object
group	factor variable of experiment groups, used to guide the alignment algorithm
bw.gap	gap parameter for "between" alignments
wn.gap	gap parameter for "within" alignments
bw.D	distance penalty for "between" alignments
wn.D	distance penalty for "within" alignments
filterMin	minimum number of peaks within a merged peak to be kept in the analysis
lite	logical, whether to keep "between" alignment details (default, FALSE)
usePeaks	logical, whether to use peaks (if TRUE) or the full 2D profile alignment (if FALSE)
df	distance from diagonal to calculate similarity
verbose	logical, whether to print information
timeAdjust	logical, whether to use the full 2D profile data to estimate retention time drifts (Note: time required)
doImpute	logical, whether to impute the location of unmatched peaks
metric	numeric, different algorithm to calculate the similarity matrix between two mass spectrum. metric=1 call normDotProduct(); metric=2 call ndpRT(); metric=3 call corPrt()
type	numeric, two different type of alignment function
penalty	penalization applied to the matching between two mass spectra if $(t_1 - t_2) > D$



---

**ndpRT***Retention Time Penalized Normalized Dot Product*

---

**Description**

This function calculates the similarity of all pairs of peaks from 2 samples, using the spectra similarity and the retention time differences

**Usage**

```
ndpRT(s1, s2, t1, t2, D)
```

**Arguments**

s1	data matrix for sample 1
s2	data matrix for sample 2
t1	vector of retention times for sample 1
t2	vector of retention times for sample 2
D	retention time window for the matching

**Details**

Computes the normalized dot product between every pair of peak vectors in the retention time window (D) and returns a similarity matrix.

**Value**

matrix of similarities

**Author(s)**

Riccardo Romoli

**See Also**

[peaksAlignment](#)

**Examples**

```
## Not Run
require(gcspikelite)
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath,"CDF", full=TRUE)

# read data, peak detection results
pd <- peaksDataset(cdfFiles[1:3], mz=seq(50,550), rtrange=c(7.5,10.5))
pd <- addXCMSPeaks(files=cdfFiles[1:3], object=pd, peakPicking=c('mF'),
```

```
                snthresh=3, fwhm=10, step=0.1, steps=2, mzdifff=0.5,
                sleep=0)
## review peak picking
plot(pd, rtrange=c(7.5, 10.5), runs=c(1:3))

r <- ndpRT(pd@peaksdata[[1]], pd@peaksdata[[2]],
           pd@peaksrt[[1]], pd@peaksrt[[2]], D=50)
## End (Not Run)
```

---

normDotProduct	<i>Normalized Dot Product</i>
----------------	-------------------------------

---

### Description

This function calculates the similarity of all pairs of peaks from 2 samples, using the spectra similarity

### Usage

```
normDotProduct(x1, x2, t1=NULL, t2=NULL, df=max(ncol(x1), ncol(x2)), D=100000, timedf=NULL, verbose=FALSE)
```

### Arguments

x1	data matrix for sample 1
x2	data matrix for sample 2
t1	vector of retention times for sample 1
t2	vector of retention times for sample 2
df	distance from diagonal to calculate similarity
D	retention time penalty
timedf	matrix of time differences to normalize to. if NULL, 0 is used.
verbose	logical, whether to print out information

### Details

Efficiently computes the normalized dot product between every pair of peak vectors and returns a similarity matrix. C code is called.

### Value

matrix of similarities

### Author(s)

Mark Robinson

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[dp](#), [peaksAlignment](#)

**Examples**

```
require(gcspikelite)

# paths and files
gcmsPath<-paste(find.package("gcspikelite"),"data",sep="/")
cdfFiles<-dir(gcmsPath,"CDF",full=TRUE)
eluFiles<-dir(gcmsPath,"ELU",full=TRUE)

# read data, peak detection results
pd<-peaksDataset(cdfFiles[1:2],mz=seq(50,550),rtrange=c(7.5,8.5))
pd<-addAMDISPeaks(pd,eluFiles[1:2])

r<-normDotProduct(pd@peaksdata[[1]],pd@peaksdata[[2]])
```

---

parseChromaTOF

*Parser for ChromaTOF files*

---

**Description**

Reads ASCII ChromaTOF-format files from AMDIS (Automated Mass Spectral Deconvolution and Identification System)

**Usage**

```
parseChromaTOF(fn,min.pc=.01,mz=seq(85,500),rt.cut=.008,rtrange=NULL,skip=1,rtDivide=60)
```

**Arguments**

fn	ChromaTOF filename to read.
min.pc	minimum percent of maximum intensity.
mz	vector of mass-to-charge bins of raw data table.
rt.cut	the difference in retention time, below which peaks are merged together.
rtrange	retention time range to parse peaks from, can speed up parsing if only interested in a small region (must be numeric vector of length 2)
skip	number of rows to skip at beginning of the ChromaTOF
rtDivide	multiplier to divide the retention times by (default: 60)

## Details

parseChromaTOF will typically be called by `addChromaTOFPeaks`, not called directly.

Peaks that are detected within `rt.cut` are merged together. This avoids peaks which are essentially overlapping.

Fragments that are less than `min.pc` of the maximum intensity fragment are discarded.

## Value

list with components `peaks` (table of spectra – rows are mass-to-charge and columns are the different detected peaks) and `tab` (table of features for each detection), according to what is stored in the ChromaTOF file.

## Author(s)

Mark Robinson

## References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

## See Also

[addAMDISPeaks](#)

## Examples

```
require(gcspikelite)

# paths and files
gcmsPath<-paste(find.package("gcspikelite"),"data",sep="/")
tofFiles<-dir(gcmsPath,"tof",full=TRUE)

# parse ChromaTOF file
cTofList<-parseChromaTOF(tofFiles[1])
```

---

parseELU

*Parser for ELU files*

---

## Description

Reads ASCII ELU-format files from AMDIS (Automated Mass Spectral Deconvolution and Identification System)

## Usage

```
parseELU(f,min.pc=.01,mz=seq(50,550),rt.cut=.008,rtrange=NULL)
```



## Arguments

f	ELU filename to read.
min.pc	minimum percent of maximum intensity.
mz	vector of mass-to-charge bins of raw data table.
rt.cut	the difference in retention time, below which peaks are merged together.
rtrange	retention time range to parse peaks from, can speed up parsing if only interested in a small region (must be numeric vector of length 2)

## Details

parseELU will typically be called by [addAMDISPeaks](#), not called directly.

Peaks that are detected within `rt.cut` are merged together. This avoids peaks which are essentially overlapping.

Fragments that are less than `min.pc` of the maximum intensity fragment are discarded.

## Value

list with components `peaks` (table of spectra – rows are mass-to-charge and columns are the different detected peaks) and `tab` (table of features for each detection), according to what is stored in the ELU file.

## Author(s)

Mark Robinson

## References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

## See Also

[addAMDISPeaks](#)

## Examples

```
require(gcspikelite)

# paths and files
gcmsPath<-paste(find.package("gcspikelite"), "data", sep="/")
eluFiles<-dir(gcmsPath, "ELU", full=TRUE)

# parse ELU file
eluList<-parseELU(eluFiles[1])
```

---

peaksAlignment-class    *Data Structure for pairwise alignment of 2 GCMS samples*

---

### Description

Store the raw data and optionally, information regarding signal peaks for a number of GCMS runs

### Usage

```
peaksAlignment(d1, d2, t1, t2, gap=0.5, D=50, timedf=NULL, df=30,
               verbose=TRUE, usePeaks=TRUE, compress=TRUE, metric=2,
               type=2, penalty=0.2)
```

### Arguments

d1	matrix of MS intensities for 1st sample (if doing a peak alignment, this contains peak apexes/areas; if doing a profile alignment, this contains scan intensities. Rows are m/z bins, columns are peaks/scans.
d2	matrix of MS intensities for 2nd sample
t1	vector of retention times for 1st sample
t2	vector of retention times for 2nd sample
gap	gap penalty for dynamic programming algorithm. Not used if type=2
D	time window (on same scale as retention time differences, t1 and t2. Default scale is seconds.)
timedf	list (length = the number of pairwise alignments) of matrices giving the expected time differences expected at each pair of peaks used with usePeaks=TRUE.
df	integer, how far from the diagonal to go to calculate the similarity of peaks. Smaller value should run faster, but be careful not to choose too low.
verbose	logical, whether to print out info.
usePeaks	logical, TRUE uses peakdata list, FALSE uses rawdata list for computing similarity.
compress	logical, whether to compress the similarity matrix into a sparse format.
metric	numeric, different algorithm to calculate the similarity matrix between two mass spectrum. metric=1 call normDotProduct(); metric=2 call ndpRT(); metric=3 call corPrt()
type	numeric, two different type of alignment function
penalty	penalization applied to the matching between two mass spectra if (t1-t2)>D

### Details

peaksAlignment is a hold-all data structure of the raw and peak detection data.

**Value**

peaksAlignment object

**Author(s)**

Mark Robinson, Riccardo Romoli

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[peaksDataset](#), [clusterAlignment](#)

**Examples**

```
## see clusterAlignment, it calls peaksAlignment

## Not Run:
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath,"CDF", full=TRUE)

# read data, peak detection results
pd <- peaksDataset(cdfFiles[1:3], mz=seq(50,550), rtrange=c(7.5,10.5))
pd <- addXCMSPeaks(files=cdfFiles[1:3], object=pd, peakPicking=c('mF'),
                  snthresh=3, fwhm=10, step=0.1, steps=2, mzdiff=0.5,
                  sleep=0)
## review peak picking
plot(pd, rtrange=c(7.5, 10.5), runs=c(1:3))

## align two chromatogram
pA <- peaksAlignment(pd@peaksdata[[1]], pd@peaksdata[[2]],
                    pd@peaksrt[[1]], pd@peaksrt[[2]], D=50,
                    metric=3, compress=FALSE, type=2, penalty=0.2)

plot(pA)
pA@v$match

par(mfrow=c(2,1))
plot(pd@peaksdata[[1]][,15], type='h', main=paste(pd@peaksrt[[1]][[15]]))
plot(pd@peaksdata[[2]][,17], type='h',
     main=paste(pd@peaksrt[[2]][[17]]))
## End (Not Run)
```

---

peaksDataset

*Data Structure for raw GCMS data and peak detection results*

---

## Description

Store the raw data and optionally, information regarding signal peaks for a number of GCMS runs

## Usage

```
peaksDataset(fns=dir(,"[Cc][Dd][Ff]"),verbose=TRUE,mz=seq(50,550),rtDivide=60,rtrange=NULL)
```

## Arguments

fns	character vector, filenames of raw data in CDF format.
verbose	logical, if TRUE then iteration progress information is output.
mz	vector giving bins of raw data table.
rtDivide	number giving the amount to divide the retention times by.
rtrange	retention time range to limit data to (must be numeric vector of length 2)

## Details

peaksDataset is a hold-all data structure of the raw and peak detection data.

## Value

peaksDataset object

## Author(s)

Mark Robinson

## References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

## Examples

```
require(gcspikelite)

# paths and files
gcmsPath<-paste(find.package("gcspikelite"),"data",sep="/")
cdfFiles<-dir(gcmsPath,"CDF",full=TRUE)
eluFiles<-dir(gcmsPath,"ELU",full=TRUE)

# read data
pd<-peaksDataset(cdfFiles[1:2],mz=seq(50,550),rtrange=c(7.5,8.5))
show(pd)
```

---

plot.peaksDataset      *Plotting functions for GCMS data objects*

---

## Description

Store the raw data and optionally, information regarding signal peaks for a number of GCMS runs

## Usage

```
.plotpD(object, runs=1:length(object@rawdata),
        mzind=1:nrow(object@rawdata[[1]]), mind=NULL,
        plotSampleLabels=TRUE, calcGlobalMax=FALSE, peakCex = 0.8,
        plotPeaks=TRUE, plotPeakBoundaries=FALSE, plotPeakLabels=FALSE,
        plotMergedPeakLabels=TRUE, mlwd=3, usePeaks=TRUE,
        plotAcrossRuns=FALSE, overlap=F, rtrange=NULL, cols=NULL, thin=1,
        max.near=median(object@rawrt[[1]]), how.near=50, scale.up=1, ...)

.plotpA(object, xlab="Peaks - run 1", ylab="Peaks - run 2",
        plotMatches=TRUE, matchPch=19, matchLwd=3,
        matchCex=.5, matchCol="black", col=colorpanel(50, "white", "green", "navyblue"),

        breaks=seq(0, 1, length=51), ...)

.plotcA(object, alignment=1, ...)
```

## Arguments

object	a peaksDataset, peaksAlignment or clusterAlignment object.
runs	for peaksDataset only: set of run indices to plot
mzind	for peaksDataset only: set of mass-to-charge indices to sum over (default, all)
mind	for peaksDataset only: matrix of aligned indices
plotSampleLabels	for peaksDataset only: logical, whether to display sample labels
calcGlobalMax	for peaksDataset only: logical, whether to calculate an overall maximum for scaling
peakCex	character expansion factor for peak labels
plotPeaks	for peaksDataset only: logical, whether to plot hashes for each peak
plotPeakBoundaries	for peaksDataset only: logical, whether to display peak boundaries
plotPeakLabels	for peaksDataset only: logical, whether to display peak labels
plotMergedPeakLabels	for peaksDataset only: logical, whether to display 'merged' peak labels
mlwd	for peaksDataset only: line width of lines indicating the alignment

<code>usePeaks</code>	for <code>peaksDataset</code> only: logical, whether to plot alignment of peaks (otherwise, scans)
<code>plotAcrossRuns</code>	for <code>peaksDataset</code> only: logical, whether to plot across peaks when unmatched peak is given
<code>overlap</code>	for <code>peaksDataset</code> only: logical, whether to plot TIC/XICs overlapping
<code>rtrange</code>	for <code>peaksDataset</code> only: vector of length 2 giving start and end of the X-axis
<code>cols</code>	for <code>peaksDataset</code> only: vector of colours (same length as the length of runs)
<code>thin</code>	for <code>peaksDataset</code> only: when <code>usePeaks=FALSE</code> , plot the alignment lines every <code>thin</code> values
<code>max.near</code>	for <code>peaksDataset</code> only: where to look for maximum
<code>how.near</code>	for <code>peaksDataset</code> only: how far away from <code>max.near</code> to look
<code>scale.up</code>	for <code>peaksDataset</code> only: a constant factor to scale the TICs
<code>plotMatches</code>	for <code>peaksDataset</code> only: logical, whether to plot matches
<code>xlab</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: x-axis label
<code>ylab</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: y-axis label
<code>matchPch</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: match plotting character
<code>matchLwd</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: match line width
<code>matchCex</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: match character expansion factor
<code>matchCol</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: match colour
<code>col</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: vector of colours for <code>colourscale</code>
<code>breaks</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: vector of breaks for <code>colourscale</code>
<code>alignment</code>	for <code>peaksAlignment</code> and <code>clusterAlignment</code> only: the set of alignments to plot
<code>...</code>	further arguments passed to the <code>plot</code> or <code>image</code> command

### Details

For `peakDataset` objects, each TIC is scale to the maximum value (as specified by the `how.near` and `max.near` values). The many parameters gives considerable flexibility of how the TICs can be visualized.

For `peakAlignment` objects, the similarity matrix is plotted and optionally, the set of matching peaks. `clusterAlignment` objects are just a collection of all pairwise `peakAlignment` objects.

### Author(s)

Mark Robinson

### References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[plotImage](#), [peaksDataset](#)

**Examples**

```
require(gcspikelite)

## paths and files
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath, "CDF", full=TRUE)
eluFiles <- dir(gcmsPath, "ELU", full=TRUE)

## read data
pd <- peaksDataset(cdfFiles[1:3], mz=seq(50,550), rtrange=c(7.5,8.5))

## image plot
plot(pd, rtrange=c(7.5,8.5), plotPeaks=TRUE, plotPeakLabels=TRUE)
```

---

<code>plotImage</code>	<i>Plot of images of GCMS data</i>
------------------------	------------------------------------

---

**Description**

Image plots (i.e. 2D heatmaps) of raw GCMS profile data

**Usage**

```
plotImage(object, run=1, rtrange=c(11, 13), main=NULL, mzrange=c(50, 200), SCALE=log2, ...)
```

**Arguments**

<code>object</code>	a <code>peaksDataset</code> object
<code>run</code>	index of the run to plot an image for
<code>rtrange</code>	vector of length 2 giving start and end of the X-axis (retention time)
<code>main</code>	main title (auto-constructed if not specified)
<code>mzrange</code>	vector of length 2 giving start and end of the Y-axis (mass-to-charge ratio)
<code>SCALE</code>	function called to scale the data (default: <code>log2</code> )
<code>...</code>	further arguments passed to the image command

**Details**

For `peakDataset` objects, each TIC is scale to the maximum value (as specified by the `how.near` and `max.near` values). The many parameters gives considerable flexibility of how the TICs can be visualized.

For `peakAlignment` objects, the similarity matrix is plotted and optionally, the set of matching peaks. `clusterAlignment` objects are just a collection of all pairwise `peakAlignment` objects.

**Author(s)**

Mark Robinson

**References**

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[plot](#), [peaksDataset](#)

**Examples**

```
require(gcspikelite)

# paths and files
gcmsPath<-paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles<-dir(gcmsPath, "CDF", full=TRUE)
eluFiles<-dir(gcmsPath, "ELU", full=TRUE)

# read data
pd<-peaksDataset(cdfFiles[1], mz=seq(50, 550), rtrange=c(7.5, 8.5))

# image plot
plotImage(pd, run=1, rtrange=c(7.5, 8.5), main="")
```

---

plotMultipleSpectra    *plotMultipleSpectra*

---

**Description**

Plot the aligned mass spectra

**Usage**

```
plotMultipleSpectra(object, outList, spectra, fullRange = TRUE,
  normalize = TRUE, ...)
```

**Arguments**

object	where to keep the mass range of the experiment
outList	where to keep the mass spectra; both abundance than m/z
spectra	a vector containing the index of the spectra to be plotted. Is referred to outList
fullRange	if TRUE uses the mass range of the whole experiment, otherwise uses only the mass range of each plotted spectrum
normalize	if TRUE normalize the intensity of the mass peak to 100, the most abundant is 100 consequentially
...	further arguments passed to the 'plot' command



**Details**

Plot the deconvoluted and aligned mass spectra collected using gatherInfo()

**Author(s)**

Riccardo Romoli <riccardo.romoli@unifi.it>

**Examples**

```
## Rd workflow
gcmsPath <- paste(find.package("gcspikelite"), "data", sep = "/")
cdfFiles <- dir(gcmsPath,"CDF", full = TRUE)

# read data, peak detection results
pd <- peaksDataset(cdfFiles[1:4], mz = seq(50,550), rtrange = c(7.5,10.5))
pd <- addXCMSPeaks(files = cdfFiles[1:4], object = pd, peakPicking = c('mF'),
                  snthresh = 2, fwhm = 8, step = 0.5, steps = 2, mzdif = 0.5,
                  sleep = 0)

## multiple alignment
ma <- multipleAlignment(pd, c(1,1,2,2), wn.gap = 0.5, wn.D = 0.05, bw.gap = 0.6,
                      bw.D = 0.2, usePeaks = TRUE, filterMin = 1, df = 50,
                      verbose = TRUE, metric = 2, type = 2)

## gather apex intensities
gip <- gatherInfo(pd, ma)
gip[[33]]
plotMultipleSpectra(object = pd, outList = gip, spectra = 33, fullRange = FALSE,
                    normalize = TRUE)
```

---

plotSpectra

*plotSpectra*

---

**Description**

Plot the mass spectra from the profile matrix

**Usage**

```
plotSpectra(object, sample, spectraID, normalize = TRUE, ...)
```

**Arguments**

object	an object of class "peaksDataset" where to keep the mass spectra; both abundance (y) than m/z (x)
sample	character, the sample from were to plot the mass spectra
spectraID	numerical, a vector containing the index of the spectra to be plotted.
normalize	logical, if TRUE normalize the intensity of the mass peak to 100, the most abundant is 100 are scaled consequentially
...	other parameter passed to the plot() function

**Details**

Plot the deconvoluted mass spectra from the profile matrix

**Author(s)**

riccardo.romoli@unifi.it

**Examples**

```
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath,"CDF", full=TRUE)
# read data, peak detection results
pd <- peaksDataset(cdfFiles[1:3], mz=seq(50,550), rtrange=c(7.5,10.5))
pd <- addXCMSPeaks(files=cdfFiles[1:3], object=pd, peakPicking=c('mF'),
                  snthresh=3, fwhm=10, step=0.1, steps=2, mzdifff=0.5,
                  sleep=0)
## align two chromatogram
pA <- peaksAlignment(pd@peaksdata[[1]], pd@peaksdata[[2]],
                    pd@peaksrt[[1]], pd@peaksrt[[2]], D=50,
                    metric=3, compress=FALSE, type=2, penalty=0.2)
pA@v$match
## plot the mass spectra
par(mfrow=c(2,1))
plotSpectra(object=pd, sample=cdfFiles[1], spectraID=10)
plotSpectra(object=pd, sample=cdfFiles[2], spectraID=12)
```

---

progressiveAlignment-class

*Data Structure for progressive alignment of many GCMS samples*

---

**Description**

Performs a progressive peak alignment (clustalw style) of multiple GCMS peak lists

**Usage**

```
progressiveAlignment(pD, cA, D=50, gap=.5, verbose=TRUE,
                    usePeaks=TRUE, df=30, compress=TRUE, type=2)
```

**Arguments**

pD	a peaksDataset object
cA	a clusterAlignment object
D	retention time penalty
gap	gap parameter
verbose	logical, whether to print information
usePeaks	logical, whether to use peaks (if TRUE) or the full 2D profile alignment (if FALSE)

df	distance from diagonal to calculate similarity
compress	logical, whether to store the similarity matrices in sparse form
type	numeric, two different type of alignment function

## Details

The progressive peak alignment we implemented here for multiple GCMS peak lists is analogous to how `clustalw` takes a set of pairwise sequence alignments and progressively builds a multiple alignment. More details can be found in the reference below.

## Value

progressiveAlignment object

## Author(s)

Mark Robinson

## References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

## See Also

[peaksDataset](#), [multipleAlignment](#)

## Examples

```
require(gcspikelite)
## paths and files
gcmsPath <- paste(find.package("gcspikelite"), "data", sep="/")
cdfFiles <- dir(gcmsPath, "CDF", full=TRUE)
eluFiles <- dir(gcmsPath, "ELU", full=TRUE)

## read data, peak detection results
pd <- peaksDataset(cdfFiles[1:2], mz=seq(50,550), rrange=c(7.5,8.5))
pd <- addAMDISPeaks(pd, eluFiles[1:2])

ca <- clusterAlignment(pd, gap=.5, D=.05, df=30, metric=1, type=1)
pa <- progressiveAlignment(pd, ca, gap=.6, D=.1, df=30, type=1)
```

---

retFatMatrix	<i>retFatMatrix</i>
--------------	---------------------

---

## Description

Build a fat data matrix

## Usage

```
retFatMatrix(object, data, minFilter = 1)
```

## Arguments

object	peakDataset object
data	a gatherInfo() object
minFilter	the minimum number for a feature to be returned in the data matrix

## Details

This function allows to extract the data from an object created using `gatherInfo` and build a data matrix using the area of the deconvoluted and aligned peaks. The row are the samples while the column represent the different peaks.

## Value

A fat data matrix containing the area of the deconvoluted and aligned peaks. The row are the samples while the column represent the different peaks

## Author(s)

Riccardo Romoli <riccardo.romoli@unifi.it>

## See Also

[gatherInfo](#)

## Examples

```
require(gcspikelite)
# paths and files
gcmsPath <- paste(find.package("gcspikelite"), "data", sep = "/")
cdfFiles <- dir(gcmsPath, "CDF", full=TRUE)
# read data, peak detection results
pd <- peaksDataset(cdfFiles[1:2], mz=seq(50,550),
                  rtrange=c(7.5,8.5))
pd <- addXCMSPeaks(files=cdfFiles[1:2], object=pd,
                  peakPicking=c('mF'), snthresh=3, fwhm=4,
                  step=1, steps=2, mzdiff=0.5)
```

```

ma <- multipleAlignment(pd = pd, group = c(1,1),
                       filterMin = 1, metric = 2, type = 2)
outList <- gatherInfo(pd, ma)
mtxD <- retFatMatrix(object = pd, data = outList, minFilter = 1)

```

---

rmaFitUnit

*Fits a robust linear model (RLM) for one metabolite*


---

### Description

Using `rlm` from MASS, this procedure fits a linear model using all the fragments

### Usage

```
rmaFitUnit(u,maxit=5,mzEffect=TRUE,cls=NULL,fitSample=TRUE,fitOrCoef=c("coef","fit"),TRANSFORM=log2)
```

### Arguments

<code>u</code>	a metabolite unit (list object with vectors <code>mz</code> and <code>rt</code> for <code>m/z</code> and retention times, respectively and a data element giving the <code>fragmentxsample</code> intensity matrix)
<code>maxit</code>	maximum number of iterations (default: 5)
<code>mzEffect</code>	logical, whether to fit <code>m/z</code> effect (default: TRUE)
<code>cls</code>	class variable
<code>fitSample</code>	whether to fit individual samples (alternative is fit by group)
<code>fitOrCoef</code>	whether to return a vector of coefficients (default: "coef"), or an <code>rlm</code> object ("fit")
<code>TRANSFORM</code>	function to transform the raw data to before fitting (default: <code>log2</code> )

### Details

Fits a robust linear model.

### Value

list giving elements of fragment and sample coefficients (if `fitOrCoef="coef"`) or a list of elements from the fitting process (if `fitOrCoef="fit"`)

### Author(s)

Mark Robinson

### References

Mark D Robinson (2008). Methods for the analysis of gas chromatography - mass spectrometry data *PhD dissertation* University of Melbourne.

**See Also**

[peaksAlignment](#), [clusterAlignment](#)

**Examples**

```
require(gcspikelite)

# paths and files
gcmsPath<-paste(find.package("gcspikelite"),"data",sep="/")
cdfFiles<-dir(gcmsPath,"CDF",full=TRUE)
eluFiles<-dir(gcmsPath,"ELU",full=TRUE)

# read data, peak detection results
pd<-peaksDataset(cdfFiles[1:2],mz=seq(50,550),rtrange=c(7.5,8.5))
pd<-addAMDISPeaks(pd,eluFiles[1:2])

# pairwise alignment using all scans
fullca<-clusterAlignment(pd, usePeaks = FALSE, df = 100)

# calculate retention time shifts
timedf<-calcTimeDiffs(pd, fullca)
```

# Index

- \* **classes**
  - betweenAlignment, 6
  - clusterAlignment, 8
  - eitherMatrix-class, 14
  - multipleAlignment-class, 19
  - peaksAlignment-class, 26
  - peaksDataset, 28
  - plot.peaksDataset, 29
  - plotImage, 31
  - progressiveAlignment-class, 34
- \* **gatherInfo()**
  - plotMultipleSpectra, 32
- \* **manip**
  - addAMDISPeaks, 2
  - addChromaTOFPeaks, 3
  - addXCMSPeaks, 5
  - calcTimeDiffs, 7
  - compress, 10
  - corPrt, 11
  - dp, 12
  - gatherInfo, 16
  - imputePeaks, 17
  - ndpRT, 21
  - normDotProduct, 22
  - parseChromaTOF, 23
  - parseELU, 24
  - rmaFitUnit, 37
- \* **plot()**
  - plotMultipleSpectra, 32
  - .plotcA (plot.peaksDataset), 29
  - .plotpA (plot.peaksDataset), 29
  - .plotpD (plot.peaksDataset), 29
- addAMDISPeaks, 2, 24, 25
- addChromaTOFPeaks, 3, 24
- addXCMSPeaks, 5
- betweenAlignment, 6, 20
- betweenAlignment-class
  - (betweenAlignment), 6
- betweenAlignment-show
  - (betweenAlignment), 6
- calcTimeDiffs, 7
- clusterAlignment, 8, 8, 10, 27, 38
- clusterAlignment-class
  - (clusterAlignment), 8
- clusterAlignment-plot
  - (clusterAlignment), 8
- clusterAlignment-show
  - (clusterAlignment), 8
- compress, 10
- compress, clusterAlignment-method
  - (compress), 10
- compress, peaksAlignment-method
  - (compress), 10
- compress, progressiveAlignment-method
  - (compress), 10
- corPrt, 11
- decompress (compress), 10
- decompress, clusterAlignment-method
  - (compress), 10
- decompress, peaksAlignment-method
  - (compress), 10
- decompress, progressiveAlignment-method
  - (compress), 10
- dp, 12, 23
- dynRT, 13
- eitherMatrix-class, 14
- exportSpectra, 15
- findPeaks.centWave, 5
- findPeaks.matchedFilter, 5
- gatherInfo, 16, 36
- imputePeaks, 17, 17
- multipleAlignment, 7, 18, 35

- multipleAlignment
  - (multipleAlignment-class), 19
- multipleAlignment-class, 19
- multipleAlignment-show
  - (multipleAlignment-class), 19
  
- ndpRT, 21
- normDotProduct, 13, 22
  
- parseChromaTOF, 4, 23
- parseELU, 3, 24
- peaksAlignment, 8–10, 12, 15, 21, 23, 38
- peaksAlignment (peaksAlignment-class), 26
- peaksAlignment-class, 26
- peaksAlignment-plot
  - (peaksAlignment-class), 26
- peaksAlignment-show
  - (peaksAlignment-class), 26
- peaksDataset, 3–5, 9, 18, 20, 27, 28, 31, 32, 35
- peaksDataset-class (peaksDataset), 28
- peaksDataset-plot (peaksDataset), 28
- peaksDataset-show (peaksDataset), 28
- plot, 32
- plot (plot.peaksDataset), 29
- plot, clusterAlignment, ANY-method
  - (clusterAlignment), 8
- plot, clusterAlignment-method
  - (clusterAlignment), 8
- plot, peaksAlignment, ANY-method
  - (peaksAlignment-class), 26
- plot, peaksAlignment-method
  - (peaksAlignment-class), 26
- plot, peaksDataset, ANY-method
  - (peaksDataset), 28
- plot, peaksDataset-method
  - (peaksDataset), 28
- plot.peaksDataset, 29
- plotImage, 31, 31
- plotImage, peaksDataset-method
  - (plotImage), 31
- plotMultipleSpectra, 32
- plotSpectra, 33
- progressiveAlignment, 10, 18, 20
- progressiveAlignment
  - (progressiveAlignment-class), 34
- progressiveAlignment-class, 34
  
- progressiveAlignment-show
  - (progressiveAlignment-class), 34
  
- retFatMatrix, 36
- rmaFitUnit, 37
  
- show, betweenAlignment-method
  - (betweenAlignment), 6
- show, clusterAlignment-method
  - (clusterAlignment), 8
- show, multipleAlignment-method
  - (multipleAlignment-class), 19
- show, peaksAlignment-method
  - (peaksAlignment-class), 26
- show, peaksDataset-method
  - (peaksDataset), 28
- show, progressiveAlignment-method
  - (progressiveAlignment-class), 34