

Package ‘sparseMatrixStats’

April 12, 2022

Type Package

Title Summary Statistics for Rows and Columns of Sparse Matrices

Version 1.6.0

Description High performance functions for row and column operations on sparse matrices.
For example: col / rowMeans2, col / rowMedians, col / rowVars etc. Currently,
the optimizations are limited to data in the column sparse format.
This package is inspired by the matrixStats package by Henrik Bengtsson.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

LinkingTo Rcpp

Imports Rcpp, Matrix, matrixStats (>= 0.60.0), methods

Depends MatrixGenerics (>= 1.5.3)

Suggests testthat (>= 2.1.0), knitr, bench, rmarkdown, BiocStyle

VignetteBuilder knitr

URL <https://github.com/const-ae/sparseMatrixStats>

BugReports <https://github.com/const-ae/sparseMatrixStats/issues>

biocViews Infrastructure, Software, DataRepresentation

git_url <https://git.bioconductor.org/packages/sparseMatrixStats>

git_branch RELEASE_3_14

git_last_commit 78627a8

git_last_commit_date 2021-10-26

Date/Publication 2022-04-12

Author Constantin Ahlmann-Eltze [aut, cre]
(<https://orcid.org/0000-0002-3762-068X>)

Maintainer Constantin Ahlmann-Eltze <artjom31415@googlemail.com>

R topics documented:

colAlls,xgCMatrix-method	3
colAnyNAs,xgCMatrix-method	4
colAnys,xgCMatrix-method	5
colAvgPerRowSet,xgCMatrix-method	7
colCollapse,xgCMatrix-method	9
colCounts,xgCMatrix-method	10
colCummaxs,dgCMatrix-method	11
colCummins,dgCMatrix-method	13
colCumprods,xgCMatrix-method	14
colCumsums,xgCMatrix-method	15
colDiffs,dgCMatrix-method	16
colIQRDiffs,dgCMatrix-method	18
colIQRs,xgCMatrix-method	19
colLogSumExps,xgCMatrix-method	20
colMadDiffs,dgCMatrix-method	22
colMads,dgCMatrix-method	23
colMaxs,dgCMatrix-method	25
colMeans2,xgCMatrix-method	26
colMedians,dgCMatrix-method	27
colMins,dgCMatrix-method	29
colOrderStats,dgCMatrix-method	30
colProds,xgCMatrix-method	31
colQuantiles,xgCMatrix-method	33
colRanges,dgCMatrix-method	34
colRanks,dgCMatrix-method	36
colSdDiffs,dgCMatrix-method	38
colSds,xgCMatrix-method	39
colSums2,xgCMatrix-method	41
colTabulates,xgCMatrix-method	42
colVarDiffs,dgCMatrix-method	43
colVars,xgCMatrix-method	45
colWeightedMads,dgCMatrix-method	46
colWeightedMeans,xgCMatrix-method	48
colWeightedMedians,dgCMatrix-method	49
colWeightedSds,xgCMatrix-method	51
colWeightedVars,xgCMatrix-method	53
xgCMatrix-class	54

`colAlls,xgCMatrix-method`

Check if all elements in a row (column) of a matrix-like object are equal to a value

Description

Check if all elements in a row (column) of a matrix-like object are equal to a value.

Usage

```
## S4 method for signature 'xgCMatrix'
colAlls(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  useNames = NA
)

## S4 method for signature 'xgCMatrix'
rowAlls(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  useNames = NA
)
```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>value</code>	The value to search for.
<code>na.rm</code>	If TRUE , NAs are excluded first, otherwise not.
<code>useNames</code>	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowAlls/matrixStats::colAlls`.

Value

Returns a `logical vector` of length `N` (`K`).

See Also

- `matrixStats::rowAlls()` and `matrixStats::colAlls()` which are used when the input is a `matrix` or `numeric` vector.
- For checks if *any* element is equal to a value, see `rowAnys()`.
- `base::all()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowAlls(mat)
colAlls(mat)
```

colAnyNAs,xgCMatrix-method

Check if any elements in a row (column) of a matrix-like object is missing

Description

Check if any elements in a row (column) of a matrix-like object is missing.

Usage

```
## S4 method for signature 'xgCMatrix'
colAnyNAs(x, rows = NULL, cols = NULL, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowAnyNAs(x, rows = NULL, cols = NULL, useNames = NA)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowAnyNAs` / `matrixStats::colAnyNAs`.

Value

Returns a [logical vector](#) of length N (K).

See Also

- `matrixStats::rowAnyNAs()` and `matrixStats::colAnyNAs()` which are used when the input is a matrix or numeric vector.
- For checks if any element is equal to a value, see [rowAnys\(\)](#).
- `base::is.na()` and `base::any()`.

Examples

```
mat <- matrix(0, nrow=10, ncol=5)
mat[sample(seq_len(5 * 10), 5)] <- NA
sp_mat <- as(mat, "dgCMatrix")
colAnyNAs(sp_mat)
```

colAnys,xgCMatrix-method

Check if any elements in a row (column) of a matrix-like object is equal to a value

Description

Check if any elements in a row (column) of a matrix-like object is equal to a value.

Usage

```
## S4 method for signature 'xgCMatrix'
colAnys(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  useNames = NA
)

## S4 method for signature 'xgCMatrix'
rowAnys(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
value	The value to search for.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowAnys` / `matrixStats::colAnys`.

Value

Returns a [logical vector](#) of length N (K).

See Also

- `matrixStats::rowAnys()` and `matrixStats::colAnys()` which are used when the input is a [matrix](#) or [numeric vector](#).
- For checks if *all* elements are equal to a value, see `rowAlls()`.
- `base::any()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowAnys(mat)
colAnys(mat)
```

colAvsPerRowSet,xgCMatrix-method

Calculates for each row (column) a summary statistic for equally sized subsets of columns (rows)

Description

Calculates for each row (column) a summary statistic for equally sized subsets of columns (rows)

Usage

```
## S4 method for signature 'xgCMatrix'
colAvsPerRowSet(
  X,
  W = NULL,
  cols = NULL,
  S,
  FUN = colMeans2,
  ...,
  na.rm = NA,
  tFUN = FALSE
)

## S4 method for signature 'xgCMatrix'
rowAvsPerColSet(
  X,
  W = NULL,
  rows = NULL,
  S,
  FUN = rowMeans2,
  ...,
  na.rm = NA,
  tFUN = FALSE
)
```

Arguments

X	An NxM matrix-like object.
W	An optional numeric NxM matrix of weights.
cols	A vector indicating the subset (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
S	An integer KxJ matrix that specifying the J subsets. Each column hold K column (row) indices for the corresponding subset. The range of values is [1, M] ([1,N]).
FUN	A row-by-row (column-by-column) summary statistic function. It is applied to to each column (row) subset of X that is specified by S.
...	Additional arguments passed to FUN.
na.rm	(logical) Argument passed to FUN() as <code>na.rm = na.rm</code> . If NA (default), then <code>na.rm = TRUE</code> is used if X or S holds missing values, otherwise <code>na.rm = FALSE</code> .
tFUN	If TRUE, X is transposed before it is passed to FUN.
rows	A vector indicating the subset (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.

Details

****Note****: the handling of missing parameters differs from `[matrixStats::colAvgPerRowSet()]`. The ‘`matrixStats`’ version always removes ‘NA’'s if there are any in the data. This method however does whatever is passed in the ‘...’ parameter.

Value

Returns a numeric JxN (MxJ) matrix.

See Also

- `matrixStats::rowAvgPerColSet()` and `matrixStats::colAvgPerRowSet()` which are used when the input is a matrix or numeric vector.

Examples

```
mat <- matrix(rnorm(20), nrow = 5, ncol = 4)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

S <- matrix(1:ncol(mat), ncol = 2)
print(S)

rowAvgPerColSet(mat, S = S, FUN = rowMeans)
rowAvgPerColSet(mat, S = S, FUN = rowVars)
```

`colCollapse,xgCMatrix-method`*Extract one cell from each row (column) of a matrix-like object*

Description

Extract one cell from each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'  
colCollapse(x, idxs, cols = NULL, useNames = NA)
```

```
## S4 method for signature 'xgCMatrix'  
rowCollapse(x, idxs, rows = NULL, useNames = NA)
```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>idxs</code>	An index vector with the position to extract. It is recycled to match the number of rows (column)
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowCollapse` / `matrixStats::colCollapse`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowCollapse()` and `matrixStats::colCollapse()` which are used when the input is a `matrix` or `numeric vector`.

Examples

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCollapse(mat, idxs = 2)
rowCollapse(mat, idxs = c(1,1,2,3,2))

colCollapse (mat, idxs = 4)

```

colCounts,xgCMatrix-method

Count how often an element in a row (column) of a matrix-like object is equal to a value

Description

Count how often an element in a row (column) of a matrix-like object is equal to a value.

Usage

```

## S4 method for signature 'xgCMatrix'
colCounts(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  useNames = NA
)

## S4 method for signature 'xgCMatrix'
rowCounts(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  useNames = NA
)

```

Arguments

x An NxK matrix-like object.

rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
value	The value to search for.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCounts/matrixStats::colCounts`.

Value

Returns a [integer vector](#) of length N (K).

See Also

- `matrixStats::rowCounts()` and `matrixStats::colCounts()` which are used when the input is a [matrix](#) or [numeric vector](#).
- For checks if any element is equal to a value, see `rowAnys()`. To check if all elements are equal, see `rowAlls()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCounts(mat)
colCounts(mat)

rowCounts(mat, value = 0)
colCounts(mat, value = Inf, na.rm = TRUE)
```

colCummaxs,dgCMatrix-method

Calculates the cumulative maxima for each row (column) of a matrix-like object

Description

Calculates the cumulative maxima for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'  
colCummaxs(x, rows = NULL, cols = NULL, useNames = NA)  
  
## S4 method for signature 'dgCMatrix'  
rowCummaxs(x, rows = NULL, cols = NULL, useNames = NA)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCummaxs / matrixStats::colCummaxs`.

Value

Returns a [numeric matrix](#) with the same dimensions as x.

See Also

- `matrixStats::rowCummaxs()` and `matrixStats::colCummaxs()` which are used when the input is a [matrix](#) or [numeric vector](#).
- For single maximum estimates, see `rowMaxs()`.
- `base::cummax()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)  
mat[2, 1] <- NA  
mat[3, 3] <- Inf  
mat[4, 1] <- 0  
  
print(mat)  
  
rowCummaxs(mat)  
colCummaxs(mat)
```

`colCummins,dgCMatrix-method`

Calculates the cumulative minima for each row (column) of a matrix-like object

Description

Calculates the cumulative minima for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'  
colCummins(x, rows = NULL, cols = NULL, useNames = NA)
```

```
## S4 method for signature 'dgCMatrix'  
rowCummins(x, rows = NULL, cols = NULL, useNames = NA)
```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>useNames</code>	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCummins / matrixStats::colCummins`.

Value

Returns a [numeric matrix](#) with the same dimensions as `x`.

See Also

- `matrixStats::rowCummins()` and `matrixStats::colCummins()` which are used when the input is a matrix or numeric vector.
- For single minimum estimates, see `rowMins()`.
- `base::cummin()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCummins(mat)
colCummins(mat)
```

colCumprods, xgCMatrix-method

Calculates the cumulative product for each row (column) of a matrix-like object

Description

Calculates the cumulative product for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colCumprods(x, rows = NULL, cols = NULL, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowCumprods(x, rows = NULL, cols = NULL, useNames = NA)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCumprods / matrixStats::colCumprods`.

Value

Returns a [numeric matrix](#) with the same dimensions as x.

See Also

- `matrixStats::rowCumprods()` and `matrixStats::colCumprods()` which are used when the input is a matrix or numeric vector.
- `base::cumprod()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCumprods(mat)
colCumprods(mat)
```

colCumsums,xgCMatrix-method

Calculates the cumulative sum for each row (column) of a matrix-like object

Description

Calculates the cumulative sum for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colCumsums(x, rows = NULL, cols = NULL, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowCumsums(x, rows = NULL, cols = NULL, useNames = NA)
```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>useNames</code>	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowCumsums / matrixStats::colCumsums`.

Value

Returns a `numeric matrix` with the same dimensions as `x`.

See Also

- `matrixStats::rowCumsums()` and `matrixStats::colCumsums()` which are used when the input is a `matrix` or `numeric vector`.
- `base::cumsum()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowCumsums(mat)
colCumsums(mat)
```

colDiffs,dgCMatrix-method

Calculates the difference between each element of a row (column) of a matrix-like object

Description

Calculates the difference between each element of a row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colDiffs(
  x,
  rows = NULL,
  cols = NULL,
  lag = 1L,
  differences = 1L,
  useNames = NA
)
```



```
## S4 method for signature 'dgCMatrix'
rowDiffs(
  x,
  rows = NULL,
  cols = NULL,
  lag = 1L,
  differences = 1L,
  useNames = NA
)
```

Arguments

<code>x</code>	An $N \times K$ matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>lag</code>	An integer specifying the lag.
<code>differences</code>	An integer specifying the order of difference.
<code>useNames</code>	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowDiffs/matrixStats::colDiffs`.

Value

Returns a [numeric matrix](#) with one column (row) less than `x`: $N \times (K - 1)$ or $(N - 1) \times K$.

See Also

- `matrixStats::rowDiffs()` and `matrixStats::colDiffs()` which are used when the input is a [matrix](#) or [numeric vector](#).
- `base::diff()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowDiffs(mat)
colDiffs(mat)
```

colIQRDiffs,dgCMatrix-method

Calculates the interquartile range of the difference between each element of a row (column) of a matrix-like object

Description

Calculates the interquartile range of the difference between each element of a row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colIQRDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  useNames = NA
)
```

```
## S4 method for signature 'dgCMatrix'
rowIQRDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
diff	An integer specifying the order of difference.
trim	A double in [0,1/2] specifying the fraction of observations to be trimmed from each end of (sorted) x before estimation.

useNames If `NA`, the default behavior of the function about naming support is remained. If `FALSE`, no naming support is done. Else if `TRUE`, names attributes of result are set.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowIQRDiffs / matrixStats::colIQRDiffs`.

Value

Returns a `numeric vector` of length `N (K)`.

See Also

- `matrixStats::rowIQRDiffs()` and `matrixStats::colIQRDiffs()` which are used when the input is a `matrix` or `numeric vector`.
- For the direct interquartile range see also `rowIQRs`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowIQRDiffs(mat)
colIQRDiffs(mat)
```

colIQRs,xgCMatrix-method

Calculates the interquartile range for each row (column) of a matrix-like object

Description

Calculates the interquartile range for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colIQRs(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowIQRs(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , NAs are excluded first, otherwise not.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowIQRs` / `matrixStats::colIQRs`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowIQRs()` and `matrixStats::colIQRs()` which are used when the input is a `matrix` or `numeric` vector.
- For a non-robust analog, see `rowSds()`. For a more robust version see `rowMads()`
- `stats::IQR()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowIQRs(mat)
colIQRs(mat)
```

colLogSumExps, xgCMatrix-method

Accurately calculates the logarithm of the sum of exponentials for each row (column) of a matrix-like object

Description

Accurately calculates the logarithm of the sum of exponentials for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colLogSumExps(lx, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowLogSumExps(lx, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

lx	An NxK matrix-like object. Typically lx are log(x) values.
rows	A vector indicating the subset (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowLogSumExps / matrixStats::colLogSumExps`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowLogSumExps()` and `matrixStats::colLogSumExps()` which are used when the input is a [matrix](#) or [numeric vector](#).
- `rowSums2()`

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowLogSumExps(mat)
colLogSumExps(mat)
```

colMadDiffs,dgCMatrix-method

Calculates the mean absolute deviation of the difference between each element of a row (column) of a matrix-like object

Description

Calculates the mean absolute deviation of the difference between each element of a row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colMadDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  constant = 1.4826,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'dgCMatrix'
rowMadDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  constant = 1.4826,
  ...,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.

diff	An integer specifying the order of difference.
trim	A double in [0,1/2] specifying the fraction of observations to be trimmed from each end of (sorted) x before estimation.
constant	A scale factor. See <code>mad</code> for details.
...	Additional arguments passed to specific methods.
useNames	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.

Details

The S4 methods for x of type `matrix`, `array`, or `numeric` call `matrixStats::rowMadDiffs / matrixStats::colMadDiffs`.

Value

Returns a `numeric vector` of length N (K).

See Also

- `matrixStats::rowMadDiffs()` and `matrixStats::colMadDiffs()` which are used when the input is a matrix or numeric vector.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMadDiffs(mat)
colMadDiffs(mat)
```

colMads,dgCMatrix-method

Calculates the median absolute deviation for each row (column) of a matrix-like object

Description

Calculates the median absolute deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colMads(
  x,
  rows = NULL,
  cols = NULL,
  center = NULL,
  constant = 1.4826,
  na.rm = FALSE,
  useNames = NA
)

## S4 method for signature 'dgCMatrix'
rowMads(
  x,
  rows = NULL,
  cols = NULL,
  center = NULL,
  constant = 1.4826,
  na.rm = FALSE,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
center	(optional) the center, defaults to the row means
constant	A scale factor. See <code>stats::mad()</code> for details.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMads/matrixStats::colMads`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowMads()` and `matrixStats::colMads()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For non-robust standard deviation estimates, see `rowSds()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMads(mat)
colMads(mat)
```

colMaxs,dgCMatrix-method

Calculates the maximum for each row (column) of a matrix-like object

Description

Calculates the maximum for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colMaxs(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)

## S4 method for signature 'dgCMatrix'
rowMaxs(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>na.rm</code>	If TRUE , NAs are excluded first, otherwise not.
<code>useNames</code>	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowMaxs` / `matrixStats::colMaxs`.

Value

Returns a `numeric vector` of length `N` (`K`).

See Also

- `matrixStats::rowMaxs()` and `matrixStats::colMaxs()` which are used when the input is a `matrix` or `numeric vector`.
- For min estimates, see `rowMins()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMaxs(mat)
colMaxs(mat)
```

colMeans2,xgCMatrix-method

Calculates the mean for each row (column) of a matrix-like object

Description

Calculates the mean for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

`x` An `NxK` matrix-like object.

`rows` A `vector` indicating the subset of rows (and/or columns) to operate over. If `NULL`, no subsetting is done.

cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMeans2/matrixStats::colMeans2`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowMeans2()` and `matrixStats::colMeans2()` which are used when the input is a [matrix](#) or [numeric vector](#).
- See also [rowMeans\(\)](#) for the corresponding function in base R.
- For variance estimates, see [rowVars\(\)](#).
- See also the base R version `base::rowMeans()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMeans2(mat)
colMeans2(mat)
```

colMedians,dgCMatrix-method

Calculates the median for each row (column) of a matrix-like object

Description

Calculates the median for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colMedians(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)

## S4 method for signature 'dgCMatrix'
rowMedians(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMedians / matrixStats::colMedians`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowMedians()` and `matrixStats::colMedians()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMedians(mat)
colMedians(mat)
```

`colMins,dgCMatrix-method`*Calculates the minimum for each row (column) of a matrix-like object*

Description

Calculates the minimum for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'  
colMins(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)  
  
## S4 method for signature 'dgCMatrix'  
rowMins(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>na.rm</code>	If TRUE , NAs are excluded first, otherwise not.
<code>useNames</code>	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMins` / `matrixStats::colMins`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowMins()` and `matrixStats::colMins()` which are used when the input is a [matrix](#) or [numeric vector](#).
- For max estimates, see `rowMaxs()`.

Examples

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowMins(mat)
colMins(mat)

```

```
colOrderStats,dgCMatrix-method
```

Calculates an order statistic for each row (column) of a matrix-like object

Description

Calculates an order statistic for each row (column) of a matrix-like object.

Usage

```

## S4 method for signature 'dgCMatrix'
colOrderStats(
  x,
  rows = NULL,
  cols = NULL,
  which = 1,
  useNames = NA,
  na.rm = FALSE
)

## S4 method for signature 'dgCMatrix'
rowOrderStats(
  x,
  rows = NULL,
  cols = NULL,
  which = 1,
  useNames = NA,
  na.rm = FALSE
)

```

Arguments

x An NxK matrix-like object.

rows A [vector](#) indicating the subset of rows (and/or columns) to operate over. If [NULL](#), no subsetting is done.

cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
which	An integer index in [1,K] ([1,N]) indicating which order statistic to be returned
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.
na.rm	If TRUE , NAs are excluded first, otherwise not.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowOrderStats / matrixStats::colOrderStats`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowOrderStats()` and `matrixStats::colOrderStats()` which are used when the input is a [matrix](#) or [numeric vector](#).

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- 2
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowOrderStats(mat, which = 1)
colOrderStats(mat, which = 3)
```

colProds,xgCMatrix-method

Calculates the product for each row (column) in a matrix

Description

Calculates the product for each row (column) in a matrix

Usage

```
## S4 method for signature 'xgCMatrix'
colProds(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowProds(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

<code>x</code>	An $N \times K$ matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , <code>NA</code> s are excluded first, otherwise not.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.

Details

Attention: This method ignores the order of the values, because it assumes that the product is commutative. Unfortunately, for 'double' this is not true. For example 'NaN * NA = NaN', but 'NA * NaN = NA'. This is relevant for this function if there are '+-Inf', because 'Inf * 0 = NaN'. This function returns 'NA' whenever there is 'NA' in the input. This is different from 'matrixStats::colProds()'.

Value

Returns a [numeric vector](#) of length $N(K)$.

See Also

- `matrixStats::rowProds()` and `matrixStats::colProds()` which are used when the input is a matrix or numeric vector.
- For sums across rows (columns), see `rowSums2()` (`colSums2()`)
- `base::prod()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowProds(mat)
colProds(mat)
```

 colQuantiles,xgCMatrix-method

Calculates quantiles for each row (column) of a matrix-like object

Description

Calculates quantiles for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colQuantiles(
  x,
  rows = NULL,
  cols = NULL,
  probs = seq(from = 0, to = 1, by = 0.25),
  na.rm = FALSE,
  type = 7L,
  useNames = NA,
  drop = TRUE
)
```

```
## S4 method for signature 'xgCMatrix'
rowQuantiles(
  x,
  rows = NULL,
  cols = NULL,
  probs = seq(from = 0, to = 1, by = 0.25),
  na.rm = FALSE,
  type = 7L,
  useNames = NA,
  drop = TRUE
)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
probs	A numeric vector of J probabilities in [0, 1].
na.rm	If TRUE , NAs are excluded first, otherwise not.
type	An integer specifying the type of estimator. See <code>stats::quantile()</code> . for more details.

useNames	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.
drop	If <code>TRUE</code> a vector is returned if <code>J == 1</code> .

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowQuantiles / matrixStats::colQuantiles`.

Value

a `numeric` `NxJ` (`KxJ`) `matrix`, where `N` (`K`) is the number of rows (columns) for which the `J` values are calculated.

See Also

- `matrixStats::rowQuantiles()` and `matrixStats::colQuantiles()` which are used when the input is a `matrix` or `numeric` vector.
- `stats::quantile`

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowQuantiles(mat)
colQuantiles(mat)
```

colRanges,dgCMatrix-method

Calculates the minimum and maximum for each row (column) of a matrix-like object

Description

Calculates the minimum and maximum for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colRanges(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)

## S4 method for signature 'dgCMatrix'
rowRanges(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowRanges / matrixStats::colRanges`.

Value

a [numeric](#) Nx2 (Kx2) [matrix](#), where N (K) is the number of rows (columns) for which the ranges are calculated.

See Also

- `matrixStats::rowRanges()` and `matrixStats::colRanges()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- For max estimates, see `rowMaxs()`.
- For min estimates, see `rowMins()`.
- `base::range()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowRanges(mat)
colRanges(mat)
```

 colRanks,dgCMatrix-method

Calculates the rank of the elements for each row (column) of a matrix-like object

Description

Calculates the rank of the elements for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colRanks(
  x,
  rows = NULL,
  cols = NULL,
  ties.method = c("max", "average", "min"),
  preserveShape = FALSE,
  na.handling = c("keep", "last"),
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'dgCMatrix'
rowRanks(
  x,
  rows = NULL,
  cols = NULL,
  ties.method = c("max", "average", "min"),
  preserveShape = TRUE,
  na.handling = c("keep", "last"),
  ...,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
ties.method	A character string specifying how ties are treated. Note that the default specifies fewer options than the original matrixStats package.
preserveShape	a boolean that specifies if the returned matrix has the same dimensions as the input matrix. By default this is true for 'rowRanks()', but false for 'colRanks()'.

na.handling	string specifying how 'NA's are handled. They can either be preserved with an 'NA' rank ('keep') or sorted in at the end ('last'). Default is 'keep' derived from the behavior of the equivalent
...	Additional arguments passed to specific methods.
useNames	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.

Details

There are three different methods available for handling ties:

'max' for values with identical values the maximum rank is returned

'average' for values with identical values the average of the ranks they cover is returned. Note, that in this case the return value is of type 'numeric'.

'min' for values with identical values the minimum rank is returned.

Value

a matrix of type `integer` is returned unless `ties.method = "average"`. It has dimensions 'N x J' (K x J) `matrix`, where N (K) is the number of rows (columns) of the input x.

See Also

- `matrixStats::rowRanks()` and `matrixStats::colRanks()` which are used when the input is a matrix or numeric vector.
- `base::rank`

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowRanks(mat)
colRanks(mat)
```

 colSdDiffs,dgCMatrix-method

Calculates the standard deviation of the difference between each element of a row (column) of a matrix-like object

Description

Calculates the standard deviation of the difference between each element of a row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colSdDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  useNames = NA
)
```

```
## S4 method for signature 'dgCMatrix'
rowSdDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
diff	An integer specifying the order of difference.
trim	A double in [0,1/2] specifying the fraction of observations to be trimmed from each end of (sorted) x before estimation.

useNames If `NA`, the default behavior of the function about naming support is remained. If `FALSE`, no naming support is done. Else if `TRUE`, names attributes of result are set.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowSdDiffs` / `matrixStats::colSdDiffs`.

Value

Returns a `numeric vector` of length `N` (`K`).

See Also

- `matrixStats::rowSdDiffs()` and `matrixStats::colSdDiffs()` which are used when the input is a `matrix` or `numeric vector`.
- for the direct standard deviation see `rowSds()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowSdDiffs(mat)
colSdDiffs(mat)
```

colSds,xgCMatrix-method

Calculates the standard deviation for each row (column) of a matrix-like object

Description

Calculates the standard deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colSds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
```

```

    center = NULL,
    useNames = NA
  )

## S4 method for signature 'xgCMatrix'
rowSds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  useNames = NA
)

```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>na.rm</code>	If TRUE , NAs are excluded first, otherwise not.
<code>center</code>	(optional) the center, defaults to the row means
<code>useNames</code>	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowSds/matrixStats::colSds`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowSds()` and `matrixStats::colSds()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For variance estimates, see `rowVars()`.

Examples

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

```



```
print(mat)

rowSds(mat)
colSds(mat)
```

colSums2, xgCMatrix-method

Calculates the sum for each row (column) of a matrix-like object

Description

Calculates the sum for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, useNames = NA)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowSums2` / `matrixStats::colSums2`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowSums2()` and `matrixStats::colSums2()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- `base::sum()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowSums2(mat)
colSums2(mat)
```

colTabulates, xgCMatrix-method

Tabulates the values in a matrix-like object by row (column)

Description

Tabulates the values in a matrix-like object by row (column).

Usage

```
## S4 method for signature 'xgCMatrix'
colTabulates(x, rows = NULL, cols = NULL, values = NULL, useNames = NA)

## S4 method for signature 'xgCMatrix'
rowTabulates(x, rows = NULL, cols = NULL, values = NULL, useNames = NA)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
values	the values to search for.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowTabulates` / `matrixStats::colTabulates`.

Value

a [numeric](#) NxJ (KxJ) [matrix](#), where N (K) is the number of rows (columns) for which the J values are calculated.

See Also

- `matrixStats::rowTabulates()` and `matrixStats::colTabulates()` which are used when the input is a matrix or numeric vector.
- `base::table()`

Examples

```
mat <- matrix(rpois(15, lambda = 3), nrow = 5, ncol = 3)
mat[2, 1] <- NA_integer_
mat[3, 3] <- 0L
mat[4, 1] <- 0L

print(mat)

rowTabulates(mat)
colTabulates(mat)

rowTabulates(mat, values = 0)
colTabulates(mat, values = 0)
```

colVarDiffs,dgCMatrix-method

Calculates the variance of the difference between each element of a row (column) of a matrix-like object

Description

Calculates the variance of the difference between each element of a row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colVarDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  useNames = NA
)

## S4 method for signature 'dgCMatrix'
rowVarDiffs(
  x,
  rows = NULL,
```

```

cols = NULL,
na.rm = FALSE,
diff = 1L,
trim = 0,
useNames = NA
)

```

Arguments

<code>x</code>	An NxK matrix-like object.
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If <code>NULL</code> , no subsetting is done.
<code>na.rm</code>	If <code>TRUE</code> , NAs are excluded first, otherwise not.
<code>diff</code>	An integer specifying the order of difference.
<code>trim</code>	A double in <code>[0,1/2]</code> specifying the fraction of observations to be trimmed from each end of (sorted) <code>x</code> before estimation.
<code>useNames</code>	If <code>NA</code> , the default behavior of the function about naming support is remained. If <code>FALSE</code> , no naming support is done. Else if <code>TRUE</code> , names attributes of result are set.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowVarDiffs / matrixStats::colVarDiffs`.

Value

Returns a [numeric vector](#) of length `N (K)`.

See Also

- `matrixStats::rowVarDiffs()` and `matrixStats::colVarDiffs()` which are used when the input is a `matrix` or `numeric vector`.
- for the direct variance see `rowVars()`.

Examples

```

mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowVarDiffs(mat)
colVarDiffs(mat)

```

 colVars, xgCMatrix-method

Calculates the variance for each row (column) of a matrix-like object

Description

Calculates the variance for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colVars(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  useNames = NA
)

## S4 method for signature 'xgCMatrix'
rowVars(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
center	(optional) the center, defaults to the row means.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowVars/matrixStats::colVars`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowVars()` and `matrixStats::colVars()` which are used when the input is a matrix or numeric vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For standard deviation estimates, see `rowSds()`.
- `stats::var()`.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)

rowVars(mat)
colVars(mat)
```

colWeightedMads,dgCMatrix-method

Calculates the weighted median absolute deviation for each row (column) of a matrix-like object

Description

Calculates the weighted median absolute deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colWeightedMads(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  constant = 1.4826,
  center = NULL,
  useNames = NA
)

## S4 method for signature 'dgCMatrix'
```

```

rowWeightedMads(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  constant = 1.4826,
  center = NULL,
  useNames = NA
)

```

Arguments

x	An NxK matrix-like object.
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
constant	A scale factor. See <code>stats::mad()</code> for details.
center	Not supported at the moment.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowWeightedMads / matrixStats::colWeightedMads`.

Value

Returns a [numeric vector](#) of length N (K).

See Also

- `matrixStats::rowWeightedMads()` and `matrixStats::colWeightedMads()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- See also [rowMads](#) for the corresponding unweighted function.

Examples

```

mat <- matrix(0, nrow=10, ncol=5)
mat[sample(prod(dim(mat)), 25)] <- rpois(n=25, 5)
sp_mat <- as(mat, "dgCMatrix")

```

```

weights <- rnorm(10, mean=1, sd=0.1)

# sparse version
sparseMatrixStats::colWeightedMads(sp_mat, weights)

# Attention the result differs from matrixStats
# because it always uses 'interpolate=FALSE'.
matrixStats::colWeightedMads(mat, weights)

```

colWeightedMeans, xgCMatrix-method

Calculates the weighted mean for each row (column) of a matrix-like object

Description

Calculates the weighted mean for each row (column) of a matrix-like object.

Usage

```

## S4 method for signature 'xgCMatrix'
colWeightedMeans(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  useNames = NA
)

## S4 method for signature 'xgCMatrix'
rowWeightedMeans(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  useNames = NA
)

```

Arguments

x	An NxK matrix-like object.
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.

cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowWeightedMeans` / `matrixStats::colWeightedMeans`.

Value

Returns a [numeric vector](#) of length `N(K)`.

See Also

- `matrixStats::rowWeightedMeans()` and `matrixStats::colWeightedMeans()` which are used when the input is a [matrix](#) or [numeric vector](#).
- See also [rowMeans2](#) for the corresponding unweighted function.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
rowWeightedMeans(mat, w = w[1:3])
colWeightedMeans(mat, w = w)
```

colWeightedMedians,dgCMatrix-method

Calculates the weighted median for each row (column) of a matrix-like object

Description

Calculates the weighted median for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'dgCMatrix'
colWeightedMedians(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  useNames = NA
)

## S4 method for signature 'dgCMatrix'
rowWeightedMedians(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NA s are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type **matrix**, **array**, or **numeric** call `matrixStats::rowWeightedMedians` / `matrixStats::colWeightedMedians`.

Value

Returns a **numeric vector** of length N (K).

See Also

- `matrixStats::rowWeightedMedians()` and `matrixStats::colWeightedMedians()` which are used when the input is a **matrix** or **numeric vector**.

- See also [rowMedians](#) for the corresponding unweighted function.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
rowWeightedMedians(mat, w = w[1:3])
colWeightedMedians(mat, w = w)
```

colWeightedSds,xgCMatrix-method

Calculates the weighted standard deviation for each row (column) of a matrix-like object

Description

Calculates the weighted standard deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colWeightedSds(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  useNames = NA
)

## S4 method for signature 'xgCMatrix'
rowWeightedSds(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for x of type **matrix**, **array**, or **numeric** call `matrixStats::rowWeightedSds / matrixStats::colWeightedSds`.

Value

Returns a **numeric vector** of length N (K).

See Also

- `matrixStats::rowWeightedSds()` and `matrixStats::colWeightedSds()` which are used when the input is a **matrix** or **numeric vector**.
- See also `rowSds` for the corresponding unweighted function.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
rowWeightedSds(mat, w = w[1:3])
colWeightedSds(mat, w = w)
```

 colWeightedVars, xgCMatrix-method

Calculates the weighted variance for each row (column) of a matrix-like object

Description

Calculates the weighted variance for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'xgCMatrix'
colWeightedVars(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  useNames = NA
)

## S4 method for signature 'xgCMatrix'
rowWeightedVars(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  useNames = NA
)
```

Arguments

x	An NxK matrix-like object.
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowWeightedVars` / `matrixStats::colWeightedVars`.

Value

Returns a `numeric vector` of length `N (K)`.

See Also

- `matrixStats::rowWeightedVars()` and `matrixStats::colWeightedVars()` which are used when the input is a `matrix` or `numeric vector`.
- See also `rowVars` for the corresponding unweighted function.

Examples

```
mat <- matrix(rnorm(15), nrow = 5, ncol = 3)
mat[2, 1] <- NA
mat[3, 3] <- Inf
mat[4, 1] <- 0

print(mat)
w <- rnorm(n = 5, mean = 3)
rowWeightedVars(mat, w = w[1:3])
colWeightedVars(mat, w = w)
```

xgCMatrix-class

Union of double and logical column-sparse matrices

Description

Union of `dgCMatrix` and `lgCMatrix`

Index

all, [4](#)
any, [5](#), [6](#)
array, [4–6](#), [9](#), [11–14](#), [16](#), [17](#), [19–21](#), [23](#), [24](#),
[26–29](#), [31](#), [34](#), [35](#), [39–42](#), [44](#), [45](#), [47](#),
[49](#), [50](#), [52](#), [54](#)

base::rank, [37](#)

colAlls, [4](#)
colAlls, xgCMatrix-method, [3](#)
colAnyNAs, [5](#)
colAnyNAs, xgCMatrix-method, [4](#)
colAnys, [6](#)
colAnys, xgCMatrix-method, [5](#)
colAvgPerRowSet, [8](#)
colAvgPerRowSet
 (colAvgPerRowSet, xgCMatrix-method),
 [7](#)
colAvgPerRowSet, xgCMatrix-method, [7](#)
colCollapse, [9](#)
colCollapse, xgCMatrix-method, [9](#)
colCounts, [11](#)
colCounts, xgCMatrix-method, [10](#)
colCummaxs, [12](#)
colCummaxs, dgCMatrix-method, [11](#)
colCummins, [13](#)
colCummins, dgCMatrix-method, [13](#)
colCumprods, [15](#)
colCumprods, xgCMatrix-method, [14](#)
colCumsums, [16](#)
colCumsums, xgCMatrix-method, [15](#)
colDiffs, [17](#)
colDiffs, dgCMatrix-method, [16](#)
colIQRDiffs, [19](#)
colIQRDiffs, dgCMatrix-method, [18](#)
colIQRs, [20](#)
colIQRs, xgCMatrix-method, [19](#)
colLogSumExps, [21](#)
colLogSumExps, xgCMatrix-method, [20](#)
colMadDiffs, [23](#)
colMadDiffs, dgCMatrix-method, [22](#)
colMads, [25](#)
colMads, dgCMatrix-method, [23](#)
colMaxs, [26](#)
colMaxs, dgCMatrix-method, [25](#)
colMeans2, [27](#)
colMeans2, xgCMatrix-method, [26](#)
colMedians, [28](#)
colMedians, dgCMatrix-method, [27](#)
colMins, [29](#)
colMins, dgCMatrix-method, [29](#)
colOrderStats, [31](#)
colOrderStats, dgCMatrix-method, [30](#)
colProds, [32](#)
colProds, xgCMatrix-method, [31](#)
colQuantiles, [34](#)
colQuantiles, xgCMatrix-method, [33](#)
colRanges, [35](#)
colRanges, dgCMatrix-method, [34](#)
colRanks, [37](#)
colRanks, dgCMatrix-method, [36](#)
colSdDiffs, [39](#)
colSdDiffs, dgCMatrix-method, [38](#)
colSds, [40](#)
colSds, xgCMatrix-method, [39](#)
colSums2, [41](#)
colSums2, xgCMatrix-method, [41](#)
colTabulates, [43](#)
colTabulates, xgCMatrix-method, [42](#)
colVarDiffs, [44](#)
colVarDiffs, dgCMatrix-method, [43](#)
colVars, [46](#)
colVars, xgCMatrix-method, [45](#)
colWeightedMads, [47](#)
colWeightedMads, dgCMatrix-method, [46](#)
colWeightedMeans, [49](#)
colWeightedMeans, xgCMatrix-method, [48](#)
colWeightedMedians, [50](#)
colWeightedMedians, dgCMatrix-method,

- 49
- colWeightedSds, 52
- colWeightedSds, xgCMatrix-method, 51
- colWeightedVars, 54
- colWeightedVars, xgCMatrix-method, 53
- cummax, 12
- cummin, 13
- cumprod, 15
- cumsum, 16
- diff, 17
- FALSE, 3, 5, 6, 9, 11–15, 17, 19–21, 23–25, 27–29, 31, 32, 34, 35, 37, 39–42, 44, 45, 47, 49, 50, 52, 53
- integer, 8, 11, 37
- IQR, 20
- is.na, 5
- logical, 4–6
- mad, 23, 24, 47
- matrix, 4–6, 9, 11–14, 16, 17, 19–21, 23, 24, 26–29, 31, 34, 35, 37, 39–42, 44, 45, 47, 49, 50, 52, 54
- NA, 3, 5, 6, 9, 11–15, 17–25, 27–29, 31–35, 37–42, 44, 45, 47, 49, 50, 52, 53
- NULL, 3, 5, 6, 8, 9, 11–15, 17, 18, 20–22, 24–33, 35, 36, 38, 40–42, 44, 45, 47–50, 52, 53
- numeric, 4–6, 9, 11–14, 16, 17, 19–21, 23, 24, 26–29, 31, 32, 34, 35, 39–42, 44–50, 52–54
- prod, 32
- quantile, 33
- range, 35
- rowAlls, 4, 6, 11
- rowAlls, xgCMatrix-method
(colAlls, xgCMatrix-method), 3
- rowAnyNAs, 5
- rowAnyNAs, xgCMatrix-method
(colAnyNAs, xgCMatrix-method), 4
- rowAnys, 4–6, 11
- rowAnys, xgCMatrix-method
(colAnys, xgCMatrix-method), 5
- rowAvgPerColSet, 8
- rowAvgPerColSet, xgCMatrix-method
(colAvgPerRowSet, xgCMatrix-method), 7
- rowCollapse, 9
- rowCollapse, xgCMatrix-method
(colCollapse, xgCMatrix-method), 9
- rowCounts, 11
- rowCounts, xgCMatrix-method
(colCounts, xgCMatrix-method), 10
- rowCummaxs, 12
- rowCummaxs, dgCMatrix-method
(colCummaxs, dgCMatrix-method), 11
- rowCummins, 13
- rowCummins, dgCMatrix-method
(colCummins, dgCMatrix-method), 13
- rowCumprods, 15
- rowCumprods, xgCMatrix-method
(colCumprods, xgCMatrix-method), 14
- rowCumsums, 16
- rowCumsums, xgCMatrix-method
(colCumsums, xgCMatrix-method), 15
- rowDiffs, 17
- rowDiffs, dgCMatrix-method
(colDiffs, dgCMatrix-method), 16
- rowIQRDiffs, 19
- rowIQRDiffs, dgCMatrix-method
(colIQRDiffs, dgCMatrix-method), 18
- rowIQRs, 19, 20
- rowIQRs, xgCMatrix-method
(colIQRs, xgCMatrix-method), 19
- rowLogSumExps, 21
- rowLogSumExps, xgCMatrix-method
(colLogSumExps, xgCMatrix-method), 20
- rowMadDiffs, 23
- rowMadDiffs, dgCMatrix-method
(colMadDiffs, dgCMatrix-method), 22
- rowMads, 25, 47
- rowMads(), 20

- rowMads, dgCMatrix-method
(colMads, dgCMatrix-method), 23
- rowMaxs, 12, 26, 29, 35
- rowMaxs, dgCMatrix-method
(colMaxs, dgCMatrix-method), 25
- rowMeans, 25, 27, 28, 40, 41, 46
- rowMeans2, 25, 27, 28, 40, 41, 46, 49
- rowMeans2, xgCMatrix-method
(colMeans2, xgCMatrix-method), 26
- rowMedians, 28, 51
- rowMedians, dgCMatrix-method
(colMedians, dgCMatrix-method), 27
- rowMins, 13, 26, 29, 35
- rowMins, dgCMatrix-method
(colMins, dgCMatrix-method), 29
- rowOrderStats, 31
- rowOrderStats, dgCMatrix-method
(colOrderStats, dgCMatrix-method), 30
- rowProds, 32
- rowProds, xgCMatrix-method
(colProds, xgCMatrix-method), 31
- rowQuantiles, 34
- rowQuantiles, xgCMatrix-method
(colQuantiles, xgCMatrix-method), 33
- rowRanges, 35
- rowRanges, dgCMatrix-method
(colRanges, dgCMatrix-method), 34
- rowRanks, 37
- rowRanks, dgCMatrix-method
(colRanks, dgCMatrix-method), 36
- rowSdDiffs, 39
- rowSdDiffs, dgCMatrix-method
(colSdDiffs, dgCMatrix-method), 38
- rowSds, 20, 25, 40, 46, 52
- rowSds(), 39
- rowSds, xgCMatrix-method
(colSds, xgCMatrix-method), 39
- rowSums2, 41
- rowSums2(), 21
- rowSums2, xgCMatrix-method
(colSums2, xgCMatrix-method), 41
- rowTabulates, 43
- rowTabulates, xgCMatrix-method
(colTabulates, xgCMatrix-method), 42
- rowVarDiffs, 44
- rowVarDiffs, dgCMatrix-method
(colVarDiffs, dgCMatrix-method), 43
- rowVars, 27, 40, 46, 54
- rowVars(), 44
- rowVars, xgCMatrix-method
(colVars, xgCMatrix-method), 45
- rowWeightedMads, 47
- rowWeightedMads, dgCMatrix-method
(colWeightedMads, dgCMatrix-method), 46
- rowWeightedMeans, 49
- rowWeightedMeans, xgCMatrix-method
(colWeightedMeans, xgCMatrix-method), 48
- rowWeightedMedians, 50
- rowWeightedMedians, dgCMatrix-method
(colWeightedMedians, dgCMatrix-method), 49
- rowWeightedSds, 52
- rowWeightedSds, xgCMatrix-method
(colWeightedSds, xgCMatrix-method), 51
- rowWeightedVars, 54
- rowWeightedVars, xgCMatrix-method
(colWeightedVars, xgCMatrix-method), 53
- stats::quantile, 34
- sum, 41
- table, 43
- TRUE, 3, 5, 6, 9, 11–15, 17–25, 27–29, 31–35, 37–42, 44, 45, 47, 49, 50, 52, 53
- var, 46
- vector, 3–6, 8, 9, 11–15, 17–33, 35, 36, 38–42, 44–50, 52–54
- xgCMatrix-class, 54