

Package ‘ProtGenerics’

November 29, 2024

Title Generic infrastructure for Bioconductor mass spectrometry packages

Description S4 generic functions and classes needed by Bioconductor proteomics packages.

Version 1.38.0

Author Laurent Gatto <laurent.gatto@uclouvain.be>,
Johannes Rainer <johannes.rainer@eurac.edu>

Maintainer Laurent Gatto <laurent.gatto@uclouvain.be>

biocViews Infrastructure, Proteomics, MassSpectrometry

URL <https://github.com/RforMassSpectrometry/ProtGenerics>

Depends methods

Suggests testthat

License Artistic-2.0

NeedsCompilation no

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/ProtGenerics>

git_branch RELEASE_3_20

git_last_commit e75a9e0

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-28

Contents

backendInitialize	2
filterFeatures	2
filterSpectra	3
Param	3
peaksData	4
ProcessingStep	4
ProtGenerics	5
Index	8

backendInitialize	<i>General backend methods</i>
-------------------	--------------------------------

Description

These methods are used for implementations of *backends* e.g. for Spectra or Chromatograms object to initialize the backend, merge backends or extract specific information from them. See the respective help pages (e.g. in the Spectra or Chromatograms packages) for information on the actual implementations of these methods.

Usage

```
backendInitialize(object, ...)
isReadOnly(object)
setBackend(object, backend, ...)
backendMerge(object, ...)
backendBpparam(object, ...)
backendParallelFactor(object, ...)
supportsSetBackend(object, ...)
```

Arguments

object	The <i>backend</i> object.
...	Optional parameters.
backend	A <i>backend</i> object.

filterFeatures	<i>Filter features</i>
----------------	------------------------

Description

Implementations of this generic filter function are supposed to filter *features* in object based on a filter criteria defined by parameter *filter*.

Usage

```
filterFeatures(object, filter, ...)
```

Arguments

object	The object to filter.
filter	The filtering criteria on which object should be filtered.
...	Optional parameters.

filterSpectra	<i>Filter Spectra</i>
---------------	-----------------------

Description

Implementations of this generic filter function are supposed to filter *spectra* (e.g. within a Spectra object) based on filter criteria defined with parameter `filter`.

Usage

```
filterSpectra(object, filter, ...)
```

Arguments

<code>object</code>	The object to filter.
<code>filter</code>	The filtering criteria based on which object should be filtered.
<code>...</code>	Optional parameters.

Param	<i>Generic parameter class</i>
-------	--------------------------------

Description

The 'Param' class is a virtual class which can be used as **base** class from which **parameter** classes can inherit.

The methods implemented for the 'Param' class are:

- 'as.list': coerces the 'Param' class to a 'list' with list elements representing the object's slot values, names the slot names. **Hidden** slots (i.e. those with a name starting with '.') are not returned. In addition, a 'Param' class can be coerced to a 'list' using 'as(object, "list")'.
- 'show': prints the content of the 'Param' object (i.e. the individual slots and their value).

Usage

```
## S4 method for signature 'Param'
as.list(x, ...)
```

```
## S4 method for signature 'Param'
show(object)
```

Arguments

<code>x</code>	'Param' object.
<code>...</code>	ignored.
<code>object</code>	'Param' object.

Author(s)

Johannes Rainer

peaksData	<i>Get or set MS peak data</i>
-----------	--------------------------------

Description

These methods get or set mass spectrometry (MS) peaks data, which can be m/z, intensity or retention time values. See the respective help pages (e.g. in the Spectra or Chromatograms packages) for information on the actual implementations of these methods.

Usage

```
peaksData(object, ...)

peaksData(object) <- value

peaksVariables(object, ...)
```

Arguments

object	A data object.
...	Optional parameters.
value	Replacement for peaks data.

ProcessingStep	<i>Processing step</i>
----------------	------------------------

Description

Class containing the function and arguments to be applied in a lazy-execution framework.

Objects of this class are created using the ProcessingStep() function. The processing step is executed with the executeProcessingStep() function.

Usage

```
ProcessingStep(FUN = character(), ARGS = list())

## S4 method for signature 'ProcessingStep'
show(object)

executeProcessingStep(object, ...)
```

Arguments

FUN	function or character representing a function name.
ARGS	list of arguments to be passed along to FUN.
object	ProcessingStep object.
...	optional additional arguments to be passed along.

Details

This object contains all relevant information of a data analysis processing step, i.e. the function and all of its arguments to be applied to the data. This object is mainly used to record possible processing steps of a Spectra or OnDiskMSnExp object (from the Spectra and MSnbase packages, respectively).

Value

The ProcessingStep function returns an object of type ProcessingStep.

Author(s)

Johannes Rainer

Examples

```
## Create a simple processing step object
ps <- ProcessingStep(sum)

executeProcessingStep(ps, 1:10)
```

ProtGenerics

S4 generic functions for Bioconductor proteomics infrastructure

Description

These generic functions provide basic interfaces to operations on and data access to proteomics and mass spectrometry infrastructure in the Bioconductor project.

For the details, please consult the respective methods' manual pages.

Usage

```
psms(object, ...)
peaks(object, ...)
modifications(object, ...)
database(object, ...)
rtime(object, ...)
tic(object, ...)
spectra(object, ...)
intensity(object, ...)
mz(object, ...)
peptides(object, ...)
proteins(object, ...)
accessions(object, ...)
scans(object, ...)
mass(object, ...)
ions(object, ...)
chromatograms(object, ...)
chromatogram(object, ...)
isCentroided(object, ...)
writeMSData(object, file, ...)
## and many more
```

Arguments

object Object of class for which methods are defined.
 file for writeMSData
 : the name of the file to which the data should be exported.
 ... Further arguments, possibly used by downstream methods.

Details

When should one define a generics?:

Generics are appropriate for functions that have *generic* names, i.e. names that occur in multiple circumstances, (with different input classes, most often defined in different packages) or, when (multiple) dispatching is better handled by the generics mechanism rather than the developer. The dispatching mechanism will then automatically call the appropriate method and save the user from explicitly calling `package::method` or the developer to handle the multiple input types cases. When no such conflict exists or is unlikely to happen (for example when the name of the function is specific to a package or domain, or for class slots accessors and replacement methods), the usage of a generic is arguably questionable, and in most of these cases, simple, straightforward functions would be perfectly valid.

When to define a generic in ProtGenerics?:

ProtGenerics is not meant to be the central package for generics, nor should it stop developers from defining the generics they need. It is a means to centralise generics that are defined in different packages (for example `mzR::psms` and `mzID::psms`, or `IRanges::score` and `mzR::score`, now `BioGenerics::score`) or generics that live in a rather big package (say `mzR`) on which one wouldn't want to depend just for the sake of that generics' definition.

The goal of ProtGenerics is to step in when namespace conflicts arise so as to to facilitate inter-operability of packages. In case such conflict appears due to multiple generics, we would (1) add these same definitions in ProtGenerics, (2) remove the definitions from the packages they stem from, which then (3) only need to import ProtGenerics. This would be very minor/straightforward changes for the developers and would resolve issues when they arise.

More generics can be added on request by opening an issue or sending a pull request on:

<https://github.com/lgatto/ProtGenerics>

Author(s)

Laurent Gatto

See Also

- The **BiocGenerics** package for S4 generic functions needed by many Bioconductor packages.
- [showMethods](#) for displaying a summary of the methods defined for a given generic function.
- [selectMethod](#) for getting the definition of a specific method.
- [setGeneric](#) and [setMethod](#) for defining generics and methods.

Examples

```
## List all the symbols defined in this package:
ls('package:ProtGenerics')

## Not run:
```

```
## What methods exists for 'peaks'  
showMethods("peaks")  
  
## To look at one method in particular  
getMethod("peaks", "mzRpviz")  
  
## End(Not run)
```

Index

* methods

- ProtGenerics, 5

- accessions (ProtGenerics), 5
- acquisitionNum (ProtGenerics), 5
- addProcessing (ProtGenerics), 5
- adjacencyMatrix (ProtGenerics), 5
- aggregateFeatures (ProtGenerics), 5
- alignRt (ProtGenerics), 5
- analyser (ProtGenerics), 5
- analyserDetails (ProtGenerics), 5
- analyzer (ProtGenerics), 5
- analyzerDetails (ProtGenerics), 5
- as.list, Param-method (Param), 3

- backendBpparam (backendInitialize), 2
- backendInitialize, 2
- backendMerge (backendInitialize), 2
- backendParallelFactor
(backendInitialize), 2
- bin (ProtGenerics), 5

- calculateFragments (ProtGenerics), 5
- centroided (ProtGenerics), 5
- centroided<- (ProtGenerics), 5
- characterOrFunction-class
(ProcessingStep), 4
- chromatogram (ProtGenerics), 5
- chromatograms (ProtGenerics), 5
- collisionEnergy (ProtGenerics), 5
- collisionEnergy<- (ProtGenerics), 5
- combineFeatures (ProtGenerics), 5
- compareChromatograms (ProtGenerics), 5
- compareSpectra (ProtGenerics), 5
- compounds (ProtGenerics), 5

- database (ProtGenerics), 5
- dataOrigin (ProtGenerics), 5
- dataOrigin<- (ProtGenerics), 5
- dataStorage (ProtGenerics), 5
- dataStorage<- (ProtGenerics), 5
- detectorType (ProtGenerics), 5

- estimatePrecursorIntensity
(ProtGenerics), 5

- executeProcessingStep (ProcessingStep),
4
- expemail (ProtGenerics), 5
- exptitle (ProtGenerics), 5

- filterAcquisitionNum (ProtGenerics), 5
- filterDataOrigin (ProtGenerics), 5
- filterDataStorage (ProtGenerics), 5
- filterEmptySpectra (ProtGenerics), 5
- filterFeatures, 2
- filterIntensity (ProtGenerics), 5
- filterIsolationWindow (ProtGenerics), 5
- filterMsLevel (ProtGenerics), 5
- filterMz (ProtGenerics), 5
- filterMzRange (ProtGenerics), 5
- filterMzValues (ProtGenerics), 5
- filterNA (ProtGenerics), 5
- filterPolarity (ProtGenerics), 5
- filterPrecursorCharge (ProtGenerics), 5
- filterPrecursorMz (ProtGenerics), 5
- filterPrecursorMzRange (ProtGenerics), 5
- filterPrecursorMzValues (ProtGenerics),
5
- filterPrecursorScan (ProtGenerics), 5
- filterProductMz (ProtGenerics), 5
- filterProductMzRange (ProtGenerics), 5
- filterProductMzValues (ProtGenerics), 5
- filterRanges (ProtGenerics), 5
- filterRt (ProtGenerics), 5
- filterSpectra, 3
- filterValues (ProtGenerics), 5

- impute (ProtGenerics), 5
- instrumentCustomisations
(ProtGenerics), 5
- instrumentManufacturer (ProtGenerics), 5
- instrumentModel (ProtGenerics), 5
- intensity (ProtGenerics), 5
- intensity<- (ProtGenerics), 5
- ionCount (ProtGenerics), 5
- ions (ProtGenerics), 5
- ionSource (ProtGenerics), 5
- ionSourceDetails (ProtGenerics), 5
- isCentroided (ProtGenerics), 5

- isolationWindowLowerMz (ProtGenerics), 5
- isolationWindowLowerMz<-
 (ProtGenerics), 5
- isolationWindowTargetMz (ProtGenerics),
 5
- isolationWindowTargetMz<-
 (ProtGenerics), 5
- isolationWindowUpperMz (ProtGenerics), 5
- isolationWindowUpperMz<-
 (ProtGenerics), 5
- isReadOnly (backendInitialize), 2

- mass (ProtGenerics), 5
- modifications (ProtGenerics), 5
- msInfo (ProtGenerics), 5
- msLevel (ProtGenerics), 5
- msLevel<- (ProtGenerics), 5
- mz (ProtGenerics), 5
- mz<- (ProtGenerics), 5

- Param, 3
- Param-class (Param), 3
- peaks (ProtGenerics), 5
- peaks<- (ProtGenerics), 5
- peaksData, 4
- peaksData<- (peaksData), 4
- peaksVariables (peaksData), 4
- peptides (ProtGenerics), 5
- polarity (ProtGenerics), 5
- polarity<- (ProtGenerics), 5
- precAcquisitionNum (ProtGenerics), 5
- precScanNum (ProtGenerics), 5
- precursorCharge (ProtGenerics), 5
- precursorCharge<- (ProtGenerics), 5
- precursorIntensity (ProtGenerics), 5
- precursorIntensity<- (ProtGenerics), 5
- precursorMz (ProtGenerics), 5
- precursorMz<- (ProtGenerics), 5
- processingData (ProtGenerics), 5
- processingData<- (ProtGenerics), 5
- ProcessingStep, 4
- ProcessingStep-class (ProcessingStep), 4
- productMz (ProtGenerics), 5
- productMz<- (ProtGenerics), 5
- proteins (ProtGenerics), 5
- ProtGenerics, 5
- ProtGenerics-package (ProtGenerics), 5
- psms (ProtGenerics), 5

- quantify (ProtGenerics), 5

- rtime (ProtGenerics), 5
- rtime<- (ProtGenerics), 5

- scanIndex (ProtGenerics), 5
- scans (ProtGenerics), 5
- selectMethod, 6
- setBackend (backendInitialize), 2
- setGeneric, 6
- setMethod, 6
- show, Param-method (Param), 3
- show, ProcessingStep-method
 (ProcessingStep), 4
- showMethods, 6
- smooth (ProtGenerics), 5
- smoothed (ProtGenerics), 5
- smoothed<- (ProtGenerics), 5
- spectra (ProtGenerics), 5
- spectra<- (ProtGenerics), 5
- spectraData (ProtGenerics), 5
- spectraData<- (ProtGenerics), 5
- spectraNames (ProtGenerics), 5
- spectraNames<- (ProtGenerics), 5
- spectrapply (ProtGenerics), 5
- spectraVariables (ProtGenerics), 5
- supportsSetBackend (backendInitialize),
 2

- tic (ProtGenerics), 5
- tolerance (ProtGenerics), 5

- uniqueMsLevels (ProtGenerics), 5

- writeMSData (ProtGenerics), 5