

Package ‘crisprBase’

November 28, 2024

Version 1.10.0

Date 2024-07-23

Title Base functions and classes for CRISPR gRNA design

Depends utils, methods, R (>= 4.1)

Imports BiocGenerics, Biostrings, GenomicRanges, graphics, IRanges,
S4Vectors, stringr

Suggests BiocStyle, knitr, rmarkdown, testthat

biocViews CRISPR, FunctionalGenomics

Description Provides S4 classes for general nucleases, CRISPR nucleases,
CRISPR nickases, and base editors. Several CRISPR-specific genome
arithmetic functions are implemented to help extract genomic coordinates
of spacer and protospacer sequences. Commonly-used CRISPR nuclease objects
are provided that can be readily used in other packages.
Both DNA- and RNA-targeting nucleases are supported.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

BugReports <https://github.com/crisprVerse/crisprBase/issues>

URL <https://github.com/crisprVerse/crisprBase>

Collate 'AllGenerics.R' 'rebase.R' 'Nuclease-class.R'
'Nickase-class.R' 'CrisprNuclease-class.R'
'CrisprNickase-class.R' 'BaseEditor-class.R' 'arithmetics.R'
'data.R' 'utils.R' 'converters.R' 'annotateMismatches.R'

LazyData true

git_url <https://git.bioconductor.org/packages/crisprBase>

git_branch RELEASE_3_20

git_last_commit 528b375

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-28

Author Jean-Philippe Fortin [aut, cre]

Maintainer Jean-Philippe Fortin <fortin946@gmail.com>

Contents

annotateMismatches	2
AsCas12a	3
baseEditorName	4
BE4max	6
CasRx	6
CrisprNickase-class	7
Csm	10
enAsCas12a	10
extractPamFromTarget	11
extractProtospacerFromTarget	11
getAvailableCrisprNucleases	12
getCutSiteFromPamSite	13
getCutSiteRanges	13
getEditingSiteFromPamSite	14
getPamRanges	15
getProtospacerRanges	16
getTargetRanges	17
MAD7	18
motifs	18
nickaseName	22
plotEditingWeights	24
reexports	25
restrictionEnzymes	25
SaCas9	26
spacerLength	26
SpCas9	29
SpGCas9	30
Index	31

annotateMismatches	<i>Annotate mismatches between spacer and protospacer sequences</i>
--------------------	---

Description

Annotate mismatches between spacer and protospacer sequences.

Usage

```
annotateMismatches(spacers, protospacers, rnase = FALSE)
```

Arguments

spacers	A character vector specifying spacer sequences (gRNA).
protospacers	A character vector specifying protospacer sequences (target DNA).
rnase	Is it for an RNase? FALSE by default. If TRUE, spacers and protospacers are expected to be the reverse complement of each other.

Value

A data.frame storing spacer and protospacer columns, as well as number of mismatches, and positions for the different mismatches, if any. Positions are relative to the 5' end of the spacer sequences. For RNAses (e.g. CasRx), this means that a mismatch at position 1 corresponds to the last nucleotide of the protospacer sequence.

Author(s)

Jean-Philippe Fortin

Examples

```
spacers <- c("CCGGAGCGAGTTGCAGTAAGCAG",
            "GCCGGAGCGAGTTGCAGTAAGCA",
            "GGCCGGAGCGAGTTGCAGTAAGC")

protospacers=c("CTGCTTACTGCAACTCGCTCTGG",
              "TGCTTAATGCAACCCGCTCCGGC",
              "GCTTACTGCAACTCGCTCCGGCC")

ann <- annotateMismatches(spacers,
                        protospacers,
                        rnase=TRUE)
```

AsCas12a

AsCas12a CrisprNuclease object

Description

CrisprNuclease object for the Wildtype Acidaminococcus Cas12a (AsCas12a) nuclease.

Usage

```
data(AsCas12a, package="crisprBase")
```

Format

CrisprNuclease object.

Details

The AsCas12a nuclease recognizes TTTV PAM sequences. Spacer sequences must be located downstream of PAM sequences.

baseEditorName	<i>An S4 class to represent a base editor</i>
----------------	---

Description

An S4 class to represent a base editor

Usage

```
baseEditorName(object)
```

```
baseEditorName(object) <- value
```

```
editingWeights(object, ...)
```

```
editingWeights(object) <- value
```

```
editingStrand(object, ...)
```

```
editingStrand(object) <- value
```

```
BaseEditor(  
  CrisprNuclease,  
  baseEditorName = NA_character_,  
  editingStrand = c("original", "opposite"),  
  editingWeights = NULL  
)
```

```
## S4 method for signature 'BaseEditor'  
show(object)
```

```
## S4 method for signature 'BaseEditor'  
baseEditorName(object)
```

```
## S4 replacement method for signature 'BaseEditor'  
baseEditorName(object) <- value
```

```
## S4 method for signature 'BaseEditor'  
editingWeights(object, substitutions = NULL)
```

```
## S4 replacement method for signature 'BaseEditor'  
editingWeights(object) <- value
```

```
## S4 method for signature 'BaseEditor'  
editingStrand(object)
```

```
## S4 replacement method for signature 'BaseEditor'  
editingStrand(object) <- value
```

Arguments

object [BaseEditor](#) object.

value	Value to replaced with.
...	Additional arguments for class-specific methods
CrisprNuclease	A CrisprNuclease object.
baseEditorName	String specifying base editor name.
editingStrand	String indicating which strand with respect to the target protospacer sequence will be edited. Must be either "original" or "opposite". "original" by default.
editingWeights	Numeric matrix of editing weights. Column names must be indicating relative position to the PAM site. Row names must be of the form "X2Y" where "X" represents the origin base, and "Y" represents the substituted base. For instance, "C2T" indicates the row corresponding to C to T editing.
substitutions	Character vector indicating which substitutions should be returned.

Value

A BaseEditor object

Functions

- BaseEditor(): Create a [BaseEditor](#) object

Slots

baseEditorName	Name of the base editor.
editingWeights	Matrix of editing weights.
editingStrand	String indicating which strand with respect to the target protospacer sequence will be edited. Must be either "original" or "opposite". "original" by default.

Constructors

Use the constructor `link{BaseEditor}` to create a BaseEditor object.

Accessors

baseEditorName:	To get the name of the base editor.
editingWeights:	To return the matrix of editing weights.
editingStrand:	To return the editing strand.

Setters

baseEditorName<-:	To change the name of the base editor.
editingWeights<-:	To change the matrix of editing weights.
editingStrand<-:	To change the editing strand.

Examples

```
# Creating an object for BE4max (C to T editor)
# based on experimental weights

ws <- c(0.7, 0.7, 0.8, 1.8, 1, 2, 1.4, 1.2, 2.3, 1.3, 2.4, 2.2, 3.4,
        2.2, 2.1, 3.5, 5.8, 16.2, 31.8, 63.2, 90.3, 100, 87, 62, 31.4,
        16.3, 10, 5.6, 3.3, 1.9, 1.8, 2.4, 1.7, 0.5, 0.2, 0.1)
ws <- matrix(ws, nrow=1, ncol=length(ws))
rownames(ws) <- "C2T"
colnames(ws) <- -36:-1
data(SpCas9, package="crisprBase")
BE4max <- BaseEditor(SpCas9,
                    baseEditorName="BE4max",
                    editingStrand="original",
                    editingWeights=ws)
metadata(BE4max)$description_base_editor <- "BE4max cytosine base editor."
```

BE4max	<i>BE4max BaseEditor object</i>
--------	---------------------------------

Description

BaseEditor for the cytosine base editor CRISPR/Cas9 system BE4max. Editing weights were obtained from <https://doi.org/10.1016/j.cell.2020.05.037>

Usage

```
data(BE4max, package="crisprBase")
```

Format

BaseEditor object.

Details

BaseEditor for the cytosine base editor CRISPR/Cas9 system BE4max. Editing weights were obtained from <https://doi.org/10.1016/j.cell.2020.05.037>.

CasRx	<i>CasRx CrisprNuclease object</i>
-------	------------------------------------

Description

CrisprNuclease object for the Cas13d-NLS from *Ruminococcus flavefaciens* strain XPD3002 nuclease (RNase).

Usage

```
data(CasRx, package="crisprBase")
```

Format

CrisprNuclease object.

Details

The CasRx nuclease was derived from Cas13d *Ruminococcus flavefaciens* strain XPD3002. See [10.1016/j.cell.2018.02.033](https://doi.org/10.1016/j.cell.2018.02.033).

CrisprNickase-class *An S4 class to represent a CRISPR nickase.*

Description

An S4 class to represent a CRISPR nickase.

Usage

```
CrisprNickase(  
  nickaseName,  
  nickingStrand = c("original", "opposite"),  
  pams = NA_character_,  
  weights = rep(1, length(pams)),  
  metadata = list(),  
  pam_side = NA_character_,  
  spacer_gap = 0L,  
  spacer_length = NA_integer_  
)  
  
## S4 method for signature 'CrisprNickase'  
show(object)  
  
## S4 method for signature 'CrisprNickase'  
pamLength(object)  
  
## S4 method for signature 'CrisprNickase'  
spacerLength(object)  
  
## S4 replacement method for signature 'CrisprNickase'  
spacerLength(object) <- value  
  
## S4 method for signature 'CrisprNickase'  
pamSide(object)  
  
## S4 replacement method for signature 'CrisprNickase'  
pamSide(object) <- value  
  
## S4 method for signature 'CrisprNickase'  
spacerGap(object)  
  
## S4 replacement method for signature 'CrisprNickase'  
spacerGap(object) <- value
```

```

## S4 method for signature 'CrisprNickase'
hasSpacerGap(object)

## S4 method for signature 'CrisprNickase'
targetLength(object)

## S4 method for signature 'CrisprNickase'
pams(object, primary = TRUE, ignore_pam = FALSE, as.character = FALSE)

## S4 method for signature 'CrisprNickase'
pamIndices(object)

## S4 method for signature 'CrisprNickase'
spacerIndices(object)

## S4 method for signature 'CrisprNickase'
prototypeSequence(object, primary = TRUE)

```

Arguments

nickaseName	Name of the CRISPR nickase.
nickingStrand	String specifying with strand with respect to the motif sequence (5' to 3') is nicked. Must be either "original" (default) or "opposite".
pams	Character vector of PAM sequence motifs written from 5' to 3'. If the point of cleavage has been determined, the precise site is marked with ^. Only letters in the IUPAC code are accepted. For nickases that cleave away from their recognition sequence, the cleavage sites are indicated in parentheses. See details for more information.
weights	Optional numeric vector specifying relative weights of the PAM sequences to specify cleavage probabilities.
metadata	Optional list providing global metadata information.
pam_side	String specifying the side of the PAM sequence sequence with respect to the protospacer sequence. Must be either '3prime' (e.g. Cas9) or '5prime' (e.g. Cas12a)
spacer_gap	Integer specifying the length (in nucleotides) between the spacer sequence and the PAM sequence (e.g. 0 for Cas9 and Cas12a).
spacer_length	Integer specifying the length of the spacer sequence
object	CrisprNickase object.
value	For spacerLength<- and gapLength<-, must be a non-negative integer. For pamSide, must be either '5prime' or '3prime'.
primary	Should only the PAM sequence with the heighest weight be returned? If no cleavage weights are stored in the CrisprNickase object, all sequences are returned. TRUE by default.
ignore_pam	Should all possible k-mer sequences for a given PAM length be returned, irrespectively of the PAM sequence motifs stored in the CrisprNickase object? FALSE by default.
as.character	Should the PAM sequences be returned as a character vector? FALSE by default.

Value

A CrisprNickase object

Functions

- CrisprNickase(): Create a [CrisprNickase](#) object

Slots

`pam_side` String specifying the side of the PAM sequence with respect to the protospacer sequence. Must be either '3prime' (e.g. SpCas9) or '5prime' (e.g. AsCas12a)

`spacer_length` Integer specifying the length of the spacer sequence

`spacer_gap` Integer specifying the length (in nucleotides) between the spacer sequence and the PAM sequence (e.g. 0 for SpCas9 and AsCas12a).

Constructors

Use the constructor `link{CrisprNickase}` to create a CrisprNickase object.

Accessors

`nickaseName`: To get the name of the CRISPR nickase.

`spacerLength`: To return the length of the spacer sequence.

`targetLength`: To return the length of the target sequence (protospacer + pam).

`pamLength`: To return the length of the PAM sequence.

`pamSide`: To return the side of the PAM sequence with respect to the spacer sequence.

`spacerGap`: To return the length of the gap between the PAM and spacer sequences.

`pams`: To return the list of PAM sequences.

Setters

`spacerGap<-`: To change the length of the gap between the PAM and spacer sequences.

`pamSide<-`: To change the side of the PAM sequence with respect to the protospacer sequence.

`spacerLength<-`: To change the length of the spacer sequence.

Utility functions for genomic arithmetics

`pamIndices`: To return the relative coordinates of the PAM sequence within the protospacer sequence.

`spacerIndices`: To return the relative coordinates of the spacer sequence within the protospacer sequence.

Examples

```
Cas9D10A <- CrisprNickase("Cas9D10A",
  nickingStrand="opposite",
  pams=c("(3)NGG", "(3)NAG", "(3)NGA"),
  weights=c(1, 0.2593, 0.0694),
  metadata=list(description="D10A-mutated Streptococcus
    pyogenes Cas9 (SpCas9) nickase"),
  pam_side="3prime",
```

```

spacer_length=20)

Cas9H840A <- CrisprNickase("Cas9H840A",
  nickingStrand="original",
  pams=c("(3)NGG", "(3)NAG", "(3)NGA"),
  weights=c(1, 0.2593, 0.0694),
  metadata=list(description="H840A-mutated Streptococcus
    pyogenes Cas9 (SpCas9) nickase"),
  pam_side="3prime",
  spacer_length=20)

```

Csm

*Csm CrisprNuclease object***Description**

CrisprNuclease object for the RNA-targeting Csm complex from *Streptococcus thermophilus*

Usage

```
data(Csm, package="crisprBase")
```

Format

CrisprNuclease object.

Details

The specific Csm complex is an RNA-targeting nuclease derived from *Streptococcus thermophilus*. There is no preferred PAM sequences, and the default (optimal) spacer length is 32nt. See <https://doi.org/10.1038/s41587-022-01649-9>.

enAsCas12a

*enAsCas12a CrisprNuclease object***Description**

CrisprNuclease object for the Enhanced *Acidaminococcus* Cas12a (AsCas12a) nuclease.

Usage

```
data(enAsCas12a, package="crisprBase")
```

Format

CrisprNuclease object.

Details

The enAsCas12a nuclease recognizes an extended set of PAM sequences beyond the canonical TTTV sequence for AsCas12a. Spacer sequences must be located downstream of PAM sequences.

extractPamFromTarget *Extract PAM sequences from target sequences*

Description

Extract PAM sequences from target sequences (protospacer + PAM) using information stored in a CrisprNuclease object.

Usage

```
extractPamFromTarget(targets, object)
```

Arguments

targets	Character vector of target sequences.
object	CrisprNuclease corresponding to the target sequences.

Value

Character vector of PAM sequences of length equal to that of the targets character vector.

Author(s)

Jean-Philippe Fortin

Examples

```
data(SpCas9, AsCas12a, package="crisprBase")
# Extracting PAM sequences from Cas9 protospacers:
targets <- c("AGGTGCTGATTGTAGTGCTGCGG",
            "AGGTGCTGATTGTAGTGCTGAGG")
extractPamFromTarget(targets, SpCas9)
# Extracting PAM sequences from Cas12a targets:
targets <- c("TTTAAGGTGCTGATTGTAGTGCTGTGT",
            "TTTCAGGTGCTGATTGTAGTGCTGAAA")
extractPamFromTarget(targets, AsCas12a)
```

extractProtospacerFromTarget
Extract protospacer sequences from target sequences

Description

Extract protospacer sequences from target sequences (protospacer + PAM) using information stored in a CrisprNuclease object.

Usage

```
extractProtospacerFromTarget(targets, object)
```

Arguments

targets Character vector of targets sequences.
object CrisprNuclease corresponding to the targets sequences.

Value

Character vector of protospacer sequences of length equal to that of the targets character vector.

Author(s)

Jean-Philippe Fortin

Examples

```
data(SpCas9, AsCas12a, package="crisprBase")
# Extracting protospacer sequences from Cas9 targets:
targets <- c("AGGTGCTGATTGTAGTGCTGCGG",
            "AGGTGCTGATTGTAGTGCTGAGG")
extractProtospacerFromTarget(targets, SpCas9)
# Extracting protospacer sequences from Cas12a targets:
targets <- c("TTTAAGGTGCTGATTGTAGTGCTGTGT",
            "TTTCAGGTGCTGATTGTAGTGCTGAAA")
extractProtospacerFromTarget(targets, AsCas12a)
```

```
getAvailableCrisprNucleases
```

Return list of available CrisprNuclease objects in crisprBase

Description

Return list of available CrisprNuclease objects in crisprBase.

Usage

```
getAvailableCrisprNucleases()
```

Value

Character vector of available CrisprNuclease objects found in crisprBase.

Author(s)

Jean-Philippe Fortin

Examples

```
getAvailableCrisprNucleases()
```

getCutSiteFromPamSite *Return cut site coordinates from PAM site coordinates*

Description

Return cut site coordinates from PAM site coordinates.

Usage

```
getCutSiteFromPamSite(pam_site, strand, nuclease = NULL)
```

Arguments

pam_site	Coordinate of the first nucleotide of the PAM sequence.
strand	Either "+" or "-".
nuclease	A CrisprNuclease object.

Value

numeric vector of cut sites

Author(s)

Jean-Philippe Fortin

Examples

```
data(SpCas9, package="crisprBase")
getCutSiteFromPamSite(pam_site=100, strand="+", nuclease=SpCas9)
getCutSiteFromPamSite(pam_site=100, strand="-", nuclease=SpCas9)
```

getCutSiteRanges *Construct a cut site GRanges from a list of PAM sites*

Description

Construct a cut site GRanges from a list of PAM sites using information stored in a CrisprNuclease object.

Usage

```
getCutSiteRanges(  
  gr = NULL,  
  seqnames = NULL,  
  pam_site = NULL,  
  strand = NULL,  
  nuclease = NULL  
)
```

Arguments

gr	GRanges object of width 1 specifying the coordinates of the first nucleotide of the PAM sequences.
seqnames	Character vector of genomic sequence names. Ignored if gr is not NULL.
pam_site	Numeric vector specifying the coordinates of the first nucleotide of the PAM sequences corresponding to the PAM sequences. Ignored if gr is not NULL.
strand	Character vector specifying the strand of the PAM. Ignored if gr is not NULL.
nuclease	CrisprNuclease object.

Value

GRanges object representing genomic coordinates of the cut sites.

Author(s)

Jean-Philippe Fortin

Examples

```
data(SpCas9, AsCas12a, package="crisprBase")
library(GenomicRanges)
gr <- GRanges("chr10",
              IRanges(start=c(100,120), width=1),
              strand=c("+", "-"))
getCutSiteRanges(gr, nuclease=SpCas9)
getCutSiteRanges(gr, nuclease=AsCas12a)
```

getEditingSiteFromPamSite

Return optimal editing site coordinates from PAM site coordinates

Description

Return optimal editing site coordinates from PAM site coordinates.

Usage

```
getEditingSiteFromPamSite(
  pam_site,
  strand,
  baseEditor = NULL,
  substitution = NULL
)
```

Arguments

pam_site	Coordinate of the first nucleotide of the PAM sequence.
strand	Either "+" or "-".
baseEditor	A BaseEditor object.
substitution	String indicating which substitution should be used to estimate the optimal editing position. E.g. "C2T" will return the optimal editing position for C to T editing.

Value

numeric vector of editing sites.

Author(s)

Jean-Philippe Fortin

Examples

```
data(BE4max, package="crisprBase")
getEditingSiteFromPamSite(pam_site=100, strand="+", baseEditor=BE4max, "C2T")
```

getPamRanges	<i>Construct a PAM GRanges from a list of PAM sites</i>
--------------	---

Description

Construct a PAM GRanges from a list of PAM sites using information stored in a CrisprNuclease object.

Usage

```
getPamRanges(
  gr = NULL,
  seqnames = NULL,
  pam_site = NULL,
  strand = NULL,
  nuclease = NULL
)
```

Arguments

gr	GRanges object of width 1 specifying the coordinates of the first nucleotide of the PAM sequences.
seqnames	Character vector of genomic sequence names. Ignored if gr is not NULL.
pam_site	Numeric vector specifying the coordinates of the first nucleotide of the PAM sequences corresponding to the PAM sequences. Ignored if gr is not NULL.
strand	Character vector specifying the strand of the PAM. Ignored if gr is not NULL.
nuclease	CrisprNuclease object.

Value

GRanges object representing genomic coordinates of PAM sequences.

Author(s)

Jean-Philippe Fortin

Examples

```
data(SpCas9, AsCas12a, package="crisprBase")
library(GenomicRanges)
gr <- GRanges("chr10",
              IRanges(start=c(100,120), width=1),
              strand=c("+","-"))
getPamRanges(gr, nuclease=SpCas9)
getPamRanges(gr, nuclease=AsCas12a)
```

getProtospacerRanges *Construct a protospacer GRanges from a list of PAM sites*

Description

Construct a protospacer GRanges from a list of PAM sites using information stored in a CrisprNuclease object.

Usage

```
getProtospacerRanges(
  gr = NULL,
  seqnames = NULL,
  pam_site = NULL,
  strand = NULL,
  nuclease = NULL,
  spacer_len = NULL
)
```

Arguments

gr	GRanges object of width 1 specifying the coordinates of the first nucleotide of the PAM sequences.
seqnames	Character vector of genomic sequence names. Ignored if gr is not NULL.
pam_site	Numeric vector specifying the coordinates of the first nucleotide of the PAM sequences corresponding to the protospacers. Ignored if gr is not NULL.
strand	Character vector specifying the strand of the protospacer. Ignored if gr is not NULL.
nuclease	CrisprNuclease object.
spacer_len	Non-negative integer to overwrite the default spacer length stored in the CrisprNuclease object. s

Value

GRanges object representing genomic coordinates of protospacer sequences.

Author(s)

Jean-Philippe Fortin

Examples

```
data(SpCas9, AsCas12a, package="crisprBase")
library(GenomicRanges)
gr <- GRanges("chr10",
              IRanges(start=c(100,120), width=1),
              strand=c("+", "-"))
getProtospacerRanges(gr, nuclease=SpCas9)
getProtospacerRanges(gr, nuclease=AsCas12a)
```

getTargetRanges

Construct a target GRanges from a list of PAM sites

Description

Construct a target (protospacer + PAM) GRanges from a list of PAM sites using information stored in a CrisprNuclease object.

Usage

```
getTargetRanges(
  gr = NULL,
  seqnames = NULL,
  pam_site = NULL,
  strand = NULL,
  nuclease = NULL,
  spacer_len = NULL
)
```

Arguments

gr	GRanges object of width 1 specifying the coordinates of the first nucleotide of the PAM sequences.
seqnames	Character vector of genomic sequence names. Ignored if gr is not NULL.
pam_site	Numeric vector specifying the coordinates of the first nucleotide of the PAM sequences corresponding to the targets. Ignored if gr is not NULL.
strand	Character vector specifying the strand of the target. Ignored if gr is not NULL.
nuclease	CrisprNuclease object.
spacer_len	Non-negative integer to overwrite the default spacer length stored in the CrisprNuclease object.

Value

GRanges object representing genomic coordinates of the target sequences.

Author(s)

Jean-Philippe Fortin

Examples

```
data(SpCas9, AsCas12a, package="crisprBase")
library(GenomicRanges)
gr <- GRanges("chr10",
              IRanges(start=c(100,120), width=1),
              strand=c("+", "-"))
getTargetRanges(gr, nuclease=SpCas9)
getTargetRanges(gr, nuclease=AsCas12a)
```

MAD7

MAD7 CrisprNuclease object

Description

CrisprNuclease object for the MAD7 nuclease (Cas12a-like nuclease)

Usage

```
data(MAD7, package="crisprBase")
```

Format

CrisprNuclease object.

Details

The MAD7 nuclease recognizes YTTV PAM sequences. Spacer sequences must be located downstream of PAM sequences.

motifs

An S4 class to represent a nuclease.

Description

Return motif string representations of recognition sites.

Return length of the recognition sites sequences.

Usage

```
motifs(object, ...)

motifLength(object, ...)

nucleaseName(object)

targetType(object)

weights(object, ...)

nucleaseName(object) <- value

targetType(object) <- value

weights(object) <- value

cutSites(object, ...)

isCutting(object)

isRnase(object)

isDnase(object)

Nuclease(
  nucleaseName,
  targetType = c("DNA", "RNA"),
  motifs = NULL,
  cutSites = NULL,
  weights = rep(1, length(motifs)),
  metadata = list()
)

## S4 method for signature 'Nuclease'
show(object)

## S4 method for signature 'Nuclease'
nucleaseName(object)

## S4 replacement method for signature 'Nuclease'
nucleaseName(object) <- value

## S4 method for signature 'Nuclease'
targetType(object)

## S4 replacement method for signature 'Nuclease'
targetType(object) <- value

## S4 method for signature 'Nuclease'
weights(object, expand = FALSE)
```

```

## S4 replacement method for signature 'Nuclease'
weights(object) <- value

## S4 method for signature 'Nuclease'
isCutting(object)

## S4 method for signature 'Nuclease'
isRnase(object)

## S4 method for signature 'Nuclease'
isDnase(object)

## S4 method for signature 'Nuclease'
motifs(
  object,
  primary = FALSE,
  strand = c("+", "-"),
  expand = FALSE,
  as.character = FALSE
)

## S4 method for signature 'Nuclease'
motifLength(object)

## S4 method for signature 'Nuclease'
cutSites(object, strand = c("+", "-", "both"), combine = TRUE, middle = FALSE)

```

Arguments

object	Nuclease object.
...	Additional arguments for class-specific methods
value	New value to pass to the setter functions.
nucleaseName	Name of the nuclease.
targetType	String specifying target type ("DNA" or "RNA").
motifs	Character vector of recognition sequence motifs written from 5' to 3' written in Rebase convention. If the point of cleavage has been determined, the precise site is marked with ^. Only letters in the IUPAC code are accepted. For nucleases that cleave away from their recognition sequence, the cleavage sites are indicated in parentheses. See details for more information.
cutSites	Matrix with 2 rows (+ and - strand, respectively) specifying the cleavage coordinates relative to the first nucleotide of the motif sequence. Each column corresponds to a motif specified in the motifs slot.
weights	Optional numeric vector specifying relative weights for the recognition motifs to specify cleavage probabilities.
metadata	Optional list providing global metadata information.
expand	Should sequences be expanded to only contain ATCG nucleotides? FALSE by default.
primary	Should only the motif with the highest weight be returned? FALSE by default. Only relevant if weights are stored in the Nuclease object.
strand	Strand to allow reverse complementation of the motif. "+" by default.

as.character	Should the motif sequences be returned as a character vector? FALSE by default.
combine	Should only unique values be considered? TRUE by default.
middle	For staggered cuts, should the middle point between the cut on the forward strand and the cut on the reverse strand be considered as the cut site? FALSE by default.

Value

A Nuclease object

Functions

- `Nuclease()`: Create a [Nuclease](#) object

Slots

`nucleaseName` Name of the nuclease.

`targetType` Character string indicating target type ("DNA" or "RNA").

`motifs` `DNAStringSet` of recognition sequence motifs written from 5' to 3'.

`cutSites` Matrix with 2 rows (+ and - strand, respectively) specifying the cleavage coordinates relative to the first nucleotide of the motif sequence. Each column corresponds to a motif specified in the `motifs` slot.

`weights` Optional numeric vector specifying relative weights for the motifs corresponding to cleavage probabilities.

`metadata` Optional string providing a description of the nuclease.

Constructors

Use the constructor `link{Nuclease}` to create a Nuclease object.

Accessors

`nucleaseName`: To get the name of the nuclease.

`targetType`: To get the target type ("DNA" or "RNA").

`metadata`: To get the metadata list of the nuclease.

`motifs`: To get the recognition motif nucleotide sequences.

`weights`: To get nuclease weights.

`cutSites`: To get nuclease cut sites.

See Also

See the [CrisprNuclease](#) for CRISPR-specific nucleases.

Examples

```
EcoRI <- Nuclease("EcoRI",
                 motifs=c("G^AATC"),
                 metadata=list(description="EcoRI restriction enzyme"))
```

nickaseName	<i>An S4 class to represent a nickase</i>
-------------	---

Description

An S4 class to represent a nickase

Usage

```
nickaseName(object)
```

```
nickaseName(object) <- value
```

```
nickingStrand(object)
```

```
nickingStrand(object) <- value
```

```
Nickase(  
  nickaseName,  
  nickingStrand = c("original", "opposite"),  
  motifs = NULL,  
  cutSites = NULL,  
  weights = rep(1, length(motifs)),  
  metadata = list()  
)
```

```
## S4 method for signature 'Nickase'  
show(object)
```

```
## S4 method for signature 'Nickase'  
nickaseName(object)
```

```
## S4 replacement method for signature 'Nickase'  
nickaseName(object) <- value
```

```
## S4 method for signature 'Nickase'  
nickingStrand(object)
```

```
## S4 replacement method for signature 'Nickase'  
nickingStrand(object) <- value
```

```
## S4 method for signature 'Nickase'  
weights(object, expand = FALSE)
```

```
## S4 replacement method for signature 'Nickase'  
weights(object) <- value
```

```
## S4 method for signature 'Nickase'  
isCutting(object)
```

```
## S4 method for signature 'Nickase'
```

```

motifs(
  object,
  primary = FALSE,
  strand = c("+", "-"),
  expand = FALSE,
  as.character = FALSE
)

## S4 method for signature 'Nickase'
motifLength(object)

## S4 method for signature 'Nickase'
cutSites(object, combine = TRUE)

```

Arguments

object	Nickase object.
value	New value to pass to the setter functions.
nickaseName	Name of the nickase.
nickingStrand	String specifying with strand with respect to the motif sequence (5' to 3') is nicked. Must be either "original" (default) or "opposite".
motifs	Character vector of recognition sequence motifs written from 5' to 3' written in Rebase convention. If the point of cleavage has been determined, the precise site is marked with ^. Only letters in the IUPAC code are accepted. For nickases that cleave away from their recognition sequence, the cleavage sites are indicated in parentheses. See details for more information.
cutSites	Vector specifying the cleavage coordinates relative to the first nucleotide of the motif sequence. Each column corresponds to a motif specified in the motifs slot.
weights	Optional numeric vector specifying relative weights for the recognition motifs to specify cleavage probabilities.
metadata	Optional list providing global metadata information.
expand	Should sequences be expanded to only contain ATCG nucleotides? FALSE by default.
primary	Should only the motif with the highest weight be returned? FALSE by default. Only relevant if weights are stored in the Nickase object.
strand	Strand to allow reverse complementation of the motif. "+" by default.
as.character	Should the motif sequences be returned as a character vector? FALSE by default.
combine	Should only unique values be considered? TRUE by default.

Value

A [Nickase](#) object

Functions

- [Nickase\(\)](#): Create a [Nickase](#) object

Slots

nickaseName Name of the nickase
motifs DNASTringSet of recognition sequence motifs written from 5' to 3'.
nickingStrand String specifying with strand with respect to the motif sequence (5' to 3') is nicked. Must be either "original" (default) or "opposite".
cutSites Vector specifying the cleavage coordinates relative to the first nucleotide of the motif sequence. Each column corresponds to a motif specified in the motifs slot.
weights Optional numeric vector specifying relative weights for the motifs corresponding to cleavage probabilities.
metadata Optional string providing a description of the nickase.

Constructors

Use the constructor `link{Nickase}` to create a Nickase object.

Accessors

nickaseName: To get the name of the nickase.
nickingStrand: To get the nicking strand.
metadata: To get the metadata list of the nickase
motifs: To get the recognition motif nucleotide sequences.
weights: To get nickase weights.
cutSites: To get nickase cut sites.

See Also

See the [CrisprNickase](#) for CRISPR-specific nickases.

Examples

```
Nb.BsmI <- Nickase("Nb.BsmI",
                  motifs=c("GAATG^C"),
                  nickingStrand="opposite",
                  metadata=list(description="Nb.BsmI nicking enzyme."))
```

`plotEditingWeights` *Quick plot to visualize editing weights*

Description

Quick plot to visualize editing weights from a BaseEditor object.

Usage

```
plotEditingWeights(
  baseEditor,
  discardEmptyRows = TRUE,
  substitutions = NULL,
  ...
)
```


Arguments

baseEditor A [BaseEditor](#) object.

discardEmptyRows Should rows that have all weight equal to 0 be discarded? TRUE by default.

substitutions Character vector specifying substitutions to be plotted. If NULL (default), all substitutions are shown.

... Additional arguments to be passed to plot

Value

Nothing. A plot is generated as a side effect.

Examples

```
if (interactive()){
  data(BE4max, package="crisprBase")
  plotEditingWeights(BE4max)
}
```

reexports	<i>Objects exported from other packages</i>
-----------	---

Description

These objects are imported from other packages. Follow the links below to see their documentation.

[S4Vectors](#) [metadata](#), [metadata<-](#)

restrictionEnzymes	<i>List of Nuclease objects representing common restriction enzymes</i>
--------------------	---

Description

List of Nuclease objects representing common restriction enzymes from REBASE database.

Usage

```
data(restrictionEnzymes, package="crisprBase")
```

Format

List of Nuclease objects.

Details

List of Nuclease objects representing common restriction enzymes from REBASE database.

SaCas9	<i>SaCas9 CrisprNuclease object</i>
--------	-------------------------------------

Description

CrisprNuclease object for the wildtype *Staphylococcus aureus* Cas9 (SaCas9) nuclease.

Usage

```
data(SaCas9, package="crisprBase")
```

Format

CrisprNuclease object.

Details

The SaCas9 nuclease recognizes NNGRRT PAM sequences. Spacer sequences must be located upstream of PAM sequences. Editing weights were obtained from [doi:10.1038/nature14299](https://doi.org/10.1038/nature14299).

spacerLength	<i>An S4 class to represent a CRISPR nuclease.</i>
--------------	--

Description

An S4 class to represent a CRISPR nuclease.

Usage

```
spacerLength(object, ...)
targetLength(object, ...)
pamLength(object, ...)
spacerGap(object)
hasSpacerGap(object)
spacerGap(object) <- value
spacerLength(object) <- value
pamSide(object, ...)
pamSide(object) <- value
pams(object, ...)
pamIndices(object, ...)
```

```
spacerIndices(object, ...)

prototypeSequence(object, ...)

CrisprNuclease(
  nucleaseName,
  targetType = c("DNA", "RNA"),
  pams = NA_character_,
  weights = rep(1, length(pams)),
  metadata = list(),
  pam_side = NA_character_,
  spacer_gap = 0L,
  spacer_length = NA_integer_
)

## S4 method for signature 'CrisprNuclease'
show(object)

## S4 method for signature 'CrisprNuclease'
pamLength(object)

## S4 method for signature 'CrisprNuclease'
spacerLength(object)

## S4 replacement method for signature 'CrisprNuclease'
spacerLength(object) <- value

## S4 method for signature 'CrisprNuclease'
pamSide(object)

## S4 replacement method for signature 'CrisprNuclease'
pamSide(object) <- value

## S4 method for signature 'CrisprNuclease'
spacerGap(object)

## S4 replacement method for signature 'CrisprNuclease'
spacerGap(object) <- value

## S4 method for signature 'CrisprNuclease'
hasSpacerGap(object)

## S4 method for signature 'CrisprNuclease'
targetLength(object)

## S4 method for signature 'CrisprNuclease'
pams(object, primary = TRUE, ignore_pam = FALSE, as.character = FALSE)

## S4 method for signature 'CrisprNuclease'
pamIndices(object)
```

```
## S4 method for signature 'CrisprNuclease'
spacerIndices(object)
```

```
## S4 method for signature 'CrisprNuclease'
prototypeSequence(object, primary = TRUE)
```

Arguments

object	CrisprNuclease object.
...	Additional arguments for class-specific methods
value	For <code>spacerLength<-</code> and <code>gapLength<-</code> , must be a non-negative integer. For <code>pamSide</code> , must be either <code>'5prime'</code> or <code>'3prime'</code> .
nucleaseName	Name of the CRISPR nuclease.
targetType	String specifying target type ("DNA" or "RNA").
pams	Character vector of PAM sequence motifs written from 5' to 3'. If the point of cleavage has been determined, the precise site is marked with <code>^</code> . Only letters in the IUPAC code are accepted. For nucleases that cleave away from their recognition sequence, the cleavage sites are indicated in parentheses. See details for more information.
weights	Optional numeric vector specifying relative weights of the PAM sequences to specify cleavage probabilities.
metadata	Optional list providing global metadata information.
pam_side	String specifying the side of the PAM sequence with respect to the protospacer sequence. Must be either <code>'3prime'</code> (e.g. Cas9) or <code>'5prime'</code> (e.g. Cas12a)
spacer_gap	Integer specifying the length (in nucleotides) between the spacer sequence and the PAM sequence (e.g. 0 for Cas9 and Cas12a).
spacer_length	Integer specifying the length of the spacer sequence
primary	Should only the PAM sequence with the heighest weight be returned? If no cleavage weights are stored in the CrisprNuclease object, all sequences are returned. TRUE by default.
ignore_pam	Should all possible k-mer sequences for a given PAM length be returned, irrespetively of the PAM sequence motifs stored in the CrisprNuclease object? FALSE by default.
as.character	Should the PAM sequences be returned as a character vector? FALSE by default.

Value

A [CrisprNuclease](#) object

Functions

- `CrisprNuclease()`: Create a [CrisprNuclease](#) object

Slots

<code>pam_side</code>	String specifying the side of the PAM sequence with respect to the protospacer sequence. Must be either <code>'3prime'</code> (e.g. SpCas9) or <code>'5prime'</code> (e.g. AsCas12a)
<code>spacer_length</code>	Integer specifying the length of the spacer sequence
<code>spacer_gap</code>	Integer specifying the length (in nucleotides) between the spacer sequence and the PAM sequence (e.g. 0 for SpCas9 and AsCas12a).

Constructors

Use the constructor `link{CrisprNuclease}` to create a `CrisprNuclease` object.

Accessors

`nucleaseName`: To get the name of the CRISPR nuclease.
`spacerLength`: To return the length of the spacer sequence.
`targetLength`: To return the length of the target sequence (protospacer + pam).
`pamLength`: To return the length of the PAM sequence.
`pamSide`: To return the side of the PAM sequence with respect to the spacer sequence.
`spacerGap`: To return the length of the gap between the PAM and spacer sequences.
`pams`: To return the list of PAM sequences.

Setters

`spacerGap<-`: To change the length of the gap between the PAM and spacer sequences.
`pamSide<-`: To change the side of the PAM sequence with respect to the protospacer sequence.
`spacerLength<-`: To change the length of the spacer sequence.

Utility functions for genomic arithmetics

`pamIndices`: To return the relative coordinates of the PAM sequence within the target sequence.
`spacerIndices`: To return the relative coordinates of the spacer sequence within the target sequence.

Examples

```
SpCas9 <- CrisprNuclease("SpCas9",
  pams=c("(3/3)NGG", "(3/3)NAG", "(3/3)NGA"),
  weights=c(1, 0.2593, 0.0694),
  metadata=list(description="Wildtype Streptococcus
    pyogenes Cas9 (SpCas9) nuclease"),
  pam_side="3prime",
  spacer_length=20)
```

SpCas9

SpCas9 CrisprNuclease object

Description

`CrisprNuclease` object for the wildtype *Streptococcus pyogenes* Cas9 (SpCas9) nuclease.

Usage

```
data(SpCas9, package="crisprBase")
```

Format

`CrisprNuclease` object.

Details

The SpCas9 nuclease recognizes NGG PAM sequences. Spacer sequences must be located upstream of PAM sequences.

SpGCas9

SpGCas9 CrisprNuclease object

Description

CrisprNuclease object for the engineered Streptococcus pyogenes Cas9 SpG nuclease.

Usage

```
data(SpGCas9, package="crisprBase")
```

Format

CrisprNuclease object.

Details

The SpGCas9 nuclease recognizes NGN PAM sequences. Spacer sequences must be located upstream of PAM sequences.

Index

* datasets

- AsCas12a, 3
- BE4max, 6
- CasRx, 6
- Csm, 10
- enAsCas12a, 10
- MAD7, 18
- restrictionEnzymes, 25
- SaCas9, 26
- SpCas9, 29
- SpGCas9, 30

* internal

- reexports, 25

annotateMismatches, 2

AsCas12a, 3

BaseEditor, 4, 5, 15, 25

BaseEditor (baseEditorName), 4

BaseEditor-class (baseEditorName), 4

baseEditorName, 4

baseEditorName, BaseEditor-method
(baseEditorName), 4

baseEditorName<- (baseEditorName), 4

baseEditorName<-, BaseEditor-method
(baseEditorName), 4

BE4max, 6

CasRx, 6

CrisprNickase, 8, 9, 24

CrisprNickase (CrisprNickase-class), 7

CrisprNickase-class, 7

CrisprNuclease, 5, 13, 21, 28

CrisprNuclease (spacerLength), 26

CrisprNuclease-class (spacerLength), 26

Csm, 10

cutSites (motifs), 18

cutSites, Nickase-method (nickaseName),
22

cutSites, Nuclease-method (motifs), 18

editingStrand (baseEditorName), 4

editingStrand, BaseEditor-method
(baseEditorName), 4

editingStrand<- (baseEditorName), 4
editingStrand<-, BaseEditor-method
(baseEditorName), 4

editingWeights (baseEditorName), 4
editingWeights, BaseEditor-method
(baseEditorName), 4

editingWeights<- (baseEditorName), 4
editingWeights<-, BaseEditor-method
(baseEditorName), 4

enAsCas12a, 10

extractPamFromTarget, 11

extractProtospacerFromTarget, 11

getAvailableCrisprNucleases, 12

getCutSiteFromPamSite, 13

getCutSiteRanges, 13

getEditingSiteFromPamSite, 14

getPamRanges, 15

getProtospacerRanges, 16

getTargetRanges, 17

hasSpacerGap (spacerLength), 26

hasSpacerGap, CrisprNickase-method
(CrisprNickase-class), 7

hasSpacerGap, CrisprNuclease-method
(spacerLength), 26

isCutting (motifs), 18

isCutting, Nickase-method (nickaseName),
22

isCutting, Nuclease-method (motifs), 18

isDnase (motifs), 18

isDnase, Nuclease-method (motifs), 18

isRnase (motifs), 18

isRnase, Nuclease-method (motifs), 18

MAD7, 18

metadata, 25

metadata (reexports), 25

metadata<- (reexports), 25

motifLength (motifs), 18

motifLength, Nickase-method
(nickaseName), 22

motifLength, Nuclease-method (motifs), 18

- motifs, 18
- motifs, Nickase-method (nickaseName), 22
- motifs, Nuclease-method (motifs), 18

- Nickase, 23
- Nickase (nickaseName), 22
- Nickase-class (nickaseName), 22
- nickaseName, 22
- nickaseName, Nickase-method (nickaseName), 22
- nickaseName<- (nickaseName), 22
- nickaseName<- , Nickase-method (nickaseName), 22
- nickingStrand (nickaseName), 22
- nickingStrand, Nickase-method (nickaseName), 22
- nickingStrand<- (nickaseName), 22
- nickingStrand<- , Nickase-method (nickaseName), 22
- Nuclease, 20, 21
- Nuclease (motifs), 18
- Nuclease-class (motifs), 18
- nucleaseName (motifs), 18
- nucleaseName, Nuclease-method (motifs), 18
- nucleaseName<- (motifs), 18
- nucleaseName<- , Nuclease-method (motifs), 18

- pamIndices (spacerLength), 26
- pamIndices, CrisprNickase-method (CrisprNickase-class), 7
- pamIndices, CrisprNuclease-method (spacerLength), 26
- pamLength (spacerLength), 26
- pamLength, CrisprNickase-method (CrisprNickase-class), 7
- pamLength, CrisprNuclease-method (spacerLength), 26
- pams (spacerLength), 26
- pams, CrisprNickase-method (CrisprNickase-class), 7
- pams, CrisprNuclease-method (spacerLength), 26
- pamSide (spacerLength), 26
- pamSide, CrisprNickase-method (CrisprNickase-class), 7
- pamSide, CrisprNuclease-method (spacerLength), 26
- pamSide<- (spacerLength), 26
- pamSide<- , CrisprNickase-method (CrisprNickase-class), 7

- pamSide<- , CrisprNuclease-method (spacerLength), 26
- plotEditingWeights, 24
- prototypeSequence (spacerLength), 26
- prototypeSequence, CrisprNickase-method (CrisprNickase-class), 7
- prototypeSequence, CrisprNuclease-method (spacerLength), 26

- reexports, 25
- restrictionEnzymes, 25

- SaCas9, 26
- show, BaseEditor-method (baseEditorName), 4
- show, CrisprNickase-method (CrisprNickase-class), 7
- show, CrisprNuclease-method (spacerLength), 26
- show, Nickase-method (nickaseName), 22
- show, Nuclease-method (motifs), 18
- spacerGap (spacerLength), 26
- spacerGap, CrisprNickase-method (CrisprNickase-class), 7
- spacerGap, CrisprNuclease-method (spacerLength), 26
- spacerGap<- (spacerLength), 26
- spacerGap<- , CrisprNickase-method (CrisprNickase-class), 7
- spacerGap<- , CrisprNuclease-method (spacerLength), 26
- spacerIndices (spacerLength), 26
- spacerIndices, CrisprNickase-method (CrisprNickase-class), 7
- spacerIndices, CrisprNuclease-method (spacerLength), 26
- spacerLength, 26
- spacerLength, CrisprNickase-method (CrisprNickase-class), 7
- spacerLength, CrisprNuclease-method (spacerLength), 26
- spacerLength<- (spacerLength), 26
- spacerLength<- , CrisprNickase-method (CrisprNickase-class), 7
- spacerLength<- , CrisprNuclease-method (spacerLength), 26
- SpCas9, 29
- SpGCas9, 30

- targetLength (spacerLength), 26
- targetLength, CrisprNickase-method (CrisprNickase-class), 7

targetLength, CrisprNuclease-method
(spacerLength), 26

targetType (motifs), 18

targetType, Nuclease-method (motifs), 18

targetType<- (motifs), 18

targetType<-, Nuclease-method (motifs),
18

weights (motifs), 18

weights, Nickase-method (nickaseName), 22

weights, Nuclease-method (motifs), 18

weights<- (motifs), 18

weights<-, Nickase-method (nickaseName),
22

weights<-, Nuclease-method (motifs), 18