Package 'chipenrich.data'

November 28, 2024

Title Companion package to chipenrich

Version 2.30.0

Date 2023-03-29

Description Supporting data for the chipenrich package. Includes pre-defined gene sets, gene locus definitions, and mappability estimates.

biocViews ChIPSeq, Epigenetics, FunctionalGenomics, GeneSetEnrichment, HistoneModification, Regression

Depends R (>= 3.4.0)

Imports AnnotationDbi, BiocGenerics, methods, GenomicRanges, GenomeInfoDb, IRanges, readr, rtracklayer, S4Vectors, utils

License GPL-3

Encoding UTF-8

LazyData true

Suggests BiocStyle, devtools, knitr, rmarkdown, roxygen2, testthat, GO.db, org.Dm.eg.db, org.Dr.eg.db, org.Hs.eg.db, org.Mm.eg.db, org.Rn.eg.db, TxDb.Dmelanogaster.UCSC.dm3.ensGene, TxDb.Dmelanogaster.UCSC.dm6.ensGene, TxDb.Drerio.UCSC.danRer10.refGene, TxDb.Hsapiens.UCSC.hg19.knownGene, TxDb.Hsapiens.UCSC.hg38.knownGene, TxDb.Mmusculus.UCSC.mm9.knownGene, TxDb.Mmusculus.UCSC.mm10.knownGene, TxDb.Rnorvegicus.UCSC.rn4.ensGene, TxDb.Rnorvegicus.UCSC.rn5.refGene, TxDb.Rnorvegicus.UCSC.rn6.refGene

VignetteBuilder knitr

RoxygenNote 6.1.1

Maintainer Kai Wang <wangdaha@umich.edu>

git_url https://git.bioconductor.org/packages/chipenrich.data

git_branch RELEASE_3_20

git_last_commit 4981ec3

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-28

Author Ryan P. Welch [aut, cph],
Chee Lee [aut],
Raymond G. Cavalcante [aut],
Kai Wang [cre],
Laura J. Scott [ths],
Maureen A. Sartor [ths]

Contents

chipenrich.data . . . 7
enhancer.dnase_thurman.0 . . . 7
gene.enh.desc . . . 8
GeneSet-class . . . 8
geneset.biocarta_pathway.hsa . . . 9
geneset.biocarta_pathway.mmu . . . 10
geneset.biocarta_pathway.rno . . . 10
geneset.ctd.hsa . . . 11
geneset.ctd.mmu . . . 11
geneset.cytoband.hsa . . . 12
geneset.drug_bank.hsa . . . 13
geneset.drug_bank.mmu . . . 13
geneset.drug_bank.rno . . . 14
geneset.GOBP.dme . . . 14
geneset.GOBP.dre . . . 15
geneset.GOBP.hsa . . . 15
geneset.GOBP.mmu . . . 16
geneset.GOBP.rno . . . 17
geneset.GOCC.dme . . . 17
geneset.GOCC.dre . . . 18
geneset.GOCC.hsa . . . 19
geneset.GOCC.mmu . . . 19
geneset.GOCC.rno . . . 20
geneset.GOMF.dme . . . 21
geneset.GOMF.dre . . . 21
geneset.GOMF.hsa . . . 22
geneset.GOMF.mmu . . . 23
geneset.GOMF.rno . . . 23
geneset.hallmark.hsa . . . 24
geneset.immunologic.hsa . . . 25
geneset.kegg_pathway.hsa . . . 25
geneset.kegg_pathway.mmu . . . 26
geneset.kegg_pathway.rno . . . 27
geneset.mesh.hsa . . . 27
geneset.mesh.mmu . . . 28
geneset.mesh.rno . . . 28
geneset.metabolite.hsa . . . 29
geneset.metabolite.mmu . . . 29
geneset.metabolite.rno . . . 30
geneset.microrna.hsa . . . 30
geneset.oncogenic.hsa . . . 31
geneset.panther_pathway.hsa . . . 31
geneset.panther_pathway.mmu . . . 32

geneset.panther_pathway.rno . . . 32
geneset.pfam.hsa . . . 33
geneset.pfam.mmu . . . 33
geneset.pfam.rno . . . 34
geneset.protein_interaction_biogrid.hsa . . . 34
geneset.reactome.dme . . . 35
geneset.reactome.dre . . . 35
geneset.reactome.hsa . . . 36
geneset.reactome.mmu . . . 37
geneset.reactome.rno . . . 37
geneset.transcription_factors.hsa . . . 38
geneset.transcription_factors.mmu . . . 39
geneset.transcription_factors.rno . . . 39
locusdef.danRer10.10kb . . . 40
locusdef.danRer10.10kb_outside . . . 40
locusdef.danRer10.10kb_outside_upstream . . . 41
locusdef.danRer10.1kb . . . 42
locusdef.danRer10.1kb_outside . . . 42
locusdef.danRer10.1kb_outside_upstream . . . 43
locusdef.danRer10.5kb . . . 44
locusdef.danRer10.5kb_outside . . . 44
locusdef.danRer10.5kb_outside_upstream . . . 45
locusdef.danRer10.exon . . . 46
locusdef.danRer10.intron . . . 46
locusdef.danRer10.nearest_gene . . . 47
locusdef.danRer10.nearest_tss . . . 48
locusdef.dm3.10kb . . . 48
locusdef.dm3.10kb_outside . . . 49
locusdef.dm3.10kb_outside_upstream . . . 50
locusdef.dm3.1kb . . . 51
locusdef.dm3.1kb_outside . . . 51
locusdef.dm3.1kb_outside_upstream . . . 52
locusdef.dm3.5kb . . . 53
locusdef.dm3.5kb_outside . . . 53
locusdef.dm3.5kb_outside_upstream . . . 54
locusdef.dm3.exon . . . 55
locusdef.dm3.intron . . . 55
locusdef.dm3.nearest_gene . . . 56
locusdef.dm3.nearest_tss . . . 57
locusdef.dm6.10kb . . . 58
locusdef.dm6.10kb_outside . . . 58
locusdef.dm6.10kb_outside_upstream . . . 59
locusdef.dm6.1kb . . . 60
locusdef.dm6.1kb_outside . . . 60
locusdef.dm6.1kb_outside_upstream . . . 61
locusdef.dm6.5kb . . . 62
locusdef.dm6.5kb_outside . . . 62
locusdef.dm6.5kb_outside_upstream . . . 63
locusdef.dm6.exon . . . 64
locusdef.dm6.intron . . . 64
locusdef.dm6.nearest_gene . . . 65
locusdef.dm6.nearest_tss . . . 66

locusdef.hg19.10kb . . . 67
locusdef.hg19.10kb_outside . . . 67
locusdef.hg19.10kb_outside_upstream . . . 68
locusdef.hg19.1kb . . . 69
locusdef.hg19.1kb_outside . . . 70
locusdef.hg19.1kb_outside_upstream . . . 70
locusdef.hg19.5kb . . . 71
locusdef.hg19.5kb_outside . . . 72
locusdef.hg19.5kb_outside_upstream . . . 72
locusdef.hg19.exon . . . 73
locusdef.hg19.intron . . . 74
locusdef.hg19.nearest_gene . . . 74
locusdef.hg19.nearest_tss . . . 75
locusdef.hg38.10kb . . . 76
locusdef.hg38.10kb_outside . . . 77
locusdef.hg38.10kb_outside_upstream . . . 77
locusdef.hg38.1kb . . . 78
locusdef.hg38.1kb_outside . . . 79
locusdef.hg38.1kb_outside_upstream . . . 79
locusdef.hg38.5kb . . . 80
locusdef.hg38.5kb_outside . . . 81
locusdef.hg38.5kb_outside_upstream . . . 81
locusdef.hg38.exon . . . 82
locusdef.hg38.intron . . . 83
locusdef.hg38.nearest_gene . . . 83
locusdef.hg38.nearest_tss . . . 84
locusdef.mm10.10kb . . . 85
locusdef.mm10.10kb_outside . . . 86
locusdef.mm10.10kb_outside_upstream . . . 86
locusdef.mm10.1kb . . . 87
locusdef.mm10.1kb_outside . . . 88
locusdef.mm10.1kb_outside_upstream . . . 88
locusdef.mm10.5kb . . . 89
locusdef.mm10.5kb_outside . . . 90
locusdef.mm10.5kb_outside_upstream . . . 90
locusdef.mm10.exon . . . 91
locusdef.mm10.intron . . . 92
locusdef.mm10.nearest_gene . . . 92
locusdef.mm10.nearest_tss . . . 93
locusdef.mm9.10kb . . . 94
locusdef.mm9.10kb_outside . . . 95
locusdef.mm9.10kb_outside_upstream . . . 95
locusdef.mm9.1kb . . . 96
locusdef.mm9.1kb_outside . . . 97
locusdef.mm9.1kb_outside_upstream . . . 97
locusdef.mm9.5kb . . . 98
locusdef.mm9.5kb_outside . . . 99
locusdef.mm9.5kb_outside_upstream . . . 99
locusdef.mm9.exon . . . 100
locusdef.mm9.intron . . . 101
locusdef.mm9.nearest_gene . . . 101
locusdef.mm9.nearest_tss . . . 102

locusdef.rn4.10kb . . . 103
locusdef.rn4.10kb_outside . . . 104
locusdef.rn4.10kb_outside_upstream . . . 104
locusdef.rn4.1kb . . . 105
locusdef.rn4.1kb_outside . . . 106
locusdef.rn4.1kb_outside_upstream . . . 106
locusdef.rn4.5kb . . . 107
locusdef.rn4.5kb_outside . . . 108
locusdef.rn4.5kb_outside_upstream . . . 108
locusdef.rn4.exon . . . 109
locusdef.rn4.intron . . . 110
locusdef.rn4.nearest_gene . . . 110
locusdef.rn4.nearest_tss . . . 111
locusdef.rn5.10kb . . . 112
locusdef.rn5.10kb_outside . . . 112
locusdef.rn5.10kb_outside_upstream . . . 113
locusdef.rn5.1kb . . . 114
locusdef.rn5.1kb_outside . . . 114
locusdef.rn5.1kb_outside_upstream . . . 115
locusdef.rn5.5kb . . . 116
locusdef.rn5.5kb_outside . . . 116
locusdef.rn5.5kb_outside_upstream . . . 117
locusdef.rn5.exon . . . 118
locusdef.rn5.intron . . . 118
locusdef.rn5.nearest_gene . . . 119
locusdef.rn5.nearest_tss . . . 120
locusdef.rn6.10kb . . . 120
locusdef.rn6.10kb_outside . . . 121
locusdef.rn6.10kb_outside_upstream . . . 122
locusdef.rn6.1kb . . . 122
locusdef.rn6.1kb_outside . . . 123
locusdef.rn6.1kb_outside_upstream . . . 124
locusdef.rn6.5kb . . . 124
locusdef.rn6.5kb_outside . . . 125
locusdef.rn6.5kb_outside_upstream . . . 126
locusdef.rn6.exon . . . 126
locusdef.rn6.intron . . . 127
locusdef.rn6.nearest_gene . . . 128
locusdef.rn6.nearest_tss . . . 128
LocusDefinition-class . . . 129
mappa.hg19.10kb.100mer . . . 130
mappa.hg19.10kb.24mer . . . 131
mappa.hg19.10kb.36mer . . . 131
mappa.hg19.10kb.40mer . . . 132
mappa.hg19.10kb.50mer . . . 133
mappa.hg19.10kb.75mer . . . 133
mappa.hg19.1kb.100mer . . . 134
mappa.hg19.1kb.24mer . . . 135
mappa.hg19.1kb.36mer . . . 135
mappa.hg19.1kb.40mer . . . 136
mappa.hg19.1kb.50mer . . . 137
mappa.hg19.1kb.75mer . . . 137

mappa.hg19.5kb.100mer . . . 138
mappa.hg19.5kb.24mer . . . 139
mappa.hg19.5kb.36mer . . . 139
mappa.hg19.5kb.40mer . . . 140
mappa.hg19.5kb.50mer . . . 141
mappa.hg19.5kb.75mer . . . 141
mappa.hg19.exon.100mer . . . 142
mappa.hg19.exon.24mer . . . 143
mappa.hg19.exon.36mer . . . 143
mappa.hg19.exon.40mer . . . 144
mappa.hg19.exon.50mer . . . 145
mappa.hg19.exon.75mer . . . 145
mappa.hg19.intron.100mer . . . 146
mappa.hg19.intron.24mer . . . 147
mappa.hg19.intron.36mer . . . 147
mappa.hg19.intron.40mer . . . 148
mappa.hg19.intron.50mer . . . 149
mappa.hg19.intron.75mer . . . 149
mappa.hg19.nearest_gene.100mer . . . 150
mappa.hg19.nearest_gene.24mer . . . 151
mappa.hg19.nearest_gene.36mer . . . 151
mappa.hg19.nearest_gene.40mer . . . 152
mappa.hg19.nearest_gene.50mer . . . 153
mappa.hg19.nearest_gene.75mer . . . 153
mappa.hg19.nearest_tss.100mer . . . 154
mappa.hg19.nearest_tss.24mer . . . 155
mappa.hg19.nearest_tss.36mer . . . 155
mappa.hg19.nearest_tss.40mer . . . 156
mappa.hg19.nearest_tss.50mer . . . 157
mappa.hg19.nearest_tss.75mer . . . 157
mappa.mm9.10kb.100mer . . . 158
mappa.mm9.10kb.36mer . . . 159
mappa.mm9.10kb.40mer . . . 159
mappa.mm9.10kb.50mer . . . 160
mappa.mm9.10kb.75mer . . . 161
mappa.mm9.1kb.100mer . . . 161
mappa.mm9.1kb.36mer . . . 162
mappa.mm9.1kb.40mer . . . 163
mappa.mm9.1kb.50mer . . . 163
mappa.mm9.1kb.75mer . . . 164
mappa.mm9.5kb.100mer . . . 165
mappa.mm9.5kb.36mer . . . 165
mappa.mm9.5kb.40mer . . . 166
mappa.mm9.5kb.50mer . . . 167
mappa.mm9.5kb.75mer . . . 167
mappa.mm9.exon.100mer . . . 168
mappa.mm9.exon.36mer . . . 169
mappa.mm9.exon.40mer . . . 169
mappa.mm9.exon.50mer . . . 170
mappa.mm9.exon.75mer . . . 171
mappa.mm9.intron.100mer . . . 171
mappa.mm9.intron.36mer . . . 172

mappa.mm9.intron.40mer . . . 173
mappa.mm9.intron.50mer . . . 173
mappa.mm9.intron.75mer . . . 174
mappa.mm9.nearest_gene.100mer . . . 175
mappa.mm9.nearest_gene.36mer . . . 175
mappa.mm9.nearest_gene.40mer . . . 176
mappa.mm9.nearest_gene.50mer . . . 177
mappa.mm9.nearest_gene.75mer . . . 177
mappa.mm9.nearest_tss.100mer . . . 178
mappa.mm9.nearest_tss.36mer . . . 179
mappa.mm9.nearest_tss.40mer . . . 179
mappa.mm9.nearest_tss.50mer . . . 180
mappa.mm9.nearest_tss.75mer . . . 181
peaks_E2F4 . . . 181
peaks_H3K4me3_GM12878 . . . 182
spline.log_dtss.90ENCODE . . . 183
tss.danRer10 . . . 183
tss.dm3 . . . 184
tss.dm6 . . . 184
tss.hg19 . . . 185
tss.hg38 . . . 185
tss.mm10 . . . 186
tss.mm9 . . . 186
tss.rn4 . . . 187
tss.rn5 . . . 187
tss.rn6 . . . 188

Index **189**

`chipenrich.data` *chipenrich.data: Data for chipenrich: gene set enrichment analysis for ChIP-seq data*

Description

Supporting data for the chipenrich package. Includes pre-defined gene sets, gene locus definitions, and mappability estimates.

`enhancer.dnase_thurman.0` *Enhancer locations*

Description

A `GRanges` with all the enhancer locations for hg19. The locations were found using a combination of DNAse data and from Thurman et al (PMID: 22955617)

Usage

```
enhancer.dnase_thurman.0
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

---

gene.enh.desc *Gene-Enhancer descriptives*

Description

A data frame with gene-level descriptions of enhancer properties using enhancers.dnase_thurman.0. Used in the adjustment of proximity test to enhancers.

gene_id The Entrez ID for the a gene

avg_denh_emp The empirical average distance to an enhancer from 90 ENCODE ChIP-seq datasets. This is used as the adjustment.

num_enh The number of enhancers assigned to the gene, defined by closest gene TSS

avgdenh The theoretical average distance to an enhancer assuming every base pair on the genome is equally likely to have a peak binding.

Usage

```
gene.enh.desc
```

Format

An object of class data.frame with 21600 rows and 4 columns.

GeneSet-class *Class "GeneSet"*

Description

Class for storing sets of genes and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form new("GeneSet").

These objects are used internally by the chipenrich package and users will not likely need to create these.

Slots

set.gene: Object of class "environment". Maps from geneset IDs to lists of Entrez gene IDs.

type: Object of class "character". The formal name for this collection of genesets.

set.name: Object of class "environment". Maps from geneset IDs to their descriptions/names.

all.genes: Object of class "character". A set of all genes present across every geneset.

organism: Object of class "character". Organism code for gene IDs.

dburl: Object of class "character". Web URL for this collection of genesets.

Note

Not typically accessed by the user - this is used internally by the chipenrich package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
# Show information about class.
showClass("GeneSet")

# What is stored inside a geneset object?
data("geneset.metabolite.hsa");
str(geneset.metabolite.hsa);

# How are the mappings from geneset IDs to gene IDs stored?
ls.str(geneset.metabolite.hsa@set.gene);
```

---

geneset.biocarta_pathway.hsa

geneset.biocarta_pathway.hsa genesets for BioCarta

Description

BioCarta (biocarta_pathway) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:46:04 2017.

Usage

```
geneset.biocarta_pathway.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

https://cgap.nci.nih.gov/Pathways/BioCarta_Pathways

`geneset.biocarta_pathway.mmu`
geneset.biocarta_pathway.mmu

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.biocarta_pathway.mmu)
```

Format

See `GeneSet-class` for a description of the format.

See Also

For more information about genesets: `chipenrich.data`

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.biocarta_pathway.rno`
geneset.biocarta_pathway.rno

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.biocarta_pathway.rno)
```

Format

See `GeneSet-class` for a description of the format.

See Also

For more information about genesets: `chipenrich.data`

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.ctd.hsa *geneset.ctd.hsa genesets for Comparative Toxicogenomics Database*

Description

Comparative Toxicogenomics Database (ctd) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:46:11 2017.

Usage

```
geneset.ctd.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://ctdbase.org

geneset.ctd.mmu *geneset.ctd.mmu genesets for Comparative Toxicogenomics Database*

Description

Comparative Toxicogenomics Database (ctd) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Sat Nov 10 15:56:37 2018.

Usage

```
geneset.ctd.mmu
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://ctdbase.org

---

geneset.cytoband.hsa *geneset.cytoband.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.cytoband.hsa)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.drug_bank.hsa *geneset.drug_bank.hsa genesets for DrugBank*

Description

DrugBank (drug_bank) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:46:13 2017.

Usage

```
geneset.drug_bank.hsa
```

Format

A `GeneSet` object with the following slots:

type A `character` indicating the type of genesets, e.g. GOBP.

dburl A `character` of the URL of the database underlying the genesets.

organism A `character` of the organism, e.g. Homo sapiens.

set.gene An `environment` containing a `list` whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are `character` vectors of Entrez Gene IDs.

all.genes A `character` vector of all the Entrez Gene IDs contained over all the genesets in this `type`.

set.name An `environment` containing a `list` whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

https://www.drugbank.ca

geneset.drug_bank.mmu *geneset.drug_bank.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.drug_bank.mmu)
```

Format

See `GeneSet-class` for a description of the format.

See Also

For more information about genesets: `chipenrich.data`

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.drug_bank.rno *geneset.drug_bank.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.drug_bank.rno)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

---

geneset.GOBP.dme *geneset.GOBP.dme genesets for Drosophila melanogaster*

Description

Gene Ontology Biological Process (GOBP) genesets for Drosophila melanogaster. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:24:38 2017.

Usage

```
geneset.GOBP.dme
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOBP.dre *geneset.GOBP.dre genesets for Danio rerio*

Description

Gene Ontology Biological Process (GOBP) genesets for Danio rerio. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

```
geneset.GOBP.dre
```

Format

A `GeneSet` object with the following slots:

type A `character` indicating the type of genesets, e.g. GOBP.

dburl A `character` of the URL of the database underlying the genesets.

organism A `character` of the organism, e.g. Homo sapiens.

set.gene An `environment` containing a `list` whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are `character` vectors of Entrez Gene IDs.

all.genes A `character` vector of all the Entrez Gene IDs contained over all the genesets in this `type`.

set.name An `environment` containing a `list` whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dr.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOBP.hsa *geneset.GOBP.hsa genesets for Homo sapiens*

Description

Gene Ontology Biological Process (GOBP) genesets for Homo sapiens. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:22:22 2017.

Usage

```
geneset.GOBP.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Hs.eg.db_3.4.2 and GO.db_3.4.2

---

geneset.GOBP.mmu *geneset.GOBP.mmu genesets for Mus musculus*

Description

Gene Ontology Biological Process (GOBP) genesets for Mus musculus. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:23:23 2017.

Usage

```
geneset.GOBP.mmu
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Mm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOBP.rno *geneset.GOBP.rno genesets for Rattus norvegicus*

Description

Gene Ontology Biological Process (GOBP) genesets for Rattus norvegicus. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:24:10 2017.

Usage

```
geneset.GOBP.rno
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Rn.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.dme *geneset.GOCC.dme genesets for Drosophila melanogaster*

Description

Gene Ontology Cellular Component (GOCC) genesets for Drosophila melanogaster. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:24:38 2017.

Usage

```
geneset.GOCC.dme
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dm.eg.db_3.4.2 and GO.db_3.4.2

---

geneset.GOCC.dre *geneset.GOCC.dre genesets for Danio rerio*

Description

Gene Ontology Cellular Component (GOCC) genesets for Danio rerio. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

```
geneset.GOCC.dre
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dr.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.hsa *geneset.GOCC.hsa genesets for Homo sapiens*

Description

Gene Ontology Cellular Component (GOCC) genesets for Homo sapiens. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:22:22 2017.

Usage

```
geneset.GOCC.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Hs.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.mmu *geneset.GOCC.mmu genesets for Mus musculus*

Description

Gene Ontology Cellular Component (GOCC) genesets for Mus musculus. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:23:23 2017.

Usage

```
geneset.GOCC.mmu
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Mm.eg.db_3.4.2 and GO.db_3.4.2

---

geneset.GOCC.rno *geneset.GOCC.rno genesets for Rattus norvegicus*

Description

Gene Ontology Cellular Component (GOCC) genesets for Rattus norvegicus. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:24:10 2017.

Usage

```
geneset.GOCC.rno
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Rn.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.dme *geneset.GOMF.dme genesets for Drosophila melanogaster*

Description

Gene Ontology Molecular Function (GOMF) genesets for Drosophila melanogaster. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:24:38 2017.

Usage

```
geneset.GOMF.dme
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.dre *geneset.GOMF.dre genesets for Danio rerio*

Description

Gene Ontology Molecular Function (GOMF) genesets for Danio rerio. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

```
geneset.GOMF.dre
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dr.eg.db_3.4.2 and GO.db_3.4.2

---

geneset.GOMF.hsa *geneset.GOMF.hsa genesets for Homo sapiens*

Description

Gene Ontology Molecular Function (GOMF) genesets for Homo sapiens. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:22:22 2017.

Usage

```
geneset.GOMF.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Hs.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.mmu *geneset.GOMF.mmu genesets for Mus musculus*

Description

Gene Ontology Molecular Function (GOMF) genesets for Mus musculus. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:23:23 2017.

Usage

```
geneset.GOMF.mmu
```

Format

A `GeneSet` object with the following slots:

type A `character` indicating the type of genesets, e.g. GOBP.

dburl A `character` of the URL of the database underlying the genesets.

organism A `character` of the organism, e.g. Homo sapiens.

set.gene An `environment` containing a `list` whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are `character` vectors of Entrez Gene IDs.

all.genes A `character` vector of all the Entrez Gene IDs contained over all the genesets in this `type`.

set.name An `environment` containing a `list` whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Mm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.rno *geneset.GOMF.rno genesets for Rattus norvegicus*

Description

Gene Ontology Molecular Function (GOMF) genesets for Rattus norvegicus. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 16:24:10 2017.

Usage

```
geneset.GOMF.rno
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Rn.eg.db_3.4.2 and GO.db_3.4.2

---

geneset.hallmark.hsa *geneset.hallmark.hsa genesets for Hallmark (MSigDB)*

Description

Hallmark (MSigDB) (hallmark) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:46:15 2017.

Usage

```
geneset.hallmark.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://software.broadinstitute.org/gsea/msigdb/collections.jsp#H

geneset.immunologic.hsa

geneset.immunologic.hsa genesets for Immunologic Signatures (MSigDB)

Description

Immunologic Signatures (MSigDB) (immunologic) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:46:45 2017.

Usage

```
geneset.immunologic.hsa
```

Format

A `GeneSet` object with the following slots:

type A `character` indicating the type of genesets, e.g. GOBP.

dburl A `character` of the URL of the database underlying the genesets.

organism A `character` of the organism, e.g. Homo sapiens.

set.gene An `environment` containing a `list` whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are `character` vectors of Entrez Gene IDs.

all.genes A `character` vector of all the Entrez Gene IDs contained over all the genesets in this `type`.

set.name An `environment` containing a `list` whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://software.broadinstitute.org/gsea/msigdb/collections.jsp#C7

geneset.kegg_pathway.hsa

geneset.kegg_pathway.hsa genesets for KEGG Pathways

Description

KEGG Pathways (kegg_pathway) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:46:53 2017.

Usage

```
geneset.kegg_pathway.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://kegg.jp

`geneset.kegg_pathway.mmu`
geneset.kegg_pathway.mmu

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.mmu)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.kegg_pathway.rno *geneset.kegg_pathway.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.rno)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.mesh.hsa *geneset.mesh.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.hsa)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.mesh.mmu *geneset.mesh.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.mmu)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.mesh.rno *geneset.mesh.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.rno)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.metabolite.hsa *geneset.metabolite.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.hsa)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.metabolite.mmu *geneset.metabolite.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.mmu)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.metabolite.rno *geneset.metabolite.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.rno)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.microrna.hsa *geneset.microrna.hsa genesets for MicroRNA Targets (MSigDB)*

Description

MicroRNA Targets (MSigDB) (microrna) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:46:56 2017.

Usage

```
geneset.microrna.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://software.broadinstitute.org/gsea/msigdb/collections.jsp#C3

geneset.oncogenic.hsa *geneset.oncogenic.hsa genesets for Oncogenic Signatures (MSigDB)*

Description

Oncogenic Signatures (MSigDB) (oncogenic) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:47:23 2017.

Usage

```
geneset.oncogenic.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://software.broadinstitute.org/gsea/msigdb/collections.jsp#C6

geneset.panther_pathway.hsa *geneset.panther_pathway.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.panther_pathway.hsa)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

`geneset.panther_pathway.mmu`
geneset.panther_pathway.mmu

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.panther_pathway.mmu)
```

Format

See `GeneSet-class` for a description of the format.

See Also

For more information about genesets: `chipenrich.data`

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.panther_pathway.rno`
geneset.panther_pathway.rno

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.panther_pathway.rno)
```

Format

See `GeneSet-class` for a description of the format.

See Also

For more information about genesets: `chipenrich.data`

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.pfam.hsa *geneset.pfam.hsa genesets for Pfam*

Description

Pfam (pfam) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:47:28 2017.

Usage

```
geneset.pfam.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://pfam.xfam.org

---

geneset.pfam.mmu *geneset.pfam.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.pfam.mmu)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.pfam.rno *geneset.pfam.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.pfam.rno)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.protein_interaction_biogrid.hsa *geneset.protein_interaction_biogrid.hsa genesets for BioGRID Protein Interactions*

Description

BioGRID Protein Interactions (protein_interaction_biogrid) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Tue Oct 24 16:05:53 2017.

Usage

```
geneset.protein_interaction_biogrid.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

https://thebiogrid.org

`geneset.reactome.dme` *geneset.reactome.dme genesets for Drosophila melanogaster*

Description

Reactome genesets for Drosophila melanogaster. All genesets are required to have >= 10 Entrez IDs. Built on Mon Mar 20 15:14:03 2017.

Usage

```
geneset.reactome.dme
```

Format

A `GeneSet` object with the following slots:

type A `character` indicating the type of genesets, e.g. Reactome.

dburl A `character` of the URL of the database underlying the genesets.

organism A `character` of the organism, e.g. Homo sapiens.

set.gene An `environment` containing a `list` whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are `character` vectors of Entrez Gene IDs.

all.genes A `character` vector of all the Entrez Gene IDs contained over all the genesets in this `type`.

set.name An `environment` containing a `list` whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

`geneset.reactome.dre` *geneset.reactome.dre genesets for Danio rerio*

Description

Reactome genesets for Danio rerio. All genesets are required to have >= 10 Entrez IDs. Built on Tue Mar 28 13:03:21 2017.

Usage

```
geneset.reactome.dre
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

---

geneset.reactome.hsa *geneset.reactome.hsa genesets for Homo sapiens*

Description

Reactome genesets for Homo sapiens. All genesets are required to have >= 10 Entrez IDs. Built on Mon Mar 20 15:13:45 2017.

Usage

```
geneset.reactome.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

geneset.reactome.mmu *geneset.reactome.mmu genesets for Mus musculus*

Description

Reactome genesets for Mus musculus. All genesets are required to have >= 10 Entrez IDs. Built on Mon Mar 20 15:13:55 2017.

Usage

```
geneset.reactome.mmu
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

geneset.reactome.rno *geneset.reactome.rno genesets for Rattus norvegicus*

Description

Reactome genesets for Rattus norvegicus. All genesets are required to have >= 10 Entrez IDs. Built on Mon Mar 20 15:13:59 2017.

Usage

```
geneset.reactome.rno
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

---

geneset.transcription_factors.hsa

geneset.transcription_factors.hsa genesets for Transcription Factor Targets (MSigDB)

Description

Transcription Factor Targets (MSigDB) (transcription_factors) genesets. All genesets are required to have >= 10 Entrez IDs. Built on Mon Oct 16 18:47:33 2017.

Usage

```
geneset.transcription_factors.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://software.broadinstitute.org/gsea/msigdb/collections.jsp#C3

geneset.transcription_factors.mmu *geneset.transcription_factors.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.transcription_factors.mmu)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

geneset.transcription_factors.rno *geneset.transcription_factors.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.transcription_factors.rno)
```

Format

See GeneSet-class for a description of the format.

See Also

For more information about genesets: chipenrich.data

For information regarding how the genesets were created: browseVignettes("chipenrich.data")

`locusdef.danRer10.10kb`

locusdef.danRer10.10kb locus definition

Description

A `LocusDefinition` where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.danRer10.10kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, danRer10.

organism A `character` indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:27 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

`locusdef.danRer10.10kb_outside`

locusdef.danRer10.10kb_outside locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.danRer10.10kb_outside
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, danRer10.

organism A `character` indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:27 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

`locusdef.danRer10.10kb_outside_upstream` *locusdef.danRer10.10kb_outside_upstream locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.danRer10.10kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, danRer10.

organism A `character` indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:27 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.danRer10.1kb *locusdef.danRer10.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.danRer10.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:25 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.danRer10.1kb_outside *locusdef.danRer10.1kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.danRer10.1kb_outside
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, danRer10.

organism A `character` indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:26 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

`locusdef.danRer10.1kb_outside_upstream` *locusdef.danRer10.1kb_outside_upstream locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.danRer10.1kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, danRer10.

organism A `character` indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:25 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.danRer10.5kb *locusdef.danRer10.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.danRer10.5kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:26 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.danRer10.5kb_outside *locusdef.danRer10.5kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.danRer10.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:27 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

---

locusdef.danRer10.5kb_outside_upstream

locusdef.danRer10.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.danRer10.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:26 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

`locusdef.danRer10.exon`

locusdef.danRer10.exon locus definition

Description

A `LocusDefinition` where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.danRer10.exon
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, danRer10.

organism A `character` indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:24 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

`locusdef.danRer10.intron`

locusdef.danRer10.intron locus definition

Description

A `LocusDefinition` where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.danRer10.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:25 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

---

locusdef.danRer10.nearest_gene

locusdef.danRer10.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.danRer10.nearest_gene
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:23 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.danRer10.nearest_tss *locusdef.danRer10.nearest_tss locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.danRer10.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:22 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.dm3.10kb *locusdef.dm3.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.dm3.10kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

---

locusdef.dm3.10kb_outside

locusdef.dm3.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.dm3.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:06 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

`locusdef.dm3.10kb_outside_upstream`
locusdef.dm3.10kb_outside_upstream locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm3.10kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm3.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

locusdef.dm3.1kb *locusdef.dm3.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.dm3.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

locusdef.dm3.1kb_outside *locusdef.dm3.1kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.dm3.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

---

locusdef.dm3.1kb_outside_upstream

locusdef.dm3.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm3.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

---

locusdef.dm3.5kb *locusdef.dm3.5kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.dm3.5kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm3.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

---

locusdef.dm3.5kb_outside *locusdef.dm3.5kb_outside locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.dm3.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

---

locusdef.dm3.5kb_outside_upstream

locusdef.dm3.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm3.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

---

locusdef.dm3.exon *locusdef.dm3.exon locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.dm3.exon
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm3.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:04 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

---

locusdef.dm3.intron *locusdef.dm3.intron locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.dm3.intron
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm3.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:04 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

`locusdef.dm3.nearest_gene`

locusdef.dm3.nearest_gene locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.dm3.nearest_gene
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm3.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:03 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

`locusdef.dm3.nearest_tss`
locusdef.dm3.nearest_tss locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.dm3.nearest_tss
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm3.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:03 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

`locusdef.dm6.10kb` *locusdef.dm6.10kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.dm6.10kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm6.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

`locusdef.dm6.10kb_outside`
locusdef.dm6.10kb_outside locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.dm6.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

---

locusdef.dm6.10kb_outside_upstream

locusdef.dm6.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm6.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

`locusdef.dm6.1kb` *locusdef.dm6.1kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.dm6.1kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm6.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:34 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

`locusdef.dm6.1kb_outside`
locusdef.dm6.1kb_outside locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.dm6.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

---

locusdef.dm6.1kb_outside_upstream

locusdef.dm6.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm6.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:34 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

`locusdef.dm6.5kb` *locusdef.dm6.5kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.dm6.5kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm6.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

`locusdef.dm6.5kb_outside`
locusdef.dm6.5kb_outside locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.dm6.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

---

locusdef.dm6.5kb_outside_upstream

locusdef.dm6.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm6.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

---

locusdef.dm6.exon *locusdef.dm6.exon locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.dm6.exon
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm6.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:33 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

---

locusdef.dm6.intron *locusdef.dm6.intron locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.dm6.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:34 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

---

locusdef.dm6.nearest_gene

locusdef.dm6.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.dm6.nearest_gene
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:33 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

`locusdef.dm6.nearest_tss`
locusdef.dm6.nearest_tss locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.dm6.nearest_tss
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, dm6.

organism A `character` indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:33 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

locusdef.hg19.10kb *locusdef.hg19.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.hg19.10kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:58 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

locusdef.hg19.10kb_outside *locusdef.hg19.10kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.hg19.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:59 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

---

locusdef.hg19.10kb_outside_upstream

locusdef.hg19.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg19.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:58 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

---

locusdef.hg19.1kb *locusdef.hg19.1kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.hg19.1kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg19.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:55 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

locusdef.hg19.1kb_outside

locusdef.hg19.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.hg19.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:56 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

locusdef.hg19.1kb_outside_upstream

locusdef.hg19.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg19.1kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg19.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:56 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

---

`locusdef.hg19.5kb` *locusdef.hg19.5kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.hg19.5kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg19.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:57 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

locusdef.hg19.5kb_outside

locusdef.hg19.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.hg19.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:58 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

locusdef.hg19.5kb_outside_upstream

locusdef.hg19.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg19.5kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg19.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:57 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

---

`locusdef.hg19.exon` *locusdef.hg19.exon locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.hg19.exon
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg19.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:53 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

locusdef.hg19.intron *locusdef.hg19.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.hg19.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:55 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

locusdef.hg19.nearest_gene *locusdef.hg19.nearest_gene locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.hg19.nearest_gene
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:51 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

---

locusdef.hg19.nearest_tss

locusdef.hg19.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.hg19.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:51 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

---

`locusdef.hg38.10kb` *locusdef.hg38.10kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.hg38.10kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:42 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.10kb_outside

locusdef.hg38.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.hg38.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:43 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.10kb_outside_upstream

locusdef.hg38.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg38.10kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:43 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

---

`locusdef.hg38.1kb` *locusdef.hg38.1kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.hg38.1kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:39 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.1kb_outside

locusdef.hg38.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.hg38.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:40 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.1kb_outside_upstream

locusdef.hg38.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg38.1kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:39 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

---

`locusdef.hg38.5kb` *locusdef.hg38.5kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.hg38.5kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:41 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

---

`locusdef.hg38.5kb_outside`
locusdef.hg38.5kb_outside locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.hg38.5kb_outside
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:42 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

---

`locusdef.hg38.5kb_outside_upstream`
locusdef.hg38.5kb_outside_upstream locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg38.5kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:41 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

---

`locusdef.hg38.exon` *locusdef.hg38.exon locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.hg38.exon
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:37 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.intron *locusdef.hg38.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.hg38.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:38 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.nearest_gene *locusdef.hg38.nearest_gene locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.hg38.nearest_gene
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:34 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

---

`locusdef.hg38.nearest_tss` *locusdef.hg38.nearest_tss locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.hg38.nearest_tss
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, hg38.

organism A `character` indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:34 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

---

locusdef.mm10.10kb *locusdef.mm10.10kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.mm10.10kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm10.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:40 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.10kb_outside

locusdef.mm10.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.mm10.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:41 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.10kb_outside_upstream

locusdef.mm10.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm10.10kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm10.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:40 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

---

`locusdef.mm10.1kb` *locusdef.mm10.1kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.mm10.1kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm10.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:37 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.1kb_outside

locusdef.mm10.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.mm10.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:38 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.1kb_outside_upstream

locusdef.mm10.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm10.1kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm10.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:37 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

---

`locusdef.mm10.5kb` *locusdef.mm10.5kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.mm10.5kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm10.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:38 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

`locusdef.mm10.5kb_outside`

locusdef.mm10.5kb_outside locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.mm10.5kb_outside
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm10.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:39 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

---

`locusdef.mm10.5kb_outside_upstream`

locusdef.mm10.5kb_outside_upstream locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm10.5kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm10.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:39 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

---

`locusdef.mm10.exon` *locusdef.mm10.exon locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.mm10.exon
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm10.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:35 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.intron *locusdef.mm10.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.mm10.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:36 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.nearest_gene *locusdef.mm10.nearest_gene locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.mm10.nearest_gene
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:33 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

---

locusdef.mm10.nearest_tss

locusdef.mm10.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.mm10.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:33 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

---

`locusdef.mm9.10kb` *locusdef.mm9.10kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.mm9.10kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm9.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:44 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.10kb_outside

locusdef.mm9.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.mm9.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:44 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.10kb_outside_upstream

locusdef.mm9.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm9.10kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm9.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:44 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

---

`locusdef.mm9.1kb` *locusdef.mm9.1kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.mm9.1kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm9.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:41 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.1kb_outside

locusdef.mm9.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.mm9.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:42 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.1kb_outside_upstream

locusdef.mm9.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm9.1kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm9.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:41 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

---

`locusdef.mm9.5kb` *locusdef.mm9.5kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.mm9.5kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm9.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:42 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.5kb_outside

locusdef.mm9.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.mm9.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:43 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.5kb_outside_upstream

locusdef.mm9.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm9.5kb_outside_upstream
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm9.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:43 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

---

`locusdef.mm9.exon` *locusdef.mm9.exon locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.mm9.exon
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, mm9.

organism A `character` indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:39 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.intron *locusdef.mm9.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.mm9.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:41 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.nearest_gene *locusdef.mm9.nearest_gene locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.mm9.nearest_gene
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:37 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

---

locusdef.mm9.nearest_tss

locusdef.mm9.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.mm9.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:37 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

---

locusdef.rn4.10kb *locusdef.rn4.10kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.rn4.10kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, rn4.

organism A `character` indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:02 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

`locusdef.rn4.10kb_outside`

locusdef.rn4.10kb_outside locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn4.10kb_outside
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, rn4.

organism A `character` indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:03 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

`locusdef.rn4.10kb_outside_upstream`

locusdef.rn4.10kb_outside_upstream locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn4.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:02 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn4.1kb *locusdef.rn4.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.rn4.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:01 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.1kb_outside

locusdef.rn4.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn4.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:01 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.1kb_outside_upstream

locusdef.rn4.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn4.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:01 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn4.5kb *locusdef.rn4.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.rn4.5kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:01 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

`locusdef.rn4.5kb_outside`

locusdef.rn4.5kb_outside locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn4.5kb_outside
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, rn4.

organism A `character` indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:02 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

`locusdef.rn4.5kb_outside_upstream`

locusdef.rn4.5kb_outside_upstream locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn4.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:02 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn4.exon *locusdef.rn4.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.rn4.exon
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:51:59 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.intron *locusdef.rn4.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.rn4.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:00 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.nearest_gene *locusdef.rn4.nearest_gene locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.rn4.nearest_gene
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:51:58 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn4.nearest_tss

locusdef.rn4.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.rn4.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:51:58 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn5.10kb *locusdef.rn5.10kb locus definition*

Description

A `LocusDefinition` where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.rn5.10kb
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, rn5.

organism A `character` indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:20 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn5.10kb_outside *locusdef.rn5.10kb_outside locus definition*

Description

A `LocusDefinition` where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn5.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:21 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn5.10kb_outside_upstream

locusdef.rn5.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn5.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:21 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.1kb *locusdef.rn5.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.rn5.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:19 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.1kb_outside *locusdef.rn5.1kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn5.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:19 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn5.1kb_outside_upstream

locusdef.rn5.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn5.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:19 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.5kb *locusdef.rn5.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.rn5.5kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:20 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.5kb_outside *locusdef.rn5.5kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn5.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:20 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

---

locusdef.rn5.5kb_outside_upstream

locusdef.rn5.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn5.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:20 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.exon *locusdef.rn5.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.rn5.exon
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:17 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.intron *locusdef.rn5.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.rn5.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:19 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

`locusdef.rn5.nearest_gene`
locusdef.rn5.nearest_gene locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.rn5.nearest_gene
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, rn5.

organism A `character` indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:16 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.nearest_tss *locusdef.rn5.nearest_tss locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.rn5.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:16 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn6.10kb *locusdef.rn6.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.rn6.10kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:39 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

---

locusdef.rn6.10kb_outside

locusdef.rn6.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn6.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:40 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.10kb_outside_upstream *locusdef.rn6.10kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn6.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:39 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.1kb *locusdef.rn6.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.rn6.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:38 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

---

locusdef.rn6.1kb_outside

locusdef.rn6.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn6.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:38 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.1kb_outside_upstream *locusdef.rn6.1kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn6.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:38 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.5kb *locusdef.rn6.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.rn6.5kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:38 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

---

locusdef.rn6.5kb_outside

locusdef.rn6.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn6.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:39 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.5kb_outside_upstream *locusdef.rn6.5kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn6.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:39 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.exon *locusdef.rn6.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.rn6.exon
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:36 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

---

locusdef.rn6.intron *locusdef.rn6.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.rn6.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:37 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.nearest_gene

locusdef.rn6.nearest_gene locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.rn6.nearest_gene
```

Format

A `LocusDefinition` object with the following slots:

granges A `GRanges` of the locus definitions with `mcols` for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A `data.frame` of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A `character` indicating the genome build. In this case, rn6.

organism A `character` indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:35 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.nearest_tss

locusdef.rn6.nearest_tss locus definition

Description

A `LocusDefinition` where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.rn6.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:34 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

LocusDefinition-class *Class* "LocusDefinition"

Description

A storage class representing gene locus definitions and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form new("LocusDefinition"). These objects are used internally by the chipenrich package and users will not likely need to create these.

Slots

dframe: Object of class "data.frame". Each row represents a locus for a particular geneid.

granges: Object of class "GenomicRanges". Locus definitions stored as a GenomicRanges object.

genome.build: Object of class "character". Genome build these definitions were generated from.

organism: Object of class "character". Organism code.

Note

Not typically accessed by the user - this is used internally by the chipenrich package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
# Show info about the class.
showClass("LocusDefinition");

# Example of what a locus definition object looks like.
data(locusdef.mm9.nearest_tss)
lapply(attributes(locusdef.mm9.nearest_tss), head)
```

---

mappa.hg19.10kb.100mer

mappa.hg19.10kb.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.10kb.24mer *mappa.hg19.10kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.10kb.36mer *mappa.hg19.10kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.10kb.40mer` *mappa.hg19.10kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.10kb.50mer` *mappa.hg19.10kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.10kb.75mer` *mappa.hg19.10kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.1kb.100mer` *mappa.hg19.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.1kb.24mer` *mappa.hg19.1kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.24mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.1kb.36mer` *mappa.hg19.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.1kb.40mer` *mappa.hg19.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.1kb.50mer` *mappa.hg19.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.1kb.75mer` *mappa.hg19.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.5kb.100mer` *mappa.hg19.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.hg19.5kb.24mer *mappa.hg19.5kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.5kb.36mer *mappa.hg19.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.5kb.40mer` *mappa.hg19.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.hg19.5kb.50mer *mappa.hg19.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.5kb.75mer *mappa.hg19.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.exon.100mer`

mappa.hg19.exon.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.hg19.exon.24mer *mappa.hg19.exon.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.exon.36mer *mappa.hg19.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.exon.40mer` *mappa.hg19.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.exon.50mer` *mappa.hg19.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.exon.75mer` *mappa.hg19.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.intron.100mer`

mappa.hg19.intron.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.intron.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.hg19.intron.24mer

mappa.hg19.intron.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

mappa.hg19.intron.36mer

mappa.hg19.intron.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.hg19.intron.40mer`

mappa.hg19.intron.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.intron.50mer *mappa.hg19.intron.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.intron.75mer *mappa.hg19.intron.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.hg19.nearest_gene.100mer`

mappa.hg19.nearest_gene.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.nearest_gene.24mer
mappa.hg19.nearest_gene.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.nearest_gene.36mer
mappa.hg19.nearest_gene.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.hg19.nearest_gene.40mer`

mappa.hg19.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.nearest_gene.50mer *mappa.hg19.nearest_gene.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.nearest_gene.75mer *mappa.hg19.nearest_gene.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.hg19.nearest_tss.100mer`

mappa.hg19.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_tss.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.hg19.nearest_tss.24mer *mappa.hg19.nearest_tss.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.nearest_tss.36mer *mappa.hg19.nearest_tss.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.hg19.nearest_tss.40mer`
mappa.hg19.nearest_tss.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.nearest_tss.50mer *mappa.hg19.nearest_tss.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.hg19.nearest_tss.75mer *mappa.hg19.nearest_tss.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.10kb.100mer` *mappa.mm9.10kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.mm9.10kb.36mer *mappa.mm9.10kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.10kb.40mer *mappa.mm9.10kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.10kb.50mer` *mappa.mm9.10kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.mm9.10kb.75mer *mappa.mm9.10kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.1kb.100mer *mappa.mm9.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.mm9.1kb.36mer` *mappa.mm9.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

`mappa.mm9.1kb.40mer` *mappa.mm9.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.1kb.50mer` *mappa.mm9.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.1kb.75mer` *mappa.mm9.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.mm9.5kb.100mer *mappa.mm9.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.5kb.36mer *mappa.mm9.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.5kb.40mer` *mappa.mm9.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.5kb.50mer` *mappa.mm9.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.5kb.75mer` *mappa.mm9.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.exon.100mer` *mappa.mm9.exon.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.exon.36mer` *mappa.mm9.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.exon.40mer` *mappa.mm9.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.mm9.exon.50mer` *mappa.mm9.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.exon.75mer *mappa.mm9.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.intron.100mer *mappa.mm9.intron.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

`mappa.mm9.intron.36mer`

mappa.mm9.intron.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.intron.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: `chipenrich.data`

mappa.mm9.intron.40mer

mappa.mm9.intron.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

mappa.mm9.intron.50mer

mappa.mm9.intron.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.mm9.intron.75mer`

mappa.mm9.intron.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.nearest_gene.100mer *mappa.mm9.nearest_gene.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.nearest_gene.36mer *mappa.mm9.nearest_gene.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.mm9.nearest_gene.40mer`
mappa.mm9.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_gene.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.nearest_gene.50mer *mappa.mm9.nearest_gene.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.nearest_gene.75mer *mappa.mm9.nearest_gene.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.mm9.nearest_tss.100mer`

mappa.mm9.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_tss.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.nearest_tss.36mer *mappa.mm9.nearest_tss.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.nearest_tss.40mer *mappa.mm9.nearest_tss.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

---

`mappa.mm9.nearest_tss.50mer`

mappa.mm9.nearest_tss.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

mappa.mm9.nearest_tss.75mer *mappa.mm9.nearest_tss.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: chipenrich.data

peaks_E2F4 *ChIP-seq Peaks for the E2F4 Transcription Factor*

Description

A dataset containing the binding locations (peaks) of the transcription factor E2F4 called from a ChIP-seq experiment

Usage

```
peaks_E2F4
```

Format

A data frame containing 16,245 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found in the following publication:

Lee, B. K., A. A. Bhinge, et al. (2011). "Wide-ranging functions of E2F4 in transcriptional activation and repression revealed by genome-wide analysis." Nucleic Acids Res 39(9): 3558-3573.

Examples

```
# Load E2F4 peak data.
data(peaks_E2F4)

# Print the first 10 peaks in the dataset.
print(head(peaks_E2F4))
```

---

peaks_H3K4me3_GM12878 *ChIP-seq Peaks for the Histone Modification H3K4me3 in GM12878*

Description

A dataset containing the binding locations (peaks) of the histone modification H3K4me3 called from a ChIP-seq experiment in the GM12878 cell line

Usage

```
peaks_H3K4me3_GM12878
```

Format

A data frame containing 57,476 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found at the following ENCODE URL:

http://hgdownload.cse.ucsc.edu/goldenPath/hg19/encodeDCC/wgEncodeBroadHistone/wgEncodeBroadHistoneGm128

Examples

```
# Load H3K4me3 in GM12878 peak data.
data(peaks_H3K4me3_GM12878)

# Print the first 10 peaks in the dataset.
print(head(peaks_H3K4me3_GM12878))
```

spline.log_dtss.90ENCODE *DTSS Spline adjustment*

Description

A mgcv::gam object on a combined data of 90 ENCODE ChIP-seq datasets that modeled the relationship between a gene's locus length the distance from a peak to the gene's transcription start site, using a cubic spline. This is used to adjust for the proximity to TSSes test.

Usage

```
spline.log_dtss.90ENCODE
```

Format

An object of class `gam` (inherits from `glm`, `lm`) of length 46.

tss.danRer10 *tss.danRer10 TSS locations*

Description

A `GRanges` with all the TSSs for danRer10. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.danRer10
```

Format

A `GRanges` object with the following `mcols`:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

tss.dm3 *tss.dm3 TSS locations*

Description

A GRanges with all the TSSs for dm3. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.dm3
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

tss.dm6 *tss.dm6 TSS locations*

Description

A GRanges with all the TSSs for dm6. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.dm6
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

tss.hg19 *tss.hg19 TSS locations*

Description

A GRanges with all the TSSs for hg19. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.hg19
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota
and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entr

tss.hg38 *tss.hg38 TSS locations*

Description

A GRanges with all the TSSs for hg38. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.hg38
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz
and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

tss.mm10 *tss.mm10 TSS locations*

Description

A GRanges with all the TSSs for mm10. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.mm10
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

tss.mm9 *tss.mm9 TSS locations*

Description

A GRanges with all the TSSs for mm9. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.mm9
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

tss.rn4 *tss.rn4 TSS locations*

Description

A GRanges with all the TSSs for rn4. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.rn4
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

tss.rn5 *tss.rn5 TSS locations*

Description

A GRanges with all the TSSs for rn5. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.rn5
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

tss.rn6 *tss.rn6 TSS locations*

Description

A GRanges with all the TSSs for rn6. Primarily used in the assign_peaks() function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.rn6
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

Index

∗ **classes**
GeneSet-class, 8
LocusDefinition-class, 129
∗ **datasets**
enhancer.dnase_thurman.0, 7
gene.enh.desc, 8
geneset.biocarta_pathway.hsa, 9
geneset.biocarta_pathway.mmu, 10
geneset.biocarta_pathway.rno, 10
geneset.ctd.hsa, 11
geneset.ctd.mmu, 11
geneset.cytoband.hsa, 12
geneset.drug_bank.hsa, 13
geneset.drug_bank.mmu, 13
geneset.drug_bank.rno, 14
geneset.GOBP.dme, 14
geneset.GOBP.dre, 15
geneset.GOBP.hsa, 15
geneset.GOBP.mmu, 16
geneset.GOBP.rno, 17
geneset.GOCC.dme, 17
geneset.GOCC.dre, 18
geneset.GOCC.hsa, 19
geneset.GOCC.mmu, 19
geneset.GOCC.rno, 20
geneset.GOMF.dme, 21
geneset.GOMF.dre, 21
geneset.GOMF.hsa, 22
geneset.GOMF.mmu, 23
geneset.GOMF.rno, 23
geneset.hallmark.hsa, 24
geneset.immunologic.hsa, 25
geneset.kegg_pathway.hsa, 25
geneset.kegg_pathway.mmu, 26
geneset.kegg_pathway.rno, 27
geneset.mesh.hsa, 27
geneset.mesh.mmu, 28
geneset.mesh.rno, 28
geneset.metabolite.hsa, 29
geneset.metabolite.mmu, 29
geneset.metabolite.rno, 30
geneset.microrna.hsa, 30
geneset.oncogenic.hsa, 31
geneset.panther_pathway.hsa, 31
geneset.panther_pathway.mmu, 32
geneset.panther_pathway.rno, 32
geneset.pfam.hsa, 33
geneset.pfam.mmu, 33
geneset.pfam.rno, 34
geneset.protein_interaction_biogrid.hsa, 34
geneset.reactome.dme, 35
geneset.reactome.dre, 35
geneset.reactome.hsa, 36
geneset.reactome.mmu, 37
geneset.reactome.rno, 37
geneset.transcription_factors.hsa, 38
geneset.transcription_factors.mmu, 39
geneset.transcription_factors.rno, 39
locusdef.danRer10.10kb, 40
locusdef.danRer10.10kb_outside, 40
locusdef.danRer10.10kb_outside_upstream, 41
locusdef.danRer10.1kb, 42
locusdef.danRer10.1kb_outside, 42
locusdef.danRer10.1kb_outside_upstream, 43
locusdef.danRer10.5kb, 44
locusdef.danRer10.5kb_outside, 44
locusdef.danRer10.5kb_outside_upstream, 45
locusdef.danRer10.exon, 46
locusdef.danRer10.intron, 46
locusdef.danRer10.nearest_gene, 47
locusdef.danRer10.nearest_tss, 48
locusdef.dm3.10kb, 48
locusdef.dm3.10kb_outside, 49
locusdef.dm3.10kb_outside_upstream, 50
locusdef.dm3.1kb, 51
locusdef.dm3.1kb_outside, 51
locusdef.dm3.1kb_outside_upstream, 52

locusdef.dm3.5kb, 53
locusdef.dm3.5kb_outside, 53
locusdef.dm3.5kb_outside_upstream, 54
locusdef.dm3.exon, 55
locusdef.dm3.intron, 55
locusdef.dm3.nearest_gene, 56
locusdef.dm3.nearest_tss, 57
locusdef.dm6.10kb, 58
locusdef.dm6.10kb_outside, 58
locusdef.dm6.10kb_outside_upstream, 59
locusdef.dm6.1kb, 60
locusdef.dm6.1kb_outside, 60
locusdef.dm6.1kb_outside_upstream, 61
locusdef.dm6.5kb, 62
locusdef.dm6.5kb_outside, 62
locusdef.dm6.5kb_outside_upstream, 63
locusdef.dm6.exon, 64
locusdef.dm6.intron, 64
locusdef.dm6.nearest_gene, 65
locusdef.dm6.nearest_tss, 66
locusdef.hg19.10kb, 67
locusdef.hg19.10kb_outside, 67
locusdef.hg19.10kb_outside_upstream, 68
locusdef.hg19.1kb, 69
locusdef.hg19.1kb_outside, 70
locusdef.hg19.1kb_outside_upstream, 70
locusdef.hg19.5kb, 71
locusdef.hg19.5kb_outside, 72
locusdef.hg19.5kb_outside_upstream, 72
locusdef.hg19.exon, 73
locusdef.hg19.intron, 74
locusdef.hg19.nearest_gene, 74
locusdef.hg19.nearest_tss, 75
locusdef.hg38.10kb, 76
locusdef.hg38.10kb_outside, 77
locusdef.hg38.10kb_outside_upstream, 77
locusdef.hg38.1kb, 78
locusdef.hg38.1kb_outside, 79
locusdef.hg38.1kb_outside_upstream, 79
locusdef.hg38.5kb, 80
locusdef.hg38.5kb_outside, 81
locusdef.hg38.5kb_outside_upstream, 81
locusdef.hg38.exon, 82
locusdef.hg38.intron, 83
locusdef.hg38.nearest_gene, 83
locusdef.hg38.nearest_tss, 84
locusdef.mm10.10kb, 85
locusdef.mm10.10kb_outside, 86
locusdef.mm10.10kb_outside_upstream, 86
locusdef.mm10.1kb, 87
locusdef.mm10.1kb_outside, 88
locusdef.mm10.1kb_outside_upstream, 88
locusdef.mm10.5kb, 89
locusdef.mm10.5kb_outside, 90
locusdef.mm10.5kb_outside_upstream, 90
locusdef.mm10.exon, 91
locusdef.mm10.intron, 92
locusdef.mm10.nearest_gene, 92
locusdef.mm10.nearest_tss, 93
locusdef.mm9.10kb, 94
locusdef.mm9.10kb_outside, 95
locusdef.mm9.10kb_outside_upstream, 95
locusdef.mm9.1kb, 96
locusdef.mm9.1kb_outside, 97
locusdef.mm9.1kb_outside_upstream, 97
locusdef.mm9.5kb, 98
locusdef.mm9.5kb_outside, 99
locusdef.mm9.5kb_outside_upstream, 99
locusdef.mm9.exon, 100
locusdef.mm9.intron, 101
locusdef.mm9.nearest_gene, 101
locusdef.mm9.nearest_tss, 102
locusdef.rn4.10kb, 103
locusdef.rn4.10kb_outside, 104
locusdef.rn4.10kb_outside_upstream, 104
locusdef.rn4.1kb, 105
locusdef.rn4.1kb_outside, 106
locusdef.rn4.1kb_outside_upstream, 106
locusdef.rn4.5kb, 107
locusdef.rn4.5kb_outside, 108
locusdef.rn4.5kb_outside_upstream, 108
locusdef.rn4.exon, 109
locusdef.rn4.intron, 110
locusdef.rn4.nearest_gene, 110
locusdef.rn4.nearest_tss, 111

locusdef.rn5.10kb, 112
locusdef.rn5.10kb_outside, 112
locusdef.rn5.10kb_outside_upstream, 113
locusdef.rn5.1kb, 114
locusdef.rn5.1kb_outside, 114
locusdef.rn5.1kb_outside_upstream, 115
locusdef.rn5.5kb, 116
locusdef.rn5.5kb_outside, 116
locusdef.rn5.5kb_outside_upstream, 117
locusdef.rn5.exon, 118
locusdef.rn5.intron, 118
locusdef.rn5.nearest_gene, 119
locusdef.rn5.nearest_tss, 120
locusdef.rn6.10kb, 120
locusdef.rn6.10kb_outside, 121
locusdef.rn6.10kb_outside_upstream, 122
locusdef.rn6.1kb, 122
locusdef.rn6.1kb_outside, 123
locusdef.rn6.1kb_outside_upstream, 124
locusdef.rn6.5kb, 124
locusdef.rn6.5kb_outside, 125
locusdef.rn6.5kb_outside_upstream, 126
locusdef.rn6.exon, 126
locusdef.rn6.intron, 127
locusdef.rn6.nearest_gene, 128
locusdef.rn6.nearest_tss, 128
mappa.hg19.10kb.100mer, 130
mappa.hg19.10kb.24mer, 131
mappa.hg19.10kb.36mer, 131
mappa.hg19.10kb.40mer, 132
mappa.hg19.10kb.50mer, 133
mappa.hg19.10kb.75mer, 133
mappa.hg19.1kb.100mer, 134
mappa.hg19.1kb.24mer, 135
mappa.hg19.1kb.36mer, 135
mappa.hg19.1kb.40mer, 136
mappa.hg19.1kb.50mer, 137
mappa.hg19.1kb.75mer, 137
mappa.hg19.5kb.100mer, 138
mappa.hg19.5kb.24mer, 139
mappa.hg19.5kb.36mer, 139
mappa.hg19.5kb.40mer, 140
mappa.hg19.5kb.50mer, 141
mappa.hg19.5kb.75mer, 141
mappa.hg19.exon.100mer, 142
mappa.hg19.exon.24mer, 143
mappa.hg19.exon.36mer, 143
mappa.hg19.exon.40mer, 144
mappa.hg19.exon.50mer, 145
mappa.hg19.exon.75mer, 145
mappa.hg19.intron.100mer, 146
mappa.hg19.intron.24mer, 147
mappa.hg19.intron.36mer, 147
mappa.hg19.intron.40mer, 148
mappa.hg19.intron.50mer, 149
mappa.hg19.intron.75mer, 149
mappa.hg19.nearest_gene.100mer, 150
mappa.hg19.nearest_gene.24mer, 151
mappa.hg19.nearest_gene.36mer, 151
mappa.hg19.nearest_gene.40mer, 152
mappa.hg19.nearest_gene.50mer, 153
mappa.hg19.nearest_gene.75mer, 153
mappa.hg19.nearest_tss.100mer, 154
mappa.hg19.nearest_tss.24mer, 155
mappa.hg19.nearest_tss.36mer, 155
mappa.hg19.nearest_tss.40mer, 156
mappa.hg19.nearest_tss.50mer, 157
mappa.hg19.nearest_tss.75mer, 157
mappa.mm9.10kb.100mer, 158
mappa.mm9.10kb.36mer, 159
mappa.mm9.10kb.40mer, 159
mappa.mm9.10kb.50mer, 160
mappa.mm9.10kb.75mer, 161
mappa.mm9.1kb.100mer, 161
mappa.mm9.1kb.36mer, 162
mappa.mm9.1kb.40mer, 163
mappa.mm9.1kb.50mer, 163
mappa.mm9.1kb.75mer, 164
mappa.mm9.5kb.100mer, 165
mappa.mm9.5kb.36mer, 165
mappa.mm9.5kb.40mer, 166
mappa.mm9.5kb.50mer, 167
mappa.mm9.5kb.75mer, 167
mappa.mm9.exon.100mer, 168
mappa.mm9.exon.36mer, 169
mappa.mm9.exon.40mer, 169
mappa.mm9.exon.50mer, 170
mappa.mm9.exon.75mer, 171
mappa.mm9.intron.100mer, 171
mappa.mm9.intron.36mer, 172
mappa.mm9.intron.40mer, 173
mappa.mm9.intron.50mer, 173
mappa.mm9.intron.75mer, 174
mappa.mm9.nearest_gene.100mer, 175
mappa.mm9.nearest_gene.36mer, 175
mappa.mm9.nearest_gene.40mer, 176
mappa.mm9.nearest_gene.50mer, 177

mappa.mm9.nearest_gene.75mer, 177
mappa.mm9.nearest_tss.100mer, 178
mappa.mm9.nearest_tss.36mer, 179
mappa.mm9.nearest_tss.40mer, 179
mappa.mm9.nearest_tss.50mer, 180
mappa.mm9.nearest_tss.75mer, 181
peaks_E2F4, 181
peaks_H3K4me3_GM12878, 182
spline.log_dtss.90ENCODE, 183
tss.danRer10, 183
tss.dm3, 184
tss.dm6, 184
tss.hg19, 185
tss.hg38, 185
tss.mm10, 186
tss.mm9, 186
tss.rn4, 187
tss.rn5, 187
tss.rn6, 188

chipenrich.data, 7, *10*, *12–14*, *26–34*, *39*, *130–181*
chipenrich.data-package (chipenrich.data), 7

enhancer.dnase_thurman.0, 7

gene.enh.desc, 8
GeneSet-class, 8
geneset.biocarta_pathway.hsa, 9
geneset.biocarta_pathway.mmu, 10
geneset.biocarta_pathway.rno, 10
geneset.ctd.hsa, 11
geneset.ctd.mmu, 11
geneset.cytoband.hsa, 12
geneset.drug_bank.hsa, 13
geneset.drug_bank.mmu, 13
geneset.drug_bank.rno, 14
geneset.GOBP.dme, 14
geneset.GOBP.dre, 15
geneset.GOBP.hsa, 15
geneset.GOBP.mmu, 16
geneset.GOBP.rno, 17
geneset.GOCC.dme, 17
geneset.GOCC.dre, 18
geneset.GOCC.hsa, 19
geneset.GOCC.mmu, 19
geneset.GOCC.rno, 20
geneset.GOMF.dme, 21
geneset.GOMF.dre, 21
geneset.GOMF.hsa, 22
geneset.GOMF.mmu, 23
geneset.GOMF.rno, 23
geneset.hallmark.hsa, 24
geneset.immunologic.hsa, 25
geneset.kegg_pathway.hsa, 25
geneset.kegg_pathway.mmu, 26
geneset.kegg_pathway.rno, 27
geneset.mesh.hsa, 27
geneset.mesh.mmu, 28
geneset.mesh.rno, 28
geneset.metabolite.hsa, 29
geneset.metabolite.mmu, 29
geneset.metabolite.rno, 30
geneset.microrna.hsa, 30
geneset.oncogenic.hsa, 31
geneset.panther_pathway.hsa, 31
geneset.panther_pathway.mmu, 32
geneset.panther_pathway.rno, 32
geneset.pfam.hsa, 33
geneset.pfam.mmu, 33
geneset.pfam.rno, 34
geneset.protein_interaction_biogrid.hsa, 34
geneset.reactome.dme, 35
geneset.reactome.dre, 35
geneset.reactome.hsa, 36
geneset.reactome.mmu, 37
geneset.reactome.rno, 37
geneset.transcription_factors.hsa, 38
geneset.transcription_factors.mmu, 39
geneset.transcription_factors.rno, 39

locusdef.danRer10.10kb, 40
locusdef.danRer10.10kb_outside, 40
locusdef.danRer10.10kb_outside_upstream, 41
locusdef.danRer10.1kb, 42
locusdef.danRer10.1kb_outside, 42
locusdef.danRer10.1kb_outside_upstream, 43
locusdef.danRer10.5kb, 44
locusdef.danRer10.5kb_outside, 44
locusdef.danRer10.5kb_outside_upstream, 45
locusdef.danRer10.exon, 46
locusdef.danRer10.intron, 46
locusdef.danRer10.nearest_gene, 47
locusdef.danRer10.nearest_tss, 48
locusdef.dm3.10kb, 48
locusdef.dm3.10kb_outside, 49
locusdef.dm3.10kb_outside_upstream, 50
locusdef.dm3.1kb, 51
locusdef.dm3.1kb_outside, 51
locusdef.dm3.1kb_outside_upstream, 52
locusdef.dm3.5kb, 53

locusdef.dm3.5kb_outside, 53
locusdef.dm3.5kb_outside_upstream, 54
locusdef.dm3.exon, 55
locusdef.dm3.intron, 55
locusdef.dm3.nearest_gene, 56
locusdef.dm3.nearest_tss, 57
locusdef.dm6.10kb, 58
locusdef.dm6.10kb_outside, 58
locusdef.dm6.10kb_outside_upstream, 59
locusdef.dm6.1kb, 60
locusdef.dm6.1kb_outside, 60
locusdef.dm6.1kb_outside_upstream, 61
locusdef.dm6.5kb, 62
locusdef.dm6.5kb_outside, 62
locusdef.dm6.5kb_outside_upstream, 63
locusdef.dm6.exon, 64
locusdef.dm6.intron, 64
locusdef.dm6.nearest_gene, 65
locusdef.dm6.nearest_tss, 66
locusdef.hg19.10kb, 67
locusdef.hg19.10kb_outside, 67
locusdef.hg19.10kb_outside_upstream, 68
locusdef.hg19.1kb, 69
locusdef.hg19.1kb_outside, 70
locusdef.hg19.1kb_outside_upstream, 70
locusdef.hg19.5kb, 71
locusdef.hg19.5kb_outside, 72
locusdef.hg19.5kb_outside_upstream, 72
locusdef.hg19.exon, 73
locusdef.hg19.intron, 74
locusdef.hg19.nearest_gene, 74
locusdef.hg19.nearest_tss, 75
locusdef.hg38.10kb, 76
locusdef.hg38.10kb_outside, 77
locusdef.hg38.10kb_outside_upstream, 77
locusdef.hg38.1kb, 78
locusdef.hg38.1kb_outside, 79
locusdef.hg38.1kb_outside_upstream, 79
locusdef.hg38.5kb, 80
locusdef.hg38.5kb_outside, 81
locusdef.hg38.5kb_outside_upstream, 81
locusdef.hg38.exon, 82
locusdef.hg38.intron, 83
locusdef.hg38.nearest_gene, 83
locusdef.hg38.nearest_tss, 84
locusdef.mm10.10kb, 85
locusdef.mm10.10kb_outside, 86
locusdef.mm10.10kb_outside_upstream, 86
locusdef.mm10.1kb, 87
locusdef.mm10.1kb_outside, 88
locusdef.mm10.1kb_outside_upstream, 88
locusdef.mm10.5kb, 89
locusdef.mm10.5kb_outside, 90
locusdef.mm10.5kb_outside_upstream, 90
locusdef.mm10.exon, 91
locusdef.mm10.intron, 92
locusdef.mm10.nearest_gene, 92
locusdef.mm10.nearest_tss, 93
locusdef.mm9.10kb, 94
locusdef.mm9.10kb_outside, 95
locusdef.mm9.10kb_outside_upstream, 95
locusdef.mm9.1kb, 96
locusdef.mm9.1kb_outside, 97
locusdef.mm9.1kb_outside_upstream, 97
locusdef.mm9.5kb, 98
locusdef.mm9.5kb_outside, 99
locusdef.mm9.5kb_outside_upstream, 99
locusdef.mm9.exon, 100
locusdef.mm9.intron, 101
locusdef.mm9.nearest_gene, 101
locusdef.mm9.nearest_tss, 102
locusdef.rn4.10kb, 103
locusdef.rn4.10kb_outside, 104
locusdef.rn4.10kb_outside_upstream, 104
locusdef.rn4.1kb, 105
locusdef.rn4.1kb_outside, 106
locusdef.rn4.1kb_outside_upstream, 106
locusdef.rn4.5kb, 107
locusdef.rn4.5kb_outside, 108
locusdef.rn4.5kb_outside_upstream, 108
locusdef.rn4.exon, 109
locusdef.rn4.intron, 110
locusdef.rn4.nearest_gene, 110
locusdef.rn4.nearest_tss, 111
locusdef.rn5.10kb, 112
locusdef.rn5.10kb_outside, 112
locusdef.rn5.10kb_outside_upstream, 113
locusdef.rn5.1kb, 114
locusdef.rn5.1kb_outside, 114
locusdef.rn5.1kb_outside_upstream, 115
locusdef.rn5.5kb, 116
locusdef.rn5.5kb_outside, 116
locusdef.rn5.5kb_outside_upstream, 117
locusdef.rn5.exon, 118
locusdef.rn5.intron, 118
locusdef.rn5.nearest_gene, 119
locusdef.rn5.nearest_tss, 120
locusdef.rn6.10kb, 120
locusdef.rn6.10kb_outside, 121

locusdef.rn6.10kb_outside_upstream, 122
locusdef.rn6.1kb, 122
locusdef.rn6.1kb_outside, 123
locusdef.rn6.1kb_outside_upstream, 124
locusdef.rn6.5kb, 124
locusdef.rn6.5kb_outside, 125
locusdef.rn6.5kb_outside_upstream, 126
locusdef.rn6.exon, 126
locusdef.rn6.intron, 127
locusdef.rn6.nearest_gene, 128
locusdef.rn6.nearest_tss, 128
LocusDefinition-class, 129

mappa.hg19.10kb.100mer, 130
mappa.hg19.10kb.24mer, 131
mappa.hg19.10kb.36mer, 131
mappa.hg19.10kb.40mer, 132
mappa.hg19.10kb.50mer, 133
mappa.hg19.10kb.75mer, 133
mappa.hg19.1kb.100mer, 134
mappa.hg19.1kb.24mer, 135
mappa.hg19.1kb.36mer, 135
mappa.hg19.1kb.40mer, 136
mappa.hg19.1kb.50mer, 137
mappa.hg19.1kb.75mer, 137
mappa.hg19.5kb.100mer, 138
mappa.hg19.5kb.24mer, 139
mappa.hg19.5kb.36mer, 139
mappa.hg19.5kb.40mer, 140
mappa.hg19.5kb.50mer, 141
mappa.hg19.5kb.75mer, 141
mappa.hg19.exon.100mer, 142
mappa.hg19.exon.24mer, 143
mappa.hg19.exon.36mer, 143
mappa.hg19.exon.40mer, 144
mappa.hg19.exon.50mer, 145
mappa.hg19.exon.75mer, 145
mappa.hg19.intron.100mer, 146
mappa.hg19.intron.24mer, 147
mappa.hg19.intron.36mer, 147
mappa.hg19.intron.40mer, 148
mappa.hg19.intron.50mer, 149
mappa.hg19.intron.75mer, 149
mappa.hg19.nearest_gene.100mer, 150
mappa.hg19.nearest_gene.24mer, 151
mappa.hg19.nearest_gene.36mer, 151
mappa.hg19.nearest_gene.40mer, 152
mappa.hg19.nearest_gene.50mer, 153
mappa.hg19.nearest_gene.75mer, 153
mappa.hg19.nearest_tss.100mer, 154
mappa.hg19.nearest_tss.24mer, 155
mappa.hg19.nearest_tss.36mer, 155
mappa.hg19.nearest_tss.40mer, 156
mappa.hg19.nearest_tss.50mer, 157
mappa.hg19.nearest_tss.75mer, 157
mappa.mm9.10kb.100mer, 158
mappa.mm9.10kb.36mer, 159
mappa.mm9.10kb.40mer, 159
mappa.mm9.10kb.50mer, 160
mappa.mm9.10kb.75mer, 161
mappa.mm9.1kb.100mer, 161
mappa.mm9.1kb.36mer, 162
mappa.mm9.1kb.40mer, 163
mappa.mm9.1kb.50mer, 163
mappa.mm9.1kb.75mer, 164
mappa.mm9.5kb.100mer, 165
mappa.mm9.5kb.36mer, 165
mappa.mm9.5kb.40mer, 166
mappa.mm9.5kb.50mer, 167
mappa.mm9.5kb.75mer, 167
mappa.mm9.exon.100mer, 168
mappa.mm9.exon.36mer, 169
mappa.mm9.exon.40mer, 169
mappa.mm9.exon.50mer, 170
mappa.mm9.exon.75mer, 171
mappa.mm9.intron.100mer, 171
mappa.mm9.intron.36mer, 172
mappa.mm9.intron.40mer, 173
mappa.mm9.intron.50mer, 173
mappa.mm9.intron.75mer, 174
mappa.mm9.nearest_gene.100mer, 175
mappa.mm9.nearest_gene.36mer, 175
mappa.mm9.nearest_gene.40mer, 176
mappa.mm9.nearest_gene.50mer, 177
mappa.mm9.nearest_gene.75mer, 177
mappa.mm9.nearest_tss.100mer, 178
mappa.mm9.nearest_tss.36mer, 179
mappa.mm9.nearest_tss.40mer, 179
mappa.mm9.nearest_tss.50mer, 180
mappa.mm9.nearest_tss.75mer, 181

peaks_E2F4, 181
peaks_H3K4me3_GM12878, 182

spline.log_dtss.90ENCODE, 183

tss.danRer10, 183
tss.dm3, 184
tss.dm6, 184
tss.hg19, 185
tss.hg38, 185
tss.mm10, 186
tss.mm9, 186
tss.rn4, 187
tss.rn5, 187
tss.rn6, 188