

# Package ‘spillR’

March 31, 2025

**Type** Package

**Title** Spillover Compensation in Mass Cytometry Data

**Version** 1.3.0

**Description** Channel interference in mass cytometry can cause spillover and may result in miscounting of protein markers. We develop a nonparametric finite mixture model and use the mixture components to estimate the probability of spillover. We implement our method using expectation-maximization to fit the mixture model.

**biocViews** FlowCytometry, ImmunoOncology, MassSpectrometry, Preprocessing, SingleCell, Software, StatisticalMethod, Visualization, Regression

**License** LGPL-3

**Encoding** UTF-8

**LazyData** false

**Config/testthat/edition** 3

**RoxygenNote** 7.3.1

**Imports** dplyr, tibble, tidyselect, stats, ggplot2, tidyr, spatstat.univar, S4Vectors, parallel

**Depends** R (>= 4.3.0), SummarizedExperiment, CATALYST

**Suggests** knitr, rmarkdown, cowplot, testthat (>= 3.0.0), BiocStyle, hexbin

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/spillR>

**git\_branch** devel

**git\_last\_commit** 7a34e97

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.21

**Date/Publication** 2025-03-30

**Author** Marco Guazzini [aut, cre] (ORCID: <https://orcid.org/0009-0007-8111-5772>),  
 Alexander G. Reisach [aut] (ORCID: <https://orcid.org/0009-0003-5057-6278>),  
 Sebastian Weichwald [aut] (ORCID: <https://orcid.org/0000-0003-0169-7244>),  
 Christof Seiler [aut] (ORCID: <https://orcid.org/0000-0001-8802-3642>)

**Maintainer** Marco Guazzini <m.guazzini@student.maastrichtuniversity.nl>

## Contents

compCytof . . . . .	2
compensate . . . . .	3
compensate_naive . . . . .	4
generate_bead . . . . .	5
generate_real . . . . .	6
plotDiagnostics . . . . .	6
tfm . . . . .	7

<b>Index</b>	<b>8</b>
--------------	----------

---

compCytof	<i>Compute spillover probability and correct for spillover</i>
-----------	--

---

## Description

Compute spillover probability and correct for spillover

## Usage

```
compCytof(
  sce,
  sce_bead,
  marker_to_barcode,
  impute_value,
  overwrite = FALSE,
  n_cores = 1,
  naive = FALSE
)
```

## Arguments

sce	<a href="#">SingleCellExperiment</a> for the real cells
sce_bead	<a href="#">SingleCellExperiment</a> for the bead experiment
marker_to_barcode	Table that maps the marker to the barcode in the beads experiment
impute_value	Imputed value for counts that are declared as spillover

overwrite	logical; if TRUE data are overwritten if FALSE data are saved in new columns
n_cores	Number of computing cores
naive	logical; if TRUE use the naive version

**Value**

A [SingleCellExperiment](#) object

**Examples**

```
library(CATALYST)
library(dplyr)
bc_key <- c(139, 141:156, 158:176)
sce_bead <- prepData(ss_exp)
sce_bead <- assignPrelim(sce_bead, bc_key, verbose = FALSE)
sce_bead <- applyCutoffs(estCutoffs(sce_bead))
sce_bead <- computeSpillmat(sce_bead)
data(mp_cells, package = "CATALYST")
sce <- prepData(mp_cells)
marker_to_barcode <- rowData(sce_bead)[, c("channel_name", "is_bc")] |>
  as_tibble() |>
  filter(is_bc == TRUE) |>
  mutate(barcode = bc_key) |>
  select(marker = channel_name, barcode)
spillR::compCytobf(sce, sce_bead, marker_to_barcode, impute_value = NA)
```

---

 compensate

---

*Compute spillover probability and correct for spillover*


---

**Description**

Compute spillover probability and correct for spillover

**Usage**

```
compensate(
  tb_real,
  tb_bead,
  target_marker,
  spillover_markers,
  impute_value = NA,
  n_iter = 1000
)
```

**Arguments**

tb_real	Data frame or tibble with proteins counts of real experiment
tb_bead	Data frame or tibble with proteins counts of bead experiment
target_marker	Marker name in real experiment
spillover_markers	Marker names in bead experiment
impute_value	Value for counts that are declared as spillover
n_iter	Maximum number of EM steps

**Value**

A list of class `spillr` containing

tb_compensate	corrected real cells
tb_spill_prob	probability curve
convergence	covergence table of EM algorithm
tb_real	input real cells
tb_bead	input bead cells
target_marker	input marker in real experiment
spillover_markers	input markers in bead experiment

---

compensate_naive	<i>Compute spillover probability and correct for spillover from beads only</i>
------------------	--

---

**Description**

Compute spillover probability and correct for spillover from beads only

**Usage**

```
compensate_naive(
  tb_real,
  tb_bead,
  target_marker,
  spillover_markers,
  impute_value = NA
)
```

**Arguments**

tb_real	Data frame or tibble with proteins counts of real experiment
tb_bead	Data frame or tibble with proteins counts of bead experiment
target_marker	Marker name in real experiment
spillover_markers	Marker names in bead experiment
impute_value	Value for counts that are declared as spillover

**Value**

A list of class `spillr` containing

tb_compensate	corrected real cells
tb_spill_prob	probability curve
convergence	covergence table of EM algorithm
tb_real	input real cells
tb_bead	input bead cells
target_marker	input marker in real experiment
spillover_markers	input markers in bead experiment

---

generate_bead	<i>Generate dataset for vignettes and simulation studies</i>
---------------	--

---

**Description**

Generate dataset for vignettes and simulation studies

**Usage**

```
generate_bead()
```

**Value**

`tibble` data frame

**Examples**

```
set.seed(23)
generate_bead()
```

---

generate_real	<i>Generate dataset for vignettes and simulation studies</i>
---------------	--

---

**Description**

Generate dataset for vignettes and simulation studies

**Usage**

```
generate_real()
```

**Value**

[tibble](#) data frame

**Examples**

```
set.seed(23)
generate_real()
```

---

plotDiagnostics	<i>Compute spillover probability and correct for spillover</i>
-----------------	--

---

**Description**

Compute spillover probability and correct for spillover

**Usage**

```
plotDiagnostics(sce, ch)
```

**Arguments**

sce	A <a href="#">SingleCellExperiment</a> object
ch	Character string specifying the channel to plot

**Value**

A list of [ggplot2](#) plots

## Examples

```
library(CATALYST)
library(dplyr)
bc_key <- c(139, 141:156, 158:176)
sce_bead <- prepData(ss_exp)
sce_bead <- assignPrelim(sce_bead, bc_key, verbose = FALSE)
sce_bead <- applyCutoffs(estCutoffs(sce_bead))
sce_bead <- computeSpillmat(sce_bead)
data(mp_cells, package = "CATALYST")
sce <- prepData(mp_cells)
marker_to_barcode <- rowData(sce_bead)[, c("channel_name", "is_bc")] |>
  as_tibble() |>
  filter(is_bc == TRUE) |>
  mutate(barcode = bc_key) |>
  select(marker = channel_name, barcode)
sce <- spillR::compCytobf(sce, sce_bead, marker_to_barcode, impute_value = NA)
plotDiagnostics(sce, "Yb173Di")
```

---

tfm

*Variance stabilizing transform of counts*

---

## Description

Variance stabilizing transform of counts

## Usage

```
tfm(x)
```

## Arguments

x                      Raw count

## Value

A transformed count

# Index

compCytof, [2](#)  
compensate, [3](#)  
compensate\_naive, [4](#)

generate\_bead, [5](#)  
generate\_real, [6](#)  
ggplot2, [6](#)

plotDiagnostics, [6](#)

SingleCellExperiment, [2](#), [3](#), [6](#)

tfm, [7](#)  
tibble, [5](#), [6](#)