

Package ‘MultiBaC’

August 8, 2025

Type Package

Title Multiomic Batch effect Correction

Version 1.19.0

Author person(` `Manuel", ` `Ugidos", email = ` `manuelugidos@gmail.com"), person(` `Sonia", ` `Tarazona", email = ` `sotacam@gmail.com"), person(` `María José", ` `Nueda", email = ` `mjnueda@ua.es")

Maintainer The package maintainer <manuelugidos@gmail.com>

Description MultiBaC is a strategy to correct batch effects from multiomic datasets distributed across different labs or data acquisition events. MultiBaC is the first Batch effect correction algorithm that dealing with batch effect correction in multiomics datasets. MultiBaC is able to remove batch effects across different omics generated within separate batches provided that at least one common omic data type is included in all the batches considered.

License GPL-3

Encoding UTF-8

biocViews Software, StatisticalMethod, PrincipalComponent, DataRepresentation, GeneExpression, Transcription, BatchEffect

Imports Matrix, ggplot2, MultiAssayExperiment, ropis, graphics, methods, plotrix, grDevices, pcaMethods

Suggests knitr, rmarkdown, BiocStyle, devtools

VignetteBuilder knitr

Collate 'auxfunctions.R' 'ARSyNcomponents.R' 'ASCA1f.R' 'PCA-GENES.R' 'ASCAfunres.R' 'ASCAfun12.R' 'ASCAfun1.R' 'ASCA2f.R' 'ARSyNbac.R' 'MultiBaC.R' 'createMbac.R' 'plot-methods.R' 'summary-function.R'

NeedsCompilation no

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/MultiBaC>

git_branch devel

git_last_commit e48c7e2

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-08-07

Contents

A.gro	2
A.rna	3
ARSyNbac	4
B.ribo	5
B.rna	6
batchCorrection	6
batchEstPlot	7
C.par	8
C.rna	9
createMbac	9
explained_varPlot	10
genMissingOmics	11
genModelList	12
inner_relPlot	13
MultiBaC	14
multiyeast	16
plot.mbac	17
plot_pca	19
Q2_plot	20
summary.mbac	21
Index	22

A.gro	<i>Transcription rate data from yeast</i>
-------	---

Description

This data set gives the transcription rates of 200 genes from yeast measured at two different conditions (glucose vs glucose starvation).

Usage

multiyeast

Format

A matrix containing 6 rows and 200 variables.

Source

Gene Expression Omnibus: GSE11521

References

- [1] Pelechano, V. and Pérez-Ortín, J.E. (2010), There is a steady-state transcriptome in exponentially growing yeast cells. *Yeast*, 27: 413-422. <https://doi.org/10.1002/yea.1768>
- [2] García-Martínez, J. and Aranda, A. and Pérez-Ortín, J. E. (2004). Genomic Run-On Evaluates Transcription Rates for All Yeast Genes and Identifies Gene Regulatory Mechanisms, *Molecular Cell*, 15. <https://doi.org/10.1016/j.molcel.2004.06.004>
- [3] Pelechano, V., Chávez, S., & Pérez-Ortín, J. E. (2010). A complete set of nascent transcription rates for yeast genes. *PloS one*, 5(11), e15442. <https://doi.org/10.1371/journal.pone.0015442>

A.rna	<i>Gene expression data from yeast</i>
-------	--

Description

This data set gives the expression of 200 genes from yeast measured at two different conditions (glucose vs glucose starvation).

Usage

multiyeast

Format

A matrix containing 6 rows and 200 variables.

Source

Gene Expression Omnibus: GSE11521

References

- [1] Pelechano, V. and Pérez-Ortín, J.E. (2010), There is a steady-state transcriptome in exponentially growing yeast cells. *Yeast*, 27: 413-422. <https://doi.org/10.1002/yea.1768>
- [2] García-Martínez, J. and Aranda, A. and Pérez-Ortín, J. E. (2004). Genomic Run-On Evaluates Transcription Rates for All Yeast Genes and Identifies Gene Regulatory Mechanisms, *Molecular Cell*, 15. <https://doi.org/10.1016/j.molcel.2004.06.004>
- [3] Pelechano, V., Chávez, S., & Pérez-Ortín, J. E. (2010). A complete set of nascent transcription rates for yeast genes. *PloS one*, 5(11), e15442. <https://doi.org/10.1371/journal.pone.0015442>

ARSyNbac

*ARSyNbac***Description**

ARSyNbac

Usage

```
ARSyNbac(
  mbac,
  batchEstimation = TRUE,
  filterNoise = TRUE,
  Interaction = FALSE,
  Variability = 0.9,
  beta = 2,
  modelName = "Model 1",
  showplot = TRUE
)
```

Arguments

mbac	mbac object generated by <code>*createMbac*</code> .
batchEstimation	Logical. If TRUE (default) the batch effect is estimated and used to correct the data. Use TRUE when the source of the batch effect is known.
filterNoise	Logical. If TRUE (default) structured noise is removed from residuals. Use this option when there is an unknown source of batch effect in data.
Interaction	Logical. Whether to model the interaction between factors or not (FALSE by default).
Variability	From 0 to 1. Minimum percent of data variability that must be explained by each model. By default, 0.90.
beta	Numeric. Components that represent more than beta times the average variability are identified as systematic noise in residuals. Used in noise reduction mode. By default, 2.
modelName	Name of the model created. This name will be showed if you use the <code>explained_var</code> plot function. By default, "Model 1".
showplot	Logical. If TRUE (default), the <code>explained_var</code> plot is showed. This plot represents the number of components selected for the ARSyN model.

Value

Custom mbac object. Elements in a mbac object:

1. `ListOfBatches`: A list of `MultiAssayExperiment` objects (one per batch).
2. `commonOmic`: Name of the common omic between the batches. It must be one of the names in `omicNames` argument. If NULL (default), the omic names that appears more times is selected as `commonOmic`.

3. CorrectedData: Same structure than ListOfBatches but with the corrected data instead of the original.
4. ARSyNmodels: ARSyN models created during MultiBaC performance (one per omic data type).

References

Nueda MJ, Ferrer A, Conesa A. ARSyN: A method for the identification and removal of systematic noise in multifactorial time course microarray experiments. *Biostatistics*. 2012;13:553–66.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, B.rna, C.rna),
                      batchFactor = c("A", "B", "C"),
                      experimentalDesign = list("A" = c("Glu+",
"Glucose", "Glu+", "Glu-",
"Glu-", "Glu-"),
"B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
"C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
                      omicNames = "RNA")
my_final_mbac <- ARSyNbac (my_mbac, batchEstimation = TRUE, filterNoise = TRUE,
                          Interaction=TRUE, Variability = 0.90, beta = 2,
                          modelName = "Model 1",
                          showplot = FALSE)
```

B.ribo

Gene translation rate data from yeast

Description

This data set gives the translation rates of 200 genes from yeast measured at two different conditions (glucose vs glucose starvation).

Usage

```
multiyeast
```

Format

A matrix containing 4 rows and 200 variables.

Source

Gene Expression Omnibus: GSE56622

References

[1] Zid, B. M., & O'Shea, E. K. (2014). Promoter sequences direct cytoplasmic localization and translation of mRNAs during starvation in yeast. *Nature*, 514(7520), 117–121. <https://doi.org/10.1038/nature13578>

B.rna	<i>Gene expression data from yeast</i>
-------	--

Description

This data set gives the expression of 200 genes from yeast measured at two different conditions (glucose vs glucose starvation).

Usage

```
multiyeast
```

Format

A matrix containing 4 rows and 200 variables.

Source

Gene Expression Omnibus: GSE56622

References

[1] Zid, B. M., & O'Shea, E. K. (2014). Promoter sequences direct cytoplasmic localization and translation of mRNAs during starvation in yeast. *Nature*, 514(7520), 117–121. <https://doi.org/10.1038/nature13578>

batchCorrection	<i>batchCorrection</i>
-----------------	------------------------

Description

This function performs the ARSyNbac correction [1] for each omic contained in mulBatchDesign input object.

Usage

```
batchCorrection(mbac, multiBatchDesign, Interaction = FALSE,
  Variability = 0.9)
```

Arguments

mbac	mbac object generated by createMbac. PLS models slot must be present.
multiBatchDesign	A list containing the original and predicted omic for each batch. All omics must be present in every batch. Output object of genMissingOmics function
Interaction	Logical. Whether to model the interaction between experimental factors and batch factor in ARSyN models. By default, FALSE.
Variability	From 0 to 1. Minimum percent of data variability that must be explained for each ARSyN model. By default, 0.90.

Value

Custom mbac object. Elements in a mbac object:

1. ListOfBatches: A list of MultiAssayExperiment objects (one per batch).
2. commonOmic: Name of the common omic between the batches.
3. CorrectedData: Same structure than ListOfBatches but with the corrected data instead of the original.
4. PLSmodels: PLS models created during MultiBaC method performance (one model per non-common omic data type).
5. ARSyNmodels: ARSyN models created during MultiBaC performance (one per omic data type).
6. InnerRelation: Table of class data.frame containing the inner correlation (i.e. correlation between the scores of X (t) and Y (u) matrices) for each PLS model across all components.

References

[1] Nueda MJ, Ferrer A, Conesa A. ARSyN: A method for the identification and removal of systematic noise in multifactorial time course microarray experiments. *Biostatistics*. 2012;13(3):553-566. doi:10.1093/biostatistics/kxr042

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+", "Glu+",
    "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"),
  commonOmic = "RNA")

my_mbac_2 <- genModelList (my_mbac, test.comp = NULL,
  scale = FALSE, center = TRUE,
  crossval = NULL,
  showinfo = TRUE)

multiBatchDesign <- genMissingOmics(my_mbac_2)
my_finalwise_mbac <- batchCorrection(my_mbac_2,
  multiBatchDesign = multiBatchDesign,
  Interaction = FALSE,
  Variability = 0.9)
```

batchEstPlot

batchEstPlot

Description

This function uses linear models to estimate the batch effect magnitude using the common data across batches. It compares the result with theoretical distribution of different levels of batch magnitude.

Usage

```
batchEstPlot(mbac, ...)
```

Arguments

`mbac` Object of class `mbac` generated by `*createMbac*`.
`...` Other graphical parameters.

Value

Batch estimation plot is displayed.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"))

batchEstPlot (my_mbac)
```

C.par

Protein binded mRNA data from yeast

Description

This data set gives the protein binding information of 200 genes from yeast measured at two different conditions (glucose vs glucose starvation).

Usage

```
multiyeast
```

Format

A matrix containing 4 rows and 200 variables.

Source

Gene Expression Omnibus: GSE43747

References

[1] Freeberg, M. A., Han, T., Moresco, J. J., Kong, A., Yang, Y. C., Lu, Z. J., Yates, J. R., & Kim, J. K. (2013). Pervasive and dynamic protein binding sites of the mRNA transcriptome in *Saccharomyces cerevisiae*. *Genome biology*, 14(2), R13. <https://doi.org/10.1186/gb-2013-14-2-r13>

C.rna	<i>Gene expression data from yeast</i>
-------	--

Description

This data set gives the expression of 200 genes from yeast measured at two different conditions (glucose vs glucose starvation).

Usage

```
multiyeast
```

Format

A matrix containing 4 rows and 200 variables.

Source

Gene Expression Omnibus: GSE43747

References

[1] Freeberg, M. A., Han, T., Moresco, J. J., Kong, A., Yang, Y. C., Lu, Z. J., Yates, J. R., & Kim, J. K. (2013). Pervasive and dynamic protein binding sites of the mRNA transcriptome in *Saccharomyces cerevisiae*. *Genome biology*, 14(2), R13. <https://doi.org/10.1186/gb-2013-14-2-r13>

createMbac	<i>createMbac</i>
------------	-------------------

Description

This function creates a list object to be used by MultiBaC function from a set of matrix R objects.

Usage

```
createMbac(inputOmics, batchFactor = NULL, experimentalDesign, omicNames,
  commonOmic = NULL)
```

Arguments

inputOmics	A list containing all the matrices or data.frame objects to be analysed. MultiAssayExperiment objects can alternatively be provided.
batchFactor	Either a vector or a factor indicating the batch were each input matrix belongs to (i.e. study, lab, time point, etc.). If NULL (default) no batch is considered and just ARSyNbac noise reduction mode could be applied.

experimentalDesign

A list with as many elements as batches. Each element can be a factor, a character vector or a data.frame indicating the experimental conditions for each sample in that batch. When being a data.frame with more than one column (multi-factorial experimental designs), the different columns will be combined into a single one to be used by MultiBaC or ARSyNbac. In any case, the experimental setting must be the same for all batches. In addition, the names of the elements in this list must be the same as declared in batches argument. If not (or if NULL), names are forced to be the same as in batches argument and in the same order.

omicNames

Vector of names for each input matrix. The common omic is required to have the same name across batches.

commonOmic

Name of the common omic between the batches. It must be one of the names in omicNames argument. If NULL (default), the omic name which is common to all batches is selected as commonOmic.

Value

Custom mbac object. Elements in a mbac object:

1. ListOfBatches: A list of MultiAssayExperiment objects (one per batch).
2. commonOmic Name of the common omic between batches.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"),
  commonOmic = "RNA")
```

explained_varPlot

explained_varPlot

Description

explained_varPlot

Usage

```
explained_varPlot(mbac, ...)
```

Arguments

mbac

Object of class mbac generated by *ARSyNbac*, *MultiBaC* or *batchCorrection*.

...

Other graphical parameters.

Value

Explained variance plot for ARSyN models is displayed.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"))

my_final_mbac <- MultiBaC (my_mbac,
  test.comp = NULL, scale = FALSE,
  center = TRUE, crossval = NULL,
  Variability = 0.90,
  Interaction = TRUE ,
  showplot = FALSE,
  showinfo = FALSE)

explained_varPlot (my_final_mbac)
```

genMissingOmics

genMissingOmics

Description

This function generates for all the batches the omic data they had not originally. This is the previous step to apply ARSyNbac [1] correction.

Usage

```
genMissingOmics(mbac)
```

Arguments

mbac mbac object generated by **createMbac**. PLS models slot must be present.

Value

A list of **MultiAssayExperiment** structures. In this case, each batch contains all the omics introduced in MultiBaC. For instance, if two batches are being studying, "A" and "B", given that "A" contains "RNA-seq" and "GRO-seq" data and "B" contains "RNA-seq" and "Metabolomics" data, after applying **genMissingOmics** function batch "A" will contain "RNA-seq", "GRO-seq" and predicted "Metabolomics" data.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"),
  commonOmic = "RNA")

my_mbac_2 <- genModelList (my_mbac, test.comp = NULL,
  scale = FALSE, center = TRUE,
  crossval = NULL,
  showinfo = TRUE)

multiBatchDesign <- genMissingOmics(my_mbac_2)
```

genModelList

genModelList

Description

This function performs PLS models for every batch. A PLS model is generated for each non-common omic in each batch.

Usage

```
genModelList(mbac, test.comp = NULL, scale = FALSE, center = TRUE,
  crossval = NULL, showinfo = TRUE)
```

Arguments

mbac	mbac object generated by <i>*createMbac*</i> .
test.comp	Maximum number of components allowed for PLS models. If NULL (default), the minimal effective rank of the matrices is used as the maximum number of components.
scale	Logical. Whether X and Y matrices must be scaled. By default, FALSE.
center	Logical. Whether X and Y matrices must be centered. By default, TRUE.
crossval	Integer: number of cross-validation segments. The number of samples (rows of 'x') must be at least $\geq$ crossval. If NULL (default) leave-one-out crossvalidation is performed.
showinfo	Logical. Whether to show the information about the function progress. By default, TRUE.

Value

Custom mbac object. Elements in a mbac object:

1. ListOfBatches: A list of MultiAssayExperiment objects (one per batch).
2. commonOmic: Name of the common omic between the batches.
3. PLSmodels: PLS models created during MultiBaC method performance (one model per non-common omic data type).
4. InnerRelation: Table of class data.frame containing the inner correlation (i.e. correlation between the scores of X (t) and Y (u) matrices) for each PLS model across all components.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"),
  commonOmic = "RNA")

my_mbac_2 <- genModelList (my_mbac, test.comp = NULL,
  scale = FALSE, center = TRUE,
  crossval = NULL,
  showinfo = TRUE)
```

inner_relPlot	<i>inner_relPlot</i>
---------------	----------------------

Description

inner_relPlot

Usage

```
inner_relPlot(mbac, comp2plot = c(1, 2), ...)
```

Arguments

mbac	Object of class mbac generated by *MultiBaC* or *genModelList*.
comp2plot	Indicates which components are plotted. Default is "c(1,2)", which means that just the inner relation plot of components 1 and 2 are shown. If more components are indicated, the function will return as many plots as needed to show all the components.
...	Other graphical parameters

Value

Inner relation plot for PLS models is displayed.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"))

my_final_mbac <- MultiBaC (my_mbac,
  test.comp = NULL, scale = FALSE,
  center = TRUE, crossval = NULL,
  Variability = 0.90,
  Interaction = TRUE ,
  showplot = FALSE,
  showinfo = FALSE)

inner_relPlot (my_final_mbac)
```

MultiBaC

MultiBaC

Description

MultiBaC performs a multi-omic, multi-batch correction

MultiBaC is a strategy to correct batch effects from multiomic datasets distributed across different labs or data acquisition events. MultiBaC is the first Batch effect correction algorithm that dealing with batch effect correction in multiomics datasets. MultiBaC is able to remove batch effects across different omics generated within separate batches provided that at least one common omic data type is included in all the batches considered.

Usage

```
MultiBaC(mbac, test.comp = NULL, scale = FALSE, center = TRUE,
  showplot = TRUE, crossval = NULL, Interaction = FALSE,
  Variability = 0.9, showinfo = TRUE)
```

Arguments

<code>mbac</code>	mbac object generated by <code>createMbac</code> .
<code>test.comp</code>	Maximum number of components allowed for PLS models. If <code>NULL</code> (default), the minimal effective rank of the matrices is used as the maximum number of components.
<code>scale</code>	Logical. Whether X and Y matrices must be scaled. By default, <code>FALSE</code> .
<code>center</code>	Logical. Whether X and Y matrices must be centered. By default, <code>TRUE</code> .
<code>showplot</code>	Logical. If <code>TRUE</code> (default), the Q2 and the explained variance plots are shown.

crossval	Integer: number of cross-validation segments. The number of samples (rows of 'x') must be at least $\geq$ crossval. If NULL (default), a leave-one-out crossvalidation is performed.
Interaction	Logical. Whether to model the interaction between experimental factors and batch factor in ARSyN models. By default, FALSE.
Variability	From 0 to 1. Minimum percent of data variability that must be explained by each ARSyN model. By default, 0.90.
showinfo	Logical. If TRUE (default), the information about the function progress is shown.

Value

Custom mbac object. Elements in a mbac object:

1. ListOfBatches: A list of MultiAssayExperiment objects (one per batch).
2. commonOmic: Name of the common omic between the batches.
3. CorrectedData: Same structure than ListOfBatches but with the corrected data instead of the original.
4. PLSmodels: PLS models created during MultiBaC method performance (one model per non-common omic data type).
5. ARSyNmodels: ARSyN models created during MultiBaC performance (one per omic data type).
6. InnerRelation: Table of class data.frame containing the inner correlation (i.e. correlation between the scores of X (t) and Y (u) matrices) for each PLS model across all components.

References

Ugidos, M., Tarazona, S., Prats-Montalbán, J. M., Ferrer, A., & Conesa, A. (2020). MultiBaC: A strategy to remove batch effects between different omic data types. *Statistical Methods in Medical Research*. <https://doi.org/10.1177/0962280220907365>

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"),
  commonOmic = "RNA")

my_final_mbac <- MultiBaC (my_mbac,
  test.comp = NULL, scale = FALSE,
  center = TRUE, crossval = NULL,
  Variability = 0.90,
  Interaction = TRUE ,
  showplot = FALSE,
  showinfo = FALSE)
```

multiyeast

*A distributed yeast multiomic dataset***Description**

The yeast expression data sets were collected from the Gene Expression Omnibus (GEO) database and from three different studies. All of them analyzed the effects of glucose starvation in yeast. Lab A is the Department of Biochemistry and Molecular Biology from Universitat de Valencia (accession number GSE11521) [@JE1, @JE2, @JE3]; Lab B is the Department of Molecular and Cellular Biology from Harvard University (accession number GSE56622) [@RIBO]; and Lab C is the Department of Biology from Johns Hopkins University (accession number GSE43747) [@PARCLIP]. These studies used equivalent yeast strains and experimental conditions but, as shown in Figure 1, the main effect on expression is due to data belonging to different labs, which are the batches in this case.

Usage

```
data("multiyeast")
```

Format

6 matrices with 6 or 4 observations on 200 variables (genes).

A.rna Gene expression data matrix from lab A.

A.gro Transcription rates data matrix from lab A.

B.rna Gene expression data matrix from lab B.

B.ribo Translation rates data matrix from lab B.

C.rna Gene expression data matrix from lab C.

C.par Protein binded RNA data matrix from lab C.

Details

The yeast expression data sets were collected from the Gene Expression Omnibus (GEO) database and from three different studies. All of them analyzed the effects of glucose starvation in yeast. Lab A is the Department of Biochemistry and Molecular Biology from Universitat de Valencia (accession number GSE11521) [@JE1, @JE2, @JE3]; Lab B is the Department of Molecular and Cellular Biology from Harvard University (accession number GSE56622) [@RIBO]; and Lab C is the Department of Biology from Johns Hopkins University (accession number GSE43747) [@PARCLIP]. These studies used equivalent yeast strains and experimental conditions but, as shown in Figure 1, the main effect on expression is due to data belonging to different labs, which are the batches in this case. After a proper data pre-processing for each case, a voom transformation (limma R package) was applied when necessary. Finally TMM normalization was performed on the whole set of samples from all labs. A reduced dataset was obtained by selecting 200 omic variables from each data matrix and just 3 samples from lab A. This yeast multiomic reduced dataset is included in *MutiBaC* package to illustrate the usage of the package. The gene expression matrices can be loaded by using the *data("multiyeast")* instruction.

Source

<https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi>

References

- [1] Pelechano, V. and Pérez-Ortín, J.E. (2010), There is a steady-state transcriptome in exponentially growing yeast cells. *Yeast*, 27: 413–422. <https://doi.org/10.1002/yea.1768>
- [2] García-Martínez, J. and Aranda, A. and Pérez-Ortín, J. E. (2004). Genomic Run-On Evaluates Transcription Rates for All Yeast Genes and Identifies Gene Regulatory Mechanisms, *Molecular Cell*, 15. <https://doi.org/10.1016/j.molcel.2004.06.004>
- [3] Pelechano, V., Chávez, S., & Pérez-Ortín, J. E. (2010). A complete set of nascent transcription rates for yeast genes. *PloS one*, 5(11), e15442. <https://doi.org/10.1371/journal.pone.0015442>
- [4] Zid, B. M., & O'Shea, E. K. (2014). Promoter sequences direct cytoplasmic localization and translation of mRNAs during starvation in yeast. *Nature*, 514(7520), 117–121. <https://doi.org/10.1038/nature13578>
- [5] Freeberg, M. A., Han, T., Moresco, J. J., Kong, A., Yang, Y. C., Lu, Z. J., Yates, J. R., & Kim, J. K. (2013). Pervasive and dynamic protein binding sites of the mRNA transcriptome in *Saccharomyces cerevisiae*. *Genome biology*, 14(2), R13. <https://doi.org/10.1186/gb-2013-14-2-r13>

Examples

```
data(multiyeast)
head(A.rna)
```

plot.mbac

Plot Method for mbac

Description

plot function for mbac class.

Usage

```
## S3 method for class 'mbac'
plot(x, y = NULL, typeP = "def", col.by.batch = TRUE,
     col.per.group = NULL, comp2plot = c(1, 2), legend.text = NULL,
     args.legend = NULL, ...)
```

Arguments

x	mbac object generated by <i>*createMbac*</i> , <i>*ARSyNbac*</i> or <i>*MultiBaC*</i> .
y	Currently not used.
typeP	type of plot showed. See details.
col.by.batch	Argument for PCA plots. TRUE or FALSE. If TRUE (default), samples are colored according to the batch factor. If FALSE, samples are colored according to the experimental conditions.
col.per.group	Argument for PCA plots. Color for each group (given by batches or experimental conditions). If NULL (default), the colors are taken from a predefined palette.
comp2plot	Argument for PCA or InnerRel plot. It indicates which components are to be plotted. The default is c(1,2), which means that, in PCA plots, component 1 is plotted in "x" axis and component 2 in "y" axis, and for InnerRel plots, the inner relation plots of components 1 and 2 are to be shown. If more components are indicated, the function will return as many plots as needed to show all the components.

legend.text	A vector of text used to construct a legend for the plot. Argument for PCA plot. If NULL (default) batch or conditions names included in the mbac object are used.
args.legend	list of additional arguments to pass to legend(); names of the list are used as argument names. Only used if legend.text is supplied.
...	Other graphical arguments.

Details

typeP options are: "def" (default option, "Q2 plot" and "Explained variance plot" in case of MultiBaC and "Explained variance plot" in case of ARSyNbac outputs), "inner" (inner correlation plots for each PLS model across the components for MultiBaC output), "pca.org" (PCA plot of original data for MultiBaC or ARSyNbac outputs), "pca.cor" (PCA plot of corrected data for MultiBaC or ARSyNbac outputs), "pca.both" (PCA plots for both original and corrected data for MultiBaC or ARSyNbac outputs), and "batch" ("Batch effect estimation" plot for all the output). Remember that PCA plots can only be generated when all the omics share the same variable space (e.g. gene identifiers are provided as names of variables for all data matrices). While the **plot** function can generate all the plot types described above, each plot can also be independently generated by its corresponding function: **Q2_plot(mbac)**, **explained_varPlot(mbac)**, **plot_pca(mbac, typeP = c("pca.org", "pca.cor", "pca.both"), col.by.batch, col.per.group, comp2plot, legend.text, args.legend)**, **batchEstPlot(mbac, commonOmic)**, or **inner_relPlot(mbac, comp2plot = c(1,2))**.

Value

A plot is displayed.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"))

my_final_mbac <- MultiBaC (my_mbac,
  test.comp = NULL, scale = FALSE,
  center = TRUE, crossval = NULL,
  Variability = 0.90,
  Interaction = TRUE ,
  showplot = FALSE,
  showinfo = FALSE)

plot(my_final_mbac)
```

plot_pca	<i>plot_pca</i>
----------	-----------------

Description

plot_pca

Usage

```
plot_pca(mbac, col.by.batch = TRUE, col.per.group = NULL,
  comp2plot = c(1, 2), typeP = "pca.both", legend.text = NULL,
  args.legend = NULL, ...)
```

Arguments

mbac	Object of class mbac generated by <i>*createMbac*</i> , <i>*ARSyNbac*</i> , <i>*MultiBaC*</i> , <i>*genModelList*</i> , or <i>*batchCorrection*</i> .
col.by.batch	Argument for PCA plots. TRUE or FALSE. If TRUE (default) samples are gruted according to the batch factor. If FALSE samples are gruted according to the experimental desing.
col.per.group	Argument for PCA plot. Indicates the color for each group defined in "groups" argument. If NULL (default) the colors are taken from a predefined pallete.
comp2plot	Indicates which components are plotted. Default is "c(1,2)", which means that component 1 is plotted in "x" axis and component 2 in "y" axis. If more components are indicated, the function will return as many plots as needed to show all the components.
typeP	"pca.cor", "pca.org" or "pca.both". If inputOmics contains original matrices, set "pca.org". However, if inputOmics contains the corrected matrices, set "pca.cor".
legend.text	a vector of text used to construct a legend for the plot.
args.legend	list of additional arguments to pass to legend(); names of the list are used as argument names. Only used if legend.text is supplied.
...	Other graphical arguments.

Value

A PCA plot is displayed.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"))

plot_pca(my_mbac, typeP = "pca.org")
```

```
my_final_mbac <- MultiBaC (my_mbac,
                           test.comp = NULL, scale = FALSE,
                           center = TRUE, crossval = NULL,
                           Variability = 0.90,
                           Interaction = TRUE ,
                           showplot = FALSE,
                           showinfo = FALSE)

plot_pca(my_final_mbac, typeP = "pca.cor")
```

Q2_plot	<i>Q2_plot</i>
---------	----------------

Description

Q2_plot

Usage

```
Q2_plot(mbac, ...)
```

Arguments

mbac Object of class mbac generated by *MultiBaC* or *genModelList*.
... Other graphical parameters

Value

Q2 plot of PLS models is displayed.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
                       batchFactor = c("A", "A", "B", "B", "C", "C"),
                       experimentalDesign = list("A" = c("Glu+", "Glu+",
                                                           "Glu+", "Glu-", "Glu-", "Glu-"),
                                                  "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
                                                  "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
                       omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"))

my_final_mbac <- MultiBaC (my_mbac,
                           test.comp = NULL, scale = FALSE,
                           center = TRUE, crossval = NULL,
                           Variability = 0.90,
                           Interaction = TRUE ,
                           showplot = FALSE,
                           showinfo = FALSE)

Q2_plot (my_final_mbac)
```

summary.mbac

*summary.mbac***Description**

Displays the structure and the content of the object of class mbac.

Usage

```
## S3 method for class 'mbac'
summary(object, ...)
```

Arguments

`object` An object of class mbac.
`...` additional arguments affecting the summary produced.

Value

Custom mbac object structure.

Examples

```
data('multiyeast')

my_mbac <- createMbac (inputOmics = list(A.rna, A.gro, B.rna, B.ribo, C.rna, C.par),
  batchFactor = c("A", "A", "B", "B", "C", "C"),
  experimentalDesign = list("A" = c("Glu+", "Glu+",
    "Glu+", "Glu-", "Glu-", "Glu-"),
    "B" = c("Glu+", "Glu+", "Glu-", "Glu-"),
    "C" = c("Glu+", "Glu+", "Glu-", "Glu-")),
  omicNames = c("RNA", "GRO", "RNA", "RIBO", "RNA", "PAR"),
  commonOmic = "RNA")

summary(my_mbac)
```

Index

- * **datasets, yeast, multiomic**
 - multiyeast, [16](#)
- * **datasets**
 - A.gro, [2](#)
 - A.rna, [3](#)
 - B.ribo, [5](#)
 - B.rna, [6](#)
 - C.par, [8](#)
 - C.rna, [9](#)
- A.gro, [2](#)
- A.rna, [3](#)
- ARSyNbac, [4](#)
- B.ribo, [5](#)
- B.rna, [6](#)
- batchCorrection, [6](#)
- batchEstPlot, [7](#)
- C.par, [8](#)
- C.rna, [9](#)
- createMbac, [9](#)
- explained_varPlot, [10](#)
- genMissingOmics, [11](#)
- genModelList, [12](#)
- inner_relPlot, [13](#)
- MultiBaC, [14](#)
- MultiBaC-package (MultiBaC), [14](#)
- multiyeast, [16](#)
- plot,mbac-method (plot.mbac), [17](#)
- plot.mbac, [17](#)
- plot_pca, [19](#)
- Q2_plot, [20](#)
- summary.mbac, [21](#)