

Package ‘breakpointRdata’

August 7, 2025

Type Package

Title Strand-seq data for demonstration purposes

Version 1.27.0

Date 2016-08

Author David Porubsky, Aaron Taudt, Ashley Sanders

Maintainer David Porubsky <david.porubsky@gmail.com>

Description Strand-seq data to demonstrate functionalities
of breakpointR package.

Depends R (>= 3.5)

Suggests knitr, BiocStyle,

License file LICENSE

VignetteBuilder knitr

biocViews ExperimentData, Homo_sapiens_Data, SequencingData,
DNASeqData, Genome, SingleCellData

NeedsCompilation no

URL <https://github.com/daewoooo/breakpointRdata>

RoxygenNote 6.1.0

git_url <https://git.bioconductor.org/packages/breakpointRdata>

git_branch devel

git_last_commit d5b2792

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-08-07

Contents

example_bams	2
example_results	2
Index	4

example_bams

*Example BAM-files***Description**

A set of BAM-files for demonstration purposes of the functions in package **breakpointR**.

Format

A BAM files with aligned reads with one read per line.

Details

BAM files contain single-end reads aligned to GRCh38 reference genome.
Read sequences and quality values have been removed in order to reduce the file size.

Source

A lymphoblastoid cell line of Puerto Rican origin (HG00731). Raw reads were aligned to the GRCh38/hg38 reference assembly. The file has been downsampled to 20% of the coverage to reduce the file size.

References

<https://www.biorxiv.org/content/early/2017/09/23/193144>

example_results

*Results for example BAM-files***Description**

Localized breakpoints in example BAM-files, generated by the **breakpointR** package.

Format

Files containing BreakPoint object.

Details

A BreakPoint object is a list containing given elements: ID, fragments, deltas, breaks, confint, counts, lib.metrics and params.

- ID - unique identifier for a given library.
- fragments - A GRanges-class object that stores analyzed sequencing reads.
- deltas - A GRanges-class object that stores binned minus reads differences.
- breaks - A GRanges-class object that stores localized breaks.
- confint - A GRanges-class object that stores confidence intervals around localized breaks.
- counts - A GRanges-class object that stores directional read counts in between localized breaks.
- lib.metrics - A named vector with some useful library metrics.
- params - A named vector with user defined parameters used to run **breakpointR** package.

Source

A lymphoblastoid cell line of Puerto Rican origin (HG00731). Raw reads were aligned to the GRCh38/hg38 reference assembly.

References

<https://www.biorxiv.org/content/early/2017/09/23/193144>

Index

bams (example_bams), [2](#)

example_bams, [2](#)

example_results, [2](#)

results (example_results), [2](#)