

# Package ‘BufferedMatrix’

November 19, 2025

**Version** 1.75.0

**Title** A matrix data storage object held in temporary files

**Author** Ben Bolstad <bmb@bmbolstad.com>

**Maintainer** Ben Bolstad <bmb@bmbolstad.com>

**Depends** R (>= 2.6.0), methods

**Description** A tabular style data object where most data is stored outside main memory. A buffer is used to speed up access to data.

**License** LGPL (>= 2)

**URL** <https://github.com/bmbolstad/BufferedMatrix>

**Collate** allGenerics.R BufferedMatrix.R as.BufferedMatrix.R  
createBufferedMatrix.R

**LazyLoad** yes

**biocViews** Infrastructure

**git\_url** <https://git.bioconductor.org/packages/BufferedMatrix>

**git\_branch** devel

**git\_last\_commit** ecdbf23

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-11-19

## Contents

|                                |   |
|--------------------------------|---|
| as.BufferedMatrix . . . . .    | 2 |
| BufferedMatrix-class . . . . . | 2 |
| createBufferedMatrix . . . . . | 5 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>6</b> |
|--------------|----------|

---

|                   |                                                 |
|-------------------|-------------------------------------------------|
| as.BufferedMatrix | <i>Check or Coerce object to BufferedMatrix</i> |
|-------------------|-------------------------------------------------|

---

### Description

'as.BufferedMatrix' will coerce the supplied object into a BufferedMatrix. 'is.BufferedMatrix' checks whether the supplied argument is a BufferedMatrix.

### Usage

```
as.BufferedMatrix(x, bufferrows=1, buffercols=1,directory=getwd())
is.BufferedMatrix(x)
```

### Arguments

|            |                                                              |
|------------|--------------------------------------------------------------|
| x          | an R object                                                  |
| bufferrows | number of rows to be buffered if the row buffer is activated |
| buffercols | number of columns to be buffered                             |
| directory  | path to directory where temporary files should be stored     |

### Details

These functions are useful for converting between R [matrix](#) objects and [BufferedMatrix](#) objects.

### Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

---

|                      |                             |
|----------------------|-----------------------------|
| BufferedMatrix-class | <i>Class BufferedMatrix</i> |
|----------------------|-----------------------------|

---

### Description

This is a class representation of a buffered matrix (of numeric data). In this case data is primarily stored outside main memory in temporary files.

### Objects from the Class

Objects can be created using the function [createBufferedMatrix](#)

### Slots

**rawBufferedMatrix:** a pointer to an external structure used to access and store the matrix data.  
**rownames:** rownames for the matrix.  
**colnames:** colnames for the matrix.

**Methods**

**ncol** signature(object = "BufferedMatrix"): Returns the number of columns in the matrix

**nrow** signature(object = "BufferedMatrix"): Returns the number of rows in the matrix

**dim** signature(object = "BufferedMatrix"): Returns the dimensions of the matrix

**buffer.dim** signature(object = "BufferedMatrix"): Returns the number of columns and the number of rows to be stored in the buffer

**set.buffer.dim** signature(object = "BufferedMatrix"): Set the buffer size or resize it

**[** signature(object = "BufferedMatrix"): matrix accessor

**[<-** signature(object = "BufferedMatrix"): matrix replacer

**show** signature(object = "BufferedMatrix"): prints basic information about the BufferedMatrix out to screen

**is.RowMode** signature(object = "BufferedMatrix"): returns TRUE if the row buffer is active and FALSE otherwise.

**is.ColMode** signature(object = "BufferedMatrix"): returns TRUE if the row buffer is inactive and FALSE otherwise.

**RowMode** signature(object = "BufferedMatrix"): Activate the row buffer.

**ColMode** signature(object = "BufferedMatrix"): Deactivate the row buffer

**duplicate** signature(object = "BufferedMatrix"): Make a copy of the BufferedMatrix

**prefix** signature(object = "BufferedMatrix"): return the initial part of the string used for temporary files

**directory** signature(object = "BufferedMatrix"): return the location where temporary files are stored

**filenames** signature(object = "BufferedMatrix"): return the fully pathed filenames for each column in the matrix

**ewApply** signature(object = "BufferedMatrix"): apply a function elementwise

**exp** signature(object = "BufferedMatrix"): Compute the exponential elementwise of the matrix

**sqrt** signature(object = "BufferedMatrix"): Compute the square-root elementwise of the matrix

**pow** signature(object = "BufferedMatrix"): Compute  $x^{\text{power}}$  elementwise of the matrix

**log** signature(object = "BufferedMatrix"): Compute logarithm elementwise of the matrix

**colMax** signature(object = "BufferedMatrix"): Returns a vector containing maximums by column

**rowMax** signature(object = "BufferedMatrix"): Returns a vector containing maximums by row

**colMeans** signature(object = "BufferedMatrix"): Returns a vector containing means by column

**rowMeans** signature(object = "BufferedMatrix"): Returns a vector containing means by row

**colMin** signature(object = "BufferedMatrix"): Returns a vector containing minimums by column

**rowMin** signature(object = "BufferedMatrix"): Returns a vector containing minimums by row

**colVars** signature(object = "BufferedMatrix"): Returns a vector containing sample variances by column

**rowVars** signature(object = "BufferedMatrix"): Returns a vector containing sample variances by row

**colSd** signature(object = "BufferedMatrix"): Returns a vector containing sample standard deviations by column

**rowSd** signature(object = "BufferedMatrix"): Returns a vector containing sample standard deviations by row

**colSums** signature(object = "BufferedMatrix"): Returns a vector containing sum by column

**rowSums** signature(object = "BufferedMatrix"): Returns a vector containing sum by row

**colMedians** signature(object = "BufferedMatrix"): Returns a vector containing medians by column

**rowMedians** signature(object = "BufferedMatrix"): Returns a vector containing medians by row. Best only used when the matrix is in RowMode (otherwise it is extremely slow)

**Max** signature(object = "BufferedMatrix"): Returns the maximum of all elements in the matrix

**Min** signature(object = "BufferedMatrix"): Returns the minimum of all elements in the matrix

**Var** signature(object = "BufferedMatrix"): Returns the sample variance of all elements in the matrix

**Sd** signature(object = "BufferedMatrix"): Returns the sample standard deviations of all elements in the matrix

**Sum** signature(object = "BufferedMatrix"): Returns the sum of all elements in the matrix

**mean** signature(object = "BufferedMatrix"): Returns the mean of all elements in the matrix

**colApply** signature(object = "BufferedMatrix"): apply a function columnwise. Returns either a vector or BufferedMatrix.

**rowApply** signature(object = "BufferedMatrix"): apply a function row-wise. Returns either a vector or BufferedMatrix.

**as.matrix** signature(object = "BufferedMatrix"): coerce BufferedMatrix into a regular R matrix

**subBufferedMatrix** signature(object = "BufferedMatrix"): gets data from BufferedMatrix and returns it in another BufferedMatrix

**rownames** signature(object = "BufferedMatrix") : access the row names

**colnames** signature(object = "BufferedMatrix") : access the column names

**rownames<-** signature(object = "BufferedMatrix") : replace the row names

**colnames<-** signature(object = "BufferedMatrix") : replace the column names

**dimnames** signature(object = "BufferedMatrix") : Access the row and column names

**dimnames** signature(object = "BufferedMatrix") : Replace the row and column names

**ReadOnlyMode** signature(object = "BufferedMatrix") : Toggles the Read Only mode on and off

**is.ReadOnlyMode** signature(object = "BufferedMatrix") : Finds out if it is in Read Only Mode

**memory.usage** signature(object = "BufferedMatrix") : Give amount of RAM currently in use by BufferedMatrix object

**disk.usage** signature(object = "BufferedMatrix") : Give amount of disk space currently in use by BufferedMatrix object

as(matrix, BufferedMatrix): Coerce matrix to BufferedMatrix.

as(BufferedMatrix, matrix): Coerce the Buffered to matrix.

AddColumn: Add an additional column to the matrix. Will be all empty (set to 0)

MoveStorageDirectory: Move the temporary files used to store the matrix from one location to another

#### Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

---

createBufferedMatrix    *createBufferedMatrix*

---

#### Description

Creates a Buffered Matrix object

#### Usage

```
createBufferedMatrix(rows, cols=0, bufferrows=1, buffercols=1, prefix="BM", directory=getwd())
```

#### Arguments

|            |                                                              |
|------------|--------------------------------------------------------------|
| rows       | Number of rows in the matrix                                 |
| cols       | Initial number of columns in the matrix                      |
| bufferrows | number of rows to be buffered if the row buffer is activated |
| buffercols | number of columns to be buffered                             |
| prefix     | String to be used as start of name for any temporary files   |
| directory  | path to directory where temporary files should be stored     |

#### Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

# Index

## \* classes

BufferedMatrix-class, 2

## \* manip

as.BufferedMatrix, 2

[, BufferedMatrix-method  
(BufferedMatrix-class), 2

[<-, BufferedMatrix-method  
(BufferedMatrix-class), 2

AddColumn (BufferedMatrix-class), 2

AddColumn, BufferedMatrix-method  
(BufferedMatrix-class), 2

as.BufferedMatrix, 2

as.matrix, BufferedMatrix-method  
(BufferedMatrix-class), 2

buffer.dim (BufferedMatrix-class), 2

buffer.dim, BufferedMatrix-method  
(BufferedMatrix-class), 2

BufferedMatrix, 2

BufferedMatrix-class, 2

coerce, BufferedMatrix, matrix-method  
(BufferedMatrix-class), 2

coerce, matrix, BufferedMatrix-method  
(BufferedMatrix-class), 2

colApply (BufferedMatrix-class), 2

colApply, BufferedMatrix-method  
(BufferedMatrix-class), 2

colMax (BufferedMatrix-class), 2

colMax, BufferedMatrix-method  
(BufferedMatrix-class), 2

colMeans (BufferedMatrix-class), 2

colMeans, BufferedMatrix-method  
(BufferedMatrix-class), 2

colMedians (BufferedMatrix-class), 2

colMedians, BufferedMatrix-method  
(BufferedMatrix-class), 2

colMin (BufferedMatrix-class), 2

colMin, BufferedMatrix-method  
(BufferedMatrix-class), 2

ColMode (BufferedMatrix-class), 2

ColMode, BufferedMatrix-method  
(BufferedMatrix-class), 2

colnames, BufferedMatrix-method  
(BufferedMatrix-class), 2

colnames<-, BufferedMatrix-method  
(BufferedMatrix-class), 2

colRanges (BufferedMatrix-class), 2

colRanges, BufferedMatrix-method  
(BufferedMatrix-class), 2

colSd (BufferedMatrix-class), 2

colSd, BufferedMatrix-method  
(BufferedMatrix-class), 2

colSums (BufferedMatrix-class), 2

colSums, BufferedMatrix-method  
(BufferedMatrix-class), 2

colVars (BufferedMatrix-class), 2

colVars, BufferedMatrix-method  
(BufferedMatrix-class), 2

createBufferedMatrix, 2, 5

dim, BufferedMatrix-method  
(BufferedMatrix-class), 2

dimnames, BufferedMatrix-method  
(BufferedMatrix-class), 2

dimnames<-, BufferedMatrix-method  
(BufferedMatrix-class), 2

directory (BufferedMatrix-class), 2

directory, BufferedMatrix-method  
(BufferedMatrix-class), 2

disk.usage (BufferedMatrix-class), 2

disk.usage, BufferedMatrix-method  
(BufferedMatrix-class), 2

duplicate (BufferedMatrix-class), 2

duplicate, BufferedMatrix-method  
(BufferedMatrix-class), 2

ewApply (BufferedMatrix-class), 2

ewApply, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 exp, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
  
 filenames (BufferedMatrix-class), 2  
 filenames, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
  
 is.BufferedMatrix (as.BufferedMatrix), 2  
 is.ColMode (BufferedMatrix-class), 2  
 is.ColMode, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 is.ReadOnlyMode (BufferedMatrix-class),  
     2  
 is.ReadOnlyMode, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 is.RowMode (BufferedMatrix-class), 2  
 is.RowMode, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
  
 log, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
  
 matrix, 2, 4  
 Max (BufferedMatrix-class), 2  
 Max, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 mean, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 memory.usage (BufferedMatrix-class), 2  
 memory.usage, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 Min (BufferedMatrix-class), 2  
 Min, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 MoveStorageDirectory  
     (BufferedMatrix-class), 2  
 MoveStorageDirectory, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
  
 ncol, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 nrow, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
  
 pow (BufferedMatrix-class), 2  
 pow, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 prefix (BufferedMatrix-class), 2  
  
 prefix, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
  
 ReadOnlyMode (BufferedMatrix-class), 2  
 ReadOnlyMode, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rowApply (BufferedMatrix-class), 2  
 rowApply, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rowMax (BufferedMatrix-class), 2  
 rowMax, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rowMeans (BufferedMatrix-class), 2  
 rowMeans, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rowMedians (BufferedMatrix-class), 2  
 rowMedians, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rowMin (BufferedMatrix-class), 2  
 rowMin, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 RowMode (BufferedMatrix-class), 2  
 RowMode, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rownames, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rownames<-, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rowSd (BufferedMatrix-class), 2  
 rowSd, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rowSums (BufferedMatrix-class), 2  
 rowSums, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 rowVars (BufferedMatrix-class), 2  
 rowVars, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
  
 Sd (BufferedMatrix-class), 2  
 Sd, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 set.buffer.dim (BufferedMatrix-class), 2  
 set.buffer.dim, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 show, BufferedMatrix-method  
     (BufferedMatrix-class), 2  
 sqrt, BufferedMatrix-method  
     (BufferedMatrix-class), 2

subBufferedMatrix  
    (BufferedMatrix-class), [2](#)  
subBufferedMatrix, BufferedMatrix-method  
    (BufferedMatrix-class), [2](#)  
Sum (BufferedMatrix-class), [2](#)  
Sum, BufferedMatrix-method  
    (BufferedMatrix-class), [2](#)  
  
Var (BufferedMatrix-class), [2](#)  
Var, BufferedMatrix-method  
    (BufferedMatrix-class), [2](#)