

Package ‘TissueEnrich’

November 20, 2025

Type Package

Title Tissue-specific gene enrichment analysis

Version 1.31.0

Description The TissueEnrich package is used to calculate enrichment of tissue-specific genes in a set of input genes. For example, the user can input the most highly expressed genes from RNA-Seq data, or gene co-expression modules to determine which tissue-specific genes are enriched in those datasets. Tissue-specific genes were defined by processing RNA-Seq data from the Human Protein Atlas (HPA) (Uhlén et al. 2015), GTEx (Ardlie et al. 2015), and mouse ENCODE (Shen et al. 2012) using the algorithm from the HPA (Uhlén et al. 2015). The hypergeometric test is being used to determine if the tissue-specific genes are enriched among the input genes. Along with tissue-specific gene enrichment, the TissueEnrich package can also be used to define tissue-specific genes from expression datasets provided by the user, which can then be used to calculate tissue-specific gene enrichments.

License MIT + file LICENSE

VignetteBuilder knitr

Depends R (>= 3.5), ggplot2 (>= 2.2.1), SummarizedExperiment (>= 1.6.5), GSEABase (>= 1.38.2)

Imports dplyr (>= 0.7.3), tidyr (>= 0.8.0), stats

Suggests knitr, rmarkdown, testthat

Encoding UTF-8

LazyData true

RoxygenNote 7.3.1

biocViews GeneSetEnrichment, GeneExpression, Sequencing

git_url <https://git.bioconductor.org/packages/TissueEnrich>

git_branch devel

git_last_commit 706448a

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2025-11-19

Author Ashish Jain [aut, cre],
Geetu Tuteja [aut]
Maintainer Ashish Jain <jain.ashishjain1@gmail.com>

Contents

teEnrichment	2
teEnrichmentCustom	3
teGeneRetrieval	5
Index	7

teEnrichment	<i>Calculate tissue-specific gene enrichment using the hypergeometric test</i>
--------------	--

Description

The teEnrichment function is used to calculate the enrichment of tissue-specific genes, given an input gene set. It uses tissue-specific genes defined by processing RNA-Seq datasets from human and mouse.

Usage

```
teEnrichment(  
  inputGenes = NULL,  
  rnaSeqDataset = 1,  
  tissueSpecificGeneType = 1,  
  multiHypoCorrection = TRUE,  
  backgroundGenes = NULL  
)
```

Arguments

- inputGenes A GeneSet object containing the input genes, organism type ('Homo Sapiens' or 'Mus Musculus'), and gene id identifier (Gene Symbol or ENSEMBL identifier).
- rnaSeqDataset An integer describing the dataset to be used for enrichment analysis. 1 for 'Human Protein Atlas' (default), 2 for 'GTEx', 3 for 'Mouse ENCODE'. Default 1.
- tissueSpecificGeneType An integer describing the type of tissue- specific genes to be used. 1 for 'All' (default), 2 for 'Tissue-Enriched', 3 for 'Tissue-Enhanced', and 4 for 'Group-Enriched'. Default 1.
- multiHypoCorrection Flag to correct P-values for multiple hypothesis using BH method. Default TRUE.

backgroundGenes

A GeneSet object containing the background gene list, organism type ('Homo Sapiens' or 'Mus Musculus'), and gene id identifier (Gene Symbol or ENSEMBL identifier). The input genes must be present in the background gene list. If not provided all the genes will be used as background.

Value

The output is a list with four objects. The first object is the SummarizedExperiment object containing the enrichment results, the second and the third object contains the expression values and tissue-specificity information of the tissue-specific genes for genes from the input gene set, and the fourth is a GeneSet object containing genes that were not identified in the tissue-specific gene data.

Author(s)

Ashish Jain, Geetu Tuteja

Examples

```
library(dplyr)
library(ggplot2)
genes<-system.file('extdata', 'inputGenes.txt', package = 'TissueEnrich')
inputGenes<-scan(genes,character())
gs<-GeneSet(geneIds=inputGenes,organism='Homo Sapiens',
geneIdType=SymbolIdentifier())
output<-teEnrichment(gs)
seEnrichmentOutput<-output[[1]]
enrichmentOutput<-setNames(data.frame(assay(seEnrichmentOutput),
row.names = rowData(seEnrichmentOutput)[,1]),
colData(seEnrichmentOutput)[,1])
enrichmentOutput$Tissue<-row.names(enrichmentOutput)
#Plotting the P-Values
ggplot(enrichmentOutput,aes(x=reorder(Tissue,-Log10PValue),y=Log10PValue,
label = Tissue.Specific.Genes,fill = Tissue))+
geom_bar(stat = 'identity')+
labs(x='', y = '-LOG10(P-Value)')+
theme_bw()+
theme(legend.position='none')+
theme(plot.title = element_text(hjust = 0.5,size = 20),axis.title =
element_text(size=15))+
theme(axis.text.x = element_text(angle = 45, vjust = 1, hjust = 1),
panel.grid.major= element_blank(),panel.grid.minor = element_blank())
```

teEnrichmentCustom

Calculate tissue-specific gene enrichment using the hypergeometric test for custom datasets

Description

The teEnrichmentCustom function is used to calculate tissue-specific gene enrichment using tissue-specific genes defined using the teGeneRetrieval function.

Usage

```
teEnrichmentCustom(
  inputGenes = NULL,
  tissueSpecificGenes = NULL,
  tissueSpecificGeneType = 1,
  multiHypoCorrection = TRUE,
  backgroundGenes = NULL
)
```

Arguments

inputGenes An *GeneSet* object containing the input genes.

tissueSpecificGenes
A *SummarizedExperiment* object. Output from 'teGeneRetrieval' function. Default NULL.

tissueSpecificGeneType
An integer describing the type of tissue-specific genes to be used. 1 for 'All' (default), 2 for 'Tissue-Enriched', 3 for 'Tissue-Enhanced', and 4 for 'Group-Enriched'. Default 1.

multiHypoCorrection
Flag to correct P-values for multiple hypothesis using BH method. Default TRUE.

backgroundGenes
A *GeneSet* object containing the background gene list, organism type ('Homo Sapiens' or 'Mus Musculus'), and gene id identifier (Gene Symbol or ENSEMBL identifier). The input genes must be present in the background gene list. If not provided all the genes will be used as background.

Value

The output is a list with three objects. The first object is the *SummarizedExperiment* object containing the enrichment results, the second object contains the tissue-specificity information of the tissue-specific genes for genes from the input gene set, and the third is a *GeneSet* object containing genes that were not identified in the tissue-specific gene data.

Author(s)

Ashish Jain, Geetu Tuteja

Examples

```
library(dplyr)
data<-system.file('extdata', 'test.expressiondata.txt', package =
'TissueEnrich')
expressionData<-read.table(data,header=TRUE,row.names=1,sep='\t')
se<-SummarizedExperiment(assays = SimpleList(as.matrix(expressionData)),
rowData = row.names(expressionData),colData = colnames(expressionData))
output<-teGeneRetrieval(se)
head(metadata(output)[['TissueSpecificGenes']])
```

```

genes<-system.file('extdata', 'inputGenesEnsembl.txt', package =
'TissueEnrich')
inputGenes<-scan(genes,character())
gs<-GeneSet(geneIds=inputGenes)
output2<-teEnrichmentCustom(gs,output)
#Plotting the P-Values
enrichmentOutput<-setNames(data.frame(assay(output2[[1]]),
row.names = rowData(output2[[1]])[,1]),
colData(output2[[1]])[,1])
enrichmentOutput$Tissue<-row.names(enrichmentOutput)
ggplot(enrichmentOutput,aes(x=reorder(Tissue,-Log10PValue),y=Log10PValue,
label = Tissue.Specific.Genes,fill = Tissue))+
geom_bar(stat = 'identity')+
labs(x='', y = '-LOG10(P-Value)')+
theme_bw()+
theme(legend.position='none')+
theme(plot.title = element_text(hjust = 0.5,size = 20),axis.title =
element_text(size=15))+
theme(axis.text.x = element_text(angle = 45, vjust = 1, hjust = 1),
panel.grid.major= element_blank(),panel.grid.minor = element_blank())

```

teGeneRetrieval

Define tissue-specific genes by using the algorithm from the Human Protein Atlas

Description

The teGeneRetrieval function is used to define tissue-specific genes, using the algorithm from the HPA (Uhlén et al. 2015). It takes a gene expression SummarizedExperiment object as input (rows as genes and columns as tissue) and classifies the genes into different gene groups. The users also have the option of changing the default thresholds to vary the degree of tissue specificity of genes. More details about the gene groups and HPA thresholds are provided below. More details about the gene groups are provided in the vignette.

Usage

```

teGeneRetrieval(
  expressionData,
  foldChangeThreshold = 5,
  maxNumberOfTissues = 7,
  expressedGeneThreshold = 1
)

```

Arguments

expressionData A SummarizedExperiment object containing gene expression values.

foldChangeThreshold
A numeric Threshold of fold change, default 5.

`maxNumberOfTissues`

A numeric Maximum number of tissues in a group for group enriched genes, default 7.

`expressedGeneThreshold`

A numeric Minimum gene expression cutoff for the gene to be called as expressed, default 1.

Value

The output is a `SummarizedExperiment` object containing the information about the tissue-specific genes with three columns: Gene, Tissue, and Enrichment group of the gene in the given tissue.

Author(s)

Ashish Jain, Geetu Tuteja

Examples

```
library(SummarizedExperiment)
data<-system.file('extdata', 'test.expressiondata.txt', package =
'TissueEnrich')
expressionData<-read.table(data,header=TRUE,row.names=1,sep='\t')
se<-SummarizedExperiment(assays = SimpleList(as.matrix(expressionData)),
rowData = row.names(expressionData),colData = colnames(expressionData))
output<-teGeneRetrieval(se)
head(assay(output))
```

Index

teEnrichment, [2](#)
teEnrichmentCustom, [3](#)
teGeneRetrieval, [5](#)