

# Package ‘martini’

April 16, 2019

**Type** Package

**Title** GWAS Incorporating Networks

**Version** 1.2.0

**Maintainer** Hector Climente-Gonzalez <hector.climente@curie.fr>

**Description** martini deals with the low power inherent to GWAS studies by using prior knowledge represented as a network. SNPs are the vertices of the network, and the edges represent biological relationships between them (genomic adjacency, belonging to the same gene, physical interaction between protein products). The network is scanned using SConES, which looks for groups of SNPs maximally associated with the phenotype, that form a close subnetwork.

**License** MIT + file LICENSE

**LazyData** TRUE

**Imports** igraph (>= 1.0.1), Matrix, methods (>= 3.3.2), Rcpp (>= 0.12.8), snpStats (>= 1.20.0), S4Vectors (>= 0.12.2), stats, utils

**Suggests** biomaRt (>= 2.34.1), httr (>= 1.2.1), IRanges (>= 2.8.2), knitr, testthat, tidyverse, rmarkdown

**Depends** R (>= 3.5)

**LinkingTo** Rgin, Rcpp, RcppEigen (>= 0.3.3.3.0)

**RoxygenNote** 6.0.1

**biocViews** Software, GenomeWideAssociation, SNP, GeneticVariability, Genetics, FeatureExtraction, GraphAndNetwork, Network

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/martini>

**git\_branch** RELEASE\_3\_8

**git\_last\_commit** 803ac70

**git\_last\_commit\_date** 2018-10-30

**Date/Publication** 2019-04-15

**Author** Hector Climente-Gonzalez [aut, cre],  
Chloe-Agathe Azencott [aut]

## R topics documented:

|                                |           |
|--------------------------------|-----------|
| evo . . . . .                  | 2         |
| get_GI_network . . . . .       | 3         |
| get_GM_network . . . . .       | 4         |
| get_GS_network . . . . .       | 5         |
| ldweight_edges . . . . .       | 5         |
| minigwas . . . . .             | 6         |
| minippi . . . . .              | 6         |
| minisnpMapping . . . . .       | 7         |
| run_scones . . . . .           | 7         |
| search_cones . . . . .         | 8         |
| simulate_causal_snps . . . . . | 9         |
| simulate_phenotype . . . . .   | 9         |
| subvert . . . . .              | 10        |
| <b>Index</b>                   | <b>12</b> |

---

evo

*Run evo.*

---

### Description

Run evo.

### Usage

evo(X, Y, W, opts)

### Arguments

|      |   |
|------|---|
| X    | A matrix with the genotypes.                                    |
| Y    | A vector with the phenotypes.                                   |
| W    | A sparse matrix containing the adjacency matrix of the network. |
| opts | A named list with the settings.                                 |

### Value

An object with the evo results.

---

|                |                                      |
|----------------|--------------------------------------|
| get_GI_network | <i>Get gene-interaction network.</i> |
|----------------|--------------------------------------|

---

### Description

Creates a network of SNPs where each SNP is connected as in the **GM** network and, in addition, to all the other SNPs pertaining to any interactor of the gene it is mapped to. Corresponds to the gene-interaction (GI) network described by Azencott et al.

### Usage

```
get_GI_network(gwas, organism, snpMapping = snp2gene(gwas, organism),
  ppi = get_ppi(organism), col_ppi = c("gene1", "gene2"),
  col_genes = c("snp", "gene"))
```

### Arguments

|            |  |
|------------|--|
| gwas       | A SnpMatrix object with the GWAS information.  |
| organism   | Tax ID of the studied organism. Required if snpMapping is not provided.  |
| snpMapping | A data.frame informing how SNPs map to genes. It contains minimum two columns: SNP id and a gene it maps to. Each row corresponds to one gene-SNP mapping. Unless column names are specified using col_genes, involved columns must be named 'snp' and 'gene'. |
| ppi        | A data.frame describing protein-protein interactions with at least two columns. Gene ids must be the contained in snpMapping. Unless column names are specified using col_ppi, involved columns must be named gene1 and gene2.                                 |
| col_ppi    | Optional, length-2 character vector with the names of the two columns involving the protein-protein interactions.  |
| col_genes  | Optional, length-2 character vector with the names of the two columns involving the SNP-gene mapping. The first element is the column of the SNP, and the second is the column of the gene.  |

### Value

An igraph network of the GI network of the SNPs.

### References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

### Examples

```
get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
```

---

|                |                                     |
|----------------|-------------------------------------|
| get_GM_network | <i>Get gene membership network.</i> |
|----------------|-------------------------------------|

---

### Description

Creates a network of SNPs where each SNP is connected as in the [GS](#) network and, in addition, to all the other SNPs pertaining to the same gene. Corresponds to the gene membership (GM) network described by Azencott et al.

### Usage

```
get_GM_network(gwas, organism = 9606, snpMapping = snp2gene(gwas, organism),
  col_genes = c("snp", "gene"))
```

### Arguments

|            |  |
|------------|--|
| gwas       | A SnpMatrix object with the GWAS information.  |
| organism   | Tax ID of the studied organism. Required if snpMapping is not provided.  |
| snpMapping | A data.frame informing how SNPs map to genes. It contains minimum two columns: SNP id and a gene it maps to. Each row corresponds to one gene-SNP mapping. Unless column names are specified using col_genes, involved columns must be named 'snp' and 'gene'. |
| col_genes  | Optional, length-2 character vector with the names of the two columns involving the SNP-gene mapping. The first element is the column of the SNP, and the second is the column of the gene.  |

### Value

An igraph network of the GM network of the SNPs.

### References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

### Examples

```
get_GM_network(minigwas, snpMapping = minisnpMapping)
```

---

|                |                                      |
|----------------|--------------------------------------|
| get_GS_network | <i>Get genomic sequence network.</i> |
|----------------|--------------------------------------|

---

### Description

Creates a network of SNPs where each SNP is connected to its adjacent SNPs in the genome sequence. Corresponds to the genomic sequence (GS) network described by Azencott et al.

### Usage

```
get_GS_network(gwas)
```

### Arguments

|      |   |
|------|---|
| gwas | A SnpMatrix object with the GWAS information. |
|------|---|

### Value

An igraph network of the GS network of the SNPs.

### References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

### Examples

```
get_GS_network(minigwas)
```

---

|                |   |
|----------------|---|
| ldweight_edges | <i>Include linkage disequilibrium information in the network.</i> |
|----------------|---|

---

### Description

Include linkage disequilibrium information in the SNP network. The weight of the edges will be lower the higher the linkage is.

### Usage

```
ldweight_edges(net, ld, method = "inverse")
```

### Arguments

|        |   |
|--------|---|
| net    | A SNP network.  |
| ld     | A dsCMatrix or dgCMatrix containing linkage disequilibrium measures, like the output of <code>ld</code> . |
| method | How to incorporate linkage-disequilibrium values into the network.  |

**Value**

A copy of net where the edges weighted according to linkage disequilibrium.

**Examples**

```
ld <- snpStats::ld(minigwas[['genotypes']], depth = 2, stats = "R.squared")
# don't weight edges for which LD cannot be calculated
ld[is.na(ld)] <- 0
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
ldGi <- ldweight_edges(gi, ld)
```

---

minigwas

*Description of the minigwas dataset.*

---

**Description**

Small GWAS example.

**Format**

A list with 3 items:

**genotypes** Genotype and phenotype information.

**fam** Simulated network.

**map** Result of running find\_cones with gwas and net.

**Examples**

```
data(minigwas)

# access different elements
minigwas[["genotypes"]]
minigwas[["map"]]
minigwas[["fam"]]
```

---

minippi

*PPIs for the minigwas dataset.*

---

**Description**

data.frame describing pairs of proteins that interact for minigwas.

**Examples**

```
data(minippi)

head(minippi)
```

---

|                |  |
|----------------|--|
| minisnpMapping | <i>Genes for the minigwas dataset.</i> |
|----------------|--|

---

**Description**

data.frame that maps SNPs from minigwas to their gene.

**Examples**

```
data(minisnpMapping)
```

```
head(minisnpMapping)
```

---

|            |                   |
|------------|-------------------|
| run_scones | <i>Run shake.</i> |
|------------|-------------------|

---

**Description**

Run scones.

**Usage**

```
run_scones(c, eta, lambda, W)
```

**Arguments**

|        |   |
|--------|---|
| c      | A vector with the association of each SNP with the phenotype. |
| eta    | A numeric with the value of the eta parameter.                |
| lambda | A numeric with the value of the eta parameter.                |
| W      | A sparse matrix with the connectivity.                        |

**Value**

A list with vector indicating if the feature was selected and the objective score.

---

|              |   |
|--------------|---|
| search_cones | <i>Find connected explanatory SNPs.</i> |
|--------------|---|

---

### Description

Finds the SNPs maximally associated with a phenotype while being connected in an underlying network (Azencott et al., 2013).

### Usage

```
search_cones(gwas, net, encoding = "additive", sigmod = FALSE, ...)
```

### Arguments

|          |   |
|----------|---|
| gwas     | A SnpMatrix object with the GWAS information.   |
| net      | An igraph network that connects the SNPs.   |
| encoding | SNP encoding. Possible values: additive (default), recessive, dominant, codominant.                         |
| sigmod   | Boolean. If TRUE, use the Sigmod variant of SConES, meant to prioritize tightly connected clusters of SNPs. |
| ...      | Extra arguments for <code>get_evo_settings</code> .   |

### Value

A copy of the `SnpMatrix$map` data.frame, with the following additions:

- C: contains the univariate association score for every single SNP.
- selected: logical vector indicating if the SNP was selected by SConES or not.
- module: integer with the number of the module the SNP belongs to.

### References

Azencott, C. A., Grimm, D., Sugiyama, M., Kawahara, Y., & Borgwardt, K. M. (2013). Efficient network-guided multi-locus association mapping with graph cuts. *Bioinformatics*, 29(13), 171-179. <https://doi.org/10.1093/bioinformatics/btt238>

### Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
search_cones(minigwas, gi)
search_cones(minigwas, gi, encoding = "recessive")
search_cones(minigwas, gi, associationScore = "skat")
```



---

simulate\_causal\_snps    *Simulate causal SNPs*

---

**Description**

Selects randomly interconnected genes as causal, then selects a proportion of them as causal.

**Usage**

```
simulate_causal_snps(net, ngenes = 20, pcausal = 1)
```

**Arguments**

|         |  |
|---------|--|
| net     | An igraph gene-interaction (GI) network that connects the SNPs.                            |
| ngenes  | Number of causal genes.  |
| pcausal | Number between 0 and 1, proportion of the SNPs in causal genes that are causal themselves. |

**Value**

A vector with the ids of the simulated causal SNPs.

**Examples**

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
simulate_causal_snps(gi, ngenes=2)
```

---

simulate\_phenotype    *Simulate phenotype*

---

**Description**

Simulates a phenotype from a GWAS experiment and a specified set of causal SNPs. If the data is qualitative, only controls are used.

**Usage**

```
simulate_phenotype(gwas, snps, h2, model = "additive",
  effectSize = rnorm(length(snps)), qualitative = FALSE, ncases, ncontrols,
  prevalence)
```

**Arguments**

|       |  |
|-------|--|
| gwas  | A SnpMatrix object with the GWAS information.  |
| snps  | Character vector with the SNP ids of the causal SNPs. Must match SNPs in gwas[["map"]][["snp.names"]]. |
| h2    | Heritability of the phenotype (between 0 and 1).   |
| model | String specifying the genetic model under the phenotype. Accepted values: "additive".                  |

|             |  |
|-------------|--|
| effectSize  | Numeric vector with the same length as the number of causal SNPs. It indicates the effect size of each of the SNPs; if absent, they are sampled from a normal distribution.        |
| qualitative | Bool indicating if the phenotype is qualitative or not (quantitative).   |
| ncases      | Integer specifying the number of cases to simulate in a qualitative phenotype. Required if qualitative = TRUE.   |
| ncontrols   | Integer specifying the number of controls to simulate in a qualitative phenotype. Required if qualitative = TRUE.  |
| prevalence  | Value between 0 and 1 specifying the population prevalence of the disease. Note that ncases cannot be greater than prevalence * number of samples. Required if qualitative = TRUE. |

### Value

A copy of the GWAS experiment with the new phenotypes in `gwas[["fam"]][["affected"]]`.

### References

Inspired from GCTA simulation tool: <http://cnsgenomics.com/software/gcta/Simu.html>.

### Examples

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
causal <- simulate_causal_snps(gi, ngenes = 2)
simulate_phenotype(minigwas, causal, h2 = 1)
```

---

|         |                                   |
|---------|-----------------------------------|
| subvert | <i>Vertices with an attribute</i> |
|---------|-----------------------------------|

---

### Description

Returns the nodes matching some condition.

### Usage

```
subvert(net, attr, values, affirmative = TRUE)
```

### Arguments

|             |   |
|-------------|---|
| net         | An igraph network.  |
| attr        | An attribute of the vertices.   |
| values      | Possible values of attr   |
| affirmative | Logical. States if a condition must be its affirmation (e.g. all nodes with gene name "X"), or its negation (all nodes not with gene name "X"). |

### Value

The vertices with attribute equal to any of the values in values.

**Examples**

```
gi <- get_GI_network(minigwas, snpMapping = minisnpMapping, ppi = minippi)
martini::subvert(gi, "gene", "A")
martini::subvert(gi, "name", c("1A1", "1A3"))
```

# Index

evo, [2](#)

get\_evo\_settings, [8](#)

get\_GI\_network, [3](#)

get\_GM\_network, [4](#)

get\_GS\_network, [5](#)

GM, [3](#)

GS, [4](#)

ld, [5](#)

ldweight\_edges, [5](#)

minigwas, [6](#)

minippi, [6](#)

minisnpMapping, [7](#)

run\_scones, [7](#)

search\_cones, [8](#)

simulate\_causal\_snps, [9](#)

simulate\_phenotype, [9](#)

subvert, [10](#)