

tigre User Guide

Antti Honkela, Pei Gao,

Jonatan Ropponen, Miika-Petteri Matikainen,
Magnus Rattray, and Neil D. Lawrence

November 3, 2024

1 Abstract

The *tigre* package implements our methodology of Gaussian process differential equation models for analysis of gene expression time series from single input motif networks. The package can be used for inferring unobserved transcription factor (TF) protein concentrations from expression measurements of known target genes, or for ranking candidate targets of a TF.

2 Citing *tigre*

The *tigre* package is based on a body of methodological research. Citing *tigre* in publications will usually involve citing one or more of the methodology papers [1, 2, 3] that the software is based on as well as citing the software package itself [4].

3 Introductory example analysis - Drosophila development

In this section we introduce the main functions of the *puma* package by repeating some of the analysis from the PNAS paper [1]¹.

3.1 Installing the *tigre* package

The recommended way to install *tigre* is to use the `BiocManager::install` function. Installing in this way should ensure that all appropriate dependencies are met.

```
> if (!requireNamespace("BiocManager", quietly=TRUE))
+   install.packages("BiocManager")
> BiocManager::install("tigre")
```

To load the package start R and run

```
> library(tigre)
```

¹Note that the results reported in the paper were run using an earlier version of this package for MATLAB, so there can be minor differences.

3.2 Loading the data

To get started, you need some preprocessed time series expression data. If the data originates from Affymetrix arrays, we highly recommend processing it with `mmgmos` from the *puma* package. This processing extracts error bars on the expression measurements directly from the array data to allow judging the reliability of individual measurements. This information is directly utilised by all the models in this package.

To start from scratch on Affymetrix data, the .CEL files from ftp://ftp.fruitfly.org/pub/embryo_tc_array_data/ may be processed using:

```
> # Names of CEL files
> expfiles <- c(paste("embryo_tc_4_", 1:12, ".CEL", sep=""),
+             paste("embryo_tc_6_", 1:12, ".CEL", sep=""),
+             paste("embryo_tc_8_", 1:12, ".CEL", sep=""))
> # Load the CEL files
> expdata <- ReadAffy(filename=expfiles,
+                   celfile.path="embryo_tc_array_data")
> # Setup experimental data (observation times)
> pData(expdata) <- data.frame("time.h" = rep(1:12, 3),
+                             row.names=row.names(pData(expdata)))
> # Run mmgMOS processing (requires several minutes to complete)
> drosophila_mmgmos_exprs <- mmgmos(expdata)
> drosophila_mmgmos_fragment <- drosophila_mmgmos_exprs
```

This data needs to be further processed to make it suitable for our models. This can be done using

```
> drosophila_gpsim_fragment <-
+   processData(drosophila_mmgmos_fragment,
+             experiments=rep(1:3, each=12))
```

Here the last argument specifies that we have three independent time series of measurements.

In order to save time with the demos, a part of the result of this is included in this package and can be loaded using

```
> data(drosophila_gpsim_fragment)
```

3.3 Learning individual models

Let us now recreate some the models shown in the plots of the PNAS paper [1]:

```
> # FBgn names of target genes
> targets <- c('FBgn0003486', 'FBgn0033188', 'FBgn0035257')
> # Load gene annotations
> library(annotate)
> aliasMapping <- getAnnMap("ALIAS2PROBE",
+                          annotation(drosophila_gpsim_fragment))
> # Get the probe identifier for TF 'twi'
> twi <- get('twi', env=aliasMapping)
> # Load alternative gene annotations
> fbgnMapping <- getAnnMap("FLYBASE2PROBE",
```

```
+               annotation(drosophila_gpsim_fragment))
> # Get the probe identifiers for target genes
> targetProbes <- mget(targets, env=fbgnMapping)
> st_models <- list()
> # Learn single-target models for each gene individually
> for (i in seq(along=targetProbes)) {
+   st_models[[i]] <- GPLearn(drosophila_gpsim_fragment,
+                             TF=twi, targets=targetProbes[i],
+                             quiet=TRUE)
+ }
> # Learn a joint model for all targets
> mt_model <- GPLearn(drosophila_gpsim_fragment, TF=twi,
+                     targets=targetProbes,
+                     quiet=TRUE)
> # Display the joint model parameters
> show(mt_model)
```

Gaussian process driving input single input motif model:

Number of time points:

Driving TF: 143396_at

Target genes (3):

148227_at

152715_at

147995_at

Basal transcription rate:

Gene 1: 0.00980051910022401

Gene 2: 0.00383779938679504

Gene 3: 4.79623507239605e-05

Kernel:

Multiple output block kernel:

Block 1

Normalised version of the kernel.

RBF inverse width: 0.7966685 (length scale 1.120369)

RBF variance: 1.666141

Block 2

Normalised version of the kernel

DISIM decay: 0.04116827

DISIM inverse width: 0.7966685 (length scale 1.120369)

DISIM Variance: 1

SIM decay: 104.8845

SIM Variance: 0.242455

RBF Variance: 1.666141

Block 3

Normalised version of the kernel

DISIM decay: 0.04116827

DISIM inverse width: 0.7966685 (length scale 1.120369)

DISIM Variance: 1

SIM decay: 0.7277987

SIM Variance: 0.05243276

RBF Variance: 1.666141

Block 4

```

    Normalised version of the kernel
    DISIM decay: 0.04116827
    DISIM inverse width: 0.7966685 (length scale 1.120369)
    DISIM Variance: 1
    SIM decay: 0.04113816
    SIM Variance: 0.003927488
    RBF Variance: 1.666141
    Log-likelihood: -39.93574

> # Learn a model without TF mRNA and TF protein translation
> nt_model <- GPLearn(drosophila_gpsim_fragment,
+                     targets=c(twi, targetProbes[1:2]), quiet=TRUE)

```

3.4 Visualising the models

The models can be plotted using commands like

```

> GPPlot(st_models[[1]], nameMapping=getAnnMap("FLYBASE",
+       annotation(drosophila_gpsim_fragment)))
> GPPlot(mt_model, nameMapping=getAnnMap("FLYBASE",
+       annotation(drosophila_gpsim_fragment)))
> GPPlot(nt_model, nameMapping=getAnnMap("FLYBASE",
+       annotation(drosophila_gpsim_fragment)))

```

3.5 Ranking the targets

Bulk ranking of candidate targets can be accomplished using

```

> ## Rank the targets, filtering weakly expressed genes with average
> ## expression z-score below 1.8
> scores <- GPRankTargets(drosophila_gpsim_fragment, TF=twi,
+       testTargets=targetProbes,
+       options=list(quiet=TRUE),
+       filterLimit=1.8)
> ## Sort the returned list according to log-likelihood
> scores <- sort(scores, decreasing=TRUE)
> write.scores(scores)

"log-likelihood" "null_log-likelihood"
"147995_at" 6.75946931727033 -487.893231050121
"152715_at" -1.51410183648596 -539.73619673943
"148227_at" -1.54140712861999 -73.4806804255218

```

To save space, `GPRankTargets` does not return the models by default. If those are needed later e.g. for plotting, they can be recreated using the inferred parameters saved together with the ranking using

```

> topmodel <- generateModels(drosophila_gpsim_fragment,
+       scores[1])
> show(topmodel)

[[1]]

```




Figure 1: Single target models for the gene FBgn0003486. The models for each repeated time series are shown in different columns.

```
Gaussian process driving input single input motif model:
Number of time points:
Driving TF: 143396_at
Target genes (1):
147995_at
Basal transcription rate:
Gene 1: 0.000135085495634398
Kernel:
Multiple output block kernel:
Block 1
Normalised version of the kernel.
RBF inverse width: 0.7607524 (length scale 1.146511)
RBF variance: 1.808364
Block 2
Normalised version of the kernel
DISIM decay: 0.01865922
DISIM inverse width: 0.7607524 (length scale 1.146511)
DISIM Variance: 1
```




Figure 2: Multiple-target model for all the example genes. The call creates independent figures for each repeated time series.

```
SIM decay: 0.01945663
SIM Variance: 0.002734328
RBF Variance: 1.808364
Log-likelihood: 6.759469
```

3.6 Ranking using known targets with multiple-target models

Ranking using known targets with multiple-target models can be accomplished simply by adding the `knownTargets` argument

```
> ## Rank the targets, filtering weakly expressed genes with average
> ## expression z-score below 1.8
> scores <- GPRankTargets(drosophila_gpsim_fragment, TF=twi,
+                         knownTargets=targetProbes[1],
+                         testTargets=targetProbes[2:3],
+                         options=list(quiet=TRUE),
+                         filterLimit=1.8)
> ## Sort the returned list according to log-likelihood
```




Figure 3: Multiple-target model without TF protein translation for selected example genes without. The call creates independent figures for each repeated time series.

```
> scores <- sort(scores, decreasing=TRUE)
> write.scores(scores)

"log-likelihood" "null_log-likelihood"
"152715_at" -28.1152693318211 -539.73619673943
"147995_at" -240.41960980211 -487.893231050121
```

3.7 Running ranking in a batch environment

GPRankTargets can be easily run in a batch environment using the argument `scoreSaveFile`. This indicates a file to which scores are saved after processing each gene. Thus one could, for example, split the data to, say, 3 separate blocks according to the remainder after division by 3 and run each of these independently. The first for loop could then be run in parallel (e.g. as separate jobs on a cluster), as each step is independent of the others. After these have all completed, the latter loop could be used to gather the results.

```
> for (i in seq(1, 3)) {
+   targetIndices <- seq(i,
```

```

+   length(featureNames(drosophila_gpsim_fragment)), by=3)
+   outfile <- paste('ranking_results_', i, '.Rdata', sep='')
+   scores <- GPrankTargets(preprocData, TF=twi,
+                           testTargets=targetIndices,
+                           scoreSaveFile=outfile)
+ }
> for (i in seq(1, 3)) {
+   outfile <- paste('ranking_results_', i, '.Rdata', sep='')
+   load(outfile)
+   if (i==1)
+     scores <- scoreList
+   else
+     scores <- c(scores, scoreList)
+ }
> show(scores)

```

4 Experimental feature: Using non-Affymetrix data

Using non-Affymetrix data, or data without associated uncertainty information for the expression data in general, requires more because of two reasons

- noise variances need to be estimated together with other model parameters; and
- weakly expressed genes cannot be easily filtered *a priori*.

The first of these is automatically taken care of by all the above functions, but the latter requires some extra steps after fitting the models.

In order to get started, you need to create an `ExpressionTimeSeries` object of your data set. This can be accomplished with the function

```

> procData <- processRawData(data, times=c(...),
+                             experiments=c(...))

```

Filtering of weakly expressed genes requires more care and visualising the fitted models is highly recommended to avoid mistakes.

Based on initial experiments, it seems possible to perform the filtering based on the statistic `loglikelihoods(scores) - baseloglikelihoods(scores)`, but selection of suitable threshold is highly dataset specific.

5 Exporting results to an SQLite database

The results of the analysis can be stored to an SQLite database. The database can then be browsed and queried using the `tigreBrowser` result browser. The data is inserted to the database by using `export.scores` function.

An example of the usage of `export.scores` is given below

```

> export.scores(scores, datasetName='Drosophila',
+               experimentSet='GPSIM/GPDISIM',
+               database='database.sqlite',

```



```
+      preprocData=drosophila_gpsim_fragment,
+      models=models,
+      aliasTypes=c('SYMBOL', 'GENENAME', 'FLYBASE', 'ENTREZID'))
```

In this example, `scores` is the return value of `GPRankTargets`, `'Drosophila'` is the name of a dataset in database and `'GPSIM/GPDISIM'` is the name of an experiment set in database. In general, results with the same dataset name are considered to be part of same dataset. That is, if no results with a given dataset are already in the database, a new dataset entry is created. On the other hand, if the database already contains results with the same dataset name, new results will be added to the old dataset.

Also, results from different experiments can be combined into a set of experiments by giving them the same experiment set name. This is useful as a result browser may display results depending on the experiment set.

`database.sqlite` is the filename of a database file. The file will be created if it does not exist already.

The function will create model figures and add them to the database if preprocessed data is given. In this example, models are given to the function as a parameter. This is not necessary, however, as the function can create models if preprocessed data is supplied. Nevertheless, the function will finish faster if it does not have to (re-)create models.

In addition to log likelihoods and z-scores, this function will also export different gene names and aliases to the database. By default, the function will read GENENAME, SYMBOL and ENTREZID datas from relevant annotations and insert those into the database. The function takes also `aliasTypes` argument which is used to define which annotation information is inserted. In the example above, FLYBASE gene numbers are also added to the genes in the database. The insertion of alias annotations and z-scores requires that the preprocessed data is supplied.

6 Session Info

```
> sessionInfo()

R Under development (unstable) (2024-10-26 r87273 ucrt)
Platform: x86_64-w64-mingw32/x64
Running under: Windows Server 2022 x64 (build 20348)

Matrix products: default

locale:
 [1] LC_COLLATE=C
 [2] LC_CTYPE=English_United States.utf8
 [3] LC_MONETARY=English_United States.utf8
 [4] LC_NUMERIC=C
 [5] LC_TIME=English_United States.utf8

time zone: America/New_York
tzcode source: internal
```

```
attached base packages:
[1] stats4      stats      graphics  grDevices  utils
[6] datasets    methods    base

other attached packages:
[1] drosgenome1.db_3.13.0  org.Dm.eg.db_3.20.0
[3] annotate_1.85.0        XML_3.99-0.17
[5] AnnotationDbi_1.69.0   IRanges_2.41.0
[7] S4Vectors_0.45.0       tigre_1.61.0
[9] Biobase_2.67.0         BiocGenerics_0.53.1
[11] generics_0.1.3

loaded via a namespace (and not attached):
[1] bit_4.5.0              jsonlite_1.8.9
[3] BiocStyle_2.35.0        compiler_4.5.0
[5] BiocManager_1.30.25     crayon_1.5.3
[7] gtools_3.9.5            blob_1.2.4
[9] bitops_1.0-9           Biostrings_2.75.0
[11] png_0.1-8              yaml_2.3.10
[13] fastmap_1.2.0          R6_2.5.1
[15] XVector_0.47.0         GenomeInfoDb_1.43.0
[17] knitr_1.48             GenomeInfoDbData_1.2.13
[19] DBI_1.2.3              rlang_1.1.4
[21] KEGGREST_1.47.0        cachem_1.1.0
[23] xfun_0.49              caTools_1.18.3
[25] bit64_4.5.2            RSQLite_2.3.7
[27] memoise_2.0.1          cli_3.6.3
[29] zlibbioc_1.53.0        digest_0.6.37
[31] xtable_1.8-4           vctrs_0.6.5
[33] KernSmooth_2.23-24     evaluate_1.0.1
[35] rmarkdown_2.28         httr_1.4.7
[37] pkgconfig_2.0.3        gplots_3.2.0
[39] UCSC.utils_1.3.0       tools_4.5.0
[41] htmltools_0.5.8.1
```

References

- [1] Antti Honkela, Charles Girardot, E. Hilary Gustafson, Ya-Hsin Liu, Eileen E M Furlong, Neil D Lawrence, and Magnus Rattray. Model-based method for transcription factor target identification with limited data. *Proc Natl Acad Sci U S A*, 107(17):7793–7798, Apr 2010. URL: <http://dx.doi.org/10.1073/pnas.0914285107>, doi:10.1073/pnas.0914285107.
- [2] Pei Gao, Antti Honkela, Magnus Rattray, and Neil D Lawrence. Gaussian process modelling of latent chemical species: applications to inferring transcription factor activities. *Bioinformatics*, 24(16):i70–i75, Aug 2008. URL: <http://dx.doi.org/10.1093/bioinformatics/btn278>, doi:10.1093/bioinformatics/btn278.

- [3] Neil D. Lawrence, Guido Sanguinetti, and Magnus Rattray. Modelling transcriptional regulation using Gaussian processes. In B. Schölkopf, J. C. Platt, and T. Hofmann, editors, *Advances in Neural Information Processing Systems*, volume 19, pages 785–792. MIT Press, Cambridge, MA, 2007.
- [4] Antti Honkela, Pei Gao, Jonatan Ropponen, Magnus Rattray, and Neil D Lawrence. tigre: Transcription factor inference through gaussian process reconstruction of expression for bioconductor. *Bioinformatics*, 27(7):1026–1027, Apr 2011. URL: <http://dx.doi.org/10.1093/bioinformatics/btr057>, doi:10.1093/bioinformatics/btr057.