

Package ‘SRADB’

May 2, 2025

Type Package

Title A compilation of metadata from NCBI SRA and tools

Version 1.71.0

Date 2024-12-03

Depends RSQLite, graph, RCurl

Imports R.utils

Suggests Rgraphviz

Author Jack Zhu and Sean Davis

Maintainer Jack Zhu <zhujack@mail.nih.gov>

Description The Sequence Read Archive (SRA) is the largest public repository of sequencing data from the next generation of sequencing platforms including Roche 454 GS System, Illumina Genome Analyzer, Applied Biosystems SOLiD System, Helicos Heliscope, and others. However, finding data of interest can be challenging using current tools. SRADB is an attempt to make access to the metadata associated with submission, study, sample, experiment and run much more feasible. This is accomplished by parsing all the NCBI SRA metadata into a SQLite database that can be stored and queried locally. Fulltext search in the package make querying metadata very flexible and powerful. fastq and sra files can be downloaded for doing alignment locally. Beside ftp protocol, the SRADB has functions supporting fastp protocol (ascp from Aspera Connect) for faster downloading large data files over long distance. The SQLite database is updated regularly as new data is added to SRA and can be downloaded at will for the most up-to-date metadata.

License Artistic-2.0

LazyLoad yes

BugReports <https://github.com/zhujack/SRADB/issues/new>

biocViews Infrastructure, Sequencing, DataImport

git_url <https://git.bioconductor.org/packages/SRADB>

git_branch devel

git_last_commit dfcc6bc

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-05-01

Contents

SRADB-package	2
ascpR	4
ascpSRA	6
colDescriptions	7
entityGraph	8
getFASTQfile	9
getFASTQinfo	10
getSRA	11
getSRADBFile	13
getSRAfile	14
getSRAinfo	15
IGVclear	16
IGVcollapse	17
IGVgenome	18
IGVgoto	18
IGVload	19
IGVsession	20
IGVsnapshot	21
IGVsocket	22
IGVsort	23
listSRAfile	23
sraConvert	24
sraGraph	25
startIGV	27
Index	28

SRADB-package

Query NCBI SRA metadata within R or from a local SQLite database

Description

The Sequence Read Archive (SRA) represents largest public repository of sequencing data from the next generation of sequencing platforms including Roche 454 GS System, Illumina Genome Analyzer, Applied Biosystems SOLiD System, Helicos Heliscope, and others. However, finding data of interest can be challenging using current tools. SRADB is an attempt to make access to the metadata associated with submission, study, sample, experiment and run much more feasible. This is accomplished by parsing all the NCBI SRA metadata into a SQLite database that can be stored and queried locally. SRADB is simply a thin wrapper around the SQLite database along with associated tools and documentation. Fulltext search in the package make querying metadata very flexible and powerful. SRA data files (sra or sra-lite) can be downloaded for doing alignment locally. Available BAM files in local or in the Meltzerlab sraDB can be loaded into IGV for visualization easily. The SQLite database is updated regularly as new data is added to SRA and can be downloaded at will for the most up-to-date metadata.

Details

Package:	SRADB
Type:	Package
Date of creation:	2012-02-13
License:	What license is it under?
LazyLoad:	yes

Author(s)

Jack Zhu and Sean Davis

Maintainer: Jack Zhu <zhujack@mail.nih.gov>

References

<https://s3.amazonaws.com/starbuck1/sradb/SRAmetadb.sqlite.gz> <https://gbnci-abcc.ncifcrf.gov/backup/SRAmetadb.sqlite.gz>

Examples

```
## Using the SRAmetadb demo database

library(SRADb)
sra_dbname <- file.path(system.file('extdata', package='SRADB'), 'SRAmetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)

## Get column descriptions
a <- colDescriptions(sra_con=sra_con)[1:5,]

## Convert SRA experiment accessions to other types
b <- sraConvert( in_acc=c(" SRR000137", "SRR000138 "), out_type=c('sample'), sra_con=sra_con )

## Fulltext search SRA meta data using SQLite fts3 module
rs <- getSRA (search_terms='breas* NEAR/2 can*', out_types=c('run','study'), sra_con=sra_con)
rs <- getSRA (search_terms='breast', out_types=c('run','study'), sra_con=sra_con)
rs <- getSRA (search_terms='"breas* can*"', out_types=c('study'), sra_con=sra_con)
rs <- getSRA (search_terms='MCF7 OR "MCF-7"', out_types=c('sample'), sra_con=sra_con)
rs <- getSRA (search_terms='study_title: brea* can*', out_types=c('run','study'), sra_con=sra_con)
rs <- getSRA (search_terms='study_title: brea* can*', out_types=c('run','study'), sra_con=sra_con, acc_onl

## List fastq file ftp or fasp addresses associated with "SRX000122"
listSRAfile (in_acc = c("SRX000122"), sra_con = sra_con, fileType = 'sra')
listSRAfile (in_acc = c("SRX000122"), sra_con = sra_con, fileType = 'sra', srcType='fasp')

## Get file size and date from NCBI ftp site for available fastq files associated with "SRS012041","SRS000290"
## Not run:
getSRAinfo (in_acc=c("SRS012041","SRS000290"), sra_con=sra_con, sraType='sra')

## End(Not run)

## Download sra files from NCBI SRA using ftp protocol:
## Not run:
getSRAfile( in_acc = c("SRR000648","SRR000657"), sra_con = sra_con, destDir = getwd(), fileType = 'sra' )
```

```

    ## Download fastq files from EBI using ftp protocol:
    getSRAfile( in_acc, sra_con, destDir = getwd(), fileType = 'fastq', srcType = 'ftp', makeDirectory = FALSE, m

## End(Not run)

    ## Download fastq files from EBI ftp siteusing fasp protocol:
    ## Not run:
    ascpCMD <- 'ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty'
    getSRAfile( in_acc, sra_con, fileType = 'fastq', srcType = 'fasp', ascpCMD = ascpCMD )
## End(Not run)

    ## Start IGV from R if no IGV running
    ## Not run: startIGV(memory='mm')

    ## load BAM files to IGV
    ## Not run:
    exampleBams = file.path(system.file('extdata',package='SRADB'), dir(system.file('extdata',package='SRADB')
    sock <- IGVsocket()
    IGVload(sock,exampleBams)

## End(Not run)
    ## Change the IGV genome
    ## Not run:
    IGVgenome(sock,genome='hg18')

## End(Not run)
    ## Go to a specified region in IGV
    ## Not run:
    IGVgoto(sock,'chr1:1-10000')
    IGVgoto(sock,'TP53')

## End(Not run)

    ## Make a snapshot of the current IGV window
    ## Not run:
    IGVsnapshot(sock)
    dir()

## End(Not run)

    ## create a graphNEL object from SRA accessions, which are full text search results of terms 'primary thyroid
    g <- sraGraph('MCF7 OR "MCF-7"', sra_con)

    ## Not run:
    library(Rgraphviz)
    attrs <- getDefaultAttrs(list(node=list(fillcolor='lightblue', shape='ellipse')))
    plot(g, attrs=attrs)

## End(Not run)
    dbDisconnect(sra_con)

    ## The actual SRAMetadb sqlite database can be downloaded using function: getSRADBFile. Warning: the actual SRA

```

Description

This function downloads files by fasp protocol using Aspera's ascp command line program, which is included in Aspera Connect software (<http://www.asperasoft.com/>).

Usage

```
ascpR( ascpCMD, ascpSource, destDir = getwd() )
```

Arguments

ascpCMD	ascp main commands, which should be constructed by a user according to the actual installation of Aspera Connect in the system, with proper options to be used. Example commands: "ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty" (Linux) or ""'/Applications/Aspera Connect.app/Contents/Resources/ascp' -QT -l 300m -i '/Applications/Aspera Connect.app/Contents/Resources/asperaweb_id_dsa.putty'" (Mac OS X). More about ascp please see the help ('ascp -h' in a shell).
ascpSource	character vector of fasp file sources for the ascp command, e.g. era-fasp@fasp.sra.ebi.ac.uk:vol1/fastq (EBI), anonftp@ftp-trace.ncbi.nlm.nih.gov:/sra/sra-instant/reads/ByExp/sra/SRX/SRX000/SRX0001 (NCBI).
destDir	destination directory to save downloaded files.

Details

The function takes advantage of Aspera's fasp transport technology (<http://www.asperasoft.com/>), which provides high-speed transferring large files over the Internet. Due to complexity with options with ascp and installation difference between different systems, this function asks users to supply main ascp commands. Users who are not familiar with ascp command line program should have IT support personnel to install the software and construct main ascp commands.

Value

A data.frame containing all matched SRA accessions and ftp or fasp addresses.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

References

<http://www.asperasoft.com/>

See Also

[ascpSRA](#), [getSRAfile](#), [getFASTQinfo](#), [getSRAinfo](#)

Examples

```
## Using the SRAMetadb demo database
## Not run:
library( SRADB )
sra_dbname <- file.path(system.file('extdata', package='SRADB'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)
rs <- getFASTQinfo (in_acc=c("SRR000648", "SRR000657"), sra_con, srcType='fasp')
```

```

ascpSource <- rs$fasp
ascpCMD <- 'ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty'
## common ascpCMD in Mac OS X:
#ascpCMD = "'/Applications/Aspera Connect.app/Contents/Resources/ascp' -QT -l 300m -i '/Applications/Aspera C

ascpR( ascpCMD, ascpSource, destDir = getwd() )
dbDisconnect( sra_con )

## End(Not run)

## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA

```

ascpSRA

Fasp SRA data file downloading using the ascp command line program

Description

This function downloads SRA data files (fastq, sra) by fasp protocol using Aspera's ascp command line program, which is included in Aspera Connect software (<http://www.asperasoft.com/>).

Usage

```
ascpSRA ( in_acc, sra_con, ascpCMD, fileType = 'sra', destDir = getwd() )
```

Arguments

in_acc	character vector of SRA accessions, which should be in same SRA data type, either submission, study, sample, experiment or run.
sra_con	connection to the SRAMetadb SQLite database.
ascpCMD	ascp main commands, which should be constructed by a user according to the actual installation of Aspera Connect in the system, with proper options to be used. Example commands: "ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty" (Linux) or "'/Applications/Aspera Connect.app/Contents/Resources/ascp' -QT -l 300m -i '/Applications/Aspera Connect.app/Contents/Resources/asperaweb_id_dsa.putty'" (Mac OS X). More about ascp please see the help ('ascp -h' in a shell).
fileType	type of SRA data files, which should be "sra", or "fastq" ('litesra' has phased out).
destDir	destination directory to save downloaded files.

Details

This function will get fasp file sources first using function [listSRAfile](#) and then download data files using function [ascpR](#).

Value

A data.frame of all matched SRA accessions and ftp or fasp file addresses.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

References

<http://www.asperasoft.com/>

See Also

[ascpR](#), [listSRAfile](#), [getSRAfile](#), [getFASTQinfo](#), [getSRAinfo](#)

Examples

```
## Using the SRAMetadb demo database
## Not run:
library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')

sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)
in_acc <- c("SRR000648", "SRR000657")
ascpCMD <- 'ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty'
## common ascpCMD for a system with Mac OS X:
#ascpCMD <- "'/Applications/Aspera Connect.app/Contents/Resources/ascp' -QT -l 300m -i '/Applications/Aspera

sraFiles <- ascpSRA( in_acc, sra_con, ascpCMD, fileType = 'sra', destDir=getwd() )
dbDisconnect(sra_con)

## End(Not run)
## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

colDescriptions

Get column descriptions of SRAMetadb.sqlite

Description

Get column descriptions of SRAMetadb.sqlite, including table, field, field data type, description and default values

Usage

```
colDescriptions( sra_con )
```

Arguments

sra_con Connection of the SRAMetadb SQLite database

Value

A seven-column data.frame including table_name, field_name, type, description, value_list.

Author(s)

Jack Zhu<zhujack@mail.nih.gov> and Sean Davis <sdavis2@mail.nih.gov>

Examples

```
## Using the SRAMetadb demo database

library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)

## Get column descriptions
a <- colDescriptions(sra_con=sra_con)[1:5,]

## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

entityGraph	<i>Create a new graphNEL object from an input entity matrix or data.frame</i>
-------------	---

Description

This function will create a new graphNEL object from an input entity matrix or data.frame

Usage

```
entityGraph(df)
```

Arguments

df	A matrix or data.frame
----	------------------------

Details

A graphNEL object with edgemode='directed' is created from input data.frame and the [plot](#) function will draw a graph

Value

A graphNEL object with edgemode='directed'

Author(s)

Jack Zhu <zhujack@mail.nih.gov> and Sean Davis <sdavis2@mail.nih.gov>

See Also

[getSRA](#), [sraConvert](#), [sraGraph](#)

Examples

```
## Using the SRAMetadb demo database

library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)

## create a graphNEL object from SRA accessions, which are full text search results of terms 'primary thyroid ce
acc <- getSRA (search_terms = 'MCF7 OR "MCF-7"', out_types=c('sra'), sra_con=sra_con, acc_only=TRUE)
g <- entityGraph(acc)
## Not run:
library(Rgraphviz)
attrs <- getDefaultAttrs(list(node=list(fillcolor='lightblue', shape='ellipse'))))
plot(g, attrs= attrs)

## End(Not run)

## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

getFASTQfile

Download SRA fastq files from EBI ENA through ftp or fasp

Description

This function downloads SRA fastq data files through ftp or fasp from EBI ENA site for a given list of SRA accessions.

Usage

```
getFASTQfile( in_acc, sra_con, destDir = getwd(), srcType = 'ftp', makeDirectory = FALSE, method = 'c
```

Arguments

<code>in_acc</code>	character vector of SRA accessions that could be be in one or more SRA sata types: study, sample, experiment and/or run.
<code>sra_con</code>	connection to the SRAMetadb SQLite database
<code>destDir</code>	destination directory to save downloaded fastq files
<code>srcType</code>	type of transfer protocol, which should be "ftp" or "fasp".
<code>makeDirectory</code>	logical, TRUE or FALSE. If TRUE and baseDir does not exists, storedir will be created to save downloaded files, otherwise downloaded fastq files will be saved to current directory.
<code>method</code>	character vector of length 1, passed to the identically named argument of download.file .
<code>ascpCMD</code>	ascp main commands, which should be constructed by a user according to the actual installation of Aspera Connect in the system, with proper options to be used. Example commands: "ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty" (Linux) or ""/Applications/Aspera Connect.app/Contents/Resources/ascp" -QT -l 300m -i "/Applications/Aspera Connect.app/Contents/Resources/asperaweb_id_dsa.putty"" (Mac OS X). More about ascp please see the help ('ascp -h' in a shell).

Details

The function first gets ftp/fasp addresses of SRA fastq files using function `getFASTQinfo` for a given list of input SRA accessions; then downloads the fastq files through ftp or fasp.

Warning

Downloading SRA fastq files through ftp over long distance could take long time and should consider using using 'fasp'.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

See Also

`getFASTQinfo`, `getSRAfile`, `ascpR`

Examples

```
## Using the SRAMetadb demo database

## Not run:
library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect( dbDriver("SQLite"), sra_dbname )

## Download fastq files from EBI ENA through ftp
getFASTQfile( in_acc = c("SRR000648", "SRR000657"), sra_con, destDir = getwd(), srcType = 'ftp', ascpCMD = NULL )

## Download fastq files from EBI ENA through fasp
ascpCMD <- 'ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty'
## common ascpCMD for a system with Mac OS X:
#ascpCMD <- "'/Applications/Aspera Connect.app/Contents/Resources/ascp' -QT -l 300m -i '/Applications/Aspera'
getFASTQfile( in_acc = c("SRR000648", "SRR000657"), sra_con, srcType='fasp', ascpCMD=ascpCMD )

dbDisconnect( sra_con )

## End(Not run)

## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

getFASTQinfo

Get SRA fastq file information and associated meta data from EBI ENA

Description

This function gets SRA fastq file information and essential associated meta data from EBI ENA web site (http://www.ebi.ac.uk/ena/data/view/reports/sra/fastq_files/) for SRA accessions given.

Usage

```
getFASTQinfo( in_acc, sra_con, srcType = 'ftp' )
```

Arguments

<code>in_acc</code>	character vector of SRA accessions that could be in one or more SRA data types: study, sample, experiment and/or run.
<code>sra_con</code>	Connection to the SRAMetadb SQLite database
<code>srcType</code>	option for listing either 'ftp' or 'fasp' addresses. The default is 'ftp'.

Details

EBI ENA web site (http://www.ebi.ac.uk/ena/data/view/reports/sra/fastq_files/) is the source for parsing information from, which is updated and verified daily. Ftp or fasp addresses got from this function can be used in either [getFASTQfile](#) or [getSRAfile](#) to download the files.

Value

A data.frame of ftp/fasp information (addresses, file size, read number, etc) and associated meta data (study, sample, experiment, run, organism, instrument.platform, instrument.model, library.name, library.layout, library.source, library.selection, run.read.count, run.base.count, etc.).

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

See Also

[getFASTQfile](#), [listSRAfile](#), [getSRAfile](#)

Examples

```
## Using the SRAMetadb demo database
## Not run:
library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)
getFASTQinfo( in_acc = c("SRR000648","SRR000657"), sra_con, srcType = 'ftp' )
getFASTQinfo( in_acc = c("SRR000648","SRR000657"), sra_con, srcType = 'fasp' )
```

```
## End(Not run)
```

```
## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

getSRA

Fulltext search SRA meta data using SQLite fts3 module

Description

This function does Fulltext search on any SRA fields in any SRA data types with Fulltext capacity in the SQLite and returns SRA records

Usage

```
getSRA(search_terms, out_types=c('sra','submission','study','experiment','sample','run'), sra_con
```

Arguments

<code>search_terms</code>	Free text search terms constructed according to SQLite query syntax defined here: http://www.sqlite.org/fts3.html#section_1_3
<code>out_types</code>	Character vector of the following SRA data types: 'sra','submission','study','sample','experiment','run'. Note: if 'sra' is within <code>out_types</code> , the <code>out_types</code> will be set to <code>c('submission','study','sample','experiment')</code>
<code>sra_con</code>	Connection to the SRAMetadb SQLite database
<code>acc_only</code>	logical, if TRUE, the function will return SRA accession for each <code>out_types</code>

Details

Queries performed by this function could be Phrase queries, e.g. `"lin* app*"`, or NEAR queries, e.g. `"ACID compliant" NEAR/2 sqlite`, or with the Enhanced Query Syntax. Check Full Text Search section on the SQLite site for details. if `'acc_only=TRUE'`, a `data.frame` containing only SRA accessions will be returned, which can be used as input for [sraGraph](#).

Value

A `data.frame` containing all returned SRA records with fields defined by `out_types`.

If `acc_only=FALSE`, a `data.frame` of matched accessions of `out_types` will be returned.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

References

<http://www.sqlite.org/>

See Also

[sraConvert](#)

Examples

```
## Using the SRAMetadb demo database

library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)

## Fulltext search SRA meta data using SQLite fts3 module:
# find all records with words of 'breast' and 'cancer' in a filed and there could be one to many words between 'breast' and 'cancer'
rs <- getSRA (search_terms='breast cancer', out_types=c('run','study'), sra_con=sra_con)

# find all records with exact phrase of 'breast cancer' in a filed:
rs <- getSRA (search_terms='"breast cancer"', out_types=c('run','study'), sra_con=sra_con)

# find records with words beginning with 'braes' and 'can', and the distance between them is equal or less than 2
rs <- getSRA (search_terms='breas* NEAR/2 can*', out_types=c('run','study'), sra_con=sra_con)

# the same as above except that only one space between the two words
rs <- getSRA (search_terms='"breas* can*', out_types=c('study'), sra_con=sra_con)

# find records with 'MCF7' or 'MCF-7' - adding double quote to avoid the SQLite to break down 'MCF-7' to 'MCF' and '7'
```

```
rs <- getSRA (search_terms ='MCF7 OR "MCF-7"', out_types=c('sample'), sra_con=sra_con)

# the same as above, but only search the field of 'study_title':
rs <- getSRA (search_terms ='study_title: brea* can*', out_types=c('run','study'), sra_con=sra_con)

# the same as above, but only search the field of 'study_title' and return only accessions:
rs <- getSRA (search_terms ='study_title: brea* can*', out_types=c('run','study'), sra_con=sra_con, acc_only=)

## The actual SRAMetadb sqlite database can be downloaded using function: getSRADBFile. Warning: the actual SRAMetadb
```

getSRADBFile	<i>Download and unzip last version of SRAMetadb.sqlite.gz from the server</i>
--------------	---

Description

This function is the standard method for downloading and unzipping the most recent SRAMetadb SQLite file from the server.

Usage

```
getSRADBFile(destdir = getwd(), destfile = "SRAMetadb.sqlite.gz",
             method)
```

Arguments

destdir	The destination directory of the downloaded file
destfile	The filename of the downloaded file. This filename should end in ".gz" as the unzipping assumes that is the case
method	Character vector of length 1, passed to the identically named argument of download.file .

Value

Prints some diagnostic information to the screen.
Returns the local filename for use later.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>, Sean Davis <sdavis2@mail.nih.gov>

Examples

```
## the SRAMetadb demo database can be used to test
sra_dbname <- file.path(system.file('extdata', package='SRADB'), 'SRAMetadb_demo.sqlite')

## Not run: geometadbfile <- getSRADBFile()
## Direct links for downloading the SRAMetadb sqlite database: https://s3.amazonaws.com/starbuck1/srddb/SRAMetadb_demo.sqlite.gz
```

getSRAfile	<i>Download SRA data file through ftp or fasp</i>
------------	---

Description

This function downloads sra data files associated with input SRA accessions from NCBI SRA or downloads fastq files from EBI ENA through ftp or fasp protocol.

Usage

```
getSRAfile( in_acc, sra_con, destDir = getwd(), fileType = 'sra', srcType = 'ftp', makeDirectory = F
```

Arguments

<code>in_acc</code>	character vector of SRA accessions, which should be in same SRA data type, either submission, study, sample, experiment or run.
<code>sra_con</code>	Connection to the SRAMetadb SQLite database
<code>destDir</code>	destination directory to save downloaded files.
<code>fileType</code>	type of SRA data files, which should be "sra", or "fastq" ('litesra' has phased out).
<code>srcType</code>	type of transfer protocol, which should be "ftp" or "fasp".
<code>makeDirectory</code>	logical, TRUE or FALSE. If TRUE and baseDir does not exists, storedir will be created to save downloaded files, otherwise downloaded fastq files will be saved to current directory.
<code>method</code>	Character vector of length 1, passed to the identically named argument of download.file .
<code>ascpCMD</code>	ascp main commands, which should be constructed by a user according to the actual installation of Aspera Connect in the system, with proper options to be used. Example commands: "ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty" (Linux) or ""/Applications/Aspera Connect.app/Contents/Resources/ascp' -QT -l 300m -i '/Applications/Aspera Connect.app/Contents/Resources/asperaweb_id_dsa.putty'" (Mac OS X). More about ascp please see the help ('ascp -h' in a shell).

Details

The function first gets ftp/fasp addresses of SRA data files with funcitn [getSRAinfo](#) for a given list of input SRA accessions; then downloads the SRA data files through ftp or fasp. The sra or sra-lite data files are downloaded from NCBI SRA and the fastq files are downloaded from EBI ENA.

Warning

Downloading SRA data files through ftp over long distance could take long time and should consider using using 'fasp'.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

See Also

[listSRAfile](#), [getSRAinfo](#), [getFASTQinfo](#), [getFASTQfile](#)

Examples

```
## Using the SRAMetadb demo database

library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect( dbDriver("SQLite"), sra_dbname )

## Not run:
## Download sra files from NCBI SRA using ftp protocol:
in_acc = c("SRR000648", "SRR000657")
getSRAfile( in_acc, sra_con = sra_con, destDir = getwd(), fileType = 'sra', srcType = 'ftp')

## Convert NCBI SRA format (.sra) data to fastq:
## Download SRA Toolkit: http://trace.ncbi.nlm.nih.gov/Traces/sra/sra.cgi?cmd=show&f=software&m=software&s=
## Run fastq-dump to
## system ("fastq-dump SRR000648.sra")

## Download fastq files from EBI using ftp protocol:
getSRAfile( in_acc, sra_con, destDir = getwd(), fileType = 'fastq', srcType = 'ftp', makeDirectory = FALSE, met

## Download fastq files from EBI ftp site using fasp protocol:
ascpCMD <- 'ascp -QT -l 300m -i /usr/local/aspera/connect/etc/asperaweb_id_dsa.putty'
getSRAfile( in_acc, sra_con, fileType = 'fastq', srcType = 'fasp', ascpCMD = ascpCMD )
dbDisconnect( sra_con )

## End(Not run)

## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

getSRAinfo

Get SRA data file information from NCBI SRA

Description

This function gets SRA .sra file information from NCBI SRA ftp site for a given list SRA accessions.

Usage

```
getSRAinfo( in_acc, sra_con, sraType = 'sra' )
```

Arguments

in_acc	character vector of SRA accessions, which should be in same SRA data type, either submission, study, sample, experiment or run.
sra_con	connection to the SRAMetadb SQLite database
sraType	type of SRA data files, which should be 'sra' ('litesra' has phased out).

Details

The function first gets ftp addressed of sra or sra-lite data files with function [listSRAfile](#) and then get file size and date from NCBI SRA ftp sites.

Value

A data.frame of ftp addresses of SRA data files, and file size and date along with input SRA accessions.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

See Also

[listSRAfile](#), [getSRAfile](#)

Examples

```
## Using the SRAMetadb demo database

library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)

## Get file size and date from NCBI ftp site for available fastq files associated with "SRS012041", "SRS000290"
# getSRAinfo (in_acc=c("SRS012041", "SRS000290"), sra_con=sra_con, sraType='sra')

## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

IGVclear

Clear IGV tracks loaded.

Description

Clear IGV tracks loaded in the current IGV.

Usage

```
IGVclear(sock)
```

Arguments

sock A socket connection to IGV.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

References

<http://www.broadinstitute.org/igv/PortCommands>

See Also

[startIGV](#), [IGVload](#), [IGVgoto](#)

Examples

```
## Not run:
## Create a file list from example bam files in the package
exampleBams = file.path(system.file('extdata',package='SRADB'),
  dir(system.file('extdata',package='SRADB'),pattern='bam$'))

##Create a socket connection to IGV
sock <- IGVsocket()
## Load the bam files into IGV
IGVload(sock, exampleBams)

## Clear loaded tracks in the current IGV
IGVclear(sock)

## End(Not run)
```

IGVcollapse

Collapse tracks in the IGV

Description

Using the remote command port of IGV, this function collapses tracks in the IGV.

Usage

```
IGVcollapse(sock)
```

Arguments

sock A socket connection to IGV.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

References

<http://www.broadinstitute.org/igv/PortCommands>

See Also

[startIGV](#), [IGVload](#)

Examples

```
## Not run:
sock <- IGVsocket()
IGVcollapse(sock)

## End(Not run)
```

IGVgenome

Set the IGV genome.

Description

Set the IGV genome via the remote command port.

Usage

```
IGVgenome(sock, genome="hg18")
```

Arguments

sock	A socket connection to IGV.
genome	String representing a genome that IGV knows about.

Author(s)

Sean Davis <sdavis2@mail.nih.gov>

References

<http://www.broadinstitute.org/igv/PortCommands>

See Also

[startIGV](#)

Examples

```
## Not run:  
sock <- IGVsocket()  
IGVgenome(sock, genome='hg18')  
  
## End(Not run)
```

IGVgoto*Go to a specified region in IGV.*

Description

Using the remote command port of IGV, go to a specified region.

Usage

```
IGVgoto(sock, region)
```

Arguments

sock	A socket connection to IGV.
region	Scrolls to a locus. Use any text that is valid in the IGV search box.

Author(s)

Sean Davis <sdavis2@mail.nih.gov>

References

<http://www.broadinstitute.org/igv/PortCommands>

See Also

[startIGV](#), [IGVload](#)

Examples

```
## Not run:
sock <- IGVsocket()
IGVgoto(sock, 'chr1:1-10000')
IGVgoto(sock, 'TP53')

## End(Not run)
```

IGVload

Load data into IGV via remote port call.

Description

Loads data via a remote call to IGV.

Usage

```
IGVload(sock, files)
```

Arguments

sock	A socket connection to IGV.
files	Character vector of one or more filenames with full path or urls to load. Among supported file types are BAM and IGV session file, for other file types please check IGV web site: http://www.broadinstitute.org/igv/ControllIGV .

Author(s)

Sean Davis <sdavis2@mail.nih.gov>

References

<http://www.broadinstitute.org/igv/PortCommands>

See Also

[startIGV](#), [IGVgoto](#)

Examples

```
## Not run:
## Create a file list from example bam files in the package
exampleBams = file.path(system.file('extdata',package='SRADB'),
  dir(system.file('extdata',package='SRADB'),pattern='bam$'))

## Create a socket connection to IGV
sock <- IGVsocket()
## Load the bam files into IGV
IGVload(sock, exampleBams)

## End(Not run)
```

IGVsession

Create an IGV session file

Description

This function will create an IGV session file

Usage

```
IGVsession(files, sessionFile, genome='hg18', VisibleAttribute='', destdir=getwd())
```

Arguments

files	Character vector of one or more filenames or urls to load - required.
sessionFile	String representing session file name - required
genome	String representing a genome that IGV knows about.
VisibleAttribute	Character vector of one or more IGV Visible Attributes to annotate data tracks to be loaded - optional.
destdir	Path where to save the IGV session file.

Details

While the current state of an IGV session can be saved to a named session file that can be opened to restore the IGV session later on, a IGV session file can be manually or programmatically created to achieve more efficient data loading and better control of IGV. IGVsession function was developed to create such IGV session files. For details please check IGV web site: <http://www.broadinstitute.org/igv/ControlIGV>

Value

An IGV session file with full file path.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

See Also

[IGVload](#), [IGVgenome](#), [IGVgoto](#)

Examples

```

library(SRAdb)
exampleBams = file.path(system.file('extdata',package='SRAdb'),
  dir(system.file('extdata',package='SRAdb'),pattern='bam$'))
exampleSessionFile <- IGVsession(exampleBams, 'exampleBams.xml');
## Not run:
## Start IGV within R. You only need one IGV instance with listen port 60151 open.
startIGV()

## Create a socket connection to IGV
sock <- IGVsocket()
## Wait until IGV fully launched and make sure the listen port for IGV is open (If not configured in IGV, follow
  IGVload(sock, exampleSessionFile)

## End(Not run)

```

IGVsnapshot

Make a file snapshot of the current IGV screen.

Description

From the IGV documentation: "Saves a snapshot of the IGV window to an image file. If filename is omitted, writes a .png file with a filename generated based on the locus. If filename is specified, the filename extension determines the image file format, which must be .png or .eps."

Usage

```
IGVsnapshot(sock, fname = "", dirname=getwd())
```

Arguments

sock	A socket connection to IGV.
fname	The filename to save. Alternatively, if not specified, IGV will create a filename based on the locus being viewed.
dirname	The directory name as a string for where to save the snapshot file.

Author(s)

Sean Davis <sdavis2@mail.nih.gov>

References

<http://www.broadinstitute.org/igv/PortCommands>

See Also

[startIGV](#)

Examples

```
## Not run:
## Create a snapshot of the current IGV window, which is usually the first launched IGV with listen port 60151 o
sock <- IGVsocket()
IGVsnapshot(sock)
dir()

## End(Not run)
```

IGVsocket

Create a Socket Connection to IGV.

Description

Create a Socket Connection to IGV by a specified port and host.

Usage

```
IGVsocket(host='localhost', port=60151)
```

Arguments

host	The name of remote host where IGV is running.
port	The port to connect to/listen on.

Author(s)

Sean Davis <sdavis2@mail.nih.gov>

References

<http://www.broadinstitute.org/igv/PortCommands>

See Also

[startIGV](#), [IGVgoto](#)

Examples

```
## Not run:
## Create a socket connection to IGV
sock <- IGVsocket()

## End(Not run)
```

IGVsort

*Sort an alignment track by the specified option.***Description**

Using the remote command port of IGV, Sorts an alignment track by the specified option. Recognized values for the option parameter are: base, position, strand, quality, sample, and readGroup.

Usage

```
IGVsort(sock, option)
```

Arguments

sock	A socket connection to IGV.
option	Recognized values for the option parameter are: base, position, strand, quality, sample, and readGroup.

Author(s)

Jack Zhu<zhujack@mail.nih.gov>

References

<http://www.broadinstitute.org/igv/PortCommands>

See Also

[startIGV](#), [IGVload](#)

Examples

```
## Not run:
sock <- IGVsocket()
IGVsort(sock, 'position')
IGVsort(sock, 'base')
IGVsort(sock, 'sample')

## End(Not run)
```

listSRAfile

*List sra, sra-lite or fastq data file names associated with input SRA accessions***Description**

This function lists all sra, sra-lite or fastq data files associated with input SRA accessions

Usage

```
listSRAfile( in_acc, sra_con, fileType = 'sra', srcType = 'ftp' )
```

Arguments

in_acc	character vector of SRA accessions, which should be in same SRA data type, either submission, study, sample, experiment or run.
sra_con	connection to the SRAMetadb SQLite database
fileType	types of SRA data files, which should be 'sra' or 'fastq'. ('litesra' has phased out).
srcType	type of transfer protocol, which should be "ftp" or "fasp".

Details

SRA fastq files are hosted at EBI ftp site (ftp://ftp.sra.ebi.ac.uk/vol1/fastq/) and .sra files are hosted at NCBI ftp site (ftp://ftp-trace.ncbi.nlm.nih.gov/sra/sra-instant/reads/). 'litesra' has phased out.

Value

A data frame of matched SRA accessions and data file names with ftp or fasp addresses.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

See Also

[getSRAfile](#)

Examples

```
## Using the SRAMetadb demo database
## Not run:
library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)

## List ftp or fasp addresses of sra files associated with "SRX000122"
listSRAfile (in_acc = c("SRX000122"), sra_con = sra_con, fileType = 'sra')
listSRAfile (in_acc = c("SRX000122"), sra_con = sra_con, fileType = 'sra', srcType='fasp')

## End(Not run)
```

The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA

sraConvert

Cross-reference between GEO data types

Description

A common task is to find all the SRA entities of one type associated with another SRA entity (eg., find all SRA samples associated with SRA study 'SRP001990'). This function provides a very fast mapping between entity types to facilitate queries of this type.

Usage

```
sraConvert(in_acc, out_type = c("sra", "submission", "study", "sample", "experiment", "run"), sra_con
```

Arguments

in_acc	Character vector of SRA accessions and should be of same SRA data type, either one of SRA submission, SRA study, SRA sample, SRA experiment and SRA run'
out_type	Character vector of the following SRA data types: 'sra', 'submission', 'study', 'sample', 'experiment', 'run'. If 'sra' is in out_type, out_type will be c("submission", "study", "sample", "experiment", "run")
sra_con	Connection to the SRAMetadb SQLite database

Value

A data.frame containing all matched SRA accessions.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

See Also

[getSRA](#), [listSRAfile](#), [getSRAinfo](#)

Examples

```
## Using the SRAMetadb demo database

library(SRAdb)
sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)

## Convert SRA experiment accessions to other types
a <- sraConvert( in_acc=c(" SRR000137", "SRR000138 "), out_type=c('sample'), sra_con=sra_con )
b <- sraConvert (in_acc=c("SRX000122"), sra_con=sra_con)

## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

sraGraph

Create a new graphNEL object of SRA accessions from SRA full text search

Description

This function will create a new graphNEL object from SRA accessions using function of [entityGraph](#) and SRA accessions are returned from SRA full text search using function of [getSRA](#)

Usage

```
sraGraph(search_terms, sra_con)
```

Arguments

search_terms	Free text search terms constructed according to SQLite query syntax defined here: http://www.sqlite.org/fts3.html#section_1_3
sra_con	Connection to the SRAMetadb SQLite database

Details

This function is a wrapper of two functions: `acc <- getSRA(search_terms, out_types='sra', sra_con, acc_only=TRUE)` and `g <- entityGraph(acc)`. A `graphNEL` object with `edgemode='directed'` is created from input data.frame of SRA accessions and the `plot` function will draw a graph

Value

A `graphNEL` object with `edgemode='directed'`

Author(s)

Jack Zhu <zhujack@mail.nih.gov> and Sean Davis <sdavis2@mail.nih.gov>

See Also

[getSRA](#), [sraConvert](#), [entityGraph](#)

Examples

```
## Using the SRAMetadb demo database

library(SRAdb)
library(Rgraphviz)

sra_dbname <- file.path(system.file('extdata', package='SRAdb'), 'SRAMetadb_demo.sqlite')
sra_con <- dbConnect(dbDriver("SQLite"), sra_dbname)

## create a graphNEL object from SRA accessions, which are full text search results of terms 'primary thyroid ce
g <- sraGraph('MCF7 OR "MCF-7"', sra_con)
attrs <- getDefaultAttrs(list(node=list(fillcolor='lightblue', shape='ellipse'))))
plot(g, attrs=attrs)

## similiar search as the above, returned much larger data.frame and graph is too clouded
g <- sraGraph('MCF', sra_con)
## Not run:
plot(g)

## End(Not run)

## The actual SRAMetadb sqlite database can be downloaded using function: getSRAdbFile. Warning: the actual SRA
```

startIGV	<i>Start IGV from R with different amount maximum memory support</i>
----------	--

Description

This function is to start the Integrative Genomics Viewer (IGV) within R, which is a high-performance visualization tool for interactive exploration of large, integrated datasets. It supports a wide variety of data types including sequence alignments, microarrays, and genomic annotations. In the SRADB, functions of load2IGV and load2newIGV can be used to load BAM format of sequencing data into IGV conveniently.

Usage

```
startIGV(memory = "mm", devel=FALSE)
```

Arguments

memory	Maximum usable memory support for the IGV to be launched, which is defined as the following: 'mm' - 1.2 GB, 'lm' - 2 GB, 'hm' - 10 GB, '' - 750 MB
devel	Start development version of IGV.

Details

IGV with 1.2 GB maximum usable memory ('mm') is usually for 32-bit Windows; IGV with 2 GB maximum usable memory ('lm') is usually for 32-bit MacOS; IGV with 10 GB maximum usable memory is for large memory 64-bit java machines; IGV with 750 MB ('') is sufficient for most applications. The IGV will be launched through Java Web Start. For details about how IGV is launched or have problems to launch it, please refer to this site: <http://www.broadinstitute.org/igv/StartIGV>. Note: if [IGVload](#) will be used to load BAM files to the new launched IGV, a connection port needs to be enabled in the IGV. This is how to enable connection port in the IGV: in IGV, go View->Preferences->Advanced->Enable port and check the checkbox.

Author(s)

Jack Zhu

References

<http://www.broadinstitute.org/igv/>

See Also

[IGVload](#), [IGVgoto](#), [IGVgenome](#)

Examples

```
## launch IGV with 1.2 GB maximum usable memory support
## Not run: startIGV("lm")
```

Index

* IO

- IGVclear, [16](#)
- IGVcollapse, [17](#)
- IGVgenome, [18](#)
- IGVgoto, [18](#)
- IGVload, [19](#)
- IGVsnapshot, [21](#)
- IGVsocket, [22](#)
- IGVsort, [23](#)

* NCBI

- colDescriptions, [7](#)

* SRA

- colDescriptions, [7](#)
- sraConvert, [24](#)

* database

- colDescriptions, [7](#)
- sraConvert, [24](#)

* package

- SRADB-package, [2](#)

ascpR, [4](#), [6](#), [7](#), [10](#)

ascpSRA, [5](#), [6](#)

colDescriptions, [7](#)

download.file, [9](#), [13](#), [14](#)

entityGraph, [8](#), [25](#), [26](#)

getFASTQfile, [9](#), [11](#), [14](#)

getFASTQinfo, [5](#), [7](#), [10](#), [10](#), [14](#)

getSRA, [8](#), [11](#), [25](#), [26](#)

getSRADBfile, [13](#)

getSRAfile, [5](#), [7](#), [10](#), [11](#), [14](#), [16](#), [24](#)

getSRAinfo, [5](#), [7](#), [14](#), [15](#), [25](#)

IGVclear, [16](#)

IGVcollapse, [17](#)

IGVgenome, [18](#), [20](#), [27](#)

IGVgoto, [16](#), [18](#), [19](#), [20](#), [22](#), [27](#)

IGVload, [16](#), [17](#), [19](#), [19](#), [20](#), [23](#), [27](#)

IGVsession, [20](#)

IGVsnapshot, [21](#)

IGVsocket, [22](#)

IGVsort, [23](#)

listSRAfile, [6](#), [7](#), [11](#), [14–16](#), [23](#), [25](#)

plot, [8](#), [26](#)

sraConvert, [8](#), [12](#), [24](#), [26](#)

SRADB (SRADB-package), [2](#)

SRADB-package, [2](#)

sraGraph, [8](#), [12](#), [25](#)

startIGV, [16–19](#), [21–23](#), [27](#)