

# Package ‘ROCpAI’

November 21, 2024

**Type** Package

**Title** Receiver Operating Characteristic Partial Area Indexes for evaluating classifiers

**Version** 1.18.0

**BugReports** <https://github.com/juanpegarcia/ROCpAI/tree/master/issues>

**Description** The package analyzes the Curve ROC, identifies it among different types of Curve ROC and calculates the area under the curve through the method that is most accurate. This package is able to standardize proper and improper pAUC.

**License** GPL-3

**Encoding** UTF-8

**LazyData** TRUE

**Depends** boot, SummarizedExperiment, fission, knitr, methods

**import** boot, SummarizedExperiment, fission, knitr, methods

**biocViews** Software, StatisticalMethod, Classification

**RoxygenNote** 7.0.2

**VignetteBuilder** knitr

**Suggests** BiocStyle, knitr, rmarkdown

**git\_url** <https://git.bioconductor.org/packages/ROCpAI>

**git\_branch** RELEASE\_3\_20

**git\_last\_commit** 5e7eba5

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.20

**Date/Publication** 2024-11-20

**Author** Juan-Pedro Garcia [aut, cre],  
Manuel Franco [aut],  
Juana-María Vivo [aut]

**Maintainer** Juan-Pedro Garcia <juanpedro.garcia4@um.es>

## Contents

mcpAUC . . . . .	2
mcpAUCboot . . . . .	3
pointsCurve . . . . .	4
tpAUC . . . . .	4
tpAUCboot . . . . .	5

---

mcpAUC

*Clasification of area under ROC curve following McClish method*


---

### Description

Calculate the area under the ROC curve following McClish methodologic from a dataset and a sample from that dataset.

### Usage

```
mcpAUC(
  dataset,
  low.value = NULL,
  up.value = NULL,
  plot = FALSE,
  selection = NULL,
  variable = NULL
)
```

### Arguments

dataset	Dataframe of the complete information of the samples
low.value	lower false positive rate value that the function will use to calculate the pAUC
up.value	upper false positive rate value that the function will use to calculate the pAUC
plot	ROC plot
selection	vector that will only be used if the parameter "dataset" is a RangedSummarized-Experiment object. This parameter is used to select the variables that will be analysed
variable	in case that dataset is a SummarizedExperiment, indicate the Gold Standard

### Value

RangedSummarizedExperiment object with the pAUC and the mcpAUC scores, and the TPR and FPR values for each ROC curve generated

### Examples

```
library(fission)
data("fission")
resultsMC <- mcpAUC(fission, low.value = 0, up.value = 0.25, plot = TRUE,
  selection = c("SPNCRNA.1080", "SPAC186.08c"), variable="strain")
```

---

mcpAUCboot

*mcpAUCboot*


---

**Description**

Calculates the confidence interval using a boot analysis

**Usage**

```
mcpAUCboot(
  dataset,
  low.value = NULL,
  up.value = NULL,
  r = 50,
  level = 0.95,
  type.interval = "perc",
  selection = NULL,
  variable = NULL
)
```

**Arguments**

dataset	dataframe or RangedSummarizedExperiment object
low.value	lower false positive rate value that the function will use to calculate the pAUC
up.value	upper false positive rate value that the function will use to calculate the pAUC
r	number of iterations.
level	confidence level
type.interval	String that represent the type of intervals required. The value should be any subset of the values c("norm","basic", "stud", "perc", "bca") or simply "all" which will compute all five types of intervals.
selection	vector that will only be used if the parameter "dataset" is a RangedSummarized-Experiment object. This parameter is used to select the variables that will be analysed
variable	in case that dataset is a SummarizedExperiment, indicate the Gold Standard

**Value**

SummarizedExperiment object with the mcpAUC, the standard deviation, and the lower and upper limits of the confidence interval.

**Examples**

```
library(fission)
data("fission")
resultsMCboot <- mcpAUCboot(fission,low.value = 0, up.value = 0.25,
  selection = c("SPNCRNA.1080","SPAC186.08c"), variable="strain")
```

---

pointsCurve                      *Points of the ROC curve*

---

### Description

It calculates the coordinates (fpr, sen) of the ROC curve. This function sorts the scores of a model test and generates the points which will be used to plot its the ROC curve

### Usage

```
pointsCurve(x, y)
```

### Arguments

x                      It is the vector of the status (gold standar)  
y                      It is the vector with the values of a predictor variable or clasificator

### Value

return a matrix with the points of 1-specificity and sensibility that will be used to generate a ROC curve

### Examples

```
library(fission)
data("fission")
strain <- fission@colData@listData$strain
pointsCurve<- pointsCurve(strain, t(assay(fission))[, "SPNCRNA.1080"])
```

---

tpAUC                              *Tigher partial area under the ROC curve*

---

### Description

It standarizes the partial area under the ROC curve by the tigher index

### Usage

```
tpAUC(
  dataset,
  low.value = NULL,
  up.value = NULL,
  plot = FALSE,
  selection = NULL,
  variable = NULL
)
```

**Arguments**

dataset	Dataframe of the complete information of the samples
low.value	lower false positive rate value that the function will use to calculate the pAUC
up.value	upper false positive rate value that the function will use to calculate the pAUC
plot	ROC plot
selection	vector that will only be used if the parameter "dataset" is a RangedSummarized-Experiment object. This parameter is used to select the variables that will be analysed
variable	in case that dataset is a SummarizedExperiment, indicate the Gold Standard

**Value**

RangedSummarizedExperiment object with the pAUC and the tpAUC scores, and the TPR and FPR values for each ROC curve generated

**Examples**

```
library(fission)
data("fission")
resultsT <- tpAUC(fission, low.value = 0, up.value = 0.25, plot = TRUE,
  selection = c("SPNCRNA.1080", "SPAC186.08c"), variable="strain")
```

---

tpAUCboot

*tpAUCboot*


---

**Description**

Calculates the confidence interval using a boot analysis

**Usage**

```
tpAUCboot(
  dataset,
  low.value = NULL,
  up.value = NULL,
  r = 50,
  level = 0.95,
  type.interval = "perc",
  selection = NULL,
  variable = NULL
)
```

**Arguments**

dataset	dataframe or RangedSummarizedExperiment objetc
low.value	lower false positive rate value that the function will use to calculate the pAUC
up.value	upper false positive rate value that the function will use to calculate the pAUC
r	number of iterations.
level	confidence level

<code>type.interval</code>	String that represent the type of intervals required. The value should be any subset of the values <code>c("norm","basic", "stud", "perc", "bca")</code> or simply "all" which will compute all five types of intervals.
<code>selection</code>	vector that will only be used if the parameter "dataset" is a <code>RangedSummarizedExperiment</code> object. This parameter is used to select the variables that will be analysed
<code>variable</code>	in case that dataset is a <code>SummarizedExperiment</code> , indicate the Gold Standard

**Value**

`SummarizedExperiment` object with the `Tp_AUC`, the standard deviation, and the lower and upper limits of the confidence interval

**Examples**

```
library(fission)
data("fission")
resultstboot<- tpAUCboot(fission,low.value = 0, up.value = 0.25,
selection = c("SPNCRNA.1080","SPAC186.08c"), variable="strain")
```

# Index

mcpAUC, [2](#)  
mcpAUCboot, [3](#)  
pointsCurve, [4](#)  
tpAUC, [4](#)  
tpAUCboot, [5](#)