

Package ‘epivizrStandalone’

November 20, 2024

Title Run Epivizr Interactive Genomic Data Visualization App within R

Version 1.34.0

Maintainer Hector Corrada Bravo <hcorrada@gmail.com>

Author Hector Corrada Bravo, Jayaram Kancherla

Description This package imports the epivizr visualization JavaScript app for genomic data interactive visualization. The 'epivizrServer' package is used to provide a web server running completely within R. This standalone version allows to browse arbitrary genomes through genome annotations provided by Bioconductor packages.

Depends R (>= 3.2.3), epivizr (>= 2.3.6), methods

License MIT + file LICENSE

LazyData true

Imports git2r, epivizrServer, GenomeInfoDb, BiocGenerics, GenomicFeatures, S4Vectors

Suggests testthat, knitr, rmarkdown, OrganismDbi (>= 1.13.9), Mus.musculus, Biobase, BiocStyle

RoxygenNote 7.1.1

VignetteBuilder knitr

biocViews Visualization, Infrastructure, GUI

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/epivizrStandalone>

git_branch RELEASE_3_20

git_last_commit 94beb58

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-20

Contents

setStandalone	2
startStandalone	2
startStandaloneApp	4

Index	6
--------------	----------

setStandalone	<i>Set settings for epiviz standalone repository.</i>
---------------	---

Description

The epiviz app run by function `startStandalone` in this package is cloned as a git repository. This function initializes the settings specifying which git repository is used. It can be either a github repository (the usual case), or local repository containing the epiviz JS app (used for testing and development).

Usage

```
setStandalone(
  url = "https://github.com/epiviz/epiviz.git",
  branch = "min",
  local_path = NULL,
  non_interactive = FALSE
)
```

Arguments

<code>url</code>	(character) github url to use. defaults to (" https://github.com/epiviz/epiviz.git ").
<code>branch</code>	(character) branch on the github repository. defaults to (master).
<code>local_path</code>	(character) if you already have a local instance of epiviz and would like to run standalone use this.
<code>non_interactive</code>	(logical) don't download repo, used for testing purposes.

Value

path to the epiviz app git repository

Examples

```
# argument non_interactive here to avoid downloading when testing
# package. Remove non_interactive argument when you try it out.
setStandalone(url="https://github.com/epiviz/epiviz.git", branch="master", non_interactive=TRUE)
```

startStandalone	<i>Start a standalone epivizr session.</i>
-----------------	--

Description

Uses the local repository of epiviz JS app to start a standalone epivizr session through the `startEpiviz` function. The epiviz app requires a list of sequence names and lengths (e.g., chromosome names and lengths) to setup genome browsing. These can be passed in the `seqinfo` argument or derived from the `gene_track` argument. The `gene_track` argument can be used to pass a genome annotation and add a gene track to the epiviz browser. See package vignette for further detail.

Usage

```
startStandalone(
  gene_track = NULL,
  seqinfo = NULL,
  keep_seqlevels = NULL,
  chr = NULL,
  start = NULL,
  end = NULL,
  non_interactive = FALSE,
  register_function = epivizr:::register_all_the_epiviz_things,
  use_viewer_option = FALSE,
  host = "127.0.0.1",
  ...
)
```

Arguments

gene_track	(OrganismDb) an object of type OrganismDb or TxDb
seqinfo	(Seqinfo) an object of type Seqinfo from which sequence names and lengths are obtained
keep_seqlevels	(character) vector of sequence names to include in the standalone app
chr	(character) chromosome to browse to on app startup.
start	(integer) start location to browse to on app startup.
end	(integer) end location to browse to on app startup.
non_interactive	(logical) run server in non-interactive mode. Used for testing and development.
register_function	(function) function used to initialize actions in epiviz app. Used for testing and development.
use_viewer_option	(logical) run application in viewer defined by <code>getOption("viewer")</code> . This allows standalone app to run in Rstudio's viewer (FALSE by default)
host	(character) host address for application (127.0.0.1 by default)
...	additional arguments passed to startEpiviz .

Value

An object of class [EpivizApp](#)

Examples

```
# see package vignete for example usage
seqinfo <- GenomeInfoDb::Seqinfo(c("chr1", "chr2"), c(10, 20))
app <- startStandalone(seqinfo=seqinfo, non_interactive=TRUE)
app$stop_app()
```

startStandaloneApp *Start a standalone epivizr session.*

Description

Uses the local installation of the epivizr desktop app to start a standalone epivizr session through the [startEpivizr](#) function. The epivizr app requires a list of sequence names and lengths (e.g., chromosome names and lengths) to setup genome browsing. These can be passed in the `seqinfo` argument or derived from the `gene_track` argument. The `gene_track` argument can be used to pass a genome annotation and add a gene track to the epivizr browser. See package vignette for further detail.

Usage

```
startStandaloneApp(
  gene_track = NULL,
  seqinfo = NULL,
  keep_seqlevels = NULL,
  chr = NULL,
  start = NULL,
  end = NULL,
  non_interactive = FALSE,
  register_function = epivizr:::register_all_the_epivizr_things,
  host = "127.0.0.1",
  ...
)
```

Arguments

<code>gene_track</code>	(OrganismDb) an object of type OrganismDb or TxDb
<code>seqinfo</code>	(Seqinfo) an object of type Seqinfo from which sequence names and lengths are obtained
<code>keep_seqlevels</code>	(character) vector of sequence names to include in the standalone app
<code>chr</code>	(character) chromosome to browse to on app startup.
<code>start</code>	(integer) start location to browse to on app startup.
<code>end</code>	(integer) end location to browse to on app startup.
<code>non_interactive</code>	(logical) run server in non-interactive mode. Used for testing and development.
<code>register_function</code>	(function) function used to initialize actions in epivizr app. Used for testing and development.
<code>host</code>	(character) host address for application (127.0.0.1 by default)
<code>...</code>	additional arguments passed to startEpivizr .

Value

An object of class [EpivizrApp](#)

Examples

```
# see package vignete for example usage
seqinfo <- GenomeInfoDb::Seqinfo(c("chr1", "chr2"), c(10, 20))
app <- startStandalone(seqinfo=seqinfo, non_interactive=TRUE)
app$stop_app()
```

Index

EpivizApp, [3](#), [4](#)

OrganismDb, [3](#), [4](#)

Seqinfo, [3](#), [4](#)

setStandalone, [2](#)

startEpiviz, [2-4](#)

startStandalone, [2](#), [2](#)

startStandaloneApp, [4](#)

TxDB, [3](#), [4](#)