

Package ‘omXplore’

November 21, 2024

Type Package

Title Vizualization tools for 'omics' datasets with R

Version 1.0.0

Description This package contains a collection of functions (written as shiny modules) for the visualisation and the statistical analysis of omics data. These plots can be displayed individually or embedded in a global Shiny module.

Additionaly, it is possible to integrate third party modules to the main interface of the package omXplore.

License Artistic-2.0

Depends R (>= 4.4.0), methods

Imports shiny, MSnbase, PSMatch, SummarizedExperiment, MultiAssayExperiment, shinyBS, shinyjs, shinyjqui, DT, RColorBrewer, gplots, highcharter, visNetwork, tibble, grDevices, stats, utils, htmlwidgets, vioplot, graphics, FactoMineR, dendextend, dplyr, factoextra, tidyr

Suggests knitr, rmarkdown, BiocStyle, testthat, Matrix, graph

biocViews Software, ShinyApps, MassSpectrometry, DataRepresentation, GUI, QualityControl

NeedsCompilation no

Collate 'Infos_adjacencyMatrix.R' 'Prostar_1x.R' 'convert_to_mae.R' 'doc-data.R' 'external_apps_examples.R' 'get_pep_prot_CC.R' 'mae_accessors.R' 'metacell_utils.R' 'mod_colorLegend.R' 'modules.R' 'omXplore_cc.R' 'omXplore_corrmatrix.R' 'omXplore_density.R' 'omXplore_format_DT.R' 'omXplore_heatmap.R' 'omXplore_intensity.R' 'omXplore_pca.R' 'omXplore_plots_tracking.R' 'omXplore_tabExplorer.R' 'omXplore_variance.R' 'omXplore_view_dataset.R' 'palette.R' 'plot_boxplot.R' 'plot_heatmap.R' 'plot_pca.R' 'plot_violin.R' 'utils.R' 'zzz.R'

RoxxygenNote 7.3.1

Encoding UTF-8

LazyData false

URL <https://github.com/prostarproteomics/omXplore>,
<https://prostarproteomics.github.io/omXplore/>

BugReports <https://github.com/prostarproteomics/omXplore/issues>

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/omXplore

git_branch RELEASE_3_20

git_last_commit a23afb8

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-20

Author Samuel Wieczorek [aut, cre] (<<https://orcid.org/0000-0002-5016-1203>>),
 Thomas Burger [aut],
 Enora Fremy [ctb]

Maintainer Samuel Wieczorek <samuel.wieczorek@cea.fr>

Contents

accessors	3
BuildColorStyles	4
Build_enriched_qdata	5
color-legend	5
converters	6
corrmatrix	8
customChart	9
customExportMenu	10
density-plot	10
ds-cc	11
ds-pca	12
ds-view	14
external_app	16
FormatDataForDT	17
format_DT	18
GetPkgVersion	19
globals	20
intensity-plots	20
is.listOf	22
omXplore-modules	22
omXplore_heatmap	23
omXplore_tabExplorer	25
palette	26
pep_prot_CC	27
pkgs.require	28
plot-variance	29
plots_tracking	30
Prostar-1x-compatible	31
q_metadata	31
sub_R25	33
vdata	34

accessors	<i>Accessors functions</i>
-----------	----------------------------

Description

Functions used to access the additional plots in the instances of the class `MultiAssayExperiment`.

Usage

```
get_adjacencyMatrix(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_adjacencyMatrix(object)

get_group(object, ...)

## S4 method for signature 'MultiAssayExperiment'
get_group(object)

get_metacell(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_metacell(object, slot.name = c("metacell", "qMetacell"))

get_cc(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_cc(object)

get_parentProtId(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_parentProtId(object)

get_colID(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_colID(object)

get_type(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_type(object)

get_pkg_version(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_pkg_version(object)
```

Arguments

`object` An instance of class `SummarizedExperiment`.

...	Additional parameters
slot.name	The name of the slot dedicated to cell metadata to search. Default values are 'metacell' and 'qMetacell'

Value

See individual method description for the return value.

If exists, the slot value requested.

A DataFrame containing the adjacency matrix of the dataset

A data.frame containing the metadata of the dataset

Examples

```
## -----
## Accessing slots from a MSnSet dataset
## -----
data(sub_R25)
se1 <- sub_R25[[1]]
parentProtId <- get_parentProtId(se1)
colID <- get_colID(se1)
type <- get_type(se1)
metacell <- get_metacell(se1)
conds <- get_group(sub_R25)
```

BuildColorStyles

Build color style for DT tables

Description

This function builds a list which is used for styling DT tables with the function `DT::styleEqual()`

Usage

`BuildColorStyles(type)`

Arguments

`type` The type of dataset. Available values are `protein` and `peptide`

Value

A list

Build_enriched_qdata	<i>Builds enriched assay with cell metadata info</i>
----------------------	--

Description

If the cell metadata exists in the object of class `SummarizedExperiment`, then these information are added to the quantitative data so as to use styles with the functions of the package `DT`.

Usage

```
Build_enriched_qdata(obj)
```

Arguments

obj	An instance of the class <code>SummarizedExperiment</code>
-----	--

Value

A `data.frame` with new columns corresponding to the cell metadata (if exists)

color-legend	<i>Color legend for DaparToolshed</i>
--------------	---------------------------------------

Description

Shows a legend based on the tags in the package 'DaparToolshed'

Usage

```
custom_metacell_colors()

colorLegend_ui(id)

colorLegend_server(
  id,
  presentTags = reactive({
    NULL
  }),
  hide.white = TRUE
)

colorLegend(obj = SummarizedExperiment::SummarizedExperiment())
```

Arguments

id	A <code>character(1)</code> which is the id of the shiny module.
presentTags	A vector of <code>character()</code> which correspond to the tags.
hide.white	A <code>boolean()</code> to indicate whether the white cells must be hidden or not.
obj	An instance of the class <code>SummarizedExperiment</code> .

Value

A vector
NA
NA
A shiny app

Examples

```
data(vdata)
shiny::runApp(colorLegend(vdata[[1]]))
```

converters

*Convert to enriched MultiAssayExperiment***Description**

The resulting object is an instance of the MultiAssayExperiment class. F

Usage

```
convert_to_mae(obj)

MSnSet_to_mae(obj)

matrix_to_mae(obj)

df_to_mae(obj)

Compute_CC(obj)

QFeatures_to_mae(obj)

SE_to_mae(obj)

MAE_to_mae(obj)

Check_se_Consistency(obj)

list_to_se(l1)

Check_List_consistency(l1)

listOfLists_to_mae(obj, colData = NULL)

listOfSE_to_mae(obj)

Check_MSnSet_Consistency(obj)
```

```
matrix_to_se(obj)  
df_to_se(obj)  
MSnSet_to_se(obj)  
Build_X_CC(se)  
listOfMSnSet_to_mae(obj)  
listOfmatrix_to_mae(obj)  
listOfdf_to_mae(obj)
```

Arguments

obj	An object compliant with the formats accepted by omXplore
11	A list
colData	A data.frame()
se	AN instance of the class SummarizedExperiment

Value

An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment
An instance of SimpleList
An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment
A boolean(1)
An enriched instance of the class SummarizedExperiment
A boolean(1)
An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment
A boolean(1)
An enriched instance of the class SummarizedExperiment
An enriched instance of the class SummarizedExperiment
An enriched instance of the class SummarizedExperiment
An enriched instance of the class SummarizedExperiment
An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment
An enriched instance of the class MultiAssayExperiment

Examples

```
#-----
# Conversion of a MultiAssayExperiment instance
#-----
data(miniACC, package = 'MultiAssayExperiment')
convert_to_mae(miniACC)
```

corrmatrix	<i>Displays a correlation matrix of the quantitative data of a numeric matrix.</i>
------------	--

Description

Displays a correlation matrix of the quantitative data of a numeric matrix.

Usage

```
omXplore_corrmatrix_ui(id)

omXplore_corrmatrix_server(
  id,
  obj = reactive({
    NULL
  }),
  i = reactive({
    NULL
  })
)

corrMatrix(data, rate = 0.5, showValues = FALSE)

omXplore_corrmatrix(obj, i)
```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>obj</code>	An instance of the class SummarizedExperiment
<code>i</code>	An integer which is the index of the assay in the param obj
<code>data</code>	An object of class 'matrix'
<code>rate</code>	The rate parameter to control the exponential law for the gradient of colors
<code>showValues</code>	A boolean which indicates whether to show values in the correlation plot.

Value

- NA
- NA
- A plot
- A shiny app

Examples

```
if (interactive()) {  
  data(vdata)  
  omXplore_corrmatrix(vdata, 1)  
}
```

customChart

Customised resetZoom Button of highcharts plots

Description

Customised resetZoom Button of highcharts plots

Usage

```
customChart(  
  hc,  
  chartType = "scatter",  
  zoomType = "None",  
  width = 0,  
  height = 0  
)
```

Arguments

hc	A highcharter object
chartType	The type of the plot
zoomType	The type of the zoom (one of "x", "y", "xy", "None")
width	The width of the plot
height	The height of the plot

Value

A highchart plot

Author(s)

Samuel Wieczorek

Examples

```
library(highcharter)  
hc <- highchart()  
hc_chart(hc, type = "line")  
hc_add_series(hc, data = c(29, 71, 40))  
customChart(hc)
```

```
customExportMenu      #' @title Customised contextual menu of highcharts plots
```

Description

#' @title Customised contextual menu of highcharts plots

Usage

```
customExportMenu(hc, fname)
```

Arguments

hc	A highcharter object
fname	The filename under which the plot has to be saved

Value

A contextual menu for highcharts plots

Author(s)

Samuel Wieczorek

Examples

```
NULL
```

```
density-plot      Displays a correlation matrix of the quantitative data of a numeric matrix.
```

Description

Displays a correlation matrix of the quantitative data of a numeric matrix.

Usage

```
omXplore_density_ui(id)

omXplore_density_server(
  id,
  obj = reactive({
    NULL
  }),
  i = reactive({
    NULL
  }),
  pal.name = reactive({
```

```

    NULL
  })
}

densityPlot(data, conds = NULL, pal.name = NULL)

omXplore_density(obj, i)

```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>obj</code>	An instance of the class <code>SummarizedExperiment</code>
<code>i</code>	An integer which is the index of the assay in the param obj
<code>pal.name</code>	A character(1) which is the name of the palette from the package RColorBrewer from which the colors are taken. Default value is 'Set1'.
<code>data</code>	A <code>data.frame()</code> of quantitative data
<code>conds</code>	A vector indicating the name of each sample.

Value

<code>NA</code>
<code>NA</code>
A plot
A shiny app

Examples

```

data(vdata)
omXplore_density(vdata, 1)

data(vdata)
qdata <- SummarizedExperiment::assay(vdata[[1]])
conds <- get_group(vdata)
densityPlot(qdata, conds)

```

Description

A shiny Module.

Usage

```
omXplore_cc_ui(id)

omXplore_cc_server(
  id,
  obj = reactive({
    NULL
  }),
  i = reactive({
    NULL
  })
)

omXplore_cc(obj, i)
```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>obj</code>	An instance of SummarizedExperiment class
<code>i</code>	An integer which is the index of the assay in the param obj

Value

- A shiny module
- A shiny plot
- A shiny module
- A shiny app
- A shiny app

Examples

```
if (interactive()) {
  data(vdata)
  omXplore_cc(vdata, 1)
}
```

ds-pca

*Bar plot of missing values per lines using highcharter.***Description**

This method plots a bar plot which represents the distribution of the number of missing values (NA) per lines (ie proteins).

- `wrapper_pca()`
- `plotPCA_Eigen_hc()`: plots the eigen values of PCA with the highcharts library
- `plotPCA_Eigen()`: plots the eigen values of PCA
- `plotPCA_Var()`
- `plotPCA_Ind()`

Usage

```
omXplore_pca_ui(id)

omXplore_pca_server(id, obj, i)

omXplore_pca(obj, i)

wrapper_pca(qdata, group, var.scaling = TRUE, ncp = NULL)

plotPCA_Eigen(res.pca)

plotPCA_Var(res.pca, chosen.axes = c(1, 2))

plotPCA_Ind(res.pca, chosen.axes = c(1, 2))

plotPCA_Eigen_hc(res.pca)
```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>obj</code>	An instance of the class <code>MultiAssayExperiment</code> .
<code>i</code>	An integer which is the index of the assay in the param <code>obj</code>
<code>qdata</code>	A <code>data.frame()</code> of quantitative data
<code>group</code>	A vector with the name of samples
<code>var.scaling</code>	A boolean indicating whether to scale the data or not
<code>ncp</code>	See <code>FactoMineR::PCA()</code>
<code>res.pca</code>	The result of the function <code>FactoMineR::PCA()</code>
<code>chosen.axes</code>	See the parameter 'axes' of the function <code>factoextra::fviz_pca_var()</code>

Value

NA	
NA	
A shiny app	
The result of the function <code>FactoMineR::PCA()</code>	
A plot	

Author(s)

Samuel Wieczorek, Enora Fremy

Examples

```

data(vdata)
# Replace missing values for the example
sel <- is.na(SummarizedExperiment::assay(vdata, 1))
SummarizedExperiment::assay(vdata[[1]])[sel] <- 0
omXplore_pca(vdata, 1)

data(vdata)
obj <- vdata[[1]]
res.pca <- wrapper_pca(SummarizedExperiment::assay(obj), get_group(obj))
plotPCA_Eigen(res.pca)
plotPCA_Var(res.pca)
plotPCA_Eigen_hc(res.pca)
plotPCA_Ind(res.pca)

```

ds-view

Bar plot of missing values per lines using highcharter.

Description

This method plots a bar plot which represents the distribution of the number of missing values (NA) per lines (i.e. proteins).

Usage

```

view_dataset_ui(id)

view_dataset_server(
  id,
  obj = reactive({
    NULL
  }),
  addons = list(),
  useModal = TRUE,
  verbose = FALSE
)

view_dataset(obj = NULL, addons = NULL, useModal = TRUE)

```

Arguments

<code>id</code>	A character(1) for the 'id' of the shiny module. It must be the same as for the ' <code>*_ui</code> ' function.
<code>obj</code>	An instance of the class <code>MultiAssayExperiment</code> .
<code>addons</code>	A list to configure the other shiny apps to integrate. Each item correspond to one package: <ul style="list-style-type: none"> • the name of the slot is the name of the package

	<ul style="list-style-type: none"> the content of the slot is a vector composed of the generic name of the shiny app. Each of the apps listed here must be an exported app of the package. For example, given the value addons = list(testPkg = c('foo', 'foo2')). That means that the package called "testPkg" must provide the four functions: foo1_ui(), foo1_server() and foo2_ui(), foo2_server()
useModal	A boolean(1) that indicates whether to open plot modules in a modal window or not. Default is TRUE.
verbose	A boolean for verbose mode. Default is FALSE.

Details

- distribution of the missing values per line,
- a bar plot which represents the distribution of the number of missing values (NA) per lines (i.e. proteins) and per conditions,
- Histogram of missing values.
- Variance : Builds a densityplot of the CV of entities in numeric matrix. The CV is calculated for each condition present in the dataset (see the slot 'Condition' in the colData() DataFrame)
- Heatmap:

The function [heatmapD\(\)](#)

The function [] is inspired from the function 'heatmap.2' that displays a numeric matrix. For more information, please refer to the help of the heatmap.2 function.

Value

NA
NA
NA

A shiny application which wraps the functions view_dataset_ui() and the view_dataset_server()

Missing values

- #* - distribution of the missing values per line,
- a bar plot which represents the distribution of the number of missing values (NA) per lines (ie proteins) and per conditions,
 - Histogram of missing values.

Author(s)

Samuel Wieczorek, Enora Fremy

Examples

```
data(vdata)
addons <- list(omXplore = c("extFoo1", "extFoo2"))
runApp(view_dataset(vdata, addons))

shiny::runApp(view_dataset(vdata))

if (interactive()) {
```

```

    data(vdata)
    view_dataset(vdata)
}

```

external_app*External module example***Description**

Example for an external shiny module, well structured to be run within a workflow for MagellanNTK

Usage

```

extFoo1_ui(id)

extFoo1_server(
  id,
  obj = reactive({
    NULL
  }),
  i = reactive({
    NULL
  })
)

extFoo1(obj, i)

extFoo2_ui(id)

extFoo2_server(
  id,
  obj = reactive({
    NULL
  }),
  i = reactive({
    NULL
  })
)

extFoo2(obj, i)

```

Arguments

- | | |
|------------|---|
| id | A character(1) which is the id of the shiny module. |
| obj | An object of instance MultiAssayExperiment |
| i | An integer which is the index of the assay in the param obj |

Value

```
NA
NA
NA
A shiny app
NA
NA
A shiny app
```

Examples

```
if (interactive()) {
  data(vdata)
  app1 <- extFoo1(vdata, 1)
  app2 <- extFoo2(vdata, 1)
  shiny::runApp(app1)
  shiny::runApp(app2)
}
```

FormatDataForDT

*Constructs a dataset suitable to use with the module format_DT.***Description**

This function builds the skeleton of a dataset which can be used by the module formatDT. It creates additional columns to be used to style the table. to colors cells.

Usage

```
FormatDataForDT(se, digits = 2)
```

Arguments

<code>se</code>	An instance of the class SummarizedExperiment
<code>digits</code>	An 'integer(1)' to specify the number of digits to display in the tables for numerical values. Default is 2.

Value

A data.frame

format_DT	<i>formatDT_ui</i> and <i>formatDT_server</i>
-----------	---

Description

A shiny Module.

See DT package homepage for more details about styling tables. If no style is precised, this module show the raw data. If any style is given, then the dataset must be well configured (I.e. it must contain the correct columns)

Usage

```
formatDT_ui(id)

formatDT_server(
  id,
  data = reactive({
    NULL
}),
  data_nostyle = reactive({
    NULL
}),
  withDLBsns = FALSE,
  showRownames = FALSE,
  dt_style = reactive({
    NULL
}),
  filename = "Prostar_export",
  selection = "single"
)
formatDT(data)
```

Arguments

<code>id</code>	shiny id
<code>data</code>	A <code>data.frame</code>
<code>data_nostyle</code>	A <code>data.frame()</code> to be bind to the main data with no custom style
<code>withDLBsns</code>	A boolean to indicate whether to display download buttons or not.
<code>showRownames</code>	A boolean to indicate whether to show rownames.
<code>dt_style</code>	A list composed of: <ul style="list-style-type: none"> • <code>data</code> : a <code>data.frame</code> • <code>colors</code> : a named vector
<code>filename</code>	A <code>character(1)</code> which is the default filename for download.
<code>selection</code>	A <code>character(1)</code> which indicates the type of selection. Default is 'single'.

Value

NA
NA
NA
NA

Examples

```
if (interactive()) {  
  data(vdata)  
  formatDT(SummarizedExperiment::assay(vdata, 1))  
}
```

GetPkgVersion

Package version

Description

Gets the version number of a package

Usage

```
GetPkgVersion(pkg)
```

Arguments

pkg The name of the package

Value

A character(1) with the name of the package and its version number.

Examples

```
GetPkgVersion('omXplore')
```

<code>globals</code>	<i>Global variables</i>
----------------------	-------------------------

Description

Defines the global variables for the package `omXplore`

Usage

```
globals()
```

Value

A list

Examples

```
globals()
```

<code>intensity-plots</code>	<i>Displays different intensity plots.</i>
------------------------------	--

Description

Displays different intensity plots.

Usage

```
omXplore_intensity_ui(id)

omXplore_intensity_server(
  id,
  obj,
  i,
  track.indices = reactive({
    NULL
}),
  remoteReset = reactive({
    NULL
}),
  is.enabled = reactive({
    TRUE
})
)

omXplore_intensity(obj, i, withTracking = FALSE)

boxPlot(obj, conds, legend = NULL, pal = NULL, subset = NULL)

violinPlot(data, conds, subset = NULL, pal.name = "Set1")
```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>obj</code>	A instance of the class <code>MultiAssayExperiment</code>
<code>i</code>	An integer which is the index of the assay in the param obj
<code>track.indices</code>	A vector of integers which are the indices of lines to track.
<code>withTracking</code>	A boolean(1) indicating whether the tracking option is activated or not.
<code>conds</code>	A vector indicating the name of each sample.
<code>legend</code>	A vector of the conditions (one condition per sample).
<code>pal</code>	A basis palette for the boxes which length must be equal to the number of unique conditions in the dataset.
<code>subset</code>	A integer() vector of index indicating the indices of rows in the dataset to highlight
<code>data</code>	A data.frame() of quantitaive data
<code>pal.name</code>	A character(1) which is the name of the palette from the package RColorBrewer from which the colors are taken. Default value is 'Set1'.

Value

NA

NA

A shiny app

A boxplot

A violin plot

Author(s)

Samuel Wieczorek, Anais Courtier, Enora Fremy

Examples

```
data(vdata)
shiny::runApp(omXplore_intensity(vdata, 1))

data(sub_R25)
conds <- legend <- SummarizedExperiment::colData(sub_R25)$group
pal <- ExtendPalette(length(unique(conds)))
boxPlot(sub_R25[[1]], conds, legend, pal, seq_len(10))
```

<code>is.listOf</code>	<i>Checks the class of a list's slots</i>
------------------------	---

Description

Checks if all slots of the given list are of the same class.

Usage

```
is.listOf(object, obj.class = NULL)
```

Arguments

<code>object</code>	A list
<code>obj.class</code>	The name of the class to search in items of the list.

Value

A character(1) with the name of the package or NULL

Examples

```
ll <- as.list(LETTERS[1:3])
is.listOf(ll, "data.frame")
is.listOf(ll, "character")
```

<code>omXplore-modules</code>	<i>Shiny modules used by omXplore</i>
-------------------------------	---------------------------------------

Description

These functions are relative to external modules that can be added into omXplore UI:

- `listShinyApps()`: Show the shiny modules recognized by omXplore and ready to be integrated in the UI of the function `view_dataset()`
- `listPlotModules()`: Show the shiny modules function names (only prefixes) recognized by omXplore and ready to use in the UI.
- `addModules()`: Add external shiny module(s) to the R global environment in such a way (specific prefix renaming of the functions) that it can be discovered by the function `view_dataset()` of the package omXplore during its launch.

Usage

```
addModules(addons = list())
listShinyApps(location = "both")
listPlotModules(location = "both")
```

Arguments

addons	A list in which each item:
	<ul style="list-style-type: none"> • is named by the name of a package containing the modules to add, • contains the name of the shiny modules to integrate (without '_ui' nor '_server' suffixes)
location	A character(0) to indicate which modules to list. Available values are: 'builtin', 'external' and 'both' (default).

Value

NA
A vector
A vector

Examples

```
listShinyApps()
listPlotModules()

#####
# Integration of a module in the package 'mypackage'
#####

addons <- list(omXplore = c("extFoo1", "extFoo2"))
addModules(addons)
```

omXplore_heatmap *Displays a correlation matrix of the quantitative data of a numeric matrix.*

Description

This function is a wrapper to `heatmap.2()` that displays assay data in an instance of `SummarizedExperiment`. For more details, see `heatmap.2()`.

Usage

```
omXplore_heatmap_ui(id)

omXplore_heatmap_server(
  id,
  obj = reactive({
    NULL
  }),
  i = reactive({
    NULL
  })
)
```

```

omXplore_heatmap(obj, i)

heatmapD(
  qdata,
 conds,
  distance = "euclidean",
  cluster = "complete",
  dendro = FALSE
)

mv.heatmap(
  x,
  col = grDevices::heat.colors(100),
  srtCol = NULL,
  labCol = NULL,
  labRow = NULL,
  key = TRUE,
  key.title = NULL,
  main = NULL,
  ylab = NULL
)

heatmapForMissingValues(
  x,
  col = NULL,
  srtCol = NULL,
  labCol = NULL,
  labRow = NULL,
  key = TRUE,
  key.title = NULL,
  main = NULL,
  ylab = NULL
)

```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>obj</code>	An instance of a class MultiAssayExperiment.
<code>i</code>	An integer which is the index of the assay in the param obj
<code>qdata</code>	A data.frame() of quantitative data.
<code>conds</code>	A vector indicating the name of each sample.
<code>distance</code>	The distance used by the clustering algorithm to compute the dendrogram.
<code>cluster</code>	the clustering algorithm used to build the dendrogram.
<code>dendro</code>	A boolean to indicate if the dendrogram has to be displayed
<code>x</code>	A matrix or array containing the quantitative data.
<code>col</code>	Colors used for the image. Defaults to heat colors (heat.colors).
<code>srtCol</code>	Angle of column conds, in degrees from horizontal
<code>labCol</code>	Character vectors with column conds to use.

labRow	Character vectors with row cond to use.
key	Logical indicating whether a color-key should be shown.
key.title	Main title of the color key. If set to NA no title will be plotted.
main	Main title; default to none.
ylab	y-axis title; default to none.

Value

NA
NA
A shiny app
A heatmap
A heatmap
A heatmap

Author(s)

Florence Combes, Samuel Wieczorek, Enora Fremy

Examples

```
data(vdata)
omXplore_heatmap(vdata, 1)
```

omXplore_tabExplorer *Explore MultiAssayExperiment objects.*

Description

Explore MultiAssayExperiment objects.

Usage

```
omXplore_tabExplorer_ui(id)

omXplore_tabExplorer_server(
  id,
  obj = reactive({
    NULL
}),
  i = reactive({
    NULL
}),
  digits = reactive({
    3
})
)

omXplore_tabExplorer(obj, i)
```

Arguments

<code>id</code>	A <code>character(1)</code> which is the id of the shiny module.
<code>obj</code>	An instance of the class <code>MultiAssayExperiment</code>
<code>i</code>	An integer which is the index of the assay in the param obj
<code>digits</code>	An integer for the number of digits shown in the table

Value

<code>NA</code>
<code>NA</code>
<code>NA</code>
A shiny app

Examples

```
data(vdata)
shiny::runApp(omXplore_tabExplorer(vdata, 1))
```

<code>palette</code>	<i>Palette for samples.</i>
----------------------	-----------------------------

Description

Builds a vector of #conditions colors for a set of samples. One color is given for a given condition. This function extends a base palette from the package [RColorBrewer](#) to 'n' colors. The colors in the returned palette are always in the same order

Usage

```
SampleColors(conds, pal.name = "Set1")
ExtendPalette(n, pal.name = "Set1")
GetColorsForConditions(conds, pal = NULL)
```

Arguments

<code>conds</code>	A <code>character()</code> of conditions. The length of the vector is the number of samples in the dataset.
<code>pal.name</code>	A <code>character(1)</code> which is the name of the palette from the package RColorBrewer from which the colors are taken. Default value is 'Set1'.
<code>n</code>	The number of desired colors in the palette
<code>pal</code>	A vector of HEX color code that form the basis palette from which to build the complete color vector for the conditions.

Value

A vector

A vector

A vector

Examples

```
#-----
# Builds a palette for a dataset with 3 conditions
# of 3 samples each.
#-----

conds <- c(rep("A", 3), rep("B", 3), rep("C", 3))
SampleColors(conds)
SampleColors(conds, "Dark2")

#-----
# Extend the default palette to 12 colors
#-----

ExtendPalette(12)

data(vdata)
conds <- get_group(vdata)
GetColorsForConditions(conds, ExtendPalette(2))
```

pep_prot_CC

Display a CC

Description

Display a CC

Connected Components infos

Usage

```
buildGraph(cc = NULL, meta = NULL)

display.CC.visNet(g = NULL, layout = "layout_with_fr")

plotCCJitter(df, clickFunction = NULL)

GetCCInfos(cc)
```

Arguments

<code>cc</code>	A list of connected component
<code>meta</code>	A <code>data.frame()</code>
<code>g</code>	An instance of a graph
<code>layout</code>	A <code>character(1)</code> which is the layout used in <code>visNetwork</code> . Default value is ' <code>layout_with_fr</code> '
<code>df</code>	A <code>data.frame()</code>
<code>clickFunction</code>	A JS function to determine the behaviour of a click

Value

A list
 A plot
 A plot
 A list of three items:

- One_One: the number of cc composed of one protein and one peptide
- One_Multi: the number of cc composed of one protein and several peptides
- Multi_Multi: the number of cc composed of several proteins and several (shared) peptides.

Author(s)

Thomas Burger, Samuel Wieczorek

Examples

```
data(sub_R25)
se <- sub_R25[[1]]
g <- buildGraph(get_cc(se)[[1]])
display.CC.visNet(g)

data(sub_R25)
GetCCInfos(get_cc(sub_R25[[1]]))
```

`pkgs.require`

Loads packages

Description

Checks if a package is available to load it

Usage

```
pkgs.require(ll.deps)
```

Arguments

<code>ll.deps</code>	A <code>character()</code> vector which contains packages names
----------------------	---

Value

NA

Author(s)

Samuel Wieczorek

Examples

```
pkgs.require('omXplore')
```

plot-variance*Variance plot*

Description

A shiny module which plots the variance of samples

Usage

```
omXplore_variance_ui(id)  
  
omXplore_variance_server(id, obj, i, pal.name = NULL)  
  
CVDist(obj, cond, pal.name = NULL)  
  
omXplore_variance(obj, i)
```

Arguments

id	A character(1) which is the id of the shiny module.
obj	An matrix
i	An integer which is the index of the assay in the param obj
pal.name	A character(1) which is the name of the palette from the package RColorBrewer from which the colors are taken. Default value is 'Set1'.
cond	A vector indicating the name of each sample.

Value

NA

NA

A plot

A shiny app

Examples

```
if (interactive()) {  
  data(vdata)  
  omXplore_variance(vdata, 1)  
}
```

<code>plots_tracking</code>	<i>plots_tracking_ui</i> and <i>plots_tracking_server</i>
-----------------------------	---

Description

This shiny module provides a tool to select

Usage

```
plots_tracking_ui(id)

plots_tracking_server(
  id,
  obj = reactive({
    NULL
}),
  i = reactive({
    NULL
}),
  remoteReset = reactive({
    NULL
}),
  is.enabled = reactive({
    TRUE
})
)

plots_tracking(obj, i)
```

Arguments

<code>id</code>	shiny id
<code>obj</code>	An instance of the class <code>MultiAssayExperiment</code>
<code>remoteReset</code>	A <code>boolean(1)</code> which indicates whether to show the 'Reset' button or not.
<code>is.enabled</code>	xxx

Value

- NA
- A list (same structure as the parameter `params`)
- A shiny app

Examples

```
data(vdata)
shiny::runApp(plots_tracking(vdata, 1))
```

Prostar-1x-compatible *Convert datasets exported by the package Prostar*

Description

Convert datasets exported by the package Prostar

Usage

```
SE_Compatibility_with_Prostar_1.x(obj, se)
```

```
MAE_Compatibility_with_Prostar_1x(obj, mae)
```

Arguments

obj	An instance of the class MSnSet
se	An instance of the class SummarizedExperiment
mae	An instance of the class MultiAssayExperiment

Value

An enriched instance of the class SummarizedExperiment

An enriched instance of the class MultiAssayExperiment

Examples

```
data(sub_R25)
```

q_metadata

Quantitative metadata vocabulary for entities

Description

This function gives the vocabulary used for the quantitative metadata of each entity in each condition.

Usage

```
metacell.def(level)
```

```
Parent(level, node = NULL)
```

```
Children(level, parent = NULL)
```

```
GetMetacellTags(metacells = NULL, level = NULL, onlyPresent = FALSE)
```

Arguments

level	A string corresponding to the type of object
node	The name of the node for which one wants its parent #` @examples Parent('protein', 'Missing') Parent('protein', 'Missing POV') Parent('protein', c('Missing POV', 'Missing MEC')) Parent('protein', c('Missing', 'Missing POV', 'Missing MEC'))
parent	The name og the parent node
metacells	A data.frame() representing the cell metadata
onlyPresent	A boolean(1)

Value

A data.frame containing the different tags and corresponding colors for the level given in parameter
A list
A vector
A vector
A vector

Glossary

Peptide-level vocabulary

|— 'Any' |—— 1.0 'Quantified' |—— 1.1 "Quant. by direct id" (color 4, white) |—— 1.2 "Quant. by recovery" (color 3, lightgrey) |—— 2.0 "Missing" (no color) |—— 2.1 "Missing POV" (color 1) |—— 2.2 'Missing MEC' (color 2) |—— 3.0 'Imputed' |—— 3.1 'Imputed POV' (color 1) |—— 3.2 'Imputed MEC' (color 2)

Protein-level vocabulary: |— 'Any' |—— 1.0 'Quantified' |—— 1.1 "Quant. by direct id" (color 4, white) |—— 1.2 "Quant. by recovery" (color 3, lightgrey) |—— 2.0 "Missing" |—— 2.1 "Missing POV" (color 1) |—— 2.2 'Missing MEC' (color 2) |—— 3.0 'Imputed' |—— 3.1 'Imputed POV' (color 1) |—— 3.2 'Imputed MEC' (color 2) |—— 4.0 'Combined tags' (color 3bis, lightgrey)

Conversion to the glossary

- A generic conversion
- Conversion for Proline datasets
- Conversion from Maxquant datasets

Author(s)

Thomas Burger, Samuel Wieczorek
Samuel Wieczorek

Examples

```
metacell.def("protein")
metacell.def("peptide")

#-----
# A shiny app to view color legends
```

```
#-----
# if(interactive()) {
#   data(vdata)
#   ui <- qMetacellLegend_ui("legend")
#
#   server <- function(input, output, session) {
#     qMetacellLegend_server("legend",
#       object = reactive({vdata[[1]]}))
#   }
# }
#
# shinyApp(ui = ui, server = server)
#
# Children("protein", "Missing")
# Children("protein", "Missing POV")
# Children("protein", c("Missing POV", "Missing MEC"))
# Children("protein", c("Missing", "Missing POV", "Missing MEC"))
# data(vdata)
# metacells <- get_metacell(vdata[[1]])
# level <- get_type(vdata[[1]])
# GetMetacellTags(metacells, level)
```

sub_R25*Feature example data*

Description

sub_R25 is a protein subset of the dataset 'Exp1_R25_pept' in the package DAPARdata.

Format

An instance of the class MultiAssayExperiment

Value

An enriched instance of the class MultiAssayExperiment

Source

sub_R25 was built from the source code available in [inst/scripts/build_datasets.R](#)

The DAPARdata package: <https://github.com/prostarproteomics/DAPARdata>

vdata	<i>Feature example data</i>
-------	-----------------------------

Description

vdata is a small object for testing and demonstration.

Format

An instance of the class MultiAssayExperiment

Value

An enriched instance of the class MultiAssayExperiment

Source

vdata was built from the source code available in [inst/scripts/build_datasets.R](#)

Index

- * datasets
 - vdata, 34
- * data
 - vdata, 34
- * internal
 - ds-cc, 11
 - plots_tracking, 30
- accessors, 3
- addModules (omXplore-modules), 22
- boxPlot (intensity-plots), 20
- Build_enriched_qdata, 5
- Build_X_CC (converters), 6
- BuildColorStyles, 4
- buildGraph (pep_prot_CC), 27
- Check_List_consistency (converters), 6
- Check_MSnSet_Consistency (converters), 6
- Check_se_Consistency (converters), 6
- Children (q_metadata), 31
- color-legend, 5
- colorLegend (color-legend), 5
- colorLegend_server (color-legend), 5
- colorLegend_ui (color-legend), 5
- Compute_CC (converters), 6
- convert_to_mae (converters), 6
- converters, 6
- corrMatrix (corrmatrix), 8
- corrmatrix, 8
- custom_metacell_colors (color-legend), 5
- customChart, 9
- customExportMenu, 10
- CVDist (plot-variance), 29
- density-plot, 10
- densityPlot (density-plot), 10
- df_to_mae (converters), 6
- df_to_se (converters), 6
- display.CC.visNet (pep_prot_CC), 27
- ds-cc, 11
- ds-pca, 12
- ds-view, 14
- ExtendPalette (palette), 26
- external_app, 16
- extFoo1 (external_app), 16
- extFoo1_server (external_app), 16
- extFoo1_ui (external_app), 16
- extFoo2 (external_app), 16
- extFoo2_server (external_app), 16
- extFoo2_ui (external_app), 16
- format_DT, 18
- FormatDataForDT, 17
- formatDT (format_DT), 18
- formatDT_server (format_DT), 18
- formatDT_ui (format_DT), 18
- get_adjacencyMatrix (accessors), 3
- get_adjacencyMatrix, SummarizedExperiment-method (accessors), 3
- get_cc (accessors), 3
- get_cc, SummarizedExperiment-method (accessors), 3
- get_colID (accessors), 3
- get_colID, SummarizedExperiment-method (accessors), 3
- get_group (accessors), 3
- get_group, MultiAssayExperiment-method (accessors), 3
- get_metacell (accessors), 3
- get_metacell, SummarizedExperiment-method (accessors), 3
- get_parentProtId (accessors), 3
- get_parentProtId, SummarizedExperiment-method (accessors), 3
- get_pkg_version (accessors), 3
- get_pkg_version, SummarizedExperiment-method (accessors), 3
- get_type (accessors), 3
- get_type, SummarizedExperiment-method (accessors), 3
- GetCCInfos (pep_prot_CC), 27
- GetColorsForConditions (palette), 26
- GetMetacellTags (q_metadata), 31
- GetPkgVersion, 19
- globals, 20

heatmapD (omXplore_heatmap), 23
 heatmapD(), 15
 heatmapForMissingValues
 (omXplore_heatmap), 23

 intensity-plots, 20
 is.listOf, 22

 list_to_se (converters), 6
 listOfdf_to_mae (converters), 6
 listOfLists_to_mae (converters), 6
 listOfmatrix_to_mae (converters), 6
 listOfMSnSet_to_mae (converters), 6
 listOfSE_to_mae (converters), 6
 listPlotModules (omXplore-modules), 22
 listShinyApps (omXplore-modules), 22

 MAE_Compatibility_with_Prostar_1x
 (Prostar-1x-compatible), 31
 MAE_to_mae (converters), 6
 matrix_to_mae (converters), 6
 matrix_to_se (converters), 6
 metacell.def (q_metadata), 31
 MSnSet_to_mae (converters), 6
 MSnSet_to_se (converters), 6
 mv.heatmap (omXplore_heatmap), 23

 omXplore-modules, 22
 omXplore_cc (ds-cc), 11
 omXplore_cc_server (ds-cc), 11
 omXplore_cc_ui (ds-cc), 11
 omXplore_corrmatrix (corrmatrix), 8
 omXplore_corrmatrix_server
 (corrmatrix), 8
 omXplore_corrmatrix_ui (corrmatrix), 8
 omXplore_density (density-plot), 10
 omXplore_density_server (density-plot),
 10
 omXplore_density_ui (density-plot), 10
 omXplore_heatmap, 23
 omXplore_heatmap_server
 (omXplore_heatmap), 23
 omXplore_heatmap_ui (omXplore_heatmap),
 23
 omXplore_intensity (intensity-plots), 20
 omXplore_intensity_server
 (intensity-plots), 20
 omXplore_intensity_ui
 (intensity-plots), 20
 omXplore_pca (ds-pca), 12
 omXplore_pca_server (ds-pca), 12
 omXplore_pca_ui (ds-pca), 12
 omXplore_tabExplorer, 25

 omXplore_tabExplorer_server
 (omXplore_tabExplorer), 25
 omXplore_tabExplorer_ui
 (omXplore_tabExplorer), 25
 omXplore_variance (plot-variance), 29
 omXplore_variance_server
 (plot-variance), 29
 omXplore_variance_ui (plot-variance), 29

 palette, 26
 Parent (q_metadata), 31
 pep_prot_CC, 27
 pkgs.require, 28
 plot-variance, 29
 plotCCJitter (pep_prot_CC), 27
 plotPCA_Eigen (ds-pca), 12
 plotPCA_Eigen_hc (ds-pca), 12
 plotPCA_Ind (ds-pca), 12
 plotPCA_Var (ds-pca), 12
 plots_tracking, 30
 plots_tracking_server (plots_tracking),
 30
 plots_tracking_ui (plots_tracking), 30
 Prostar-1x-compatible, 31

 q_metadata, 31
 QFeatures_to_mae (converters), 6

 RColorBrewer, 11, 21, 26, 29

 SampleColors (palette), 26
 SE_Compatibility_with_Prostar_1.x
 (Prostar-1x-compatible), 31
 SE_to_mae (converters), 6
 sub_R25, 33

 vdata, 34
 view_dataset (ds-view), 14
 view_dataset_server (ds-view), 14
 view_dataset_ui (ds-view), 14
 violinPlot (intensity-plots), 20

 wrapper_pca (ds-pca), 12